BOOSTING THE CERTIFIED ROBUSTNESS OF L-INFINITY DISTANCE NETS

ABSTRACT

Recently, Zhang et al. (2021) developed a new neural network architecture based on ℓ_∞-distance functions, which naturally possesses certified robustness by its construction. Despite the excellent theoretical properties, the model so far can only achieve comparable performance to conventional networks. In this paper, we significantly boost the certified robustness of ℓ_∞-distance nets through a careful analysis of its training process. In particular, we show the ℓ_p-relaxation, a crucial way to overcome the non-smoothness of the model, leads to an unexpected large Lipschitz constant at the early training stage. This makes the optimization insufficient using hinge loss and produces sub-optimal solutions. Given these findings, we propose a simple approach to address the issues above by using a novel objective function which combines a scaled cross-entropy loss with clipped hinge loss. Our experiments show that using the proposed training strategy, the certified accuracy of ℓ_∞-distance net can be dramatically improved from 33.30% to 40.06% on CIFAR-10 ($\epsilon = 8/255$), meanwhile significantly outperforming other approaches in this area. Such result clearly demonstrates the effectiveness and potential of ℓ_∞-distance net for certified robustness.

1 INTRODUCTION

Modern neural networks, while achieving high accuracy on various tasks, are found to be vulnerable to small, adversarially-chosen perturbations of the inputs (Szegedy et al., 2013; Biggio et al., 2013). Given an image x correctly classified by a neural network, there often exists a small adversarial perturbation δ, such that the perturbed image $x + \delta$ looks indistinguishable to x, but fools the network to predict an incorrect class with high confidence. Such vulnerability creates security concerns in many real-world applications.

A large body of works has been developed to obtain robust classifiers. One line of works proposed heuristic approaches that are empirically robust to particular attack methods, among which adversarial training is the most successful approach (Goodfellow et al., 2014; Madry et al., 2017; Zhang et al., 2019a). However, a variety of these heuristics have been subsequently broken by stronger and adaptive attacks (Carlini & Wagner, 2017; Athalye et al., 2018; Uesato et al., 2018; Tramer et al., 2020; Croce & Hein, 2020), and there are no formal guarantees whether the resulting model is truly robust. This motivates another line of works that seeks certifiably robust classifiers whose prediction is guaranteed to remain the same under all allowed perturbations. Representatives of this field use convex relaxation (Wong & Kolter, 2018; Mirman et al., 2018; Gowal et al., 2018; Zhang et al., 2020) or randomized smoothing (Cohen et al., 2019; Salman et al., 2019a; Zhai et al., 2020; Yang et al., 2020b). However, almost all these approaches suffer from high computational cost, yet still cannot achieve satisfactory results for commonly used ℓ_∞-norm perturbation scenario.

Recently, Zhang et al. (2021) proposed a fundamentally different approach by designing a new network architecture called ℓ_∞-distance net, a name coming from its construction that the basic neuron is defined as the ℓ_∞-distance function. Using the fact that any ℓ_∞-distance net is inherently a 1-Lipschitz mapping, one can easily obtain the certified robust accuracy of any data point according to the output margin. The whole procedure only requires a forward pass without any additional computation. The authors further showed that the model family has strong expressive power, e.g., a large enough ℓ_∞-distance net can approximate any 1-Lipschitz function on a bounded domain. However, the empirical model performance did not reflect the theoretical advantages. As shown in

Zhang et al. (2021), it is necessary to use a conventional multi-layer perception (MLP)[1] on top of an ℓ_∞-distance net backbone to achieve better performance compared to the baseline methods. It calls into question whether the ℓ_∞-distance net is really a better model configuration than conventional architectures in the regime of certified robustness.

In this paper, we give an affirmative answer by showing that ℓ_∞-distance net alone suffices for good performance and can be well learned using an improved training strategy. We first mathematically prove that under mild assumptions of the dataset, there exists an ℓ_∞-distance net with reasonable size *by construction* that achieves perfect certified robustness. This result explicitly indicates strong expressive power of ℓ_∞-distance nets in practice, which seems to contradict the previous empirical observations. It also suggests that the model may fail to find an optimal solution and further motivates us to revisit the optimization process designed in Zhang et al. (2021). Due to the non-smoothness of the ℓ_∞-distance function, Zhang et al. (2021) developed several training tricks to overcome the optimization difficulty. A notable trick is called the ℓ_p-relaxation, in which ℓ_p-distance neurons are used during optimization to give a smooth approximation of ℓ_∞-distance. However, we find that the relaxation on neurons unexpectedly relaxes the Lipschitz constant of the network to an exponentially large value, making the objective function no longer maximize the robust accuracy and lead to sub-optimal solutions.

We develop a novel modification of the objective function to bypass the problem mentioned above. To be concrete, we propose a new loss function, which is a linear combination of a scaled cross-entropy term and a modified clipped hinge term. The cross-entropy loss maximizes the output margin despite the model's Lipschitzness and makes optimization sufficient at the early training stage when p is small. The clipped hinge loss then focuses on robustness for correctly classified samples at the later training phase when p approaches infinity. The switch from cross-entropy loss to clipped hinge loss is reflected in the weight coefficient in the loss combination, which decays to zero as p grows to infinity throughout the training procedure. Despite its simplicity, our experimental results show significant performance gains on various datasets. In particular, an ℓ_∞-distance net backbone can achieve **40.06%** certified robust accuracy on CIFAR-10 ($\epsilon = 8/255$). This goes far beyond the previous results, which achieved 33.30% certified accuracy on CIFAR-10 using the same architecture (Zhang et al., 2021). Besides, it surpasses the relaxation-based certification approaches by at least 5 points (Shi et al., 2021; Lyu et al., 2021), establishing a new state-of-the-art result.

To summarize, both the theoretical finding and empirical results in this paper demonstrate the merit of ℓ_∞-distance net for certified robustness. Considering the simplicity of the architecture and training strategy used in this paper, we believe there are still many potentials for future research of ℓ_∞-distance nets, and more generally, the class of Lipschitz architectures.

2 PRELIMINARY

In this section, we briefly introduce the ℓ_∞-distance net and its training strategy. We refer readers to Zhang et al. (2021) for a detailed description of the model.

An ℓ_∞-distance net is constructed using ℓ_∞-distance neurons as the basic component. The ℓ_∞-distance neuron u takes vector $\boldsymbol{x}$ as the input and calculates the ℓ_∞-norm distance between $\boldsymbol{x}$ and parameter $\boldsymbol{w}$ with a bias term b. The neuron can be written as

$$u(\boldsymbol{x}, \{\boldsymbol{w}, b\}) = \|\boldsymbol{x} - \boldsymbol{w}\|_\infty + b. \tag{1}$$

Based on the neuron definition, a fully connected ℓ_∞-distance net can then be constructed. Formally, the network $\boldsymbol{g}$ takes $\boldsymbol{x}^{(0)} = \boldsymbol{x}$ as the input, and the lth layer $\boldsymbol{x}^{(l)}$ is calculated by

$$x_i^{(l)} = u(\boldsymbol{x}^{(l-1)}, \{\boldsymbol{w}^{(l,i)}, b_i^{(l)}\}) = \|\boldsymbol{x}^{(l-1)} - \boldsymbol{w}^{(l,i)}\|_\infty + b_i^{(l)}, \quad l \in [L], i \in [n_l]. \tag{2}$$

Here L is the number of layers and n_l is the number of neurons in the lth layer. For K-class classification problems, $n_L = K$. The network outputs $\boldsymbol{g}(\boldsymbol{x}) = \boldsymbol{x}^{(L)}$ as logits and predicts the class $\arg\max_{i \in [K]} [\boldsymbol{g}(\boldsymbol{x})]_i$.

An important property of ℓ_∞-distance net is its Lipschitz continuity, as is stated below.

---

[1]Without any confusion, in this paper, a *conventional* neural network model is referred to as a network composed of linear transformations with non-linear activations.

Definition 2.1. A mapping $\boldsymbol{f}(\boldsymbol{z}) : \mathbb{R}^m \to \mathbb{R}^n$ is called λ-Lipschitz with respect to ℓ_p-norm $\|\cdot\|_p$, if for any $\boldsymbol{z}_1, \boldsymbol{z}_2$, the following holds:

$$\|\boldsymbol{f}(\boldsymbol{z}_1) - \boldsymbol{f}(\boldsymbol{z}_2)\|_p \le \lambda \|\boldsymbol{z}_1 - \boldsymbol{z}_2\|_p.$$

Proposition 2.2. *The mapping of an ℓ_∞-distance layer is 1-Lipschitz with respect to ℓ_∞-norm. Thus by composition, any ℓ_∞-distance net $\boldsymbol{g}(\cdot)$ is 1-Lipschitz with respect to ℓ_∞-norm.*

ℓ_∞-distance nets naturally possess certified robustness using the Lipschitz property. In detail, for any data point $\boldsymbol{x}$ with label y, denote the output margin of network $\boldsymbol{g}$ as

$$\mathsf{margin}(\boldsymbol{x}, y; \boldsymbol{g}) = [\boldsymbol{g}(\boldsymbol{x})]_y - \max_{j \ne y}[\boldsymbol{g}(\boldsymbol{x})]_j. \tag{3}$$

If $\boldsymbol{x}$ is correctly classified by $\boldsymbol{g}$, then the prediction of a perturbed input $\boldsymbol{x} + \boldsymbol{\delta}$ will remain the same as $\boldsymbol{x}$ if $\|\boldsymbol{\delta}\|_\infty < \mathsf{margin}(\boldsymbol{x}, y; \boldsymbol{g})/2$. In other words, we can obtain the certified robust accuracy for a given perturbation level ϵ according to $\mathbb{I}(\mathsf{margin}(\boldsymbol{x}, y; \boldsymbol{g})/2 > \epsilon)$, where $\mathbb{I}(\cdot)$ is the indicator function. We call this *margin-based certification*. Given this certification approach, a corresponding training approach can then be developed, where one simply learns a large margin classifier using standard loss functions, e.g., hinge loss, without using adversarial training. Therefore the whole training procedure is as efficient as training standard networks with *no* additional cost.

Zhang et al. (2021) further show that ℓ_∞-distance nets are Lipschitz-universal approximators. In detail, a large enough ℓ_∞-distance net can approximate any 1-Lipschitz function with respect to ℓ_∞-norm on a bounded domain arbitrarily well.

Training ℓ_∞-distance net. One major challenge in training ℓ_∞-distance net is that the gradients of the ℓ_∞-distance operation ($\nabla_{\boldsymbol{x}}\|\boldsymbol{x} - \boldsymbol{w}\|_\infty$ and $\nabla_{\boldsymbol{w}}\|\boldsymbol{x} - \boldsymbol{w}\|_\infty$) are highly sparse. To mitigate the problem, Zhang et al. (2021) used ℓ_p-distance neurons instead of ℓ_∞-distance ones during training, resulting in approximate and non-sparse gradients. Typically p is set to a small value (e.g., 8) in the beginning and increases throughout training until it reaches a large number (e.g., 1000). The authors also designed several other tricks to further address the optimization difficulty. However, even with the help of tricks, ℓ_∞-distance nets only perform competitively to previous works. The authors thus considered using a hybrid model architecture, in which the ℓ_∞-distance net serves as a robust feature extractor, and an additional conventional multi-layer perceptron is used as the prediction head. This architecture achieves the best performance, while the certification approach becomes complicated again due to the presence of the non-Lipschitz MLP layers.

3 THE ROBUST EXPRESSIVE POWER OF ℓ_∞-DISTANCE NETS

Zhang et al. (2021) provides a universal approximation theorem and shows that ℓ_∞-distance nets can serve as a good class of models to represent Lipschitz functions. However, this result focuses on real-valued function approximation and is not directly helpful for certified robustness in classification. Practically, we care more about whether a certifiably robust classifier exists *given a dataset* with *an acceptable number of parameters* for training. In this section, we show one can explicitly construct an ℓ_∞-distance net that achieves perfect certified robustness on a dataset if the dataset satisfies the following (weak) condition called r-separation (Yang et al., 2020b).

Definition 3.1. Consider a labeled dataset $\mathcal{D} = \{(\boldsymbol{x}_i, y_i)\}$ where $y_i \in [K]$ is the label of $\boldsymbol{x}_i$. We say $\mathcal{D}$ is r-separated with respect to ℓ_p-norm if for any pair of samples $(\boldsymbol{x}_i, y_i), (\boldsymbol{x}_j, y_j)$, as long as $y_i \ne y_j$, we have $\|\boldsymbol{x}_i - \boldsymbol{x}_j\|_p \ge 2r$.

It is easy to see that r-separation is a necessary condition for robustness under ℓ_p-norm perturbation $\epsilon = r$. In fact, the condition holds for all commonly used datasets (e.g., MNIST, CIFAR-10): the value of r in each dataset is much greater than the allowed perturbation level ϵ as is demonstrated in Yang et al. (2020b) (see Table 1 below). The authors took a further step and showed that there always exists a classifier that achieves perfect robust accuracy if the conditional holds. We now prove that even if we restrict the classifier to be the network function class represented by ℓ_∞-distance nets (containing only 1-Lipschitz functions), the conclusion is still correct: a simple two-layer ℓ_∞-distance net with hidden size $O(n)$ can already achieve perfect robustness for r-separated datasets.

Theorem 3.2. *Let $\mathcal{D}$ be a dataset with n elements satisfying the r-separation condition with respect to ℓ_∞-norm. Then there exists a two-layer ℓ_∞-distance net with hidden size n, such that the certified ℓ_∞ robust accuracy is 100% on $\mathcal{D}$ under perturbation $\epsilon = r$.*

Table 1: The r-separation property of commonly used datasets, taken from Yang et al. (2020b).

Dataset	r	commonly used ϵ
MNIST	0.737	0.3
CIFAR-10	0.212	8/255

Proof sketch. Consider a two layer ℓ_∞-distance net $\boldsymbol{g}$ defined in Equation (2). Let its parameters be assigned by

$$\boldsymbol{w}^{(1,i)} = \boldsymbol{x}_i, b_i^{(1)} = 0 \qquad \text{for } i \in [n]$$
$$w_i^{(2,j)} = C \cdot \mathbb{I}(y_i = j), b_j^{(2)} = -C \qquad \text{for } i \in [n], j \in [K]$$

where $C = 4 \max_{i \in [n]} \|\boldsymbol{x}_i\|_\infty$ is a constant, and $\mathbb{I}(\cdot)$ is the indicator function. For the above assignment, the first layer simply calculates the ℓ_∞-distance between $\boldsymbol{x}$ and each sample in dataset $\mathcal{D}$, and it can be proved that the second layer (network output) calculates

$$[\boldsymbol{g}(\boldsymbol{x})]_j = x_j^{(2)} = - \min_{i \in [n], y_i = j} \|\boldsymbol{x} - \boldsymbol{x}_i\|_\infty. \tag{4}$$

From Equation (4) the network $\boldsymbol{g}$ can represent a nearest neighbor classifier, in that it outputs the negative of the nearest neighbor distance between input $\boldsymbol{x}$ and the samples of each class. Therefore, given data $\boldsymbol{x} = \boldsymbol{x}_i$ in dataset $\mathcal{D}$, the output margin of $\boldsymbol{g}(\boldsymbol{x})$ is at least $2r$ due to the r-separation condition. In other words, $\boldsymbol{g}$ achieves 100% certified robust accuracy on $\mathcal{D}$. $\square$

The above result can be extended to multi-layer networks. In general, we can prove the existence of such networks with L layers and no more than $O(n/L + K + d)$ hidden neurons for each hidden layer where d is the input dimension. See Appendix A for details of the proof.

Remark 3.3. Theorem 3.2 clearly shows that the ℓ_∞-distance net has the capability to achieve perfect certified robustness on well-conditioned datasets. While it does not necessarily mean the model can achieve high certified robustness on test data, it does show strong *robust expressive power* of ℓ_∞-distance nets. We further make a comparison between Theorem 3.2 and the Lipschitz-universal approximation theorem in Zhang et al. (2021). First, our results focus on the ability of ℓ_∞-distance nets on the robust certification in classification problems while Zhang et al. (2021) focuses on universal function approximation. More importantly, the required network size in Theorem 3.2 is only $O(n)$ which is close to practical applications. It is much smaller than the size needed for function approximation (e.g. $O(1/\varepsilon^d)$ under approximation error ε), which scales exponentially in the input dimension d.

4 INVESTIGATING THE TRAINING OF ℓ_∞-DISTANCE NETS

Since robust ℓ_∞-distance nets exist in principle, the remaining thing is understanding why the current training strategy cannot find a robust solution. In this section, we first provide evidence that the training method in Zhang et al. (2021) is indeed problematic and cannot achieve good certified robustness, then provide a novel way to address the issue.

4.1 PROBLEMS OF THE CURRENT TRAINING STRATEGY

As shown in Section 2, given any perturbation level ϵ, the certified accuracy of data point $\boldsymbol{x}$ can be calculated according to $\mathbb{I}(\mathsf{margin}(\boldsymbol{x}, y; \boldsymbol{g})/2 \leq \epsilon)$ for 1-Lipschitz functions. Then the hinge loss becomes standard to learn a robust ℓ_∞-distance net:

$$\mathcal{L}_{\mathrm{hinge}}(\boldsymbol{g}, \mathcal{D}; \theta) = \mathbb{E}_{(\boldsymbol{x}_i, y_i) \in \mathcal{D}} \left[\max \left\{ \theta - \mathsf{margin}(\boldsymbol{x}_i, y_i; \boldsymbol{g}), 0 \right\} \right], \tag{5}$$

where θ is the hinge threshold which should be larger than 2ϵ. Hinge loss aims at making the output margin for any sample greater than θ, and $\mathcal{L}_{\mathrm{hinge}}(\boldsymbol{g}, \mathcal{D}; \theta) = 0$ if and only if the network $\boldsymbol{g}$ achieves perfect certified robustness under perturbation $\epsilon = \theta/2$.

Hinge loss fails to learn robust classifiers. We first start with some empirical observations. Consider a plain ℓ_∞-distance net trained on CIFAR-10 dataset using the same approach and the same hyper-parameters provided in Zhang et al. (2021). When the training finishes, we count the percentage of training samples whose margin is greater than θ, i.e., achieving zero loss. We expect the value to be large if the optimization is successful. However, the result surprisingly reveals that only 1.62% of the training samples are classified correctly with a margin greater than θ. Even if we use much longer training epochs (e.g. 4000 epochs on CIFAR-10), the percentage is still below 2.5%

(a)   (b)

Figure 1: Experiments of ℓ_∞-distance net training on CIFAR-10 dataset using the hinge loss function. Training details can be found in Section 5.1. (a) The percentage of training samples with output margin greater than θ throughout training. We use very long training epochs, and the final percentage is still below 2.5%. The dashed lines indicate different p values of ℓ_p-distance neurons. (b) The certified accuracy on training dataset and test dataset respectively, trained using different hinge threshold θ. Training gets worse when $\theta \leq 6\epsilon$.

(see Figure 1(a)). Thus we conclude that hinge loss fails to optimize well for most of the training samples.

Since the output margins of the vast majority of training samples are less than θ, the loss approximately degenerates to a linear function without the maximum operation:

$$\begin{aligned}
\mathcal{L}_{\text{hinge}}(\boldsymbol{g}, \mathcal{D}; \theta) \approx \widetilde{\mathcal{L}}_{\text{hinge}}(\boldsymbol{g}, \mathcal{D}; \theta) &= \mathbb{E}_{(\boldsymbol{x}_i, y_i) \in \mathcal{D}} \left[\theta - \text{margin}(\boldsymbol{x}_i, y_i; \boldsymbol{g}) \right] \\
&= \theta - \mathbb{E}_{(\boldsymbol{x}_i, y_i) \in \mathcal{D}} \left[\text{margin}(\boldsymbol{x}_i, y_i; \boldsymbol{g}) \right],
\end{aligned} \tag{6}$$

where θ becomes irrelevant, and training becomes to optimize *the average margin over the dataset* regardless of the allowed perturbation ϵ which is definitely problematic.

After checking the hyper-parameters used in Zhang et al. (2021), we find that the hinge threshold θ is set to 80/255, which is *much larger* than the perturbation level $\epsilon = 8/255$. This partly explains the above degeneration phenomenon, but it is still unclear why such a large value has to be taken. We then conduct experiments to see the performance with different chosen hinge thresholds θ. The results are illustrated in Figure 1(b). As we can see, a smaller hinge threshold not only reduces certified test accuracy but even makes *training* worse.

Why does this happen? We find that the reason for the loss degeneration stems from the ℓ_p-relaxation used in training. While ℓ_p-relaxation alleviates the sparse gradient problem, it destroys the Lipschitz property of the ℓ_∞-distance neuron, as stated in Proposition 4.1:

Proposition 4.1. *A layer constructed using ℓ_p-distance neurons*

$$u_p(\boldsymbol{x}, \{\boldsymbol{w}, b\}) = \|\boldsymbol{x} - \boldsymbol{w}\|_p + b$$

is $d^{1/p}$ Lipschitz with respect to ℓ_∞-norm, where d is the dimension of $\boldsymbol{x}$. Thus by composition, an L layer ℓ_p-distance net is $d^{L/p}$ Lipschitz with respect to ℓ_∞-norm.

Zhang et al. (2021) uses a small p in the beginning and increases its value gradually during training. From Proposition 4.1, the Lipschitz constant of the smoothed network can be significantly large[2] at the early training stage. Note that the robust certification $\mathbb{I}(\text{margin}(\boldsymbol{x}, y; \boldsymbol{g})/2 \leq \epsilon)$ holds for 1-Lipschitz functions. When the Lipschitz constant is large, even if the margin of a data point passes the threshold, the data point can still lie near to classification boundary. This makes the training at the early stage ineffective and converge to a wrong solution far from the real optima. We argue that the early-stage training is important as when p rises to a large value, the optimization becomes intrinsically difficult to push the parameters back to the correct solution due to sparse gradients.

---

[2]For a 6-layer ℓ_p-distance net ($p = 8$) with hidden size 5120 used in Zhang et al. (2021), Proposition 4.1 approximately gives a Lipschitz constant of 600. We also run experiments to validate such upper bound is relatively tight. See Appendix for more details.

Such argument can be verified from Figure 1(a), in which we plot the percentage of training samples with margins greater than θ throughout a long training process. After p starts to rise, the margin decreases drastically, and the percentage sharply drops and never increases again during the whole ℓ_p-relaxation procedure. It is also clear why the value of θ must be chosen to be much larger than 2ϵ. For small θ, the margin optimization becomes insufficient at early training stages when the Lipschitz constant is exponentially large, leading to worse performance even on the training dataset.

4.2 OUR SOLUTION

In the previous section, we can see that the hinge loss and the ℓ_p-relaxation are incompatible. As the ℓ_p-relaxation is essential to overcome the sparse gradient problem, we focus on developing better loss functions. We show in this section that a simple change of the objective function can address the above problem, leading to non-trivial improvements.

We approach the issue by investigating the commonly used cross-entropy loss. For conventional non-Lipschitz networks, cross-entropy loss aims at increasing the logit of the true class while decreasing the other logits as much as possible, therefore enlarges the output margin without a threshold constraint. This is particularly helpful for training ℓ_p-distance nets with small p when the Lipschitz constant is large. However, cross-entropy loss only coarsely enlarges the margin, rather than exactly optimizing the surrogate of certified accuracy $\mathbb{I}(\mathrm{margin}(\boldsymbol{x}, y; \boldsymbol{g})/2 \leq \epsilon)$ when the model is almost 1-Lipschitz. Therefore we seek to combine cross-entropy loss and hinge loss and obtain the following objective function:

$$\mathcal{L}(\boldsymbol{g}, \mathcal{D}; \theta) = \mathbb{E}_{(\boldsymbol{x}_i, y_i) \in \mathcal{D}} [\underbrace{\lambda \ell_{\mathrm{CE}}(s \cdot \boldsymbol{g}(\boldsymbol{x}_i), y_i)}_{\text{for classification}} + \underbrace{\min\{\ell_{\mathrm{hinge}}(\boldsymbol{g}(\boldsymbol{x}_i)/2\theta, y_i), 1\}}_{\text{for robustness}}] \tag{7}$$

where $\ell_{\mathrm{CE}}(\boldsymbol{z}, y) = \log(\sum_i \exp(z_i)) - z_y$ and $\ell_{\mathrm{hinge}}(\boldsymbol{z}, y) = \max\{\max_{i \neq y} z_i - z_y + 1, 0\}$. We now make further explanations about each term in Equation (7).

Scaled cross-entropy loss $\ell_{\mathrm{CE}}(s \cdot \boldsymbol{g}(\boldsymbol{x}_i), y_i)$. The cross-entropy loss is invariant to the shift operation (adding a constant to each output logit) but not scaling. For conventional networks, the output logits are produced through the last linear layer, and the scaling factor can be implicitly learned in the parameters of the linear layer during optimization. However, ℓ_∞-distance net is strictly 1-Lipschitz and does not have any scaling operation. We thus introduce a learnable scalar (temperature) s that multiplies the network output $\boldsymbol{g}(\boldsymbol{x}_i)$ before taking cross-entropy loss. We simply initialize it to be 1.

Clipped hinge loss $\min\{\ell_{\mathrm{hinge}}(\boldsymbol{g}(\boldsymbol{x}_i)/2\theta, y_i), 1\}$. Unlike the standard hinge loss, the clipped version plateaus if the output margin is negative (i.e., misclassified). The reason for applying such a loss function is two-fold. (i) Since we have already used cross-entropy loss for classification, hinge loss does not need to focus on wrongly classified samples. In fact, the gradient of hinge loss w.r.t. output logit is discontinuous, sparse (only two non-zero elements), and does not make full use of the information provided by the logit, making the model harder to optimize comparing to cross-entropy loss. (ii) the clipped hinge loss is a better surrogate for 0-1 robust error $\mathbb{I}(\mathrm{margin}(\boldsymbol{x}, y; \boldsymbol{g})/2 \leq \epsilon)$. It is closer to our goal and thus more likely to achieve better certified accuracy. Finally, due to the presence of cross-entropy loss, we will show in Section 5 that the hinge threshold θ can be set to a much smaller value unlike Figure 1(b), which thus avoids optimizing the average margin.

The weight coefficient λ. The coefficient λ in loss (7) plays a role in the trade-off between cross-entropy and hinge loss. It is worth noting that here λ decays from λ_0 to zero throughout the process of ℓ_p-relaxation (λ_0 is a hyper-parameter). When p is small at the early training stage, we focus more on cross-entropy loss since hinge loss is problematic due to the large Lipschitz constant. After p grows large, λ vanishes, and a surrogate of 0-1 robust error is optimized.

We point out that objective functions similar to (7) also appeared in previous literature. In particular, the TRADES loss (Zhang et al., 2019a) and MMA loss (Ding et al., 2019) are both composed of a mixture of the cross-entropy loss and a form of robust loss. Nevertheless, our approach differs from theirs in at least two aspects. Firstly, the motivation is entirely different. For example, TRADES was proposed based on the theoretical results suggesting robustness may be at odds with accuracy (Tsipras et al., 2019), while our training approach is mainly motivated by the optimization issue. Secondly, the implementation is quite different. We use clipped hinge loss to achieve robustness due to its simplicity and uses a decaying λ correlate to p in ℓ_p-relaxation, which is necessary due to the optimization problem in Section 4.1.

5 EXPERIMENTS

5.1 EXPERIMENTAL SETTING

In this section, we evaluate the proposed training strategies on benchmark datasets MNIST and CIFAR-10 to show the effectiveness of ℓ_∞-distance net.

Model details. We use exactly the same model as Zhang et al. (2021) for a fair comparison. Specifically, we consider the simple fully-connect ℓ_∞-distance nets defined in Equation (2). All hidden layers have 5120 neurons. We use a 5-layer network for MNIST and a 6-layer one for CIFAR-10.

Training details. In all experiments, we choose the Adam optimizer with a batch size of 512. The learning rate is set to 0.03 initially and decayed using a simple cosine annealing throughout the whole training process. We use padding and random crop data augmentation for MNIST and CIFAR-10, and also use random horizontal flip for CIFAR-10. The ℓ_p-relaxation starts at $p = 8$ and ends at $p = 1000$ with p increasing exponentially. The mixture coefficient λ decays exponentially during the ℓ_p-relaxation process from λ_0 to a vanishing value λ_{end}. We do not use further tricks in Zhang et al. (2021), e.g. the ℓ_p weight decay or a warmup over perturbation ϵ, to keep our training clean and simple. The dataset dependent hyper-parameters, including θ, λ_0, λ_{end} and the number of epochs T, can be found in Appendix. All experiments are run for 8 times on a single NVIDIA Tesla-V100 GPU, and the median of the performance number is reported.

Evaluation. We test the robustness of the trained models under ϵ-bounded ℓ_∞-norm perturbations. Following the common practice (Madry et al., 2017), we mainly use $\epsilon = 0.3$ for MNIST dataset and $8/255$ for CIFAR-10 dataset. We also provide results under other perturbation magnitudes, e.g. $\epsilon = 0.1$ for MNIST and $\epsilon = 2/255$, $\epsilon = 16/255$ for CIFAR-10. We first evaluate the robust test accuracy under the Projected Gradient Descent (PGD) attack (Madry et al., 2017). The number of iterations of the PGD attack is set to a large number of 100. We then calculate the certified robust accuracy based on the output margin.

5.2 EXPERIMENTAL RESULTS

Results are presented in Table 2. For each method in the table, we report the clean test accuracy without perturbation (denoted as Clean), the robust test accuracy under PGD attack (denoted as PGD), and the certified robust test accuracy (denoted as Certified). We do not compare with randomized smoothing, as it provides probabilistic certified guarantee and only works for very small ϵ (e.g. $\epsilon = 2/255$ for CIFAR-10) according to Salman et al. (2019a).

Comparing with Zhang et al. (2021). It can be seen that for all perturbation levels ϵ and datasets, our proposed training strategy improves the performance of ℓ_∞-distance nets. In particular, we boost the certified accuracy on CIFAR-10 from 33.30% to 40.06% under $\epsilon = 8/255$, and from 19.28% to 29.14% under a larger $\epsilon = 16/255$. Note that we use exactly the same architecture as Zhang et al. (2021), and a larger network with better architecture may further improve the results. Another observation from Table 2 is that the improvement of our proposed training strategy gets more prominent with the increase of ϵ. This is consistent with our finding in Section 4.1, in that the optimization is particularly insufficient for large ϵ using hinge loss, and in this case adding cross-entropy loss can significantly alleviate such problem.

Comparing with other certification methods. For most settings in Table 2, our results establish new state-of-the-arts over previous baselines, despite we use the margin-based certification which is much simpler. The gap is most noticeable for $\epsilon = 8/255$ on CIFAR-10, where we surpass the relaxation-based approaches by more than 5 points. It can also be observed that ℓ_∞-distance net is most suitable for the case when ℓ_∞ perturbation is relatively large. This is not surprising since Lipschitz property is well exhibited in this case. If ϵ is vanishing small, the advantage of the Lipschitz property will not be well-exploited and ℓ_∞-distance net will face more optimization and generalization problems compared with conventional networks.

5.3 INVESTIGATING THE PROPOSED TRAINING STRATEGY

We finally demonstrate by experiments that the proposed training strategy indeed addresses the optimization problem in Section 4.1. We first trace the output margin of the training samples throughout

Table 2: Comparison of our results with existing methods.

Dataset	ϵ	Method	Reference	Clean	PGD	Certified
MNIST	0.1	CAP	(Wong et al., 2018)	98.92	-	96.33
		IBP*	(Gowal et al., 2018)	98.92	97.98	97.25
		CROWN-IBP	(Zhang et al., 2020)	98.83	98.19	97.76
		CROWN-IBP	(Shi et al., 2021)	98.84	-	**97.95**
		ℓ_∞-distance Net[†]	(Zhang et al., 2021)	98.66	97.79[‡]	97.70
		ℓ_∞-distance Net	This paper	98.93	98.03	**97.95**
	0.3	IBP*	(Gowal et al., 2018)	97.88	93.22	91.79
		CROWN-IBP	(Zhang et al., 2020)	98.18	93.95	92.98
		CROWN-IBP	(Shi et al., 2021)	97.67	-	**93.10**
		ℓ_∞-distance Net+MLP	(Zhang et al., 2021)	98.56	95.28[‡]	93.09
		ℓ_∞-distance Net	(Zhang et al., 2021)	98.54	94.71[‡]	92.64
		ℓ_∞-distance Net	This paper	98.56	94.73	**93.20**
CIFAR-10	2/255	CAP	(Wong et al., 2018)	68.28	-	53.89
		IBP*	(Gowal et al., 2018)	61.46	50.28	44.79
		CROWN-IBP	(Zhang et al., 2020)	71.52	59.72	**53.97**
		CROWN-IBP	(Shi et al., 2021)	66.84	-	52.85
		ℓ_∞-distance Net[†]	(Zhang et al., 2021)	60.33	51.45[‡]	50.94
		ℓ_∞-distance Net	This paper	60.61	54.28	**54.12**
	8/255	IBP*	(Gowal et al., 2018)	50.99	31.27	29.19
		CROWN-IBP	(Zhang et al., 2020)	45.98	34.58	33.06
		CROWN-IBP	(Xu et al., 2020)	46.29	35.69	33.38
		CROWN-IBP	(Shi et al., 2021)	48.94	-	34.97
		CROWN-LBP	(Lyu et al., 2021)	48.06	37.95	34.92
		ℓ_∞-distance Net+MLP	(Zhang et al., 2021)	50.80	37.06[‡]	**35.42**
		ℓ_∞-distance Net	(Zhang et al., 2021)	56.80	37.46[‡]	33.30
		ℓ_∞-distance Net	This paper	54.30	41.84	**40.06**
	16/255	IBP*	(Gowal et al., 2018)	31.03	23.34	21.88
		CROWN-IBP	(Zhang et al., 2020)	33.94	24.77	23.20
		CROWN-IBP	(Shi et al., 2021)	36.65	-	**24.48**
		ℓ_∞-distance Net[†]	(Zhang et al., 2021)	55.05	26.02[‡]	19.28
		ℓ_∞-distance Net	This paper	48.50	32.73	**29.04**

[*] The IBP results are obtained from Zhang et al. (2020).

[†] These results are obtained by running the code in the authors' github.

[‡] The PGD step is chosen as 20 in Zhang et al. (2021).

(a)   (b)

Figure 2: Experiments of ℓ_∞-distance net training on CIFAR-10 dataset ($\epsilon = 8/255$) using the proposed objective function (7). (a) The percentage of training samples with output margin greater than θ (blue), less than 0 (orange), or between 0 and θ (green) throughout training. The dashed lines indicate different p values of ℓ_p-relaxation. (b) The final performance of the trained network using different hinge threshold θ.

training on CIFAR-10 dataset ($\epsilon = 8/255$), and plot the percentage of samples with a margin greater than θ, less than 0, or between 0 and θ in Figure 2(a). It can be seen that the percentage of samples with a margin between 0 and θ is always below 50%, therefore the loss does not degenerate in the whole training process. We then demonstrate in Figure 2(b) that the accuracy curve regarding different choices of hinge threshold θ is well-behaved compared with Figure 1(b). In particular, the best θ that maximizes the certified accuracy on training dataset approaches is slightly larger than 2ϵ (while for original hinge loss the value is 6ϵ). The peak certified accuracy on training dataset also improves by 10 points (see blue lines in 1(b) and 2(b)). All evidence clearly demonstrates the effectiveness of the proposed training strategy.

6 RELATED WORK

Existing approaches mainly fall into two categories: adversarial training and certified defenses.

Adversarial training. Adversarial training methods first leverage attack algorithms to generate adversarial examples of the inputs on the fly, then update the model's parameters using these perturbed inputs together with the original labels (Goodfellow et al., 2014; Kurakin et al., 2016; Madry et al., 2017). In particular, Madry et al. (2017) suggested using Projected Gradient Descent (PGD) as the universal attacker to find a perturbation that maximizes the standard cross-entropy loss, which achieves decent empirical robustness. Some recent works considered other training objectives that combine cross-entropy loss and a carefully designed robust surrogate loss (Zhang et al., 2019a; Ding et al., 2019; Wang et al., 2020), which show similarities to this paper. However, all methods above are evaluated empirically using first-order attacks such as PGD, and there is no formal guarantee whether the learned model is truly robust. This motivates researchers to study a new type of method called certified defenses, in which the prediction is guaranteed to remain the same under all allowed perturbations, thus provably resists against all potential attacks.

Relaxation-based certified defenses. These methods adopt convex relaxation to calculate a convex region containing all possible network outputs for a given input under perturbation (Wong & Kolter, 2018; Wong et al., 2018; Dvijotham et al., 2018; 2020; Raghunathan et al., 2018; Weng et al., 2018; Singh et al., 2018; Mirman et al., 2018; Gehr et al., 2018; Wang et al., 2018; Gowal et al., 2018; Zhang et al., 2018; 2020; Xiao et al., 2019; Croce et al., 2019; Balunovic & Vechev, 2020; Lee et al., 2020; Xu et al., 2020; Lyu et al., 2021; Shi et al., 2021). If all points in this region correspond to the correct prediction, then the network is provably robust. However, the relaxation procedure is usually complicated and computationally expensive. Furthermore, Salman et al. (2019b) indicated that there might be an inherent barrier to tight relaxation for a large class of convex relaxation approaches. This is also reflected in experiments, where the trained model often suffers from severe accuracy drop even on training data.

Randomized smoothing for certified robustness. Randomized smoothing provides another way to calculate a probabilistic certification under ℓ_2 perturbations (Lecuyer et al., 2019; Li et al., 2019; Cohen et al., 2019; Salman et al., 2019a; Zhai et al., 2020; Jeong & Shin, 2020). For any classifier, if a Gaussian random noise is added to the input, the resulting "smoothed" classifier then possesses a certified guarantee under ℓ_2 perturbations. Randomized smoothing has been scaled up to ImageNet and achieves state-of-the-art certified accuracy for ℓ_2 perturbations. However, recent studies implies that it cannot achieve nontrivial certified accuracy for ℓ_p perturbations under $\epsilon = \Omega(d^{1/p-1/2})$ when $p > 2$ which depends on the input dimension d (Yang et al., 2020a; Blum et al., 2020; Kumar et al., 2020). Therefore it is not suitable for ℓ_∞ perturbation scenario if ϵ is not very small.

Lipschitz networks. An even simpler way for certified robustness is to use Lipschitz networks, which directly possess margin-based certification. Earlier works in this area mainly regard the Lipschitz property as a kind of regularization and penalize (or constrain) the Lipschitz constant of a conventional ReLU network based on the spectral norms of its weight matrices (Cisse et al., 2017; Yoshida & Miyato, 2017; Gouk et al., 2018; Tsuzuku et al., 2018; Farnia et al., 2019; Qian & Wegman, 2019; Pauli et al., 2021). However, these methods either can not provide certified guarantees or provide a vanishing small certified radius. Anil et al. (2019) figured out that current Lipschitz networks intrinsically lack expressivity to some simple Lipschitz functions, and designed the first Lipschitz-universal approximator called GroupSort network. Leino et al. (2021) achieved the state-of-the-art certified robustness using GroupSort network under ℓ_2 perturbations. However, none of these approaches above can provide good certified results for ℓ_∞ robustness. The most relevant work to this paper is Zhang et al. (2021), in which the author designed a novel Lipschitz network with respect to ℓ_∞-norm. We show such architecture can establish new state-of-the-art results in the ℓ_∞ perturbation scenario.

7 CONCLUSION

In this paper, we demonstrate that a simple ℓ_∞-distance net suffices for good certified robustness from both theoretical and experimental perspectives. The results show a large gain over previous certification approaches. We hope this work can make promising the study of ℓ_∞-distance net, and more generally, the global Lipschitz architectures for certified robustness.

REFERENCES

Cem Anil, James Lucas, and Roger Grosse. Sorting out lipschitz function approximation. In *International Conference on Machine Learning*, pp. 291–301, 2019.

Anish Athalye, Nicholas Carlini, and David Wagner. Obfuscated gradients give a false sense of security: Circumventing defenses to adversarial examples. In *International conference on machine learning*, pp. 274–283. PMLR, 2018.

Mislav Balunovic and Martin Vechev. Adversarial training and provable defenses: Bridging the gap. In *International Conference on Learning Representations*, 2020.

Battista Biggio, Igino Corona, Davide Maiorca, Blaine Nelson, Nedim Šrndić, Pavel Laskov, Giorgio Giacinto, and Fabio Roli. Evasion attacks against machine learning at test time. In *Joint European conference on machine learning and knowledge discovery in databases*, pp. 387–402. Springer, 2013.

Avrim Blum, Travis Dick, Naren Manoj, and Hongyang Zhang. Random smoothing might be unable to certify ℓ_∞ robustness for high-dimensional images, 2020.

Nicholas Carlini and David Wagner. Adversarial examples are not easily detected: Bypassing ten detection methods. In *Proceedings of the 10th ACM workshop on artificial intelligence and security*, pp. 3–14, 2017.

Moustapha Cisse, Piotr Bojanowski, Edouard Grave, Yann Dauphin, and Nicolas Usunier. Parseval networks: Improving robustness to adversarial examples. In *International Conference on Machine Learning*, pp. 854–863, 2017.

Jeremy Cohen, Elan Rosenfeld, and Zico Kolter. Certified adversarial robustness via randomized smoothing. In *International Conference on Machine Learning*, pp. 1310–1320. PMLR, 2019.

Francesco Croce and Matthias Hein. Reliable evaluation of adversarial robustness with an ensemble of diverse parameter-free attacks. In *International conference on machine learning*, pp. 2206–2216. PMLR, 2020.

Francesco Croce, Maksym Andriushchenko, and Matthias Hein. Provable robustness of relu networks via maximization of linear regions. In *the 22nd International Conference on Artificial Intelligence and Statistics*, pp. 2057–2066. PMLR, 2019.

Gavin Weiguang Ding, Yash Sharma, Kry Yik Chau Lui, and Ruitong Huang. Mma training: Direct input space margin maximization through adversarial training. In *International Conference on Learning Representations*, 2019.

Krishnamurthy Dvijotham, Robert Stanforth, Sven Gowal, Timothy Mann, and Pushmeet Kohli. A dual approach to scalable verification of deep networks, 2018.

Krishnamurthy Dj Dvijotham, Robert Stanforth, Sven Gowal, Chongli Qin, Soham De, and Pushmeet Kohli. Efficient neural network verification with exactness characterization. In *Uncertainty in Artificial Intelligence*, pp. 497–507. PMLR, 2020.

Farzan Farnia, Jesse Zhang, and David Tse. Generalizable adversarial training via spectral normalization. In *International Conference on Learning Representations*, 2019.

Timon Gehr, Matthew Mirman, Dana Drachsler-Cohen, Petar Tsankov, Swarat Chaudhuri, and Martin Vechev. Ai2: Safety and robustness certification of neural networks with abstract interpretation. In *2018 IEEE Symposium on Security and Privacy (SP)*, pp. 3–18. IEEE, 2018.

Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. *arXiv preprint arXiv:1412.6572*, 2014.

Henry Gouk, Eibe Frank, Bernhard Pfahringer, and Michael Cree. Regularisation of neural networks by enforcing lipschitz continuity. *arXiv preprint arXiv:1804.04368*, 2018.

Sven Gowal, Krishnamurthy Dvijotham, Robert Stanforth, Rudy Bunel, Chongli Qin, Jonathan Uesato, Relja Arandjelovic, Timothy Mann, and Pushmeet Kohli. On the effectiveness of interval bound propagation for training verifiably robust models. *arXiv preprint arXiv:1810.12715*, 2018.

Jongheon Jeong and Jinwoo Shin. Consistency regularization for certified robustness of smoothed classifiers. *Advances in Neural Information Processing Systems*, 33, 2020.

Aounon Kumar, Alexander Levine, Tom Goldstein, and Soheil Feizi. Curse of dimensionality on randomized smoothing for certifiable robustness. In *International Conference on Machine Learning*, pp. 5458–5467. PMLR, 2020.

Alexey Kurakin, Ian Goodfellow, and Samy Bengio. Adversarial machine learning at scale. *arXiv preprint arXiv:1611.01236*, 2016.

Mathias Lecuyer, Vaggelis Atlidakis, Roxana Geambasu, Daniel Hsu, and Suman Jana. Certified robustness to adversarial examples with differential privacy. In *2019 IEEE Symposium on Security and Privacy (SP)*, pp. 656–672. IEEE, 2019.

Sungyoon Lee, Jaewook Lee, and Saerom Park. Lipschitz-certifiable training with a tight outer bound. *Advances in Neural Information Processing Systems*, 33, 2020.

Klas Leino, Zifan Wang, and Matt Fredrikson. Globally-robust neural networks. In *International Conference on Machine Learning (ICML)*, 2021.

Bai Li, Changyou Chen, Wenlin Wang, and Lawrence Carin. Certified adversarial robustness with additive noise. *Advances in Neural Information Processing Systems*, 32:9464–9474, 2019.

Zhaoyang Lyu, Minghao Guo, Tong Wu, Guodong Xu, Kehuan Zhang, and Dahua Lin. Towards evaluating and training verifiably robust neural networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 4308–4317, 2021.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. *arXiv preprint arXiv:1706.06083*, 2017.

Matthew Mirman, Timon Gehr, and Martin Vechev. Differentiable abstract interpretation for provably robust neural networks. In *International Conference on Machine Learning*, pp. 3578–3586. PMLR, 2018.

Patricia Pauli, Anne Koch, Julian Berberich, Paul Kohler, and Frank Allgower. Training robust neural networks using lipschitz bounds. *IEEE Control Systems Letters*, 2021.

Haifeng Qian and Mark N. Wegman. L2-nonexpansive neural networks. In *International Conference on Learning Representations*, 2019.

Aditi Raghunathan, Jacob Steinhardt, and Percy Liang. Certified defenses against adversarial examples. In *International Conference on Learning Representations*, 2018.

Hadi Salman, Greg Yang, Jerry Li, Pengchuan Zhang, Huan Zhang, Ilya Razenshteyn, and Sébastien Bubeck. Provably robust deep learning via adversarially trained smoothed classifiers. In *Proceedings of the 33rd International Conference on Neural Information Processing Systems*, pp. 11292–11303, 2019a.

Hadi Salman, Greg Yang, Huan Zhang, Cho-Jui Hsieh, and Pengchuan Zhang. A convex relaxation barrier to tight robustness verification of neural networks. *Advances in Neural Information Processing Systems*, 32:9835–9846, 2019b.

Zhouxing Shi, Yihan Wang, Huan Zhang, Jinfeng Yi, and Cho-Jui Hsieh. Fast certified robust training with short warmup. In *ICML 2021 Workshop on Adversarial Machine Learning*, 2021.

Gagandeep Singh, Timon Gehr, Matthew Mirman, Markus Püschel, and Martin Vechev. Fast and effective robustness certification. In *Advances in Neural Information Processing Systems*, pp. 10802–10813, 2018.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. *arXiv preprint arXiv:1312.6199*, 2013.

Florian Tramer, Nicholas Carlini, Wieland Brendel, and Aleksander Madry. On adaptive attacks to adversarial example defenses. *Advances in Neural Information Processing Systems*, 33, 2020.

Dimitris Tsipras, Shibani Santurkar, Logan Engstrom, Alexander Turner, and Aleksander Madry. Robustness may be at odds with accuracy. In *International Conference on Learning Representations*, 2019.

Yusuke Tsuzuku, Issei Sato, and Masashi Sugiyama. Lipschitz-margin training: Scalable certification of perturbation invariance for deep neural networks. In *Advances in neural information processing systems*, pp. 6541–6550, 2018.

Jonathan Uesato, Brendan O'donoghue, Pushmeet Kohli, and Aaron Oord. Adversarial risk and the dangers of evaluating against weak attacks. In *International Conference on Machine Learning*, pp. 5025–5034. PMLR, 2018.

Shiqi Wang, Kexin Pei, Justin Whitehouse, Junfeng Yang, and Suman Jana. Efficient formal safety analysis of neural networks. *Advances in Neural Information Processing Systems*, 31, 2018.

Yisen Wang, Difan Zou, Jinfeng Yi, James Bailey, Xingjun Ma, and Quanquan Gu. Improving adversarial robustness requires revisiting misclassified examples. In *International Conference on Learning Representations*, 2020.

Lily Weng, Huan Zhang, Hongge Chen, Zhao Song, Cho-Jui Hsieh, Luca Daniel, Duane Boning, and Inderjit Dhillon. Towards fast computation of certified robustness for relu networks. In *International Conference on Machine Learning*, pp. 5276–5285. PMLR, 2018.

Eric Wong and Zico Kolter. Provable defenses against adversarial examples via the convex outer adversarial polytope. In *International Conference on Machine Learning*, pp. 5286–5295. PMLR, 2018.

Eric Wong, Frank R Schmidt, Jan Hendrik Metzen, and J Zico Kolter. Scaling provable adversarial defenses. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, pp. 8410–8419, 2018.

Kai Y Xiao, Vincent Tjeng, Nur Muhammad Mahi Shafiullah, and Aleksander Madry. Training for faster adversarial robustness verification via inducing relu stability. In *International Conference on Learning Representations*, 2019.

Kaidi Xu, Zhouxing Shi, Huan Zhang, Yihan Wang, Kai-Wei Chang, Minlie Huang, Bhavya Kailkhura, Xue Lin, and Cho-Jui Hsieh. Automatic perturbation analysis for scalable certified robustness and beyond. *Advances in Neural Information Processing Systems*, 33, 2020.

Greg Yang, Tony Duan, J Edward Hu, Hadi Salman, Ilya Razenshteyn, and Jerry Li. Randomized smoothing of all shapes and sizes. In *International Conference on Machine Learning*, pp. 10693–10705. PMLR, 2020a.

Yao-Yuan Yang, Cyrus Rashtchian, Hongyang Zhang, Russ R Salakhutdinov, and Kamalika Chaudhuri. A closer look at accuracy vs. robustness. In *Proceedings of the 34rd International Conference on Neural Information Processing Systems*, 2020b.

Yuichi Yoshida and Takeru Miyato. Spectral norm regularization for improving the generalizability of deep learning. *arXiv preprint arXiv:1705.10941*, 2017.

Runtian Zhai, Chen Dan, Di He, Huan Zhang, Boqing Gong, Pradeep Ravikumar, Cho-Jui Hsieh, and Liwei Wang. Macer: Attack-free and scalable robust training via maximizing certified radius. In *International Conference on Learning Representations*, 2020.

Bohang Zhang, Tianle Cai, Zhou Lu, Di He, and Liwei Wang. Towards certifying l-infinity robustness using neural networks with l-inf-dist neurons. In *International Conference on Machine Learning*, pp. 12368–12379. PMLR, 2021.

Hongyang Zhang, Yaodong Yu, Jiantao Jiao, Eric Xing, Laurent El Ghaoui, and Michael Jordan. Theoretically principled trade-off between robustness and accuracy. In *International Conference on Machine Learning*, pp. 7472–7482. PMLR, 2019a.

Hongyi Zhang, Yann N Dauphin, and Tengyu Ma. Fixup initialization: Residual learning without normalization. In *International Conference on Learning Representations*, 2019b.

Huan Zhang, Tsui-Wei Weng, Pin-Yu Chen, Cho-Jui Hsieh, and Luca Daniel. Efficient neural network robustness certification with general activation functions. *Advances in Neural Information Processing Systems*, 31:4939–4948, 2018.

Huan Zhang, Hongge Chen, Chaowei Xiao, Sven Gowal, Robert Stanforth, Bo Li, Duane Boning, and Cho-Jui Hsieh. Towards stable and efficient training of verifiably robust neural networks. In *International Conference on Learning Representations*, 2020.

A   PROOF OF THEOREM 3.2 AND BEYOND

Theorem A.1. *Let $\mathcal{D}$ be a dataset with n elements satisfying the r-separation condition with respect to ℓ_∞-norm. Then there exists a two-layer ℓ_∞-distance net with hidden size n, such that the certified ℓ_∞ robust accuracy is 100% on $\mathcal{D}$ under perturbation $\epsilon = r$.*

Proof. Consider a two layer ℓ_∞-distance net $\boldsymbol{g}$ defined in Equation (2). Let its parameters be assigned by

$$
\begin{aligned}
\boldsymbol{w}^{(1,i)} &= \boldsymbol{x}_i, b_i^{(1)} = 0 && \text{for } i \in [n] \\
w_i^{(2,j)} &= C \cdot \mathbb{I}(y_i = j), b_j^{(2)} = -C && \text{for } i \in [n], j \in [K]
\end{aligned}
\tag{8}
$$

where $C = 4 \max_{i \in [n]} \|\boldsymbol{x}_i\|_\infty$ is a constant, and $\mathbb{I}(\cdot)$ is the indicator function. The chosen of C is large enough so that the following holds:

$$
\|\boldsymbol{x}_i - \boldsymbol{x}_j\| \le C/2 \qquad \forall (\boldsymbol{x}_i, y_i), (\boldsymbol{x}_j, y_j) \in \mathcal{D}
\tag{9}
$$

For the above assignment, the first layer simply calculates the ℓ_∞-distance between $\boldsymbol{x}$ and each sample in dataset $\mathcal{D}$, and we now derive the output of the second layer. We have

$$
\begin{aligned}
[\boldsymbol{g}(\boldsymbol{x})]_j = x_j^{(2)} &= \|\boldsymbol{x}^{(1)} - \boldsymbol{w}^{(2,j)}\| + b^{(2,j)} \\
&= b^{(2,j)} + \max_{i \in [n]} |x_i^{(1)} - w_i^{(2,j)}| \\
&= -C + \max \left\{ \max_{i \in [n], y_i = j} |x_i^{(1)} - C|, \max_{i \in [n], y_i \ne j} |x_i^{(1)}| \right\} \\
&= -C + \max \left\{ \max_{i \in [n], y_i = j} |\|\boldsymbol{x} - \boldsymbol{x}_i\| - C|, \max_{i \in [n], y_i \ne j} \|\boldsymbol{x} - \boldsymbol{x}_i\| \right\} \tag{10} \\
&= -C + \max_{i \in [n], y_i = j} (C - x_i^{(1)}) \tag{11} \\
&= - \min_{i \in [n], y_i = j} \|\boldsymbol{x} - \boldsymbol{x}_i\|_\infty. \tag{12}
\end{aligned}
$$

Here a core step is Equation (11) which follows by using Inequality (9) when the image $\boldsymbol{x}$ is in dataset $\mathcal{D}$.

From Equation (12) the network $\boldsymbol{g}$ can represent a nearest neighbor classifier, in that it outputs the negative of the nearest neighbor distance between input $\boldsymbol{x}$ and the samples of each class. Therefore, given data $\boldsymbol{x} = \boldsymbol{x}_i$ in dataset $\mathcal{D}$, the output $[\boldsymbol{g}(\boldsymbol{x})]_j$ is either 0 or less than $-2r$ depending on whether $j = y_i$, due to the r-separation condition. Therefore the output margin is at least $2r$. In other words, $\boldsymbol{g}$ achieves 100% certified robust accuracy on $\mathcal{D}$. $\qquad\square$

We now give a general result which shows that any L layer ($L \ge 2$) ℓ_∞-distance net with hidden size $O(n/L + K + d)$ can achieve perfect certified robustness. In this general setting, the total number of neurons in the network is thus $O(n + KL + dL)$ which is still close to real practice.

Theorem A.2. *Let $\mathcal{D}$ be a dataset with n elements satisfying the r-separation condition with respect to ℓ_∞-norm. Then there exists an L-layer ℓ_∞-distance net with hidden size no more than $\lceil \frac{n}{L-1} \rceil + K + d$ where d is the input dimension, such that the certified ℓ_∞ robust accuracy is 100% on $\mathcal{D}$ under perturbation $\epsilon = r$.*

Proof. The basic idea is to rearrange the computation process of the two-layer network in the above proof by order so as to satisfy the width constraint. Define K prefix arrays $h_j (j \in [K])$ as follows:

$$
h_{j,k} = - \min_{i \in [k], y_i = j} \|\boldsymbol{x} - \boldsymbol{x}_i\|_\infty.
\tag{13}
$$

Note that we want the network output to be the negative of the nearest neighbor distance of all sample in a class j, i.e. $-\min_{i \in [n], y_i = j} \|\boldsymbol{x} - \boldsymbol{x}_i\|_\infty$, which corresponds to $h_{j,n}$.

For any hidden layer $\boldsymbol{x}^{(l)}$, we separate it into three sets: $\mathcal{S}_1^{(l)} = \{x_i^{(l)} : i \in [d]\}$, $\mathcal{S}_2^{(l)} = \{x_i^{(l)} : i \in d+1, \cdots, d+K\}$ and the rest $\lceil \frac{n}{L-1} \rceil$ neurons $\mathcal{S}_3^{(l)}$. We also denote $\mathcal{S}_2^{(L)} = \{x_i^{(L)} : i \in [K]\}$ for

ease of presentation. We let the neurons of $\mathcal{S}_1^{(l)}$ in each layer exactly represent the input $\boldsymbol{x}$. This is feasible since an ℓ_∞-distance neuron can represent the operation that fetches an element of the neuron input on a bounded domain, e.g.

$$u(\boldsymbol{x}, \{\boldsymbol{w}, b\}) = \|\boldsymbol{x} - \boldsymbol{w}\|_\infty + b = x_j \quad \forall \boldsymbol{x} \in \mathbb{K} \tag{14}$$

if we assign $w_j = -C, b = -C, w_k = 0 (k \neq j)$ where C is sufficiently larger than twice the diameter of domain $\mathbb{K}$. In this way, all hidden neurons in the network can have access to the network input $\boldsymbol{x}$.

Next, we aim at designing the following computation pattern for $\mathcal{S}_2^{(l)}$:

$$\mathcal{S}_2^{(l)} = \{h_{j, \lceil \frac{n(l-1)}{L-1} \rceil} : j \in K\}. \tag{15}$$

In this way $\mathcal{S}_2^{(L)} = \{h_{j,n} : j \in [K]\}$, and the network exactly represents a nearest neighbor classifier. To represent $\mathcal{S}_2^{(l+1)}$, we use the simple recursive relation

$$h_{j, \lceil \frac{nl}{L-1} \rceil} = \max \left\{ h_{j, \lceil \frac{n(l-1)}{L-1} \rceil}, \max_{i \in \left\{ \lceil \frac{n(l-1)}{L-1} \rceil + 1, \cdots, \lceil \frac{nl}{L-1} \rceil \right\}, y_i = j} -\|\boldsymbol{x} - \boldsymbol{x}_i\|_\infty \right\}. \tag{16}$$

Note that $h_{j, \lceil \frac{n(l-1)}{L-1} \rceil}$ is already calculated in $\mathcal{S}_2^{(l)}$ in the previous layer. The left thing is to calculate $\|\boldsymbol{x} - \boldsymbol{x}_i\|_\infty$ for all $i \in \left\{ \lceil \frac{n(l-1)}{L-1} \rceil + 1, \cdots, \lceil \frac{nl}{L-1} \rceil \right\}$, which can be done by the neurons of the set $\mathcal{S}_3^{(l)}$ in the previous layer. The neurons in $\mathcal{S}_2^{(l+1)}$ finally merges all these values (a neuron in $\mathcal{S}_2^{(l)}$ and part of neurons in $\mathcal{S}_3^{(l)}$), using the construction similar to (8). Proof completes. $\square$

B ADDITIONAL EXPERIMENTAL DETAILS AND HYPER-PARAMETERS

Our experiments are implemented using the Pytorch framework. For all experiments, we use a single NVIDIA Tesla-V100 GPU. The CUDA version is 11.2.

The learnable scalar in Equation (7) is initialized to be one and trained using a smaller learning rate that is one-fifth of the base learning rate. This is mainly to make training stable as suggested in Zhang et al. (2019b) since the scalar scales the whole network output. For random crop data augmentation, we use padding = 1 for MNIST and padding = 3 for CIFAR-10. The model is initialized using identity-map initialization (see Section 5.3 in Zhang et al. (2021)), and mean-shift batch normalization is used for all intermediate layers. The training procedure is as follows:

- In the first e_1 epochs, we set $p = 8$ in ℓ_p-relaxation and use $\lambda = \lambda_0$ as the mixture coefficient;
- In the next e_2 epochs, p is exponentially increased from 8 to 1000. Accordingly, λ exponentially decreases from λ_0 to a vanishing small value λ_{end};
- In the final e_3 epochs, p is set to infinity and λ is set to 0.

All hyper-parameters are provided in Table 3.

We also run additional experiments using the training strategy in Zhang et al. (2021) for performance comparison when the original paper does not present the corresponding results. This mainly includes the case $\epsilon = 0.1$ on MNIST and $\epsilon = 2/255, \epsilon = 16/255$ on CIFAR-10, as shown in Table 2. We use the same hyper-parameters in Zhang et al. (2021), except for the hinge threshold θ where we perform a careful grid search. The choice of θ are shown in Table 4.

Table 3: Hyper-parameters used in this paper.

Dataset	MNIST		CIFAR-10		
ϵ	0.1	0.3	2/255	8/255	16/255
Optimizer	Adam($\beta_1 = 0.9, \beta_2 = 0.99, \epsilon = 10^{-10}$)				
Learning rate	0.03				
Batch size	512				
p_{start}	8				
p_{end}	1000				
Epochs	$e_1 = 25, e_2 = 375, e_3 = 50$		$e_1 = 100, e_2 = 1150, e_3 = 50$		
Total Epochs	450		1300		
Hinge threshold θ	0.6	0.9	20/255	48/255	80/255
Mixture coefficient λ_0	0.05	0.05	0.05	0.1	0.1
Mixture coefficient λ_{end}	2×10^{-4}	2×10^{-4}	2×10^{-3}	5×10^{-4}	2×10^{-4}

Table 4: Best hinge threshold for different settings using the training strategy in Zhang et al. (2021).

Dataset	MNIST		CIFAR-10		
ϵ	0.1	0.3	2/255	8/255	16/255
Hinge threshold θ	0.8	0.9	32/255	80/255	128/255