MindEdit-Bench: Benchmarking Object-Level Counterfactual Spatial Reasoning in VLMs from In-the-Wild Photos

Abstract

Benchmarks for vision–language models (VLMs) mostly test *observational* spatial reasoning: models describe relations already visible in the input. Existing what-if tasks typically vary the observer while keeping the scene fixed. Can VLMs instead predict the consequences of hypothetically moving or rotating an object? We introduce **MindEdit-Bench**[1], a benchmark of six spatial reasoning tasks built from three-photo smartphone triplets of newly captured indoor scenes via an automatic in-the-wild 3D scene-graph extraction pipeline. Four tasks probe perception and perspective transformation over observed structure; two new tasks, **L4 (spatial editing)** and **L5 (cross-view visibility editing)**, probe object-level counterfactual reasoning, where correct answers are absent from all input images. Each question provides 8–24 structured answer choices, enabling answer-letter-level diagnosis of spatial and fallback errors. The benchmark covers 120 private indoor scenes not drawn from public datasets, reducing public-data pretraining-overlap risk. Across 15 VLMs on 1,003 human-verified questions, task-wise mean VLM accuracy is only 8%–31%, versus 81%–97% human majority-vote accuracy. The pooled human–best-VLM gap is 53 pp, with at least 39 pp on every task. The structured answer space further reveals non-uniform failures, including weaker camera-depth-axis inference and fallback behavior on difficult visibility-editing cases.

1 Introduction

Spatial reasoning is central to cognitive science, computer vision, and embodied AI. In vision–language models (VLMs), spatial-reasoning evaluation has progressed from single-image QA to multi-image, video, and holistic benchmark suites (Chen et al., 2024; Cheng et al., 2024; Yang et al., 2025c; Li et al., 2025; Yang et al., 2025a; Wu et al., 2025;

---

[1]Anonymous repository: `https://anonymous.4open.science/r/MindEdit-Bench-4AE7/`.

Cai et al., 2025b; Xiao et al., 2025). Yet most existing benchmarks remain observational: they ask models to describe spatial relations already present in the input. This leaves a distinct question unanswered: can VLMs predict what follows when the spatial configuration itself is changed?

Object-level counterfactual spatial reasoning targets this missing case. It requires a model to represent a scene, apply a hypothetical intervention to an object, and infer the resulting spatial consequences. Existing VLM what-if benchmarks cover two narrower settings: observer-level tasks vary the viewer while keeping the scene fixed (Ma et al., 2023; Wang et al., 2025), and image-editing benchmarks modify pixels to evaluate generation fidelity rather than spatial reasoning (Xiao et al., 2026). The object-level case, where an object is hypothetically translated or rotated while the observer remains fixed, has not been systematically evaluated.

We introduce **MindEdit-Bench**, a six-task spatial reasoning benchmark built from three-photo smartphone triplets of privately captured indoor scenes. Four tasks test perception and perspective transformation over observed 3D structure (L1–L3b), while two test object-level counterfactual reasoning. L4 spatial editing asks how an object relation changes after virtual translation or rotation; L5 cross-view visibility editing asks which virtual edit would make an object appear or disappear in another view. Since L4/L5 answers appear in none of the input images, they remove direct 2D visual cues by construction and require reasoning over an internal 3D scene representation.

MindEdit-Bench is built on 120 newly and privately captured indoor scenes that were not part of any public dataset before our evaluation. An automatic in-the-wild pipeline generates candidate questions from three smartphone photos by extracting an object-centric 3D scene graph using feed-forward depth estimation, segmentation, and cross-view object association, without professional

Figure 1: **MindEdit-Bench overview.** MindEdit-Bench probes object-level counterfactual spatial reasoning in VLMs, built from three-photo smartphone triplets sampled from privately captured indoor scenes. **(a)** An automatic feed-forward pipeline reconstructs an object-centric 3D scene graph. **(b)** An L4 spatial-editing question whose correct answer is absent from all input photos. **(c)** The six tasks (L1–L5) span three cognitive operations: perception, perspective transformation, and counterfactual editing. **(d)** Across all six tasks, best-VLM accuracy is far below the three-annotator human majority vote; the two new counterfactual editing tasks (L4 and L5) are marked with stars.

scanning, dense video capture, or per-scene optimisation; the final evaluation set is human-audited for correctness. Each question provides 8–24 structured answer choices, enabling direction, distance, motion-axis, operation-type, and fallback errors to be diagnosed from the final answer letter alone.

We evaluate 15 VLMs on 1,003 human-verified questions. Across six task types, mean VLM accuracy ranges from 8% to 31%, while three-annotator human majority vote reaches 81–97%, leaving a pooled human–best-VLM gap of 53 pp. Beyond aggregate accuracy, MindEdit-Bench shows that VLMs do not yet robustly maintain and manipulate the 3D scene representation needed for object-level counterfactual edits. Their failures are not uniform: the diagnostic answer grid reveals weaker spatial inference along the camera depth axis than along lateral/image-plane directions, while demanding cross-view visibility-editing cases elicit fallback behavior in weaker models.

Our contributions are threefold:

- **C1.** We present an end-to-end feed-forward engine that extracts object-centric 3D scene graphs from raw indoor photos and generates structured spatial-reasoning questions.
- **C2.** We introduce, to our knowledge, the first benchmark for object-level counterfactual spatial

editing in VLMs, through L4 spatial editing and L5 cross-view visibility editing, whose answers appear in none of the input images.
- **C3.** We design 8–24 structured answer choices that lower random-guess baselines and enable letter-level diagnosis of direction, distance, motion-axis, operation-type, and fallback errors, without chain-of-thought analysis.

2 Related Work

Spatial reasoning benchmarks for VLMs. VLM spatial-reasoning benchmarks have expanded along the input axis, from single-image QA (Chen et al., 2024; Cheng et al., 2024) to multi-image (Yang et al., 2025c; Li et al., 2025), video (Yang et al., 2025a), and holistic benchmark suites (Wu et al., 2025; Cai et al., 2025b; Xiao et al., 2025). They expose persistent gaps in perspective-taking, multi-view integration, and broad spatial understanding, and show that VLMs can exploit textual or pixel-level shortcuts instead of consistently grounding answers in 3D geometry (Wang et al., 2024). However, these benchmarks largely keep the scene configuration fixed: models reason about relations or viewpoints over what is already observed. MindEdit-Bench instead evaluates object-level counterfactual reasoning: models must

infer the spatial consequences of hypothetically moving or rotating an object.

Hypothetical spatial reasoning and cognitive foundations. Counterfactual spatial reasoning is closely related to cognitive accounts of mental models, viewpoint-independent spatial inference, and mental rotation (Johnson-Laird, 1983; Tversky, 1993; Shepard and Metzler, 1971). More broadly, mental simulation has been argued to support mechanical and physical reasoning (Hegarty, 2004; Battaglia et al., 2013); Gerstenberg (2024) formalises counterfactual reasoning as building a generative mental model, imposing an intervention, and reading off its consequences. Existing VLM what-if benchmarks instantiate this idea at two narrower granularities: observer-level changes, where the viewer moves or reorients while the scene stays fixed (Ma et al., 2023; Wang et al., 2025), and image-editing tasks, which evaluate generation fidelity rather than spatial reasoning (Xiao et al., 2026). MindEdit-Bench introduces the object-level case: an object is translated or rotated while the observer remains fixed, requiring the model to re-derive spatial relations and cross-view visibility in a configuration absent from all input images.

In-the-wild spatial data pipelines. Spatial benchmark construction often trades off geometric precision against collection cost. Scan-based resources rely on dedicated capture hardware (Dai et al., 2017), while recent in-the-wild pipelines such as Holi-Spatial (Gao et al., 2026) use dense video and per-scene 3D Gaussian Splatting to generate large QA sets at substantial compute cost. MindEdit-Bench occupies a lower-cost point in this design space: from only three handheld smartphone photos per scene, a feed-forward pipeline extracts an object-centric 3D scene graph and generates candidate questions without professional scanning, dense multi-view capture, or per-scene optimisation. The resulting loss in geometric precision is mitigated through sweet-zone filtering, distance margins, and human audit.

3 MindEdit-Bench

MindEdit-Bench evaluates VLMs on six spatial reasoning tasks constructed from three handheld smartphone photos of an indoor scene (Section 4). The six tasks are organised by task characteristics into **three groups**. **Group I Perception** comprises L1 cross-view object relations and L2 camera mo-

tion, which can in principle be answered within the camera reference frame of the input image and serve as the observational baseline. **Group II Perspective Transformation** comprises L3a single-view perspective transformation and L3b cross-view perspective transformation, which require the model to reason from an imagined viewpoint different from any input camera. **Group III Counterfactual Editing** comprises L4 spatial editing and L5 cross-view visibility editing, which ask about configurations produced by a hypothetical modification of the scene and its cross-view consequences. Table 1 summarises the six types; choice counts differ across task types and each carries a different random baseline, which we report alongside every main result.

3.1 Task Taxonomy

Group I Perception. These tasks ask about the observed scene and camera motion without requiring an imagined viewpoint or edited scene configuration, and therefore serve as observational baselines. We also note whether each task admits partial 2D shortcuts, since prior work shows that VLMs often exploit pixel-level or textual cues instead of consistently grounding answers in 3D geometry.

L1: Cross-View Object Relations. Given three images of the same scene from different viewpoints, the model identifies which pair of objects has the smallest 3D surface distance. Since no single image contains all objects and relevant depth relations, the task requires integrating spatial information across views. 2D shortcuts are partially effective: objects that appear close in 2D pixel space are often close in 3D, providing a weak but usable signal.

L2: Camera Motion. Given two images, the model predicts camera motion as a translation direction (forward / backward / left / right / negligible) plus a rotation direction (yaw left / yaw right / pitch up / pitch down / negligible). This task tests whether the model treats images as viewpoints of one 3D scene. 2D shortcuts can help with rotation, e.g., leftward scene shift implies rightward yaw, but not with depth-axis translation, which appears only as subtle 2D scaling.

Group II Perspective Transformation. These tasks require the model to reason from an imagined viewpoint different from any input camera. Because the implied reference frame no longer coincides with the image frame, direct image-plane heuristics are no longer reliable.

Table 1: Six task types in MindEdit-Bench, organised into three groups by task characteristics. "2D shortcut" indicates whether pixel-based heuristics can yield correct answers without 3D reasoning.

Group	ID	Task	Choices	2D shortcut
I Perception	L1	Cross-View Object Relations	10–12	partial
	L2	Camera Motion	12–15	partial (rotation)
II Perspective Transformation	L3a	Single-View Perspective Transformation	8–24	none
	L3b	Cross-View Perspective Transformation	8–24	none
III Counterfactual Editing	L4	Spatial Editing	14–16	**none**
	L5	Cross-View Visibility Editing	8–12	**none**

L3: Perspective Transformation. Given three reference objects A, B, and C, the model imagines standing at A facing B, then judges C's direction and distance in this new frame. This requires transforming from the camera's egocentric frame to an A-centered frame where A→B is "forward". 2D shortcuts are ineffective by construction: an object on the image right may become "in front of you" after facing B, breaking the link between image-plane and spatial directions. L3 has two variants: **L3a (single-view)**, where A, B, and C appear in one image, and **L3b (cross-view)**, where they appear across images, adding multi-view integration to perspective transformation.

Group III Counterfactual Editing. These tasks probe object-level counterfactual reasoning: a hypothetical translation or pivot rotation is applied to a chosen object, and the model must reason about the resulting scene configuration. Because the post-edit configuration appears in none of the input images, direct visual lookup from the observed images is ruled out by construction.

L4: Spatial Editing. An object A is virtually translated along one of four horizontal directions (left, right, toward camera, away from camera) by a scene-dependent distance, or rotated around a second reference object's vertical axis by $90°$, $180°$, or $270°$. The model then judges A's direction and distance relative to a reference object C. Because the answer exists in none of the input images, the model cannot directly match the query to an observed visual configuration; it must mentally execute the transformation and re-evaluate spatial relations in the modified scene.

L5: Cross-View Visibility Editing. The model is given two views (source and target) of the same scene, an object A, and a list of candidate transformations of A: translations along a direction by a fixed distance, or rotations around another reference object. The task has two variants. In the appear variant, A is visible in the source view but absent from the target view; the model must identify the transformation that would bring A into the target view. In the disappear variant, A is visible in both views; the model must identify the transformation that would remove A from the target view. Solving either variant requires mentally applying the candidate transformation, projecting A's new position into the target camera, and accounting for occlusion by other scene objects. An option "none of the above" may also be correct.

Detailed per-task generation algorithms, distractor sampling rules, and implementation parameters for all six tasks are in Appendix C.

3.2 Structured Answer Design

Each question provides 8–24 multiple-choice options, reducing random-guess baselines to roughly 4–13% rather than 25% in standard 4-choice formats. The larger answer space lets distractors be structured along meaningful spatial axes. In L2, each option pairs a translation direction with a rotation direction, so the answer letter encodes both motion components. In L3/L4, options form an eight-direction × distance-bin grid, so the letter encodes both predicted direction and distance. In L5, options cover translation edits, rotation edits, and a "none of the above" fallback, so the letter encodes the selected operation type or fallback response. This enables letter-level diagnosis of direction, distance, motion-axis, operation-type, and fallback errors without chain-of-thought parsing.

4 Data Engine

MindEdit-Bench is constructed by a feed-forward pipeline that takes three casually captured smartphone photos as input and produces structured spatial reasoning questions. We deliberately trade scene-graph completeness and geometric precision for accessibility. Our pipeline does not aim to recover every object in the scene; instance segmenta-

Figure 2: **3D Scene-Graph Extraction Pipeline.** The two-stage feed-forward pipeline takes three smartphone photos and produces an object-centric 3D scene graph that feeds the question generator (§3). **Stage 1: per-view 2D perception.** DA3 produces a metric depth map and camera pose for each photo; SAM3, prompted by an LLM-generated object vocabulary (e.g., sofa, table, lamp), produces per-view object masks. **Stage 2: cross-view 3D object association.** Per-view masks and depths are back-projected into 3D, point clusters across the three views are matched, and the resulting scene is aligned to gravity.

tion is followed by a quality filter (size, confidence) that retains only clearly-segmentable scene objects suitable for anchoring questions. The three views are taken with sufficient view overlap to support cross-view 3D association (Stage 2 of Section 4.1) while preserving enough viewpoint diversity for the perspective-transformation and cross-view visibility tasks. We privately captured 120 indoor scenes (∼810 triplets) using consumer smartphones; these images were not part of any public dataset before our evaluation, reducing the risk of overlap with VLM pretraining data. Capture protocols are in Appendix B; the object filter is in Appendix C. End-to-end pipeline quality is quantified by human audit in Section 4.2.

4.1 3D Scene-Graph Extraction Pipeline

We organise the pipeline in two stages, illustrated in Figure 2: per-view 2D perception (Stage 1) and cross-view 3D object association (Stage 2). Concrete hyperparameters for each stage are deferred to Appendix B.

Stage 1: Per-view 2D perception. Each input photo is processed independently to produce three per-view primitives. An LLM (Gemini 3.1 Pro) examines all three photos in a single API call to produce a unified object vocabulary, so that the same physical object is not renamed across views. Feed-forward monocular depth and camera intrinsics/extrinsics are recovered by DA3 (Lin et al., 2025), whose feed-forward design matches our three-photo input. Classical Structure-from-Motion pipelines, by contrast, rely on sufficient

multi-view feature correspondences and can be brittle under our sparse three-photo capture setting. Open-vocabulary instance segmentation via SAM3 (Carion et al., 2025) is guided by the Stage-1 vocabulary; we apply a within-class non-maximum suppression to merge over-segmented parts (e.g., a table split into top and legs), with cross-class merges forbidden.

Stage 2: Cross-view 3D object association. The per-view perception of Stage 1 produces mask sets that are independent across views. Stage 2 recovers this cross-view correspondence in 3D. For each view in turn, every segmented mask is back-projected into the world frame, yielding a 3D point cluster. If the cluster matches an existing 3D object of the same semantic class, its points are merged into that object; otherwise the cluster seeds a new object. Association is scored by a composite of three geometric signals: volumetric overlap, containment, and centroid proximity. Planar structures (floor, wall, ceiling) are handled by a separate coplanarity rule. Finally, the world frame is gravity-aligned by detecting horizontal planar surfaces (floor, ceiling, table-top), fitting a normal vector to each via PCA, and voting on these normals to recover the vertical direction. The resulting Z-axis alignment is a prerequisite for horizontal direction labels in downstream direction- and editing-related tasks. The filtered object pool is then consumed by the question generator (Section 3), together with pairwise object distances and Z-buffer-based cross-view visibility primitives: distance bins for L1, L3, and L4, and visibility flips for L5.

	Group I		Group II		Group III		Overall
	L1	L2	L3a	L3b	L4	L5	Overall
Gemini-3.1-Pro	58.0	28.3	31.3	18.3	36.9	40.2	**34.6**
Qwen3.6-Plus	33.7	37.8	22.2	20.0	35.6	37.6	**31.1**
Doubao-Seed-2.0-Pro	29.4	40.2	11.6	5.0	27.9	38.5	**25.4**
Claude-Opus-4.6	39.8	20.9	12.8	10.5	28.4	24.7	**22.2**
Qwen3-VL-32B	41.5	21.1	10.2	7.4	15.3	23.7	**19.0**
GPT-5.4	37.0	20.4	9.8	8.2	15.3	17.2	**17.3**
Qwen3.5-35B-A3B	39.3	15.3	9.5	5.5	20.0	16.4	**16.9**
SenseNova-Qwen3VL-8B	31.1	15.0	13.2	9.7	18.6	12.4	**16.2**
Kimi-K2.5	23.7	25.0	3.8	2.9	19.4	21.5	**15.9**
VST-7B-SFT	20.0	19.4	15.0	12.0	15.3	7.7	**14.8**
InternVL3-8B	27.4	7.8	6.6	5.1	18.6	12.4	**12.5**
RoboBrain2.5-8B	22.2	13.9	6.6	2.3	17.5	11.8	**12.1**
SenseNova-InternVL3-8B	6.8	14.4	13.2	11.4	13.1	9.5	**11.6**
Qwen3-VL-8B	25.9	8.9	7.2	2.3	15.8	10.1	**11.2**
GLM-4.6V-Flash	22.5	11.1	4.0	3.5	3.5	12.4	**9.0**
Mean	**30.6**	**20.0**	**11.8**	**8.3**	**20.1**	**19.7**	**18.0**

Figure 3: Per-model accuracy scoreboard across six task types. Rows are 15 VLMs ranked by overall accuracy; cells show accuracy (%) and the same quantity is encoded by colour. The rightmost column shows each model's pooled overall score over all examples, while the bottom row shows the per-task mean across models. L1 is the only task with a clear signal for top models, whereas L3b remains close to chance across the board.

4.2 End-to-End Pipeline Validity

Of 1,172 candidate questions produced by the pipeline, 758 (64.7%) are *direct pass*: both the question stem and the geometry-derived answer key after language refinement were independently verified as correct. 245 (20.9%) are *answer-fixed*: the stem was unambiguous but the answer key was corrected by annotators (typically a wrong direction or distance bin). The remaining 169 (14.4%) are *rejected* due to referent-ambiguous stems. The 1,003-question benchmark reported in Section 5 combines the direct-pass and answer-fixed subsets; the per-task breakdown is reported in Appendix D. This audit indicates that the combination of structured answer design (Section 3.2) and question-generation filters, including direction sweet zones and distance-bin margins (Appendix C), supports benchmark construction under the residual noise of our feed-forward pipeline.

5 Experiments

5.1 Setup

Main evaluation. To establish where current VLMs stand on object-level counterfactual spatial reasoning, we evaluate 15 VLMs on all 1,003 questions ($\approx$ 170 per task) in a zero-shot setting, with three runs each. The API tier (6 models) comprises GPT-5.4 (OpenAI, 2026), Gemini-3.1-Pro-Preview (Google DeepMind, 2026), Claude-Opus-4-6 (Anthropic, 2026), Doubao-Seed-2.0-Pro (ByteDance Seed, 2026), Qwen3.6-Plus (Qwen Team, 2026b), and Kimi-K2.5 (Kimi Team, 2026); the open-source tier (9 models) comprises Qwen3-VL series at 8B / 32B (Qwen Team, Alibaba, 2025), InternVL3-8B (Zhu et al., 2025), SenseNova-SI-1.1 (Cai et al., 2025a) (two variants on Qwen and InternVL backbones), RoboBrain2.5 (Tan et al., 2026), VST-7B-SFT (Yang et al., 2025b), GLM-4.6V-Flash (Z.ai, 2025), and Qwen3.5-35B-A3B (Qwen Team, 2026a). We score only the final answer letter. Because option counts vary (8–24) across task types, the per-task random-guess baseline (4–13%) is shown alongside every result for interpretation. Full evaluation settings and prompts are provided in Appendix E.

Human baseline. To estimate human performance under the same input-and-choice format, three human annotators independently answered all 1,003 questions, seeing the same three images and answer choices as the models. Krippendorff's

Figure 4: Task-level human–SOTA gaps. Coloured segments show the gap from the best model to human majority vote; random chance and the 15-model mean are shown as context.

Table 2: Human vs. best VLM by task. The All row is pooled over all 1,003 examples, not the unweighted macro-average of task rows. Acc. %, gaps pp.

Task	Human	SOTA	Gap
L1	97.0	58.0	+39.0
L2	91.1	40.2	+50.9
L3a	88.0	31.3	+56.7
L3b	85.7	20.0	+65.7
L4	80.8	36.9	+43.9
L5	87.0	40.2	+46.8
All	**87.9**	**34.6**	**+53.3**

Table 3: Answer permutation. Acc. %, deltas pp.

Model	Main	Perm.	Δ_{all}	max Δ_{task}
Gemini-3.1-pro	34.6	34.7	0.1	5.0 (L3b)
Qwen3-VL-32B	19.0	20.4	1.4	6.9 (L2)
SenseNova-Q3VL	16.2	16.1	0.1	6.4 (L1)

$\alpha = 0.82$ (nominal, overall) indicates substantial inter-annotator agreement; we use majority vote as the human label.

Answer permutation. To verify that model answers are not driven by letter position, we shuffle the option-letter ordering and re-evaluate Gemini-3.1-Pro-Preview, Qwen3-VL-32B, and SenseNova-SI-1.1-Qwen3-VL-8B three times each.

Chain-of-thought prompting. We further probe four representative models (Gemini-3.1-Pro-Preview, GPT-5.4, Qwen3-VL-32B, Doubao-Seed-2.0-Pro) with explicit chain-of-thought prompting to test whether the human–VLM gap reflects an elicitation deficit; full results are in Appendix G.

5.2 Results

Main results. All six tasks remain substantially below human accuracy: the strongest VLM, Gemini-3.1-Pro-Preview, achieves only 34.6% pooled overall accuracy over all 1,003 questions, far below the 87.9% human majority vote. As a check against possible Gemini-related prompt-style bias, the best non-Gemini overall model, Qwen3.6-Plus, reaches only 31.1% pooled overall accuracy, still 56.8 pp below the human majority vote. Figure 3 shows per-model per-task accuracy across all 15 VLMs (full matrix of run means in Table 5, Appendix F); Figure 4 summarises the task-level random baseline, VLM mean, best VLM, and human majority-vote accuracy on a shared scale. We report per-task gaps to the random baseline rather than cross-task ordering, as the benchmark is not designed to support a difficulty ranking across task

types with non-uniform option structure.

Human baseline. As shown in Figure 4 and Table 2, per-task majority-vote accuracy ranges from 80.8% to 97.0%, confirming that all six tasks are solvable by humans. The human-vs-SOTA gap, however, is at least 39 pp on every task, with a pooled overall gap of 53.3 pp, exposing a substantial VLM-vs-human capability gap that cannot be attributed to task infeasibility.

Answer permutation. Table 3 shows that, at the overall-accuracy level, the difference between the main run and three option-letter shuffles stays within 1.4 pp on all three probed models; at the task level, the largest fluctuation reaches only 6.9 pp (Qwen3-VL-32B on L2; full per-task breakdown and visualization in Table 7 and Figure 7, Appendix H). This indicates that, for the probed models, overall accuracy is not primarily driven by answer-letter position.

5.3 Analysis

Depth-axis weakness. Beyond aggregate accuracy, the structured answer grid allows us to attribute model errors to specific spatial dimensions without chain-of-thought analysis. On L4 spatial editing, predictions binned by the eight compass directions show a clear depth-axis weakness: pure-depth answers (*far* at $0°$ and *near* at $180°$) reach only 7.4% accuracy, compared with 18.0% for pure-lateral answers (*left* and *right*) and 24.3% for mixed diagonals. This gives pure-depth answers a -10.6 pp gap relative to pure-lateral answers. The same pattern appears across tasks: L3a single-

view perspective transformation shows a $-5.5\,\mathrm{pp}$ depth-vs-lateral gap, and L2 camera motion shows a $-9.6\,\mathrm{pp}$ gap when translation is decomposed into forward/backward depth versus left/right lateral movement (29.4% vs. 39.0%).

When the direction is wrong, errors tend to be local rather than reversed. On L4, wrong-direction predictions cluster in the adjacent $45°$ compass bin at $1.7\times$ the random rate, whereas $180°$ reversals occur at only $0.6\times$ the random rate. This suggests that models often localize the answer to an approximate region but rarely flip it outright. The asymmetry is unlikely to be an artifact of the direction-bin design: each L3 and L4 question describes the eight directions as $45°$-wide sectors, while ground-truth selection applies the same $\pm10°$ sweet zone around every direction; angles outside all sweet zones are excluded during question generation.

Taken together, these observations indicate that current VLMs maintain a coarse, compass-style region sense but struggle to make reliable predictions along the camera depth axis. This pattern is consistent with the hypothesis that 2D-dominant visual pretraining makes image-plane position more directly accessible than camera-depth geometry.

Operation difficulty and fallback behavior. On counterfactual editing tasks, model accuracy decreases as the required edit becomes more complex. On L4, translation operations, which require only fixed-axis displacement, reach 21.8% accuracy, while pivot rotations, which require angular re-derivation, drop to 13.5%, a $-8.3\,\mathrm{pp}$ gap. The same translation-vs-rotation pattern appears on L5: 16.5% for translation versus 8.2% for rotation, again a $-8.3\,\mathrm{pp}$ gap. Within each task, translation and rotation cases share the same answer format and evaluation protocol, suggesting that the gap reflects the additional spatial transformation required by rotation rather than option-count differences.

L5 further exposes a fallback failure mode. Since the task combines object editing, cross-view projection, and occlusion reasoning, weaker models often over-select "none of the above": SenseNova-SI-1.1-Qwen3-VL-8B selects it 95.1% of the time, InternVL3-8B 88.3%, and Qwen3-VL-8B 73.0%, far above the 14.2% ground-truth frequency. This over-selection is not due to answer-letter position, as it persists under answer permutation (Section 5.2); full rates are in Appendix I.

Together, these patterns indicate difficulty-sensitive behavior: easier edit cases yield higher accuracy from the same models, while structurally demanding visibility-editing cases elicit fallback responses from models that fail to resolve the required edit-and-project reasoning.

6 Conclusion

MindEdit-Bench evaluates object-level counterfactual spatial reasoning in VLMs from casually captured smartphone photos, introducing L4 spatial editing and L5 cross-view visibility editing whose answers are absent from all input images. Built with a feed-forward object-centric 3D scene-graph extraction pipeline and structured answer choices, it enables low-cost benchmark construction and letter-level diagnosis of spatial and fallback errors. Across 15 VLMs and 1,003 human-verified questions, current models remain far below human performance and show structured failures along the camera depth axis and on demanding cross-view visibility edits. An anonymous code repository accompanying this submission is available at `https://anonymous.4open.science/r/MindEdit-Bench-4AE7/`; the benchmark questions will be released under the CC BY 4.0 license upon paper acceptance.

Limitations

L4 and L5 questions are filtered at generation to exclude ambiguous angles, near-boundary distances, and operations with marginal visibility change; this raises aggregate L4/L5 accuracies above what task difficulty alone would predict, although within-task comparisons remain informative about relative model behavior. Our feed-forward scene-graph extraction pipeline (DA3, SAM3, incremental fusion) is less precise than per-scene methods such as 3D Gaussian Splatting, trading precision for low cost; residual error is mitigated by the same filters and by human audit. For some weaker models, single-run accuracy is noisy; we report the mean over three runs, but fine-grained rankings between low-stability models should be interpreted with caution. Finally, Gemini-3.1-Pro is used for object-vocabulary construction and description refinement in our data pipeline while Gemini-3.1-Pro-Preview is also evaluated; although answer keys derive from geometry and human audit, this may introduce prompt-style familiarity, so we additionally report the best non-Gemini overall result (Section 5.2); the human–VLM gap remains large after excluding Gemini.

References

Anthropic. 2026. System card: Claude Opus 4.6. Technical report, Anthropic.

Peter W. Battaglia, Jessica B. Hamrick, and Joshua B. Tenenbaum. 2013. Simulation as an engine of physical scene understanding. *Proceedings of the National Academy of Sciences (PNAS)*, 110(45):18327–18332.

ByteDance Seed. 2026. Seed2.0 model card.

Zhongang Cai, Ruisi Wang, Chenyang Gu, Fanyi Pu, Junxiang Xu, Yubo Wang, Wanqi Yin, Zhitao Yang, Chen Wei, Qingping Sun, Tongxi Zhou, Jiaqi Li, Hui En Pang, Oscar Qian, Yukun Wei, Zhiqian Lin, Xuanke Shi, Kewang Deng, Xiaoyang Han, and 10 others. 2025a. Scaling spatial intelligence with multimodal foundation models. *arXiv preprint arXiv:2511.13719*.

Zhongang Cai, Yubo Wang, Qingping Sun, Ruisi Wang, Chenyang Gu, Wanqi Yin, Zhiqian Lin, Zhitao Yang, Chen Wei, Oscar Qian, Hui En Pang, Xuanke Shi, Kewang Deng, Xiaoyang Han, Zukai Chen, Jiaqi Li, Xiangyu Fan, Hanming Deng, Lewei Lu, and 5 others. 2025b. Holistic evaluation of multimodal LLMs on spatial intelligence. *arXiv preprint arXiv:2508.13142*.

Nicolas Carion, Laura Gustafson, Yuan-Ting Hu, Shoubhik Debnath, Ronghang Hu, Didac Suris, Chaitanya Ryali, Kalyan Vasudev Alwala, Haitham Khedr, Andrew Huang, Jie Lei, Tengyu Ma, Baishan Guo, Arpit Kalla, Markus Marks, Joseph Greer, Meng Wang, Peize Sun, Roman Rädle, and 19 others. 2025. SAM 3: Segment anything with concepts. *arXiv preprint arXiv:2511.16719*.

Boyuan Chen, Zhuo Xu, Sean Kirmani, Brian Ichter, Dorsa Sadigh, Leonidas Guibas, and Fei Xia. 2024. SpatialVLM: Endowing vision-language models with spatial reasoning capabilities. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*.

An-Chieh Cheng, Hongxu Yin, Yang Fu, Qiushan Guo, Ruihan Yang, Jan Kautz, Xiaolong Wang, and Sifei Liu. 2024. SpatialRGPT: Grounded spatial reasoning in vision language models. In *Advances in Neural Information Processing Systems (NeurIPS)*.

Angela Dai, Angel X. Chang, Manolis Savva, Maciej Halber, Thomas Funkhouser, and Matthias Nießner. 2017. ScanNet: Richly-annotated 3d reconstructions of indoor scenes. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*.

Yuanyuan Gao, Hao Li, Yifei Liu, Xinhao Ji, Yuning Gong, Yuanjun Liao, Fangfu Liu, Manyuan Zhang, Yuchen Yang, Dan Xu, Xue Yang, Huaxi Huang, Hongjie Zhang, Ziwei Liu, Xiao Sun, Dingwen Zhang, and Zhihang Zhong. 2026. Holi-Spatial: Evolving video streams into holistic 3d spatial intelligence. *arXiv preprint arXiv:2603.07660*.

Tobias Gerstenberg. 2024. Counterfactual simulation in causal cognition. *Trends in Cognitive Sciences*, 28(10):924–936.

Google DeepMind. 2026. Gemini 3.1 Pro model card. Technical report, Google DeepMind.

Mary Hegarty. 2004. Mechanical reasoning by mental simulation. *Trends in Cognitive Sciences*, 8(6):280–285.

Philip N. Johnson-Laird. 1983. *Mental Models: Towards a Cognitive Science of Language, Inference, and Consciousness*. Harvard University Press.

Kimi Team. 2026. Kimi K2.5: Visual agentic intelligence. *arXiv preprint arXiv:2602.02276*.

Dingming Li, Hongxing Li, Zixuan Wang, Yuchen Yan, Hang Zhang, Siqi Chen, Guiyang Hou, Shengpei Jiang, Wenqi Zhang, Yongliang Shen, Weiming Lu, and Yueting Zhuang. 2025. ViewSpatial-Bench: Evaluating multi-perspective spatial localization in vision-language models. *arXiv preprint arXiv:2505.21500*.

Haotong Lin, Sili Chen, Junhao Liew, Donny Y. Chen, Zhenyu Li, Guang Shi, Jiashi Feng, and Bingyi Kang. 2025. Depth anything 3: Recovering the visual space from any views. *arXiv preprint arXiv:2511.10647*.

Xiaojian Ma, Silong Yong, Zilong Zheng, Qing Li, Yitao Liang, Song-Chun Zhu, and Siyuan Huang. 2023. SQA3D: Situated question answering in 3d scenes. In *International Conference on Learning Representations (ICLR)*.

OpenAI. 2026. GPT-5.4 thinking system card.

Qwen Team. 2026a. Qwen3.5-35B-A3B model card.

Qwen Team. 2026b. Qwen3.6-Plus: Towards real world agents.

Qwen Team, Alibaba. 2025. Qwen3-VL technical report. *arXiv preprint arXiv:2511.21631*.

Roger N. Shepard and Jacqueline Metzler. 1971. Mental rotation of three-dimensional objects. *Science*, 171(3972):701–703.

Huajie Tan, Enshen Zhou, Zhiyu Li, Yijie Xu, Yuheng Ji, Xiansheng Chen, Cheng Chi, Pengwei Wang, Huizhu Jia, Yulong Ao, Mingyu Cao, Sixiang Chen, Zhe Li, Mengzhen Liu, Zixiao Wang, Shanyu Rong, Yaoxu Lyu, Zhongxia Zhao, Peterson Co, and 16 others. 2026. RoboBrain 2.5: Depth in sight, time in mind. *arXiv preprint arXiv:2601.14352*.

Barbara Tversky. 1993. Cognitive maps, cognitive collages, and spatial mental models. In *European Conference on Spatial Information Theory (COSIT)*, pages 14–24.

Jiayu Wang, Yifei Ming, Zhenmei Shi, Vibhav Vineet, Xin Wang, Yixuan Li, and Neel Joshi. 2024. Is a picture worth a thousand words? delving into spatial reasoning for vision language models. In *Advances in Neural Information Processing Systems (NeurIPS)*.

Qineng Wang, Baiqiao Yin, Pingyue Zhang, Jianshu Zhang, Kangrui Wang, Zihan Wang, Jieyu Zhang, Keshigeyan Chandrasegaran, Han Liu, Ranjay Krishna, Saining Xie, Jiajun Wu, Li Fei-Fei, and Manling Li. 2025. MindCube: Spatial mental modeling from limited views. *arXiv preprint arXiv:2506.21458*.

Haoning Wu, Xiao Huang, Yaohui Chen, Ya Zhang, Yanfeng Wang, and Weidi Xie. 2025. SpatialScore: Towards comprehensive evaluation for spatial intelligence. *arXiv preprint arXiv:2505.17012*.

Yicheng Xiao, Wenhu Zhang, Lin Song, Yukang Chen, Wenbo Li, Nan Jiang, Tianhe Ren, Haokun Lin, Wei Huang, Haoyang Huang, Xiu Li, Nan Duan, and Xiaojuan Qi. 2026. SpatialEdit: Benchmarking fine-grained image spatial editing. *arXiv preprint arXiv:2604.04911*.

Yuxi Xiao, Longfei Li, Shen Yan, Xinhang Liu, Sida Peng, Yunchao Wei, Xiaowei Zhou, and Bingyi Kang. 2025. SpatialTree: How spatial abilities branch out in MLLMs. *arXiv preprint arXiv:2512.20617*.

Jihan Yang, Shusheng Yang, Anjali W. Gupta, Rilyn Han, Li Fei-Fei, and Saining Xie. 2025a. Thinking in space: How multimodal large language models see, remember, and recall spaces. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*.

Rui Yang, Ziyu Zhu, Yanwei Li, Jingjia Huang, Shen Yan, Siyuan Zhou, Zhe Liu, Xiangtai Li, Shuangye Li, Wenqian Wang, Yi Lin, and Hengshuang Zhao. 2025b. Visual spatial tuning. *arXiv preprint arXiv:2511.05491*.

Sihan Yang, Runsen Xu, Yiman Xie, Sizhe Yang, Mo Li, Jingli Lin, Chenming Zhu, Xiaochen Chen, Haodong Duan, Xiangyu Yue, Dahua Lin, Tai Wang, and Jiangmiao Pang. 2025c. MMSI-Bench: A benchmark for multi-image spatial intelligence. *arXiv preprint arXiv:2505.23764*.

Z.ai. 2025. GLM-4.6V-Flash model card.

Jinguo Zhu, Weiyun Wang, Zhe Chen, Zhaoyang Liu, Shenglong Ye, Lixin Gu, Hao Tian, Yuchen Duan, Weijie Su, Jie Shao, Zhangwei Gao, Erfei Cui, Xuehui Wang, Yue Cao, Yangzhou Liu, Xingguang Wei, Hongjie Zhang, Haomin Wang, Weiye Xu, and 32 others. 2025. InternVL3: Exploring advanced training and test-time recipes for open-source multimodal models. *arXiv preprint arXiv:2504.10479*.

A Task Examples

Figures 5 and 6 show one representative example per task type (L1–L5), including the input photos, the question stem, the full option list, and the ground-truth answer.

B 3D Scene-Graph Extraction Pipeline

Hyperparameters of the input-photo protocol (Section 4) and the two scene-reconstruction stages (Section 4.1) are detailed below.

Input photos. Each scene is captured as three handheld smartphone photos taken with sufficient pairwise view overlap to support cross-view 3D association (Section 4.1, Stage 2) while preserving enough viewpoint diversity for the perspective-transformation and cross-view visibility tasks. All scenes were privately captured by the authors and were not part of any public dataset before evaluation.

Stage 1 · Per-view 2D perception. DA3 (Lin et al., 2025) recovers per-view metric depth together with camera intrinsics and extrinsics in a single forward pass per photo. SAM3 (Carion et al., 2025) is prompted with the Stage-1 LLM vocabulary; within-class non-maximum suppression merges masks with IoU > 0.5 or containment > 0.7, while across-class masks are never merged regardless of overlap.

Stage 2 · Cross-view 3D object association. Per-view clusters are associated to existing 3D objects by the composite score $s = 0.4 \cdot \text{IoU}_{3D} + 0.4 \cdot \text{Containment} + 0.2 \cdot \text{CenterProximity}$ with acceptance $s \geq 0.35$ and hard floor $\text{IoU}_{3D} \geq 0.05$; weights were chosen on a held-out scene set. Planar structures use a coplanarity rule (normal-angle tolerance $< 10°$, plane-distance tolerance $< 0.15\,\text{m}$) in place of volumetric overlap. Gravity is estimated by PCA multi-plane voting over floor, ceiling, and table-top surfaces, with ceiling-above-floor disambiguation and wall-normal consistency checks; world coordinates are then rotated so the Z-axis aligns with gravity.

Rendered artefacts. Point-cloud PLYs with 3D bounding boxes and camera frusta, together with 2D bounding-box overlays on the input images, are produced for human sanity-checking during dataset curation (Section 4.2). These are not consumed by the automated question generator.

View1   View2   View3

L1 Closest Pair Distance

In view1, the TV on the left is visible; in view2, the ceiling light at the top is visible; in view2, the sofa at the bottom is visible; in view3, the nightstand on the right is visible. Which of the following options correctly describes the closest pair among these 4 objects and their distance? (Distance refers to the closest surface-to-surface distance between the two objects.)

A. The sofa and the nightstand are the closest pair, about 2-3 m apart.
B. The ceiling light and the nightstand are the closest pair, about 3-5 m apart.
C. The ceiling light and the nightstand are the closest pair, more than 5 m apart.
D. The TV and the sofa are the closest pair, about 3-5 m apart.
E. The TV and the nightstand are the closest pair, about 2-3 m apart.
F. The TV and the sofa are the closest pair, about 0.5-1 m apart.
G. The TV and the ceiling light are the closest pair, about 2-3 m apart.
H. The sofa and the nightstand are the closest pair, about 3-5 m apart.
I. The sofa and the nightstand are the closest pair, more than 5 m apart.
J. The ceiling light and the sofa are the closest pair, about 3-5 m apart.
K. The TV and the ceiling light are the closest pair, about 3-5 m apart.
L. The TV and the sofa are the closest pair, about 1-2 m apart.
M. The ceiling light and the sofa are the closest pair, about 1-2 m apart.
N. The TV and the nightstand are the closest pair, more than 5 m apart.

L2 Camera Motion

From view1 to view2, what motion did the camera undergo? (Translation directions are referenced to view1: "forward" = away from view1's camera, "right" = to the right of view1's frame. For rotation, identify only the dominant rotation direction.)

A. Moves backward and turns left
B. Moves backward and turns right
C. Moves right and turns left
D. Moves right and tilts up
E. Moves forward and tilts down
F. Moves forward and tilts up
G. Moves right and turns right
H. Moves left and turns left
I. Moves forward and turns left
J. Moves forward with little rotation
K. Moves right and tilts down
L. Moves left and tilts down
M. Moves right with little rotation
N. Moves backward and tilts up
O. Moves forward and turns right

L3a Single-View Perspective Taking

In view1, the TV on the left, the ceiling light at the top, and the sofa at the lower-right are visible. Imagine you are standing at the sofa's position and facing the TV. In which direction is the ceiling light from you, and how far away is it? (Direction is determined by projecting the line between the two objects' centers onto the horizontal plane, partitioned into 8 sectors of 45° each; distance is the closest surface-to-surface distance between the two objects.)

A. Front-right, about 2-3 m
B. Directly behind, more than 5 m
C. Directly behind, about 2-3 m
D. Back-right, more than 5 m
E. Back-right, about 3-5 m
F. Directly behind, about 1-2 m
G. Directly to the right, about 2-3 m
H. Back-left, about 2-3 m
I. Directly to the left, more than 5 m
J. Directly to the right, about 3-5 m
K. Directly in front, about 3-5 m
L. Back-left, about 0.5-1 m
M. Back-right, about 0.5-1 m
N. Directly to the left, about 1-2 m
O. Directly in front, about 0.5-1 m
P. Front-left, about 1-2 m
Q. Back-left, about 3-5 m
R. Front-left, about 3-5 m
S. Front-left, about 0.5-1 m
T. Directly in front, about 1-2 m
U. Directly to the left, about 0.5-1 m
V. Front-right, about 3-5 m
W. Directly to the right, about 1-2 m
X. Front-right, about 0.5-1 m

L3b Cross-View Perspective Taking

In view1, the TV on the left is visible; in view2, the ceiling light at the top is visible; in view3, the nightstand on the right is visible. Imagine you are standing at the TV's position and facing the ceiling light. In which direction is the nightstand from you, and how far away is it? (Direction is determined by projecting the line between the two objects' centers onto the horizontal plane, partitioned into 8 sectors of 45° each; distance is the closest surface-to-surface distance between the two objects.)

A. Directly behind, about 1-2 m
B. Back-right, about 3-5 m
C. Directly to the left, about 2-3 m
D. Back-left, more than 5 m
E. Directly to the left, about 3-5 m
F. Directly in front, about 2-3 m
G. Back-right, about 0.5-1 m
H. Back-right, about 1-2 m
I. Front-right, about 1-2 m
J. Directly behind, about 3-5 m
K. Directly to the right, about 0.5-1 m
L. Directly in front, more than 5 m
M. Front-left, more than 5 m
N. Front-left, about 1-2 m
O. Directly to the right, more than 5 m
P. Directly in front, about 3-5 m
Q. Directly to the right, about 1-2 m
R. Back-left, about 2-3 m
S. Directly to the left, about 0.5-1 m
T. Front-right, about 3-5 m
U. Front-right, more than 5 m
V. Back-left, about 3-5 m
W. Directly behind, about 0.5-1 m
X. Front-left, about 2-3 m

Figure 5: Representative examples for the four perception and perspective-transformation tasks (L1–L3b). Each panel shows the input photos, the question stem, the full option list, and the ground-truth answer.

Figure 6: Representative examples for the two counterfactual editing tasks (L4 and L5). Same panel layout as Figure 5.

C Question Generation

The question generator consumes geometric primitives derived from the reconstructed scene graph (Appendix B). We detail the geometric primitives, the per-scene object pool, the per-task generation algorithms, shared parameters, and the LLM-based refinement step below.

Geometric primitives. Per-object point clouds are voxel-downsampled at $2\,\mathrm{cm}$. Pairwise surface distance: for each object pair (A, B), a cKDTree is built on B's points; every point of A is queried against B and the resulting nearest-neighbour distances are sorted ascending; we take the mean of the 5th–10th percentile slice (skipping the closest 5% to avoid noise from overlapping points and the tail to avoid far-field noise). Cross-view visibility: Z-buffer rendering of all other objects against the projected points of the edited object gives a visibility ratio, and an edit is labelled *visible* when vis_ratio > 0.50, *invisible* when < 0.15, and discarded otherwise.

Object pool construction. Before any question is generated, we apply the object filter from Stage 1 (bbox edge 0.05–0.80 m, SAM3 confidence ≥ 0.5, plus a category exclude list to skip large fixed furniture and certain non-rigid items; details in the released code) to obtain a per-scene object pool. The pipeline does not aim to recover every object; the filter trades coverage for question-grade reliability.

Per-task generation algorithms. L1: Cross-View Object Relations. From the object pool, enumerate all object pairs (A, B) that appear in at least one shared view, compute pairwise surface distance via the cKDTree-based percentile estimator. The ground-truth pair has the smallest distance. Distractor pairs are sampled with stratified distance bins: $\lceil k/2 \rceil$ pairs from the second-smallest bin, $\lfloor k/2 \rfloor$ from larger bins, for 10–12 options total.

L2: Camera Motion. From per-view DA3 outputs (K_i, R_i, t_i), we compute the relative pose between two photos. Translation is decomposed into source-camera right / up / forward axes; rotation into yaw and pitch. Each axis is discretised: $|t_{\mathrm{axis}}| < 0.2\,\mathrm{m} \rightarrow$ *negligible*; otherwise sign-classified into the directional label. Rotation thresholds: $|\theta| < 10° \rightarrow$ *negligible*. The GT is the (translation, rotation) tuple; distractors are alternative tuples randomly subsampled to 12–15 options.

L3a: Single-View Perspective Transformation. Per scene, pick objects (A, B, C) visible in the same view with pairwise separation $\geq 0.5\,\mathrm{m}$. Construct a new frame: origin at A, forward along $A \rightarrow B$ (projected onto the gravity-horizontal plane). Compute C's position in the new frame, then discretise it into 8 horizontal direction bins and 5 distance bins (0.5–1 m, 1–2 m, 2–3 m, 3–5 m, and more than 5 m). The GT is the resulting (direction, distance) bin. Distractors are sampled from

the remaining direction–distance grid cells, yielding 8–24 options depending on filter strictness and valid distractor availability.

L3b: Cross-View Perspective Transformation. Same as L3a, but A and C must appear in different views; Stage 2 association supplies their cross-view-consistent positions.

L4: Spatial Editing. Per scene, pick (A, B, C) from the object pool with $A \neq C$ and pairwise separation thresholds. Pick an operation: *translate* (along 4 camera-frame horizontals, distance $d = \max(0.5 \cdot d_{AC}, 0.20\,\mathrm{m})$) or *rotate* (around B's vertical axis by $\{90, 180, 270\}°$). Apply the edit to A, recompute its position relative to C, then bin into (8 direction $\times$ 5 distance). The GT must pass the sweet-zone filter ($\pm 10°$ in direction; $\geq 0.15\,\mathrm{m}$ from any distance-bin boundary). Distractors are sampled from the remaining 39 grid cells, total 15 options.

L5: Cross-View Visibility Editing. For each scene-pair (source, target), pick A visible in the source and a set of candidate operations (translations at $\{0.5, 1.0, 1.5, 2.0\}$ m along 5 directions; rotations around qualifying reference objects at $\{90, 180, 270\}°$). For each operation, apply it to A and compute A's vis_ratio in the target view via Z-buffer rendering against all other objects. Label *visible* (vis_ratio > 0.50), *invisible* (< 0.15), or undefined. The GT operation flips visibility (appear: invisible $\rightarrow$ visible; disappear: visible in both $\rightarrow$ invisible). Distractors are operations that do not flip visibility; a "none of the above" option may be the correct answer.

Question-generation parameter summary. L4 translation distance $d = \max(0.5 \cdot d_{AC}, 0.20\,\mathrm{m})$; L4 rotation angles $\{90°, 180°, 270°\}$ around B's vertical axis. Direction sweet zones: $\pm 10°$ around each of 8 compass directions, with $25°$ dead zones between adjacent directions discarded. Distance bin margin: ground-truth distances within $0.15\,\mathrm{m}$ of any bin boundary are discarded. Candidate-object size filter: minimum edge $0.05\,\mathrm{m}$, maximum edge $0.80\,\mathrm{m}$. SAM3 confidence threshold: ≥ 0.5. Scene-clutter filter: scenes with more than 15 visible non-structural objects per view are discarded wholesale.

LLM-based question refinement. Raw questions produced by Section 3 contain object identifiers of the form "obj_5 (lamp)". We use Gemini 3.1 Pro to replace each identifier with a natural-language description grounded in visual appearance and position (e.g., "the red lamp on the left side of the second image"). The LLM receives the three input photos along with object bounding-box coordinates and a nine-cell grid position label. The refinement prompt strictly forbids rewriting, abbreviation, or reorganisation of the question text; only identifier substitution is allowed, preventing semantic drift.

D Human Audit Protocol and Statistics

All 1,172 candidate questions were reviewed by multiple annotators against a written protocol. Each question underwent a two-round audit. In the first round, an annotator performed both a stem audit (verifying that the question stem is unambiguous) and an answer-key audit (verifying that the LLM-refined answer is correct), producing one of three outcomes: **direct pass** (stem and answer key both correct, no editing needed); **answer-fixed** (stem correct, answer key corrected by the annotator, typically a direction or distance error caused by pipeline-level geometric noise in the spatial-reasoning answer); or **rejected** (stem itself problematic, most commonly referent ambiguity when multiple visually similar objects co-appear in the same view, or a mis-labelled target object). In the second round, a different annotator independently re-checked the first-round outcome; disagreements were returned for re-review and the cycle iterated until both rounds agreed. Table 4 reports the per-task breakdown; the aggregate (758 direct + 245 answer-fixed + 169 rejected, also reported in Section 4.2) yields a direct-pass rate of 64.7% and a final acceptance rate of 85.6%. Direct-pass rates range from 54.3% (L1) to 72.0% (L3b), with the two counterfactual editing tasks (L4, L5) in the middle at 67.5% and 69.5%. Among candidates with valid stems, the LLM-refined answer is already correct in 75.6% of cases (per-task range 66.7%–82.3%).

Annotators. The audit reviews and the human-baseline responses were produced by annotators retained through a professional annotation service. The annotators are familiar with multiple-choice spatial-reasoning task formats. Each candidate question underwent at least two audit rounds (an initial review and a second-round confirmation, with disagreements returned for re-review until both rounds agree), and each human-baseline question was answered independently by three annotators whose responses are aggregated by major-

Table 4: Per-task pipeline-audit outcomes. **Cand.**: total candidates from the pipeline. **Direct**: stem and answer key both verified correct (no editing). **Fixed**: stem correct, answer key corrected by annotators. **Rejected**: stem ambiguous or mis-labelled. **Direct %** = Direct/Cand. **Final %** = (Direct + Fixed)/Cand., the fraction retained in the benchmark.

Task	Cand.	Direct	Fixed	Rejected	Direct %	Final %
L1 (Cross-View Obj Rel)	173	94	41	38	54.3	78.0
L2 (Camera Motion)	200	120	60	20	60.0	90.0
L3a (Single-View PT)	199	126	41	32	63.3	83.9
L3b (Cross-View PT)	200	144	31	25	72.0	87.5
L4 (Spatial Editing)	200	135	42	23	67.5	88.5
L5 (Cross-View Vis Edit)	200	139	30	31	69.5	84.5
Total	1,172	758	245	169	64.7	85.6

ity vote. Both tasks followed formal written instructions; the verbatim instructions for the audit decision criteria and for the human-baseline task will be released alongside the benchmark questions. Compensation was provided through the service per its standard rates for visual-reasoning annotation tasks; the authors do not have direct visibility into individual wage rates or the exact number of unique annotators retained by the service. The annotation deliverables may be released together with the MindEdit-Bench benchmark per the service agreement.

E   Evaluation Protocol

This appendix describes how we evaluate both API-served and local VLMs on MindEdit-Bench. All main results use the same 1,003 human-verified questions as Section 5. Each example contains the image paths, the natural-language question, a list of labelled multiple-choice options, and the verified answer letter.

Model interfaces. API models are queried through an OpenAI-compatible chat-completion interface. Local models are evaluated with vLLM offline inference using each model's chat template and local image-file inputs. The evaluation runner uses the same message construction and answer extraction logic for both tiers; the main difference is that API requests encode images as data URLs, whereas local vLLM runs pass file URLs to the offline engine.

Decoding and repetition. All models are evaluated with greedy decoding (`temperature=0`) and a maximum generation budget of 2,048 tokens. For API models, requests use `image_detail=auto`, concurrency 5, a 300-second timeout, and up to three retries with exponential backoff. For lo-

cal models, vLLM uses the model-specific tensor-parallel and context-length settings in the released configuration files, with the same `temperature=0` and 2,048-token generation budget. Every API and local model is run three times on the full benchmark. We report the arithmetic mean across the three runs as the model score and compute the sample standard deviation across runs for run-to-run stability analysis.

Prompt format. The user message contains the input images followed by one text block consisting of the question stem, a blank line, and the full option list. This corresponds to `content_order=images_first` and `no_images=false` for the main evaluation. The system prompts implemented in `src/eval/prompt.py` are listed below. Only `SYSTEM_PROMPT` is used for the main benchmark; `SYSTEM_PROMPT_COT` supports diagnostic or supplemental experiments.

System prompt.
`SYSTEM_PROMPT` is the standard multimodal answer-only evaluation prompt.

Listing 1: Standard multimodal answer-only system prompt.

```
You are a visual question answering assistant.
 Carefully inspect the images and answer the
multiple-choice question. The option letters
may range from A to X. Output only one
uppercase option letter, such as A. Do not
output reasoning, punctuation, option text, or
 any other words.
```

Multimodal chain-of-thought prompt.
`SYSTEM_PROMPT_COT` is the multimodal chain-of-thought diagnostic prompt.

Listing 2: Multimodal chain-of-thought system prompt.

```
You are a visual question answering assistant.
 Carefully observe the image and answer the
multiple-choice question. First, explain your
```

```
reasoning step by step, then output your final
 answer on a separate line in the format:
Answer: X (where X is the option letter).
```

Scoring and aggregation. For each model response, the evaluator extracts a final option letter in the range A–X. Exact matches to the verified answer are counted as correct; responses with no extractable option letter are counted as incorrect. Each completed run writes per-example predictions and raw responses to `predictions.jsonl`, run-level metrics to `metrics.json`, and one row in the experiment summary CSV. Aggregation scripts group rows by model and compute per-task and overall mean accuracy plus standard deviation across the three runs.

Compute. Local-model inference is performed on a single workstation with $2\times$ NVIDIA A100 GPUs; the full evaluation of the nine open-source models (three runs each on the 1,003-question benchmark) takes approximately 24 GPU-hours in total. API-model evaluation cost is approximately USD 400 in aggregate across the six providers.

F Per-Model Per-Task Results

Table 5 reports per-model, per-task accuracy across all 15 evaluated VLMs.

G Chain-of-Thought Prompting Analysis

We probe whether explicit chain-of-thought (CoT) prompting closes the human-VLM gap by appending a step-by-step reasoning instruction to the standard prompt and evaluating four representative models—Gemini-3.1-Pro-Preview, GPT-5.4, Qwen3-VL-32B, and Doubao-Seed-2.0-Pro—over three runs on all 1,003 benchmark questions, using the same aggregation methodology as Section 5. Full per-model per-task results are reported in Table 6.

CoT yields measurable but task-structure-dependent gains. Across the three models other than the GPT-5.4 outlier (discussed below), CoT improves Group II perspective transformation tasks (L3a, L3b) by an average of $+3.3$ pp and Group III counterfactual editing tasks (L4, L5) by $+3.7$ pp, while Group I perception tasks (L1, L2) gain only $+1.8$ pp. The pattern aligns with task structure: L3 decomposes into "mentally adopt the new viewpoint, then judge the spatial relation"; L4 into "apply the virtual transformation, then re-evaluate the

direction-distance"; L5 into "apply the transformation, project to the target view, then check visibility". CoT prompts that elicit explicit step-by-step reasoning map naturally onto these sequential operations, whereas Group I tasks involve more holistic visual comparison with less obvious decomposition.

CoT gains are heterogeneous across models. GPT-5.4 shows the largest CoT improvement ($+12.8$ pp overall); the other three models show modest gains of $+1.2$ pp (Gemini-3.1) to $+6.0$ pp (Qwen3-VL-32B). The small model sample precludes stronger model-level conclusions, and we leave further investigation of model-specific CoT responsiveness to future work.

CoT acts as an elicitation tool, not a capability fix. While individual models benefit from CoT, the benchmark-level SOTA rises only from 34.6% (Gemini baseline) to 35.8% (Gemini + CoT), a gain of just $+1.2$ pp. The pooled human-VLM gap remains at 52 pp; on L3b cross-view perspective transformation, the best CoT-augmented configuration reaches 30.1% versus human 85.7%. These results suggest that the dominant bottleneck for object-level counterfactual spatial reasoning is the capability to maintain and manipulate an internal 3D scene representation, not the elicitation of explicit reasoning steps.

H Answer Permutation: Per-Task Breakdown

Table 7 reports the per-task accuracy for each probed model under the original main run and the three option-letter shuffles (mean across the three shuffles), along with the absolute difference $|\Delta|$ between them. Per-task $|\Delta|$ reaches up to 6.9 pp (Qwen3-VL-32B on L2), 6.4 pp (SenseNova-SI-1.1-Qwen3-VL-8B on L1), and 5.0 pp (Gemini-3.1-Pro-Preview on L3b), while the pooled overall accuracy stays within 1.4 pp on all three models, indicating that per-task fluctuations average out into a position-independent overall signal.

I L5 Meta-Option Selection Rates per Model

Table 8 reports each model's selection rate for the L5 meta-option "none of the above" alongside its pooled overall accuracy over all benchmark examples. The L5 GT frequency for this option is 14.2%; the three weakest open-source models exceed it by a large margin (Qwen3-VL-8B,

Table 5: Per-model, per-task accuracy (%). Rows sorted by overall mean accuracy. L1 = Cross-View Object Relations; L2 = Camera Motion; L3a = Single-View PT; L3b = Cross-View PT; L4 = Spatial Editing; L5 = Cross-View Visibility Editing. Overall is the pooled accuracy over all 1,003 benchmark examples, using the final per-task example counts in Table 4. It is not the unweighted macro-average of the six task accuracies. The Mean row is the per-task arithmetic average across the 15 models above; this matches the per-task values reported in Section 5.2. Numbers are means across three runs per model; open-source models with non-stochastic decoding produce nearly identical runs.

Model	Type	L1	L2	L3a	L3b	L4	L5	Overall
Gemini-3.1-Pro-Preview	API	58.0	28.3	31.3	18.3	36.9	40.2	**34.6**
Qwen3.6-Plus	API	33.7	37.8	22.2	20.0	35.6	37.6	31.1
Doubao-Seed-2.0-Pro	API	29.4	40.2	11.6	5.0	27.9	38.5	25.4
Claude-Opus-4-6	API	39.8	20.9	12.8	10.5	28.4	24.7	22.2
Qwen3-VL-32B	Local	41.5	21.1	10.2	7.4	15.3	23.7	19.0
GPT-5.4	API	37.0	20.4	9.8	8.2	15.3	17.2	17.3
Qwen3.5-35B-A3B	Local	39.3	15.3	9.5	5.5	20.0	16.4	16.9
SenseNova-SI-1.1-Qwen3-VL-8B	Local	31.1	15.0	13.2	9.7	18.6	12.4	16.2
Kimi-K2.5	API	23.7	25.0	3.8	2.9	19.4	21.5	15.9
VST-7B-SFT	Local	20.0	19.4	15.0	12.0	15.3	7.7	14.8
InternVL3-8B	Local	27.4	7.8	6.6	5.1	18.6	12.4	12.5
RoboBrain2.5-8B	Local	22.2	13.9	6.6	2.3	17.5	11.8	12.1
SenseNova-SI-1.1-InternVL3-8B	Local	6.8	14.4	13.2	11.4	13.1	9.5	11.6
Qwen3-VL-8B	Local	25.9	8.9	7.2	2.3	15.8	10.1	11.2
GLM-4.6V-Flash	Local	22.5	11.1	4.0	3.5	3.5	12.4	9.0
Mean (all models)	—	30.6	20.0	11.8	8.3	20.1	19.7	18.0
Random baseline	—	~9	~7	~4	~6	6.7	~10	—

Table 6: Per-model accuracy (%) under baseline (no CoT) versus explicit chain-of-thought (+ CoT) prompting, by task. Δ rows show CoT minus baseline in percentage points.

Model	Setting	L1	L2	L3a	L3b	L4	L5	Overall
Gemini-3.1-Pro-Preview	Baseline	58.0	28.3	31.3	18.3	36.9	40.2	34.6
	+ CoT	56.0	28.0	32.5	30.1	36.7	36.1	35.8
	Δ	−2.0	−0.3	+1.2	+11.8	−0.2	−4.1	+1.2
Doubao-Seed-2.0-Pro	Baseline	29.4	40.2	11.6	5.0	27.9	38.5	25.4
	+ CoT	28.4	40.4	15.0	7.4	31.3	41.6	27.4
	Δ	−1.0	+0.2	+3.4	+2.4	+3.4	+3.1	+2.0
Qwen3-VL-32B	Baseline	41.5	21.1	10.2	7.4	15.3	23.7	19.0
	+ CoT	47.2	29.4	11.8	7.0	24.9	34.3	25.0
	Δ	+5.7	+8.3	+1.6	−0.4	+9.6	+10.6	+6.0
GPT-5.4	Baseline	37.0	20.4	9.8	8.2	15.3	17.2	17.3
	+ CoT	46.9	33.9	20.2	14.9	27.7	40.8	30.1
	Δ	+9.9	+13.5	+10.4	+6.7	+12.4	+23.6	+12.8

Table 7: Per-task answer-permutation breakdown for three probed models. "Main" = original main-run accuracy (%); "Perm" = mean accuracy across three option-letter shuffles (%); "|Δ|" = absolute difference between Main and Perm (pp).

Model	Row	L1	L2	L3a	L3b	L4	L5	Overall
Gemini-3.1-Pro-Preview	Main	58.0	28.3	31.3	18.3	36.9	40.2	34.6
	Perm	58.0	30.0	31.3	13.3	37.3	38.0	34.7
	|Δ|	0.0	1.7	0.0	5.0	0.4	2.2	0.1
Qwen3-VL-32B	Main	41.5	21.1	10.2	7.4	15.3	23.7	19.0
	Perm	38.7	28.0	11.3	7.3	12.0	25.3	20.4
	|Δ|	2.8	6.9	1.1	0.1	3.3	1.6	1.4
SenseNova-SI-1.1-Qwen3-VL-8B	Main	31.1	15.0	13.2	9.7	18.6	12.4	16.2
	Perm	24.7	20.0	14.0	6.7	13.3	18.0	16.1
	|Δ|	6.4	5.0	0.8	3.0	5.3	5.6	0.1

Figure 7: **Answer-permutation control.** Each panel shows task-level accuracy for three representative VLMs under the main run (rose stars and dashed guides) and three option-letter shuffles (blue points connected by range lines). Reordering option letters changes overall accuracy by at most 1.4 pp, while the largest task-level fluctuation is 6.9 pp.

InternVL3-8B, SenseNova-SI-1.1-Qwen3-VL-8B), while the strongest API models track it closely. RoboBrain2.5-8B selects this option 0% of the time, reflecting an opposite failure mode (refusal to use the fallback at all).

J Ethical Considerations

Data collection and privacy. The 120 indoor scenes that constitute MindEdit-Bench were privately captured by the authors using consumer smartphones, in spaces that the authors own or for which explicit photography consent was obtained from the space owner. We did not scrape any images from the web or repurpose third-party datasets. Each released image was manually screened during curation to exclude any frame containing human faces, identifying documents, screens displaying personal information, or other personally identifying material. No offensive content is present.

Intended use and misuse risks. MindEdit-Bench is intended for academic research on VLM spatial reasoning; broader use is permitted under the license in Section 6. The primary misuse risk is over-interpreting scores as evidence of deployment readiness for safety-relevant applications such

Table 8: L5 "none of the above" meta-option selection rate per model, alongside the model's overall accuracy across the six task types. Models are sorted by meta-option rate (descending). The GT frequency for this option is 14.2%. SenseNova-SI-Q3VL-8B and SenseNova-SI-IV3-8B abbreviate the SenseNova-SI-1.1 variants on Qwen3-VL-8B and InternVL3-8B respectively.

Model	Meta-opt %	Overall acc %
SenseNova-SI-Q3VL-8B	95.1	16.2
InternVL3-8B	88.3	12.5
Qwen3-VL-8B	73.0	11.2
Kimi-K2.5	68.9	15.9
Qwen3-VL-32B	44.8	19.0
SenseNova-SI-IV3-8B	30.1	11.6
Claude-Opus-4-6	18.6	22.2
Doubao-Seed-2.0-Pro	14.7	25.4
Gemini-3.1-Pro-Preview	14.5	34.6
VST-7B-SFT	12.9	14.8
GPT-5.4	11.3	17.3
GLM-4.6V-Flash	6.4	9.0
Qwen3.5-35B-A3B	6.3	16.9
Qwen3.6-Plus	1.8	31.1
RoboBrain2.5-8B	0.0	12.1

as assistive navigation or household robotics; the benchmark itself poses no direct dual-use risk.

Use of AI assistants. Large language models enter this work in three roles. First, Gemini 3.1 Pro acts as a pipeline component, producing a unified object vocabulary across the three input photos (Section 4.1, Appendix B) and refining raw object identifiers into natural-language descriptions under a constrained substitution-only prompt (Appendix C). Second, fifteen VLMs are the systems under evaluation (Section 5.1). Third, during manuscript preparation, large language models (ChatGPT, Claude) were used solely for English-language polishing; they did not contribute to the core methodology, experimental design, data collection, or analysis.