BILCO: An Efficient Algorithm for Joint Alignment of Time Series

Abstract

Multiple time series data occur in many real applications and the alignment among them is usually a fundamental step of data analysis. Frequently, these multiple time series are inter-dependent, which provides extra information for the alignment task and this information cannot be well utilized in the conventional pairwise alignment methods. Recently, the joint alignment was modeled as a max-flow problem, in which both the profile similarity between the aligned time series and the distance between adjacent warping functions are jointly optimized. However, despite the new model having elegant mathematical formulation and superior alignment accuracy, the long computation time and large memory usage, due to the use of the existing general-purpose max-flow algorithms, limit significantly its well-deserved wide use. In this report, we present BIdirectional pushing with Linear Component Operations (BILCO), a novel algorithm that solves the joint alignment max-flow problems efficiently and exactly. We develop the strategy of linear component operations that integrates dynamic programming technique and the push-relabel approach. This strategy is motivated by the fact that the joint alignment max-flow problem is a generalization of dynamic time warping (DTW) and numerous individual DTW problems are embedded. Further, a bidirectional-pushing strategy is proposed to introduce prior knowledge and reduce unnecessary computation, by leveraging another fact that good initialization can be easily computed for the joint alignment max-flow problem. We demonstrate the efficiency of BILCO using both synthetic and real experiments. Tested on thousands of datasets under various simulated scenarios and in three distinct application categories, BILCO consistently achieves at least 10 and averagely 20-folds increase in speed, and uses at most 1/8 and averagely 1/10 memory compared with the best existing max-flow method.

1   Introduction

Time series data appear naturally in a wide range of fields, such as motion capture, speech recognition, and bioinformatics. As sequences are usually not directly comparable due to possible delay and distortion, alignment among them is a prerequisite step before further analysis. The most popular alignment technique, dynamic time warping (DTW) [3], finds an optimal match between two sequences in linear time using dynamic programming (DP). However, DTW and its variants [2, 15] only compare a single pair of time series, while real data often contain structural information. For example, in time-lapse microscopy data, the pixel intensities are recorded over time in a 2D grid, and adjacent pixels tend to have similar temporal patterns. Thus, joint alignment of more than a single pair is expected to achieve better performance by taking advantage of dependency from the structure.

For long time, it was not clear how to incorporate the structural information in a principled way. Various heuristic tricks were developed [13, 19]. In a recent theoretical breakthrough, the joint alignment problems were elegantly modeled as a max-flow problem of graphical time warping

Figure 1: (a-c) The alignment between sequences x and y. DTW graph of alignment is shown in (b) and its dual graph in (c). In (b), if warping path crosses (k_1, k_2), $x[k_1]$ and $y[k_2]$ are matched. Each warping path in (b) is dual to a corresponding cut in (c). (d) GTW graph construction for time series arranged on 2D grid. Details are shown for two adjacent pairs (m, n). Given warping functions P_m and P_n (top panel), their corresponding cuts segmented the dual graph into the sink side (red) and source side (blue) (bottom panel). $dist(P_m, P_n)$ (the green shadow in top panel) is proportional to the number of cross edges linking source side and sink side. (e) application of pairwise alignment and joint alignment to calculating signal propagation. (f) application to extracting depth information (data from [16]).

(GTW) graph by optimizing both the time series pairwise similarity and the distance between warping functions [22]. GTW was shown to have superior alignment accuracy in many applications, such as brain activity analysis [21] and liquid chromatography-mass spectrometry (LC-MS) proteomics [23]. The binocular stereo vision formulation in [11] is also a special case of GTW. Two examples are given in Fig.1(e)(f). However, the long computation time and large memory usage severely limit its potential broad applications, because GTW was solved by existing general-purpose max-flow algorithms and the graph is often huge. Indeed, for a typical dataset with 5000 pairs of time series, if each time series contains 200 time points, all popular methods, such as incremental breadth-first search (IBFS) [8], Hochbaum's pseudoflow (HPF)[10], Boykov-kolmogorov (BK) max-flow [4, 12], and highest-label push-relabel (HIPR) [9, 5], cost hours and more than 100 gigabytes memory.

In this paper, we identify two important properties of the joint alignment max-flow problem and show that they can be leveraged to design a novel algorithm with improvements in both speed and memory efficiency. Specifically, first, joint alignment is a generalization of pairwise alignment and numerous individual DTW problems are embedded, as shown in Fig.1(a)-(d). If the dependency is neglected, it is reduced to multiple independent DTW problems, which can be solved in linear time through DP. Although the dependency makes the problem more complex, the property of DTW problem can still be utilized. Second, a coarse approximate solution to joint alignment can be readily estimated in many applications. Such prior knowledge can be incorporated to accelerate the max-flow algorithms.

Taking advantage of these two properties, we develop BIdirectional pushing with Linear Component Operations (BILCO), a novel algorithm that solves the joint alignment max-flow problem exactly and more efficiently. The algorithm consists of two major strategies: (a) By utilizing the first property, we propose Excess pushing with Linear Component Operations (ELCO) that integrates DP and the push-relabel approach [9]. Each component is defined as a small subgraph including connected nodes and their related edges. The components are automatically and adaptively determined. We show that all operations on each component can be achieved in linear time by combining DP and subgraph properties. With linear component operations, ELCO can achieve higher efficiency than generic push-relabel approach. (b) By leveraging the second property, we design a bidirectional-pushing strategy to utilize prior knowledge as initialization. The strategy simplifies the original problem into two smaller sub-problems with opposite pushing directions. In each sub-problem, ELCO is applied, but the separation of two pushing directions dramatically reduces unnecessary computation.

Figure 2: An analogy to joint alignment max-flow problem. Water, tube, tank, and partition represent excess, cross edge, subgraph, and cut, respectively. (a) In the initial stage, source has pushed all water it can to water tanks. (b) "Drain" operation: water in the tanks is drained to sink. (c) "Discharge" operation: water flows from active component to inactive component in a neighbor water tank, where water needs to concentrate at the connecting tube first. (d) After (c), the previously inactive component in G_2 becomes active and water can be drained again. Due to the concentration step in (c), there is one new partition in G_1 that further segments it into three components. (e) One intermediate stage of a tank, where multiple components are segmented in a subgraph and some tubes are blocked.

BILCO has the same theoretical time complexity as the best popular methods such as HIPR, but it provides a significant empirical efficiency boost without sacrificing the accuracy in the task of joint alignment. Its effectiveness is evidenced through both synthetic and real experiments. Compared with IBFS, HPF, BK, and HIPR on thousands of datasets under various simulated scenarios and three real applications in distinct categories, BILCO improves the speed by 10-50 folds and costs averagely $1/10$ memory relative to the best peer method.

2 Problem formulation

The joint alignment problem can be formulated as [22]:

$$\min_{P_n, n=1,2,\ldots,N} \left(\sum_{n=1}^{N} cost(P_n) + \kappa \sum_{(m,n)\in Neib} dist(P_m, P_n) \right) \tag{1}$$

where P_n denotes the warping path for the n_{th} time series pair, N is the total number of time series pairs that are jointly aligned, $cost(P_n)$ is the alignment cost of the n_{th} time series pair, $dist(P_m, P_n)$ is the warping path distance defined by the area of the region bounded by P_m and P_n. $Neib$ is the set of pair indices (m, n) representing the adjacent time series, and κ is the hyperparameter to balance the alignment cost term and the distance term. For example, for 2D grid time-series data, $Neib$ may include the pair of neighboring pixels, and κ represents a prior similarity between the pixels.

As shown in Fig.1, Equation (1) can be converted to a flow network and solved by finding the min-cut of it. The constructed graph, GTW graph, consisting of N GTW subgraphs $\{G^k = (V^k, E^k)|1 \le n \le N\}$ and cross edges E_{cross} with capacity $\frac{\kappa}{2}$ (Fig.1(d)). The edges within GTW subgraph are called E_{within}. For convenience, in the following content, we refer to "GTW subgraph" as "subgraph". Each subgraph G^k is dual to a DTW graph, which represents the warping between a pair of time series. The cut within a subgraph is dual to a warping path of the time series pair [1] (Fig.1(b)-(c)), and thus the min-cut of one DTW graph can be solved in linear time through DP by finding the shortest path. The cross edges constrain the difference between cuts in neighboring subgraphs, corresponding to the distance term in Equation (1) (Fig.1(d)). To ensure the monotonicity and continuity of warping paths, the capacities of reverse edges in each subgraph are set infinite [22].

3 Method

BILCO contains two major parts, ELCO and bidirectional pushing, as discussed in Sections 3.1 and 3.2, respectively. Based on the initialization of warping functions, bidirectional-pushing strategy

Figure 3: An example of graph conversion to incorporate flows on E_{cross} into E_{within}. (a) Subgraph with flows on E_{cross} in the first column. (b) Entering flow and outgoing flow are like extra edges linking to source and sink. (c) Purple cut would segment the subgraph into source side and sink side, where extra edges lead to counting two more cuts in the cost. (d) Costs are added to all paths/cuts below the edge linking to the source, and to all paths/cuts above the edge linking to the sink. (e) The first column of the converted planar DTW graph. (f) The converted GTW subgraph.

converts a max-flow problem into two sub-problems and we solve each of them with ELCO. The integration leads to BILCO (Section 3.3), followed by the analysis of time complexity and memory usage in Section 3.4 and 3.5. All lemmas and theorems are proved in the supplementary.

3.1 Excess pushing with linear component operations (ELCO)

Since GTW graph contains many subgraphs dual to DTW graphs and each DTW graph can be linearly solved by DP, we hope the DTW graph and DP algorithm can be exploited in our approach. While the cross edges between subgraphs prohibit the direct use of DP, we found that the component as defined in Subsection 3.1.1 is the maximum subgraph that can allow the use of DP. By combining the newly designed graph conversion strategy (Fig.3) and DP, we establish that the operations on components, "Drain" and "Discharge" (defined in Subsections 3.1.1), can indeed be linearly implemented as in Subsections 3.1.2 and 3.1.3. To guarantee global optimality, we design a new labeling function as in Subsection 3.1.4 and use that to guide our component operations.

3.1.1 The basic unit of operation is component, not node or subgraph

To exploit the property of each subgraph, ELCO borrows the idea from push-relabel algorithm, whose operations are localized. ELCO allows the existence of excess, which is the surplus between the entering flow and outgoing flow of one node. The nodes that carry excess are regarded as "active". Based on the location of flow exchanges, we define two operations, "Drain" and "Discharge". "Drain" pushes excess within single subgraph through E_{within}, while "Discharge" pushes excess across neighbor subgraphs through E_{cross}. By alternatively executing these two operations, more and more excess can be sent to sink (Fig.2). The spread of excess leads to many edges being saturated, resulting in multiple cuts in the same subgraph. These cuts segments the subgraph into different components (Fig.2(e)). Formally, we define one component as a subset of GTW subgraph bounded by two adjacent cuts. ELCO uses component, instead of node or subgraph, as the basic operation unit, because it is the largest possible unit to use DP to push flows.

Lemma 1: If two nodes are in the same component, then there is at least one path linking them.

By Lemma 1, if one node in a component is active, the excess can spread anywhere in the same component. Thus, the whole component can be seen as one unit. On contrary, cuts block the flow across components in the same subgraph, it is inapplicable to take a whole subgraph as one unit.

3.1.2 Linear time implementation of "Drain" component operation

Regarding "Drain" operation, we only need to calculate the min-cut of one active component that links to the sink, then all the excess above the new cut is drained and the part below the new cut is identified as a new active component (Fig.2(b)(c)). As mentioned, the min-cut can be quickly solved by DP on its dual graph. However, with flows on E_{cross}, DP cannot be applied directly. The graph is not planar anymore (Fig.3(a)(b)) and its dual graph does not exist. Here we design a linear-time graph conversion strategy as shown in Fig.3 (see algorithm in supplementary), which can incorporate known flows on E_{cross} into E_{within} and obtain an equivalent planar graph where DP can still be applied. Combining with DP, the "Drain" component operation is linear.

Lemma 2: The corresponding cut values/path costs before and after graph conversion are the same.

Algorithm 1 ELCO

$R_k = G^k$, $d(R_k) = 0$, $cut = \text{Drain}(R_k)$, Split (R_k, cut) for $k = 1, 2, ..., N$ ▷ Initialization
while active region exists **do**
    Pick active region with highest label, R_i ▷ Highest-label selection rule
    if $d(R_i) = 0$ **then** ▷ sink component
        $cut = \text{Drain}(R_i)$, Split (R_i, cut) ▷ First type operation and update
    else ▷ No direct edge linking to sink
        if $\exists R_j$ that $R_i \rightarrow R_j$ and $d(R_i) = d(R_j) + 1$ **then**
            $cut = \text{Discharge}(R_i)$, Split (R_i, cut) ▷ Second type operation and update
        else
            Relabel(R_i) ▷ Relabel
            Gap-relabel heuristic ▷ Relabel may result in label gap
        end if
    end if
end while

Algorithm 2 Relabel(R), $R \in G^k$

$d_{minCross} = \min\{d(R_j)|R \rightarrow R_j, R_j \notin G^k\}$ ▷ Lowest reachable label in neighbor subgraphs
$d_{minWithin} = \min\{d(R_j)|R \rightarrow R_j, R_j \in G^k\}$ ▷ Lowest reachable label in same subgraph
if $d_{minCross} < d_{minWithin}$ **then**
    $d(R) = d_{minCross} + 1$
else ▷ Consider the validity
    $d(R) = d_{minWithin}$
    $R = R \bigcup \{R_j|R \rightarrow R_j, d(R) = d(R_j), R \in G^k, R_j \in G^k\}$ into R ▷ Merge
    Relabel(R)
end if

3.1.3 Linear time implementation of "Discharge" component operation

To discharge one component, we try to push excess out on each node as much as possible to make sure the component has sent all the excess it can since excess can flow anywhere in the same component.

Lemma 3: The amount of maximum possible excess on node v is the min-cut value in residual graph by taking v as sink.

Working on the modified DTW graph, DP can still be applied to calculate such excess by finding the difference between the shortest path below v and the shortest path of the whole graph. The difference can represent the min-cut value mentioned in Lemma 3. To implement linear-complexity component discharge operation, here we use another layer of DP that reuses the stored dynamic matrices that save the shortest distance recursively. The detailed algorithm of "Discharge" is given in supplementary.

3.1.4 A new labeling function to guide excess approaching the sink across components

We design a new labeling function to guide excess approaching t across components from high label to low label. Different from the one in generic push-relabel [9], our labeling function implies the distance from one component to sink rather than from the node. Since the cut blocks the connection of components in the same subgraph, only E_{cross} is counted. Derived from such distance, we define our labeling function $d : V \rightarrow \mathbb{N}$ to be valid if for all residual edges,

$$d(v) \leq d(w) \quad (v, w) \in E_{within} \tag{2a}$$
$$d(v) \leq d(w) + 1 \quad (v, w) \in E_{cross} \tag{2b}$$

With such definitions, we have,

Lemma 4: All nodes in the same component have the same label.

Lemma 5: The new labeling function (2) is consistent with generic push-relabel labeling function if treating each component as one unit.

Lemma 4 suggests that we can set the same label to one component and all the nodes in it. And lemma 5 implies that ELCO can be seen as an alternative push-relabel approach that uses component

Figure 4: Bidirectional pushing. (a) Initial cut C_0 segments graph into V_{S_0} and V_{T_0}. (b) Replace nodes in V_{S_0} by source, pushing excess leads to the new cut C_1 which segments the new sink side V_{T_1} out. (c) The residual graph of (b), while V_{S_0} cannot push more before replacing nodes. (d) Replace nodes in V_{T_1} by sink, the optimal cut of the whole problem is found by pushing deficit.

as the operation unit, and all the statements in the generic push-relabel approach [9] hold on the component level. Since the validity of the labeling function is maintained in ELCO (see the proof in supplementary), the optimal solution can be achieved in polynomial component operation.

The ELCO is outlined in Algo.1 and Algo.2 and details can be found in supplementary. $R_1 \rightarrow R_2$ if for $v \in R_1$ and $w \in R_2$ that (v, w) has positive residual capacity. Highest-label selection rule is applied, and both global-relabel heuristic and gap-relabel heuristic in [9] are utilized for acceleration.

3.2 Bidirectional-pushing strategy

Generic push-relabel methods, and ELCO alike, attempts to push as much as excess to the sink. If part of the excess fails to reach sink due to the limited edge capacity, they need to be absorbed back by source, which may take a long time and incur high computational cost. Since this part of excess can neither make an impact on the max-flow nor change the final cut, such computation is redundant. ELCO reduces part of redundancy within each component through linear component operations, but it cannot solve the problem across components, especially with large κ (large capacities of E_{cross}). Under large κ, E_{within} are easier to be saturated and components are more likely to be segmented into a smaller size. Thus, the redundancy is hard to be reduced if we focus on each component alone.

Consider an extreme case in which all nodes are divided into the source side V_T according to the cut. All excess can then reach the sink and all push operations are not redundant. In the other extreme, all nodes belong to the source side V_S. Then most excess cannot reach the sink but is still pushed, leading to the redundant computation. Reversely, rather than pushing excess from the source, a better strategy is pushing deficit from the sink. Deficit means input flow is less than output flow. Pushing deficit is just pushing excess in a graph with source and sink switched. Since all nodes are divided into V_S, all operations for pushing deficit in the opposite direction are not redundant. In conclusion, pushing excess in the sink side V_T or pushing deficit in the source side V_S will not result in invalid computation. If prior knowledge is available to guide us to find an initialization of warping paths, we only need to push excess on the sink side and deficit on the source side. After that, little computation would be wasted. This idea motivates us to design the bidirectional-pushing strategy (Fig.4):

- Initialization: Estimate initial cut C_0 for GTW graph. The corresponding source side and sink side are denoted as V_{S_0} and V_{T_0}, respectively.
- Push excess: Replace all the nodes in V_{S_0} by source, solve the max-flow problem by pushing excess. The new sink side segmented by the new min-cut C_1 is denoted as V_{T_1}.
- Push deficit: Replace all the nodes in V_{T_1} by sink, solve the max-flow problem of the graph by pushing deficit. The obtained min-cut C_2 is the min-cut of the original GTW graph.

The strategy is guaranteed to achieve optimal solution by the following statements:

Lemma 6: Assume the min-cut segments the nodes V into source side V_S and sink side V_T, then replacing the nodes in V_S or V_T by source or sink does not impact the min-cut.

Lemma 7: Assume V_T represents the nodes of sink side segmented by the real min-cut of original GTW graph, then $V_{T_1} \subset V_T$.

Theorem 1: The obtained min-cut in bidirectional strategy is the min-cut of the original graph.

In joint alignment problem, since the final cuts tend to be similar because larger κ brings larger similarity penalty, a good initialization is easy to be found.

3.3 Bidirectional pushing with linear component operations

We propose BILCO as the top-level algorithm integrating ELCO and the bidirectional-pushing strategy. Under small κ, the component is usually large so that ELCO can work efficiently. While under large κ, the cuts in different subgraphs are similar and the initial solution can be easily estimated. Therefore, bidirectional-pushing strategy works well. By setting initialization on each subgraph as the optimal warping path of averaged subgraph, which is also the solution of joint alignment with infinite κ, BILCO could take both advantages and has a good performance under any κ. We use such initialization in our experiments and get good performance. Therefore, we recommend it as the default setting for BILCO, at least for similar applications.

3.4 Complexity

Bidirectional-pushing strategy can convert the original problem to two smaller sub-problems, which may help accelerate *any* max-flow methods. For example, in the best case, the initialization is accurate and divide problem into two half-size sub-problems. Then the speed for one $O(|V|^2\sqrt{|E|})$ method may be accelerated nearly 3 times, since both $|V|$ and $|E|$ are halved. Even with a bad initialization, the strategy can only increase the operation number without impacting the complexity bound.

ELCO is somehow like the integration of DTW (with complexity $\Theta(|V|)$) and HIPR (with complexity $O(|V|^2\sqrt{|E|})$ [5]). On one hand, E_{cross} makes ELCO more complex than DTW, thus it has a lower bound $\Omega(|V|)$. On the other hand, using linear component operations to push excess, ELCO has fewer operation units and less complexity than HIPR. Even in the worst case where each component contains only one node, ELCO is still equivalent to HIPR with the same upper bound.

Therefore, the worst complexity of BILCO is $O(|V|^2\sqrt{|E|})$.

3.5 Memory usage

BILCO can also improve memory efficiency by utilizing the structure of GTW graph. In general max-flow methods, the majority of memory is used to record the relationship between nodes and edges. With a known graph structure, BILCO stores nodes and edges in coordinate order so that the relationship can be derived from their positions. The expense for storing components is insignificant in real applications since the component number is usually neglectable compared with large $|V|$ and $|E|$. Table 1 compares the memory usage of BILCO and peer methods based on their implementation.

Table 1: Memory usage (bytes) among BILCO, IBFS, HPF, BK, and HIPR.

BILCO	IBFS	HPF	BK	HIPR
$8|V| + 4|E|$	$48|V| + 64|E|$	$156|V| + 96|E|$	$48|V| + 64|E|$	$64|V| + 112|E|$

4 Experiments

In this section, we compare the efficiency of BILCO with four peer methods IBFS, HPF, BK, and HIPR under synthetic simulation and real applications. All experiments were conducted in MATLAB with Intel(R) Xeon(R) Gold 6140@2.30Hz, 128GB memory, Windows 10 64 bit and Microsoft VC++ complier. No GPU is used. All methods are implemented in C/C++ with MATLAB wrapper.

4.1 Synthetic data

Following a similar scheme in [22], we simulated an image signal propagation dataset with varying pixels (N) and frames (T). 4-connected neighbors are used and thus the GTW graph has around $|V| = 2NT^2$ nodes and $|E| = 7NT^2$ edges. A bell-shaped signal propagated from the center of the image to the boundary. Gaussian noise was added so that the signal-to-noise ratio is 10dB , which mimics real scenario. To make hyperparameter κ comparable, we normalized the synthetic data by dividing the standard deviation of noise. We tested 20 instances for each combination of N, T, and κ.

Fig.5 (a-d) compares BILCO and peer methods under different graph sizes, where BILCO is at least 10 times faster than any peer method and costs only $1/10$ memory. The impact of hyperparameter κ is demonstrated in Fig.5 (e), where HIPR combined with our bidirectional-pushing strategy (BI-HIPR)

Figure 5: (a)-(d) compare the running time and memory usage under different graph size. (e) compares the running time of max-flow methods under different κ, including BI-HIPR and ELCO.

and ELCO method are also compared. As shown, the running time of the majority of the methods grows as κ becomes larger, because larger capacities of E_{cross} give more freedom to exchange flow and make the graph more complex. Among all methods, BILCO shows the best efficiency under any κ. By comparing ELCO with BILCO, or HIPR with BI-HIPR, we find that bidirectional-pushing strategy speeds up both methods, especially under large κ. It's due to the fact that the default initialization in Section 3.3 gets closer to the optimal solution when κ gets larger, which effectively removes unnecessary computation. Fig.5(e) also shows that the two strategies, ELCO and bidirectional pushing are complementary and synergistic. When κ is small, ELCO dominates the acceleration. When κ is large, the bidirectional pushing makes a bigger impact. Interestingly, the two strategies synergistically improve the speed for the large κ. For example, under the largest κ, both BI-HIPR and ELCO are nearly 4 times faster than HIPR, suggesting a speed up of 16 folds for independent effects, while BILCO shows around 100-fold speedup compared to HIPR.

4.2 Real data

Here we compare our BILCO with four peer methods in three distinct application categories: calculating signal propagation [21], extracting depth information [11], and signature identification [13]. Since all these max-flow methods would give the same results, here we only compare running time and memory usage, as shown in Table. 2, where * in the name represents the spatially downsampled data. BILCO is used as the baseline and we show how many times others cost. The first application is similar to the one in Section 4.1 and we won't go into detail here. In the second application, the depth can be derived from the misalignment of the same row between two images, while the depth distributions in adjacent rows are assumed to be similar. To avoid unnecessary computation while allowing relatively large disparity, we set a window size with $1/5$ sequence length in this experiment. In the third application, 20 persons' signatures [14] are identified where totally 500 real signatures and 500 forgeries are compared with the reference signature. Smoothness is imposed on the feature sequences of the same signature, and in the table we show the summation of running time and maximum memory usage for two signature categories. The detailed preprocessing steps and experiment settings are given in the supplementary. As shown, BILCO always performs best for all these joint alignment applications. It shows around 10 to 50 times speed improvement and only costs nearly $1/10$ memory compared with the best peer method. Especially for the application of estimating signal propagation, BILCO performs averagely 29 times (range from 18 to 50) faster than other methods. Considering these applications are diverse and the dependency structures are various from 2-connected neighbors for depth, 4-connected neighbors for propagation, to all-connected neighbors for signature, this forcefully demonstrates the superiority and broad applicability of BILCO.

5 Conclusion and discussion

Compared with DTW, joint alignment utilizes the dependency in the data and could obtain better performance, however, at the expense of speed and memory. In this paper, we developed BILCO algorithm to minimize such an expense by exploiting the special properties of the problem. It can efficiently solve joint alignment max-flow problems and get exactly the optimal solution. Besides

Table 2: Efficiency comparison of different methods on real data.

	Problem		BILCO	IBFS	HPF	BK	HIPR
Name	$\|V\|$	$\|E\|$	Time
Memory	Time/(Time of BILCO)
Memory/(Memory of BILCO)			
Calculate signal propagation in imaging data (first two generated by us, last two from [20] and [21])							
Glia Ca^{2+}	1.1×10^9	3.8×10^9	**586s**
25.1GB	Out of
Memory	Out of
Memory	Out of
Memory	Out of
Memory
Glia Ca^{2+} *	7.0×10^7	2.3×10^8	**7s**
1.5GB	×50.0
×12.1	×109.4
×21.1	×348.0
×12.1	×385.6
×18.6
5_rat_astro_ATP	7.9×10^7	2.7×10^8	**32s**
1.6GB	×17.8
×12.8	×19.5
×22.4	×480.2
×12.8	×76.3
×19.8
Exvivo Ca^{2+}	6.5×10^7	2.2×10^8	**26s**
1.4GB	×20.2
×12.1	×18.4
×21.1	×665.7
×12.1	×74.1
×18.6
Extract depth information in binocular stereo (data from [16])							
pendulum1	2.9×10^9	7.2×10^9	**6065s**
59.2GB	Out of
Memory	Out of
Memory	Out of
Memory	Out of
Memory
artroom2	2.9×10^9	7.2×10^9	**7316s**
58.9GB	Out of
Memory	Out of
Memory	Out of
Memory	Out of
Memory
pendulum1*	7.7×10^7	1.9×10^8	**35s**
1.9GB	×10.0
×7.9	×13.6
×16.7	×32.5
×7.9	×72.6
×14.1
artroom2*	7.7×10^7	1.9×10^8	**33s**
1.8GB	×9.8
×8.3	×12.1
×16.7	×19.2
×8.3	×58.9
×14.8
Signature identification (data from [14])							
Real signatures	1.7×10^4
$\sim 6.3 \times 10^6$	5.9×10^4
$\sim 2.2 \times 10^7$	**204s**
0.14GB	×15.2
×11.4	×19.5
×20.7	×34.8
×11.4	×156.3
×21.4
Forgeries	1.7×10^4
$\sim 1.6 \times 10^7$	8.8×10^4
$\sim 5.8 \times 10^7$	**564s**
0.53GB	×20.9
×8.3	×16.6
×14.7	×77.9
×8.3	×145.4
×14.5

theoretical analysis, we demonstrated the efficiency of BILCO through both synthetic experiments and real applications, where BILCO showed around 10 to 50 times speed improvement and only cost averagely $1/10$ memory compared with the best one among peer methods IBFS, HPF, BK, and HIPR. The testing was conducted on a wide range of scenarios, suggesting the broad applicability of BILCO. We expect our work could facilitate greatly the application of joint alignment and help obtain better performance in different fields.

We observed that the bidirectional-pushing strategy can not only be regarded as a general push-relabel acceleration trick but also work synergistically with linear component operations for BILCO. Because of the bidirectional strategy, the graph is separated so that the less unnecessary excess or deficit needs to be pushed, the fewer saturated edges and cuts appear, and then the larger components will be. With larger components, the number of operations can be reduced greatly, which makes BILCO even faster (100×) than the multiplication of BI-HIPR (4×) and ELCO (4×) when compared to HIPR as mentioned in Section 4.1.

Our BILCO algorithm is a specialized approach to a specific max-flow problem. While inventing max-flow algorithms has a long history, all the existing methods fail to solve our problem efficiently, no matter whether they are based on augmenting path [4, 12, 8], localized operations as in push-relabel [9, 5], the combination of the two [17, 7], or integrating graph decomposition [18, 6, 17]. To the best of our knowledge, we are the first of integrating DP and push-relabel method to solve max-flow problems. Although there is a general feeling in the field that initialization does not help much for max-flow algorithms, we showed bidirectional pushing is a good strategy to leverage initialization and it is particularly powerful when coupled with the linear component operations. We hope our efforts here will be not only useful for the application of joint alignment but also inspiring for the methodology development of specific network flow problems. We have a general sense that while it is hard to invent better generic algorithms for classical problems, there are a lot of opportunities for more specialized problems and indeed great demands due to the super large scale of recent problems.

References

[1] RK Ahujia, Thomas L Magnanti, and James B Orlin. Network flows: Theory, algorithms and applications. *New Jersey: Rentice-Hall*, 1993.

[2] Ghazi Al-Naymat, Sanjay Chawla, and Javid Taheri. Sparsedtw: A novel approach to speed up dynamic time warping. *arXiv preprint arXiv:1201.2969*, 2012.

[3] Donald J Berndt and James Clifford. Using dynamic time warping to find patterns in time series. In *KDD workshop*, volume 10, pages 359–370. Seattle, WA, USA:, 1994.

[4] Yuri Boykov and Vladimir Kolmogorov. An experimental comparison of min-cut/max-flow algorithms for energy minimization in vision. *IEEE transactions on pattern analysis and machine intelligence*, 26(9):1124–1137, 2004.

[5] Boris V Cherkassky and Andrew V Goldberg. On implementing push-relabel method for the maximum flow problem. In *International Conference on Integer Programming and Combinatorial Optimization*, pages 157–171. Springer, 1995.

[6] Andrew Delong and Yuri Boykov. A scalable graph-cut algorithm for nd grids. In *2008 IEEE Conference on Computer Vision and Pattern Recognition*, pages 1–8. IEEE, 2008.

[7] Andrew V Goldberg, Sagi Hed, Haim Kaplan, Pushmeet Kohli, Robert E Tarjan, and Renato F Werneck. Faster and more dynamic maximum flow by incremental breadth-first search. In *Algorithms-ESA 2015*, pages 619–630. Springer, 2015.

[8] Andrew V Goldberg, Sagi Hed, Haim Kaplan, Robert E Tarjan, and Renato F Werneck. Maximum flows by incremental breadth-first search. In *European Symposium on Algorithms*, pages 457–468. Springer, 2011.

[9] Andrew V Goldberg and Robert E Tarjan. A new approach to the maximum-flow problem. *Journal of the ACM (JACM)*, 35(4):921–940, 1988.

[10] Dorit S Hochbaum. The pseudoflow algorithm: A new algorithm for the maximum-flow problem. *Operations research*, 56(4):992–1009, 2008.

[11] Hiroshi Ishikawa and Davi Geiger. Occlusions, discontinuities, and epipolar lines in stereo. In *European conference on computer vision*, pages 232–248. Springer, 1998.

[12] Pushmeet Kohli and Philip HS Torr. Dynamic graph cuts for efficient inference in markov random fields. *IEEE transactions on pattern analysis and machine intelligence*, 29(12):2079–2088, 2007.

[13] Manabu Okawa. Template matching using time-series averaging and dtw with dependent warping for online signature verification. *IEEE Access*, 7:81010–81019, 2019.

[14] Javier Ortega-Garcia, J Fierrez-Aguilar, D Simon, J Gonzalez, Marcos Faundez-Zanuy, V Espinosa, A Satue, I Hernaez, J-J Igarza, C Vivaracho, et al. Mcyt baseline corpus: a bimodal biometric database. *IEE Proceedings-Vision, Image and Signal Processing*, 150(6):395–401, 2003.

[15] Thomas Prätzlich, Jonathan Driedger, and Meinard Müller. Memory-restricted multiscale dynamic time warping. In *2016 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 569–573. IEEE, 2016.

[16] Daniel Scharstein, Heiko Hirschmüller, York Kitajima, Greg Krathwohl, Nera Nešić, Xi Wang, and Porter Westling. High-resolution stereo datasets with subpixel-accurate ground truth. In *German conference on pattern recognition*, pages 31–42. Springer, 2014.

[17] Alexander Shekhovtsov and Václav Hlaváč. A distributed mincut/maxflow algorithm combining path augmentation and push-relabel. *International journal of computer vision*, 104(3):315–342, 2013.

[18] Petter Strandmark and Fredrik Kahl. Parallel and distributed graph cuts by dual decomposition. In *2010 IEEE Computer Society Conference on Computer Vision and Pattern Recognition*, pages 2085–2092. IEEE, 2010.

[19] Gineke A Ten Holt, Marcel JT Reinders, and Emile A Hendriks. Multi-dimensional dynamic time warping for gesture recognition. In *Thirteenth annual conference of the Advanced School for Computing and Imaging*, volume 300, page 1, 2007.

[20] Yinxue Wang, Guilai Shi, David J Miller, Yizhi Wang, Congchao Wang, Gerard Broussard, Yue Wang, Lin Tian, and Guoqiang Yu. Automated functional analysis of astrocytes from chronic time-lapse calcium imaging data. *Frontiers in neuroinformatics*, 11:48, 2017.

[21] Yizhi Wang, Nicole V DelRosso, Trisha V Vaidyanathan, Michelle K Cahill, Michael E Reitman, Silvia Pittolo, Xuelong Mi, Guoqiang Yu, and Kira E Poskanzer. Accurate quantification of astrocyte and neuro-transmitter fluorescence dynamics for single-cell and population-level physiology. *Nature neuroscience*, 22(11):1936–1944, 2019.

[22] Yizhi Wang, David J Miller, Kira Poskanzer, Yue Wang, Lin Tian, and Guoqiang Yu. Graphical time warping for joint alignment of multiple curves. In *Proceedings of the 30th International Conference on Neural Information Processing Systems*, pages 3655–3663, 2016.

[23] Chiung-Ting Wu, Yizhi Wang, Yinxue Wang, Timothy Ebbels, Ibrahim Karaman, Gonçalo Graça, Rui Pinto, David M Herrington, Yue Wang, and Guoqiang Yu. Targeted realignment of lc-ms profiles by neighbor-wise compound-specific graphical time warping with misalignment detection. *Bioinformatics*, 36(9):2862–2871, 2020.