DOES DEEP LEARNING LEARN TO ABSTRACT?
A SYSTEMATIC PROBING FRAMEWORK

ABSTRACT

Abstraction is a desirable capability for deep learning models, which means to induce abstract concepts from concrete instances and flexibly apply them beyond the learning context. At the same time, there is a lack of clear understanding about both the presence and further characteristics of this capability in deep learning models. In this paper, we introduce a systematic probing framework to explore the abstraction capability of deep learning models from a transferability perspective. A set of controlled experiments are conducted based on this framework, providing strong evidence that two probed pre-trained language models (PLMs), T5 and GPT2, have the abstraction capability. We also conduct in-depth analysis, thus shedding further light: (1) the whole training phase exhibits a "memorize-then-abstract" two-stage process; (2) the learned abstract concepts are gathered in a few middle-layer attention heads, rather than being evenly distributed throughout the model; (3) the probed abstraction capabilities exhibit robustness against concept mutations, and are more robust to low-level/source-side mutations than high-level/target-side ones; (4) PLMs exhibit better abstraction capability with larger model sizes, larger data scales, and higher diversity in data.

1 INTRODUCTION

Whereas concrete concepts are typically concerned only with things in the world, abstract concepts are about internal events. — Barsalou et al. (1999)

Abstraction means capturing the general patterns (often referred to as **abstract concepts**) efficiently in a specific learning context and reusing these patterns flexibly beyond the context (Mitchell, 2021; Kumar et al., 2022; Giunchiglia & Walsh, 1992; Hull, 1920). For instance, the abstraction on language means recognizing the underlying syntax and semantics behind concrete sentences. It is thought to be one of the fundamental attributes in human cognition for effectively learning, understanding and robustly generalizing, and has been studied for a long time in cognitive psychology and behavioral sciences (Gentner & Medina, 1998; Barsalou et al., 1999; Shivhare & Kumar, 2016; Konidaris, 2019).

The abstraction capability is also critical for deep learning, but many previous studies suggested that the surprising success of deep learning may come from the memorization of some surface patterns (also called superficial correlations or shortcuts) (Geirhos et al., 2020; Du et al., 2022), such as some special tokens (Niven & Kao, 2020; Gururangan et al., 2018), overlapping contexts (Lai et al., 2021; Sen & Saffari, 2020), and familiar vocabularies (Aji et al., 2020). It is still unclear whether the models just memorize these patterns without abstractions, or they do learn abstract concepts (yet overwhelmed by surface patterns when applied in a similar context as in training). Therefore, this paper aims to take a step forward to **probe the abstraction capability of deep learning models**, keeping the effects of abstract concepts and surface patterns decoupled and controlled individually.

Our key idea is to probe the abstraction capability from a **transferability** perspective, since surface patterns are always bounded with **task-specific characteristics** while abstract concepts can be more generally reused. We consider designing multiple tasks with shared abstract concepts and totally different surface patterns, then tracing whether the learning on one task can boost the performance on another. Figure 1 demonstrates a motivating example.

Motivating Example As shown in Figure 1, suppose we want to examine whether a model can **learn the abstract rule** (i.e., the symbolic mapping rule $x_1 x_2 \rightarrow X_1 X_2$, in which x_i and X_i are

Figure 1: Motivating example: the abstract concepts learned in task A can be effectively reused in task B, but surface patterns are useless. Unused patterns or concepts are whitened after the update.

general variable slots) from the task A, or just **memorize surface mappings** (e.g., $ab \rightarrow AB$, in which a and A are task-specific symbols). To reveal the different transferability of two learning mechanisms, we utilize a **probing task** B that contains the same underlying abstract rule as task A but does not overlap with its symbol set. If the model could learn the abstract rule from task A, it would reuse it to interpret new context, thus effectively solving task B. But if not, memorizing some surface mappings that are bounded with task-specific symbols is less effective to solve task B.

Motivated by this example, we **design a systematic framework for probing abstraction capability**. This framework considers a set of probing tasks along with three procedures of experiments based on the transfer learning paradigm. The use of abstract concepts and task-specific characteristics in probing tasks are separately controlled. To probe the abstraction capability of language models, this work mainly considers **grammar** as the abstract concept[1]. The grammar of a formal language is a set of hidden rules behind concrete sentences and determines how terminals are combined into sentences that are valid to the syntax. We want to explore **whether the model can be aware of the grammar, or simply memorize some specific word combinations**. We instantiate our framework as a grammar probe that is constructed from the designed formal grammar and terminal sets. The probing results **show strong evidence that two probed PLMs** (specifically, T5-Base (Raffel et al., 2020) and GPT2-Medium (Radford et al., 2019)) **have the abstraction capability** to learn abstract concepts from concrete instances, rather than just simply memorizing surface patterns.

After probing the existence of abstraction capability, we further explore the following questions. **RQ1**: What is the characteristic of the training dynamics on learning abstraction? **RQ2**: How are these learned abstract concepts distributed in the model? Concentrated in a few modules or evenly distributed in whole model? **RQ3**: How robust is the abstraction capability on tasks with mutated abstract concepts? **RQ4**: How would general factors in deep learning (e.g., model size, data scale, and data diversity) influence abstraction? Here we outline some **interesting findings from our in-depth investigations**: (1) the training phase exhibits a "memorize-then-abstract" two-stage process; (2) the abstract concepts learned in our probes are gathered in a few middle-layer heads; (3) abstraction capability is more robust to source-side/low-level mutations than to target-side/high-level ones; (4) scaling up model size, data scale and diversity can help PLMs exhibit better abstraction capability.

Contributions 1) We propose a systematic probing framework for abstraction capability, guiding the design of controlled tasks and procedures from a transferability perspective. 2) We instantiate this framework with concrete tasks and show strong evidence that two probed PLMs have the abstraction capability. 3) We further analyze this capability and provide insightful conclusions by investigating the above research questions. We will release our data and code, and hope that this can be a useful tool to facilitate understanding of the abstraction capability of contemporary deep model.

2 RELATED WORK

Probing deep learning models. To explore whether deep learning models have certain capabilities, there has been much work examining these black-box models in some specially designed settings,

---

[1]We also probed other abstract concepts such as operation semantics in Appendix C

called probes (Petroni et al., 2019; Tenney et al., 2018; Warstadt et al., 2019; Lin et al., 2019; Hewitt & Manning, 2019; Vulić et al., 2020). The key challenge in designing probes is to exclude superficial correlations. That is, the performance of the model in the probing setting should be highly correlated with the capability to be probed rather than other influencing factors. For instance, to probe whether the model encodes some knowledge/information in the representation rather than just over-fit the data, a standard approach is to freeze the model parameters (Petroni et al., 2019; Tenney et al., 2018); to probe whether the model have compositionality rather than just memorize the label distribution, previous work injected statistical bias into the data splits (Lake & Baroni, 2018; Keysers et al., 2019; Kim & Linzen, 2020). In this work, to explore whether models can learn abstractions rather than just simply memorize surface patterns, we design probes using their different cross-task transferability.

Abstraction capability. Abstraction has been studied for a long term in cognitive psychology and behavioral sciences (Hull, 1920; Gentner & Medina, 1998; Barsalou et al., 1999; Burgoon et al., 2013; Wang, 2015; Shivhare & Kumar, 2016; Lake et al., 2017; Daniel, 2017; Konidaris, 2019) and has attracted attention in the artificial intelligence field (Giunchiglia & Walsh, 1992; Richardson et al., 2020; Clark et al., 2020; Talmor et al., 2020; Mitchell, 2021; Zadrozny, 2021; Millhouse et al., 2021; Kumar et al., 2022). The abstraction capability of DNN models has been explored in many tasks such as visual reasoning (Johnson et al., 2017; Barrett et al., 2018; Chollet, 2019; Kumar et al., 2022), grounded language understanding (Ruis et al., 2020), and game playing (Tsividis et al., 2021). As our work focuses on language models, another closely related topic is compositional generalization (Lake & Baroni, 2018; Keysers et al., 2019; Kim & Linzen, 2020), which explored whether neural models could learn high-level grammars from specially designed training examples and apply the learned grammars through compositions. These works concluded that general-propose neural models (such as LSTM and Transformer) could not learn the full grammar with biased observations and demonstrated the importance of symbolic mechanisms for abstraction (Liu et al., 2020; Chen et al., 2020; Liu et al., 2021a). Some other previous work also explored the abstraction of language models in their specially designed tasks (Chollet, 2019; Mitchell, 2021; Zadrozny, 2021).

Most previous explorations of DNN abstraction capabilities were based on in-task probes, where training and test data may contain the same task-specific characteristics. For these probes, there are potential risks that the model may perform well in terms of surface patterns over-fitted to task-specific designs (e.g., patterns in candidate answers (Zhang et al., 2019)) rather than abstract concepts. To alleviate the potential influence from such superficial correlations, some previous work considered using biased task-specific designs in training and test data separately (Kim & Linzen, 2020; Barrett et al., 2018), but the probing results may be influenced by these designed biases rather than abstract concepts; other work has attempted to regenerate data to alleviate some observed problem in existing probes (Hu et al., 2021; Benny et al., 2021), but these ad hoc fixes are hardly guaranteed to avoid all kinds of potential performance leakages from task-specific knowledge. In this work, we propose a more promising and natural way to mitigate this issue in designing abstraction probes: leveraging cross-task settings where surface patterns learned from a particular task can hardly be effective in another task, while abstract concepts can be more generally and conveniently reused.

3 Probing Framework

As mentioned in Section 1, abstraction capability means to induce **abstract concepts** from concrete instances in a certain learning context and flexibly generalize these concepts beyond the context. A key difference between a surface pattern and an abstract concept is their different cross-task transferability, as the former is always bounded with some task-specific characteristics (e.g., a certain vocabulary) while the latter is transferable across tasks. We formally define this property as following.

Property: Transferability of Abstraction. Consider two machine learning tasks A and B that do not share any common instances between their task-specific characteristics spaces, but have essentially the same set of abstract concepts behind them, the transferability of abstraction means that learning A can help better learn B.

Notations: We denote two learning paradigms: $A \Rightarrow B$ as a procedure that the model is first trained on A and then fine-tuned on B, and $\Uparrow B$ as a procedure of directly training on B without the pre-training on A. The transferability of abstraction can be evaluated with the performance gain from procedure $A \Rightarrow B$ compared to $\Uparrow B$, denoted as $\Delta(A \Rightarrow B)$.

Figure 2: The illustration of the probing framework.

Based on this property, **we can verify the abstraction of a model by examining whether the model exhibits transferability (i.e., assessing $\Delta(A \Rightarrow B)$).** In the following, we formally design a framework for the probing of abstraction in a systematic manner and illustrate it in Figure 2.

Aiming

- This framework examines whether a probed model could learn abstract concepts $\mathbb{C}_A$ from the **aiming task** A with a **train set** $\overline{A}$.

Task Design

- **Probing task** B with the **transfer set** $\hat{B}$ and **test set** $\overline{B}$ contains the abstract concepts $\mathbb{C}_B$ that is required to be the same as $\mathbb{C}_A$. The task-specific characteristics used to construct $\hat{B} \cup \overline{B}$ do not overlap with that of $\overline{A}$. In addition, the examples in $\hat{B}$ are restricted to contain insufficient information for the probed model to learn $\mathbb{C}_B$ perfectly. Thus, the gain from the abstraction in task A would be noticeable.

- **Contrast task** C with the **contrast set** $\overline{C}$ aims to further confirm that the performance in task B is principally correlated with abstractions rather than other factors. The abstract concepts $\mathbb{C}_C$ is constructed by greatly breaking (changing) $\mathbb{C}_A$, thus compared with task A, the abstraction on task C is less effective for solving task B. The task-specific characteristics and other latent factors in constructing $\overline{C}$ are kept the same with that in $\overline{A}$.

Procedures of Experiments (abbreviated as Exp)

- **Controlled Exp** $\Uparrow B$**:** only train the model on $\hat{B}$ and test on $\overline{B}$.

- **Main Exp** $A \Rightarrow B$**:** train the model on $\overline{A}$, then fine-tune on $\hat{B}$, finally test on $\overline{B}$.

- **Contrast Exp** $C \Rightarrow B$**:** train the model on $\overline{C}$, then fine-tune on $\hat{B}$, finally test on $\overline{B}$.

Hypothesis and Expectations

- **Hypothesis:** the probed model can learn abstract concepts $\mathbb{C}_A$ from $\overline{A}$.

- **Expectation 1:** $\Delta(A \Rightarrow B)$ is significantly high, i.e., $A \Rightarrow B$ brings considerable gain compared with $\Uparrow B$.

- **Expectation 2:** $\Delta(C \Rightarrow B)$ is significantly lower than $\Delta(A \Rightarrow B)$ (or close to zero), i.e., Expectation 1 is highly correlated with the learning of abstract concepts rather than other factors.

4 PROBING ABSTRACTION CAPABILITY OF LANGUAGE MODELS

The abstract concepts mainly considered in this work is grammar, a set of hidden rules behind concrete sentences that determine how terminals are combined into sentences that are valid to the syntax. To design a grammar probe, we instantiate the framework with formal language translation (FLT) tasks. We assume that **the generative grammar of the source and target languages contain the abstract concepts of FLT tasks**, and that the surface patterns (e.g., familiar bigrams) are bounded with task-specific terminal sets. We give a more specific definition of abstraction in FLT tasks:

Table 1: Part of the grammar used in our grammar probe. Rules in the last row are allowed to iterate up to 12 times. We use $\twoheadrightarrow$ in production rules, which is distinct from the notation of mapping $\rightarrow$.

Source	Target	Type
verb $\twoheadrightarrow \mathbf{S}_v$
sub / direct-obj / indirect-obj $\twoheadrightarrow \mathbf{S}_n$
conj $\twoheadrightarrow \mathbf{S}_c$	PREDICATE $\twoheadrightarrow \mathbf{S}_P$
AGENT / THEME / RECIPIENT $\twoheadrightarrow \mathbf{S}_E$
CONCAT $\twoheadrightarrow \mathbf{S}_C$	T-Production Rule
sentence $\twoheadrightarrow$ subj verb
sentence $\twoheadrightarrow$ subj verb direct-obj indirect-obj
sentence $\twoheadrightarrow$ sentence conj sentence	CLAUSE $\twoheadrightarrow$ PREDICATE (AGENT)
CLAUSE $\twoheadrightarrow$ PREDICATE (AGENT, THEME, RECIPIENT)
CLAUSE $\twoheadrightarrow$ CLAUSE CONCAT CLAUSE	N-Production Rule

Definition: Considering an FLT task $T : \mathcal{L}_s \rightarrow \mathcal{L}_t$ that translate the source language $\mathcal{L}_s$ (with grammar $\mathbb{G}_s$ and terminals $\mathbf{S}_s$) to the target language $\mathcal{L}_t$ (with grammar $\mathbb{G}_t$ and terminals $\mathbf{S}_t$), and a set of concrete pairs $\overline{T} = \{(l_s^i \rightarrow l_t^i)\}^k$ in which l_s^i and l_t^i are sentences from $\mathcal{L}_s$ and $\mathcal{L}_t$ respectively, the abstraction capability is learning a mapping from $\mathbb{G}_s$ to $\mathbb{G}_t$ during training on $\overline{T}$ rather than just simply memorizing terminal-specific patterns that are bounded with $\mathbf{S}_s$ and $\mathbf{S}_t$.

Our FLT tasks are majorly derived from the synthetic semantic parsing task COGS (Kim & Linzen, 2020) and the Probabilistic Context-Free Grammar (PCFG) it used. We directly take the source grammar $\mathbb{G}_s$ of COGS which mimics the English natural language grammar, and reconstruct the target grammar $\mathbb{G}_t$ to be chain-structured (detailed in Appendix J.1). Part of the $\mathbb{G}_s$ and $\mathbb{G}_t$ are shown in Table 1. Terminals in $\mathbb{G}_s$ (and in $\mathbb{G}_t$) can be divided into three groups respectively: the verb terminals $\mathbf{S}_v$ (the PREDICATE terminals $\mathbf{S}_P$ in $\mathbb{G}_t$), the noun terminals $\mathbf{S}_n$ (the ENTITY terminals $\mathbf{S}_E$) and the conjunction terminals $\mathbf{S}_c$ (the CONCAT terminals $\mathbf{S}_C$). The production rules can also be categorized as T-Production rules (i.e., rules only containing terminals at the right side) and N-Production rules (i.e., rules only involving non-terminals). We assign task A and B (also C and B) with different group of terminals to ensure that there is no overlap between the task-specific characteristic spaces generated by the PCFG of task A and B (also C and B). We describe the instantiation of different sets $\overline{A}$, $\hat{B}$, $\overline{B}$ and $\overline{C}$ as following. Examples of these sets are contained in Appendix E.1.

Train set $\overline{A}$. To synthesis $\overline{A}$, we first derive the new source and target grammar (denoted as $\mathbb{G}_s^+$ and $\mathbb{G}_t^+$) from $\mathbb{G}_s$ and $\mathbb{G}_t$ by only one-to-one replacing the terminals with a group of new terminals[2] sampled from the Wordlist Corpora in NLTK (Bird et al., 2009). Additionally, as the original terminal group $\mathbf{S}_c$ (also $\mathbf{S}_C$) only contains a single terminal, we add 31 additional terminals into the new $\mathbf{S}_c$ (and $\mathbf{S}_C$) to increase the diversity. The terminal diversity will be further discussed in Section 6.4. Then, we use $\mathbb{G}_s^+$ and $\mathbb{G}_t^+$ to generate examples for train set $\overline{A}$. Note that $\mathbb{G}_s^+$ and $\mathbb{G}_s$ (also $\mathbb{G}_t^+$ and $\mathbb{G}_t$) share all non-terminals, N-Production rules, and the one-to-one mappings from source N-Production rules to target N-Production rules, except for the terminal sets.

Transfer set $\hat{B}$ and Test set $\overline{B}$. We take the train set in COGS as $\hat{B}$, and take the sentential complement (*Com.*) set and subject modification (*Mod.*) set as $\overline{B}$ for two sub-probes. The $\hat{B}$ only contains examples with up to 2 recursions and object modifications, while the $\overline{B}$ contains up to 12 recursions and subject modifications. It has been proved that training on $\hat{B}$ is not enough for a DNN model to learn the full grammars of COGS for handling the test cases in $\overline{B}$ (Kim & Linzen, 2020).

Contrast set $\overline{C}$. Compared with $\overline{A}$, $\overline{C}$ is generated with the same source grammar $\mathbb{G}_s^+$, but the target grammar is totally changed as $\mathbb{G}_t^-$: for each rule of $\mathbb{G}_t^+$, its right-side word order is reversed[3]. Except for the generative grammar, all other factors are kept the same with $\overline{A}$ during generating $\overline{C}$.

5 EXPERIMENTAL SETUP AND MAIN RESULTS

We probe two pre-trained language models: T5-Base (Raffel et al., 2020) and GPT2-Medium (Radford et al., 2019). Our experiments are based on the Huggingface Transformer models (Wolf et al., 2020). For both (continue) pre-training and fine-tuning, we take Adam (Loshchilov & Hutter, 2018) with 1e-5 learning rate and 0.01 weight decay. Batch size is 8 and max training step is 100k. We generate 3 groups of new terminals, repeat the experiments on each group with 2 random seeds, and finally

---

[2]Some non-semantic terminals are kept the same, such as the period in L_{src} and parentheses in L_{tgt}.

[3]Some basic rules are preserved (e.g., the order of the preceding and following parentheses).

Table 2: The main results of our probe. $\Delta(A \Rightarrow B)$ and $\Delta(C \Rightarrow B)$ are in brackets. The evaluation metric is exact match accuracy (%). *Com.* and *Mod.* represent the sentential complement and subject modification sets for $\overline{B}$. These results are in line with our two expectations.

Model	Sub-Probe	Controlled Exp $\Uparrow B$	Main Exp $A \Rightarrow B$	Contrast Exp $C \Rightarrow B$	Model	Sub-Probe	Controlled Exp $\Uparrow B$	Main Exp $A \Rightarrow B$	Contrast Exp $C \Rightarrow B$
T5	Avg.	18.7	71.9 (+53.2)	16.0 (-2.7)	GPT2	Avg.	8.0	47.9 (+39.8)	8.1 (+0.1)
	Com.	23.1	88.2	15.4		*Com.*	1.9	48.2	2.6
	Mod.	14.3	55.6	16.5		*Mod.*	14.1	47.6	13.6

average 6 results. The default evaluation metric is exact match accuracy. The early-stopping strategy is applied to avoid catastrophic forgetting. Detailed settings are listed in Appendix J.

Table 2 shows the main results of our probe. For both two sub-probes, the performances of two probed models are **in line with two Expectations** set in Section 3. First, the results of $\Uparrow B$ are very low, and $A \Rightarrow B$ can bring significant improvement, which is in line with Expectation 1. Second, the results of $C \Rightarrow B$ are much lower than $A \Rightarrow B$ (and are even just comparable with $\Uparrow B$), which is in line with Expectation 2. As two expectations are experimentally examined, we can draw a preliminary conclusion: **our probing results provide strong evidence that two probed PLMs have the abstraction capability** to learn abstract concepts from concrete instances rather than just memorize surface patterns, and to transfer the learned abstract concepts beyond specific tasks.

6 ANALYSIS

Based on our designed probe and results above, we further analyze the abstraction capability of PLMs to answer the RQs mentioned in Section 1. All experiments below are derived from *Com.* sub-probe, and are mainly conducted with T5-Base model except that are explicitly mentioned.

6.1 LEARNING PROCESS OF ABSTRACT CONCEPTS

To investigate the **learning process of abstract concepts**, we save checkpoints for every 1,000 steps during training on $\overline{A}$. Each checkpoint is further fine-tuned on $\hat{B}$ and tested on $\overline{B}$. For comparison, we also investigate **the process of memorizing in-task patterns** by directly examining each checkpoint on the held-out dev set in task A. Figure 3 shows the performance curves of two learning processes.

The training phase exhibits a "memorize-then-abstract" two-stage process. As shown in Figure 3, there is an obvious phase difference (48k training steps) between two time points that two learning processes achieve their 90% relative performance, respectively. Such a phase difference means that when the model has already performed well on task A in an early training phase, the learning of desired abstract concepts is still on-going. In other words, the in-task performance in an early training phase comes mainly from the effects of some task-specific characteristics rather than general abstract concepts. With extending the training phase, the abstract concepts can be further extracted/enhanced. This phase difference also suggests that **the pre-training process should be continued even if the model has already achieved a good in-pre-training performance**.

The learning of abstract concepts is accelerated after in-task examples are well learned. After the model reaches 90% in-task relative performance (i.e. right side of the red dashed line), the learning curve of abstract concepts (i.e., the blue curve) rises more rapidly.

The learning of abstract concepts is not stable in the early training phase. The curve of in-task performance is much smoother than the cross-task one. This suggests that the learning and transfer of abstract concepts is not stable. Nevertheless, the large fluctuations occur mainly in the early phases of training. With increasing training steps, this instability gradually decreases.

6.2 ABSTRACT ATTENTION HEADS

To investigate how the learned abstract concepts are distributed in the model, we first conduct preliminary experiments by separately freezing parameters in each layer and sub-layer during fine-tuning, and find that the parameters in attention sub-layers play important roles (detailed in Appendix D). To further determine the contribution of each attention head, we consider measuring the performance

Figure 3: Two learning process. Blue curves represent the learning performance of abstract concepts and red curves represent the learning performance of in-task examples. Curves in the right figure are min-max normalization of curves in the left.

Figure 4: DPC of each pruned head. The heads sorted from left to right are located from the first to the last layer in the model. It indicates that only a dozen of the whole 432 attention heads take charge of abstract concepts, and that these abstract heads are located in a few middle layers in the model.

degradation after excluding the effect of each head. Specifically, we evaluate the change in perplexity (PPL) of examples in $\overline{B}$ after pruning the normalized wight of each head as follows,

$$\Delta_{\theta,\overline{B}}(h) = \frac{1}{|\overline{B}|}\sum_i [\text{PPL}(l_t^i|l_s^i;\theta_{-h}) - \text{PPL}(l_t^i|l_s^i;\theta)], \tag{1}$$

in which h represents a certain head, θ is the full set of parameters in PLM after fine-tuning on $\hat{B}$, θ_{-h} means pruning the h head, and (l_s^i, l_t^i) is the input-output pair in $\overline{B}$. Note that a higher PPL means a lower performance. Considering that some heads may store the task-specific knowledge learned from fine-tuned data $\hat{B}$, pruning these heads may also lead to performance changes. Therefore, we also evaluate a baseline PPL change $\Delta_{\theta,\hat{B}}(h)$ on fine-tuned examples in $\hat{B}$ and measure the difference in PPL changes (DPC)$= \Delta_{\theta,\overline{B}} - \Delta_{\theta,\hat{B}}$. The DPC of each head is shown in Figure 4.

Abstract concepts are largely contained in a few heads, not evenly distributed in all heads. Note that there are totally 432 attention heads in T5-Base. Figure 4 shows that among hundreds of heads, only a dozen of them are highly correlated with storing abstract concepts in our probe.

These abstract attention heads are gathered in middle layers in T5. A larger index in Figure 4 means that the corresponding head is more away from the input side and closer to the output side. It shows that the abstract attention heads (i.e., heads with high DPC) are mainly located in the middle layers of T5-Base model, i.e., the last encoder layers and first decoder layers.

We further explore whether abstract concepts are modularized in the model. A modular is a part of parameters that can individually perform a specific target functionality (Csordás et al., 2020). To investigate modularity, we take the method of freezing certain parameters during fine-tuning to examine whether the update of these parameters can be independent. We consider the first 36 heads in Figure 4 (which contain some redundant heads) as a set of abstract heads. For comparison, we separately experiment with freezing 36 random heads. Table 3 shows that freezing abstract heads takes effect while freezing random heads does not. We further explore the modularity in Appendix D.

Table 3: Freeze abstract heads.

Method	$A \Rightarrow B$
Baseline	92.8
+Freeze Abstract Heads	96.6 (+3.8)
+Freeze Random Heads	92.9

Table 4: PLMs performance with fuzzy abstract concepts.

Probe	Model	Controlled Exp $\Uparrow B$	Main Exp $A \Rightarrow B$	Contrast Exp $C \Rightarrow B$
Fuzzy Grammar	T5	24.0	35.1 (+11.1)	26.2 (+2.2)
	GPT2	16.4	21.0 (+4.6)	11.6 (-4.8)

(a) Source-Side Mutations   (b) Target-Side Mutations

Figure 5: Performance with different derivations of (a) source and (b) target grammar.

6.3 ROBUSTNESS OF ABSTRACTION CAPABILITY

We explore the robustness of the probed abstraction capability when the abstract concepts in our designed probes are mutated. Different from the contrast task C in which the target grammar is totally changed, here we consider partially injecting mutations into source/target-side grammar. According to the formal grammar in Table 1, we consider injecting mutations at different abstract levels: changing T-Production rules can be regarded as a **low-level mutation**, since only terminals will be influenced and the whole sentence structure is kept; changing non-iterative N-Production rules can be regarded as a **mid-level mutation**, since the local structure will be mutated but the whole recursive structure is preserved; changing iterative N-Production rules can be regarded as a **high-level mutation**, since the whole recursive structure will be reconstructed. Based on the grammar used in formal language task A, we design three derivations $\mathbb{G}_t^*$ by injecting mutations into the original $\mathbb{G}_t^+$ in different levels. Examples of different derivations are contained in Appendix E.4.

Coarse $\mathbb{G}_t^*$ (low-level mutation): We omit the non-terminals AGENT, THEME, RECIPIENT, and their corresponding terminals. In other words, the second T-Production rule in Table 1 is removed. Compared with $\mathbb{G}_t^+$ (also $\mathbb{G}_t$), Coarse $\mathbb{G}_t^*$ does not contain detailed arguments of PREDICATE.

Local Reverse (LocalR) $\mathbb{G}_t^*$ (mid-level mutation): The local word order in a sentence is reversed. Specifically, we reverse the right-side word orders of the N-Production rules, except for the rule in the last row of Table 1 which is an iterative one. It means that the order of CLAUSEs (determined by the last rule) remains the same, while the terminals in each CLAUSE are locally reversed.

Nested $\mathbb{G}_t^*$ (high-level mutation): It is obtained by changing the iterative rule (i.e, the last rule in Table 1) from the chain-structure to be nested. The new N-Production rule is "CLAUSE $\twoheadrightarrow$ PREDICATE (AGENT, CONCAT CLAUSE)".

We can also construct $\mathbb{G}_s^*$ from $\mathbb{G}_s^+$ with the same technique except for the coarse one, as the source language must contain enough information to generate targets. Thus, we design a Redundant $\mathbb{G}_s^*$ which contains redundant terminals that are not mapped into targets (detailed in Appendix E.3). We separately change the source and target grammars to derivations and show results in Figure 5.

PLMs can exhibit robustness against mutations in abstract concepts. Results of these derivations with mutations are higher than the Controlled Exp (and Contrast Exp), indicating that even though the learned abstract concepts are only partially matched with that in downstream tasks, the abstraction capability of PLMs can still leverage the similar parts in two sets of mutated abstract concepts.

Abstraction capability is more robust to low-level mutations. Among three kinds of derivations, the low-level mutated ones (Coarse $\mathbb{G}_t^*$ and Redundant $\mathbb{G}_s^*$) perform best, while the high-level mutated ones (Nested $\mathbb{G}_t^*$ and $\mathbb{G}_s^*$) perform worst. This trend implies that the robustness of the abstraction capability decreases as the mutation level of abstract concept rises. This also suggests that matching of high-level abstract concepts should be prioritized when selecting pre-training tasks.

Abstraction capability is more robust to source-side mutations. Comparing the results in Figure 5a and 5b, source-side mutations bring less affects to downstream performance than target-side ones, indicating that PLMs can more robustly reuse source-side abstract concepts.

Redundant information barely affects abstraction. Surprisingly, the performance of Redundant $\mathbb{G}_s^*$ is nearly the same with that of the original $\mathbb{G}_s^+$, which means that injecting redundant information into inputs would hardly affect the learning of abstract concepts. It indicates that the abstract capability of PLM can naturally exclude the influence of irrelevant information.

Figure 6: Performance with different model sizes, data scales and data diversity.

Fuzzy abstract concepts can also be learned and transferred. Compared with the formal grammar discussed above, which can be concretely defined, fuzzy grammar is more free (such as natural language grammar). To explore how would abstraction capability perform on fuzzy grammar, we take natural language sentences for experiments and design different sets by mimicking the *Com.* sub-probe. Detailed designs are described in Appendix G. We report BLEU score in Table 4. It shows that the performance of PLMs on learning fuzzy grammar is also in line with our two expectations.

6.4 GENERAL FACTORS: MODEL SIZE, DATA SCALE, AND DATA DIVERSITY

As explored in previous work, there are some general factors that influence the performance of DNN models (Bommasani et al., 2021; Wei et al., 2022; Henighan et al., 2020), such as model size, data scale, and data diversity. We investigate how these factors influence the learning of abstract concepts.

PLMs exhibit better abstraction with larger model sizes. For T5 models, we take T5-Small, T5-Base, and T5-Large ($\sim$60M, $\sim$220M, and $\sim$770M). For GPT2 models, we take GPT2, GPT2-Medium, and GPT2-Large (117M, 345M, and 762M). Figure 6a and 6b show that larger pre-trained language model has better abstraction capability than the smaller one, as we can observe that the gains from the Controlled Exp to the Main Exp become greater with the model sizes increasing.

Larger data scale and higher data diversity in pre-training helps better abstraction. In our default setting, the train set $\overline{A}$ contains 34k instances. Here, we take the number of instances from 1.7K to 680K and experiment with different model sizes of T5 models. Results in Figure 6c indicate that the model exhibit better abstraction with larger data scales, as the overall performance trend is going up with the data scale increasing, and this trend is consistent with different model sizes.

Higher data diversity in pre-training helps better abstraction. Finally, we explore whether the diversity in data would influence the model to exhibit abstraction. Here, we consider the **terminal diversity** as a perspective of data diversity, i.e., the number of terminals of the grammar. Following Section 4, we only change the number of terminals in $\mathbf{S}_c$ and $\mathbf{S}_C$, increasing from 1 to 128. Figure 6d shows the results under different terminal diversity. The overall performance trend is upward with the terminal diversity increasing for all three model sizes. Further analysis are contained in Appendix F.1.

7 CONCLUSIONS

In this paper, we introduce a systematic probing framework from a transferability perspective to guide the design of probes for abstraction capability. We instantiate this framework as a grammar probe and show strong evidence that two probed PLMs have the abstraction capability. We further analyze this probed capability by investigating several in-depth questions and provide insightful conclusions.

8 ETHICS STATEMENT

A sufficiently robust abstraction capability that can perfectly extract abstract concepts and exclude concrete information in any situation will help deep learning models avoid many potential risks of ethical issues such as social bias and privacy breaches. However, as investigated in this work, the abstraction capability of some commonly used deep learning models may be fragile and can be affected by their training situation. This suggests that the abstraction capabilities of these models are still not reliable enough to naturally avoid these potential ethical issues, and calls for future work to explore ways to strengthen the robustness of the abstraction capabilities of deep learning models.

REFERENCES

Alham Fikri Aji, Nikolay Bogoychev, Kenneth Heafield, and Rico Sennrich. In neural machine translation, what does transfer learning transfer? Association for Computational Linguistics, 2020.

Mikel Artetxe, Sebastian Ruder, and Dani Yogatama. On the cross-lingual transferability of monolingual representations. In Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics, pp. 4623–4637, 2020.

David Barrett, Felix Hill, Adam Santoro, Ari Morcos, and Timothy Lillicrap. Measuring abstract reasoning in neural networks. In International conference on machine learning, pp. 511–520. PMLR, 2018.

Lawrence W Barsalou et al. Perceptual symbol systems. Behavioral and brain sciences, 22(4): 577–660, 1999.

Yaniv Benny, Niv Pekar, and Lior Wolf. Scale-localized abstract reasoning. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pp. 12557–12565, 2021.

Steven Bird, Ewan Klein, and Edward Loper. Natural language processing with Python: analyzing text with the natural language toolkit. " O'Reilly Media, Inc.", 2009.

Rishi Bommasani, Drew A Hudson, Ehsan Adeli, Russ Altman, Simran Arora, Sydney von Arx, Michael S Bernstein, Jeannette Bohg, Antoine Bosselut, Emma Brunskill, et al. On the opportunities and risks of foundation models. arXiv preprint arXiv:2108.07258, 2021.

Erin M Burgoon, Marlone D Henderson, and Arthur B Markman. There are many ways to see the forest for the trees: A tour guide for abstraction. Perspectives on Psychological Science, 8(5): 501–520, 2013.

Xudong Cao, David Wipf, Fang Wen, Genquan Duan, and Jian Sun. A practical transfer learning algorithm for face verification. In Proceedings of the IEEE international conference on computer vision, pp. 3208–3215, 2013.

Xinyun Chen, Chen Liang, Adams Wei Yu, Dawn Song, and Denny Zhou. Compositional generalization via neural-symbolic stack machines. Advances in Neural Information Processing Systems, 33:1690–1701, 2020.

François Chollet. On the measure of intelligence. arXiv preprint arXiv:1911.01547, 2019.

Peter Clark, Oyvind Tafjord, and Kyle Richardson. Transformers as soft reasoners over language. arXiv preprint arXiv:2002.05867, 2020.

Róbert Csordás, Sjoerd van Steenkiste, and Jürgen Schmidhuber. Are neural nets modular? inspecting functional modularity through differentiable weight masks. In International Conference on Learning Representations, 2020.

Kahneman Daniel. Thinking, fast and slow, 2017.

Mengnan Du, Fengxiang He, Na Zou, Dacheng Tao, and Xia Hu. Shortcut learning of large language models in natural language understanding: A survey. arXiv preprint arXiv:2208.11857, 2022.

Robert Geirhos, Jörn-Henrik Jacobsen, Claudio Michaelis, Richard Zemel, Wieland Brendel, Matthias Bethge, and Felix A Wichmann. Shortcut learning in deep neural networks. Nature Machine Intelligence, 2(11):665–673, 2020.

Dedre Gentner and Jose Medina. Similarity and the development of rules. Cognition, 65(2-3): 263–297, 1998.

Fausto Giunchiglia and Toby Walsh. A theory of abstraction. Artificial intelligence, 57(2-3):323–389, 1992.

Ian J Goodfellow, Mehdi Mirza, Da Xiao, Aaron Courville, and Yoshua Bengio. An empirical investigation of catastrophic forgetting in gradient-based neural networks. arXiv preprint arXiv:1312.6211, 2013.

Suchin Gururangan, Swabha Swayamdipta, Omer Levy, Roy Schwartz, Samuel Bowman, and Noah A Smith. Annotation artifacts in natural language inference data. In Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 2 (Short Papers), pp. 107–112, 2018.

Tom Henighan, Jared Kaplan, Mor Katz, Mark Chen, Christopher Hesse, Jacob Jackson, Heewoo Jun, Tom B Brown, Prafulla Dhariwal, Scott Gray, et al. Scaling laws for autoregressive generative modeling. arXiv preprint arXiv:2010.14701, 2020.

John Hewitt and Percy Liang. Designing and interpreting probes with control tasks. In Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP), pp. 2733–2743, 2019.

John Hewitt and Christopher D Manning. A structural probe for finding syntax in word representations. In Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers), pp. 4129–4138, 2019.

Sheng Hu, Yuqing Ma, Xianglong Liu, Yanlu Wei, and Shihao Bai. Stratified rule-aware network for abstract visual reasoning. In Proceedings of the AAAI Conference on Artificial Intelligence, volume 35, pp. 1567–1574, 2021.

Clark L Hull. Quantitative aspects of evolution of concepts: An experimental study. Psychological monographs, 28(1):i, 1920.

Justin Johnson, Bharath Hariharan, Laurens van der Maaten, Li Fei-Fei, C Lawrence Zitnick, and Ross Girshick. Clevr: A diagnostic dataset for compositional language and elementary visual reasoning. In 2017 IEEE Conference on Computer Vision and Pattern Recognition (CVPR), pp. 1988–1997. IEEE Computer Society, 2017.

Ronald Kemker, Marc McClure, Angelina Abitino, Tyler Hayes, and Christopher Kanan. Measuring catastrophic forgetting in neural networks. In Proceedings of the AAAI Conference on Artificial Intelligence, volume 32, 2018.

Daniel Keysers, Nathanael Schärli, Nathan Scales, Hylke Buisman, Daniel Furrer, Sergii Kashubin, Nikola Momchev, Danila Sinopalnikov, Lukasz Stafiniak, Tibor Tihon, et al. Measuring compositional generalization: A comprehensive method on realistic data. In International Conference on Learning Representations, 2019.

Daniel Khashabi, Sewon Min, Tushar Khot, Ashish Sabharwal, Oyvind Tafjord, Peter Clark, and Hannaneh Hajishirzi. Unifiedqa: Crossing format boundaries with a single qa system. In Findings of the Association for Computational Linguistics: EMNLP 2020, pp. 1896–1907, 2020.

Najoung Kim and Tal Linzen. Cogs: A compositional generalization challenge based on semantic interpretation. In 2020 Conference on Empirical Methods in Natural Language Processing, EMNLP 2020, pp. 9087–9105. Association for Computational Linguistics (ACL), 2020.

Philipp Koehn. Europarl: A parallel corpus for statistical machine translation. In Proceedings of machine translation summit x: papers, pp. 79–86, 2005.

George Konidaris. On the necessity of abstraction. Current opinion in behavioral sciences, 29:1–7, 2019.

Sreejan Kumar, Ishita Dasgupta, Raja Marjieh, Nathaniel D Daw, Jonathan D Cohen, and Thomas L Griffiths. Disentangling abstraction from statistical pattern matching in human and machine learning. arXiv preprint arXiv:2204.01437, 2022.

Yuxuan Lai, Chen Zhang, Yansong Feng, Quzhe Huang, and Dongyan Zhao. Why machine reading comprehension models learn shortcuts? In Findings of the Association for Computational Linguistics: ACL-IJCNLP 2021, pp. 989–1002, 2021.

Brenden Lake and Marco Baroni. Generalization without systematicity: On the compositional skills of sequence-to-sequence recurrent networks. In International conference on machine learning, pp. 2873–2882. PMLR, 2018.

Brenden M Lake, Tomer D Ullman, Joshua B Tenenbaum, and Samuel J Gershman. Building machines that learn and think like people. Behavioral and brain sciences, 40, 2017.

Yongjie Lin, Yi Chern Tan, and Robert Frank. Open sesame: Getting inside bert's linguistic knowledge. In Proceedings of the 2019 ACL Workshop BlackboxNLP: Analyzing and Interpreting Neural Networks for NLP, pp. 241–253, 2019.

Chenyao Liu, Shengnan An, Zeqi Lin, Qian Liu, Bei Chen, Jian-Guang Lou, Lijie Wen, Nanning Zheng, and Dongmei Zhang. Learning algebraic recombination for compositional generalization. arXiv preprint arXiv:2107.06516, 2021a.

Qian Liu, Shengnan An, Jian-Guang Lou, Bei Chen, Zeqi Lin, Yan Gao, Bin Zhou, Nanning Zheng, and Dongmei Zhang. Compositional generalization by learning analytical expressions. Advances in Neural Information Processing Systems, 33:11416–11427, 2020.

Qian Liu, Bei Chen, Jiaqi Guo, Morteza Ziyadi, Zeqi Lin, Weizhu Chen, and Jian-Guang Lou. Tapex: Table pre-training via learning a neural sql executor. In International Conference on Learning Representations, 2021b.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. In International Conference on Learning Representations, 2018.

Tyler Millhouse, Melanie Moses, and Melanie Mitchell. Foundations of intelligence in natural and artificial systems: A workshop report. arXiv preprint arXiv:2105.02198, 2021.

Melanie Mitchell. Abstraction and analogy-making in artificial intelligence. Annals of the New York Academy of Sciences, 1505(1):79–101, 2021.

Timothy Niven and Hung Yu Kao. Probing neural network comprehension of natural language arguments. In 57th Annual Meeting of the Association for Computational Linguistics, ACL 2019, pp. 4658–4664. Association for Computational Linguistics (ACL), 2020.

Fabio Petroni, Tim Rocktäschel, Sebastian Riedel, Patrick Lewis, Anton Bakhtin, Yuxiang Wu, and Alexander Miller. Language models as knowledge bases? In Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP), pp. 2463–2473, 2019.

Yada Pruksachatkun, Jason Phang, Haokun Liu, Phu Mon Htut, Xiaoyi Zhang, Richard Yuanzhe Pang, Clara Vania, Katharina Kann, and Samuel Bowman. Intermediate-task transfer learning with pretrained language models: When and why does it work? In Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics, pp. 5231–5247, 2020.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. Language models are unsupervised multitask learners. OpenAI blog, 1(8):9, 2019.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. Journal of Machine Learning Research, 21:1–67, 2020.

Vinay Venkatesh Ramasesh, Aitor Lewkowycz, and Ethan Dyer. Effect of scale on catastrophic forgetting in neural networks. In International Conference on Learning Representations, 2021.

Ryokan Ri and Yoshimasa Tsuruoka. Pretraining with artificial language: Studying transferable knowledge in language models. In Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pp. 7302–7315, 2022.

Kyle Richardson, Hai Hu, Lawrence Moss, and Ashish Sabharwal. Probing natural language inference models through semantic fragments. In Proceedings of the AAAI Conference on Artificial Intelligence, volume 34, pp. 8713–8721, 2020.

Laura Ruis, Jacob Andreas, Marco Baroni, Diane Bouchacourt, and Brenden M Lake. A benchmark for systematic generalization in grounded language understanding. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin (eds.), Advances in Neural Information Processing Systems, volume 33, pp. 19861–19872. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper/2020/file/e5a90182cc81e12ab5e72d66e0b46fe3-Paper.pdf.

Priyanka Sen and Amir Saffari. What do models learn from question answering datasets? In Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP), pp. 2429–2438, 2020.

Radhika Shivhare and Ch Aswani Kumar. On the cognitive process of abstraction. Procedia Computer Science, 89:243–252, 2016.

Alon Talmor, Oyvind Tafjord, Peter Clark, Yoav Goldberg, and Jonathan Berant. Leap-of-thought: Teaching pre-trained models to systematically reason over implicit knowledge. Advances in Neural Information Processing Systems, 33:20227–20237, 2020.

Ian Tenney, Patrick Xia, Berlin Chen, Alex Wang, Adam Poliak, R Thomas McCoy, Najoung Kim, Benjamin Van Durme, Samuel R Bowman, Dipanjan Das, et al. What do you learn from context? probing for sentence structure in contextualized word representations. In International Conference on Learning Representations, 2018.

Pedro A Tsividis, Joao Loula, Jake Burga, Nathan Foss, Andres Campero, Thomas Pouncy, Samuel J Gershman, and Joshua B Tenenbaum. Human-level reinforcement learning through theory-based modeling, exploration, and planning. arXiv preprint arXiv:2107.12544, 2021.

Ivan Vulić, Edoardo Maria Ponti, Robert Litschko, Goran Glavaš, and Anna Korhonen. Probing pretrained language models for lexical semantics. In Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP), pp. 7222–7240, 2020.

Yingxu Wang. Concept algebra: a denotational mathematics for formal knowledge representation and cognitive robot learning. Journal of Advanced Mathematics and Applications, 4(1):61–86, 2015.

Alex Warstadt, Yu Cao, Ioana Grosu, Wei Peng, Hagen Blix, Yining Nie, Anna Alsop, Shikha Bordia, Haokun Liu, Alicia Parrish, et al. Investigating bert's knowledge of language: Five analysis methods with npis. In Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP), pp. 2877–2887, 2019.

Jason Wei, Yi Tay, Rishi Bommasani, Colin Raffel, Barret Zoph, Sebastian Borgeaud, Dani Yogatama, Maarten Bosma, Denny Zhou, Donald Metzler, et al. Emergent abilities of large language models. arXiv preprint arXiv:2206.07682, 2022.

Thomas Wolf, Julien Chaumond, Lysandre Debut, Victor Sanh, Clement Delangue, Anthony Moi, Pierric Cistac, Morgan Funtowicz, Joe Davison, Sam Shleifer, et al. Transformers: State-of-the-art natural language processing. In Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations, pp. 38–45, 2020.

Wlodek W Zadrozny. Abstraction, reasoning and deep learning: A study of the" look and say" sequence. arXiv preprint arXiv:2109.12755, 2021.

Chi Zhang, Feng Gao, Baoxiong Jia, Yixin Zhu, and Song-Chun Zhu. Raven: A dataset for relational and analogical visual reasoning. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pp. 5317–5327, 2019.

This is the Appendix of the paper *Does Deep Learning Learn to Abstract? A Systematic Probing Framework*.

A   DISCUSSIONS

Below are more discussions about our work.

Potential factors that may hinder our probing.   We consider the main factor that could block the use of our probing framework is the catastrophic forgetting problem in deep learning (Goodfellow et al., 2013; Kemker et al., 2018). Since our probing framework relies on the transferability property of abstract concepts, if catastrophic forgetting dominates the learning of downstream tasks, such transferability will hardly take effect and the probing results will fail to reveal the abstraction capabilities. Considering this problem, we utilize the early-stopping strategy (detailed in Appendix) to alleviate catastrophic forgetting. Moreover, our tested pre-trained models are naturally more robust to catastrophic forgetting (Ramasesh et al., 2021).

Better understanding "why does transfer learning work".   Recent success of transfer learning shows that pre-training (or continue pre-training) with similar source tasks can help better solve downstream target task (e.g., question answering (Khashabi et al., 2020; Liu et al., 2021b), face verification (Cao et al., 2013), and general NLU tasks (Pruksachatkun et al., 2020)). Some previous work in cross-lingual transfer learning empirically observed that the model can transfer some knowledge beyond vocabulary (Artetxe et al., 2020; Ri & Tsuruoka, 2022), but they did not consider to exclude the influence from other potential factors. Our results can serve as stronger evidence for the reason to the success of transfer learning, that in addition to transferring some surface patterns, the better target performance can also benefit from similar abstract concepts learned from source tasks.

Limitations and future work.   The main limitations in this work are 1) we do not quantify the abstraction capability and 2) we only test two large pre-trained models. We leave these two points to our future work. Another future direction is to further explore the mechanisms behind abstractions.

B   PRINCIPLES FOR DESIGNING PROBING TASKS

To verify whether the model could learn abstract concepts from task A by assessing $\Delta(A \Rightarrow B)$, we propose the following principles for designing task B:

1) The space of task-specific characteristics of B should be very different from that of A so that the memorization of surface patterns in A is helpless to B.

2) The abstract concepts of B should be the same as that of A so that the abstraction made on A could be reflected with a better performance on B.

3) The fine-tuning-only approach $\Uparrow B$ should be not enough to learn task B perfectly; otherwise, the gain from the abstraction on A would not be noticeable.

Furthermore, to verify that the performance gain on B is from the abstraction on A rather than other factors, we consider a contrast task C of A:

4) The abstract concepts of C should be very different from A (also B), while other latent factors are kept the same such as data scale and pre-training steps.

The consideration of contrast task is similar to *selectivity* (Hewitt & Liang, 2019).

C   AN OPERATION PROBE

The operations semantics (e.g., conjunction) in the Boolean algebra can be regarded as transition functions between the given Boolean variables and corresponding outputs. We want to examine **whether the model can learn the meaning of operations from concrete logical expressions, or just learn superficial correlations from specific sketches in expressions**.

In operation probe, we instantiate the framework with logical expression evaluation (LEE) tasks. We consider **operation semantics in logical expressions as abstract concepts**, and surface patterns (e.g., local string matching) are bounded with operation sketches.

(a) Two kind of sketches.   (b) Transitions of operations.

Figure 7: Four operations and two sketches in our operation probe. (a) shows the chain sketch used in task A and C, and the tree sketch used in $\hat{B} \cup \overline{B}$. Each 'OP' represents one operation. (b) shows the transition results of four operations with different left and right Boolean variables.

Figure 7a shows two kind of sketches: chain sketch and tree sketch. The model trained on chain sketch may learned the meaning of operations (e.g., conjunction of two Boolean variables) or simply memorize some head or tail patterns of strings (e.g., if the head of input string is "False AND (", the output is always "False"). Learning operation semantics can more generally help understand other expressions with different sketches, but memorizing head or tail patterns in chain sketches is helpless or even harmful to understand tree sketches, since these surface patterns can lead to wrong results in different sketches. We give a more specific definition of abstraction in LEE tasks:

Definition 2: Considering an LEE task $L : \mathcal{E}_s \to \mathcal{B}_t$ that the source logical expressions $\mathcal{E}_s$ (with operation semantics $\mathbb{P}_s$ and sketch $\mathbf{K}_s$) are evaluated as Boolean values $\mathcal{B}_t$, and a set of input-output pairs $\overline{L} = \{(e_s^i \to b_t^i)\}^k$ in which e_s^i is an logical expression sampled from $\mathcal{E}_s$ and $b_t^i \in \{True, False\}$ is the evaluation result of e_s^i, the abstraction capability is learning the meanings of operations $\mathbb{P}_s$ during training on $\overline{L}$ rather than memorizing sketch-specific patterns that are bounded with $\mathbf{K}_s$.

Our LLE tasks probe the learning of four logical operations: $\mathbb{P}_s^+ = \{$Conjunction (Conj.), Disconjunction (Disc.), Alternative Denial (Alt.), Joint Denial (Joi.)$\}$. Figure 7b illustrates the transition functions of these operations.. For generating data, each operations in $\mathbb{P}_s^+$ is constantly aligned with one operator (i.e., a concrete string) in $\mathbf{S}_o$. Examples of these sets are contained in Appendix E.2.

Train set $\overline{A}$. We synthesize the data in $\overline{A}$ with $\mathbb{P}_s^+$ and chain sketch. Each expression contains eight operators which are sampled from $\mathbf{S}_o$.

Transfer set $\hat{B}$ and Test set $\overline{B}$. We synthesize the data in $\hat{B} \cup \overline{B}$ with $\mathbb{P}_s^+$ and tree sketch. Each expression contains eight operators which sampled from $\mathbf{S}_o$. When probing a certain operation $\mathbf{p}_s \in \mathbb{P}_s^+$, we limit that the expression in $\hat{B}$ does not contain $\mathbf{p}_s$, while each expression in $\overline{B}$ must contain $\mathbf{p}_s$. To make the model familiar with operators in $\mathbf{S}_o$ or not forget them during further fine-tuning, we supplement $\hat{B}$ with 100 two-operator expressions which cover the full $\mathbf{S}_o$. Empirically, as DNN models can be easily influenced by the statistical bias in label distributions, we balance the 'True' and 'False' examples during sampling.

Contrast set $\overline{C}$. The operators and sketch in $\overline{C}$ are kept the same with $\overline{A}$, but each operator in $\mathbf{S}_o$ is aligned with another set of logical operations $\mathbb{P}_s^- = \{$Material Implication, Converse Implication, Material Non-implication, Converse Non-implication$\}$. The transition functions of these operations are listed in Appendix E.2.

Results of our operation probe is shown in Table 5.

D ABSTRACT CONCEPTS ARE MODULARIZED IN PLMS

To supplement our analysis on abstract attention heads, here we provide our detailed explorations to identify the modulars in PLMs that store abstract concepts in our probes. Our explorations are based on the following property and assumption.

Property: Forgetting of Abstract Concepts. Consider the Main Exp $A \Rightarrow B$ that task A and B share the abstract concepts but do not share task-specific knowledge. After fully fine-tuning on

Table 5: Results in our operation probe.

Probe	Model	Sub-Probe	Controlled Exp $\Uparrow B$	Main Exp $A \Rightarrow B$	Contrast Exp $C \Rightarrow B$
Operation	T5	Avg.	70.1	88.9 (+18.8)	71.2 (+1.1)
		Conj.	63.3	90.8	65.3
		Disc.	58.9	84.8	72.8
		Alt.	79.1	90.7	72.6
		Joi.	79.2	89.2	74.3
	GPT2	Avg.	64.7	76.3 (+11.6)	64.0 (-0.7)
		Conj.	61.8	78.6	61.1
		Disc.	59.8	72.5	64.1
		Alt.	69.0	78.6	65.4
		Joi.	68.3	75.3	65.3

task B, the model's parameters will somehow over-fit the task-specific knowledge in task B and the abstract concepts stored in these parameters will be partially forgotten.

Assumption: Identifying the Modularization of Abstraction by Freezing Parameters. If a modular in the model individually store a part of abstract concepts, these parameters can be directly reused in new tasks without further fine-tuning. Furthermore, considering the property above, freezing this abstract modular can avoid the forgetting of abstract concepts, resulting in the performance improvement in Main Exp $A \Rightarrow B$.

Based on this assumption, to identify whether abstract concepts are modularized in some parameters, we partially freeze the model in a coarse-to-fine manner. The following experiments are conducted on one of the three pre-training terminal sets. First, we freeze each layer in the model, showing in Figure 8. We find that the last layer in encoder and the first layer in decoder modularize part of abstract concepts. Furthermore, we freeze these two layers in our Contrast Exp $C \Rightarrow B$ and find no improvements in Figure 9a, indicating that the improvement of freezing these two layers comes from keep abstract concepts.

In next step, we try to identify the abstract concepts are stored in attention layers or FF layers. We separately freeze the attention sub-layer and FF sub-layer in the last encoder layer and first decoder layer. Figure 9b shows that attention layers take more responsibility for storing abstract concepts.

Then, we analyze whether these abstract concepts are modularized in some attention heads or averaged in the whole attention layers. Our investigation in Section 6.2 finds that the abstract concepts are centralized in some middle-layer attention heads. Based on the results in Figure 4, we freeze the top 36 heads to further verify that they are responsible for storing abstract concepts. Results in Table 6 indicate that abstract concepts are modularized in this small part of attention heads.

Figure 8: Freeze 24 layers separately in $A \Rightarrow B$.

E EXAMPLES IN OUR DESIGNED TASKS

Here, we list some examples in our designed probing tasks. The full sets are contained in our Supplementary Material.

(a) Freeze layers in $C \Rightarrow B$.

(b) Separately freeze attention and FF in $A \Rightarrow B$.

Figure 9: Further explore the modularity in the middle two layers.

Table 6: Supplement to Table 3. Freeze a set of abstract heads and fine-tune.

	Fine-Tuning
Baseline $A \Rightarrow B$	92.8
+Freeze Abstract Heads	96.6 (+3.8)
+Freeze Random Heads	92.9
-Prune Abstract Concepts	13.6
Baseline $C \Rightarrow B$	13.9
+Freeze Abstract Heads	14.4

E.1 GRAMMAR PROBE

Table 7 and 8 shows examples in *Com.* and *Mod.* sub-probes in grammar probe, respectively.

E.2 OPERATION PROBE

Table 9 lists the operation behind each symbol, and Table 10 shows examples in Conj. sub-probe in operation probe. Figure 10 illustrates the transitions of operations used in contrast task in operation probe.

Table 7: Examples in different sets in *Com.* sub-probe in grammar probe. The terminal NONE in target side is omitted to more clearly show the structure of the target example.

Set	Side	Example
Train Set	Source	Soke incurve huave the soon upon huave a ban bibb huave acetum goladar .
	Target	INCURVE (SOKE) LG UPON (SOON) LG BIBB (BAN) LG GOLADAR (ACETUM)
Transfer Set	Source	Emma liked that a girl saw .
	Target	LIKE (EMMA) CCOMP SEE (GIRL)
Test Set	Source	Emma admired that Daniel liked that James meant that a lion froze .
	Target	ADMIRE (EMMA) CCOMP LIKE (DANIEL) CCOMP MEAN (JAMES) CCOMP FREEZE (LION)
Contrast Set	Source	Soke incurve huave the soon upon huave a ban bibb huave acetum goladar .
	Target	(ACETUM) GOLADAR LG (BAN) BIBB LG (SOON) UPON LG (SOKE) INCURVE

E.3 REDUNDANT DESIGNS

For Redundant $\mathbb{G}_s^*$, we supplement the second T-Production rule in Table 1 as "sub / direct-obj / indirect-obj ⇀ $\mathbf{S}_{adj}$ $\mathbf{S}_n$". Terminals in $\mathbf{S}_{adj}$ can re regarded as adjectives for $\mathbf{S}_n$. These terminals are only contained in the source side and no terminals in target side are aligned with them. Table 12 shows an example in Redundant $\mathbb{G}_s^*$.

E.4 DERIVATIONS

Here we show examples of different derivations of original grammars. Table 11 shows examples in different $\mathbb{G}_t^*$. The terminal 'NONE' is omitted.

Table 8: Examples in different sets in mod. sub-probe in grammar probe.

Set	Side	Example
Train Set	Source	Safe above the poddy cord the soon a pial .
	Target	CORD (ABOVE (SAFE , PODDY) , PIAL , SOON)
Transfer Set	Source	Emma ate the ring beside a bed .
	Target	EAT (EMMA , BESIDE (RING , BED) , NONE)
Test Set	Source	The baby on a tray in the house screamed .
	Target	SCREAM (ON (BABY , IN (TRAY , HOUSE)) , NONE , NONE)
Contrast Set	Source	Safe above the poddy cord the soon a pial .
	Target	(SOON , PIAL , (PODDY , SAFE) ABOVE) CORD

Table 9: Symbols and operations in different tasks in operation probe.

Symbol	Operation in A and B	Operation in C
a1	Conjunction	Material Non-implication
b2	Alternative Denial	Material Implication
c3	Disjunction	Converse Non-implication
d4	Joint Denial	Converse Implication

F MORE EXPERIMENTAL RESULTS

We present additional experimental results to supplement our probing and analysis.

F.1 TERMINAL DIVERSITY

Interestingly, in Figure 6d, we observe that for all three models, their performances achieve the peak before rising to 128 terminals and then keep oscillating. We speculate that their performances are bounded by the limited data scale, as we control the data scale as 34K instances when increasing the terminal diversity. To examine our speculation, we conduct another experiment on T5-Base that pre-training on 680K instances with 128 terminals, achieving an average accuracy rate of 93.5%. This performance is higher than the result after pre-training on 680K instances with 32 terminals (89.2%) and higher than the best average accuracy of T5-Base in Figure 6d (88.4%), suggesting that higher data diversity should be equipped with a larger data scale.

F.2 MULTI-GRAMMAR PRE-TRAINING

Before this section, we consider the setup in which we only see one pair of input and output grammars during pre-training. This section explores whether multi-grammar pre-training would influence the model to exhibit abstraction. Here, we consider two cases: can or can not access the golden grammar. The golden grammar is the grammar used in the downstream task. For the multi-grammar pre-training, we assemble different target grammars in Section 6.3 while keep the source grammar. During generating pre-training data with more than one target grammar, for each instance, we add a prefix (chosen from *original*, *coarse*, *localreverse*, *nest*, and *reverse*) at the beginning of the source tokens, guiding the model which target grammar it should use. Table 13 shows the results with different ensemble grammars.

First, consider that we have no access to the golden grammar. We take the target grammar that performs the best in Section 6.3, Coarse $\mathbb{G}_t^*$, as the single-grammar baseline. Table 13 shows that augmenting the Coarse $\mathbb{G}_t^*$ with other target grammars can always perform better than the single grammar. Even augmenting with the Reverse $\mathbb{G}_t^*$ from the contrast task can bring a slight gain (1.4% accuracy). It indicates that even though the model has no access to the golden abstract concepts, **increasing the diversity of abstract concepts can make the model better aware of the existence of abstract concepts**. This awareness can be regarded as a higher level of abstraction ability.

Then, considering that the model has access to the golden grammar, the downstream task performance is lower than only pre-training on the golden grammar (accuracy 88.2%). Therefore, augmenting

Table 10: Examples in different sets in operation probe.

Set	Side	Example
Train Set	Source	False c3 (((False a1 (((False b2 (True d4 True)) d4 True) d4 True)) d4 False) b2 False)
	Target	True
Transfer Set	Source	((False c3 (False b2 False)) b2 True) d4 (True b2 ((False b2 (False b2 False)) c3 True))
	Target	True
Test Set	Source	(True b2 ((False a1 False) d4 False)) a1 (False c3 (((True a1 True) c3 True) a1 True))
	Target	False
Contrast Set	Source	False c3 (((False a1 (((False b2 (True d4 True)) d4 True) d4 True)) d4 False) b2 False)
	Target	False

Figure 10: Transitions of operations used in contrast task in operation probe.

other similar abstract concepts would confuse the model and make it hard to choose which concepts should be used for the downstream task.

G   FUZZY GRAMMAR

The abstract concepts discussed in grammar probe in Section 4 can be concretely defined, but in many application scenarios, abstract concepts can be fuzzy (e.g., natural language grammar). Here, we want to examine whether models can learn fuzzy grammar or just can recognize the concrete one. We take natural language sentences for experiments and design different sets by mimicking the *Com.* sub-probe in our grammar probe.

Data in our fuzzy grammar probe is taken from Europarl v7 Koehn (2005), a large parallel corpus for machine translation . For the probing on natural language data, we can not guarantee to satisfy the requirements in our framework perfectly, as the grammar of the natural language is hard to be controllable as the formal language. We describe the instantiation of different sets as following.

Train set $\overline{A}$. We take the German-to-French (De-Fr) sentence paris as $\overline{A}$.

Transfer set $\hat{B}$ and Test set $\overline{B}$. We take English-to-Romanian (En-Ro) as the probing task B. As both German and English are belong to the West Germanic language branch while both French and Romanian are belong to Italic branch, the abstract grammars used in De-Fr and En-Ro have some similarities. To satisfy that the $\Uparrow B$ performs poorly, we limit the $\hat{B}$ with only short sentences (15.7/13.8 words in En/Ro sentences in average) while $\overline{B}$ with only long sentences (78.0/74.4 words in En/Ro sentences in average). It means that the model can learn most of the lexicons from $\hat{B}$ but can not be aware of the grammars of long sentences.

Contrast set $\overline{C}$. Mimicking the construction of $\overline{C}$ in the formal language task, we also reverse the word order in the target language of $\overline{A}$.

Table 4 shows the performance of two models on natural language data. These results indicate that fuzzy grammar in natural language data can also be learned and transferred by the two PLMs. In addition, as this setting can also be regarded as a length generalization problem, the low $\Delta(C \Rightarrow B)$ further confirm that **our probing results benefit from learning abstract concepts rather than surface patterns (i.e., length distribution)**.

Table 11: Examples in different $\mathbb{G}_t^*$.

Derivation	Target Example
Coarse	CLAN ( ) LG INCURVE ( ) LG UPON ( )
LocalR	(BAN) CLAN LG (SOKE) INCURVE LG (BIBB, GOALDER, SOON) UPON
Nested	CLAN (BAN, LG INCURVE (SOKE, LG UPON (SOON, GOALDER, BIBB)))

Table 12: Examples in Redundant $\mathbb{G}_s^*$. Gray terminals are redundant that would not be mapped to targets.

Derivation	Source Example
Redundant	A angry pial was ozophen to zogo by odd dermestes .

H   TRY TO MEASURE ABSTRACTION CAPABILITY

As mentioned in Section A that one limitation in our probing is the lack of a metric that can quantitatively measure the abstraction ability. Thus, we can not compare the abstraction ability of two models with different architectures. Here, we try to design such a metric to compare the abstraction ability of T5-Base, with $\sim$220M parameters, and GPT2-Medium, with 345M parameters.

In the beginning, we want to clarify that this metric is just for primary exploration, as it is based on a strong assumption that can not be satisfied in all situations.

Assumption: We assume that the performance score of a certain task (such as accuracy and BLEU score) can linearly reflect the ability of the model to solve this task.

It means that, for instance, improving the accuracy from 90% to 100% is not harder than improving from 40% to 50%. Apparently, this assumption does not suit all tasks and performance scores (even the tasks and scores in our probing). But it does not influence the comparison between T5-Base and GPT2-Medium. The reason will be discussed later.

Intuitively, we consider the contribution of abstract concepts to overall performance as a measure of abstraction ability, that is,

$$\text{MoA} = \frac{\text{score}_a}{\text{score}_f}, \tag{2}$$

in which the MoA means the **M**etric **o**f **A**bstraction, score_f means the full performance score on a certain task without limiting the training data, and score_a means the part of the score contributed by the abstract concepts. Following our probing framework, we consider the score_a as the relative gain from $\Uparrow B$ to $A \Rightarrow B$. Furthermore, considering the influence of other factors which is reflected by $C \Rightarrow B$, we design the score_a as:

$$\text{score}_a = \text{score}(A \Rightarrow B) - \max[\text{score}(\Uparrow B), \text{score}(C \Rightarrow B)], \tag{3}$$

in which $\text{score}()$ represents the performance score of a certain procedure, and $\max[\text{score}(\Uparrow B), \text{score}(C \Rightarrow B)]$ means to choose the maximum performance score between $\Uparrow B$ and $C \Rightarrow B$. For the full performance score in the denominator in Equation 2, we evaluate the model performance on $\overline{B}$ after (only) fine-tuning on the full set $\tilde{B}$, which is sampled in the same distribution of $\overline{B}$ (rather than a limited distribution of $\hat{B}$). We denote this procedure as $\Uparrow \tilde{B}$. Thus, the metric in Equation 2 can be formalized as:

$$\text{MoA} = \frac{\text{score}(A \Rightarrow B) - \max[\text{score}(\Uparrow B), \text{score}(C \Rightarrow B)]}{\text{score}(\Uparrow \tilde{B})}. \tag{4}$$

Table 14 shows MoA for two models on grammar probe and fuzzy grammar probe, and lists the scores required to calculate MoA. On each task, MoA of T5-Base is higher than that of GPT2-Medium. Furthermore, during calculating MoA, the baseline score $\max[\text{score}(\Uparrow B), \text{score}(C \Rightarrow B)]$ of T5-Base is always higher than that of GPT2-Medium. As it is harder for the model to improve the accuracy and BLEU scores on these tasks from a relatively higher baseline, MoA can just underestimate the abstract ability of T5-Base. Therefore, we can roughly conclude that the abstraction ability of T5-Base is higher than GPT2-Medium.

Table 13: Downstream performance under different multi-grammar settings.

	Grammars				Accuracy
	Reverse	Nest	LocalR	Coarse	
				✓	41.6
	✓			✓	43.0
Without Golden Grammar		✓		✓	46.4
			✓	✓	54.6
	✓	✓	✓	✓	55.3
With Golden Grammar	✓	✓	✓	✓	74.0

Table 14: MoA of two models on both grammar probe and fuzzy grammar probe and the scores required to calculate MoA. T5 and GPT2 are T5-Base and GPT2-Medium, respectively.

Probe	Score	Model	Scores of Procedures				MoA
			$A \Rightarrow B$	$\Uparrow B$	$C \Rightarrow B$	$\tilde{\Uparrow} B$	
Grammar	Accuracy (%)	T5	88.2	23.1	15.4	95.7	0.68
		GPT2	48.2	1.9	2.6	93.2	0.49
Fuzzy Grammar	BLEU Score	T5	35.1	24.0	26.2	41.9	0.21
		GPT2	21.0	16.4	11.6	42.2	0.11

I COMPARISON WITH PREVIOUS NEGATIVE RESULTS

Some previous work demonstrated that neural models could not learn abstract concepts (Liu et al., 2020; Chen et al., 2020; Liu et al., 2021a; Chollet, 2019; Mitchell, 2021; Zadrozny, 2021). Our probing results shed some light that neural models, especially PLMs, exhibit abstraction ability to some extent. Compared with previous work, two points could lead to different conclusions.

The first point is the probing methodology. In all works (including ours), the basic idea of probing abstraction is to separate it with memorization. To implement this idea, previous work has almost always involved designing a special probing task in which memorization of the train set is helpless to solve the test set. However, such an implementation constraints the generation of the train set, which could bring some biases or limitations in training data. To overcome these biases or limitations, the model should have some other abilities more than abstraction, such as reasoning and systematic generalizability. Therefore, the previous disappointing results may have been caused by the lack of other abilities rather than abstraction.

The second point is the test model. Some previous work probed the vanilla Transformer or LSTM while we take the pre-trained language models. We suppose that the model may acquire better abstraction ability from the pre-training corpus, and can better exhibit this ability with larger model sizes.

J DETAILS OF EXPERIMENTS

J.1 DATA

We show more details about the sets described in Section 4, including data scales, average input lengths and average output lengths.

For the target side grammar of our formal language tasks, we mentioned in Section 4 that we change the original target grammar of COGS to be chain-structured. In Table 16, we list some examples with the original target grammar and the new chain-structured grammar. First, to distinguish the input and output tokens, we capitalize all output tokens (e.g., from "rose" to "ROSE"). Second, we replace the variables (e.g., "x _ 1") in the original grammar with its corresponding terminals (e.g., "ROSE"). Then, we group the terminals of AGENT (e.g., "DOG"), THEME (e.g., "ROSE") and RECIPIENT with their corresponding terminal of PREDICATE (e.g., "HELP") and combine this group of terminals in a function format, i.e., "PREDICATE (AGENT, THEME, RECIPIENT)". If the predicate is not equipped with an agent, theme or recipient in the original grammar, the corresponding new non-terminals (i.e., AGENT, THEME and RECIPIENT, respectively) in the function format above will be filled with the terminal NONE (e.g., "HELP (DOG, ROSE, NONE)"). For simplicity, we omitted NONE in Table 1, Table 7, and Table 11. Such a function format is the minimum unit of a

Table 15: Data scales, average input lengths, and average output lengths of different sets in our probing.

| Probe | A | | | $\hat{B}$ | | | $\overline{B}$ | | | $\overline{C}$ | | |
	Data Scale	Avg Input Len	Avg Output Len	Data Scale	Avg Input Len	Avg Output Len	Data Scale	Avg Input Len	Avg Output Len	Data Scale	Avg Input Len	Avg Output Len
Grammar	34,175	16.8	29.9	24,155	9.5	10.5	1,002	34.4	76.6	34,175	16.8	29.9
Operation	100,000	16.8	1	20,000	9.5	1	1,000	34.4	1	100,000	16.8	1
Fuzzy Grammar	400,000	38.9	40.8	200,000	15.7	13.8	1,004	78.0	74.4	400,000	38.9	40.8

Table 16: Examples with the original grammar and the new chain-structured grammar.

Original Target Grammar	Chain-Structured Target Grammar
rose (x _ 1) AND help . theme (x _ 3 , x _ 1) AND help . agent (x _ 3 , x _ 6) AND dog (x _ 6)	HELP (DOG, ROSE, NONE)
* captain (x _ 1) ; eat . agent (x _ 2 , x _ 1)	EAT (CAPTION, NONE, NONE)
* dog (x _ 4) ; hope . agent (x _ 1 , Liam) AND hope . ccomp (x _ 1 , x _ 5) AND prefer . agent (x _ 5 , x _ 4)	HOPE (LIAM, NONE, NONE) CCOMP PREFER (DOG, NONE, NONE)

CLAUSE. Finally, each CLAUSE is concatenated with another CLAUSE by the terminal CCOMP (e.g., "HOPE (LIAM, NONE, NONE) CCOMP PREFER (DOG, NONE, NONE)").

J.2 PROCEDURE

Training Each pre-training takes 100,000 steps, and the final-step checkpoint is used for fine-tuning. Each fine-tuning takes 100,000 steps, and the checkpoints for every 10,000 steps are saved.

Evaluation We take an early-stopping strategy in our evaluation to avoid catastrophic forgetting. First, each checkpoint saved during fine-tuning is evaluated on the held-out dev set. We choose the first checkpoint that achieves the best dev score for testing. For formal language tasks, we utilize the constraint decoding strategy that the model can only generate the words in the vocabulary.

Compute and Resources We majorly use Tesla-V100-16GB GPUs for training and evaluation, except for the experiments on T5-Large or GPT2-Large, which require Tesla-V100-32GB GPUs. On average, one pre-training takes ~15 GPU hours, one fine-tuning takes ~15 GPU hours (including saving checkpoints), and one testing takes ~2 GPU hours (as test cases are very long).

J.3 HYPERPARAMETERS

Table 17: Hyperparameters for training and testing.

| | Grammar Probe | | Operation Probe | |
	T5	GPT	T5	GPT2
Learning Rate	1e-5	1e-5	1e-4	1e-4
Weight Decay	0.01	0.01	0.01	0.01
Batch Size	8	8	8	8
Label Smooth	0.1	0.1	0.1	0.1
Max Input Len	1024	-	1024	-
Max Output Len	1024	-	1024	-
Max Total Len	-	1024	-	1024
Beam Size	5	5	1	1

Hyperparameters used for training and testing are listed in Table 17.

J.4 DEFINITION OF PERPLEXITY (PPL)

Th following equation explain how to calculate PPL in Equation 1,

$$\text{PPL}(l_t^i | l_s^i; \theta) = \exp[-\frac{1}{|l_t^i|} \sum_j \log p_\theta(l_t^{i,j} | l_s^i, l_t^{i,<j})]. \tag{5}$$

J.5 RESULTS

We list the detailed results that are plotted in the figures (i.e., Figure 5 and Figure 6), including the average scores, minimum scores, maximum scores, and standard deviations for all replicate experiments.

Table 18: Detailed results for Figure 5.

| | Input Grammar | | | | | Output Grammar | | | | |
	Original	Redundant	LocalR	Nest	Reverse	Original	Coarse	LocalR	Nest	Reverse
Avg	88.2	86.0	76.2	55.5	15.0	88.2	41.6	33.5	29.1	15.4
Min	72.8	68.3	70.4	49.1	13.0	72.8	34.5	19.8	27.7	12.1
Max	96.9	95.6	80.6	61.1	20.1	96.9	50.8	38.7	31.7	19.2
Std	8.5	10.2	4.2	4.3	2.5	8.5	4.9	6.7	1.3	2.4

Table 19: Detailed results for Figure 6a and 6b.

| | Main Exp | | | | | | Controlled Exp | | | | | |
	T5-Small	T5-Base	T5-Large	GPT2	GPT2-Medium	GPT2-Large	T5-Small	T5-Base	T5-Large	GPT2	GPT2-Medium	GPT2-Large
Avg	34.4	88.2	94.0	3.5	48.9	68.7	9.0	23.1	19.5	0.0	2.0	3.4
Min	20.7	72.8	83.2	0.0	23.9	47.2	3.0	22.6	17.8	0.1	1.1	3.1
Max	47.4	96.9	97.2	12.4	63.8	85.7	6.0	23.5	21.1	0.2	2.9	3.6
Std	9.8	8.5	4.9	4.4	14.5	13.7	3.0	0.5	1.7	0.1	0.9	0.3

Table 20: Detailed results for Figure 6c.

(a) T5-Large

| | Data Scale (T5-Large) | | | | | | | |
	1.7K	3.4K	6.8K	17K	34K	68K	170K	680K
Avg	90.4	96.7	96.7	92.3	94.0	98.8	97.6	98.9
Min	73.5	96.0	94.2	73.6	83.2	98.0	92.4	96.9
Max	97.1	98.1	98.5	98.7	97.2	99.3	99.8	99.7
Std	10.5	0.9	1.7	10.8	4.9	0.5	3.0	1.1

(b) T5-Base

| | Data Scale (T5-Base) | | | | | | | |
	1.7K	3.4K	6.8K	17K	34K	68K	170K	680K
Avg	75.1	82.8	84.0	85.0	88.2	82.0	87.0	89.2
Min	61.5	74.0	69.2	79.3	72.8	74.8	82.5	76.9
Max	90.8	88.7	94.4	97.2	96.9	92.3	92.7	94.4
Std	10.0	4.9	8.5	6.3	8.5	6.3	3.8	7.6

(c) T5-Small

| | Data Scale (T5-Small) | | | | | | | |
	1.7K	3.4K	6.8K	17K	34K	68K	170K	680K
Avg	28.3	31.9	26.1	27.3	34.4	40.5	38.7	39.4
Min	27.4	11.5	16.1	21.2	20.7	19.7	23.5	29.7
Max	29.2	50.5	36.2	33.7	47.4	62.9	50.9	56.0
Std	0.9	15.6	9.2	4.1	9.8	19.0	9.9	9.5

Table 21: Detailed results for Figure 6d.

(a) T5-Large

| | Terminal Diversity (T5-Large) | | | | | | | |
	1	2	4	8	16	32	64	128
Avg	90.5	93.3	96.4	97.9	98.1	94.0	96.9	94.2
Min	79.7	85.9	95.6	95.9	97.1	83.2	93.2	87.3
Max	97.9	97.4	98.1	98.9	99.1	97.2	98.1	99.0
Std	6.9	3.9	0.9	1.0	0.7	4.9	1.7	4.6

(b) T5-Base

| | Terminal Diversity (T5-Base) | | | | | | | |
	1	2	4	8	16	32	64	128
Avg	66.5	72.5	76.3	85.3	88.4	88.2	86.4	84.2
Min	53.0	61.4	69.2	71.6	75.7	72.8	54.6	71.1
Max	79.4	86.1	92.2	94.1	96.4	96.9	93.7	97.5
Std	9.8	10.1	7.8	9.4	7.6	8.5	15.2	10.7

(c) T5-Small

| | Terminal Diversity (T5-Small) | | | | | | | |
	1	2	4	8	16	32	64	128
Avg	23.5	24.2	23.3	26.6	29.3	34.4	26.7	32.8
Min	3.3	12.6	10.2	16.1	21.0	20.7	22.6	24.7
Max	35.8	34.5	38.6	41.0	36.1	47.4	32.4	47.5
Std	10.1	7.5	8.3	9.2	4.9	9.8	4.3	9.6