THOMAS: Trajectory Heatmap Output with learned Multi-Agent Sampling

Abstract

In this paper, we propose THOMAS, a joint multi-agent trajectory prediction framework allowing for efficient and consistent prediction of multi-agent multi-modal trajectories. We present a unified model architecture for fast and simultaneous agent future heatmap estimation leveraging hierarchical and sparse image generation. We demonstrate that heatmap output enables a higher level of control on the predicted trajectories compared to vanilla multi-modal trajectory regression, allowing to incorporate additional constraints for tighter sampling or collision-free predictions in a deterministic way. However, we also highlight that generating scene-consistent predictions goes beyond the mere generation of collision-free trajectories. We therefore propose a learnable trajectory recombination model that takes as input a set of predicted trajectories for each agent and outputs its consistent reordered recombination. We report our results on the Interaction multi-agent prediction challenge and rank 1^{st} on the online test leaderboard.

1 Introduction

Motion forecasting is an essential step in the pipeline of an autonomous driving vehicle, transforming perception data into future prediction which are then leveraged to plan the future moves of the autonomous cars. The self-driving stacks needs to predict the future trajectories for all the neighbor agents, in a fast and coherent way.

The interactivity between agents plays an important role for accurate trajectory prediction. Agents need to be aware of their neighbors in order to adapt their speed, yield right of way and merge in neighbor lanes. To do so, different interaction mechanisms have been developed, such as social pooling (Alahi et al., 2016; Lee et al., 2017; Deo & Trivedi, 2018), graphs (Salzmann et al., 2020; Zeng et al., 2021) or attention (Mercat et al., 2020; Messaoud et al., 2020; Luo et al., 2020; Gao et al., 2020; Liang et al., 2020; Ngiam et al., 2021). These mechanisms allow agents to look at and share features with neighbors, to take them into account in their own predictions.

Multi-modality is another very important aspect of the possible future trajectories. A car can indeed chose to turn right or left, or decide to realise a certain maneuver in various ways. Uncertainty modeled as variance of Gaussians is insufficient to model these multiple cases, as it can only represent a continuous spread and can't show multiple discrete possibilities. Therefore, current state-of-the-art produces not one but K possible trajectories for each agent predicted, and most recent benchmarks (Caesar et al., 2020; Chang et al., 2019; Zhan et al., 2019; Ettinger et al., 2021)include multi-modality in their metrics, taking only the minimum error over a predicted set of K trajectories.

However, up until very recently and the opening of multi-agent joint interaction challenges (Ettinger et al., 2021; Zhan et al., 2021), no motion forecasting prediction datasets were taking into account the coherence of modalities between different agents predicted at the same time. As a result, the first predicted modality of a given agent could crash with the first predicted modality of another agent without any check.

Our THOMAS model encodes the past trajectories of all the agent presents in the scenes, as well as the HD-Map lanelet graph, and merges their information using self and cross attention. It then predicts for each agent a sparse heatmap representing the future probability distribution at a fixed timestep in the future. A deterministic sampling algorithm then iteratively selects the best K tra-

jectory endpoints according to the heatmap for each agent. These endpoints are recombined to be scene-consistent by the THOMAS model, and full trajectories are then generated for each endpoint.

Our contributions are summarized as follow:

- We present an efficient graph-based model enabling fast and efficient multi-agent future motion estimation
- We propose a collision-aware endpoint sampling from the heatmap that takes into account agent collisions
- We design a novel recombination model able to recombine the sampled endpoints in order to obtain scene-consistent trajectories across the agents

2 RELATED WORK

Learning-based models have quickly overtaken physics-based methods for trajectory prediction, as the sequential nature of trajectories is a logical application for recurrent architectures (Alahi et al., 2016; Altché & de La Fortelle, 2017; Lee et al., 2017; Mercat et al., 2020; Khandelwal et al., 2020), and convolutional layers can easily be applied to bird-view rasters of the map context (Lee et al., 2017; Tang & Salakhutdinov, 2019; Cui et al., 2019; Hong et al., 2019; Salzmann et al., 2020; Chai et al., 2020; Gilles et al., 2021b), benefiting from the latest progresses in computer vision. Surrounding HD-Maps, usually formalized as connected lanelets, can also be encoded using Graph Neural Networks (Gao et al., 2020; Liang et al., 2020; Zeng et al., 2021; Gilles et al., 2021a), in order to get a more compact representation closer to the trajectory space. Finally, some point-based approaches (Ye et al., 2021) can be applied in a broader way to trajectory prediction, as both lanes and trajectories can be considered as ordered set of points.

Multi-modality in prediction can be obtained simply through a multiple prediction head in the model (Cui et al., 2019; Liang et al., 2020; Ngiam et al., 2021; Deo et al., 2021). However some methods rather adopt a candidate-based approach, where potential endpoints are obtained either from anchor trajectories obtained through clustering (Chai et al., 2020; Phan-Minh et al., 2020) or a model-based generator (Song et al., 2021). Other approaches use a broader set of candidates from the context graph (Zhang et al., 2020; Zhao et al., 2020; Zeng et al., 2021; Kim et al., 2021) or a dense grid around the target agent (Deo & Trivedi, 2020; Gu et al., 2021; Gilles et al., 2021b;a). Another family of approaches use variational inference to generate diverse predictions, through latent variables (Lee et al., 2017; Rhinehart et al., 2018; Tang & Salakhutdinov, 2019; Casas et al., 2020) or GAN (Gupta et al., 2018; Rhinehart et al., 2018; Sadeghian et al., 2019) but the sampling of these trajectories is random and doesn't provide any probability value for each sample.

While very little work has directly tackled multi-agent prediction and evaluation so far, multiple methods hint at the ability to predict multiple agents at the same time (Liang et al., 2020; Zeng et al., 2021) even if they then focus on a more single-agent oriented framework. SceneTransformer (Ngiam et al., 2021) repeats each agent features across possible modalities, and performes self-attention operations inside each modality before using a joint loss to train a model and evaluate on the WOMD (Ettinger et al., 2021) interaction track, but this evaluation focuses on dual agent prediction and doesn't broaden to a large number of agents at the same time. ILVM (Casas et al., 2020) uses scene latent representations conditioned on all agents to generate scene-consistent samples, but its variational inference doesn't provide confidence score for each modality . AIR^2 (Wu & Wu, 2021) extends Multipath (Chai et al., 2020) and produces a cross-distribution for two agents along all possible trajectory anchors, but it scales exponentially with the number of agents, making impractical for a real-time implementation that could encounter more than 10 agents at the same time.

3 METHOD

Our goal is to predict the future T timesteps of A agents using their past history made of H timesteps and the HD-Map context. Similar to recent work (Zhao et al., 2020; Zeng et al., 2021; Gu et al., 2021), we will divide the problem into goal-based prediction followed by full trajectory reconstruction. Our prediction pipeline is displayed in Fig. 1. We first encode each agent trajectory and the

Figure 1: Illustration of the THOMAS multi-agent prediction pipeline

HD-Map context graph into a common representation. We then decode a future probability heatmap for each agent in the scene, which we sample heuristically to maximize coverage. Finally, we recombine the sampled endpoints into scene-consistent modalities across agents, and build the full trajectories for each agent.

3.1 MODEL BACKBONE

3.1.1 GRAPH ENCODER

We use the same encoder as the GOHOME model (Gilles et al., 2021a). The agent trajectories are encoded though $TrajEncoder$ using a 1D CNN followed by a UGRU recurrent layer, and the HD-Map is encoded as a lanelet graph using a GNN $GraphEncoder$ made of graph convolutions. We then run cross-attention $Lanes2Agents$ to add context information to the agent features, followed by self-attention $Agents2Agents$ to observe interaction between agents. The final result is an encoding F_a for each agent, where history, context and interactions have been summarized. This encoding F_a is used in the next decoder operations, but is also stored to be potentially used in modality recombination described in Sec. 3.2.2. The resulting architecture of these encoding operations is illustrated in the first half of Fig. 2.

3.1.2 HIERARCHICAL GRID DECODER

Our aim here is to decode each agent encoding into a heatmap representing its future probability distribution at prediction horizon T. Since we create this heatmap for each agent in the scene, the decoding process has to be fast so that it can be applied to a great number of agents in parallel. HOME (Gilles et al., 2021b) generates a heatmap through CNN operations, but these are costly and don't scale well with prediction range. DenseTNT (Gu et al., 2021) uses attention on dense gridpoints sampled arround the lanes only, while GOHOME (Gilles et al., 2021a) create curvilinear rasters for a subselection of lanes before merging them together, but both these approaches neglects possible endpoints outside the drivable area so they can achieve reasonable inference times. We inspire ourselves from these previous works, with a few modifications so that we can predict endpoints anywhere on the map while smartly focusing the decoding computational load only on interesting parts of the space surrounding the agent of interest.

Figure 2: Model architecture for multi-agent prediction with shared backbone

Figure 3: Hierarchical iterative refinement of the grid probabilities. First, the full grid is evaluated at a very low resolution, then the highest cells are up-sampled and evaluated at a higher resolution, until final resolution is reached. We higlight in grey the restricted area considered for refinement at each step.

We use hierarchical predictions at various levels of resolutions so that the decoder has the possibility of predicting over the full surroundings of the agent but learns to refine with more precision only in places where the agent will end up with high probability. This hierarchical process is illustrated in Fig. 3.

We first predict a full dense grid probability at resolution $R_0 \times R_0$ by pixels. We then select the N_1 highest ranking grid points, and upsample only these points to a $R_1 \times R_1$ intermediary resolution. We repeat the process to select the top N_2 points of this grid and upsample them to a final $R_2 \times R_2$ grid for the definitive heatmap prediction. At each step, the grid points features are computed by a 2-layer MLP applied on the point coordinates, they are then concatenated to the agent encoding followed by a linear layer, and finally refined by a 2-layer cross-attention on the graph lane features. For a given W output range, this hierarchical process allows the model to only operate on $\frac{W}{R_0} \times \frac{W}{R_0} + N_1 \times \frac{R_0}{R_1} \times \frac{R_0}{R_1} + N_2 \times \frac{R_1}{R_2} \times \frac{R_1}{R_2}$ grid points instead of the $\frac{W}{R_2} \times \frac{W}{R_2}$ available. In practice, with $(W, R_0, N_1, R_1, N_2, R_2) = (192\text{m}, 8\text{m}, 16, 2\text{m}, 64, 0.5\text{m})$, we compute only 1856 grid points from the 147 456 available, with no performance loss.

3.1.3 FULL TRAJECTORY GENERATION

From each heatmap, we decode K end points using the same MR optimization algorithm as Gilles et al. (2021b). We then generate the full trajectories for each end point using also the same model, a fully-connected MLP. The MLP takes the car history and predicted endpoint as input and produces T 2D-coordinates representing the full future trajectory. At training time, this model is trained using ground-truth endpoints.

3.2 MULTI-AGENT CONSISTENT PREDICTION

The difficulty in multimodal multi-agent prediction comes from having coherent modalities between each agent. Since the modalities are considered scene-wise, the first predicted modality has to match with the first prediction of the other agents, and so on. Moreover, these modalities must not collide with each other, as they should represent realistic scenarios.

3.2.1 COLLISION-FREE ENDPOINT SAMPLING

We designed a deterministic sampling algorithm based on the heatmaps generated in previous section in order to sample endpoints for each agent in a collision aware manner. We use the same sampling algorithm as Gilles et al. (2021a) based on MR optimization, but add a sequential iteration over the agents for each modalities.

For a single modality k, we predict the possible endpoint of a first agent a by taking the maximum accumulated predicted probability under an area of radius r. We then not only set to zero the heatmap values of this agent heatmap $\mathcal{I}_{k'}^a$ around the sampled location so not to sample it in the next

Figure 4: Illustration of THOMAS methods for generation of scene-consistent agent modalities

modalities k', but we also set to zero the same area on the heatmaps $\mathcal{I}_k^{a'}$ of the other agents a' on the same modality k, so that these other agents cannot be sampled at the same position for this modality. This way, we try to enforce collision-free endpoints, and expect that considering collisions brings logic to improve the overall consistency of the predictions. However, as will be highlighted in Sec. 4.4, this methods significantly improves the collision rate without the need for any additional learned model but it does barely improve the multi agent consistency.

3.2.2 MODALITY COMBINATION RANKING

We address the scene consistency after the initial endpoint deterministic sampling. Our goal is to output a joint prediction $\mathcal{J} = (K, A)$ from the marginal prediction $\mathcal{M} = (A, K)$, where each scene modality k_s belonging to $\mathcal{J}$ selects the combination of agent modalities k_a among $\mathcal{M}$ that are the most coherent together. To achieve this, our main hypothesis lays in the fact that good trajectory proposals are already present in the marginal predictions, but they need to be coherently aligned among agents to achieve a consistent overall scene prediction. In practice we are claiming that a consistent multi-agent prediction $\mathcal{J}$ could be achieved by smartly re-ordering $\mathcal{M}$ among agents.

We illustrate our scene modality generation process in Fig. 4. We initialize L scene modality vectors S_l of D features each. $K \times A$ agent modality vectors A_k^a are also derived from each agent modality position. These vectors are obtained through a 2-layer MLP applied on the agent modality coordinates p_k^a, to which the stored agent encoding F_a (previously described in Sec. 3.1.1) is concatenated in order to help the model recognising modalities from the same agent. The scene modality vectors S_l are enriched through cross-attention layers on the agent modality encodings A_k^a. Then, for each scene modality l, for each agent a, a matching score is computed for each agent modality k as a scalar dot product between the scene modality vector S_l and the agent modality vector A_k^a:

$$s_l^{k_a} = S_l . A_k^a$$

Since argmax is non-differentiable, we employ a soft argmax as a weighted linear combination of the agent modalities p_k^a using a softmax on the $s_l^{k_a}$ scores:

$$p_l^a = softmax(s_l^{k_a})p_k^a$$

The final output is therefore no strictly a re-ordering of the k input modalities, but l linear recombinations. However, the space of possible strict re-ordering is included in the actual possible output space of the model, and is extended with possible interpolation for more accurate prediction, as well as the ability to select multiple times the same modality, which can be crucial for optimized scene joint coverage as we will show later.

4 EXPERIMENTS

4.1 DATASET

We use the Interaction v1.2 dataset that has recently opened a new multi-agent track in the context of its Interpret challenge. It contains 47 584 training cases, 11 794 validation cases and 2 644 testing cases, with each case containing between 1 and 40 agents to predict simultaneously.

4.2 METRICS

For a set of k predictions p_k^a for each agent a in a scene, we report the minimum Final Displacement Error (minFDE$_k$) to the ground truth $\hat{p}^a$ and the MissRate (MR$_k$). In their usual marginal definition, these metrics are averaged over agents after the minimum operation, which means that the best modality of each agent is selected independently for each and then averaged:

$$minFDE_k = \frac{1}{A} \sum_a min_k \|p_k^a - \hat{p}^a\|_2 \,, \; MR_k = \frac{1}{A} \sum_a min_k \mathbb{1}_{miss\,k}^a$$

As in Ettinger et al. (2021) and Zhan et al. (2019), a miss is counted when the prediction is closer than a lateral (1m) and an longitudinal threshold with regard to speed:

$$\text{Threshold}_{\text{lon}} = \begin{cases} 1 & v < 1.4m/s \\ 1 + \frac{v-1.4}{11-1.4} & 1.4m/s \le v \le 11m/s \\ 2 & v \ge 11m/s \end{cases}$$

For consistent scene multi-agent prediction, we report the joint metrics, where the average operation over the agents is done before the minimum operator. In this formulation, the minimum is taken over scene modalities, meaning that only the best scene (joint over agents) modality is taken into account:

$$minJointFDE_k = min_k \frac{1}{A} \sum_a \|p_k^a - \hat{p}^a\|_2 \,, \; JointMR_k = min_k \frac{1}{A} \sum_a \mathbb{1}_{miss\,k}^a$$

In other words, the marginal metrics pick their optimal solutions in a pool of k to the power of a predicted solutions, while the joint metrics restrict this pool to only k possibilities, making it a much more complex problem.

We also report $CrossCollisionrate$ (Col) which is the percentage of modalities where two or more agents collide together, and $ConsistentMinJointMR$ (cMR), which is $JointMR$ where colliding modalities are also counted as misses even if they are closer than the defined threshold.

4.3 COMPARISON WITH STATE-OF-THE-ART

We compare our THOMAS model performance with other joint predictions methods ILVM (Casas et al., 2020) and SceneTransformer (Ngiam et al., 2021). For fair comparison, we use a GOHOME encoder for each of the method, and adapt them accordingly so that they predict only endpoints similar to our method. For each method, we focus on implementing the key idea meant to solve scene consistency and keep the remaining part of the model as close as possible to our approach for fair comparison:

ILVM (Casas et al., 2020) uses variational inference to learn a latent representation of the scene conditioned of each agent with a Scene Interaction Module, and decodes it with a similar Scene Interaction Module. The required number of modalities is obtained by sampling the latent space as many times as require. Even though the sampling is independent for each agent, the latent space is generated conditionally on all the agents. We use a GOHOME encoder for the prior, posterior and decoder Scene Interaction Modules. We weight the KL term with $\beta = 1$ which worked best according to our experiments.

SceneTransformer (Ngiam et al., 2021) duplicates the agent encoding with the number of modalities required and adds a one-hot encoding specific to each modality. They then apply a shared transformer architecture on all modalities to encode intra-modality interactions between agents and

Table 1: Comparison of consistent solutions on Interpret multi-agent validation track

	Marginal metrics			Joint metrics			
	mADE	mFDE	MR	mFDE	MR	Col	cMR
ILVM (Casas et al., 2020)	0.30	0.62	10.8	0.84	19.8	5.7	21.3
SceneTranformer (Ngiam et al., 2021)	**0.29**	**0.59**	10.5	0.84	15.7	3.4	17.3
THOMAS	0.31	0.60	**8.2**	**0.76**	**11.8**	**2.4**	**12.7**

Table 2: Results on Interpret multi-agent regular scene leaderboard (test set)

	jointMinADE	JointMinFDE	JointMR	CrossCollision	ConsistentJointMR
05oct	0.47	1.16	23.8	**6.9**	26.8
THOMAS	**0.42**	**0.97**	**17.9**	12.8	**25.2**

generate the final trajectories. The initial paper applies a transformer architecture on a $[F, A, T, D]$ tensor where F is the potential modality dimension, A the agent dimension and T the time dimension, with D the feature embedding, with factorized self-attention to the agent and time dimensions separately, so that agents can look at each-other inside a specific scene modality. The resulting output is optimized using a jointly formalized loss. For our implementation, we get rid of the T dimension as we focus on endpoint prediction and coherence between the A agents. The initial encoded $[A, D]$ tensor is obtained with a GOHOME encoder, multiplied across the F futures and concatenated with a modality-specific one-hot encoding as in Ngiam et al. (2021) to obtain the $[F, A, D]$ tensor. We then apply two layers of agent self-attention similar to the original paper, before decoding the endpoints through a MLP.

The results are reported in Tab. 1. While having comparable marginal distance performance (demonstrating that our model is not inherently more powerful or leveraging more information), THOMAS significantly outperforms other methods on every joint metric. JointMR is improved by about 25% and $CrossCollisionrate$ by almost 30%, leading to a combined $ConsistentMinJointMR$ decreased by also more than 25%.

We also report our numbers from the Interpret multi-agent track challenge online leaderboard in Table 2. At time of submission (5^{th} October 2021), and despite the Challenge being opened since more than 2 months, there is only one other visible entry on the leaderboard, named '05oct', but we hope for other methods to join us soon there.

4.4 ABLATION STUDIES

We establish the following baselines to assess the effects our THOMAS recombination

- **Scalar output**: we train a model with the GOHOME graph encoder ans a multimodal scalar regression head similar to Liang et al. (2020); Ngiam et al. (2021). We optimize it with either marginal and joint loss formulation.

- **Heatmap output** with deterministic sampling: we try various sampling methods applied on the heatmap. *Deterministic sampling*: we apply the sampling algorithm as described in Gilles et al. (2021a). We also evaluate a joint variant as described in Sec 3.2.1. *Learned sampling*: we train a model to directly regress the sampled modalities from the input heatmap. This model is also optimized using either of the marginal or joint loss formulation

We report the comparison between the aforementioned baselines and THOMAS in Tab. 3. Compared to these baselines, THOMAS can be seen as an hybrid sampling method that takes the result of deterministic sampling as input and learns to recombine it into a more coherent solution. With regard to the joint algorithmic sampling that only tackled collisions but has little to no effect on actual consistency, as highlighted by the big drop in CrossCollisionRate from 7.2% to 2.6% but a similar JointMR, THOMAS actually brings a lot of consistency in the multi-agent prediction and drops the JointMR from 14.8% to 11.8%.

Table 3: Comparison of consistent solutions on Interpret multi-agent validation track

Output	Sampling	Objective	Marginal metrics			Joint metrics			
			mADE	mFDE	MR	mFDE	MR	Col	cMR
Scalar	–	Marg	0.28	0.59	10.4	1.04	23.7	6.4	24.9
Scalar	–	Joint	0.34	0.77	16.2	0.90	19.9	49	21.7
Heat	Learned	Marg	**0.26**	**0.46**	4.9	0.98	20.9	4.1	21.9
Heat	Learned	Joint	0.29	0.58	9.8	0.88	15.2	3.0	16.4
Heat	Algo	Marg	0.29	0.54	**3.8**	0.83	14.8	7.2	15.9
Heat	Algo	Joint	0.29	0.54	**3.8**	0.83	14.8	2.6	15.6
Heat	Combi	Joint	0.31	0.60	8.2	**0.76**	**11.8**	**2.4**	**12.7**

Usually, scalar marginal models already suffer from learning difficulties as only one output modality, the closest one to ground, can be trained at a time. Some modalities may therefore converge faster to acceptable solutions, and benefit from a much increased number of training samples compared to the others. This problem is aggravated in the joint training case, since the modality selected is the same for all agents in a training sample. The joint scalar model therefore actually fails to learn multi-modality as illustrated by a higher marginal minFDE$_6$ than any other model, and an extremely high crossCollisionRate since some modalities never train and always point to the same coordinates regardless of the queried agent. Note that, despite a similar training loss, SceneTransformer doesn't suffer of the same pitfalls in Tab. 1 as is shares the same weights between all modalities and only differentiates them in the initialization of the features.

4.5 QUALITATIVE EXAMPLES

In this section, we will mostly compare the model before recombination, which we will refer by the $Before$ model, to the model after recombination, referenced as the $After$ model. We display four qualitative examples in Fig. 5 with colliding modalities in the $Before$ model (in dashed orange) and the solved modality (in full line orange) after recombination. For each model ($Before$-dashed or $After$-full), the highlighted modality in orange is the best modality according to the $jointMR_6$ metric among the 6 modalities available. We also display in dashed grey the other 5 predicted $Before$ modalities, and highlight that the recombination model indeed selects modalities already available in the vanilla set and reorders them so that non-colliding modalities are aligned together.

Figure 5: Qualitative examples of recombination model assembling collision-free modalities together compared to initial colliding modalities. For each example we display the general context with highlighted agents and area of interest, then two zooms in on the agents, one displaying the initial best modality before recombination in dashed orange and all the other available modalities in grey. The second zooms shows the best modality after recombination in full line orange.

Figure 6: Qualitative examples of recombination model selecting fewer but more pronounced and impactful agent modalities compared to initial colliding modalities. For each example we display on the left the vanilla model modalities with dashed lines, with the initial best modality in dashed orange and all the other available modalities in grey. On the right we display the selected modalities after recombination, where the model focuses on the most likely occurance in most agents and only isolates a few uncertainties.

We also show more qualitative examples in Fig. 6, where we highlight the comparison in modality diversity between the $Before$ model (in dashed lines) and the $After$ model (in full lines). While the $Before$ model tries to spread the modalities for all agents to minimize marginal miss-rate, the recombinated model presents much less spread compared to the original model, maintaining a multimodal behavior only in presence of very different possible agent intentions such as different possible exits or turn choices. For most other agents, almost all modalities are located at the same position, deemed the most likely by the model, so that if the truly uncertain agents have to select the second or third most likely modality, the other agents still have their own most likely modality.

5 CONCLUSION

We have presented THOMAS, a recombination module that can be added after any trajectory prediction module outputing multi-modal predictions. By design, THOMAS allows to generate scene-consistent modalities across all agents, by making the scene modalities select coherent agent modalities and restricting the modality bugdet on the agents that truly need it. We show significant performance increase when adding the THOMAS module compared to the vanilla model, and state-of-the-art results compared to already existing methods tackling scene-consistent predictions.

REPRODUCIBILITY STATEMENT

We use the publicly available Interaction 1.2 dataset (Zhan et al., 2019) available at `http://challenge.interaction-dataset.com/dataset/download`. We detail dataset preprocessing in Appendix A.1, training process in Appendix A.2 and give a precise illustration of our model architecture with each layer size in A.3.

REFERENCES

Alexandre Alahi, Kratarth Goel, Vignesh Ramanathan, Alexandre Robicquet, Li Fei-Fei, and Silvio Savarese. Social lstm: Human trajectory prediction in crowded spaces. In *CVPR*, 2016.

Florent Altché and Arnaud de La Fortelle. An lstm network for highway trajectory prediction. In *ITSC*, 2017.

Holger Caesar, Varun Bankiti, Alex H Lang, Sourabh Vora, Venice Erin Liong, Qiang Xu, Anush Krishnan, Yu Pan, Giancarlo Baldan, and Oscar Beijbom. nuscenes: A multimodal dataset for autonomous driving. In *CVPR*, 2020.

Sergio Casas, Cole Gulino, Simon Suo, Katie Luo, Renjie Liao, and Raquel Urtasun. Implicit latent variable model for scene-consistent motion forecasting. In *ECCV*, 2020.

Yuning Chai, Benjamin Sapp, Mayank Bansal, and Dragomir Anguelov. Multipath: Multiple probabilistic anchor trajectory hypotheses for behavior prediction. In *CoRL*, 2020.

Ming-Fang Chang, John Lambert, Patsorn Sangkloy, Jagjeet Singh, Slawomir Bak, Andrew Hartnett, De Wang, Peter Carr, Simon Lucey, Deva Ramanan, et al. Argoverse: 3d tracking and forecasting with rich maps. In *CVPR*, 2019.

Henggang Cui, Vladan Radosavljevic, Fang-Chieh Chou, Tsung-Han Lin, Thi Nguyen, Tzu-Kuo Huang, Jeff Schneider, and Nemanja Djuric. Multimodal trajectory predictions for autonomous driving using deep convolutional networks. In *ICRA*, 2019.

Nachiket Deo and Mohan M Trivedi. Convolutional social pooling for vehicle trajectory prediction. In *CVPR*, 2018.

Nachiket Deo and Mohan M Trivedi. Trajectory forecasts in unknown environments conditioned on grid-based plans. *arXiv:2001.00735*, 2020.

Nachiket Deo, Eric M Wolff, and Oscar Beijbom. Multimodal trajectory prediction conditioned on lane-graph traversals. In *CoRL*, 2021.

Scott Ettinger, Shuyang Cheng, Benjamin Caine, Chenxi Liu, Hang Zhao, Sabeek Pradhan, Yuning Chai, Ben Sapp, Charles Qi, Yin Zhou, et al. Large scale interactive motion forecasting for autonomous driving: The waymo open motion dataset. *arXiv:2104.10133*, 2021.

Jiyang Gao, Chen Sun, Hang Zhao, Yi Shen, Dragomir Anguelov, Congcong Li, and Cordelia Schmid. Vectornet: Encoding hd maps and agent dynamics from vectorized representation. In *CVPR*, 2020.

Thomas Gilles, Stefano Sabatini, Dzmitry Tsishkou, Bogdan Stanciulescu, and Fabien Moutarde. Gohome: Graph-oriented heatmap output forfuture motion estimation. *arXiv preprint arXiv:2108.09640*, 2021a.

Thomas Gilles, Stefano Sabatini, Dzmitry Tsishkou, Bogdan Stanciulescu, and Fabien Moutarde. Home: Heatmap output for future motion estimation. In *ITSC*, 2021b.

Junru Gu, Chen Sun, and Hang Zhao. Densetnt: End-to-end trajectory prediction from dense goal sets. In *ICCV*, 2021.

Agrim Gupta, Justin Johnson, Li Fei-Fei, Silvio Savarese, and Alexandre Alahi. Social gan: Socially acceptable trajectories with generative adversarial networks. In *CVPR*, 2018.

Joey Hong, Benjamin Sapp, and James Philbin. Rules of the road: Predicting driving behavior with a convolutional model of semantic interactions. In *CVPR*, 2019.

Siddhesh Khandelwal, William Qi, Jagjeet Singh, Andrew Hartnett, and Deva Ramanan. What-if motion prediction for autonomous driving. *arXiv:2008.10587*, 2020.

ByeoungDo Kim, Seong Hyeon Park, Seokhwan Lee, Elbek Khoshimjonov, Dongsuk Kum, Junsoo Kim, Jeong Soo Kim, and Jun Won Choi. Lapred: Lane-aware prediction of multi-modal future trajectories of dynamic agents. In *CVPR*, 2021.

Namhoon Lee, Wongun Choi, Paul Vernaza, Christopher B Choy, Philip HS Torr, and Manmohan Chandraker. Desire: Distant future prediction in dynamic scenes with interacting agents. In *CVPR*, 2017.

Ming Liang, Bin Yang, Rui Hu, Yun Chen, Renjie Liao, Song Feng, and Raquel Urtasun. Learning lane graph representations for motion forecasting. In *ECCV*, 2020.

Chenxu Luo, Lin Sun, Dariush Dabiri, and Alan Yuille. Probabilistic multi-modal trajectory prediction with lane attention for autonomous vehicles. *arXiv:2007.02574*, 2020.

Jean Mercat, Thomas Gilles, Nicole El Zoghby, Guillaume Sandou, Dominique Beauvois, and Guillermo Pita Gil. Multi-head attention for multi-modal joint vehicle motion forecasting. In *ICRA*, 2020.

Kaouther Messaoud, Nachiket Deo, Mohan M Trivedi, and Fawzi Nashashibi. Multi-head attention with joint agent-map representation for trajectory prediction in autonomous driving. *arXiv:2005.02545*, 2020.

Jiquan Ngiam, Benjamin Caine, Vijay Vasudevan, Zhengdong Zhang, Hao-Tien Lewis Chiang, Jeffrey Ling, Rebecca Roelofs, Alex Bewley, Chenxi Liu, Ashish Venugopal, et al. Scene transformer: A unified multi-task model for behavior prediction and planning. *arXiv preprint arXiv:2106.08417*, 2021.

Tung Phan-Minh, Elena Corina Grigore, Freddy A Boulton, Oscar Beijbom, and Eric M Wolff. Covernet: Multimodal behavior prediction using trajectory sets. In *CVPR*, 2020.

Nicholas Rhinehart, Kris M Kitani, and Paul Vernaza. R2p2: A reparameterized pushforward policy for diverse, precise generative path forecasting. In *ECCV*, 2018.

Amir Sadeghian, Vineet Kosaraju, Ali Sadeghian, Noriaki Hirose, Hamid Rezatofighi, and Silvio Savarese. Sophie: An attentive gan for predicting paths compliant to social and physical constraints. In *CVPR*, 2019.

Tim Salzmann, Boris Ivanovic, Punarjay Chakravarty, and Marco Pavone. Trajectron++: Dynamically-feasible trajectory forecasting with heterogeneous data. In *ECCV*, 2020.

Haoran Song, Di Luan, Wenchao Ding, Michael Yu Wang, and Qifeng Chen. Learning to predict vehicle trajectories with model-based planning. In *CoRL*, 2021.

Yichuan Charlie Tang and Ruslan Salakhutdinov. Multiple futures prediction. In *NeurIPS*, 2019.

David Wu and Yunnan Wu. Air^2 for interaction prediction. Waymo Open Dataset Challenges Reports, CVPR Workshop on Autonomous Driving, `http://cvpr2021.wad.vision/`, 2021.

Maosheng Ye, Tongyi Cao, and Qifeng Chen. Tpcn: Temporal point cloud networks for motion forecasting. In *CVPR*, 2021.

Wenyuan Zeng, Ming Liang, Renjie Liao, and Raquel Urtasun. Lanercnn: Distributed representations for graph-centric motion forecasting. In *IROS*, 2021.

Wei Zhan, Liting Sun, Di Wang, Haojie Shi, Aubrey Clausse, Maximilian Naumann, Julius Kummerle, Hendrik Konigshof, Christoph Stiller, Arnaud de La Fortelle, et al. Interaction dataset: An international, adversarial and cooperative motion dataset in interactive driving scenarios with semantic maps. *arXiv:1910.03088*, 2019.

Wei Zhan, Liting Sun, Di Wang, Haojie Shi, Aubrey Clausse, Maximilian Naumann, Julius Kummerle, Hendrik Konigshof, Christoph Stiller, Arnaud de La Fortelle, et al. Interpret: Interaction-dataset-based prediction challenge. `http://challenge.interaction-dataset.com/prediction-challenge/intro`, 2021. Accessed: 2021-10-03.

Lingyao Zhang, Po-Hsun Su, Jerrick Hoang, Galen Clark Haynes, and Micol Marchetti-Bowick. Map-adaptive goal-based trajectory prediction. In *CoRL*, 2020.

Hang Zhao, Jiyang Gao, Tian Lan, Chen Sun, Benjamin Sapp, Balakrishnan Varadarajan, Yue Shen, Yi Shen, Yuning Chai, Cordelia Schmid, et al. Tnt: Target-driven trajectory prediction. *CoRL*, 2020.

A   APPENDIX

A.1   DATASET PROCESSING

We use the training/validation split provided in Interaction 1.2. We select for each scene a reference agent on which the scene will be centered and oriented according to its heading at prediction time. At training time, this reference agent is chosen randomly across all agents. At validation and testing time, we compute the barycenter of all agents and select the closest agent as the scene reference point. We use for training all agents that have ground-truth available at prediction horizon T=3s.

We use the provided dataset HD-Maps to create the context graphs. As in Liang et al. (2020), we use four relations:$\{predecessor, successor, left, right\}$ obtained from the lane graph connectivity. We upsample long lanelets to have a maximum of 10 points in each lanelet.

For each agent, we use their trajectory history made of position, yaw and speed in the past second sampled at 10Hz. We also provide the model a mask indicating if the agent was present in a given time-frame, and pad with zeros when the agent is not tracked at a specific timestep.

A.2   TRAINING DETAILS

We train all models with Adam optimizer and batchsize 32. We initialize the learning rate at $1e^{-3}$ and divide it by 2 at epochs 3, 6, 9 and 13, before stopping the training at epoch 16. We use ReLU activation after every linear layer unless specified otherwise, and LayerNormalization after every attention and graph convolution layer.

During training, since a scene can contain up to 40 agents, which is too much for gradient computation in batches of 32, we restrict the number of predicted agents to 8 by randomly sampling them across available agents. We do not use other data augmentation.

The final heatmap Y predicted cover a range of 192 meters at resolution 0.5m, hence a (384, 384) image. For heatmap generation, we use the same pixel-wise focal loss over the pixels p as in Gilles et al. (2021b):

$$L = -\frac{1}{P}\sum_p (Y_p - \hat{Y}_p)^2 f(Y_p, \hat{Y}_p) \text{ with } f(Y_p, \hat{Y}_p) = \begin{cases} \log(\hat{Y}_p) & \text{if } Y_p=1 \\ (1 - Y_p)^4 \log(1 - \hat{Y}_p) & \text{else} \end{cases}$$

where $\hat{Y}$ is defined as a Gaussian centered on the agent future position at prediction horizon T with a standard deviation of 4 pixels, equivalent to 2m.

A.3 DETAILED ARCHITECTURE

Figure 7: Detailed illustration of our heatmap generator model

A.4 HEATMAP QUALITATIVE RESULTS

Figure 8: Qualitative examples of heatmap output from our multi-agent model. All the heatmaps from one scene are the results from one single forward pass in our model predicting all agents at once. We use matching colors for the agent history, current location and their future predicted heatmap (best viewed in color).