Back to Reality for Imitation Learning

Edward Johns
The Robot Learning Lab at Imperial College London

Abstract: Imitation learning, and robot learning in general, emerged due to break-throughs in machine learning, rather than breakthroughs in robotics. As such, evaluation metrics for robot learning are deeply rooted in those for machine learning, and focus primarily on data efficiency. We believe that a better metric for real-world robot learning is time efficiency. This is a call to arms to the robot learning community to develop our own evaluation metrics tailored towards the long-term goals of real-world robotics.

Keywords: Imitation learning, Reinforcement learning, Evaluation, Benchmarks

1 Introduction

How do we define the term *robot learning*? Let us consider two options. Firstly, *the study of machine learning techniques for applications to robotics*. And secondly, *the study of techniques to enable robots to learn*. The choice between these two can be distilled down to whether robot learning is considered fundamentally to be a field within machine learning, or a field within robotics, respectively. But whilst this distinction may appear to be arbitrary, the implication is in fact profound, for the following reason. It determines the evaluation metrics used to judge the performance of new techniques, and therefore, it determines the long-term impact that the field is shaping itself around. In this paper, we argue that metrics which guide development of a technology should be driven by the target application of that technology, irrespective of the methods used by that technology. And therefore, we argue that robot learning metrics should be driven by real-world robotics applications, rather than the underlying machine learning algorithms. However, this is not what we observe in the robot learning community today: evaluation is dominated by traditional machine learning metrics. In this paper, we expose a worrying trend that this has led to, which deserves foresight, attention, and debate.

Robot learning emerged from machine learning, not robotics. Whilst the fields of both machine learning and robotics have existed for decades, the field of robot learning is a more recent development, such as with the arrival of our first CoRL in 2017. But its growth in popularity can largely be attributed to breakthroughs in machine learning, and in particular, breakthroughs in deep learning and reinforcement learning, rather than breakthroughs in classical robotics. And during this emergence, the robot learning community has brought with it evaluation metrics that were designed by the machine learning community, for machine learning problems. For example, a typical rein-forcement learning paper published at a machine learning conference today, will present graphs of *Success Rate vs Number of Environment Interactions*. And similarly, for a typical paper published at CoRL, *Success Rate vs Number of Environment Interactions* remains a popular evaluation metric. Now, for the machine learning community, this metric is sensible: it encourages data efficiency, which is arguably the most fundamental aim in machine learning research. But is data efficiency the most fundamental aim in robotics research?

2 Back to Reality

The curse of simulators. To answer the above question, we examine the differences between the simulation environments typically studied in machine learning papers, and the environments of real-world robots. Our first observation is that, whilst simulators often assume prior existence of a task definition, such as a reward function, in reality tasks must be manually defined, such as

Blue Sky Papers, 5th Conference on Robot Learning (CoRL 2021), London, UK.

with a demonstration. As such, when we move away from simulators and into the real world, a large number of robot learning problems can be considered as a form of imitation learning, particularly for robot manipulation where tasks are highly varied. Our second observation is that, whilst simulators facilitate rapid prototyping and large-scale quantitative benchmarking, as a consequence they often make two problematic assumptions: (1) environment resetting comes for free, and (2) low-dimensional ground-truth states (e.g. object poses) are readily available. In real-world robotics, however, (1) automatic environment resetting requires significant human supervision or construction of task-specific apparatus, and (2) obtaining low-dimensional states requires additional development of a state estimator for each new task.

Time efficiency vs data efficiency. Due to this, we argue that data efficiency should not be the most fundamental aim in robotics research, and instead, we should be optimising our methods for *time efficiency*. Time efficiency can be expressed as how quickly a robot can learn a new task in a given amount of time, regardless of the amount of data collected during that time. If a method requires environment resetting, then the additional time to reset the environment should be a penalty, when that method is evaluated relative to other methods that do not require as much environment resetting. Similarly, if a method requires object poses, then the additional time taken to train that pose estimator should be accounted for. But this is not to say that data efficiency should not be encouraged; data efficiency is always beneficial as long as it does not come at the cost of time efficiency. Instead, we argue for a more comprehensive metric than only data efficiency: the best imitation learning method is one which optimally trades off all aspects that contribute to time efficiency, and data efficiency is just one of those aspects.

Two flavours of time efficiency. Imitation learning involves humans teaching robots. This takes time, but it also takes effort. An ideal imitation learning method would be one which minimises both time and effort, but these factors are not independent. For example, an inverse reinforcement learning method seeded with a larger number of demonstrations may learn more quickly, but at the cost of more human effort. As such, we now propose two flavours of the time efficiency metric.

Clock time efficiency. We define clock time efficiency as the speed at which a robot learns a new task with respect to the amount of wall clock time. This could be the metric of choice in a factory setting, for example, where an engineer would like a robot to learn a new task as quickly as possible to then begin a manufacturing job, even if the engineer needs to supervise the learning throughout.

Human time efficiency. We define human time efficiency as the speed at which a robot learns a new task with respect to the amount of time a human spends supervising the learning. This could be the metric of choice in a domestic setting, for example, where a consumer would like the robot to learn a new task as autonomously as possible and with minimal human effort, even if the robot takes a long time to learn.

Figure 1: A comparison of two hypothetical methods using data efficiency (left) and time efficiency (right) metrics.

A choice of two futures. Figure 1 left shows how robot learning methods are typically evaluated today. According to the data efficiency metric, the red method is superior. Hypothetically, let us consider that the blue method requires no environment resetting and learns end-to-end from images, whilst the red method requires regular environment resetting and ground-truth object poses. Figure 1 right then shows how these two methods would be evaluated with a time efficiency metric. Here,

whilst the data efficiency and time efficiency of the blue method are proportional, the red method is significantly less time efficient than it is data efficient. Today, we are being encouraged to develop the red method. Through this paper, we aim to motivate the robot learning community towards a future where we are instead developing the blue method.

3 Meta-analysis of CoRL 2020

Having established our criteria for good imitation learning metrics, we can now analyse existing evaluation metrics used by the robot learning community today. To do this, we performed a meta-analysis of all imitation learning papers published at CoRL 2020. To select these papers, we first searched for all papers which contained either "imitation" or "demonstration" in the paper's abstract. From these, we inspected each paper and retained those which actually involved providing a demonstration to learn a new task, which resulted in 19 papers. We then analysed each paper to determine whether it evaluated success rate as a function of either clock time or human time. We also recorded whether a paper assumed ground-truth object poses, and whether it required environment resetting. In some cases, the experiments themselves did not require environment resetting but only because the tasks were simple target reaching tasks, and in these cases we made a judgement as to whether environment resetting would be required with more typical, everyday tasks. For each paper, we also recorded whether any real-world experiments were done.

Table 1 shows the results of this meta-analysis. Papers are grouped into 8 groups, where all the papers in one group contained the same yes/no answers across all 5 columns. The first observation we make is that not a single paper evaluated the clock time efficiency or human time efficiency, with most methods instead evaluating data efficiency. Some papers did involve studying success rate as a function of the number of demonstrations, but in those cases, the overall clock time or human time was not evaluated. The second observation we make is that 10 out of the 19 papers assume access to ground-truth object poses, and 13 papers required regular environment resetting. Neither of these properties make for practical, real-world imitation learning. To obtain these poses, some papers required manually pre-training an object pose estimator for each new task [1, 2], but timing information for this was not provided nor included when comparing the method to alternatives. A final observation we make is that 8 out of the 19 papers only include simulation experiments, an unfortunate trend at all CoRL conferences which results in authors focussing mainly on machine learning metrics, rather than those more appropriate to real-world robotics.

# Papers	Clock Time Efficiency?	Human Time Efficiency?	Assumes Object Poses?	Environment Resetting?	Real-World?
4 [3, 4, 5, 6]	No	No	Yes	Yes	No
3 [7, 8, 2]	No	No	Yes	Yes	Yes
3 [9, 10, 11]	No	No	No	Yes	No
3 [12, 1, 13]	No	No	No	Yes	Yes
3 [14, 15, 16]	No	No	Yes	No	Yes
1 [17]	No	No	No	No	Yes
1 [18]	No	No	No	No	No
1 [19]	No	No	No	No	Yes

Table 1: Meta-analysis of 19 imitation learning papers at CoRL 2020.

4 Our Recommendations

Simulators are still important. We have established our argument for use of time efficiency instead of data efficiency. But in practice, both clock time efficiency and human time efficiency are difficult to objectively evaluate with real-world experiments. For example, if the authors themselves are the robot teachers, then there are likely to be implicit or explicit biases in the time taken depending on whether the authors' own method, or a baseline, are being evaluated. As such, we still recommend the use of simulation benchmarks for large-scale objective evaluation, but with some significant changes that will mitigate the aforementioned problems with these benchmarks. Specifically, these changes should model any aspects of task learning which require time to perform. For example, each time an environment would be manually reset, a fixed amount of time should be added to both the method's clock time and it's human time counters. As another example, each task can

optionally be provided with ground-truth object poses, but a fixed amount of time must be added to the method's clock time counter to model the user or robot collecting data for an object pose estimator. Given benchmarks such as these, we believe that the community will begin to develop methods which more optimally trade off all the different aspects of real-world robot learning.

Visualising time efficiency. In Figure 2, we also present various options for visualising these metrics, on hypothetical data. Figure 2a compares three different methods by plotting success rates as a function of human time. Whilst Method D has the highest human time efficiency, it is not necessarily the most data efficient. Therefore, it would not necessarily be considered a desirable method if traditional machine learning metrics were used. Figure 2b then presents a more complete evaluation of one individual method. Here, each line is a Pareto front representing a particular success rate on the task being learned, where every point on one line equally trades off the amount of human time required, and the overall clock time required. This is a useful visualisation for choosing an operating point during deployment, where a user may have a particular preference for minimising overall training time, compared to minimising overall human effort or expertise. Figure 2c then shows the trade-off between pre-training time and fine-tuning time across three different methods. For example, meta-learning methods typically require a large amount of pre-training, whereas behavioural cloning methods typically learn from scratch. Again, a Pareto front represents all data for a particular success rate. This graph provides an intuitive way to compare methods across entirely different families of imitation learning approaches, which is typically not possible when considering only one of these dimensions. Here, Method I outperforms both Methods G and H, and we can see that Method H is faster than Method G at learning new tasks when there is an abundance of pre-training time, and vice versa.

Figure 2: Examples of how evaluations could be visualised using our proposed clock time efficiency and human time efficiency metrics.

5 Conclusions

In this paper, we have argued that data efficiency is not the optimal evaluation metric for robot learning, when the long-term goal is real-world robotics. Instead, two alternative aspects should be considered: the overall time taken for learning a new task, and the amount of time spent by the human supervising the learning. Methods which are the most data efficient may not necessarily be the most time efficient, and may sacrifice consideration of real-world practicalities in an attempt to beat the state-of-the-art on simulation benchmarks. Our intention through this paper, is to stimulate the community to change the current direction of imitation learning evaluation, and develop benchmarks which more accurately model the real-world costs of robot learning.

Acknowledgments

This work was supported by the Royal Academy of Engineering under the Research Fellowship scheme.

References

[1] Model-based inverse reinforcement learning from visual demonstrations. In *Conference on Robot Learning (CoRL)*, 2020.

[2] Acnmp: Skill transfer and task extrapolation through learning from demonstration and reinforcement learning via representation sharing. In *Conference on Robot Learning (CoRL)*, 2020.

[3] f-irl: Inverse reinforcement learning via state marginal matching. In *Conference on Robot Learning (CoRL)*, 2020.

[4] Tolerance-guided policy learning for adaptable and transferrable delicate industrial insertion. In *Conference on Robot Learning (CoRL)*, 2020.

[5] Learning dexterous manipulation from suboptimal experts. In *Conference on Robot Learning (CoRL)*, 2020.

[6] Learning from demonstrations using signal temporal logic. In *Conference on Robot Learning (CoRL)*, 2020.

[7] Generative adversarial training of product of policies for robust and adaptive movement primitives. In *Conference on Robot Learning (CoRL)*, 2020.

[8] Learning from suboptimal demonstration via self-supervised reward regression. In *Conference on Robot Learning (CoRL)*, 2020.

[9] Task-relevant adversarial imitation learning. In *Conference on Robot Learning (CoRL)*, 2020.

[10] Positive-unlabeled reward learning. In *Conference on Robot Learning (CoRL)*, 2020.

[11] Augmenting gail with bc for sample efficient imitation learning. In *Conference on Robot Learning (CoRL)*, 2020.

[12] Cloud: Contrastive learning of unsupervised dynamics. In *Conference on Robot Learning (CoRL)*, 2020.

[13] Generalization guarantees for imitation learning. In *Conference on Robot Learning (CoRL)*, 2020.

[14] Modeling long-horizon tasks as sequential interaction landscapes. In *Conference on Robot Learning (CoRL)*, 2020.

[15] Interactive imitation learning in state-space. In *Conference on Robot Learning (CoRL)*, 2020.

[16] Learning interactively to resolve ambiguity in reference frame selection. In *Conference on Robot Learning (CoRL)*, 2020.

[17] Learning object manipulation skills via approximate state estimation from real videos. In *Conference on Robot Learning (CoRL)*, 2020.

[18] Transformers for one-shot visual imitation. In *Conference on Robot Learning (CoRL)*, 2020.

[19] Visual imitation made easy. In *Conference on Robot Learning (CoRL)*, 2020.