RIDE: Difficulty Evolving Perturbation with Item Response Theory for Mathematical Reasoning

Abstract

Large language models (LLMs) achieve high performance on mathematical reasoning, but these results can be inflated by training data leakage or superficial pattern matching rather than genuine reasoning. To this end, an adversarial perturbation–based evaluation is needed to measure true mathematical reasoning ability. Current rule-based perturbation methods often generate ill-posed questions and impede the systematic evaluation of question difficulty and the evolution of benchmarks. To bridge this gap, we propose RIDE, a novel adversarial question-rewriting framework that leverages Item Response Theory (IRT) to rigorously measure question difficulty and to generate intrinsically more challenging, well-posed variations of mathematical problems. We employ 35 LLMs to simulate students and build a difficulty ranker from their responses. This ranker provides a reward signal during reinforcement learning and guides a question-rewriting model to reformulate existing questions across difficulty levels. Applying RIDE to competition-level mathematical benchmarks yields perturbed versions that degrade advanced LLM performance, with experiments showing an average 22.24% drop across 28 models, thereby exposing limited robustness in mathematical reasoning and confirming the validity of our evaluation approach.

1 Introduction

Mathematical reasoning is regarded as a crucial testament for evaluating the reasoning capabilities of large language models (LLMs). Recent works like DeepSeek-Math (Shao et al., 2024) and Qwen2.5-Math (Yang et al., 2024) clearly demonstrate the benefits of reinforcement learning (RL) for mathematical reasoning. Nevertheless, strong performance in mathematical reasoning may not directly reflect the model's reasoning ability (Wu et al., 2025). It may instead result from data contamination during pretraining (Golchin and Surdeanu, 2024) that leads to memorization-based answers (Zhang et al., 2024; Li et al., 2025), or from the model relying primarily on superficial pattern matching without understanding mathematical knowledge (Li et al., 2024; Mirzadeh et al., 2025). This phenomenon undermines the reliability of LLMs as genuine mathematical reasoners.

To address this issue, there is an urgent need for a more adversarial evaluation benchmark that can faithfully characterize the robustness of mathematical reasoning. For example, a rule-based rewriting method is proposed (Li et al., 2024; Zhou et al., 2025), which applies operations such as numerical substitution and symbol modification to reformulate questions. This method has been shown to reduce model performance. However, rule-based approaches may render the rewritten questions ill-posed and unsolvable (Xue et al., 2025), thereby undermining their validity as reliable benchmarks. Moreover, previous work has focused mainly on low-difficulty datasets (Cobbe et al., 2021), with limited attempts at more challenging data. Based on this, we identify the following challenges: (1) **Robust Adversarial Perturbation.** Robust perturbations to the data need to both degrade the model performance and remain credible and reasonable, which requires shifting from injecting noise to reformulating questions into formats that are inherently more challenging for the model to resolve correctly. Moreover, the perturbation should be unpredictable for changing, and simple rules cannot capture the evolution. (2) **More Challenging Data.** The perturbation of data should not be limited to the same difficulty level of mathematical reasoning. It is also necessary to explore its effectiveness on difficulty evolution, ensuring reasonable perturbations can be applied to mathematical competition questions. These challenges require us to perturb existing benchmarks in ways that substantively increase the intrinsic difficulty of the

questions (Huang et al., 2025). A question's difficulty is often defined by whether a model answers correctly (Lan et al., 2026), but this definition depends heavily on the selected models, and majority voting across these models ignores the individual differences in capabilities. Besides, defining difficulty by the steps of the reasoning chain (Yu et al., 2025) is easily misled by shortcut reasoning and does not account for the numerical computation complexity specific to mathematical reasoning.

Figure 1: Difficulty evolution via RIDE. The original question (left) is successfully answered, whereas the rewritten question (right) with added constraints triggers a reasoning error of the Qwen3-30B-A3B model.

To this end, we propose **RIDE**, a benchmark perturbation rewriting framework that incorporates Item Response Theory (IRT) to measure question difficulty (Vania et al., 2021; Scarlatos et al., 2025). Specifically, 35 cutting-edge LLMs are treated as students to answer $2,000$ questions sampled from the high-difficulty mathematical dataset DeepMath (He et al., 2025). A statistical model jointly characterizes the latent abilities of the student models and the difficulty parameters of the questions. This difficulty is not human cognitive complexity but a model-centric metric representing the inherent challenge a specific question format poses to the model's ability to respond correctly. Based on the IRT-estimated difficulty, a pairwise ranker is trained, which outputs the probability that one question is more difficult than another. The ranker's output serves as a difficulty reward for RL on Qwen3-8B, resulting in the question rewriting model RIDE-8B. Applying RL to difficulty-evolving question rewriting encourages the model to adaptively generate questions with higher difficulty, thus avoiding superficial modifications, while further enhancing consistency between the rewritten questions and their answers by setting a correctness reward. RIDE-8B is then applied to rewrite competition-level mathematical benchmarks such

as AIME-24 and AMC-23, achieving difficulty evolution for these datasets. Experiments demonstrate that the perturbed benchmarks induce performance drops in frontier reasoning models, including GPT-5, DeepSeek-V3.1, and others, thereby enabling robust evaluation and comparison of advanced models' mathematical reasoning abilities (as shown in Figure 1). In addition, RIDE can be used as a data augmentation method to enhance training data and improve mathematical reasoning performance. Our contributions are as follows:

- We propose a benchmark perturbation framework with IRT to evaluate robustness in mathematical reasoning. We measure robustness via performance degradation and observe that most LLMs are sensitive to perturbations, indicating poor robustness.

- We propose an IRT-based difficulty ranker and introduce a RL-based scheme for training a question-rewriting model. We also release our question rewriting model (RIDE-8B), two rewritten competition-level benchmarks (RIDE-AIME and RIDE-AMC), and a training dataset of over 10K rewritten questions (RIDE-DeepMath).

2 Related Work

Robustness Evaluation. Existing LLM robustness evaluations (Ul Abedin et al., 2025) use controlled perturbations to test whether models truly understand tasks rather than memorize surface patterns (Yang et al., 2025a; Negi et al., 2026). A practice is to construct original items and perturbed counterparts around the same semantics and compare the performance drop (Chang et al., 2023; Hou et al., 2025; Yang et al., 2025b). For example, GSM-PLUS (Li et al., 2024) applies rule-based perturbations such as numerical substitution and operation modification, revealing degradation in many LLMs. Unlike rule-based methods, we adapt a RL-based rewriting approach to generate perturbations, producing better-formed data, avoiding unsolvable cases, and increasing unpredictability.

Item Response Theory (IRT). Originating from educational measurement, IRT is widely applied in AI for automated item difficulty estimation (Feng et al., 2025; Chen and Shiu, 2025) and efficient evaluation (Polo et al., 2024). IRT depends on real student responses, which are often difficult to obtain due to privacy constraints. Prior work addresses this by simulating response matrices (Lalor

et al., 2019; Truong et al., 2025). We use 35 LLMs as students to obtain simulated response matrix and reframe difficulty estimation as a pairwise ranking task to reduce numerical prediction errors.

3 Preliminary

We briefly introduce the IRT-based difficulty in our method. Consider a test taker with fixed ability θ and a math reasoning question q with a difficulty score d. The response y is modeled as a Bernoulli random variable that indicates correctness, where $y = 1$ denotes a correct answer and $y = 0$ denotes an incorrect answer. We introduce the Rasch model (Rasch, 1993), a foundational one-parameter (1-PL) IRT model in which the probability of a correct response is the logistic function of the difference between the test taker's ability θ and the item's difficulty d:

$$\Pr(y = 1 \mid \theta, d) = \sigma(\theta - d) = \frac{1}{1 + e^{-(\theta - d)}}$$

Given a binary response matrix $\mathbf{Y} \in \{0, 1\}^{M \times N}$, where M and N denote the number of test takers and questions, respectively. Each entry Y_{ij} indicates the i-th test taker's answer to the j-th question. Based on this response matrix, one can estimate the ability parameters θ and the difficulty parameters d using statistical inference methods. In this paper, we fit the Rasch model using stochastic variational inference provided by *py-irt* (Lalor and Rodriguez, 2023). Specifically, we adopt a mean-field Normal guide for the latent ability θ_i and difficulty d_j, and maximize the evidence lower bound (ELBO) $\mathcal{L}$:

$$\max_{g} \mathcal{L} = \sum_{i=1}^{M} \sum_{j=1}^{N} \mathbb{E}_g \big[Y_{ij}(\theta_i - d_j) \\ - \log\big(1 + e^{\theta_i - d_j}\big) \big] - \mathrm{KL}\big(g \,\|\, p\big)$$

where g is the variational distribution and p is the prior over (θ, d). We take the posterior means from g as point estimates for the d_j of each question.

4 Method

In this section, we elaborate on the details of RIDE-Math. Inspired by the IRT-based difficulty estimation method with LLMs acting as students (Truong et al., 2025), we construct a difficulty ranker for math questions by performing parameter estimation described in Section 3. This ranker serves as a reward model by providing difficulty reward signals,

which are used to guide reinforcement learning on the existing high-difficulty dataset DeepMath (He et al., 2025). Through this rewriting process, we are able to generate difficulty in evolving math reasoning data. The overall architecture of our method is shown in Figure 2.

4.1 IRT-guided Difficulty Ranker

4.1.1 IRT Parameter Estimation

We draw $N = 2,000$ math questions from the DeepMath dataset to construct a quiz. We then employ $M = 35$ cutting-edge LLMs with different parameter scales and architectures as students to solve these questions, thereby constructing a response matrix $\mathbf{Y} \in \{0, 1\}^{M \times N}$. Specifically, for a math question j, the response vector can be described as

$$\mathbf{v}^j = [\mathbb{I}[g^j = y_1], \mathbb{I}[g^j = y_2]..., \mathbb{I}[g^j = y_M]]^\top$$

Here, $\mathbb{I}$ denotes the $0 - 1$ indicator function, g^j denotes the answer to the j-th question, y_i represents the response of the i-th student model. After obtaining the response vectors for N questions, we combine them to form the response matrix Y:

$$\mathbf{Y} = \big[\, \mathbf{v}^1, \; \mathbf{v}^2, \; \ldots, \; \mathbf{v}^N \,\big]$$

We perform IRT estimation based on the response matrix $\mathbf{Y}$. Following the parameter estimation method described in Section 3, we obtain an IRT-estimated difficulty d for each question and construct N question-difficulty pairs (q, d) for training the difficulty ranker, where q denotes the question.

4.1.2 Pairwise Difficulty Ranker

In traditional IRT, estimating the difficulty of a new question requires collecting fresh student response data. To endow IRT difficulty estimation with generalization to unseen questions, we adopt an amortized approach (Truong et al., 2025), which extracts content features via an embedding model and learn a mapping from question content to difficulty value. However, due to the domain-specific symbolic semantics of math questions (Mirzadeh et al., 2025), directly regressing from embeddings to a scalar difficulty may result in unreliable performance. Therefore, instead of regressing the difficulty value, we frame the task as a pairwise ranking question, training a ranker to identify the more difficult question from a pair of question embeddings. We use OpenAI's text-embedding-3-large [1] to obtain embedding vectors for each question-difficulty pair

---

[1] https://platform.openai.com/docs/models/text-embedding-3-large

Figure 2: The overall architecture of RIDE. RIDE trains a difficulty ranker based on IRT estimations to provide reward signals, guiding reinforcement learning to drive the LLM to rewrite original math questions into variations that expose model's reasoning vulnerabilities.

(q, d), creating N question-embedding-difficulty triplets as (q, e, d). We then group these pairs by fine-grained topics (Gao et al., 2025) like algebra, geometry, and so on. Within each subcategory, ranking data are generated by forming pairwise combinations of questions. Specifically, for any two questions (q_i, q_j) within the same subcategory, we create the ordered pair (e_i, e_j, r_{ij}) and its symmetric counterpart $(e_j, e_i, 1 - r_{ij})$ to reduce positional bias, where r_{ij} denotes to the ranking label: it equals to 1 if the question i's difficulty d_i exceeds the question j's difficulty d_j, and 0 otherwise. To account for the influence of the magnitude gap between difficulty scores d, we assign a weight to each ranking pair. For (e_i, e_j, r_{ij}), the weight is $w_{ij} = \sqrt{|d_i - d_j|}$. We use these pairwise samples to train a multilayer perceptron (MLP) as the difficulty ranker. The input $\mathbf{x}$ of MLP is a fusion of absolute and relative features:

$$\mathbf{x}_{ij} = \big(e_i \,||\, e_j \,||\, e_i - e_j \,||\, |e_i - e_j| \big)$$

Weighted binary cross-entropy loss is used as the optimization target to train an MLP with hyperparameter ϕ. The MLP ranker outputs the logit and calculates $p(i, j)$, which measures the probability that question i is more difficult than question j:

$$p(i, j) = \sigma(\mathrm{MLP}_\phi(\mathbf{x}_{ij}))$$

$$\mathcal{L}_{\mathrm{BCE}} = \frac{1}{|\mathcal{B}|} \sum_{(i,j) \in \mathcal{B}} w_{ij} \big(-r_{ij} \log p(i, j) - (1 - r_{ij}) \log\big(1 - p(i, j)\big) \big)$$

p_{ij} will be used to form the difficulty reward for rewriting questions in reinforcement learning.

4.2 Reinforcement Learning for Difficulty Evolution

We use Qwen3-8B (Team, 2025) as the base model, trained via Supervised Fine-Tuning (SFT) followed by Reinforcement Learning (RL). We curate 2,000 rewriting pairs $\mathcal{D}$ by distilling and filtering GPT-5-mini [2] outputs, then perform full-parameter SFT to equip the model with an initial ability to rewrite questions q into harder variants q' and align the model's rewritten output with format constraints.

In the RL stage, we use the Group Sequence Policy Optimization (GSPO) algorithm (Zheng et al., 2025) for optimization. Starting from SFT model with parameter θ_{SFT}, for each q we sample a group $\mathcal{G}(q) = \{q'_k\}_{k=1}^K \sim \mathcal{P}_\theta(\cdot|q)$ with group size K, compute rewards $R(q, q'_k)$ and group-normalized advantages, and update model parameter θ with GSPO. Our rewards consist of:

- **Difficulty Reward.** We obtain embedding vectors e and e' for the original question q and its rewrite q', respectively, and concatenate them as the input to the difficulty ranker. The ranker returns $p(q', q)$ and its reverse $p(q, q')$, which respectively describe the probabilities that q' is harder than q and vice versa. The difficulty reward is defined as:

$$R_{\mathrm{diff}} = p(q', q) - p(q, q')$$

---
[2] https://openai.com/

- **Correctness Reward.** Due to the base model's limited reasoning ability, the rewritten questions may contain errors. We use GPT-5-mini to verify each rewrite and output a correctness reward $R_{\text{cor}} \in \{-1, 1\}$, with -1 for incorrect and 1 for correct.

Given reward weights α and β, the final reward R is defined as their weighted sum. For each q with samples $\mathcal{G}(q) = \{q'_k\}_{k=1}^K$, let $R_k \equiv R(q, q'_k)$ and compute advantage A_k:

$$R = \alpha R_{\text{diff}} + \beta R_{\text{cor}}, \quad A_k = \frac{R_k - \frac{1}{K}\sum_{k=1}^K R_k}{\text{std}(R_{1:K})},$$

where $\text{std}(R_{1:K})$ denotes the standard deviation over the group $\{R_i\}_{i=1}^K$. Let θ_{old} be the policy for sampling $\mathcal{G}(q)$, initialized as θ_{SFT} and updated online to θ. The sequence-level importance ratio:

$$\rho_k(\theta) = \left(\frac{\mathcal{P}_\theta(q'_k \mid q)}{\mathcal{P}_{\theta_{\text{old}}}(q'_k \mid q)} \right)^{1/|q'_k|}$$

$$= \exp\left(\frac{1}{|q'_k|} \sum_{t=1}^{|q'_k|} \log \frac{\pi_\theta(q'_{k,t} \mid q, q'_{k,<t})}{\pi_{\theta_{\text{old}}}(q'_{k,t} \mid q, q'_{k,<t})} \right)$$

Here, t indexes positions in the generated response q'_k; $q'_{k,t}$ denotes the t-th response token and $q'_{k,<t}$ is its prefix. The normalization length $|q'_k|$ counts response tokens only, and accordingly $\log \mathcal{P}_\theta(q'_k \mid q)$ is computed as the sum of token-level log probabilities over those response positions. We maximize the clipped surrogate:

$$\mathcal{L}_{\text{GSPO}}(\theta) = \mathbb{E}_{q \in \mathcal{D}} \left[\frac{1}{K} \sum_{k=1}^K \min \Big(\rho_k(\theta) A_k, \right.$$

$$\left. \text{clip}\big(\rho_k(\theta), 1 - \varepsilon, 1 + \varepsilon \big) A_k \Big) \right]$$

At iteration i, we set $\theta_{\text{old}} = \theta^{(i)}$; for each source question q, we sample a group $\mathcal{G}(q)$ and compute the component rewards R_{diff}, R_{cor} and their mixture R, form the group-normalized advantages A_k, and then update the parameters by maximizing the GSPO surrogate:

$$\theta^{(i+1)} = \arg\max_\theta \mathcal{L}_{\text{GSPO}}(\theta)$$

After reward convergence, we obtain the difficulty-aware rewriting model **RIDE-8B**. Given an original question q_{original} and answer a_{original} from existing benchmarks, RIDE-8B generates a rewritten question q_{rewrite}, solution s_{rewrite}, and answer a_{rewrite}. The prompt (Appendix A.3) provides only high-level guidance rather than prescriptive rules, allowing the model to freely explore difficulty progression paths. Including the solution s_{rewrite} in the output strengthens serves as a chain-of-thought for question and answer consistency.

5 Experiment

5.1 Experiment Setup

We use our rewriting model **RIDE-8B** to perform difficulty evolution on the competition-level mathematical-reasoning benchmarks AMC-23 and AIME-24. Using GPT-5, we filter out questions that are unsolvable or have incorrect answers to construct the final perturbed benchmarks **RIDE-AMC** and **RIDE-AIME**, which are further manually checked to ensure answer correctness. We evaluate the pass@1 performance of LLMs in the zero-shot setting. In addition, we extract data from the DeepMath dataset for rewriting, and after filtering with DeepSeek-V3.1 (DeepSeek-AI, 2024), we obtain 10K high-quality mathematical reasoning samples, referred to as **RIDE-DeepMath**, which serve as training data to improve the models' ability for mathematical reasoning.

5.2 Main Results

We evaluate 28 LLMs comprising 7 proprietary models and 21 open-source models, spanning parameter counts from 0.6B to 1TB and covering multiple model series. We report pass@1 performance on the original AMC-23 and AIME-24 benchmarks, and then apply the same prompts to our perturbed benchmarks, RIDE-AMC and RIDE-AIME, again recording pass@1 performance. To quantify robustness, we compute the performance drop rate (PDR) (Li et al., 2024):

$$\text{PDR} = 1 - \frac{\frac{1}{|\mathcal{D}_a|} \sum_{(x,y) \in \mathcal{D}_a} \mathbb{I}[\text{LM}(x) = y]}{\frac{1}{|\mathcal{D}|} \sum_{(x,y) \in \mathcal{D}} \mathbb{I}[\text{LM}(x) = y]},$$

where x and y denote the question and the answer, respectively, $\mathcal{D}$ is the original benchmark (AMC-23 or AIME-24), $\mathcal{D}_a$ is the corresponding perturbed benchmark (RIDE-AMC or RIDE-AIME), $\text{LM}(\cdot)$ is the model's prediction, and $\mathbb{I}[\cdot]$ is the indicator function. Lower PDR indicates greater robustness. Results are presented in Table 1.

For AMC-23 and RIDE-AMC we use Qwen's non-thinking mode, whereas for AIME-24 and RIDE-AIME we use Qwen's thinking mode. Results show that our difficulty evolution perturbation

Model	Params	AIME-24	RIDE-AIME	PDR (↓%)	AMC-23	RIDE-AMC	PDR (↓%)
Proprietary Models							
Claude-4-Sonnet	-	40.00	36.67	8.33	85.00	82.50	2.94
Claude-4.1-Opus	-	53.33	36.67	31.24	87.50	82.50	5.71
Gemini-2.0-Flash	-	30.00	30.00	0.00	85.00	80.00	5.88
GPT-3.5-turbo	-	10.00	3.33	66.70	55.00	50.00	9.09
GPT-o3-mini	-	76.67	76.67	0.00	100.00	97.50	2.50
GPT-5	-	93.33	86.67	7.14	100.00	100.00	0.00
Grok-4	-	100.00	96.67	3.33	100.00	95.00	5.00
Open-source Models							
DeepSeek-V3.1	671B	60.00	56.67	5.55	87.50	85.00	2.86
DeepSeek-V3.1-Thinking	671B	93.33	83.33	10.71	100.00	100.00	0.00
DeepSeek-V4-Flash	284B	93.33	86.67	7.14	100.00	87.50	12.50
gemma-4-E4B-it	4B	56.67	46.67	17.65	95.00	87.50	7.89
gemma-4-26B-A4B-it	26B	80.00	73.33	8.34	97.50	82.50	15.38
GLM-4.5	355B	93.33	80.00	14.28	100.00	92.50	7.50
Kimi-K2-Instruct	1TB	73.33	56.67	22.72	90.00	85.00	5.56
Kimi-K2.5	1TB	76.67	66.67	13.04	95.00	82.50	13.16
Llama2-70B	70B	26.67	3.33	87.51	40.00	30.00	25.00
Llama3.1-70B	70B	20.00	6.67	66.65	47.50	30.00	36.84
Llama3.1-405B	405B	23.33	6.67	71.41	47.50	35.00	26.32
Llama4-Scout	109B	30.00	3.33	88.90	57.50	45.00	21.74
Mistral-large	123B	30.00	20.00	33.33	70.00	60.00	14.29
Qwen2.5-7B	7B	10.00	10.00	0.00	50.00	30.00	40.00
Qwen2.5-Math-7B	7B	16.67	3.33	80.02	60.00	32.50	45.83
Qwen2.5-Math-72B	72B	26.67	10.00	62.50	70.00	60.00	14.29
Qwen2.5-72B	72B	16.67	10.00	40.01	70.00	52.50	25.00
Qwen3-0.6B	0.6B	10.00	3.33	66.70	37.50	20.00	46.67
Qwen3-30B-A3B	30B	83.33	80.00	4.00	80.00	72.50	9.38
Qwen3.5-35B-A3B	35B	96.67	90.00	6.90	95.00	90.00	5.26
Qwen3.6-35B-A3B	35B	96.67	90.00	6.90	95.00	87.50	7.89

Table 1: Comparison of the model's pass@1 performance before and after benchmark perturbation. After benchmark perturbation, most models show a significant performance drop. The top-3 models with the largest average performance decline are highlighted in blue.

method leads to performance drops in the majority of both proprietary and open-source models, which shows the validation of our method. On the more challenging benchmark AIME-24, the average PDR is higher than on AMC-23. Across all models, the mean PDR reached 22.24%. From the model perspective, proprietary models generally have lower PDRs, indicating better robustness. Open-source models show substantial variation, and several LLaMA and Qwen models suffer large declines, with the highest PDR reaching 88.90%.

6 Analysis

In this section, we conduct experiments to explore and analyze the effectiveness and impact of RIDE.
Pass@n Performance. To verify the stability of our method against model performance perturbations, we evaluate Qwen2.5-Math-72B and Llama-4-Scout on AIME-24, AMC-23, and their perturbed RIDE-AIME and RIDE-AMC using pass@n (n = 1, 2, 4, 8). Results (Figure 3) show that accuracy improves as n increases, but performance on perturbed benchmarks remains notably lower, confirming the stability of our method in testing robustness.
Win Rate Comparison of RIDE and Other Methods. To evaluate rewrite quality, we design prompts assessing completeness, clarity, conceptual consis-

Figure 3: Comparison of pass@n performance before and after benchmark perturbation.

tency, structural perturbations, and avoidance of shortcuts (Appendix A.3). GPT-5 acts as an evaluator to compare the outputs from different methods. Each pair is judged twice with swapped order to mitigate position bias. We compute two win rate metrics: (1) Average win rate—the proportion of times a method is selected across both evaluations; (2) Consistent win rate—the proportion of questions where a method is selected in both evaluations. Ties are allowed in the evaluator's output. We run three rounds and report average results. We

compare our method with the following method: (1) **Rule-based method.** Following GSM-Plus (Li et al., 2024), we use Qwen3-8B to generate perturbed data with the same prompting strategy as rule-based baseline. (2) **Contrastive prompting.** Following the contrastive prompting method (Yao, 2025), we instruct Qwen3-8B to generate an easier and a more difficult rewrite at the same time and choose the difficult one as the final question. (3) **SFT-only model and RL model without difficulty reward.** We generate rewrites using the SFT-only model (without RL) and an RL model trained without the difficulty reward R_{diff} as part of our ablation study. As shown in Table 2, our method significantly outperforms the rule-based and contrastive prompting on both metrics, demonstrating that RIDE rewrites achieve higher quality. Ablation study also shows the effect of our RL stage and difficulty reward.

Compared Method	Dataset	Average		Consistent	
		Baseline	RIDE	Baseline	RIDE
Rule-based	AMC-23	40.83	**58.75**	28.33	**48.33**
	AIME-24	36.67	**63.33**	28.89	**55.56**
Contrastive Prompting	AMC-23	49.17	**50.83**	40.00	**40.83**
	AIME-24	32.78	**67.22**	26.67	**61.11**
SFT-only	AMC-23	38.75	**60.00**	33.33	**53.33**
	AIME-24	36.67	**62.22**	26.67	**52.22**
w/o R_{diff}	AMC-23	43.75	**54.17**	35.83	**47.50**
	AIME-24	27.78	**72.22**	21.11	**65.56**

Table 2: Win rate comparison of RIDE and baselines.

Data Augmentation For Training Data. Our method also serves as an effective data augmentation strategy for mathematical reasoning. Using RIDE-8B, we apply rewriting to the Deep-Math dataset and filtered incorrect samples with DeepSeek-V3.1, yielding **RIDE-DeepMath** with over 10K examples. Without SFT, we train Qwen3-0.6B, Qwen3-1.7B and Gemma3-4B-It with GSPO, producing **RIDE-Qwen-0.6B-Thinking**, **RIDE-Qwen-1.7B** and **RIDE-Gemma-4B**. Results (Table 3) show that models trained with RL on our data achieve improvements over their base models. In particular, RIDE-Qwen-0.6B-Thinking and RIDE-Gemma3-4B have surpassed GPT-4o and Qwen2.5-Math-72B, and are close to Qwen3-4B in the non-thinking mode.

Case Study and Rewrite Strategy Analysis. Figure 4a illustrates the rewritten question. The original question is a coupon collector question with replacement. The rewritten question (1) clarifies the "pick 10 marbles at a time with replacement" procedure without changing the core idea; (2) raises

Model	Params	AIME-25
GPT-4o	-	13.33
Qwen3-0.6B	0.6B	3.33
Qwen3-0.6B-Thinking	0.6B	10.00
RIDE-Qwen-0.6B-Thinking	0.6B	**20.00**
Qwen3-1.7B	1.7B	6.67
RIDE-Qwen-1.7B	1.7B	**13.33**
Qwen3-4B	4B	23.33
Gemma3-4B-It	4B	13.33
RIDE-Gemma3-4B	4B	**20.00**
Qwen2.5-Math-7B	7B	6.67
Qwen2.5-Math-72B	72B	13.33
Qwen3-30B-A3B	30B	23.33

Table 3: Pass@1 performance comparison on AIME-25 benchmark. Models trained with reinforcement learning on our augmented rewritten data achieve higher performance than the corresponding base models.

the target success probability, increasing the required trials; and (3) requires using the Poisson approximation and the union bound, increasing restrictions. To analyze these rewrites, we distill six core rewrite strategies from the rewritten questions: (1) Wording and Paraphrasing Modification, (2) Distracting Info, (3) Numerical Substitution, (4) Add Extra Steps, (5) Change Constraints, and (6) Change Target. (Detailed descriptions are provided in the Appendix A.4). Our analysis (Figure 4b) reveals that these strategies are frequently combined. Over 60% of the rewritten questions are composed of two or more strategies. We categorize strategies 1-3 as Surface Strategies, which have a minor impact on reasoning depth, and the others as Deep Strategies, which significantly affect the required reasoning. Statistics show that rewrites using a mix of both Surface and Deep strategies are the most common (44.3%). The accuracy of Qwen2.5-Math-72B and Llama4-Scout on questions corresponding to each strategy shows that performance varies across different strategies. In summary, our method can generate combinations of one or more rewrite strategies without explicitly defining specific rules. These combinations effectively provide a difficulty perturbation for the original question.

The Relation Between Difficulty and Robustness. To disentangle whether the performance drop stems from increased human-perceived difficulty or from the model's inherent vulnerability, we apply McNemar's test on paired samples from the surface-level rewriting dataset, which preserves human cognitive difficulty. The resulting p-value of 2.3847×10^{-11} reveals a significant asymmetry, confirming that the drop is driven by non-robustness rather than difficulty shifts. Moreover, consistent degradation

Original Question: A bag contains 100 unique marbles. With replacement, you pick 10 marbles at a time, at random. How many times must you pick the marbles to have a **95%** probability of having seen every unique marble at least once ?

Original Answer: 76

Rewritten Question: A bag contains 100 unique marbles. You repeatedly draw 10 marbles uniformly at random from the bag, record the set of distinct marbles seen in that draw, and then return those 10 marbles to the bag. You do this many independent times. Approximate the smallest number of such draws required so that the probability of having seen every unique marble at least once is at least **0.99**. Use the Poisson approximation for the coupon collector problem (i.e., approximate the probability that a particular marble has not been seen after n draws by $e^{-n \cdot p}$ where $p = 10/100$ is the probability of seeing that marble in a single draw), and then apply the union bound to obtain a conservative estimate. Give a numerical answer .

Rewritten Answer: 93

(a) Case study for our method.

(b) Rewrite strategy analysis.

Figure 4: Case study and analysis. (a) The original and rewritten questions from DeepMath and RIDE-DeepMath. (b) The analysis of rewrite strategies.

across all difficulty levels (Appendix B.1) further indicates that the effect is independent of reasoning depth. In essence, "difficulty evolution" transforms questions into formats challenging for the model and the two perspectives are complementary rather than contradictory.

Effect Analysis. We additionally train RIDE-4B based on Qwen3-4B and keep SFT checkpoints (RIDE-4B-SFT, RIDE-8B-SFT) to disentangle SFT from RL effects. As shown in Table 4, Difficulty score is defined as the predicted probability from our difficulty ranker that the rewritten question is more difficult than the original. The results show that the RL-tuned RIDE-8B achieves the highest average Difficulty score, thereby validating the effect of our RL strategy. We also conduct ablation studies on the RIDE-4B model. We intro-

duce two variations: (1) replacing the verifier for the correctness reward R_{cor} with DeepSeek-V3.2 (RIDE-4B-DeepSeek), and (2) removing R_{cor}. We employ GPT-5 to evaluate the correctness. The results indicate that RIDE-4B (GPT-5-mini verifier) achieves the highest correctness. RIDE-4B-DeepSeek model follows, as DeepSeek-V3.2 tends to output more false negatives (see Appendix B.4), whereas removing R_{cor} leads to decline in correctness. The DeepSeek verifier also improves correctness shows that our method is not heavily dependent on proprietary models, as open-source models are also effective. This confirms the validity and necessity of our correctness reward. Besides, We compare different IRT models for difficulty estimation. The 2-PL model adds a discrimination parameter, while the 3-PL further introduces a guessing parameter. We randomly mask 20% of the response matrix for estimation, and evaluate performance using AUC-ROC. We select the 1-PL model with VI for parameter estimation.

Model	Difficulty	Correctness
Qwen3-8B	74.61	40.00
RIDE-8B-SFT	78.78	40.00
RIDE-8B	**80.18**	**42.50**
RIDE-4B	-	**45.00**
RIDE-4B-DeepSeek	-	37.50
RIDE-4B w/o R_{cor}	-	32.50

Model	Method	AUC-ROC
1-PL	VI	**91.29**
1-PL	MCMC	89.81
2-PL	VI	86.56
3-PL	VI	91.01

Table 4: Effect Analysis. The top table shows the ablation study on RL and the correctness reward R_{cor}, while the bottom table compares different IRT models.

7 Conclusion

In this paper, we propose a question rewriting framework based on difficulty evolution. The method estimates question difficulty using IRT, then trains a difficulty ranker to provide a difficulty reward, guiding reinforcement learning for the rewriting. Experiments show that our method causes performance drops in 28 LLMs, validating its effectiveness and robustness in adversarial perturbation. Our method outperforms traditional rule-based perturbations and can be applied for training data augmentation. Further analyses confirm its effectiveness, offering a new perspective on robust evaluation from the view of "question difficulty".

Limitations

While RIDE demonstrates significant efficacy in evaluating mathematical reasoning robustness, several areas for refinement remain. First, the IRT parameter estimation necessitates an initial response matrix from multiple models. The approach requires a degree of upfront computational investment when migrating to entirely new domains. Second, the LLM-based verifier used for correctness rewards exhibits a "conservative" tendency with relatively low recall. While this ensures high precision in reward signals, it may result in some valid rewrites being discarded, potentially affecting sample efficiency during the reinforcement learning stage. Finally, as the study currently focuses on competitive mathematical benchmarks with objective evaluation criteria , the generalizability of this difficulty-evolving mechanism to more open-ended reasoning scenarios, such as code generation or complex creative writing, remains an avenue for future exploration.

References

Iz Beltagy, Matthew E. Peters, and Arman Cohan. 2020. Longformer: The long-document transformer. *Preprint*, arXiv:2004.05150.

Shuaichen Chang, Jun Wang, Mingwen Dong, Lin Pan, Henghui Zhu, Alexander Hanbo Li, Wuwei Lan, Sheng Zhang, Jiarong Jiang, Joseph Lilien, Steve Ash, William Yang Wang, Zhiguo Wang, Vittorio Castelli, Patrick Ng, and Bing Xiang. 2023. Dr.spider: A diagnostic evaluation benchmark towards text-to-sql robustness. *Preprint*, arXiv:2301.08881.

Ching Han Chen and Ming Fang Shiu. 2025. Kaqg: A knowledge-graph-enhanced rag for difficulty-controlled question generation.

Jianlyu Chen, Shitao Xiao, Peitian Zhang, Kun Luo, Defu Lian, and Zheng Liu. 2024. M3-embedding: Multi-linguality, multi-functionality, multi-granularity text embeddings through self-knowledge distillation. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 2318–2335, Bangkok, Thailand. Association for Computational Linguistics.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. 2021. Training verifiers to solve math word problems. *Preprint*, arXiv:2110.14168.

DeepSeek-AI. 2024. Deepseek-v3 technical report. *Preprint*, arXiv:2412.19437.

Wanyong Feng, Peter Tran, Stephen Sireci, and Andrew Lan. 2025. *Reasoning and Sampling-Augmented MCQ Difficulty Prediction via LLMs*, pages 31–45.

Bofei Gao, Feifan Song, Zhe Yang, Zefan Cai, Yibo Miao, Qingxiu Dong, Lei Li, Chenghao Ma, Liang Chen, Runxin Xu, Zhengyang Tang, Benyou Wang, Daoguang Zan, Shanghaoran Quan, Ge Zhang, Lei Sha, Yichang Zhang, Xuancheng Ren, Tianyu Liu, and Baobao Chang. 2025. Omni-MATH: A universal olympiad level mathematic benchmark for large language models. In *The Thirteenth International Conference on Learning Representations*.

Shahriar Golchin and Mihai Surdeanu. 2024. Time travel in llms: Tracing data contamination in large language models. *Preprint*, arXiv:2308.08493.

Zhiwei He, Tian Liang, Jiahao Xu, Qiuzhi Liu, Xingyu Chen, Yue Wang, Linfeng Song, Dian Yu, Zhenwen Liang, Wenxuan Wang, Zhuosheng Zhang, Rui Wang, Zhaopeng Tu, Haitao Mi, and Dong Yu. 2025. Deepmath-103k: A large-scale, challenging, decontaminated, and verifiable mathematical dataset for advancing reasoning. *CoRR*, abs/2504.11456.

Yutao Hou, Zeguan Xiao, Fei Yu, Yihan Jiang, Xuetao Wei, Hailiang Huang, Yun Chen, and Guanhua Chen. 2025. Automatic robustness stress testing of llms as mathematical problem solvers. *Preprint*, arXiv:2506.05038.

Kaixuan Huang, Jiacheng Guo, Zihao Li, Xiang Ji, Jiawei Ge, Wenzhe Li, Yingqing Guo, Tianle Cai, Hui Yuan, Runzhe Wang, Yue Wu, Ming Yin, Shange Tang, Yangsibo Huang, Chi Jin, Xinyun Chen, Chiyuan Zhang, and Mengdi Wang. 2025. Math-perturb: Benchmarking llms' math reasoning abilities against hard perturbations. *Preprint*, arXiv:2502.06453.

Diederik P Kingma and Max Welling. 2013. Autoencoding variational bayes. *arXiv preprint arXiv:1312.6114*.

John P. Lalor, Hao Wu, and Hong Yu. 2019. Learning latent parameters without human response patterns: Item response theory with artificial crowds. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 4249–4259, Hong Kong, China. Association for Computational Linguistics.

John Patrick Lalor and Pedro Rodriguez. 2023. py-irt: A scalable item response theory library for python. *INFORMS Journal on Computing*, 35(1):5–13.

Yunshi Lan, Xinyuan Li, Hanyue Du, Xuesong Lu, Ming Gao, Weining Qian, and Aoying Zhou. 2026. Survey of Natural Language Processing for Education: Taxonomy, Systematic Review, and Future Trends . *IEEE Transactions on Knowledge & Data Engineering*, 38(01):659–678.

Huihan Li, You Chen, Siyuan Wang, Yixin He, Ninareh Mehrabi, Rahul Gupta, and Xiang Ren. 2025. Diagnosing memorization in chain-of-thought reasoning, one token at a time. *Preprint*, arXiv:2508.02037.

Qintong Li, Leyang Cui, Xueliang Zhao, Lingpeng Kong, and Wei Bi. 2024. GSM-plus: A comprehensive benchmark for evaluating the robustness of LLMs as mathematical problem solvers. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 2961–2984. Association for Computational Linguistics.

Seyed Iman Mirzadeh, Keivan Alizadeh, Hooman Shahrokhi, Oncel Tuzel, Samy Bengio, and Mehrdad Farajtabar. 2025. GSM-symbolic: Understanding the limitations of mathematical reasoning in large language models. In *The Thirteenth International Conference on Learning Representations*.

Kajal Negi, Giovanni Puccetti, and Andrea Esuli. 2026. Gsm-identity: Evaluating mathematical reasoning in llms via equivalence transformations. *Machine Learning*, 115(4):88.

Felipe Maia Polo, Lucas Weber, Leshem Choshen, Yuekai Sun, Gongjun Xu, and Mikhail Yurochkin. 2024. tinybenchmarks: evaluating llms with fewer examples. In *ICML*.

Georg Rasch. 1993. *Probabilistic models for some intelligence and attainment tests.* ERIC.

Jeff Rasley, Samyam Rajbhandari, Olatunji Ruwase, and Yuxiong He. 2020. Deepspeed: System optimizations enable training deep learning models with over 100 billion parameters. In *KDD*, pages 3505–3506.

Alexander Scarlatos, Nigel Fernandez, Christopher Ormerod, Susan Lottridge, and Andrew Lan. 2025. Smart: Simulated students aligned with item response theory for question difficulty prediction. *Preprint*, arXiv:2507.05129.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, Y. K. Li, Y. Wu, and Daya Guo. 2024. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *Preprint*, arXiv:2402.03300.

Qwen Team. 2025. Qwen3 technical report. *Preprint*, arXiv:2505.09388.

Sang T. Truong, Yuheng Tu, Percy Liang, Bo Li, and Sanmi Koyejo. 2025. Reliable and efficient amortized model-based evaluation. In *Forty-second International Conference on Machine Learning*.

Zain Ul Abedin, Shahzeb Qamar, Lucie Flek, and Akbar Karimi. 2025. ArithmAttack: Evaluating robustness of LLMs to noisy context in math problem solving. In *Proceedings of the The First Workshop on LLM Security (LLMSEC)*, pages 48–53, Vienna, Austria. Association for Computational Linguistics.

Clara Vania, Phu Mon Htut, William Huang, Dhara Mungra, Richard Yuanzhe Pang, Jason Phang, Haokun Liu, Kyunghyun Cho, and Samuel R. Bowman. 2021. Comparing test sets with item response theory. *Preprint*, arXiv:2106.00840.

Leandro von Werra, Younes Belkada, Lewis Tunstall, Edward Beeching, Tristan Thrush, Nathan Lambert, Shengyi Huang, Kashif Rasul, and Quentin Gallouédec. 2020. Trl: Transformer reinforcement learning. https://github.com/huggingface/trl.

Mingqi Wu, Zhihao Zhang, Qiaole Dong, Zhiheng Xi, Jun Zhao, Senjie Jin, Xiaoran Fan, Yuhao Zhou, Huijie Lv, Ming Zhang, Yanwei Fu, Qin Liu, Songyang Zhang, and Qi Zhang. 2025. Reasoning or memorization? unreliable results of reinforcement learning due to data contamination. *Preprint*, arXiv:2507.10532.

Zhangchen Xu, Yuetai Li, Fengqing Jiang, Bhaskar Ramasubramanian, Luyao Niu, Bill Yuchen Lin, and Radha Poovendran. 2025. Tinyv: Reducing false negatives in verification improves rl for llm reasoning. *Preprint*, arXiv:2505.14625.

Boyang Xue, Qi Zhu, Rui Wang, Sheng Wang, Hongru Wang, Fei Mi, Yasheng Wang, Lifeng Shang, Qun Liu, and Kam-Fai Wong. 2025. Reliablemath: Benchmark of reliable mathematical reasoning on large language models. *Preprint*, arXiv:2507.03133.

An Yang, Beichen Zhang, Binyuan Hui, Bofei Gao, Bowen Yu, Chengpeng Li, Dayiheng Liu, Jianhong Tu, Jingren Zhou, Junyang Lin, Keming Lu, Mingfeng Xue, Runji Lin, Tianyu Liu, Xingzhang Ren, and Zhenru Zhang. 2024. Qwen2.5-math technical report: Toward mathematical expert model via self-improvement. *Preprint*, arXiv:2409.12122.

Bo Yang, Qingping Yang, Yingwei Ma, and Runtao Liu. 2025a. UTMath: A benchmark for math evaluation with unit test. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, pages 5899–5915, Suzhou, China. Association for Computational Linguistics.

Yuli Yang, Hiroaki Yamada, and Takenobu Tokunaga. 2025b. Evaluating robustness of LLMs to numerical variations in mathematical reasoning. In *The Sixth Workshop on Insights from Negative Results in NLP*, pages 171–180, Albuquerque, New Mexico. Association for Computational Linguistics.

Liang Yao. 2025. Large language models are contrastive reasoners. *Preprint*, arXiv:2403.08211.

Jianxing Yu, Shiqi Wang, Hanjiang Lai, Wenqing Chen, Yanghui Rao, Qinliang Su, and Jian Yin. 2025. Generating commonsense reasoning questions with controllable complexity through multi-step structural composition. In *Proceedings of the 31st International Conference on Computational Linguistics*, pages 2261–2276, Abu Dhabi, UAE. Association for Computational Linguistics.

Hugh Zhang, Jeff Da, Dean Lee, Vaughn Robinson, Catherine Wu, Will Song, Tiffany Zhao, Pranav Raja, Charlotte Zhuang, Dylan Slack, Qin Lyu, Sean Hendryx, Russell Kaplan, Michele Lunati, and Summer Yue. 2024. A careful examination of large language model performance on grade school arithmetic. *Preprint*, arXiv:2405.00332.

Chujie Zheng, Shixuan Liu, Mingze Li, Xiong-Hui Chen, Bowen Yu, Chang Gao, Kai Dang, Yuqiong Liu, Rui Men, An Yang, Jingren Zhou, and Junyang Lin. 2025. Group sequence policy optimization. *Preprint*, arXiv:2507.18071.

Yaowei Zheng, Richong Zhang, Junhao Zhang, Yanhan Ye, and Zheyan Luo. 2024. LlamaFactory: Unified efficient fine-tuning of 100+ language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 3: System Demonstrations)*, pages 400–410, Bangkok, Thailand. Association for Computational Linguistics.

Zihao Zhou, Shudong Liu, Maizhen Ning, Wei Liu, Jindong Wang, Derek Wong, Xiaowei Huang, Qiufeng Wang, and Kaizhu Huang. 2025. Is your model really a good math reasoner? evaluating mathematical reasoning with checklist. In *International Conference on Learning Representations*, volume 2025, pages 34238–34281.

A Experimental Setup

A.1 Implementation Details

We use the API interface provided by OpenAI to call models and obtain the response matrix of LLMs (for the GLM series, we use the ZHIPU interface). The size of the response matrix is 35×2000. We perform IRT parameter estimation through *py-irt* (Lalor and Rodriguez, 2023). The statistics of each student model's performance is shown in Figure 5, along with the accuracy and estimated ability θ are shown in Table 5. The results indicate that within the same model series (e.g., Qwen2.5 or Qwen3), model parameter size is positively correlated with capability. However, this relationship is not numerically linear. Additionally, frontier reasoning models generally exhibit higher capability scores.

In the SFT stage, we use the *LLaMA-Factory* (Zheng et al., 2024) framework for training, with a dataset of $2,000$ rewritten mathematical questions distilled from GPT-5-mini. In the reinforcement learning stage, we use the *TRL* (von Werra et al., 2020) framework for training, with $3,000$ questions extracted from the DeepMath dataset (He et al., 2025).

A.2 Hyperparameter Setup

The hyperparameters used in our work are summarized in Table 6. For the IRT parameter estimation and the training of the difficulty ranker, we perform a greedy search to select the optimal group of hyperparameters based on evaluation metrics. For the SFT and reinforcement learning stages, the hyperparameters are chosen by balancing model performance with the available computational resources.

A.3 Prompt Strategy

For constructing the response matrix and evaluating model performance on both the original benchmark and the perturbed benchmark, we use the same zero-shot prompt to instruct models to answer mathematical questions (Figure 6a), requiring only that answers follow a specific format for verification. In practice, we find that even without explicitly telling the model to "think step by step", all evaluated models still produce chain-of-thought outputs.

Figure 6b shows the prompt we use to guide the model in rewriting mathematical questions during the SFT and reinforcement learning stages. We

Model	Parameter	Pass@1 (%)	θ
Claude-3.5-haku	-	46.75	-1.132
Claude-3.7-sonnet	-	76.85	0.710
Deepseek-R1-Distill-Llama-8B	8B	74.65	0.552
Deepseek-R1-Distill-Qwen-1.5B	1.5B	71.65	0.324
Deepseek-R1-distill-Qwen-14B	14B	88.75	1.822
Deepseek-v3-0328	671B	85.85	1.534
Gemini-2.0-flash	-	82.65	1.203
Gemini-2.5-flash	-	93.15	2.406
Gemma3-12B-it	12B	64.80	-0.115
Gemma3-4B-it	4B	49.80	-0.970
GLM-4-9B-chat	9B	30.50	-2.038
GLM-4-plus	-	60.25	-0.347
GLM-Z1-airx	-	93.10	2.417
GLM-Z1-flash	-	91.80	2.222
GPT-3.5-turbo	-	29.85	-2.079
GPT-4o	-	64.15	-0.135
Grok-2	-	62.35	-0.213
Grok-3	-	81.25	1.064
Kimi-K2-Instruct	1TB	93.05	2.462
Llama-3.1-70B	70B	53.10	-0.770
Llama-3.1-8B	8B	28.20	-2.168
Llama-4-scout	109B	70.90	0.284
Mistral-7B-Instruct-V0.2	7B	13.20	-3.427
Mistral-Small-3.1-24B-Instruct	24B	50.05	-0.947
Qwen-math-72B	72B	75.05	0.555
Qwen-math-7B	7B	63.60	-0.143
Qwen2.5-0.5B	0.5B	19.25	-2.799
Qwen2.5-14B	14B	64.90	-0.106
Qwen2.5-72B	72B	71.90	0.332
Qwen2.5-7B	7B	56.20	-0.541
Qwen3-0.6B	0.6B	26.95	-2.263
Qwen3-14B	14B	77.05	0.735
Qwen3-32B	32B	79.00	0.883
Qwen3-235B-A22B	235B	83.95	1.262
QwQ-32B	32B	95.00	2.813

Table 5: Statistics of each student model's performance and estimated ability.

do not impose a single, detailed rule. Instead, we briefly outline several ways to increase difficulty and allow the model to improvise, making the trajectory of difficulty evolution unpredictable.

Figure 6c presents the prompt we use to instruct GPT-5 to choose the one that better meets the requirements from two rewritten questions, enabling us to compute the win rate of our method against the rule-based approach. We specify in detail that the rewritten question must address covering question completeness, clarity, conceptual consistency, structural perturbations, and the avoidance of reasoning shortcuts.

A.4 Rewrite Strategy

We distill six core rewrite strategies from the rewritten questions: (1) Wording and Paraphrasing Modification, (2) Distracting Info, (3) Numerical Substitution, (4) Add Extra Steps, (5) Change Constraints, and (6) Change Target. The detailed descriptions are shown in Table 7. To determine the strategies involved in each question, we employed a model-based annotation process. We fed each question to both GPT-5 and DeepSeek-V3.2 three times each, for a total of six annotations. A specific strategy was only recorded as being present for a given question if it was selected by a majority (i.e., at least three out of six) of the model runs.

B Effect Analysis

B.1 Orthogonality between question difficulty and robustness verification

The verification of model robustness and the evolution of question difficulty can coexist in our method. We define the robustness of LLMs in mathematical reasoning as follows: for a question x and the model's response correctness $y \in \{0, 1\}$, given a semantic-preserving transformation family $\mathcal{T}$, if $f(x) = y$, then for the vast majority of $t \in \mathcal{T}$, $f(t(x)) = y$ holds. Figure 8 shows that the semantic similarity between our rewritten and original questions consistently exceeds 80%, confirming

Hyperparameter	Description	Value
IRT & Difficulty Ranker		
M	The number of student models	35
N	The number of mathematical questions	2,000
S	The number of virtual students by VAE	200
T	The number of virtual students by Sampling	200
β-VAE	Weight of KLD loss for VAE	0.5
Latent dimension	Dimension of latent space	32
Priors	Prior distribution of IRT parameters	vague
Random Seed	Random seed for partitioning missing values in the response matrix	42
Batch size	Number of samples per batch	64
Embedding dimension	Dimension of input embeddings	3,072
Hidden dimension	Hidden layer size of MLP	(512,256)
Dropout rate	Dropout probability for hidden layers	0.3
Activation	Non-linear activation function	ReLU
Epochs (CV)	Training epochs for cross-validation	8 (5-CV)
Supervised Fine-Tuning		
Device	Device used for SFT	1 * NVIDIA A800 80GB PCIe
Finetuning type	Finetuning strategy	full
Template	Prompt/format template of LLaMA-Factory	qwen3
Cutoff length	Max sequence length (tokens)	8192
Per-device train batch size	Batch size per device	2
Gradient accumulation steps	Grad accumulation steps	4
Learning rate	Initial learning rate	1e-5
Epochs	Number of training epochs	3.0
Warmup ratio	Warmup ratio	0.1
Bf16	bfloat16 training	true
Deepspeed (Rasley et al., 2020)	Deepspeed Stage	3
Reinforcement Learning		
Device	Device used for RL	4 * NVIDIA A800 80GB PCIe
Finetuning type	Finetuning strategy	LoRA
Method	RL algorithm	GSPO
Per-device batch size	Prompts per device per step	1
Gradient accumulation steps	Steps to accumulate gradients	4
Group size K	Generations per prompt	4
Max prompt length	Max tokens of prompt	512
Max new tokens	Max tokens to generate per sample	4096
Temperature	Sampling temperature	0.7
Top-p	Nucleus sampling p	0.95
Max steps	Maximum training steps	500
KL coef	KL penalty coefficient	0.0
LoRA rank	Rank	64
LoRA α	Scaling factor	64
LoRA dropout	Dropout probability	0.05
Deepspeed	Deepspeed Stage	2
α	Weight of difficulty reward	0.5
β	Weight of correctness reward	0.5

Table 6: Main hyperparameter setup.

Figure 5: Statistics of each student model's performance. Difficulty Level is given by DeepMath Dataset.

Strategy	Definition
Wording	Rephrases the question using different vocabulary or structures without altering math logic.
Distracting	Adds irrelevant information, definitions, or values to the question description.
Numerical	Replaces key numerical values in the question with new values.
Extra Steps	Introduces new events or steps that must be incorporated into the calculation.
Constraints	Adds stricter limitations or alters core rules to change the solution's domain.
Target	Changes the final expression to a more complex or generalized version.

Table 7: Definitions of the Rewrite Strategies.

that performance degradation does not stem from semantic disparity. Building on this, we decouple question difficulty from robustness verification. We identify "surface-level modifications" that preserve reasoning depth. An example is shown in Figure 7. In this example, the evolution of the question is manifested in the formalized mathematical conditions and changes in phrasing, which do not impact the depth of reasoning required, making this a case for verifying model robustness. For example, Qwen2.5-72B answered the original question correctly but failed on the rewritten question. We collected similar surface-only rewrites and categorized them into three difficulty levels—easy, medium, and hard—based on the accuracy rates of

10 LLMs on the original questions. The questions rewritten using the surface-only strategy maintain a reasoning depth consistent with the original questions, leaving the surface form as the sole variable. If the model's performance degradation were solely dependent on difficulty, the magnitude of the performance drop on the rewritten questions should vary significantly across the three difficulty levels. Conversely, if question difficulty and robustness verification can be decoupled, the variations in performance decline across the three difficulty levels should be insignificant. We evaluated the performance degradation between the original and rewritten questions across different difficulty levels (Table 8). The results indicate that surface-level rewrit-

Level	Original Accuracy	Rewritten Accuracy	Δ
Easy	80.00	68.57	11.43
Medium	68.57	55.71	12.86
Hard	62.50	43.75	18.75

Table 8: Performance drop comparison across different difficulty levels.

ing induces performance degradation even on easy questions, thereby highlighting the necessity of robustness verification. Moreover, the performance drop across difficulty levels is not significant, with a particularly negligible variation in the magnitude of change between easy and medium questions. We additionally recorded the counts of "Correct on Original, Incorrect on Rewritten" and "Incorrect on Original, Correct on Rewritten" for each paired sample in the surface-level rewriting dataset and

calculated the p-value using McNemar's test. The resulting p-value of 2.3847×10^{-11} is substantially lower than 0.05, revealing a significant asymmetry. This demonstrates that the performance decline originates from the model's non-robustness rather than changes in difficulty. In summary, through case study and statistical analysis, we decoupled question difficulty from robustness verification and found that the two are orthogonal, allowing them to coexist within our method.

B.2 Effect of IRT models and difficulty ranker.

As a limited number of student models is not enough to estimate IRT parameters accurately, while employing a large number of LLMs as students is computationally costly, we augment the student–response data to simulate additional student behaviors. We adopt two augmentation strategies:

- **Variational Autoencoder (VAE) method.** We mitigate the scarcity of student responses by training a VAE (Kingma and Welling, 2013) on the response matrix $\mathbf{Y}$ to learn a low-dimensional manifold of student behavior. During generation, we draw a latent code $\mathbf{z}$ from the Gaussian prior and decode it into per-question correctness probabilities $\pi(\mathbf{z})$, from which Bernoulli draws yield a synthetic student-question response vector with conditional independence across items given $\mathbf{z}$:

$$\mathbf{r}_{\text{VAE},j} \mid \mathbf{z} \sim \text{Bernoulli}\big(\pi_j(\mathbf{z})\big),$$
$$j = 1, \ldots, N$$

- **Sampling method.** We simulate the responses of students by drawing from the empirical distribution observed in $\mathbf{Y}$. For each question j, we compute the empirical correctness rate C over the observed responses and use it as the Bernoulli success probability:

$$\mathbf{r}_{\text{Sampling},j} \sim \text{Bernoulli}\big(C_j\big),$$
$$j = 1, \ldots, N$$

Each sampled $\mathbf{r}_{\text{VAE}}$ and $\mathbf{r}_{\text{Sampling}}$ is then appended as a new student row to $\mathbf{Y}$.

These methods let us synthesize student–item response vectors that respect observed item statistics and student tendencies. We concatenate the synthetic responses $\mathbf{r}_{\text{VAE}}$ and $\mathbf{r}_{\text{Sampling}}$ with the originals to form an augmented matrix $\tilde{\mathbf{Y}} \in \{0, 1\}^{M+S+T,N}$:

$$\tilde{\mathbf{Y}} = \begin{bmatrix} \mathbf{Y} \\ \mathbf{R}_{\text{VAE}} \\ \mathbf{R}_{\text{Sampling}} \end{bmatrix},$$
$$\mathbf{R}_{\text{VAE}} = [\mathbf{r}_{\text{VAE}}^1, \ldots, \mathbf{r}_{\text{VAE}}^S]^\intercal,$$
$$\mathbf{R}_{\text{Sampling}} = [\mathbf{r}_{\text{Sampling}}^1, \ldots, \mathbf{r}_{\text{Sampling}}^T]^\intercal$$

S and T denote the number of synthetic students by VAE and sampling, respectively. Then the modeling ability of IRT calibration for question difficulties can be improved. We perform IRT parameter estimation based on the response matrix $\tilde{\mathbf{Y}}$.

As described in Section 6, we conducted additional experiments to verify the effectiveness of the choice of the IRT model and data augmentation methods. The results are shown in Table 9. We consider two priors provided by *py-irt*: a vague prior that exerts minimal influence so the likelihood largely drives estimation, and a hierarchical prior that treats parameters as draws from a shared group-level distribution with hyperpriors, enabling partial pooling to stabilize estimates and shrink extremes, especially with sparse data. For evaluation, in addition to AUC-ROC for discrimination, we also report the Brier Score, the mean squared difference between predicted probabilities and observed outcomes (lower is better), which captures overall probabilistic accuracy and calibration and thus complements AUC-ROC's ranking focus.

Besides, we explore regression, classification, and ranking methods to fit IRT-estimated question difficulties from textual features. Regression task is evaluated by RMSE, consistently yields values above 1 across models and embeddings, indicating large bias. Classification treats questions with difficulty below 0 as "easy" and above 0 as "hard," but F1 scores remain below 60% due to class imbalance. Finally, we adopt a pairwise ranking approach with AUC-ROC as the metric, achieving around 72%, with little variation across embedding models.

B.3 Statistics of RIDE rewritten model.

Starting from Qwen3-1.7B and Qwen3-4B, we trained RIDE-1.7B and RIDE-4B, and preserved SFT checkpoints (RIDE-1.7B-SFT, RIDE-4B-SFT, RIDE-8B-SFT) to separate SFT from RL effects. The questions rewritten by each model are evaluated in terms of average generation time, average token count, correctness, and semantic similarity.

Model	Method	Data Augmentation		Prior	AUC-ROC	Brier Score↓
		VAE	Sampling			
1-PL	VI	-	-	vague	89.81	11.97
1-PL	VI	-	-	hierarchical	90.03	11.89
1-PL	VI	✓	-	vague	91.01	11.54
1-PL	VI	✓	-	hierarchical	90.95	11.61
1-PL	VI	-	✓	vague	91.06	11.25
1-PL	VI	-	✓	hierarchical	91.03	11.29
1-PL	VI	✓	✓	vague	**91.29**	**11.29**
1-PL	VI	✓	✓	hierarchical	91.27	11.32
1-PL	MCMC	-	-	vague	89.81	11.95
1-PL	MCMC	-	-	hierarchical	90.08	11.85
2-PL	VI	-	-	vague	85.18	15.87
2-PL	VI	-	-	hierarchical	90.41	11.72
2-PL	VI	✓	-	vague	86.19	15.50
2-PL	VI	✓	-	hierarchical	90.89	11.64
2-PL	VI	-	✓	vague	86.24	15.73
2-PL	VI	-	✓	hierarchical	89.62	12.53
2-PL	VI	✓	✓	vague	86.56	15.52
2-PL	VI	✓	✓	hierarchical	89.81	12.27
2-PL	MCMC	-	-	vague	84.56	15.72
2-PL	MCMC	-	-	hierarchical	88.06	13.34
3-PL	VI	-	-	vague	89.52	12.21
3-PL	VI	-	-	hierarchical	89.52	12.21
3-PL	VI	✓	-	vague	90.76	11.73
3-PL	VI	✓	-	hierarchical	90.76	11.73
3-PL	VI	-	✓	vague	90.05	12.50
3-PL	VI	-	✓	hierarchical	90.05	12.50
3-PL	VI	✓	✓	vague	91.01	12.13
3-PL	VI	✓	✓	hierarchical	91.01	12.13

Table 9: Comparison of IRT models, data augmentation and prior method.

Method	Task	Embedding	Metrics
LR	Regression	Qwen3-8B	1.0375
LR	Regression	BGE-M3 (Chen et al., 2024)	1.1380
SVR	Regression	Qwen3-8B	1.0108
MLP	Regression	Qwen3-8B	1.0931
Longformer (Beltagy et al., 2020)	Regression	Qwen3-8B	1.0746
SVM	Classification	Qwen3-8B	58.34
MLP	Classification	Qwen3-8B	53.60
MLP	Ranking	Qwen3-8B	71.95
MLP	Ranking	text-embedding-3-large	71.98

Table 10: Comparison of regression, classification and ranking tasks on different models.

Generation time and token count use the minimum of three runs, correctness is judged by GPT-5 and similarity is measured via text-embedding-3-large. The results are shown in Figure 8. Compared to Qwen3-8B, our SFT and reinforcement learning models produce longer outputs and slower inference, showing that rewrites expand questions, solutions, and answers. Semantic similarity drops slightly, indicating greater diversity while preserving affinity with the original questions. Reinforcement learning improves correctness over both the original and SFT-only models. RIDE-8B and RIDE-4B demonstrate much higher correctness than RIDE-1.7B, indicating that parameter size influences the correctness of generated questions. However, this difference is not significant between the 4B and 8B models, suggesting a limited effect of scale within this range.

B.4 Effect of LLM verifier

We use the proprietary GPT-5 series models to provide correctness rewards and as filtering models. To verify that our method can also use low-cost, open-source models, we employ GPT-5-mini and Deepseek-V3.2 (non-thinking mode) as verifiers. We provide $2,000$ math questions (without answers), along with the solutions and answers generated by two test models (Qwen2.5-Math-7B and Gemma3-12B), as input to these verifiers to judge the correctness of the test models' responses. The results, shown in Table 11, indicate that the verification accuracy of the closed-source model GPT-5-mini reach over 85%. In contrast, the accuracy of DeepSeek-V3.2 was relatively lower, but still over 65%. However, both verifiers achieve a precision of around 90%. This indicates that both models can precisely assign low reward signals to incorrect solutions and are effective for filtering erroneous data. The relatively low recall, however, implies that the verifiers tend to be conservative, flagging an otherwise correct solution and answer as incorrect. This may be because the model's solution contains minor errors even when the final answer is correct. This situation is acceptable, given that rule-based or model-based rewards in Reinforcement Learning with Verified Rewards (RLVR) also exhibit a high number of false negatives (Xu et al., 2025). While this situation affects training efficiency, it does not directly lead to training failure, as our verifier assigns low reward signals to incorrect rewrites. Therefore, our method can also use open-source models as verifiers and is not merely a distillation from proprietary models.

Response Source	Verifier	Precision	Recall	F_1	Accuracy
Qwen2.5-Math-7B	GPT-5-mini	97.96	79.17	87.57	85.70
	Deepseek-V3.2	89.48	62.19	73.38	71.30
Gemma3-12B	GPT-5-mini	98.38	79.71	88.06	86.00
	Deepseek-V3.2	93.84	54.09	68.62	67.95

Table 11: Verification performance of GPT-5-mini and Deepseek-V3.2 verifiers on solutions generated by different response models.

C Item Response Theory Analysis

C.1 Human Difficulty & LLM Difficulty

In human cognition, the difficulty of a math question is often determined by its required reasoning depth. Consequently, researchers have established the AoPS (Art of Problem Solving) standard to measure the difficulty of math competition questions from a human perspective, and methods have emerged that use LLMs in conjunction with the AoPS standard to automatically assign difficulty ratings to math questions (Gao et al., 2025). The DeepMath dataset, which we utilize in the IRT modeling phase, also applies this standard to provide difficulty levels for its questions. However, we discover a discrepancy between this human-centric standard and actual LLM performance. After grouping the responses of our 35 models on $2,000$ questions by their given AoPS difficulty levels, we calculate the mean empirical accuracy for each level. The Spearman and Kendall correlation coefficients between the AoPS difficulty and the mean empirical accuracy are found to be **-0.5152** and **-0.5111**, respectively, indicating that while the expected negative correlation exists (i.e., higher human-perceived difficulty corresponds to lower model accuracy), the relationship is not sufficiently strong to consider them equivalent. Therefore, we conclude that a deviation exists between the human cognitive difficulty defined by the AoPS standard and the empirical error rate demonstrated by LLMs.

Furthermore, treating lower empirical accuracy directly as higher "LLM difficulty" introduces a fundamental flaw: empirical accuracy assigns equal weight to the responses of all tested LLMs. We therefore introduce IRT to define difficulty, which allows us to derive a statistically robust difficulty value by incorporating the ability of all participating LLMs into the calculation.

Additionally, we compare the correlation of both the empirical error rate (ungrouped) and IRT difficulty against the human-perceived difficulty, again using Spearman coefficients, as shown in Table 12. The results show that both empirical error rate and our IRT difficulty (fitted on 35 model responses) have a similar correlation with the given human difficulty. Our work is primarily focused on this "LLM difficulty" rather than human-perceived difficulty.

vs Human-Rated Difficulty	Spearman
Empirical Error Rate	0.3362
IRT Difficulty	0.3418
IRT Difficulty w/o augmentation	0.3364
IRT Difficulty (Qwen-only)	0.2839

Table 12: Correlation analysis of empirical error rate, IRT difficulty and human-rated difficulty. Spearman & Kendall measure the strength and direction of the monotonic relationship (or rank-order correlation) between two variables.

We also conduct ablation studies by fitting IRT models on the original response matrix without augmentation, and on a matrix using only the Qwen-series models. The results show that the difficulty values derived solely from the Qwen series (11 test-takers) correlate poorly with both empirical accuracy and human difficulty, as the limited number of subjects introduces significant bias into the IRT fit. Besides, the original response matrix without augmentation is also less correlated due to data sparsity. This finding validates the effectiveness of our VAE and Sampling data augmentation methods. By learning from the original response matrix and empirical accuracy to generate a large number of distributionally-consistent virtual responses to expand the matrix, our approach enhances the robustness of the IRT fitting process. This prevents parameter estimation bias caused by an insufficient number of subjects.

C.2 Case for IRT Difficulty

As previously discussed, although both empirical error rate and IRT difficulty can be regarded as values for LLM Difficulty, empirical error rate's drawback is its assumption of equal weighting for all LLMs, leading to a lack of item discrimination. In Figure 9, we present a case study of two questions. Although both questions have the identical empirical accuracy (**37.14%**), their IRT difficulties differ significantly: Question 1 has an IRT difficulty of **0.599**, whereas Question 2 has an IRT difficulty of **0.778**. This discrepancy arises because the profile of models that answer each question correctly is different. Specifically, four high-ability models including Deepseek-R1-Distill-Qwen-1.5B, Gemini-2.5-Flash, GLM-Z1-AIRX, and Qwen3-235B-A22B (see ability values in Table 5) answer Question 1 correctly but fail to answer Question 2. Therefore, even with the same empirical accuracy, Question 1 is more likely to be solved by high-ability LLMs, thus receiving a lower IRT difficulty score. This case validates the advantage of using IRT difficulty over simple empirical error rate, as it successfully distinguishes item difficulty based on the ability of the solvers, not just the raw pass count.

vs 35-LLMs IRT Difficulty	Spearman	Kendall
35-LLMs + lower-performing 2-LLMs	1.00	0.9968
35-LLMs + 5-LLMs	1.00	0.9954

Table 13: Correlation analysis between the original 35-LLM fitted IRT difficulty and those fitted with 2 additional lower-performing LLMs or all 5 additional LLMs.

C.3 Distribution Shift

To validate the stability of our IRT parameter estimations, we collect additional responses for the same $2,000$ items using five extra models: Qwen2-72B, Mistral-large, GPT-oss-20B, Qwen3-1.7B, and GPT-4.1-nano. Among these, Qwen2-72B and Qwen3-1.7B are classified as "lower-performing LLMs" as their accuracies fell below the 67.98% average accuracy of our initial 35 LLMs. We then conduct two experiments: first, we added only these weaker LLMs to the original 35-LLM response matrix; second, we added all 5 new models to the original 35-LLM matrix. We then fit IRT parameters for both augmented matrices and calculate the Spearman and Kendall correlation coefficients against the original IRT difficulty parameters derived from the initial 35 LLMs. The

results (shown in Table 13) indicate that in both scenarios—whether adding only the weaker models or all five additional models—the changes in the Spearman and Kendall correlation coefficients are minimal. This demonstrates the stability of our method, confirming that our IRT parameter estimations are robust and not significantly perturbed by the inclusion of a certain amount of new response data.

(a) Prompt for mathematical question answering.

(b) Prompt for rewriting mathematical questions.

(c) Prompt for judging which rewritten question is better.

Figure 6: Overview of prompts.

Original Question: In a table tennis tournament every participant played every other participant exactly once. Although there were twice as many right-handed players as left-handed players, the number of games won by left-handed players was 40% more than the number of games won by right-handed players. (There were no ties and no ambidextrous players.) What is the total number of games played?
Original Answer: 36

Rewritten Question: In a round-robin table tennis tournament, every participant plays every other participant exactly once (no ties, no ambidextrous players). Let R be the number of right-handed players and L be the number of left-handed players, with R = 2L. Over the whole tournament, the total number of games won by left-handed players is 40% more than the total number of games won by right-handed players. Find the total number of games played.
Rewritten Answer: 36

Figure 7: A case study of the rewritten questions with surface-only strategies.

Figure 8: Statistics of average token count, average generation time, correctness and semantic similarity across different models.

Question 1: Given a 4×4 real matrix T such that $T^4=0$, determine which of the following sequences $k_1, \\ k_2,\\ k_3,\\ k_4$ is NOT a possible combination for the nullity of T^i:\n\n1. $k_1 = 3,\\ k_2 = 4,\\ k_3 = 4,\\ k_4 = 4$\n2. $k_1 = 1,\\ k_2 = 3,\\ k_3 = 4,\\ k_4 = 4$\n3. $k_1 = 2,\\ k_2 = 4,\\ k_3 = 4,\\ k_4 = 4$\n4. $k_1 = 2,\\ k_2 = 3,\\ k_3 = 4,\\ k_4 = 4$\n\nNote: Since $T^4=0$, T is nilpotent and its eigenvalues are all 0. Consider the properties of nilpotent matrices to determine the answer.
Answer: 2

Empirical Accuracy: 37.14%
IRT Difficulty: 0.599

Question 2: In the right triangle \\(ABC\\), the altitude \\(BH\\) is drawn to the hypotenuse \\(AC\\). Points \\(X\\) and \\(Y\\) are the centers of the circles inscribed in triangles \\(ABH\\) and \\(CBH\\) respectively. The line \\(XY\\) intersects the legs \\(AB\\) and \\(BC\\) at points \\(P\\) and \\(Q\\). Given that \\(BH = h\\), find the area of triangle \\(BPQ\\).
Answer: \\dfrac{h^2}{2}

Empirical Accuracy: 37.14%
IRT Difficulty: 0.778

Figure 9: A case study of two questions with identical empirical accuracy and different IRT difficulties.