PRiMeFlow: capturing complex expression heterogeneity in perturbation response modelling

Zichao Yan [* 1]   Yan Wu [* 2]   Mica Xu Ji [* 1]   Chaitra Agrahar [* 1]   Esther Wershof [* 1]   Marcel Nassar [* 1]
Mehrshad Sadria [* 1]   Ridvan Eksi [* 1]   Vladimir Trifonov [1]   Ignacio Ibarra [1]   Telmo Felgueira [3]   Błażej Osiński [4]
Rory Stark [1]

Abstract

Predicting the effects of perturbations in-silico on cell state can identify drivers of cell behavior at scale and accelerate drug discovery. However, modeling challenges remain due to the inherent heterogeneity of single cell gene expression and the complex, latent gene dependencies. Here, we present PRiMeFlow, an end-to-end flow matching based approach to directly model the effects of genetic and small molecule perturbations in the gene expression space. The distribution-fitting approach taken by PRiMeFlow enables it to accurately approximate the empirical distribution of single-cell gene expression, which we demonstrate through extensive benchmarking inside PerturBench. Through ablation studies, we also validate important model design choices such as operating in gene expression space and parameterizing the velocity field with a U-Net architecture. Finally, by scaling PRiMeFlow to a broad perturbation data atlas spanning multiple datasets and employing a carefully designed pretraining-finetuning strategy, we demonstrate its outstanding performance on the H1 human embryonic stem cells from the ARC Virtual Cell Challenge benchmark.

1. Introduction

Novel imaging and genomics methods have enabled high-throughput small molecule and genetic perturbation technology with rich imaging and single cell gene expression measurements (Zhang et al., 2025; Dixit et al., 2016; Chandrasekaran et al., 2023). However despite these advances, the space of potential small molecule and genetic perturba-

tions remains massive, especially since the effects of perturbations depend on covariates such as cell type and many key cell state shifts only occur in response to multiple perturbations (Watanabe et al., 2019; Wei et al., 2009).

Machine learning models that can predict counterfactual response to perturbations are thus valuable in unlocking in-silico screens that can prioritize the most promising sets of perturbations for experimental testing. To this end, significant benchmarking efforts have emerged in the literature space, for example PerturBench (Wu et al., 2024). Its novel rank-based metrics have been widely adopted in the field, for example in the first annual Virtual Cell Challenge (ARC VCC, Roohani et al. (2025)). We provide background information on PerturBench and the Virtual Cell Challenge in Section 2.1.

Empirical results from PerturBench show that, surprisingly, simpler model variants could outperform more complex versions. For example, ablating the adversarial loss from CPA (Lotfollahi et al., 2023) and the sparsity constraint from SAMS-VAE (Bereket & Karaletsos, 2023) improve *covariate transfer* task performance. This suggests that while strong inductive biases are interesting from a modelling perspective and can be performant in specific test settings, design choices should be rigorously ablated as simpler algorithms can generalize better in practice.

Motivated by the insights of PerturBench, we seek to design an expressive yet conceptually simple generative model to better capture the heterogeneous cellular responses to perturbations. We present PRiMeFlow [1] which is the first of its kind to apply end-to-end learning principles to flow matching for perturbation response modeling. We intentionally make the design choice of eliminating the need for fixed pretrained latent embeddings, typically derived from either PCA or single-cell foundation models (Klein et al., 2025; Palla et al., 2025). While these methods compress expression profiles into more tractable lower-dimensional spaces, they risk losing critical biological signals for accurate downstream prediction, as well as error accumulation

---

[1] Altos Labs [2] Verge Genomics [3] Loka [4] Independent Researcher. Correspondence to: Zichao Yan <zyan@altoslabs.com>, Rory Stark <rstark@altoslabs.com>.

Accepted at the 2026 Workshop on Generative and Agentic AI for Biology (ICML 2026)

---

[1] PRiMe stands for: **P**erturbation **R**esponse [**i**] **M**odeling

in the multi-stage inference pipeline.

Distinctively, PRiMeFlow directly operates in the gene expression space and employs a U-Net architecture to parameterize the velocity field. We formulate our contributions in this work as follows:

(1) We propose PRiMeFlow, a novel flow matching approach that introduces a straightforward, end-to-end design principle for perturbation response modeling.

(2) We demonstrate PRiMeFlow's superior distribution-fitting capabilities through extensive experiments within PerturBench against a wide array of baselines. Our method achieves significant gains in key distributional metrics, such as the recall of ground truth differentially expressed genes (DEGs), highlighting its ability to accurately model gene expression variance and recapitulate the biological heterogeneity observed in single cell populations.

(3) Through ablation studies, we validate our core design choices. Specifically, we observe significant gains from three key decisions: parameterizing the velocity field in the gene expression space rather than the latent space, using a U-Net over an MLP, and training with independent coupling instead of optimal transport based coupling.

(4) We experiment scaling PRiMeFlow to large perturbation data atlas spanning multiple datasets, and through a carefully designed pretraining-finetuning strategy, we demonstrate the outstanding performance of PRiMeFlow on the H1 human embryonic stem cells (hESCs) from the Arc Virtual Cell Challenge (Roohani et al., 2025)

2. Background

2.1. Benchmarking virtual cell models in PerturBench

To rigorously evaluate the performance of PRiMeFlow, we use the PerturBench platform (Wu et al., 2024) which contains well-defined tasks, numerous perturb-seq datasets and diverse evaluation metrics. PerturBench includes widely-adopted, pseudobulk-level metrics such as cosine similarity of log fold-change (LogFC) and root mean square error (RMSE). To evaluate the model ability of generating biologically meaningful single-cell populations, it also provides distribution-based metrics such as maximum mean discrepancy (MMD) in gene expression (GEX) or PCA space, and differentially expressed genes (DEG) recall. Finally, PerturBench provides rank-based versions of these metrics which quantify prediction-specificity.

PerturBench also includes preprocessed perturb-seq datasets, some of which are selected in this work for benchmarking purposes. Refer to Table 1 and Appendix section A for details. In particular, we benchmark our models

in `Srivatsan20` and `Jiang24` datasets under the *covariate transfer* task, and in `Norman19` dataset under the *combo prediction* task.

2.2. ARC Virtual Cell Challenge 2025

In 2025, the ARC institute hosted the first annual Virtual Cell Challenge with a task setup that resembles Perturbench's *covariate transfer*. 300 perturbations from H1 hESCs are selected with stratified effect sizes, and partitioned into training (150), public test (50), and private test (100) sets (Roohani et al., 2025). The competition permits the use of public or proprietary data [2].

The competition attracted over 1200 teams worldwide and received over 300 final submissions. Initial evaluations relied on mean absolute error (MAE), differential expression score (DES), and a PerturBench-motivated perturbation discrimination score (PDS). The community highlighted that L1-based PDS is scale-sensitive, highlighting the need for careful, multi-metric benchmarking (Liu et al., 2025; Arc Institute, 2025). Thus, a broader set of evaluation metrics was introduced to establish a separate Generalist leaderboard, where models are ranked in each of the seven metrics in total and the average rank is used a holistic assessment of model generalization capability. Details of the expanded metric set can be found in Appendix section B.

2.3. Flow Matching

Flow matching belongs to a family of generative models which transport a known source distribution (p_0, e.g., simple Gaussian distribution) to the unknown data distribution (p_{data}), using a neural network parameterized mapping ψ^θ. The goal is to align the transformed distribution (i.e., *pushforward* $\psi^\theta_\# p_0$) to p_{data}, traditionally achieved by minimizing the negative data log-likelihood (Rezende & Mohamed, 2015): $L(\theta) = -\sum_i^n \log(\psi^\theta_\# p_0(x_i))$.

A particular example is the continuous normalizing flow (CNF) (Chen et al., 2018) which parameterizes the time-dependent velocity field $v^\theta_t(x)$ with neural networks. By enforcing Lipschitz continuity constraint in x as well as continuity constraint in t, it uniquely defines a diffeomorphic mapping ψ^θ_t through the ordinary differential equation (ODE):

$$\frac{d}{dt}\psi^\theta_t(x) = v^\theta_t(\psi^\theta_t(x)), \quad \psi^\theta_0(x) = x$$

At inference time, the learned velocity is used iteratively to solve the ODE, given initial conditions which are samples from p_0, where the resulting ODE integration ideally leads to high quality samples that capture the diversity in p_{data}. We denote the intermediate probability densities as p_t and

---

[2] `https://virtualcellchallenge.org/datasets`

Table 1. Summary of benchmarking datasets.

Dataset	Single / Dual perturbations	Modality	Biological states	Cells	GEX length	Task
Srivatsan20	188 / 0	small molecule	3	178,213	8,630	*covariate transfer*
Jiang24	219 / 0	genetic	30	1,628,476	15,473	*covariate transfer*
Norman19	155 / 131	genetic	1	91,168	5,575	*combo prediction*

consider v_t generating p_t if the two quantities satisfy the continuity equation:

$$\partial p_t + \nabla \cdot (p_t v_t) = 0$$

Advantages aside, the training of CNF is impeded by expensive ODE simulation required to compute the log-likelihood. This is where a flow matching approach offers a more efficient and simulation-free alternative.

In flow matching, we first consider designing the probability path p_t that interpolates between p_0 and p_{data}. This requires selecting a conditioning variable z (e.g., $z \sim p_{data}$) and the conditional probability path $p_t(x|z)$ that can be used to recover p_t through a weighted aggregation of the conditional paths: $p_t(x) = \int p_t(x|z)p(z)dz$.

It is important that $p_t(x|z)$ is selected to induce simple closed-form expressions in its corresponding conditional velocities $v_t(x|z)$. In the example of $z \sim p_{data}$ and assuming p_0 is the standard Gaussian distribution, $p_t(x|z)$ takes the form of $\mathcal{N}(x|t \cdot z, (1-t)^2 \cdot I)$, and through the continuity equation, it can be shown that $v_t(x|z) = \frac{z-x}{1-t}$.

A further result from (Lipman et al., 2022) shows that the ground truth generating velocity of p_t, referred to as the marginal velocity $v_t(x)$, is connected to $v_t(x|z)$ in the following way:

$$v_t(x) = \int v_t(x|z) \frac{p_t(x|z)p(z)}{p_t(x)} dz$$

It is obvious that the marginal velocity is intractable, hence the difficulty of directly using it as a regression target for the learned velocity field, as in the naive flow matching loss:

$$\mathcal{L}_{FM} = \mathbb{E}_{t,x \sim p_t} ||v_t^\theta(x) - v_t(x)||^2 \quad (1)$$

And this leads to the conditional flow matching loss proposed in (Lipman et al., 2022):

$$\mathcal{L}_{CFM} = \mathbb{E}_{t,z \sim p_z, x \sim p_t(x|z)} ||v_t^\theta(x) - v_t(x|z)||^2 \quad (2)$$

which is a tractable alternative to $\mathcal{L}_{FM}$. It has been shown in (Lipman et al., 2022) Theorem 2 that $\nabla_\theta \mathcal{L}_{CFM} = \nabla_\theta \mathcal{L}_{FM}$, thus optimizing the tractable Eq. 2 leads to the same gradient as Eq. 2, making both effectively equivalent in expectation. The conditional flow matching loss has been

widely applied in generative modeling contexts and has offered a wide selection of conditioning variables and conditional probability paths, such as nonlinear interpolations, couplings between empirical data distributions, and optimal transport (Albergo et al., 2023; Liu et al., 2022; Tong et al., 2023).

3. Method

For a perturb-seq dataset $\mathcal{D}$, consider the set of $\log 1p$ normalized gene expression profiles $\mathcal{X} = \{x_i \in \mathbb{R}^m\}_{i=1}^n$ where n denotes the size of the dataset and m denotes the number of expression genes. The identity of the genes, for example gene names, is denoted by $\mathcal{G} = \{g_j\}_{j=1}^m$.

Every expression profile corresponds to a cell with condition c specifying genetic/small-molecule perturbations p, and covariates cov such as cell subtype and other cell treatments which are dataset specific. We denote the set of conditions with $\mathcal{C} = \{c_i\}_{i=1}^n$ where $c_i = (\{p_{i,k}\}_{k=1}^{n_i}, cov_i)$. Given the possibility of combinatorial perturbations, each condition may contain a plurality of perturbations as indicated by the set $\{p_{i,k}\}_{k=1}^{n_i}$ where n_i denotes the number of perturbations. An empty perturbation set ($n_i = 0$) indicates a control cell.

3.1. Direct flow matching in gene expression space

In this section, we introduce PRiMeFlow, our perturbation response model. A simplified view of the PRiMeFlow workflow is shown in Figure 1. The design philosophy behind PRiMeFlow is straightforward: to tackle the heterogeneity of gene expression measurements (both inter- and intra-condition) and the complex interaction relationships among genes, we propose to directly parameterize the velocity field v_t^θ in the gene expression space.

While this exposes the velocity field to the full complexity in the raw gene expression data, it also creates an opportunity for the model to learn dynamics that directly govern the transition of expression profiles, especially when the velocity field is parameterized with an architecture that is adequate for capturing the noise and intricate structures inherent in gene expression data.

In particular, v_t^θ takes as input three main components:

• Gene expression profile x_t and gene identities $\mathcal{G}$. x_t

Figure 1. PRiMeFlow workflow overview. The velocity field is directly parameterized in the gene expression space, using a U-Net architecture, and is conditioned on information of the perturbation, covariates, as well as the time variable. The velocity field is learned with the standard conditional flow matching loss. At the inference time, perturbed cells are sampled by solving the initial value problems using the learned velocity field.

is sinusoidally encoded to add a feature dimension i.e., $\mathrm{Enc}(x_t) \in \mathbb{R}^{m \times d}$. $\mathcal{G}$ is included to ingest biological interpretation in the first dimension in x_t and is mapped to learnable embedding vectors: $\mathrm{Emb}(\mathcal{G}) \in \mathbb{R}^{m \times d}$;

- Condition $c_i = (\{p_{i,k}\}_{k=1}^{n_i}, cov_i)$. We use a compositional encoding of potentially combinatorial perturbations and one-hot encoding for covariate: $\mathrm{Enc}(c_i) = [\sum_k \mathrm{OneHot}(p_{i,k}) || \mathrm{OneHot}(cov_i)]$, where $[...||...]$ denotes concatenation along the feature dimension;

- Time t which is also sinusoidally encoded in $\mathrm{Enc}(t)$.

The output of the velocity field is in the following form:

$$\hat{v} = v_t^\theta(\mathrm{Enc}(x_t) + \mathrm{Emb}(\mathcal{G}), \mathrm{Enc}(c_i), \mathrm{Enc}(t)) \quad (3)$$

v_t^θ is parameterized with a U-Net architecture which we have found crucial for its performance. We have implemented our U-Net based on OpenAI's guided diffusion library (Dhariwal & Nichol, 2021).

Remark 1 (Architecture choice for velocity field) *U-Nets are designed to capture spatial relationships, such as the relationship between spatial coordinates in imaging data, which do not apply to gene expression vectors where the ordering of genes is arbitrary. While theoretically suboptimal compared to permutation-invariant architectures like Transformer (Vaswani et al., 2017), we found the U-Net to be a pragmatic choice: it is highly parameter efficient compared to the Transformer, requires significantly lower computational resources, and empirically outperforms MLP.*

Algorithm 1 PRiMeFlow Training

Require: $p_0, p_{data}, \theta, \mathcal{G}, p_{uncond}$, noise schedule σ, batch size b, learning rate η.
0: Initialize parameters θ.
0: **while** not converged **do**
0:     Sample $x_1 \in \mathbb{R}^{b \times m} \sim p_{data}$.
0:     Retrieve conditions $C = \{c_i\}_{i=1}^b$,
            where $c_i \leftarrow \emptyset$ with prob p_{uncond}.
0:     Sample $x_0 \in \mathbb{R}^{b \times m} \sim p_0$.
0:     Sample time steps $t \in \mathbb{R}^b \sim \mathrm{Uniform}(0, 1)$.
0:     Sample $x_t \sim \mathcal{N}(x \,|\, (1-t)x_0 + tx_1, \sigma^2 \mathcal{I})$.
0:     Compute target $v_t(x|(x_0, x_1)) = x_1 - x_0$.
0:     Predict velocity $\hat{v}$ as Eq. 3.
0:     Compute $\mathcal{L}_{CFM}$ as Eq. 2.
0:     Update parameters: $\theta \leftarrow \theta - \eta \nabla_\theta \mathcal{L}_{CFM}(\theta)$.
0: **end while**=0

3.2. Training PRiMeFlow and ablations

To train PRiMeFlow, we construct probability paths as independent couplings between p_0 and p_{data}. We choose p_0 to be the standard Gaussian distribution, and p_{data} to be the empirical cell populations that includes both perturbed and control cells. For training step details, refer to Algorithm 1.

To understand the importance of architecture choices we perform ablation studies. We provide an ablation model referred to as PRiMeFlow MLP which parameterizes the velocity field with an MLP instead of U-Net. The training steps of PRiMeFlow MLP remain unchanged.

To demonstrate the value of end-to-end learning, we provide an alternative implementation of PRiMeFlow that operates in the PCA space of gene expression, with and without optimal transport. These baselines are referred to as Flow-Matching PCA and FlowMatching PCA OT respectively. While FlowMatching PCA still uses a standard Gaussian as p_0, FlowMatching PCA OT uses empirical control cells as p_0 and is trained with optimal transport-based data-coupling. Both FlowMatching PCA and FlowMatching PCA OT use MLP for the velocity field. The training steps of FlowMatching PCA OT are altered to take data coupling into account and, in effect, become similar to CellFlow (Klein et al., 2025).

4. Experiments

In sections 4.1, 4.2 and 4.3, we evaluate PRiMeFlow in PerturBench benchmarks. Comparison to important prior work is made, such as to CPA, SAMS-VAE, Biolord and their variants which are implemented in PerturBench (Wu et al., 2024). For simple baselines, we include Latent Additive, Linear Additive, and Decoder-Only models. We also compare to various ablation models such as PRiMeFlow MLP, FM PCA and FM PCA OT.

All models were trained using five random seeds, and we report the mean and standard deviation. Hyperparameters for PRiMeFlow MLP and FM PCA were selected separately through 60-trial HPO sweeps. FM PCA OT reuses FM PCA hyperparameters while adding OT-specific hyperparameters. PRiMeFlow hyperparameters were manually determined due to the model's higher computational cost and our resource constraints. We report the hyperparameters in the Appendix section G.

To compute the evaluation metrics, we sampled 1,000 single-cell gene expression profiles from each model. For inference in the four flow matching based methods, we used 100 Euler integration steps and explored CFG settings from 1 to 5. All results are reported on the test split.

In section 4.4, we evaluate PRiMeFlow on H1 hESCs from the ARC VCC. We employ a carefully designed pretraining-finetuning strategy, first scaling PRiMeFlow across a large perturbation data atlas (VCC+public+proprietary data), then followed by targeted finetuning using a subset of the data to facilitate transfer learning of perturbation effects from external datasets (i.e., any non-VCC data) to public/private test perturbations in H1 hESCs. Due to space constraints, detailed description of our data composition and splits, training and inference strategies, are deferred to Appendix section B.

4.1. Performance of PRiMeFlow in *covariate transfer* task

In this section, we evaluate PRiMeFlow in `Srivatsan20` and `Jiang24` datasets under the *covariate transfer* task. The task measures the model's ability to capture the effects of small-molecule and genetic perturbations in novel co-variate conditions where those effects are unmeasured in the training data. Results for `Srivatsan20` are reported in Table 2. Results for the complete distributional metrics, more ablation models such as PRiMeFlow MLP and FM PCA OT, are reported in Table 9 in the Appendix due to space constraints. The complete results for `Jiang24` dataset is reported in Appendix Table 11.

Overall, we observe that PRiMeFlow (CFG=1) achieves state-of-the-art performance in both datasets across major distributional metrics which are MMD in either GEX or PCA space, DEG recall as well as DEG recall rank. In `Srivatsan20` dataset, PRiMeFlow achieves SOTA performance in MMD GEX rank while maintaining a competitive edge in MMD PCA rank. The converse is true in `Jiang24`. Increasing the CFG weight from 1 to 5 generally degrades distributional fit. However, stronger guidance appears to yield marginal improvements in DEG recall and its rank metrics in `Srivatsan20` dataset. This holds true for both PRiMeFlow and FM PCA, but not for PRiMeFlow MLP or FM PCA OT.

In particular, comparing PRiMeFlow to FM PCA in both datasets suggests that operating end-to-end in the full gene expression space and directly updating the gene expression vectors through time with ODE integration results in a significantly closer fit to the ground truth distribution of gene expression. An immediate benefit of this approach is the explicit modeling of gene expression variance, which translates directly to a higher recall of ground-truth DEGs. Furthermore, comparing FM PCA to FM PCA OT shows that optimal transport based data coupling did not meaningfully add to model performance. Further, the MLP variant struggles to achieve decent fits on distributional or traditional pseudobulk based metrics, suggesting the the U-Net architecture possesses an advantageous inductive bias.

Finally, we report traditional metrics, such as LogFC, RMSE and their rank versions, for `Srivatsan20` and `Jiang24` datasets in Appendix Table 6 and Table 8. While PRiMeFlow remains generally competitive, it is outperformed by earlier works such as CPA and SAMS-VAE on those pseudobulk-based metrics. This highlights a crucial trade-off: while earlier models excel at predicting mean expression, PRiMeFlow's unique advantage lies in capturing the higher-order characteristics of the ground-truth gene expression distribution. This distinction also illustrates how metric selection fundamentally shapes performance evaluation and the definition of model success.

Table 2. Distributional metric performance of PRiMeFlow on the `Srivatsan20` dataset.

Model	MMD GEX	MMD GEX rank	MMD PCA	DEG recall
PRiMeFlow CFG1	$\mathbf{0.13 \pm 4 \times 10^{-3}}$	$\mathbf{0.13 \pm 8 \times 10^{-3}}$	$\mathbf{0.14 \pm 8 \times 10^{-3}}$	$\mathbf{0.26 \pm 1 \times 10^{-2}}$
PRiMeFlow CFG3	$0.25 \pm 2 \times 10^{-3}$	$0.22 \pm 7 \times 10^{-3}$	$0.31 \pm 1 \times 10^{-2}$	$\mathbf{0.27 \pm 6 \times 10^{-3}}$
PRiMeFlow CFG5	$0.47 \pm 1 \times 10^{-2}$	$0.29 \pm 2 \times 10^{-2}$	$0.60 \pm 2 \times 10^{-2}$	$0.25 \pm 5 \times 10^{-3}$
FM PCA CFG1	$1.2 \pm 7 \times 10^{-3}$	$0.26 \pm 6 \times 10^{-3}$	$0.50 \pm 2 \times 10^{-2}$	$0.042 \pm 2 \times 10^{-3}$
FM PCA CFG3	$1.3 \pm 5 \times 10^{-3}$	$0.25 \pm 7 \times 10^{-3}$	$0.44 \pm 1 \times 10^{-2}$	$0.071 \pm 3 \times 10^{-3}$
FM PCA CFG5	$1.4 \pm 4 \times 10^{-3}$	$0.29 \pm 4 \times 10^{-3}$	$0.53 \pm 1 \times 10^{-2}$	$0.10 \pm 3 \times 10^{-3}$
CPA	$2.4 \pm 1 \times 10^{-2}$	$0.30 \pm 9 \times 10^{-3}$	$0.53 \pm 4 \times 10^{-3}$	$0.0073 \pm 2 \times 10^{-3}$
CPA (noAdv)	$2.3 \pm 3 \times 10^{-2}$	$0.25 \pm 5 \times 10^{-3}$	$0.49 \pm 1 \times 10^{-2}$	$0.0040 \pm 2 \times 10^{-3}$
SAMS-VAE	$2.5 \pm 2 \times 10^{-2}$	$0.30 \pm 8 \times 10^{-3}$	$0.69 \pm 1 \times 10^{-2}$	$0.00016 \pm 1 \times 10^{-4}$
SAMS-VAE (S)	$2.9 \pm 1 \times 10^{-2}$	$0.28 \pm 5 \times 10^{-3}$	$0.79 \pm 1 \times 10^{-2}$	0 ± 0
Biolord	$4.9 \pm 3 \times 10^{0}$	$0.36 \pm 2 \times 10^{-1}$	$4.3 \pm 4 \times 10^{0}$	$4.7e - 05 \pm 1 \times 10^{-4}$
Latent	$4.3 \pm 2 \times 10^{-1}$	$0.26 \pm 6 \times 10^{-2}$	$2.0 \pm 2 \times 10^{-1}$	$0.0 \pm 0.$
Decoder	$4.2 \pm 4 \times 10^{-3}$	$0.16 \pm 2 \times 10^{-2}$	$1.9 \pm 5 \times 10^{-3}$	N/A
Linear	$2.2 \pm 7 \times 10^{-3}$	$0.31 \pm 1 \times 10^{-3}$	$0.76 \pm 9 \times 10^{-4}$	$0.0036 \pm 3 \times 10^{-4}$

4.2. Performance of PRiMeFlow in *combo prediction* task

For the *combo prediction* task, we use the `Norman19` dataset and report the results in Table 3. Pseudobulk-based metrics are reported in Appendix Table 7. Full distributional metrics and additional ablation models such as PRiMeFlow MLP and FM PCA OT are shown in Appendix Table 10.

Similar to our previous observations, PRiMeFlow demonstrates a significantly higher distribution-fitting capability and remains competitive on MMD GEX/PCA rank metrics amongst all baselines, despite being outperformed by simpler baselines such as Decoder-Only and Latent Additive models on a subset of metrics. This highlights the ongoing need for improved combinatorial prediction capabilities in perturbation response modeling.

Through extensive comparison to ablated models in Appendix Table 10, we are also able to make similar conclusions regarding the benefits of leveraging U-Net architectures, operating in full gene expression space, as well as simple independent coupling between standard Gaussian distribution p_0 and p_{data}.

Overall, it is important to point out that throughout Table 2 and 3, PRiMeFlow is the only method to achieve a decent recall performance on the top 50 ground truth DEGs, which is explained by its superior capability for capturing the full gene expression distribution on a single-cell level.

4.3. PRiMeFlow captures heterogeneous gene expressions

In Figure 2, we take 1,000 sampled cells from each model and project them into the same PCA space as the reference test data in the `Srivatsan20` dataset. The reference cells including control and perturbed cells, cluster naturally into three cell lines that are K562, A549, and MCF-7. We select two random conditions, which are Ellagic acid in a549 and Pirarubicin in k562. The ground truth perturbed cells are colored in green.

In both cases, the projection illustrates how gene expression from PRiMeFlow (CFG=1) is fitted more closely to ground truth perturbed cells at a distributional level compared to baseline methods, confirmed by its superior MMD metrics in both gene expression and PCA space. This suggests PRiMeFlow is less prone to mode collapse, especially compared to traditional methods such as SAMS-VAE and Latent Additive, which struggled to properly cover the whole target distribution. This is in line with observations made in PerturBench (Wu et al., 2024).

FM PCA also demonstrates strong distribution-fitting capability, but it is worth pointing out that in terms of MMD computed in the PCA space, PRiMeFlow still outperforms FM PCA. Notably, while the visualizations rely on only the top two principal components (PCs), the PCA-based MMD is robustly computed using 30 PCs.

Interestingly, in the case of Ellagic acid in a549, increasing CFG weight from 1 to 5 led to improved DEG recall performance at the cost of other distributional metrics, resulting in a distortion in the visualization. Nevertheless, amplifying the perturbational effect can benefit certain downstream

Table 3. Distributional metric performance of PRiMeFlow on the `Norman19` dataset.

Model	MMD GEX	MMD GEX rank	MMD PCA	DEG recall
PRiMeFlow CFG1	$\mathbf{0.26 \pm 7 \times 10^{-3}}$	$0.019 \pm 4 \times 10^{-3}$	$\mathbf{0.34 \pm 2 \times 10^{-2}}$	$0.54 \pm 2 \times 10^{-2}$
PRiMeFlow CFG3	$0.61 \pm 3 \times 10^{-2}$	$0.066 \pm 9 \times 10^{-3}$	$0.86 \pm 5 \times 10^{-2}$	$\mathbf{0.61 \pm 8 \times 10^{-3}}$
PRiMeFlow CFG5	$1.3 \pm 4 \times 10^{-2}$	$0.17 \pm 1 \times 10^{-2}$	$1.8 \pm 5 \times 10^{-2}$	$0.56 \pm 1 \times 10^{-2}$
FM PCA CFG1	$0.77 \pm 4 \times 10^{-3}$	$0.059 \pm 3 \times 10^{-3}$	$0.61 \pm 5 \times 10^{-3}$	$0.37 \pm 2 \times 10^{-3}$
FM PCA CFG3	$1.1 \pm 8 \times 10^{-3}$	$0.098 \pm 2 \times 10^{-3}$	$0.82 \pm 9 \times 10^{-3}$	$0.45 \pm 2 \times 10^{-3}$
FM PCA CFG5	$1.9 \pm 4 \times 10^{-2}$	$0.18 \pm 1 \times 10^{-2}$	$1.6 \pm 4 \times 10^{-2}$	$0.43 \pm 4 \times 10^{-3}$
CPA	$5.6 \pm 3 \times 10^{-2}$	$0.14 \pm 9 \times 10^{-3}$	$2.2 \pm 2 \times 10^{-2}$	$0.032 \pm 4 \times 10^{-3}$
CPA (noAdv)	$5.5 \pm 1 \times 10^{-1}$	$0.13 \pm 2 \times 10^{-2}$	$2.2 \pm 1 \times 10^{-1}$	$0.016 \pm 9 \times 10^{-3}$
SAMS-VAE	$4.1 \pm 4 \times 10^{-2}$	$0.034 \pm 1 \times 10^{-2}$	$1.9 \pm 3 \times 10^{-2}$	0 ± 0
SAMS-VAE (S)	$3.3 \pm 5 \times 10^{-2}$	$0.088 \pm 6 \times 10^{-3}$	$0.74 \pm 5 \times 10^{-2}$	$0.028 \pm 6 \times 10^{-3}$
Biolord	$2.8 \pm 5 \times 10^{-3}$	$0.066 \pm 3 \times 10^{-3}$	$1.6 \pm 5 \times 10^{-3}$	0 ± 0
Latent	$6.7 \pm 4 \times 10^{-3}$	$0.012 \pm 1 \times 10^{-3}$	$3.2 \pm 6 \times 10^{-3}$	$0.00043 \pm 3 \times 10^{-4}$
Decoder	$6.7 \pm 6 \times 10^{-3}$	$\mathbf{0.0090 \pm 8 \times 10^{-4}}$	$3.2 \pm 4 \times 10^{-3}$	N/A
Linear	$2.5 \pm 4 \times 10^{-2}$	$0.026 \pm 2 \times 10^{-3}$	$1.2 \pm 4 \times 10^{-2}$	$0.018 \pm 2 \times 10^{-3}$

Table 4. PRiMeFlow performance on H1 hESCs private test set using all seven ARC VCC metrics.

Model	DES ↑	PDS ↑	MAE ↓	SPEARMAN ↑	SPEARMAN_LFC ↑	AUPRC ↑	PEARSON ↑
PRiMeFlow pretrained	0.210	0.695	0.074	0.406	0.320	0.264	0.181
PRiMeFlow 300pts	0.223	0.725	0.084	0.431	0.381	0.264	0.193
PRiMeFlow 250pts	0.228	0.747	0.086	0.473	0.396	0.266	0.203
xBio	0.305	0.811	0.770	0.564	0.087	0.252	0.217
Mean Predictors	0.305	0.741	6.723	0.294	0.213	0.582	0.217
Shippers	0.354	0.699	0.231	0.000	0.227	0.576	0.123

tasks that are focused on perturbation-specific DEGs. Overall, this crucial trade-off highlights the importance of looking at a comprehensive set of evaluation metrics, and that selection of models should be based on needs of the biological tasks. Additional visualization results in `Srivatsan20` and `Jiang24` are shown in Appendix section E and F.

4.4. Performance of PRiMeFlow on H1 hESCs from ARC Virtual Cell Challenge

In Table 4, we report the performance of PRiMeFlow on the 100 held-out private test perturbations in H1 hESCs. We evaluate our models across the expanded ARC VCC metrics set, and select the top-three performing models from the Generalist leaderboard [3] for comparison. Additional results on the 50 held-out public test perturbations can be found in Appendix section C.

While the pretrained-only PRiMeFlow demonstrates decent predictive capability, it is significantly outperformed by our

two finetuned models: PRiMeFlow-300pts and PRiMeFlow-250pts. For PRiMeFlow-300pts, finetuning takes place on a subset of pretraining data atlas that includes the entire 300 VCC perturbations in H1 hESCs and other external datasets to facilitate transfer learning of the perturbation effects across cell lines and datasets. Similarly, finetuning PRiMeFlow-250pts is further restricted to the 150 training perturbations and the final 100 private test perturbations.

These results highlight the need of adapting virtual cell models, usually pretrained on large data atlas, to specific cellular contexts and perturbations in order to unlock their full predictive power. Notably, thanks to the *covariate transfer* task setup, this adaptation can be achieved without additional ground-truth data. Our findings also show that narrowing the finetuning scope to focus more on specific inference-time perturbations will lead to further performance gain.

While specific baselines can achieve higher scores on individual metrics, our best finetuned model — PRiMeFlow-250pts, attained the lowest average rank overall in the complete Generalist leaderboard. In particular, PRiMeFlow achieved strong performance across all metrics while hav-

---

[3]`https://virtualcellchallenge.org/ leaderboard`

Figure 2. Visualization of cells (ground truth and model predictions) in `Srivatsan20` test split. Gray marks all the cells in the test split, used for computing PCA and illustrated as background. Green cells are the ground truth perturbed cells for one condition, repeated in each subplot. From each model, 100 cells are sampled, then projected to the same PCA space. **A**): Ellagic acid perturbation in a549 cell line; **B**) Pirarubicin perturbation in k562 cell line.

ing minimal distortion from the ground truth cell population, as evidenced by its lower MAE, outperforming a number of other architectures including STATE (Adduri et al., 2025).

5. Related Work

Early approaches such as CPA and SAMS-VAE, use variational autoencoders (VAEs) to learn disentangled latent spaces where basal cellular states and perturbation effects are modeled as independent and compositional components.

CPA (Lotfollahi et al., 2023) established this framework by decomposing cellular responses into a collection of independent embeddings for basal states, perturbations and covariates. A recent follow-up work that is SAMS-VAE (Bereket & Karaletsos, 2023), introduces sparsity constraints to the latent encodings of perturbation effects and shows improved biological interpretability. Biolord (Piran et al., 2024) leverages biological attributes such as perturbation and covariates to partition the latent space which leads to biologically meaningful latent representations.

Single-cell foundation models such as scGPT and STATE have leveraged the Transformer architecture and massive pre-training to capture complex gene-gene interactions across millions of cells. scGPT (Cui et al., 2024) treats genes as tokens and utilizes a masked value modeling objective to capture complex gene-gene interactions and reconstruct perturbed cellular states. The State (Adduri et al., 2025) model employs a state embedding module that maps 270 million cells into a shared latent space, and a state transition transformer that explicitly models sets of cells and transitions between control and perturbed cell states.

More recent methods have leveraged flow matching and diffusion frameworks to capture the heterogeneity and high-dimensional geometry of cellular responses (Klein et al., 2025; Sadria & Layton, 2025; He et al., 2025; Palla et al., 2025; Wang et al., 2026). CellFlow (Klein et al., 2025) utilizes a conditional flow-matching objective to learn time-dependent vector fields, employing an optimal transport based data coupling to encourage parsimonious, shortest-path dynamics between source and target populations. Similarly, scLDM (Palla et al., 2025) leverages a latent diffusion objective within a compressed token space, utilizing a multi-head cross-attention block (MCAB) to ensure gene permutation invariance and classifier-free guidance to steer the denoising process toward specific attributes. SquiDiff (He et al., 2025) is another diffusion-based model capable of directly generating transcriptomic profiles of perturbed cells, although the number of expression genes are usually limited to a few hundreds (e.g., predicting 203 genes in K562 cells), and a performance degradation is observed as the feature dimensionality increases (Song et al., 2026).

To combat the inherent noise and sparsity of transcriptomic data, frameworks like PRESAGE (Littman et al., 2025) integrate prior biological knowledge by aggregating gene embeddings from external sources (e.g., gene embeddings derived from protein-protein interaction networks and existing Perturb-seq datasets). Another approach which captures the population-level variability using distributional shifts is PerturbDiff (Yuan et al., 2026), where the entire perturbed population is treated as a random variable, allowing for an accounting of batch effects and other relevant factors. Finally, PerturbGen (Chi Hao Ly et al., 2026) is a trajectory-aware model which aims to understand the trajectory of evolution of the perturbation effects rather than just static effects before and after the perturbation is applied, using a generative architecture to model state-to-state transitions.

6. Discussion

PRiMeFlow takes a distinctly different approach from prior models like CellFlow and scLDM. While compressing data into a latent space helps address the high dimensionality and inherent sparsity of single-cell gene expression data, it risks distorting the information in gene expression profiles and discarding crucial biological signals needed to capture subtle, perturbation-specific effects. Instead, PRiMeFlow applies the flow matching framework directly in the full gene expression space, is trained end-to-end, and employs a dedicated U-Net architecture to model the complex underlying gene dependencies. Through extensive benchmarking and ablation experiments, we demonstrate the practical benefits of our new formulation, including a closer fit to the target distribution of perturbed cells, capturing more perturbation-specific effects, and a higher recall of ground truth DEGs. On the H1 hESCs from the ARC Virtual Cell Challenge, these attributes helped our model to achieve outstanding performance across the expanded metric suite.

While we have demonstrated the empirical success of the U-Net architecture for velocity field parameterization, exactly why it performs so well remains an open question. The strong empirical results suggest that using multi-scale feature aggregation on top of raw gene expression for predicting continuous time gene expression dynamics is a strong inductive bias, reflecting the information processing of biophysical cells as continuous time protein generation processes. However, U-Net assumes inherent inductive bias of learning sequence order in each input, whereas for gene expression data, the order of genes is arbitrary. In addition to gaining a deeper understanding of this behavior, exciting future work includes applying cross-attention mechanisms, such as Perceiver-IO (Jaegle et al., 2021) and the MCAB module in scLDM (Palla et al., 2025). These approaches could learn to optimally aggregate information along the gene dimension of raw expression vectors without relying on the spatial inductive biases that are commonly seen in the convolutional U-Net architectures.

With the emergence of massive single-cell Perturb-seq datasets such as Tahoe-100M (Zhang et al., 2025) and Illumina Billion Cell Atlas (Illumina, 2026), another exciting direction is the development of generative foundation models for virtual cells. Ultimately, this would enable generalization to rare or even unseen contexts and perturbations, either through in-context learning (Dong et al., 2026) or by leveraging insights from causal inference (Dibaeinia et al., 2026). Having a powerful, high-resolution generative backbone, such as the one established in this paper, will be crucial for driving these models forward.

There are also numerous opportunities to improve the flow matching methodology to better account for biological realism, biological scales, modalities, and the practical challenges of modelling single-cell perturb-seq data. Ultimately, the transition from modeling virtual cells to simulating entire virtual organisms (Song et al., 2024), may lead to the next major frontier at the intersection of machine learning and biology.

References

Adduri, A. K., Gautam, D., Bevilacqua, B., Imran, A., Shah, R., Naghipourfar, M., Teyssier, N., Ilango, R., Nagaraj, S., Dong, M., Ricci-Tam, C., Carpenter, C., Subramanyam, V., Winters, A., Tirukkovular, S., Sullivan, J., Plosky, B. S., Eraslan, B., Youngblut, N. D., Leskovec, J., Gilbert, L. A., Konermann, S., Hsu, P. D., Dobin, A., Burke, D. P., Goodarzi, H., and Roohani, Y. H. Predicting cellular responses to perturbation across diverse contexts with state. *bioRxiv preprint biorxiv: 2025.06.26.661135*, 2025.

Akiba, T., Sano, S., Yanase, T., Ohta, T., and Koyama, M. Optuna: A next-generation hyperparameter optimization framework. In *Proceedings of the 25th ACM SIGKDD international conference on knowledge discovery & data mining*, pp. 2623–2631, 2019.

Albergo, M. S., Boffi, N. M., and Vanden-Eijnden, E. Stochastic interpolants: A unifying framework for flows and diffusions. *arXiv preprint arXiv:2303.08797*, 2023.

Arc Institute. Virtual cell challenge 2025 wrap-up: Winners and reflections, 2025. URL https://arcinstitute.org/news/virtual-cell-challenge-2025-wrap-up.

Bereket, M. and Karaletsos, T. Modelling cellular perturbations with the sparse additive mechanism shift variational autoencoder. *Advances in Neural Information Processing Systems*, 36:1–12, 2023.

Chandrasekaran, S. N., Ackerman, J., Alix, E., Ando, D. M., Arevalo, J., Bennion, M., Boisseau, N., Borowa, A., Boyd, J. D., Brino, L., et al. Jump cell painting dataset: morphological impact of 136,000 chemical and genetic perturbations. *BioRxiv*, pp. 2023–03, 2023.

Chen, R. T., Rubanova, Y., Bettencourt, J., and Duvenaud, D. K. Neural ordinary differential equations. *Advances in neural information processing systems*, 31, 2018.

Chi Hao Ly, K., Miraki Feriz, A., Isobe, T., Vahidi, A., Vaghari, D., Rostron, A., Quiroga Londoño, M., Mende, N., Vijayabaskar, M., Moullet, M., Rose Foster, A., Graves, E., Torabi, F., Admane, C., Horsfall, D., Basurto-Lozada, D., Stephenson, E., Botting, R. A., Iskander, D., Webb, S., Goh, I., Jafree, D. J., Sturgess, K. H. M., Scott, J., Sendama, W., Magnani, L., Hannah, R., Asadollahzadeh, H., Holland, A., Prete, M., Simpson, J., Roy, A., Roberts, I., Jardine, L., Laurenti, E., Trynka, G., Wilson, N. K., Haniffa, M., Göttgens, B., and Lotfollahi, M. Predicting how perturbations reshape cellular trajectories with perturbgen. *bioRxiv*, 2026. doi: 10.64898/2026.03.04.709254. URL https://www.biorxiv.org/content/early/2026/03/05/2026.03.04.709254.

Cui, H., Wang, C., Maan, H., Pang, K., Luo, F., Duan, N., and Wang, B. scgpt: toward building a foundation model for single-cell multi-omics using generative ai. *Nature methods*, 21(8):1470–1480, 2024.

Dhariwal, P. and Nichol, A. Diffusion models beat gans on image synthesis. *Advances in neural information processing systems*, 34:8780–8794, 2021.

Dibaeinia, P., Babu, S., Knudson, M., ElSheikh, A., Wen, Y., Liu, H., Perera, J., and Khan, A. A. Virtual cells need context, not just scale. *bioRxiv*, pp. 2026–02, 2026.

Dixit, A., Parnas, O., Li, B., Chen, J., Fulco, C. P., Jerby-Arnon, L., Marjanovic, N. D., Dionne, D., Burks, T., Raychowdhury, R., et al. Perturb-seq: dissecting molecular circuits with scalable single-cell rna profiling of pooled genetic screens. *cell*, 167(7):1853–1866, 2016.

Dong, M., Adduri, A., Gautam, D., Carpenter, C., Shah, R., Ricci-Tam, C., Kluger, Y., Burke, D. P., and Roohani, Y. H. Stack: In-context learning of single-cell biology. *bioRxiv*, pp. 2026–01, 2026.

Feng, C., Peets, E. M., Zhou, Y., Crepaldi, L., Usluer, S., Dunham, A., Braunger, J. M., Su, J., Strauss, M. E., Muraro, D., et al. A genome-scale single-cell crispri map of trans gene regulation across human pluripotent stem cell lines. *Cell Genomics*, 6(2), 2026.

He, S., Zhu, Y., Tavakol, D. N., Ye, H., Lao, Y.-H., Zhu, Z., Xu, C., Chauhan, S., Garty, G., Tomer, R., et al. Squidiff: predicting cellular development and responses to perturbations using a diffusion model. *Nature methods*, pp. 1–13, 2025.

Illumina. Illumina introduces billion cell atlas to accelerate ai and drug discovery, 2026. URL https://www.illumina.com/company/news-center/press-releases/2026/fda84c92-b4b3-4691-a402-35555abe8605.html.

Jaegle, A., Borgeaud, S., Alayrac, J.-B., Doersch, C., Ionescu, C., Ding, D., Koppula, S., Zoran, D., Brock, A., Shelhamer, E., et al. Perceiver io: A general architecture for structured inputs & outputs. *arXiv preprint arXiv:2107.14795*, 2021.

Jiang, L., Dalgarno, C., Papalexi, E., Mascio, I., Wessels, H.-H., Yun, H., Iremadze, N., Lithwick-Yanai, G., Lipson, D., and Satija, R. Systematic reconstruction of molecular pathway signatures using scalable single-cell perturbation screens. *bioRxiv*, pp. 2024.01.29.576933, January 2024. URL https://doi.org/10.1101/2024.01.29.576933.

Klein, D., Fleck, J. S., Bobrovskiy, D., Zimmermann, L., Becker, S., Palma, A., Dony, L., Tejada-Lapuerta, A., Huguet, G., Lin, H.-C., et al. Cellflow enables generative single-cell phenotype modeling with flow matching. *bioRxiv*, pp. 2025–04, 2025.

Lipman, Y., Chen, R. T., Ben-Hamu, H., Nickel, M., and Le, M. Flow matching for generative modeling. *arXiv preprint arXiv:2210.02747*, 2022.

Littman, R., Levine, J., Maleki, S., Lee, Y., Ermakov, V., Qiu, L., Wu, A., Huang, K., Lopez, R., Scalia, G., Biancalani, T., Richmond, D., Regev, A., and Hütter, J.-C. Gene-embedding-based prediction and functional evaluation of perturbation expression responses with presage. *bioRxiv preprint bioarxiv: 2025.06.03.657653*, 2025.

Liu, Q., Zhang, Q., Du, J., Zhao, S., and Wang, J. Effects of distance metrics and scaling on the perturbation discrimination score. *arXiv preprint arXiv:2511.16954*, 2025.

Liu, X., Gong, C., and Liu, Q. Flow straight and fast: Learning to generate and transfer data with rectified flow. *arXiv preprint arXiv:2209.03003*, 2022.

Lotfollahi, M., Klimovskaia Susmelj, A., De Donno, C., Hetzel, L., Ji, Y., Ibarra, I. L., Srivatsan, S. R., Naghipourfar, M., Daza, R. M., Martin, B., et al. Predicting cellular responses to complex perturbations in high-throughput screens. *Molecular systems biology*, 19(6):e11517, 2023.

McFaline-Figueroa, J. L., Srivatsan, S., Hill, A. J., Gasperini, M., Jackson, D. L., Saunders, L., Domcke, S., Regalado, S. G., Lazarchuck, P., Alvarez, S., et al. Multiplex single-cell chemical genomics reveals the kinase dependence of the response to targeted therapy. *Cell genomics*, 4(2), 2024.

Nadig, A., Replogle, J. M., Pogson, A. N., Murthy, M., McCarroll, S. A., Weissman, J. S., Robinson, E. B., and O'Connor, L. J. Transcriptome-wide analysis of differential expression in perturbation atlases. *Nature Genetics*, 57(5):1228–1237, 2025.

Norman, T. M., Horlbeck, M. A., Replogle, J. M., Ge, A. Y., Xu, A., Jost, M., Gilbert, L. A., and Weissman, J. S. Exploring genetic interaction manifolds constructed from rich single-cell phenotypes. *Science*, 365(6455):786–793, 2019.

Palla, G., Babu, S., Dibaeinia, P., Pearce, J. D., Li, D., Khan, A. A., Karaletsos, T., and Tomczak, J. M. Scalable single-cell gene expression generation with latent diffusion models. *arXiv preprint arXiv:2511.02986*, 2025.

Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen, T., Lin, Z., Gimelshein, N., Antiga, L., Desmaison, A., Köpf, A., Yang, E. Z., DeVito, Z., Raison, M., Tejani, A., Chilamkurthy, S., Steiner, B., Fang, L., Bai, J., and Chintala, S. Pytorch: An imperative style, high-performance deep learning library. *Advances in Neural Information Processing Systems*, abs/1912.01703, 2019. URL http://arxiv.org/abs/1912.01703.

Piran, Z., Cohen, N., Hoshen, Y., and Nitzan, M. Disentanglement of single-cell data with biolord. *Nature Biotechnology*, 42(11):1678–1683, 2024.

Replogle, J. M., Norman, T. M., Xu, A., Hussmann, J. A., Chen, J., Cogan, J. Z., Meer, E. J., Terry, J. M., Riordan, D. P., Srinivas, N., et al. Combinatorial single-cell crispr screens by direct guide rna capture and targeted sequencing. *Nature biotechnology*, 38(8):954–961, 2020.

Replogle, J. M., Saunders, R. A., Pogson, A. N., Hussmann, J. A., Lenail, A., Guna, A., Mascibroda, L., Wagner, E. J., Adelman, K., Lithwick-Yanai, G., et al. Mapping information-rich genotype-phenotype landscapes with genome-scale perturb-seq. *Cell*, 185(14):2559–2575, 2022.

Rezende, D. and Mohamed, S. Variational inference with normalizing flows. In *International conference on machine learning*, pp. 1530–1538. PMLR, 2015.

Roohani, Y. H., Hua, T. J., Tung, P.-Y., Bounds, L. R., Yu, F. B., Dobin, A., Teyssier, N., Adduri, A., Woodrow, A., Plosky, B. S., et al. Virtual cell challenge: Toward a turing test for the virtual cell. *Cell*, 188(13):3370–3374, 2025.

Sadria, M. and Layton, A. Scvaeder: integrating deep diffusion models and variational autoencoders for single-cell transcriptomics analysis. *Genome Biology*, 26(1), 2025.

Song, L., Segal, E., and Xing, E. Toward ai-driven digital organism: Multiscale foundation models for predicting, simulating and programming biology at all levels. *arXiv preprint arXiv:2412.06993*, 2024.

Song, Z., Xiang, Y., Song, Z., Jin, W., Li, J., Sun, C., and Xie, L. Pertdiffbench: Benchmarking diffusion models for single-cell perturbation response prediction. *bioRxiv*, pp. 2026–06, 2026.

Srivatsan, S. R., McFaline-Figueroa, J. L., Ramani, V., Saunders, L., Cao, J., Packer, J., Pliner, H. A., Jackson, D. L., Daza, R. M., Christiansen, L., Zhang, F., Steemers, F., Shendure, J., and Trapnell, C. Massively multiplex chemical transcriptomics at single-cell resolution. *Science*,

367(6473):45–51, January 2020. ISSN 0036-8075. doi: 10.1126/science.aax6234.

Tong, A., Fatras, K., Malkin, N., Huguet, G., Zhang, Y., Rector-Brooks, J., Wolf, G., and Bengio, Y. Improving and generalizing flow-based generative models with mini-batch optimal transport. *arXiv preprint arXiv:2302.00482*, 2023.

Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, Ł., and Polosukhin, I. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

Wang, C., Karimzadeh, M., Ravindra, N. G., Bounds, L. R., Alerasool, N., Huang, A. C., Ma, S., Gulbranson, D. R., Cui, H., Lee, Y., Arjavalingam, A., MacKrell, E. J., Wilken, M. S., Chen, J., Herken, B. W., Weber, J. A., Onesto, M. M., Gonzalez-Teran, B., Leung, N. F., Shi, S. Y., Smith, B. J., Lam, S. K., Barner, A., Wright, P., Rumsey, E. M., Kim, S., Sit, R. V., Litterman, A. J., Chu, C., and Wang, B. X-cell: Scaling causal perturbation prediction across diverse cellular contexts via diffusion language models. *bioRxiv*, 2026. doi: 10.64898/2026.03.18.712807. URL https://www.biorxiv.org/content/early/2026/03/20/2026.03.18.712807.

Watanabe, K., Panchy, N., Noguchi, S., Suzuki, H., and Hong, T. Combinatorial perturbation analysis reveals divergent regulations of mesenchymal genes during epithelial-to-mesenchymal transition. *NPJ systems biology and applications*, 5(1):21, 2019.

Wei, Z., Yang, Y., Zhang, P., Andrianakos, R., Hasegawa, K., Lyu, J., Chen, X., Bai, G., Liu, C., Pera, M., et al. Klf4 interacts directly with oct4 and sox2 to promote reprogramming. *Stem cells*, 27(12):2969–2978, 2009.

Wu, Y., Wershof, E., Schmon, S. M., Nassar, M., Osiński, B., Eksi, R., Yan, Z., Stark, R., Zhang, K., and Graepel, T. Perturbench: Benchmarking machine learning models for cellular perturbation analysis. *arXiv preprint arXiv:2408.10609*, 2024.

Yuan, X., Liu, X., Zhang, Y. S., Zhang, Z., Guo, H., and Tang, J. Perturbdiff: Functional diffusion for single-cell perturbation modeling, 2026. URL https://arxiv.org/abs/2602.19685.

Zhang, J., Ubas, A. A., De Borja, R., Svensson, V., Thomas, N., Thakar, N., Lai, I., Winters, A., Khan, U., Jones, M. G., et al. Tahoe-100m: A giga-scale single-cell perturbation atlas for context-dependent gene function and cellular modeling. *BioRxiv*, pp. 2025–02, 2025.

A. PerturBench dataset information

In this section, we recapitulate the information of the three main PerturBench benchmarking datasets used in our paper, based on the original information provided in (Wu et al., 2024) section D.1.

Dataset 1 (`Srivatsan20`) *This dataset is originally curated from (Srivatsan et al., 2020), featuring 188 small molecule perturbations across the K562, A549, and MCF-7 cell lines, and filtered to contain only the perturbation with the highest dose. In each of the three cell lines, 30% of perturbations are selected and assigned to val/test split while ensuring they have been observed in the other two cell lines.*

Dataset 2 (`Jiang24`) *This dataset is originally curated from (Jiang et al., 2024), featuring 219 genetic perturbations across 6 cell lines and 5 cytokine treatments. From the 30 distinct biological states (6 cell lines × 5 cytokine treatments), we selected 12 states and held out 70% of the perturbations within them for validation and testing.*

Dataset 3 (`Norman19`) *This datasets is originally curated from Norman et al. (2019), featuring 287 gene overexpression perturbations where 131 are dual perturbations in K562 cells.*

B. ARC Virtual Cell Challenge: additional information

B.1. ARC VCC evaluation metrics

The ARC Virtual Cell Challenge has evaluated model performance using a comprehensive suite of seven metrics. In this section, we detail the three core metrics (DES, PDS, and MAE), as well as the four additional metrics that were introduced in the expanded evaluation suite for the Generalist leaderboard.

- **Differential Expression Score (DES):** Similar to the DEG recall metric in PerturBench (Wu et al., 2024), DES here also evaluates a model's ability of recalling the ground truth differential genes. Let $G_{k,true}$ be the ground-truth differentially expressed genes for perturbation k, $G_{k,pred}$ be the differentially expressed genes from the model prediction for perturbation k, and $\tilde{G}_{k,pred}$ be the subset of $G_{k,pred}$ where its size is capped to $|\tilde{G}_{k,pred}| = |G_{k,true}|$ by selecting genes the largest absolute values of log fold changes, then:

$$DES_k = \begin{cases} \frac{|G_{k,pred} \cap G_{k,true}|}{|G_{k,true}|}, & \text{if } |G_{k,pred}| \leq |G_{k,true}| \\ \frac{|\tilde{G}_{k,pred} \cap G_{k,true}|}{|G_{k,true}|} & \text{if } |G_{k,pred}| > |G_{k,true}| \end{cases} \tag{4}$$

  Note that DES uses the Wilcoxon rank-sum test, different from the default paired Student's t-test in PerturBench.

  Scale: 0: lowest possible recall of ground-truth DEGs; 1: highest possible recall of ground-truth DEGs.

- **Perturbation Discrimination Score (PDS):** PDS measures a model's ability to capture the unique effects of a perturbation relative to all other perturbations. This metric is related to the rank metric introduced in PerturBench (Wu et al., 2024), which, for a given observed perturbation, computes how close the model prediction is to the observation, compared to predictions made for other perturbations. PDS is calculated as:

$$PDS_p = 1 - \frac{argind\{d_{pt}\}_{t=p} - 1}{N} \tag{5}$$

  where $d_{pt} = d_{L1}(\hat{\delta}_p) - \delta_t|_{\text{sort by t}}$, with $\delta_k = x_k - x_{ntc}$ being the perturbation delta of the pseudobulk expression profile between the perturbed states (x_k) and non-targeting controls (x_{ntc}).

  Scale: 0: the predicted perturbation effects are not unique to each perturbation; 1: the predicted perturbation effects are highly unique to each perturbation.

- **Mean Absolute Error (MAE):** MAE captures the overall predictive accuracy across the entire gene expression profile. If G is the number of genes, indexed by g, the MAE is given by:

$$MAE_k = \frac{1}{G}\Sigma_{g=1}^{G}|\hat{y}_{kg} - y_{kg}| \tag{6}$$

  Scale: 0: perfect fidelity in the predicted gene expression profiles; ∞: a complete lack of fidelity.

Later into the competition, four other scores were included to for the basis of a Generalist leaderboard:

- **Pearson Delta Correlation:** Measures the correlation between the predicted changes in gene expression and the actual observed changes.

  Scale: -1: a perfectly negative correlation between the predicted and observed changes; 1: a perfectly positive correlation between the predicted and observed changes.

- **Spearman Correlation of Log-Fold Change:** Evaluates how well the ranking of genes from most upregulated to most downregulated matches between the prediction and ground truth, ignoring exact numerical values.

  Scale: -1: completely reversed rankings; 1: perfect match between predicted and observed rankings of genes .

- **Area Under Precision Recall Curve (AUPRC):** A single score summarizing how well a model identifies "true" hits (e.g., differentially expressed genes) while minimizing false positives, which is especially useful when real hits are rare.

  Scale: 0: worst performance; 1: best performance.

- **Spearman Correlation of Effect Size:** Measures the Spearman correlation of the magnitude of the biological effect (the number of differentially expressed genes) between the predicted and observed data, across all test perturbations.

  Scale: -1: completely reversed rankings; 1: perfectly matching rankings.

B.2. Data composition and pretraining-finetuning strategies

Pretraining data atlas composition

Our perturbation data atlas for PRiMeFlow pretraining is composed as follows:

- Roohani et al. (2025): The dataset provided by the ARC Virtual Cell Challenge, which includes 150 gene knockdowns as well as non-targeting controls in H1 hESCs, within the training partition.

- Replogle et al. (2022): A comprehensive genome-scale Perturb-seq atlas targeting approximately 11,000 genes in K562 and RPE1 cell lines.

- Nadig et al. (2025): Large-scale Perturb-seq datasets profiling essential gene knockdowns in Jurkat and HepG2 cell lines.

- McFaline-Figueroa et al. (2024): A highly multiplexed single-cell chemical genomics (sci-Plex-GxE) dataset probing 522 human kinases combined with targeted drug treatments in glioblastoma cells.

- Replogle et al. (2020): A small Perturb-seq dataset in K562 cells. We only select the subset of single gene knockdowns for our data atlas.

- Jiang et al. (2024): The same `Jiang24` dataset in PerturBench which we have used for benchmarking.

- Feng et al. (2026): A large Perturb-seq dataset of 7,226 gene knockdowns across 34 iPSC lines from 24 donors.

- Internally generated proprietary data, derived from fully differentiated, non-pluripotent cell lines that are biologically distinct from H1 hESCs and iPSCs.

In total, our pretraining data atlas comprises 6,975,767 cells spanning seven public datasets and one proprietary dataset. The public data accounts for 89% of the entire atlas and encompasses 14 distinct cell lines [4] and 10,944 gene knockdowns.

Internal validation split on H1 hESCs

---

[4]All 14 cell lines from public data: iPSCs, H1 hESCs, HepG2, Jurkat, A549, BxPC-3, HAP1, HT-29, K562, MCF-7, A172, T98G, U-87 MG, and RPE1.

- To ensure robust model selection, we established an internal validation split by holding out 43 of the 150 designated training perturbations in H1 hESCs [5].

- Our internal validation split also includes a subset of 9,544 H1 hESC control cells.

Finetuning and covariate transfer strategy

The core objective of our finetuning strategy is to facilitate transfer learning, allowing the model to project perturbation effects learned from the expansive external data atlas onto the specific public and private test perturbations in H1 hESCs.

- During the finetuning phase, the validation split is significantly reduced: only 5 [6] of the original 43 held-out perturbations are retained for validation.

- The remaining 38 perturbations are reassigned back into the training split to maximize the model's exposure to training signals in H1 hESCs.

We implemented two distinct finetuning variants to evaluate the impact of targeted data subsets:

- PRiMeFlow-300pts finetuning: This dataset includes all 150 training set perturbations sourced from both the VCC H1 hESCs and all external datasets. Furthermore, it incorporates an additional 150 perturbations (comprising 50 public test perturbations and 100 private test perturbations) derived exclusively from the external datasets.

- PRiMeFlow-250pts finetuning: This dataset similarly begins with all 150 training set perturbations from both the VCC H1 hESCs and external datasets. However, it isolates the additional data to strictly include the 100 private test perturbations from the external datasets. By narrowing the scope of the included perturbations, this strategy allows the model to focus more on predicting the private test set.

Note that we keep all control cells from external data during finetuning.

B.3. Inference-time strategy

To generate predictions from PRiMeFlow, we solve the initial value problem using the learned velocity field via the Dopri5 (i.e., the Dormand-Prince method) solver. The ODE integration starts from samples from the standard Gaussian distribution and is conditioned on the specific public or private test perturbation in the H1 hESC cell-line covariate.

During generation, we apply classifier-free guidance with a weight of 20 for perturbed cells and a weight of 5 for synthetic control cells. Empirical evaluations on our internal validation split demonstrated that these asymmetric CFG settings significantly benefit the PDS metric by amplifying the uniqueness and specificity of the predicted perturbation delta. For cell counts, we generate the exact number of perturbed cells recommended by the VCC guidelines (i.e., *pert_counts_Validation.csv* and *pert_counts_Test.csv*), while maintaining a fixed number of 200 synthetic control cells.

Afterwards, we perform per-perturbation expression normalization, also using the recommended median sequencing depth from the VCC guidelines (*median_umi_per_cell*). Because PRiMeFlow is trained on log1p-normalized data, we execute a postprocessing step:

1. convert the predictions to the raw count space through expm1;

2. perform median normalization;

3. rounding to the nearest integer;

4. perform a second median normalization, still using the same recommended median;

---

[5]43 held-out perturbations for internal validation: CHMP3, SHPRH, TMSB4X, TCF3, DHCR24, SMARCA5, SSBP1, PBX1, EID2, SRC, HSBP1, MED13, TET1, KDR, TFAM, MAST2, SMAGP, CAST, MTA1, GSK3B, STAT6, ARID1A, CREG1, RRM1, ZNF714, CASP2, CENPO, PTPN1, UBE3C, TGFBR2, MED24, MKI67, TAF13, NRAS, MED1, NIT1, ZNF562, PHF10, WSB2, SIN3B, METTL3, SEC62, BRD9
[6]Validation perturbations at the finetuning stage: EID2, TFAM, PHF10, BRD9, and SIN3B

5. convert the expression values back to log-1p space.

Finally, we manually set the target gene expression values in the predicted perturbed expression profiles to 0s.

C. PRiMeFlow results in ARC VCC public test

Table 5. PRiMeFlow performance on H1 hESCs public test set using all seven ARC VCC metrics.

Model	DES ↑	PDS ↑	MAE ↓	SPEARMAN ↑	SPEARMAN_LFC ↑	AUPRC ↑	PEARSON ↑
PRiMeFlow pretrained	0.221	0.712	0.078	0.440	0.310	0.284	0.199
PRiMeFlow 200pts	0.224	0.817	0.092	0.603	0.386	0.289	0.216
x.Compass	0.344	0.852	4.215	-	-	-	-
Outlier	0.378	0.832	4.218	-	-	-	-
WIND	0.333	0.822	0.605	-	-	-	-

Table 5 shows the PRiMeFlow performance in the 50 held-out public test perturabtions in H1 hESCs. The PRiMeFlow-200pts is funetuned to the subset of the pretraining data atlas that include the 250 VCC perturbations (150 training+50 public test) across the H1 hESCs and other external datasets.

We also include the top-three performing models from the ARC VCC public test leaderboard for comparison. Note that we did not include the expanded evaluation metrics for these modes as the public test leaderboard only shows the three core evaluation metrics: DES, PDS and MAE.

Again, finetuning has been shown to benefit PRiMeFlow across most of the expanded evaluation suite, and overall, PRiMeFlow is able to achieve strong DES and PDS performance, while incurring minimal extortion to the ground truth gene expression values as shown by its significantly lower MAE.

D. Additional PerturBench results

Table 6. Performance of PRiMeFlow on traditional pseudobulk-based metrics in `Srivatsan20` dataset.

Model	Cosine logFC	Cosine logFC rank	RMSE mean	RMSE mean rank
PRiMeFlow CFG1	$0.46 \pm 1 \times 10^{-2}$	$0.12 \pm 1 \times 10^{-2}$	$0.019 \pm 5 \times 10^{-4}$	$0.14 \pm 6 \times 10^{-3}$
PRiMeFlow CFG3	$0.43 \pm 9 \times 10^{-3}$	$\mathbf{0.10 \pm 4 \times 10^{-3}}$	$0.029 \pm 3 \times 10^{-4}$	$0.22 \pm 5 \times 10^{-3}$
PRiMeFlow CFG5	$0.39 \pm 1 \times 10^{-2}$	$\mathbf{0.10 \pm 2 \times 10^{-3}}$	$0.041 \pm 4 \times 10^{-4}$	$0.29 \pm 1 \times 10^{-2}$
PRiMeFlow MLP CFG1	$-0.012 \pm 4 \times 10^{-4}$	$0.46 \pm 1 \times 10^{-2}$	$0.31 \pm 9 \times 10^{-4}$	$0.42 \pm 1 \times 10^{-2}$
PRiMeFlow MLP CFG3	$-0.0071 \pm 2 \times 10^{-3}$	$0.45 \pm 3 \times 10^{-2}$	$0.33 \pm 5 \times 10^{-3}$	$0.44 \pm 2 \times 10^{-2}$
PRiMeFlow MLP CFG5	$-0.0026 \pm 3 \times 10^{-3}$	$0.45 \pm 3 \times 10^{-2}$	$0.40 \pm 1 \times 10^{-2}$	$0.47 \pm 2 \times 10^{-2}$
FM PCA CFG1	$0.15 \pm 2 \times 10^{-3}$	$0.34 \pm 6 \times 10^{-3}$	$0.042 \pm 4 \times 10^{-4}$	$0.24 \pm 9 \times 10^{-3}$
FM PCA CFG3	$0.16 \pm 3 \times 10^{-3}$	$0.30 \pm 3 \times 10^{-3}$	$0.041 \pm 2 \times 10^{-4}$	$0.22 \pm 5 \times 10^{-3}$
FM PCA CFG5	$0.17 \pm 3 \times 10^{-3}$	$0.28 \pm 6 \times 10^{-3}$	$0.045 \pm 2 \times 10^{-4}$	$0.25 \pm 3 \times 10^{-3}$
FM PCA OT CFG1	$0.12 \pm 2 \times 10^{-4}$	$0.42 \pm 4 \times 10^{-2}$	$0.044 \pm 5 \times 10^{-4}$	$0.41 \pm 2 \times 10^{-2}$
FM PCA OT CFG3	$0.12 \pm 6 \times 10^{-4}$	$0.42 \pm 4 \times 10^{-2}$	$0.044 \pm 5 \times 10^{-4}$	$0.40 \pm 2 \times 10^{-2}$
FM PCA OT CFG5	$0.12 \pm 1 \times 10^{-3}$	$0.42 \pm 4 \times 10^{-2}$	$0.044 \pm 4 \times 10^{-4}$	$0.40 \pm 2 \times 10^{-2}$
CPA	$0.38 \pm 5 \times 10^{-3}$	$0.15 \pm 9 \times 10^{-3}$	$0.020 \pm 2 \times 10^{-4}$	$0.16 \pm 7 \times 10^{-3}$
CPA (noAdv)	$0.40 \pm 5 \times 10^{-3}$	$\mathbf{0.09 \pm 5 \times 10^{-3}}$	$0.020 \pm 1 \times 10^{-4}$	$\mathbf{0.10 \pm 6 \times 10^{-3}}$
SAMS-VAE	$0.44 \pm 1 \times 10^{-3}$	$0.17 \pm 1 \times 10^{-2}$	$0.023 \pm 8 \times 10^{-5}$	$0.17 \pm 1 \times 10^{-2}$
SAMS-VAE (S)	$\mathbf{0.53 \pm 1 \times 10^{-2}}$	$0.12 \pm 1 \times 10^{-2}$	$\mathbf{0.018 \pm 3 \times 10^{-4}}$	$0.13 \pm 1 \times 10^{-2}$
Biolord	$0.26 \pm 2 \times 10^{-1}$	$0.26 \pm 2 \times 10^{-1}$	$0.074 \pm 5 \times 10^{-2}$	$0.25 \pm 2 \times 10^{-1}$
Latent	$0.45 \pm 2 \times 10^{-3}$	$0.13 \pm 4 \times 10^{-3}$	$\mathbf{0.018 \pm 6 \times 10^{-5}}$	$0.15 \pm 3 \times 10^{-3}$
Decoder	$0.35 \pm 5 \times 10^{-3}$	$0.16 \pm 1 \times 10^{-2}$	$\mathbf{0.018 \pm 1 \times 10^{-4}}$	$0.14 \pm 7 \times 10^{-3}$
Linear	$0.16 \pm 1 \times 10^{-2}$	$0.28 \pm 5 \times 10^{-3}$	$0.030 \pm 5 \times 10^{-4}$	$0.27 \pm 2 \times 10^{-3}$

Table 7. Performance of PRiMeFlow on traditional pseudobulk-based metrics in `Norman19` dataset.

Model	Cosine logFC	Cosine logFC rank	RMSE mean	RMSE mean rank
PRiMeFlow CFG1	$0.77 \pm 4 \times 10^{-3}$	$0.0057 \pm 8 \times 10^{-4}$	$0.046 \pm 1 \times 10^{-3}$	$0.022 \pm 6 \times 10^{-3}$
PRiMeFlow CFG3	$\mathbf{0.79 \pm 2 \times 10^{-3}}$	$0.0072 \pm 3 \times 10^{-3}$	$0.074 \pm 2 \times 10^{-3}$	$0.077 \pm 8 \times 10^{-3}$
PRiMeFlow CFG5	$0.74 \pm 3 \times 10^{-3}$	$0.015 \pm 3 \times 10^{-3}$	$0.11 \pm 2 \times 10^{-3}$	$0.19 \pm 1 \times 10^{-2}$
PRiMeFlow MLP CFG1	$0.024 \pm 6 \times 10^{-3}$	$0.27 \pm 3 \times 10^{-2}$	$0.29 \pm 2 \times 10^{-3}$	$0.16 \pm 4 \times 10^{-2}$
PRiMeFlow MLP CFG3	$0.054 \pm 8 \times 10^{-3}$	$0.27 \pm 2 \times 10^{-2}$	$0.31 \pm 2 \times 10^{-3}$	$0.25 \pm 2 \times 10^{-2}$
PRiMeFlow MLP CFG5	$0.080 \pm 9 \times 10^{-3}$	$0.26 \pm 2 \times 10^{-2}$	$0.33 \pm 4 \times 10^{-3}$	$0.31 \pm 1 \times 10^{-2}$
FM PCA CFG1	$0.50 \pm 2 \times 10^{-3}$	$0.053 \pm 3 \times 10^{-3}$	$0.062 \pm 9 \times 10^{-5}$	$0.067 \pm 3 \times 10^{-3}$
FM PCA CFG3	$0.61 \pm 3 \times 10^{-3}$	$0.040 \pm 2 \times 10^{-3}$	$0.076 \pm 6 \times 10^{-4}$	$0.083 \pm 1 \times 10^{-3}$
FM PCA CFG5	$0.63 \pm 4 \times 10^{-3}$	$0.034 \pm 3 \times 10^{-3}$	$0.11 \pm 2 \times 10^{-3}$	$0.15 \pm 1 \times 10^{-2}$
FM PCA OT CFG1	$0.056 \pm 5 \times 10^{-3}$	$0.32 \pm 2 \times 10^{-2}$	$0.095 \pm 7 \times 10^{-4}$	$0.33 \pm 2 \times 10^{-2}$
FM PCA OT CFG3	$0.060 \pm 6 \times 10^{-3}$	$0.32 \pm 2 \times 10^{-2}$	$0.094 \pm 8 \times 10^{-4}$	$0.32 \pm 2 \times 10^{-2}$
FM PCA OT CFG5	$0.065 \pm 7 \times 10^{-3}$	$0.32 \pm 2 \times 10^{-2}$	$0.094 \pm 8 \times 10^{-4}$	$0.32 \pm 2 \times 10^{-2}$
CPA	$0.76 \pm 4 \times 10^{-3}$	$0.0067 \pm 2 \times 10^{-3}$	$0.046 \pm 4 \times 10^{-4}$	$0.019 \pm 3 \times 10^{-3}$
CPA (noAdv)	$0.77 \pm 1 \times 10^{-2}$	$\mathbf{0.0053 \pm 3 \times 10^{-3}}$	$0.046 \pm 1 \times 10^{-3}$	$0.017 \pm 1 \times 10^{-3}$
SAMS-VAE	$0.45 \pm 2 \times 10^{-2}$	$0.019 \pm 7 \times 10^{-3}$	$0.084 \pm 7 \times 10^{-4}$	$0.025 \pm 4 \times 10^{-3}$
SAMS-VAE (S)	$\mathbf{0.78 \pm 6 \times 10^{-3}}$	$0.020 \pm 4 \times 10^{-3}$	$0.047 \pm 2 \times 10^{-3}$	$0.030 \pm 6 \times 10^{-3}$
Biolord	$0.45 \pm 8 \times 10^{-3}$	$0.026 \pm 4 \times 10^{-3}$	$0.083 \pm 2 \times 10^{-4}$	$0.034 \pm 2 \times 10^{-3}$
Latent	$\mathbf{0.79 \pm 1 \times 10^{-2}}$	$\mathbf{0.005 \pm 2 \times 10^{-3}}$	$\mathbf{0.043 \pm 4 \times 10^{-4}}$	$\mathbf{0.014 \pm 1 \times 10^{-3}}$
Decoder	$0.73 \pm 2 \times 10^{-2}$	$0.017 \pm 6 \times 10^{-3}$	$\mathbf{0.043 \pm 3 \times 10^{-4}}$	$\mathbf{0.014 \pm 4 \times 10^{-4}}$
Linear	$0.60 \pm 2 \times 10^{-2}$	$0.035 \pm 4 \times 10^{-3}$	$0.057 \pm 3 \times 10^{-3}$	$0.016 \pm 8 \times 10^{-4}$

Table 8. Performance of PRiMeFlow on traditional pseudobulk-based metrics in `Jiang24` dataset.

Model	Cosine logFC	Cosine logFC rank	RMSE mean	RMSE mean rank
PRiMeFlow CFG1	$0.47 \pm 5 \times 10^{-3}$	$0.39 \pm 2 \times 10^{-2}$	$0.019 \pm 3 \times 10^{-4}$	$0.40 \pm 2 \times 10^{-2}$
PRiMeFlow CFG3	$0.41 \pm 4 \times 10^{-3}$	$0.38 \pm 1 \times 10^{-2}$	$0.034 \pm 5 \times 10^{-4}$	$0.43 \pm 1 \times 10^{-2}$
PRiMeFlow CFG5	$0.36 \pm 4 \times 10^{-3}$	$0.37 \pm 1 \times 10^{-2}$	$0.045 \pm 5 \times 10^{-4}$	$0.43 \pm 7 \times 10^{-3}$
PRiMeFlow MLP CFG1	$0.053 \pm 1 \times 10^{-4}$	$0.45 \pm 5 \times 10^{-3}$	$0.33 \pm 6 \times 10^{-4}$	$0.46 \pm 1 \times 10^{-3}$
PRiMeFlow MLP CFG3	$0.053 \pm 7 \times 10^{-5}$	$0.43 \pm 1 \times 10^{-2}$	$0.33 \pm 6 \times 10^{-4}$	$0.46 \pm 3 \times 10^{-3}$
PRiMeFlow MLP CFG5	$0.053 \pm 9 \times 10^{-5}$	$0.43 \pm 1 \times 10^{-2}$	$0.33 \pm 7 \times 10^{-4}$	$0.47 \pm 3 \times 10^{-3}$
FlowMatching PCA CFG1	$0.071 \pm 8 \times 10^{-5}$	$0.37 \pm 9 \times 10^{-3}$	0.10 ± 0	$0.39 \pm 9 \times 10^{-3}$
FlowMatching PCA CFG3	$0.072 \pm 1 \times 10^{-4}$	$0.36 \pm 4 \times 10^{-3}$	$0.10 \pm 9 \times 10^{-5}$	$0.42 \pm 5 \times 10^{-3}$
FlowMatching PCA CFG5	$0.072 \pm 3 \times 10^{-4}$	$0.36 \pm 5 \times 10^{-3}$	$0.10 \pm 2 \times 10^{-4}$	$0.44 \pm 5 \times 10^{-3}$
FlowMatching PCA OT CFG1	$0.068 \pm 3 \times 10^{-4}$	$0.47 \pm 2 \times 10^{-2}$	$0.10 \pm 8 \times 10^{-4}$	$0.47 \pm 4 \times 10^{-3}$
FlowMatching PCA OT CFG3	$0.068 \pm 4 \times 10^{-4}$	$0.47 \pm 2 \times 10^{-2}$	$0.11 \pm 2 \times 10^{-4}$	$0.47 \pm 8 \times 10^{-4}$
FlowMatching PCA OT CFG5	$0.068 \pm 6 \times 10^{-4}$	$0.47 \pm 1 \times 10^{-2}$	$0.11 \pm 2 \times 10^{-3}$	$0.47 \pm 3 \times 10^{-3}$
CPA	$0.60 \pm 2 \times 10^{-3}$	$0.40 \pm 9 \times 10^{-3}$	$\mathbf{0.015 \pm 5 \times 10^{-5}}$	$0.41 \pm 1 \times 10^{-2}$
CPA (noAdv)	$0.60 \pm 2 \times 10^{-3}$	$0.39 \pm 1 \times 10^{-2}$	$\mathbf{0.015 \pm 4 \times 10^{-5}}$	$0.40 \pm 1 \times 10^{-2}$
SAMS-VAE	$0.59 \pm 3 \times 10^{-3}$	$0.43 \pm 1 \times 10^{-2}$	$0.017 \pm 1 \times 10^{-4}$	$0.43 \pm 1 \times 10^{-2}$
SAMS-VAE (S)	$0.57 \pm 5 \times 10^{-2}$	$0.43 \pm 1 \times 10^{-2}$	$0.017 \pm 2 \times 10^{-3}$	$0.42 \pm 4 \times 10^{-2}$
Latent	$0.47 \pm 1 \times 10^{-3}$	$0.38 \pm 6 \times 10^{-3}$	$\mathbf{0.015 \pm 6 \times 10^{-5}}$	$0.38 \pm 7 \times 10^{-3}$
Decoder	$\mathbf{0.64 \pm 1 \times 10^{-3}}$	$\mathbf{0.32 \pm 8 \times 10^{-3}}$	$\mathbf{0.015 \pm 3 \times 10^{-5}}$	$\mathbf{0.32 \pm 5 \times 10^{-3}}$
Linear	$0.17 \pm 9 \times 10^{-5}$	$0.34 \pm 2 \times 10^{-4}$	$0.038 \pm 5 \times 10^{-5}$	$0.43 \pm 1 \times 10^{-3}$

Table 9. All distributional metrics performance on the `Srivatsan20` dataset.

Model	MMD GEX	MMD GEX rank	MMD PCA	MMD PCA rank	DEG recall	DEG recall rank
PRiMeFlow CFG1	$\mathbf{0.13 \pm 4 \times 10^{-3}}$	$\mathbf{0.13 \pm 8 \times 10^{-3}}$	$\mathbf{0.14 \pm 8 \times 10^{-3}}$	$0.14 \pm 9 \times 10^{-3}$	$\mathbf{0.26 \pm 1 \times 10^{-2}}$	$0.27 \pm 2 \times 10^{-2}$
PRiMeFlow CFG3	$0.25 \pm 2 \times 10^{-3}$	$0.22 \pm 7 \times 10^{-3}$	$0.31 \pm 1 \times 10^{-2}$	$0.21 \pm 9 \times 10^{-3}$	$\mathbf{0.27 \pm 6 \times 10^{-3}}$	$\mathbf{0.24 \pm 1 \times 10^{-2}}$
PRiMeFlow CFG5	$0.47 \pm 1 \times 10^{-2}$	$0.29 \pm 2 \times 10^{-2}$	$0.60 \pm 2 \times 10^{-2}$	$0.26 \pm 9 \times 10^{-3}$	$0.25 \pm 5 \times 10^{-3}$	$\mathbf{0.24 \pm 1 \times 10^{-2}}$
PRiMeFlow MLP CFG1	$14. \pm 5 \times 10^{-2}$	$0.43 \pm 2 \times 10^{-2}$	$8.8 \pm 1 \times 10^{-1}$	$0.42 \pm 2 \times 10^{-2}$	$0.011 \pm 8 \times 10^{-4}$	$0.47 \pm 6 \times 10^{-3}$
PRiMeFlow MLP CFG3	$15. \pm 2 \times 10^{-1}$	$0.44 \pm 2 \times 10^{-2}$	$11. \pm 6 \times 10^{-1}$	$0.43 \pm 5 \times 10^{-3}$	$0.11 \pm 2 \times 10^{-2}$	$0.49 \pm 2 \times 10^{-2}$
PRiMeFlow MLP CFG5	$18. \pm 8 \times 10^{-1}$	$0.47 \pm 2 \times 10^{-2}$	$18. \pm 1 \times 10^{0}$	$0.46 \pm 2 \times 10^{-2}$	$0.13 \pm 1 \times 10^{-2}$	$0.49 \pm 4 \times 10^{-2}$
FM PCA CFG1	$1.2 \pm 7 \times 10^{-3}$	$0.26 \pm 6 \times 10^{-3}$	$0.50 \pm 2 \times 10^{-2}$	$0.24 \pm 1 \times 10^{-2}$	$0.042 \pm 2 \times 10^{-3}$	$0.46 \pm 6 \times 10^{-3}$
FM PCA CFG3	$1.3 \pm 5 \times 10^{-3}$	$0.25 \pm 7 \times 10^{-3}$	$0.44 \pm 1 \times 10^{-2}$	$0.22 \pm 8 \times 10^{-3}$	$0.071 \pm 3 \times 10^{-3}$	$0.39 \pm 1 \times 10^{-2}$
FM PCA CFG5	$1.4 \pm 4 \times 10^{-3}$	$0.29 \pm 4 \times 10^{-3}$	$0.53 \pm 1 \times 10^{-2}$	$0.26 \pm 6 \times 10^{-3}$	$0.10 \pm 3 \times 10^{-3}$	$0.36 \pm 9 \times 10^{-3}$
FM PCA OT CFG1	$1.3 \pm 3 \times 10^{-2}$	$0.43 \pm 2 \times 10^{-2}$	$0.62 \pm 5 \times 10^{-3}$	$0.40 \pm 3 \times 10^{-2}$	$0.023 \pm 4 \times 10^{-4}$	$0.51 \pm 3 \times 10^{-3}$
FM PCA OT CFG3	$1.3 \pm 3 \times 10^{-2}$	$0.42 \pm 2 \times 10^{-2}$	$0.61 \pm 4 \times 10^{-3}$	$0.40 \pm 3 \times 10^{-2}$	$0.024 \pm 6 \times 10^{-4}$	$0.51 \pm 2 \times 10^{-3}$
FM PCA OT CFG5	$1.3 \pm 3 \times 10^{-2}$	$0.43 \pm 2 \times 10^{-2}$	$0.60 \pm 4 \times 10^{-3}$	$0.39 \pm 2 \times 10^{-2}$	$0.024 \pm 6 \times 10^{-4}$	$0.51 \pm 4 \times 10^{-3}$
CPA	$2.4 \pm 1 \times 10^{-2}$	$0.30 \pm 9 \times 10^{-3}$	$0.53 \pm 4 \times 10^{-3}$	$0.20 \pm 9 \times 10^{-3}$	$0.0073 \pm 2 \times 10^{-3}$	$0.46 \pm 5 \times 10^{-3}$
CPA (noAdv)	$2.3 \pm 3 \times 10^{-2}$	$0.25 \pm 5 \times 10^{-3}$	$0.49 \pm 1 \times 10^{-2}$	$0.13 \pm 1 \times 10^{-2}$	$0.0040 \pm 2 \times 10^{-3}$	$0.48 \pm 5 \times 10^{-2}$
SAMS-VAE	$2.5 \pm 2 \times 10^{-2}$	$0.30 \pm 8 \times 10^{-3}$	$0.69 \pm 1 \times 10^{-2}$	$\mathbf{0.060 \pm 3 \times 10^{-3}}$	0 ± 0	$0.50 \pm 4 \times 10^{-2}$
SAMS-VAE (S)	$2.9 \pm 1 \times 10^{-2}$	$0.28 \pm 5 \times 10^{-3}$	$0.79 \pm 1 \times 10^{-2}$	$0.18 \pm 2 \times 10^{-2}$	0 ± 0	$0.50 \pm 4 \times 10^{-2}$
Biolord	$4.9 \pm 3 \times 10^{0}$	$0.36 \pm 2 \times 10^{-1}$	$4.3 \pm 4 \times 10^{0}$	$0.32 \pm 2 \times 10^{-1}$	$4.7e-05 \pm 1 \times 10^{-4}$	$0.49 \pm 2 \times 10^{-2}$
Latent	$4.3 \pm 2 \times 10^{-1}$	$0.26 \pm 6 \times 10^{-2}$	$2.0 \pm 2 \times 10^{-1}$	$0.26 \pm 5 \times 10^{-2}$	0.0 ± 0.0	$0.49 \pm 3 \times 10^{-2}$
Decoder	$4.2 \pm 4 \times 10^{-3}$	$0.16 \pm 2 \times 10^{-2}$	$1.9 \pm 5 \times 10^{-3}$	$0.15 \pm 1 \times 10^{-2}$	N/A	N/A
Linear	$2.2 \pm 7 \times 10^{-3}$	$0.31 \pm 1 \times 10^{-3}$	$0.76 \pm 9 \times 10^{-4}$	$0.30 \pm 3 \times 10^{-4}$	$0.0036 \pm 3 \times 10^{-4}$	$0.49 \pm 5 \times 10^{-2}$

Table 10. All distributional metrics performance on the `Norman19` dataset.

Model	MMD GEX	MMD GEX rank	MMD PCA	MMD PCA rank	DEG recall	DEG recall rank
PRiMeFlow CFG1	$\mathbf{0.26 \pm 7 \times 10^{-3}}$	$\mathbf{0.019 \pm 4 \times 10^{-3}}$	$\mathbf{0.34 \pm 2 \times 10^{-2}}$	$0.023 \pm 5 \times 10^{-3}$	$0.54 \pm 2 \times 10^{-2}$	$0.024 \pm 6 \times 10^{-3}$
PRiMeFlow CFG3	$0.61 \pm 3 \times 10^{-2}$	$0.066 \pm 9 \times 10^{-3}$	$0.86 \pm 5 \times 10^{-2}$	$0.063 \pm 6 \times 10^{-3}$	$\mathbf{0.61 \pm 8 \times 10^{-3}}$	$\mathbf{0.0060 \pm 3 \times 10^{-3}}$
PRiMeFlow CFG5	$1.3 \pm 4 \times 10^{-2}$	$0.17 \pm 1 \times 10^{-2}$	$1.8 \pm 5 \times 10^{-2}$	$0.14 \pm 1 \times 10^{-2}$	$0.56 \pm 1 \times 10^{-2}$	$0.0085 \pm 2 \times 10^{-3}$
PRiMeFlow MLP CFG1	$7.2 \pm 8 \times 10^{-2}$	$0.19 \pm 4 \times 10^{-2}$	$3.7 \pm 1 \times 10^{-1}$	$0.16 \pm 4 \times 10^{-2}$	$0.057 \pm 8 \times 10^{-3}$	$0.42 \pm 2 \times 10^{-2}$
PRiMeFlow MLP CFG3	$7.6 \pm 9 \times 10^{-2}$	$0.27 \pm 2 \times 10^{-2}$	$4.5 \pm 2 \times 10^{-1}$	$0.25 \pm 2 \times 10^{-2}$	$0.20 \pm 3 \times 10^{-2}$	$0.28 \pm 1 \times 10^{-2}$
PRiMeFlow MLP CFG5	$8.5 \pm 2 \times 10^{-1}$	$0.32 \pm 8 \times 10^{-3}$	$6.3 \pm 4 \times 10^{-1}$	$0.31 \pm 1 \times 10^{-2}$	$0.30 \pm 3 \times 10^{-2}$	$0.21 \pm 3 \times 10^{-2}$
FM PCA CFG1	$0.77 \pm 4 \times 10^{-3}$	$0.059 \pm 3 \times 10^{-3}$	$0.61 \pm 5 \times 10^{-3}$	$0.066 \pm 4 \times 10^{-3}$	$0.37 \pm 2 \times 10^{-3}$	$0.069 \pm 9 \times 10^{-3}$
FM PCA CFG3	$1.1 \pm 8 \times 10^{-3}$	$0.098 \pm 2 \times 10^{-3}$	$0.82 \pm 9 \times 10^{-3}$	$0.076 \pm 1 \times 10^{-3}$	$0.45 \pm 2 \times 10^{-3}$	$0.030 \pm 2 \times 10^{-3}$
FM PCA CFG5	$1.9 \pm 4 \times 10^{-2}$	$0.18 \pm 1 \times 10^{-2}$	$1.6 \pm 4 \times 10^{-2}$	$0.12 \pm 4 \times 10^{-3}$	$0.43 \pm 4 \times 10^{-3}$	$0.031 \pm 3 \times 10^{-3}$
FM PCA OT CFG1	$2.6 \pm 1 \times 10^{-2}$	$0.33 \pm 2 \times 10^{-2}$	$1.8 \pm 2 \times 10^{-2}$	$0.32 \pm 2 \times 10^{-2}$	$0.0012 \pm 9 \times 10^{-4}$	$0.56 \pm 2 \times 10^{-2}$
FM PCA OT CFG3	$2.6 \pm 1 \times 10^{-2}$	$0.32 \pm 2 \times 10^{-2}$	$1.8 \pm 2 \times 10^{-2}$	$0.32 \pm 2 \times 10^{-2}$	$0.0017 \pm 1 \times 10^{-3}$	$0.55 \pm 2 \times 10^{-2}$
FM PCA OT CFG5	$2.6 \pm 2 \times 10^{-2}$	$0.32 \pm 2 \times 10^{-2}$	$1.8 \pm 3 \times 10^{-2}$	$0.32 \pm 2 \times 10^{-2}$	$0.0020 \pm 1 \times 10^{-3}$	$0.54 \pm 2 \times 10^{-2}$
CPA	$5.6 \pm 3 \times 10^{-2}$	$0.14 \pm 9 \times 10^{-3}$	$2.2 \pm 2 \times 10^{-2}$	$0.044 \pm 5 \times 10^{-3}$	$0.032 \pm 4 \times 10^{-3}$	$0.30 \pm 5 \times 10^{-2}$
CPA (noAdv)	$5.5 \pm 1 \times 10^{-1}$	$0.13 \pm 2 \times 10^{-2}$	$2.2 \pm 1 \times 10^{-1}$	$0.038 \pm 5 \times 10^{-3}$	$0.016 \pm 9 \times 10^{-3}$	$0.28 \pm 5 \times 10^{-2}$
SAMS-VAE	$4.1 \pm 4 \times 10^{-2}$	$0.034 \pm 1 \times 10^{-2}$	$1.9 \pm 3 \times 10^{-2}$	$0.020 \pm 2 \times 10^{-3}$	0 ± 0	$0.46 \pm 4 \times 10^{-2}$
SAMS-VAE (S)	$3.3 \pm 5 \times 10^{-2}$	$0.088 \pm 6 \times 10^{-3}$	$0.74 \pm 5 \times 10^{-2}$	$0.029 \pm 4 \times 10^{-3}$	$0.028 \pm 6 \times 10^{-3}$	$0.38 \pm 3 \times 10^{-2}$
Biolord	$2.8 \pm 5 \times 10^{-3}$	$0.066 \pm 3 \times 10^{-3}$	$1.6 \pm 5 \times 10^{-3}$	$0.042 \pm 3 \times 10^{-3}$	0 ± 0	$0.47 \pm 3 \times 10^{-2}$
Latent	$6.7 \pm 4 \times 10^{-3}$	$0.012 \pm 1 \times 10^{-3}$	$3.2 \pm 6 \times 10^{-3}$	$0.013 \pm 8 \times 10^{-4}$	$0.00043 \pm 3 \times 10^{-4}$	$0.50 \pm 1 \times 10^{-2}$
Decoder	$6.7 \pm 6 \times 10^{-3}$	$0.0090 \pm 8 \times 10^{-4}$	$3.2 \pm 4 \times 10^{-3}$	$\mathbf{0.0098 \pm 4 \times 10^{-4}}$	N/A	N/A
Linear	$2.5 \pm 4 \times 10^{-2}$	$0.026 \pm 2 \times 10^{-3}$	$1.2 \pm 4 \times 10^{-2}$	$0.017 \pm 4 \times 10^{-4}$	$0.018 \pm 2 \times 10^{-3}$	$0.40 \pm 4 \times 10^{-2}$

Table 11. All distributional metrics performance on the `Jiang24` dataset.

Model	MMD GEX	MMD GEX rank	MMD PCA	MMD PCA rank	DEG recall	DEG recall rank
PRiMeFlow CFG1	$\mathbf{0.14 \pm 4 \times 10^{-3}}$	$0.41 \pm 9 \times 10^{-3}$	$\mathbf{0.057 \pm 6 \times 10^{-4}}$	$\mathbf{0.39 \pm 1 \times 10^{-2}}$	$\mathbf{0.099 \pm 5 \times 10^{-3}}$	$\mathbf{0.41 \pm 3 \times 10^{-2}}$
PRiMeFlow CFG3	$0.37 \pm 4 \times 10^{-2}$	$0.44 \pm 1 \times 10^{-2}$	$0.38 \pm 2 \times 10^{-3}$	$0.44 \pm 8 \times 10^{-3}$	$0.061 \pm 4 \times 10^{-3}$	$0.43 \pm 7 \times 10^{-3}$
PRiMeFlow CFG5	$0.73 \pm 7 \times 10^{-2}$	$0.44 \pm 9 \times 10^{-3}$	$0.73 \pm 3 \times 10^{-2}$	$0.44 \pm 9 \times 10^{-3}$	$0.056 \pm 3 \times 10^{-3}$	$0.43 \pm 2 \times 10^{-2}$
PRiMeFlow MLP CFG1	$17. \pm 7 \times 10^{-2}$	$0.46 \pm 2 \times 10^{-3}$	$9.5 \pm 8 \times 10^{-2}$	$0.46 \pm 3 \times 10^{-3}$	$0.0037 \pm 3 \times 10^{-4}$	$0.45 \pm 1 \times 10^{-2}$
PRiMeFlow MLP CFG3	$17. \pm 4 \times 10^{-2}$	$0.46 \pm 3 \times 10^{-3}$	$9.8 \pm 1 \times 10^{-1}$	$0.46 \pm 2 \times 10^{-3}$	$0.0031 \pm 3 \times 10^{-4}$	$0.44 \pm 4 \times 10^{-3}$
PRiMeFlow MLP CFG5	$17. \pm 5 \times 10^{-2}$	$0.47 \pm 3 \times 10^{-3}$	$9.8 \pm 1 \times 10^{-1}$	$0.46 \pm 2 \times 10^{-3}$	$0.0033 \pm 5 \times 10^{-4}$	$0.45 \pm 1 \times 10^{-2}$
FlowMatching PCA CFG1	$6.2 \pm 9 \times 10^{-3}$	$0.46 \pm 2 \times 10^{-3}$	$4.2 \pm 4 \times 10^{-3}$	$0.45 \pm 3 \times 10^{-3}$	0.0055 ± 0	0.46 ± 0
FlowMatching PCA CFG3	$6.8 \pm 3 \times 10^{-2}$	$0.46 \pm 3 \times 10^{-3}$	$4.0 \pm 1 \times 10^{-2}$	$0.44 \pm 6 \times 10^{-3}$	0.0055 ± 0	0.46 ± 0
FlowMatching PCA CFG5	$7.1 \pm 7 \times 10^{-2}$	$0.46 \pm 2 \times 10^{-3}$	$4.1 \pm 3 \times 10^{-2}$	$0.44 \pm 7 \times 10^{-3}$	$0.0056 \pm 6 \times 10^{-5}$	$0.46 \pm 3 \times 10^{-3}$
FlowMatching PCA OT CFG1	$6.3 \pm 9 \times 10^{-2}$	$0.47 \pm 9 \times 10^{-4}$	$3.7 \pm 2 \times 10^{-2}$	$0.47 \pm 4 \times 10^{-3}$	0.0055 ± 0	0.46 ± 0
FlowMatching PCA OT CFG3	$6.5 \pm 1 \times 10^{-1}$	$0.47 \pm 3 \times 10^{-3}$	$3.6 \pm 2 \times 10^{-2}$	$0.47 \pm 4 \times 10^{-3}$	0.0055 ± 0	$0.46 \pm 3 \times 10^{-4}$
FlowMatching PCA OT CFG5	$6.7 \pm 2 \times 10^{-1}$	$0.47 \pm 1 \times 10^{-3}$	$3.6 \pm 4 \times 10^{-2}$	$0.47 \pm 5 \times 10^{-3}$	$0.0057 \pm 2 \times 10^{-4}$	$0.46 \pm 4 \times 10^{-3}$
CPA	$8.0 \pm 2 \times 10^{-3}$	$0.44 \pm 7 \times 10^{-3}$	$2.5 \pm 4 \times 10^{-3}$	$0.43 \pm 4 \times 10^{-3}$	$0.0044 \pm 2 \times 10^{-3}$	$0.48 \pm 5 \times 10^{-3}$
CPA (noAdv)	$8.0 \pm 2 \times 10^{-3}$	$0.44 \pm 6 \times 10^{-3}$	$2.5 \pm 3 \times 10^{-3}$	$0.42 \pm 4 \times 10^{-3}$	$0.0052 \pm 6 \times 10^{-4}$	$0.48 \pm 1 \times 10^{-2}$
SAMS-VAE	$4.5 \pm 7 \times 10^{-3}$	$0.47 \pm 3 \times 10^{-3}$	$0.32 \pm 5 \times 10^{-3}$	$0.43 \pm 1 \times 10^{-2}$	$1.8e - 05 \pm 4 \times 10^{-5}$	$0.48 \pm 1 \times 10^{-3}$
SAMS-VAE (S)	$6.5 \pm 2 \times 10^{0}$	$0.44 \pm 2 \times 10^{-2}$	$1.6 \pm 1 \times 10^{0}$	$0.43 \pm 1 \times 10^{-2}$	$0.0015 \pm 1 \times 10^{-4}$	$0.48 \pm 4 \times 10^{-3}$
Latent	$8.0 \pm 9 \times 10^{-4}$	$0.41 \pm 5 \times 10^{-3}$	$2.6 \pm 2 \times 10^{-3}$	$0.40 \pm 5 \times 10^{-3}$	$0.0010 \pm 5 \times 10^{-4}$	$0.47 \pm 6 \times 10^{-3}$
Decoder	$8.0 \pm 2 \times 10^{-3}$	$\mathbf{0.36 \pm 9 \times 10^{-3}}$	$2.6 \pm 2 \times 10^{-3}$	$\mathbf{0.38 \pm 8 \times 10^{-3}}$	N/A	N/A
Linear	$3.1 \pm 2 \times 10^{-3}$	$0.44 \pm 1 \times 10^{-3}$	$1.3 \pm 2 \times 10^{-3}$	$0.45 \pm 6 \times 10^{-4}$	$0.0033 \pm 2 \times 10^{-4}$	$0.48 \pm 3 \times 10^{-3}$

E. Additional PCA visualization for `Srivatsan20` dataset

Figure 3. Visualization of cells (ground truth and model predictions) in `Srivatsan20` test split. Gray marks all the cells in the test split, used for computing PCA and illustrated as background. Green cells are the ground truth perturbed cells for one condition, repeated in each subplot. From each model, 100 cells are sampled, then projected to the same PCA space. **A**): SB431542 perturbation in k562 cell line; **B**) Obatoclax Mesylate (GX15-070) perturbation in mcf7 cell line.

Figure 4. Visualization of cells (ground truth and model predictions) in `Srivatsan20` test split. Gray marks all the cells in the test split, used for computing PCA and illustrated as background. Green cells are the ground truth perturbed cells for one condition, repeated in each subplot. From each model, 100 cells are sampled, then projected to the same PCA space. **A**): GSK J1 perturbation in k562 cell line; **B**) Tacedinaline (C1994) perturbation in k562 cell line.

F. PCA visualization for `Jiang24` dataset

Figure 5. Visualization of cells (ground truth and model predictions) in `Jiang24` test split. Gray marks all the cells in the test split, used for computing PCA and illustrated as background. Green cells are the ground truth perturbed cells for one condition, repeated in each subplot. From each model, 100 cells are sampled, then projected to the same PCA space. **A**): DR1 perturbation in mcf7 cell line and treated with INS; **B**) ZC3H3 (C1994) perturbation in hap1 cell line and treated with IFNG.

Figure 6. Visualization of cells (ground truth and model predictions) in `Jiang24` test split. Gray marks all the cells in the test split, used for computing PCA and illustrated as background. Green cells are the ground truth perturbed cells for one condition, repeated in each subplot. From each model, 100 cells are sampled, then projected to the same PCA space. **A**): SP1 perturbation in ht29 cell line and treated with INS; **B**) PIK3CA perturbation in k562 cell line and treated with INS.

G. Hyperparameters

Hyperparameters for PRiMeFlow MLP and FM PCA are found through 60-trial HPO sweeps with Optuna (Akiba et al., 2019). All activation functions in our models are `torch.nn.SiLU` (Paszke et al., 2019).

Table 12. Manually selected hyperparameters for PRiMeFlow in `Srivatsan20` dataset.

Hyperparameter	Value	Description
architecture	U-Net	Architecture choice for the velocity field
num_res_blocks	2	Number of residual blocks after each down/upsampling
hidden_dim	256	Base feature dim in U-Net and in input MLPs
dropout	0.1	Dropout rate
channel_mult	[1, 2, 2, 4, 4]	Hidden dim multipliers at each level
conv_resample	True	Learnable up/downsampling
num_heads	8	Number of attention heads
attention_resolutions	[16]	Resolution levels using multihead self-attention
n_layers_gene_expression	2	MLP layers for gene expression input
n_layers_conditions	2	MLP layers for condition input
n_layers_time	2	MLP layers for time input
prob_unconditional	0.2	Probability of dropping out conditions
interpl_type	Linear	Interpolation type in conditional probability path
sigma	0.	Constant noise schedules
learning_rate	5e-5	Learning rate
weight_decay	0.	Weight decay
batch_size	54	Batch size
num_gpus	4	Number of GPUs
grad_clip_threshold	5.0	Gradient clipping threshold
grad_accum_batches	4	Number of gradient accumulation steps

Table 13. Manually selected hyperparameters for PRiMeFlow in `Norman19` dataset.

Hyperparameter	Value	Description
architecture	U-Net	Architecture choice for the velocity field
num_res_blocks	2	Number of residual blocks after each down/upsampling
hidden_dim	256	Base feature dim in U-Net and in input MLPs
dropout	0.1	Dropout rate
channel_mult	[1, 1, 2, 2, 4]	Hidden dim multipliers at each level
conv_resample	True	Learnable up/downsampling
num_heads	8	Number of attention heads
attention_resolutions	[16]	Resolution levels using multihead self-attention
n_layers_gene_expression	2	MLP layers for gene expression input
n_layers_conditions	2	MLP layers for condition input
n_layers_time	2	MLP layers for time input
prob_unconditional	0.2	Probability of dropping out conditions
interpl_type	Linear	Interpolation type in conditional probability path
sigma	0.	Constant noise schedules
learning_rate	5e-5	Learning rate
weight_decay	0.	Weight decay
batch_size	100	Batch size
num_gpus	4	Number of GPUs
grad_clip_threshold	5.0	Gradient clipping threshold
grad_accum_batches	4	Number of gradient accumulation steps

Table 14. Manually selected hyperparameters for PRiMeFlow in `Jiang24` dataset.

Hyperparameter	Value	Description
architecture	U-Net	Architecture choice for the velocity field
num_res_blocks	2	Number of residual blocks after each down/upsampling
hidden_dim	256	Base feature dim in U-Net and in input MLPs
dropout	0.1	Dropout rate
channel_mult	[1, 1, 2, 2, 4]	Hidden dim multipliers at each level
conv_resample	True	Learnable up/downsampling
num_heads	8	Number of attention heads
attention_resolutions	[32]	Resolution levels using multihead self-attention
n_layers_gene_expression	2	MLP layers for gene expression input
n_layers_conditions	2	MLP layers for condition input
n_layers_time	2	MLP layers for time input
prob_unconditional	0.2	Probability of dropping out conditions
interpl_type	Linear	Interpolation type in conditional probability path
sigma	0.	Constant noise schedules
learning_rate	5e-5	Learning rate
weight_decay	0.	Weight decay
batch_size	38	Batch size
num_gpus	4	Number of GPUs
grad_clip_threshold	5.0	Gradient clipping threshold
grad_accum_batches	4	Number of gradient accumulation steps

Table 15. HPO selected hyperparameters for PRiMeFlow MLP in `Srivatsan20` dataset.

Hyperparameter	Value	Description
architecture	MLP	Architecture choice for the velocity field
hidden_dim	3072	Base feature dim in input MLPs and decoding MLP
dropout	0.0	Dropout rate
n_layers_gene_expression	1	MLP layers for gene expression input
n_layers_conditions	1	MLP layers for condition input
n_layers_time	3	MLP layers for time input
n_layers_decoding	2	MLP layers for decoding
prob_unconditional	0.0	Probability of dropping out conditions
interpl_type	Linear	Interpolation type in conditional probability path
sigma	0.01	Constant noise schedules
learning_rate	3.71e-05	Learning rate
weight_decay	4.05e-07	Weight decay
batch_size	512	Batch size
Non HPO hyperparameters		
num_gpus	1	Number of GPUs
grad_clip_threshold	5.0	Gradient clipping threshold
grad_accum_batches	1	Number of gradient accumulation steps

Table 16. HPO selected hyperparameters for PRiMeFlow MLP in `Norman19` dataset.

Hyperparameter	Value	Description
architecture	MLP	Architecture choice for the velocity field
hidden_dim	2048	Base feature dim in input MLPs and decoding MLP
dropout	0.1	Dropout rate
n_layers_gene_expression	2	MLP layers for gene expression input
n_layers_conditions	3	MLP layers for condition input
n_layers_time	5	MLP layers for time input
n_layers_decoding	1	MLP layers for decoding
prob_unconditional	0.1	Probability of dropping out conditions
interpl_type	Trigonometric	Interpolation type in conditional probability path
sigma	0.1	Constant noise schedules
learning_rate	8.56e-06	Learning rate
weight_decay	9.58e-07	Weight decay
batch_size	1024	Batch size
Non HPO hyperparameters		
num_gpus	1	Number of GPUs
grad_clip_threshold	5.0	Gradient clipping threshold
grad_accum_batches	1	Number of gradient accumulation steps

Table 17. HPO selected hyperparameters for PRiMeFlow MLP in `Jiang24` dataset.

Hyperparameter	Value	Description
architecture	MLP	Architecture choice for the velocity field
hidden_dim	3840	Base feature dim in input MLPs and decoding MLP
dropout	0.1	Dropout rate
n_layers_gene_expression	2	MLP layers for gene expression input
n_layers_conditions	2	MLP layers for condition input
n_layers_time	2	MLP layers for time input
n_layers_decoding	4	MLP layers for decoding
prob_unconditional	0.5	Probability of dropping out conditions
interpl_type	Linear	Interpolation type in conditional probability path
sigma	0.1	Constant noise schedules
learning_rate	2.34e-06	Learning rate
weight_decay	3.50e-07	Weight decay
batch_size	512	Batch size
Non HPO hyperparameters		
num_gpus	1	Number of GPUs
grad_clip_threshold	5.0	Gradient clipping threshold
grad_accum_batches	1	Number of gradient accumulation steps

Table 18. HPO selected hyperparameters for FM PCA in `Srivatsan20` dataset.

Hyperparameter	Value	Description
architecture	MLP	Architecture choice for the velocity field
hidden_dim	3072	Base feature dim in input MLPs and decoding MLP
dropout	0.2	Dropout rate
n_layers_gene_expression	2	MLP layers for gene expression input
n_layers_conditions	3	MLP layers for condition input
n_layers_time	4	MLP layers for time input
n_layers_decoding	4	MLP layers for decoding
prob_unconditional	0.4	Probability of dropping out conditions
interpl_type	Trigonometric	Interpolation type in conditional probability path
sigma	0.1	Constant noise schedules
learning_rate	8.18e-05	Learning rate
weight_decay	1.28e-10	Weight decay
batch_size	1024	Batch size
Non HPO hyperparameters		
num_gpus	1	Number of GPUs
grad_clip_threshold	5.0	Gradient clipping threshold
grad_accum_batches	1	Number of gradient accumulation steps

Table 19. HPO selected hyperparameters for FM PCA in `Norman19` dataset.

Hyperparameter	Value	Description
architecture	MLP	Architecture choice for the velocity field
hidden_dim	1792	Base feature dim in input MLPs and decoding MLP
dropout	0.2	Dropout rate
n_layers_gene_expression	4	MLP layers for gene expression input
n_layers_conditions	2	MLP layers for condition input
n_layers_time	2	MLP layers for time input
n_layers_decoding	4	MLP layers for decoding
prob_unconditional	0.4	Probability of dropping out conditions
interpl_type	Trigonometric	Interpolation type in conditional probability path
sigma	0.01	Constant noise schedules
learning_rate	1.73e-04	Learning rate
weight_decay	6.75e-06	Weight decay
batch_size	2048	Batch size
Non HPO hyperparameters		
num_gpus	1	Number of GPUs
grad_clip_threshold	5.0	Gradient clipping threshold
grad_accum_batches	1	Number of gradient accumulation steps

Table 20. HPO selected hyperparameters for FM PCA in `Jiang24` dataset.

Hyperparameter	Value	Description
architecture	MLP	Architecture choice for the velocity field
hidden_dim	3072	Base feature dim in input MLPs and decoding MLP
dropout	0.0	Dropout rate
n_layers_gene_expression	5	MLP layers for gene expression input
n_layers_conditions	3	MLP layers for condition input
n_layers_time	4	MLP layers for time input
n_layers_decoding	5	MLP layers for decoding
prob_unconditional	0.3	Probability of dropping out conditions
interpl_type	Linear	Interpolation type in conditional probability path
sigma	0.01	Constant noise schedules
learning_rate	8.41e-05	Learning rate
weight_decay	1.29e-08	Weight decay
batch_size	2048	Batch size
Non HPO hyperparameters		
num_gpus	1	Number of GPUs
grad_clip_threshold	5.0	Gradient clipping threshold
grad_accum_batches	1	Number of gradient accumulation steps

Table 21. Additional hyperparameters for FM PCA OT in `Srivatsan20` dataset.

num_samples_per_condition	128	Number of cells sampled per condition to compute the mini-batch OT coupling
solver_type	unbalanced	OT solver algorithm
tau_a	1.0	Source marginal constraint weight
tau_b	1.0	Target marginal constraint weight

Table 22. Additional hyperparameters for FM PCA OT in `Norman19` dataset.

num_samples_per_condition	256	Number of cells sampled per condition to compute the mini-batch OT coupling
solver_type	unbalanced	OT solver algorithm
tau_a	1.0	Source marginal constraint weight
tau_b	1.0	Target marginal constraint weight

Table 23. Additional hyperparameters for FM PCA OT in `Jiang24` dataset.

num_samples_per_condition	256	Number of cells sampled per condition to compute the mini-batch OT coupling
solver_type	unbalanced	OT solver algorithm
tau_a	1.0	Source marginal constraint weight
tau_b	1.0	Target marginal constraint weight