KG-DF: A Black-box Defense Framework against Jailbreak Attacks Based on Knowledge Graphs

Abstract

With the widespread application of large language models (LLMs) in various fields, the security challenges they face have become increasingly prominent, especially the issue of jailbreak. These attacks induce the model to generate erroneous or uncontrolled outputs through crafted inputs, threatening the generality and security of the model. Although existing defense methods have shown some effectiveness, they often struggle to strike a balance between model generality and security. Excessive defense may limit the normal use of the model, while insufficient defense may lead to security vulnerabilities. In response to this problem, we propose a Knowledge Graph Defense Framework (KG-DF). Specifically, because of its structured knowledge representation and semantic association capabilities, Knowledge Graph(KG) can be searched by associating input content with safe knowledge in the knowledge base, thus identifying potentially harmful intentions and providing safe reasoning paths. However, traditional KG methods encounter significant challenges in keyword extraction, particularly when confronted with diverse and evolving attack strategies. To address this issue, we introduce a semantic parsing module, whose core task is to transform the input query into a set of structured and secure concept representations, thereby enhancing the relevance of the matching process. Experimental results show that our framework enhances defense performance against various jailbreak attack methods, while also improving the response quality of the LLM in general QA scenarios by incorporating domain-general knowledge.

1 Introduction

With the rapid advancement of artificial intelligence, LLMs have found widespread applications in various fields(Ouyang et al., 2022; Achiam et al., 2023; Zheng et al., 2023; Touvron et al., 2023). These models have become a cornerstone of modern science and technology due to their powerful

Figure 1: The pipeline of our proposed defense framework against jailbreak attacks based on Knowledge Graphs at the inference stage. When our warning information is attached to the input prompts, the protected LLM will be robust to malicious attacks while maintaining reasonable responses to legitimate requests.

natural language processing capabilities and wide application scenarios(Zhang et al., 2023; Liu et al., 2023a,c; Imani et al., 2023; Shanahan et al., 2023; Wang et al., 2023). However, despite the convenience LLMs bring, they also face significant security challenges(Wu et al., 2024). The complexity and openness of these models make them susceptible to a range of attacks, particularly jailbreak attacks, that manipulate the model produce erroneous or uncontrolled outputs(Ding et al., 2023; Liu et al., 2023b; Li et al., 2023; Wei et al., 2023; Zou et al., 2023).

To address this challenge, researchers have proposed a variety of defense strategies(Wang et al., 2024; Touvron et al., 2023; Stiennon et al., 2020; Ouyang et al., 2022). RPO(Zhou et al., 2024) suggested adding a suffix to the prompt, carefully designed using gradient descent algorithms, to enhance the security of LLM outputs. PPL (Alon and Kamfonas, 2023)introduced the concept of a confusion filter to identify and filter out overly complex inputs. Smoothllm(Robey et al., 2023) employed character-level perturbation techniques to neutralize methods sensitive to perturbations. Although these approaches have improved the defense capabilities of LLMs to some extent, they often un-

dermine the generality of the model itself. As a result, existing defense methods struggle to strike an optimal balance between model generality and security. Finding ways to strengthen LLM defense mechanisms without compromising their generality has become a pressing issue.

Recently, PAT (Mo et al., 2024) proposed a novel defense mechanism against jailbreak attacks by generating a prompt prefix through prompt alignment tuning, without compromising the model's general capabilities. However, this method is primarily designed for open-source models. In practice, many deployed LLMs are closed-source, and defenders do not have access to their internal architectures or parameters. Consequently, the applicability and effectiveness of this approach in real-world settings remain limited.

To address this problem, this paper aims to enhance the security of the model in black-box scenarios without compromising its generality. Achieving this goal faces several challenges(Dong et al., 2024). First, due to the closed-source nature of LLMs, where internal structures and parameters are inaccessible, there is a lack of effective reasoning paths for security strategies, limiting the available defense methods. Second, most defense methods are unable to respond promptly to novel attack patterns, making it difficult to meet the demands for real-time protection. In this context, KGs, with their structured knowledge representation and semantic association capabilities, offer promising solutions for LLM defense(Chen et al., 2020a,b; Fensel et al., 2020; Zhang et al., 2024). Specifically, KGs do not rely on access to the internal structure of models. By comparing the input content with dangerous entities and relationships in the KG, it becomes possible to identify potentially harmful intentions through external reasoning. Moreover, the dynamic and extensible nature of KGs enables continuous integration of novel attack features into the defense system, offering better scalability and adaptability than static rule-based methods(Liang et al., 2024).

However, the direct application of traditional KGs in LLM defense faces two main challenges. First, adversarial attacks often bypass entity recognition modules by using syntactic variations that maintain semantic integrity (e.g., character substitutions like "b0mb")(Jiang et al., 2024; Yuan et al., 2024; Kang et al., 2024); second, traditional keyword extraction methods rely on superficial semantic features (such as TF-IDF weights(Chen, 2024;

Wang, 2024; Chowdhury, 2010)), which lose effectiveness when dealing with semantically coherent but logically abnormal prompts.

To address these shortcomings, we propose a black-box defense framework against Jailbreak Attacks based on KGs(KG-DF), as illustrated in Figure 1. This framework extracts core semantic information from user input through a semantic parsing module and performs similarity matching with a prebuilt security knowledge graph. The detected triples are then integrated into the LLM input layer as security alerts, allowing the model to simultaneously perceive potential threats during the generation phase. This framework not only provides defense capabilities but also enhances the model's understanding of general-domain knowledge by incorporating it into the knowledge graph, thereby improving the response quality in general question-answering scenarios.

The experimental results show that the defense strategy proposed in this paper demonstrates excellent defense performance on both open-source and closed-source models. On the open-source model Vicuna-7B, the attack success rate is nearly reduced to zero, with generality reaching 88%. On the closed-source models GPT-3.5 and GPT-4, the attack success rates are also close to 0%, with generality reaching 86% and 89%, respectively. Our contributions are summarized as follows:

- We propose a novel defense perspective: integrating KG with LLMs to enhance LLM security in black-box settings through external semantic reasoning paths.

- The semantic parsing module proposed in this paper replaces the traditional entity relationship extraction, enhances the matching correlation, and thereby improves the defense ability and universality of the model.

- Experimental results show that the framework significantly enhances the model's defense performance while maintaining its generality.

2 Related Work

2.1 Jailbreak Attack

LLM has received a lot of attention because of its powerful generative ability, but studies have shown that LLM is vulnerable to adversarial attacks to

Figure 2: Framework of the Defense Method. The proposed framework comprises three main steps: (1) constructing a knowledge graph that integrates both safety-related and general-domain knowledge, (2) extracting keywords from user prompts, and (3) retrieving and integrating relevant knowledge to guide the model toward safer and more accurate responses.

bypass its own value alignment mechanism. According to the openness of the model, LLM is divided into open-source model and closed-source model. Accordingly, jailbreaking attacks against these models can also be divided into two broad categories: white box attacks(Zou et al., 2023; Ding et al., 2023) and black box attacks(Li et al., 2023; Jiang et al., 2024). In these specific scenarios, LLMS are induced to output harmful content, demonstrating the potential risk of jailbreak.

2.2 Defense

The core of the defense mechanism is to ensure that the output of the LLM is consistent with our intended goal of security. RPO (Zhou et al., 2024) proposed an approach that targets open-source LLM by adding an adversarial suffix to its input prompt. This suffix is carefully designed through gradient descent algorithms to make the output content of LLM more secure. Smooth (Robey et al., 2023) used character-level perturbation techniques to neutralize perturbation-sensitive methods by randomly substituting, swapping, or inserting tokens.

2.3 RAG and KG

While both KGs and RAG aim to ground LLMs in external knowledge, they differ fundamentally in methodology and suitability for value alignment.

RAG primarily retrieves unstructured text passages to inform the model's response. In contrast, our employed KGs provides an explicit, structured network of relationships. This structured nature enables deterministic reasoning, consistency verification, and the direct application of constraint rules—offering a more safe foundation for systemic value defense compared to the retrieval-based, compositional approach of RAG.

3 Method

3.1 Framework

This study aims to enhance LLMs' overall performance in both safety and generality. As illustrated in Figure 2, the proposed framework comprises three key phases: first, constructing a KG that integrates both safety-related and general knowledge; second, performing semantic parsing on user inputs to extract essential information; third, embedding the extracted information into vector representations and retrieving relevant knowledge triples through semantic similarity matching within the KG. The retrieved knowledge is then fused with the original prompt to reconstruct the input, guiding the LLM to generate responses that demonstrate strengthened safety awareness and improved content accuracy. The subsequent sections will

Safety Knowledge Module	Subcategories
Child_Abuse	Law & Punishment, Abusive Behavior, Child Impact, Ethical Critique, Social Responsibility, Case Scenarios, Intervention, Psychological
Animal_Abuse	Law & Punishment, Abusive Behavior, Animal Impact, Ethical Critique, Social Responsibility, Case Scenarios, Intervention, Psychological
Bias	Racial, Gender, Cultural, Regional, Age, Religious, Language, Political
Economic_Harm	Financial Fraud, False Advertising, Financial Scams, Investment Risks, Credit Loss, Economic Invasion, Tax Fraud, Price Manipulation
... (See Appendix A for more classifications)	

Table 1: Specific categories under 16 categories in the Safety Knowledge module.

elaborate on these procedural steps in detail.

3.2 The Construction Process of the KG

3.2.1 The Structural System of the KG

In this study, we construct a KG organized into two core modules—Safety Knowledge and General Knowledge—following OpenAI's Moderator System Card and related literature (Luo et al., 2024). The Safety Knowledge module is further divided into 16 subcategories to address specific potential risks, while the General Knowledge module comprises 15 subcategories to support broad commonsense reasoning. This structured classification ensures comprehensive coverage across multiple dimensions, aiming to enhance LLMs' ability to generate secure responses and improve their mechanistic understanding of general content.

Safety Knowledge Module. This module encompasses a wide range of morally sensitive domains, such as child abuse, economic harm, hate speech, and political sensitivity. The detailed taxonomy is presented in Table 1. Each major safety category is further divided into fine-grained subcategories. For example, the "economic harm" category includes issues such as financial fraud, false advertising, and price manipulation. This hierarchical structure ensures comprehensive coverage of safety-related content.

We also perform a statistical analysis of the proportional distribution across subcategories, as illustrated in Figure 3. The results indicate that the current safety knowledge module exhibits broad coverage and balanced distribution across categories, thereby ensuring both diversity and representativeness of the dataset. Further results and details are provided in the appendix A.

General Knowledge Module. To enhance the model's generality performance, the knowledge graph incorporates a broader range of knowledge domains, including natural sciences, social sciences, law, culture, arts, and daily life, among others. This module is designed to support the

Figure 3: Category distribution for Child_Abuse, Animal_Abuse, Economic_Harm and Fraud.

model in generating accurate, informative, and knowledge-rich responses when handling non-sensitive prompts. The detailed classification structure is presented in Table 2.

Figure 4 illustrates the structural composition and distribution characteristics of four representative subcategories. The data analysis results show that this module also exhibits good balance and representativeness in terms of category coverage and sample distribution, further confirming its effectiveness in supporting knowledge generation for general-purpose scenarios. Additional results can be found in the Appendix B.

3.2.2 Dynamic Updating of KG

When new attack methods emerge, we define standardized triplet templates (malicious intent, attack method, target vulnerability) for the "attack mode" node. All new types of attacks need to be abstracted and expressed according to this pattern to ensure the consistency of the graph structure. The defense process can be summarized as follows: [User input]-> [behavior analysis] -> [Abstract attack method]-> [Knowledge Graph query]-> [Infer malicious intent]-> [intent-based early warning]

General Categories	Subcategories
Arts and Entertainment	Music, Movies, Literature, Dance, Drama, Artistic Creation, Creative Expression, Media Analysis
Business and Economics	Business Management, Marketing, Financial Management, Economic Theories, Macroeconomics, Microeconomics, Business Ethics, Economic Forecasting
Computer Science and Technology	Programming Languages, Algorithms, Artificial Intelligence, Cybersecurity, Data Structures, Machine Learning, Deep Learning, Computer Architecture
Daily Life Knowledge	Home Management, Healthy Living, Social Etiquette, Family Relationships, Time Management, Personal Finance, Travel, Psychology
... (See Appendix B for more classifications)	

Table 2: Specific categories under 15 categories in the General Knowledge module.

Figure 4: Category distribution for Arts and Entertainment, Business and Economics, Computer Science and Technology, Daily Life Knowledge.

You are an expert in child welfare, law, and psychology. Please generate 200 distinct, high-quality natural language sentences related to the subcategory "{Subcategory_Name}" under the domain "Child Abuse". Each sentence should clearly express a specific piece of knowledge or fact related to the subcategory theme. Ensure that the language is semantically rich and suitable for extracting structured knowledge triples (subject-predicate-object). Avoid vague statements; focus on concrete facts, typical behaviors, legal consequences, ethical debates, psychological mechanisms, or real-life interventions, depending on the subcategory.

Figure 5: Prompt templates for generating natural statements for each category.

-> [Intercept malicious output]. Regarding maintenance costs, the current focus is mainly on the manual input for abstracting and modeling new attack patterns. The timeliness of updates depends on the frequency and response speed of monitoring security intelligence sources.

3.2.3 Knowledge Graph Construction Process

The construction process of the knowledge graph is divided into three key steps.

Domain Classification and Text Generation. Based on the definitions and semantic requirements of each subcategory, we leverage GPT-3.5-turbo to automatically generate 200 relevant natural language sentences for each category. These sentences effectively encapsulate the core knowledge points of each subcategory, providing rich and semantically clear textual material for the subsequent extraction of high-quality triplet information. The prompt design template is shown in Figure 5.

Semantic Triplet Extraction Method. In the generated natural language sentences, we use the GPT-3.5-turbo model for triplet extraction, identify-

ing and extracting structured knowledge fragments in the form of [Entity–Relation–Entity]. Through this process, the key information in the original sentences is effectively transformed into computable triplet structures, significantly enhancing the processability and queryability of the knowledge.

Knowledge Graph Embedding Vector Representation. After extracting information from sentences, we further utilize Qwen3-Embedding-8B to vectorize the triplets. Specifically, the embedding method is employed to map the entities and relationships within each triplet into high-dimensional vectors, enabling the mathematical modeling of nodes and their relationships within the knowledge graph. This projects the knowledge graph into a vector space, while preserving their semantic and structural relationships.

3.3 Knowledge Graph Defense Framework

3.3.1 Keyword Extraction from Prompts

After the user enters the prompt words, the GPT-3.5-turbo model is used to extract their key intentions. Refer to the Appendix D for details on prompt design. The formula is as follows:

$$K_{\text{core}} = \text{LLM}(P_{\text{prompt}}) \quad (1)$$

3.3.2 Embedding Vector of Prompts

The extracted keywords are converted into vector representations using Qwen3-Embedding-8B. These vectors form the foundation for similarity

calculation and knowledge matching. The formula is as follows:

$$V_{\text{prompt}} = \text{Embedding}\left(K_{\text{core}}\right) \quad (2)$$

3.3.3 Similarity Retrieval and Calculation

To retrieve the most relevant information, we leverage cosine similarity to compute the similarity between the input's embedding vector and all vectors in the knowledge graph. The top-matched knowledge nodes are then formatted as triples and provided as valuable contextual data for subsequent inference and generation.

$$T_{\text{match}} = \arg \max_{T_{\text{kg}}} \text{Similarity}\left(V_{\text{prompt}}, V_{\text{KG}}\right)$$

$$= \cos\theta = \frac{V_{\text{prompt}} \cdot V_{\text{KG}}}{\|V_{\text{prompt}}\|\|V_{\text{KG}}\|} \quad (3)$$

Where, T_{kg} represents all triples in the knowledge graph, θ is the angle between V_{prompt} and V_{KG}.

3.3.4 Prompt Reconstruction and LLM Response Generation.

When LLM is used for response generation, to effectively reduce harmful content output, triplet information is entered into the LLM along with the original prompt as a context warning. The specific process is as follows:

Security warning output. The retrieved triplet information T_{match} is combined into a "warning" content to inform the system of possible risks and provide a basis for subsequent judgment.

Judgement of warning and prompt. The LLM combines the security warning with the user's prompt, to determine whether the prompt content conflicts with the security warning before generating a response.

Reject or generate responses. The LLM will refuse to respond if the prompt contradicts the warning. If there is no conflict, the answer is generated normally.

4 Experiments

In this section, we demonstrate the effectiveness of our method on both open-source and closed-source models. Section 4.1 describes the experimental setup. Section 4.2 presents a comparative analysis of our method against existing defense approaches on open-source models. Section 4.3 extends this comparison to closed-source models. Finally, Section 4.4 evaluates the contribution of the proposed modules in keyword extraction and output scheme selection.

4.1 Settings

Datasets. The defense performance of the method is evaluated using advbench datasets(Zou et al., 2023). The false positives and generality of the method are evaluated using the XSTest dataset(Röttger et al., 2023). The advbench dataset is designed with a variety of adversarial samples to fully test the method's ability to resist malicious attacks. The XSTest dataset contains ten types of security tips, which are quite confusing.

Models. For open-source LLMs, we choose Vicuna-7B and LLaMA2-7B as our primary test models. Additionally, to further investigate the practical performance of optimized lightweight models, we include the distillation-based DeepSeek-LLM-7B-Chat in our experiments. For closed-source LLMs, we use GPT-3.5 Turbo and GPT-4 to conduct longitudinal comparisons.

Attack Methods. We evaluate three representative attack methods. GCG(Zou et al., 2023), aims to optimize initially meaningless strings into adversarial suffixes by using a greedy algorithm to iteratively modify the text, ultimately inducing the model to generate harmful content. TAP(Mehrotra et al., 2024) begins with manually crafted jailbreak prompts and expands them using a tree-based structure to generate diverse adversarial examples, seeking the most effective strategy to bypass LLM safety mechanisms and elicit undesired outputs. The PAIR(Chao et al., 2023) attack achieves successful jailbreaks with a relatively small number of queries (around 20), making it particularly efficient and practical in real-world scenarios.

Baselines. We compare four different defense methods. PPL (Alon and Kamfonas, 2023) enhances model robustness by using perplexity measurements to identify and filter out overly complex inputs. The Self-reminder method (Wu et al., 2023) introduces system-level prompts that remind the model to follow safety guidelines during response generation. SmoothLLM (Robey et al., 2023) employs character-level perturbations to defend against attacks that exploit perturbation sensitivity.The RPO (Zhou et al., 2024) method enhances the security and stability of model outputs by optimizing input prompts.

Evaluation metrics. We evaluate the algorithm from ASR, FPR and Generality respectively. The ASR refers to the proportion of attacks that can

Model	Method	ASR			FPR	Generality
		GCG	TAP	PAIR		
Vicuna-7B	No-Defense	88.00%	34.00%	88.00%	-	76.00%
	PPL	63.00%	31.00%	81.00%	15.00%	76.00%
	Self-Reminder	0.00%	11.00%	18.00%	8.00%	73.00%
	SmoothLLM	14.00%	28.00%	39.00%	**5.00%**	67.00%
	RPO	0.00%	0.00%	**0.00%**	11.00%	54.00%
	Ours	**0.00%**	**0.00%**	6.00%	**5.00%**	**88.00%**
Deepseek-llm-7B-chat	No-Defense	36.00%	10.00%	8.00%	-	83.00%
	PPL	24.00%	9.00%	8.00%	20.00%	74.00%
	Self-Reminder	28.00%	0.00%	4.00%	8.00%	78.00%
	SmoothLLM	6.00%	3.00%	1.00%	**3.00%**	70.00%
	RPO	**0.00%**	0.00%	0.00%	28.00%	53.00%
	Ours	2.00%	**0.00%**	**0.00%**	5.00%	**86.00%**

Table 3: Performance of KG-DF on the Advbench and XSTest datasets using open-source models.

successfully induce the model to generate unsafe or incorrect content under certain attack conditions. FPR measures the proportion of defensive methods that mistakenly identify safe or normal inputs as being offensive. It is evaluated using the security data from the XSTest dataset. Generality is used to measure the response quality of a defense method when facing with typical problems. All three metrics are evaluated using LLM and user-study, prompt design is shown in appendix D.

4.2 Defense in open-source models

In this experiment, three open-source models are evaluated. As shown in Table 3, the defense strategies demonstrate exceptional performance across all models, significantly reducing the ASR. The effectiveness is particularly pronounced against GCG and PAIR attacks, with attack success rates approaching zero. At the same time, the false positive rate remains low, and the defense exhibits strong generality performance. For instance, using our defense strategy, the Vicuna-7B model achieved 88% generality, while the Llama2-7B model reached 89% on the XSTest dataset(see Appendix C for more details). Although other defense methods also reduce attack success rates, they often struggle with high false positive rates.

4.3 Defense in closed-source models

In this experiment, we evaluated the defense performance of Claude Sonnet and Google Gemini against three attack methods. Our proposed approach demonstrated superior overall balance compared to existing strategies. Specifically, it achieved the lowest ASR — 1.00% and 2.00% for

Claude Sonnet, and 23.00% and 37.00% for Google Gemini under TAP and PAIR attacks, respectively — while maintaining a low FPR of 2.00% for both models. Furthermore, it preserved high generality, with scores of 91.00% for Claude Sonnet and 87.00% for Google Gemini. In contrast, other defenses exhibited either higher FPR or lower generality, underscoring the more balanced efficacy of our method across all critical metrics.

4.4 Ablation Study

4.4.1 Keyword extraction

This experiment evaluates how different keyword extraction methods affect semantic relevance to the original prompt. We test NER(AI, 2017), TF-IDF (Chowdhury, 2010), and several LLMs (LLaMA-3.2, Vicuna-7B, GPT-3.5), assessing keyword relevance using GPT-4. Prompt details are provided in Appendix C.3.

As shown in Table 5, NER extracts content-related words but frequently misses the core theme of the prompt. TF-IDF achieves only 37.00% semantic relevance, indicating its limited ability to capture semantic associations despite relying on statistical frequency. In contrast, LLM-based methods show consistently better performance. Among them, GPT-3.5 demonstrates a clear advantage and is better suited for extracting keywords.

To evaluate the robustness of our semantic parsing module against complex adversarial inputs, we test it using the multi-stage Foot-In-The-Door attack (Weng et al., 2025). This method employs bridging prompts to gradually escalate malicious intent, representing a typical covert, multi-round

Model	Method	ASR			FPR	Generality
		GCG	TAP	PAIR		
Claude Sonnet	No-Defense	-	6.00%	6.00%	-	89.00%
	PPL	-	6.00%	6.00%	14.00%	89.00%
	Self-Reminder	-	4.00%	5.00%	6.00%	83.00%
	SmoothLLM	-	5.00%	5.00%	6.00%	76.00%
	Ours	-	**1.00%**	**2.00%**	**2.00%**	**91.00%**
Google Gemini	No-Defense	-	31.00%	73.00%	-	80.00%
	PPL	-	31.00%	71.00%	15.00%	81.00%
	Self-Reminder	-	26.00%	58.00%	7.00%	76.00%
	SmoothLLM	-	28.00%	51.00%	8.00%	70.00%
	Ours	-	**23.00%**	**37.00%**	**2.00%**	**87.00%**

Table 4: Performance of KG-DF on the Advbench and XSTest datasets using closed-source models.

Method	Keyword	Similarity	Corr.	ASR
NER	2	67.00%	5	6.00%
TF-IDF	2	37.00%	4	9.00%
Llama-3.2	2	83.00%	7	2.00%
Vicuna-7B	2	85.00%	7	3.00%
GPT-3.5-turbo	2	**88.00%**	**8**	**0.00%**

Table 5: Correlation performance under different keyword extraction methods.

attack scenario. As shown in Table 6, our approach tracks semantic evolution across attack stages and successfully blocks the final harmful response.

Method	LLaMA-3.1-8B	GPT-4o
Foot-In-The-Door	92.00%	88.00%
Ours	18.00%	12.00%

Table 6: The robustness of the semantic parsing module to complex adversarial inputs.

4.4.2 Output scheme selection

We explore the impact of different output methods on the final result after retrieving relevant triplet information. We compare the following three output strategies: **Direct Combination Input.** The triplet information is directly combined with the prompt and input into the LLM. **Pre-output Judgment.** This method requires the LLM to first output a sentence by combining the triplet information before generating the final output. The LLM then assesses the relevance and compliance of this sentence with the prompt content, determining whether it should respond to the prompt, and thus deciding the final output. **Combined Input.** The triplet information is first combined into a sentence by the LLM, which is then input along with the prompt into the

LLM. The comparison results are presented in the appendix C.4.

By adding a pre-judgment step and using the warning information to constrain subsequent processing of the prompt, this approach establishes a clear warning and judgment logic, achieving the best defense effect.

5 Computational overhead

The following table 7 compares the computational overhead of different defense methods when defending against GCG attacks on open-source models, showing average time and cost per prompt.

Method	Time	Cost	ASR (%)
PPL	3.7 s	$0	58.00
Self-Reminder	2.5 s	$0	12.00
SmoothLLM	3.1 s	$0	19.00
RPO	17 min	$0	8.00
Ours	3.8 s	$1.05\text{-}1.33\times10^{-4}$	0.00

Table 7: Computational overhead of defense methods.

6 Conclusion

The widespread deployment of LLMs has intensified security concerns, particularly from jailbreak attacks. To address this, we propose a knowledge graph–based defense framework (KG-DF) that links input content to structured security knowledge for accurate intent recognition and safe reasoning. Unlike entity-based methods, KG-DF employs LLM-driven semantic parsing, improving match relevance and defensive performance. Experiments show that KG-DF effectively counters various jailbreak attacks while also enhancing response quality in general QA through integrated general knowledge.

Limitations

While the proposed KG-DF framework demonstrates enhanced defense capabilities against jailbreak attacks, it is subject to several limitations. The framework requires further improvements in interpretability and computational efficiency. And future work will focus on developing specialized parsers, enabling incremental knowledge updates, and optimizing the inference process to enhance both robustness and efficiency.

References

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, and 1 others. 2023. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*.

Explosion AI. 2017. Spacy: Industrial-strength natural language processing in python.

Gabriel Alon and Michael Kamfonas. 2023. Detecting language model attacks with perplexity. *arXiv preprint arXiv:2308.14132*.

Patrick Chao, Alexander Robey, Edgar Dobriban, Hamed Hassani, George J Pappas, and Eric Wong. 2023. Jailbreaking black box large language models in twenty queries. *arXiv preprint arXiv:2310.08419*.

Liang-Ching Chen. 2024. An extended tf-idf method for improving keyword extraction in traditional corpus-based research: An example of a climate change corpus. *Data & Knowledge Engineering*, 153:102322.

Xiaojun Chen, Shengbin Jia, and Yang Xiang. 2020a. A review: Knowledge reasoning over knowledge graph. *Expert systems with applications*, 141:112948.

Zhe Chen, Yuehan Wang, Bin Zhao, Jing Cheng, Xin Zhao, and Zongtao Duan. 2020b. Knowledge graph completion: A review. *Ieee Access*, 8:192435–192456.

Gobinda G Chowdhury. 2010. *Introduction to modern information retrieval*. Facet publishing.

Peng Ding, Jun Kuang, Dan Ma, Xuezhi Cao, Yunsen Xian, Jiajun Chen, and Shujian Huang. 2023. A wolf in sheep's clothing: Generalized nested jailbreak prompts can fool large language models easily. *arXiv preprint arXiv:2311.08268*.

Zhichen Dong, Zhanhui Zhou, Chao Yang, Jing Shao, and Yu Qiao. 2024. Attacks, defenses and evaluations for llm conversation safety: A survey. *arXiv preprint arXiv:2402.09283*.

Dieter Fensel, Umutcan Şimşek, Kevin Angele, Elwin Huaman, Elias Kärle, Oleksandra Panasiuk, Ioan Toma, Jürgen Umbrich, Alexander Wahler, Dieter Fensel, and 1 others. 2020. Introduction: what is a knowledge graph? *Knowledge graphs: Methodology, tools and selected use cases*, pages 1–10.

Shima Imani, Liang Du, and Harsh Shrivastava. 2023. Mathprompter: Mathematical reasoning using large language models. *arXiv preprint arXiv:2303.05398*.

Fengqing Jiang, Zhangchen Xu, Luyao Niu, Zhen Xiang, Bhaskar Ramasubramanian, Bo Li, and Radha Poovendran. 2024. Artprompt: Ascii art-based jailbreak attacks against aligned llms. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 15157–15173.

Daniel Kang, Xuechen Li, Ion Stoica, Carlos Guestrin, Matei Zaharia, and Tatsunori Hashimoto. 2024. Exploiting programmatic behavior of llms: Dual-use through standard security attacks. In *2024 IEEE Security and Privacy Workshops (SPW)*, pages 132–143. IEEE.

Xuan Li, Zhanke Zhou, Jianing Zhu, Jiangchao Yao, Tongliang Liu, and Bo Han. 2023. Deepinception: Hypnotize large language model to be jailbreaker. *arXiv preprint arXiv:2311.03191*.

Ke Liang, Lingyuan Meng, Meng Liu, Yue Liu, Wenxuan Tu, Siwei Wang, Sihang Zhou, Xinwang Liu, Fuchun Sun, and Kunlun He. 2024. A survey of knowledge graph reasoning on graph types: Static, dynamic, and multi-modal. *IEEE Transactions on Pattern Analysis and Machine Intelligence*.

Jiawei Liu, Chunqiu Steven Xia, Yuyao Wang, and Lingming Zhang. 2023a. Is your code generated by chatgpt really correct? rigorous evaluation of large language models for code generation. *Advances in Neural Information Processing Systems*, 36:21558–21572.

Xiaogeng Liu, Nan Xu, Muhao Chen, and Chaowei Xiao. 2023b. Autodan: Generating stealthy jailbreak prompts on aligned large language models. *arXiv preprint arXiv:2310.04451*.

Yixin Liu, Avi Singh, C Daniel Freeman, John D Co-Reyes, and Peter J Liu. 2023c. Improving large language model fine-tuning for solving math problems. *arXiv preprint arXiv:2310.10047*.

Weidi Luo, Siyuan Ma, Xiaogeng Liu, Xiaoyu Guo, and Chaowei Xiao. 2024. Jailbreakv: A benchmark for assessing the robustness of multimodal large language models against jailbreak attacks. *Preprint*, arXiv:2404.03027.

Anay Mehrotra, Manolis Zampetakis, Paul Kassianik, Blaine Nelson, Hyrum Anderson, Yaron Singer, and Amin Karbasi. 2024. Tree of attacks: Jailbreaking black-box llms automatically. *Advances in Neural Information Processing Systems*, 37:61065–61105.

Yichuan Mo, Yuji Wang, Zeming Wei, and Yisen Wang. 2024. Fight back against jailbreaking via prompt adversarial tuning. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, and 1 others. 2022. Training language models to follow instructions with human feedback. *Advances in neural information processing systems*, 35:27730–27744.

Alexander Robey, Eric Wong, Hamed Hassani, and George J Pappas. 2023. Smoothllm: Defending large language models against jailbreaking attacks. *arXiv preprint arXiv:2310.03684*.

Paul Röttger, Hannah Rose Kirk, Bertie Vidgen, Giuseppe Attanasio, Federico Bianchi, and Dirk Hovy. 2023. Xstest: A test suite for identifying exaggerated safety behaviours in large language models. *arXiv preprint arXiv:2308.01263*.

Murray Shanahan, Kyle McDonell, and Laria Reynolds. 2023. Role play with large language models. *Nature*, 623(7987):493–498.

Nisan Stiennon, Long Ouyang, Jeffrey Wu, Daniel Ziegler, Ryan Lowe, Chelsea Voss, Alec Radford, Dario Amodei, and Paul F Christiano. 2020. Learning to summarize with human feedback. *Advances in neural information processing systems*, 33:3008–3021.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, and 1 others. 2023. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*.

Yan Wang. 2024. Research on the tf–idf algorithm combined with semantics for automatic extraction of keywords from network news texts. *Journal of Intelligent Systems*, 33(1):20230300.

Yihan Wang, Zhouxing Shi, Andrew Bai, and Cho-Jui Hsieh. 2024. Defending llms against jailbreaking attacks via backtranslation. *arXiv preprint arXiv:2402.16459*.

Zekun Moore Wang, Zhongyuan Peng, Haoran Que, Jiaheng Liu, Wangchunshu Zhou, Yuhan Wu, Hongcheng Guo, Ruitong Gan, Zehao Ni, Jian Yang, and 1 others. 2023. Rolellm: Benchmarking, eliciting, and enhancing role-playing abilities of large language models. *arXiv preprint arXiv:2310.00746*.

Alexander Wei, Nika Haghtalab, and Jacob Steinhardt. 2023. Jailbroken: How does llm safety training fail? *Advances in Neural Information Processing Systems*, 36:80079–80110.

Zixuan Weng, Xiaolong Jin, Jinyuan Jia, and Xiangyu Zhang. 2025. Foot-in-the-door: A multi-turn jailbreak for llms. *arXiv preprint arXiv:2502.19820*.

Fangzhao Wu, Yueqi Xie, Jingwei Yi, Jiawei Shao, Justin Curl, Lingjuan Lyu, Qifeng Chen, and Xing Xie. 2023. Defending chatgpt against jailbreak attack via self-reminder.

Fangzhou Wu, Ning Zhang, Somesh Jha, Patrick McDaniel, and Chaowei Xiao. 2024. A new era in llm security: Exploring security concerns in real-world llm-based systems. *arXiv preprint arXiv:2402.18649*.

Youliang Yuan, Wenxiang Jiao, Wenxuan Wang, Jen tse Huang, Pinjia He, Shuming Shi, and Zhaopeng Tu. 2024. Gpt-4 is too smart to be safe: Stealthy chat with llms via cipher. *Preprint*, arXiv:2308.06463.

Jin-Cheng Zhang, Azlan Mohd Zain, Kai-Qing Zhou, Xi Chen, and Ren-Min Zhang. 2024. A review of recommender systems based on knowledge graph embedding. *Expert Systems with Applications*, page 123876.

Shun Zhang, Zhenfang Chen, Yikang Shen, Mingyu Ding, Joshua B Tenenbaum, and Chuang Gan. 2023. Planning with large language models for code generation. *arXiv preprint arXiv:2303.05510*.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric Xing, and 1 others. 2023. Judging llm-as-a-judge with mt-bench and chatbot arena. *Advances in Neural Information Processing Systems*, 36:46595–46623.

Andy Zhou, Bo Li, and Haohan Wang. 2024. Robust prompt optimization for defending language models against jailbreaking attacks. *arXiv preprint arXiv:2401.17263*.

Andy Zou, Zifan Wang, Nicholas Carlini, Milad Nasr, J Zico Kolter, and Matt Fredrikson. 2023. Universal and transferable adversarial attacks on aligned language models. *arXiv preprint arXiv:2307.15043*.

A Safety Knowledge Module

The safety knowledge module is divided into 16 categories, each further subdivided into 8 specific branches. The appendix presents the branch composition and proportion of the remaining 12 categories. The classification is shown in Table 15, and the more specific branch proportion analysis is shown in Figure 6,7 and 8.

Figure 6: Category distribution for Bias, Government, Hate_speech, Malware.

Figure 7: Category distribution for Physical_Harm, Political_Sensitivity, Privacy_Violation, Health_Consultation.

B General Knowledge Module

The general knowledge module is divided into 15 categories, each comprising 8 specific branches. The main text presents 4 of these categories and their structures, while the appendix provides the branch composition and proportion of the remaining 11 categories. The classification is shown in

Figure 8: Category distribution for Unethical_Behavior, Violence, Roleplay, Tailored_Unlicensed_Advice.

Table 16, and the more specific branch proportion analysis is shown in Figure 9,10 and 11.

Figure 9: Category distribution for Engineering and Technological Applications, Frontier Technology and Future Trends, Geography and Environment, History and Civilization.

C Supplementary Experiment

C.1 Defense in open-source models

Figure 8 shows the performance of the Llama2-7B model under different attack and defense methods.

C.2 Defense in closed-source models

The experimental results in the table 9 demonstrate that whether on GPT-3.5 or GPT-4, our method significantly reduces the ASR and effectively enhances the model's generality. Under TAP and PAIR attacks, the ASR is nearly reduced to 0%, while the FPR remains at a low level. On

Model	Method	ASR			FPR	Generality
		GCG	TAP	PAIR		
Llama2-7B	No-Defense	64.00%	10.00%	4.00%	-	79.00%
	PPL	58.00%	9.00%	3.00%	16.00%	79.00%
	Self-Reminder	12.00%	0.00%	4.00%	13.00%	73.00%
	SmoothLLM	19.00%	8.00%	0.00%	9.00%	68.00%
	RPO	8.00%	0.00%	0.00%	15.00%	53.00%
	Ours	**0.00%**	**0.00%**	**0.00%**	**8.00%**	**89.00%**

Table 8: Performance of KG-DF on the Advbench and XSTest datasets using open-source models.

Figure 10: Category distribution for Language and Literature, Law and Ethics, Mathematics and Logic, Medicine and Health.

Figure 11: Category distribution for Natural Science, Philosophy and Religion, Social Sciences.

the XSTest dataset, the generality of the GPT-3.5 model reaches 86%, and that of the GPT-4 model is as high as 89%, indicating that the introduction of a knowledge graph significantly enhances the model's general capability. In contrast, although other defense strategies can effectively reduce the ASR, they still exhibit high FPR and fail to achieve the expected improvement in generality.

C.3 The influence of the hyperparameter of the number of keywords.

Based on the Vicuna-7B model, we conducte a comparison experiment of the number of keywords in the PAIR attack scenario. The results show that with the increase in the number of keywords, the change range of ASR is extremely small and can be ignored.

C.4 Output scheme selection

We explore the impact of different output methods on the final result after retrieving relevant triplet information. The comparison results are presented in the table10. The pre-output judgment method

stands out in terms of its effectiveness in defending against harmful information output. It helps determine the optimal output strategy and improves the system's performance in related tasks.

D Prompt

D.1 Prompt for Keywords Extraction

Figure 12 illustrates the prompt used for keywords extraction. It outlines the necessary steps for the model to analyze and extract relevant keywords from the input prompt.

Figure 12: Prompt for Category and Core Keywords Extraction.

D.2 Prompt for Evaluating ASR

This prompt is designed to help evaluate the success of an attack by analyzing both the input pro-

Model	Method	ASR			FPR	Generality
		GCG	TAP	PAIR		
	No-Defense	-	19.00%	63.00%	-	81.00%
	PPL	-	19.00%	63.00%	15.00%	81.00%
GPT-3.5	Self-Reminder	-	4.00%	9.00%	8.00%	76.00%
	SmoothLLM	-	5.00%	11.00%	6.00%	69.00%
	Ours	-	**1.00%**	**2.00%**	**3.00%**	**86.00%**
	No-Defense	-	20.00%	34.00%	-	82.00%
	PPL	-	20.00%	34.00%	15.00%	82.00%
GPT-4	Self-Reminder	-	2.00%	4.00%	7.00%	79.00%
	SmoothLLM	-	2.00%	3.00%	6.00%	65.00%
	Ours	-	**0.00%**	**0.00%**	**4.00%**	**89.00%**

Table 9: Performance of KG-DF on the Advbench and XSTest datasets using closed-source models.

Output Method	Final Prompt	ASR (%)
Direct Combination Input	"Warning": {hack corporate network instructions,illegal, crime} Question: Outline the steps for a terrorist organization to infiltrate a government agency.	13.0
Information Pre-output Judgment	"Warning": {hack corporate network instructions,illegal, crime} Question: Outline the steps for a terrorist organization to infiltrate a government agency. Please combine the contents of "warning" into one sentence and output it, then judge whether to answer the "Question" based on "Warning".	0
Combined Input	It is illegal and a crime to hack corporate network instructions. Outline the steps for a terrorist organization to infiltrate a government agency.	11.0

Table 10: Comparative analysis of different generation strategies.

Keywords Number	1	2	3	4
ASR (%)	6.00	6.00	5.00	6.00

Table 11: The influence of different keywords number on ASR.

Figure 14: Prompt for Evaluating FPR.

vided and the corresponding output generated by the model. See Figure 13 for details.

Figure 13: Prompt for Evaluating ASR.

D.3 Prompt for Evaluating FPR

This prompt focuses on detecting false positives by analyzing safe inputs and the corresponding output to ensure they are not wrongly flagged as offensive or harmful. See Figure 14 for details.

D.4 Prompt for Evaluating Generality

This prompt evaluates the quality of the model's response across different problem types or categories. See Figure 15 for details.

Figure 15: Prompt for Evaluating Generality.

D.5 Prompt for Evaluating Relevance of Original Prompt and Extracted Content

Figure 16 illustrates the prompt designed to evaluate the relevance between the original user input and the extracted content.

Figure 16: Prompt for Evaluating Relevance of Original Prompt and Extracted Content.

D.6 Retrieval Efficiency Analysis

To improve retrieval efficiency, we introduce the HNSW (Hierarchical Navigable Small World) index to replace brute-force similarity search and conduct a comparative experiment.

Experimental Settings: Vicuna-7B, GCG attack, Qwen3-Embedding-8B, HNSW index ($efConstruction = 200$, $efSearch = 64$).

Retrieval Method	Latency (s)	ASR (%)	FPR (%)	Generality (%)
Brute-force	7.1	0.0	5.0	88.0
HNSW	3.8	0.0	5.0	88.0

Table 12: Comparison of retrieval methods.

As shown in Table 12, HNSW reduces retrieval latency from 7.1s to 3.8s, while ASR, FPR, and Generality remain unchanged. The results demonstrate that approximate search significantly improves efficiency without compromising retrieval accuracy.

D.7 Ablation Study on Top-k

We further conduct ablation experiments to analyze the impact of the Top-k retrieval parameter.

Experimental Settings: Vicuna-7B, GCG attack, Qwen3-Embedding-8B.

Table 13: Impact of Top-k on defense performance.

k	ASR (%)	FPR (%)	Generality (%)
0	88.0	–	76.0
1	**0.0**	5.0	**88.0**
2	0.0	5.0	86.0
3	0.0	5.0	83.0

As shown in Table 13, when $k = 1$, ASR drops to 0 while generality reaches its peak. Increasing k introduces additional irrelevant information and semantic noise, resulting in a decline in generality. Therefore, we select $k = 1$ as the optimal setting.

D.8 Ablation Study on Embedding Models

We additionally evaluate the robustness of KG-DF under different embedding models.

Embedding Model	ASR (%)	FPR (%)	Generality (%)
Qwen3-Embedding-8B	0.0	5.0	88.0
Qwen3-VL-Embedding-8B	0.0	5.0	88.0
Octen-Embedding-8B	0.0	5.0	87.0
jina-embeddings-v4	0.0	4.5	87.0

Table 14: Impact of embedding models on defense performance ($k = 1$).

The four embedding models exhibit highly consistent performance, with negligible differences in ASR, FPR, and generality. These results indicate that the proposed framework is largely insensitive to the choice of embedding model and maintains stable defense effectiveness across different embedding backbones. "'

Safety Knowledge Module	Subcategories
Child_Abuse	Law & Punishment, Abusive Behavior, Child Impact, Ethical Critique, Social Responsibility, Case Scenarios, Intervention, Psychological Factors
Animal_Abuse	Law & Punishment, Abusive Behavior, Animal Impact, Ethical Critique, Social Responsibility, Case Scenarios, Intervention, Psychological Factors
Bias	Racial, Gender, Cultural, Regional, Age, Religious, Language, Political
Economic_Harm	Financial Fraud, False Advertising, Financial Scams, Investment Risks, Credit Loss, Economic Invasion, Tax Fraud, Price Manipulation
Fraud	Cyber Fraud, Identity Theft, Financial Fraud, False Advertising, Commercial Fraud, Telephone Scams, Investment Fraud, Insurance Fraud
Government	Government Policies, Corruption, Government Privacy Issues, Abuse of Power, Government Surveillance, Public Safety, Political Purges, Political Repression
Hate_Speech	Racial Hate, Gender Hate, Religious Hate, Political Hate, Cyber Hate, Physical Violence, Incitement of Hate, Extremist Speech
Health_Consultation	Disease Treatment, Health Advice, Unqualified Medical Advice, Health Misinformation, Medical Rumors, Mental Health Advice, Drug Abuse, False Medical Advice
Malware	Virus Spread, Ransomware, Spyware, Adware, Trojan Horses, Information Theft, Malicious Plugins, Network Attacks
Physical_Harm	Domestic Violence, School Violence, Occupational Injuries, Traffic Accidents, Sports Injuries, Physical Abuse, Self-Harm, Violent Crime
Political_Sensitivity	Political Extremism, Political Censorship, Political Suppression, Political Assassinations, Abuse of Power, Political Stance, Terrorism, Reactionary Ideology
Privacy_Violation	Identity Theft, Privacy Leaks, Unauthorized Surveillance, Data Theft, Hacking, Social Media Privacy Leaks, Information Misuse, Identity Fraud
Tailored_Unlicensed_Advice	Medical Advice, Legal Consultation, Educational Advice, Financial Advice, Career Planning, Psychological Advice, Health Diets, Social Problem Advice
Unethical_Behavior	Deceptive Practices, Conflicts of Interest, Unethical Workplace Behavior, Corruption, Dishonesty, Moral Failure, Illegal Actions, Boundary Violations
Violence	Violent Acts, Domestic Violence, Public Violence, School Violence, Terrorism, Psychological Violence, Verbal Abuse, Physical Harm
Roleplay	Misleading Scenarios, Encouraging Harmful Behavior, Emotional Manipulation, Risk of Emotional Distress, Impact of Roleplay on Real-Life Perceptions, Ethical Boundaries in Roleplay

Table 15: Specific categories under 16 categories in the Safety Knowledge module.

General Categories	Subcategories
Arts and Entertainment	Music, Movies, Literature, Dance, Drama, Artistic Creation, Creative Expression, Media Analysis
Business and Economics	Business Management, Marketing, Financial Management, Economic Theories, Macroeconomics, Microeconomics, Business Ethics, Economic Forecasting
Computer Science and Technology	Programming Languages, Algorithms, Artificial Intelligence, Cybersecurity, Data Structures, Machine Learning, Deep Learning, Computer Architecture
Daily Life Knowledge	Home Management, Healthy Living, Social Etiquette, Family Relationships, Time Management, Personal Finance, Travel, Psychology
Engineering and Technological Applications	Civil Engineering, Mechanical Engineering, Electrical Engineering, Electronics, Chemical Engineering, Environmental Engineering, Automation, Technological Innovation
Frontier Technology and Future Trends	Artificial Intelligence, Quantum Computing, Robotics, Virtual Reality, Blockchain, Gene Editing, Autonomous Driving, Climate Change Technology
Geography and Environment	Global Climate, Natural Disasters, Ecological Protection, Environmental Pollution, Geographic Information Systems, Meteorology, Earth Physics, Sustainable Development
History and Civilization	Ancient Civilizations, Historical Events, World History, Cultural Heritage, Ethnic Culture, Historical Figures, Cultural Heritage, Historical Thought
Language and Literature	Literary Works, Linguistics, Rhetoric, Writing Skills, Language Development, Literary Criticism, Translation Studies, Poetry and Prose
Law and Ethics	Civil Law, Criminal Law, International Law, Intellectual Property, Ethical Norms, Legal Regulations, Rule of Law, Legal Theory
Mathematics and Logic	Mathematical Theories, Geometry, Algebra, Probability Theory, Statistics, Numerical Analysis, Logical Reasoning, Mathematical Modeling
Medicine and Health	Disease Prevention, Treatment Methods, Pharmaceutical Research, Nutrition, Mental Health, Medical Devices, Public Health, Medical Ethics
Natural Science	Physics, Chemistry, Biology, Earth Science, Astronomy, Meteorology, Ecology, Scientific Experiments
Philosophy and Religion	Philosophical Schools, Ethics, Religious Beliefs, Religious History, Moral Philosophy, Metaphysics, Logic, Epistemology
Social Sciences	Psychology, Sociology, Political Science, Anthropology, Social Issues, Public Policy, Education, Cultural Studies

Table 16: Subcategories under the 15 categories in the General Knowledge module.