CONTRASTIVE AUDIO-VISUAL MASKED AUTOENCODER

ABSTRACT

In this paper, we first extend the recent Masked Auto-Encoder (MAE) model from a single modality to audio-visual multi-modalities. Subsequently, we propose the Contrastive Audio-Visual Masked Auto-Encoder (CAV-MAE) by combining contrastive learning and masked data modeling, two major self-supervised learning frameworks, to learn a joint *and* coordinated audio-visual representation.

Our experiments show that the contrastive audio-visual correspondence learning objective not only enables the model to perform audio-visual retrieval tasks, but also helps the model learn a better joint representation. As a result, our fully self-supervised pretrained CAV-MAE achieves a new SOTA accuracy of 65.9% on VGGSound, and is comparable with the previous best supervised pretrained model on AudioSet in the audio-visual event classification task.

1 INTRODUCTION

Acoustic and visual modalities have different properties, yet humans are able to seamlessly connect and integrate them to perceive the world. Developing learning algorithms to replicate these abilities, especially for multi-modal audio-visual fusion and retrieval is of great interest. Since manually annotating audio and video is expensive and difficult to scale, how to utilize web-scale *unlabeled* video data in a *self-supervised* manner has become a core research question.

One major line of audio-visual self-supervised learning research is leveraging the natural audio-visual correspondences found in videos. Among numerous ways to use such correspondences, *Contrastive Audio-Visual Learning* has shown to be a simple yet effective approach (Arandjelovic & Zisserman, 2018; Morgado et al., 2021b; Rouditchenko et al., 2021). It learns *coordinated* [1] representations that are closer for paired audio and visual samples than for mismatched samples. Such *coordinated* representations are particularly useful for tasks such as cross-modal retrieval.

Another vetted commonly used self-supervised learning framework is *Masked Data Modeling (MDM)*, which learns a meaningful representation with the pretext task of recovering the original inputs or features from the corrupted ones (Devlin et al., 2019). Particularly, based on the Audio Spectrogram Transformer (Gong et al., 2021a) and Vision Transformer (Dosovitskiy et al., 2020) backbones, the single-modal *Masked Auto-Encoder (MAE)* (He et al., 2022) achieved state-of-the-art (SOTA) performance on images and audio tasks (Xu et al., 2022) individually. Inspired by these advances, we propose to extend the single-modal MAE to *Audio-Visual Masked Auto-Encoder* (AV-MAE). By allowing the model to reconstruct one modality based on the information of another modality, AV-MAE learns a *joint* representation that fuses the unimodal signals.

Although these two major self-supervised frameworks have been widely used individually, to the best of our knowledge, they have never been combined in audio-visual learning. In fact, we find they are complementary: Contrastive audio-visual learning explicitly leverages the very useful audio-visual pair information, but it could discard modality-unique information that is useful in downstream tasks; The reconstruction task of AV-MAE forces its representation to encode the majority of the input information in the fusion, but it lacks an explicit audio-visual correspondence objective.

---

[1]Multi-modal representations can be divided into two categories: *joint* representations that combine the unimodal signals into the same representation space, and *coordinated* representations that process unimodal signals separately, but enforce certain similarity constraints on them. (Baltrušaitis et al., 2018)

This motivates us to design the *Contrastive Audio-Visual Masked Autoencoder (CAV-MAE)* that integrates contrastive learning and masked data modeling which learns a joint *and* coordinated audio-visual representation with a single model. Our experiments support our design: on audio-visual event classification, CAV-MAE significantly outperforms baseline models trained with only contrastive or masked data modeling objectives, demonstrating that the two objectives are complementary in learning a strong joint audio-visual representation. As a result, CAV-MAE achieves a new SOTA accuracy of 65.9% on VGGSound, and is comparable with the previous best supervised pretrained model on AudioSet. Moreover, when it comes to audio-visual retrieval, CAV-MAE also performs equally well or even better than models trained with only the contrastive objective, which demonstrates that CAV-MAE can learn both a joint *and* coordinated representation well. Finally, CAV-MAE multi-modal pretraining improves single-modal performance, consequently, CAV-MAE achieves a new SOTA for audio-based event classification on AudioSet-20K and VGGSound.

In summary, our contributions are: (1) we extend the single-modal MAE to multi-modal AV-MAE, which fuses audio-visual inputs for self-supervised learning through cross-modal masked data modeling; (2) More importantly, we investigate how to best combine contrastive audio-visual learning with masked data modeling and propose CAV-MAE; (3) We demonstrate that contrastive and masked data modeling objectives are complementary. As a result, CAV-MAE matches or outperforms SOTA models on audio-visual classification. We will release the code upon acceptance.

2   CONSTRASTIVE AUDIO-VISUAL MASKED AUTOENCODER

2.1   PRELIMINARIES

2.1.1   AUDIO AND IMAGE PRE-PROCESSING AND TOKENIZATION

As depicted in Figure 1 (A), we follow pre-processing and tokenization in AST (Gong et al., 2021a) and ViT (Dosovitskiy et al., 2020) for audio and image inputs, respectively. Specifically, we use 10-second videos (with parallel audios) in AudioSet (Gemmeke et al., 2017) and VGGSound (Chen et al., 2020) to pretrain and fine-tune the model. For audio, each 10-second audio waveform is first converted to a sequence of 128-dimensional log Mel filterbank (fbank) features computed with a 25ms Hanning window every 10ms. This results in a $1024(\text{time}) \times 128(\text{frequency})$ spectrogram. We then split the spectrogram into 512 16×16 square patches $\mathbf{a} = [a^1, ..., a^{512}]$ as the input of the model. Processing video with Transformer models is expensive and typically requires industrial-level computation resources. To lower the computational overhead and fit our resources, we use a *frame aggregation* strategy. Specifically, we uniformly sample 10 RGB frames from each 10-second video (i.e., 1 FPS). During training, we randomly select one RGB frame as the input; during inference, we average the model prediction of each RGB frame as the video prediction. Compare with concatenating multiple RGB frames as the input of the Transformer that has a quadratic complexity (e.g., in Nagrani et al. (2021)), frame aggregation is much more efficient with a linear complexity in time at a cost of not considering inter-frame correlation. For each RGB frame, we resize and center crop it to 224×224, and then split it into 196 16×16 square patches $\mathbf{v} = [v^1, ..., v^{196}]$.

2.1.2   THE TRANSFORMER ARCHITECTURE

Throughout this paper, we use the standard Transformer (Vaswani et al., 2017) as our main model component. Each Transformer layer consists of multi-headed self-attention (MSA), layer normalization (LN) , and multilayer perceptron (MLP) blocks with residual connections. Specifically, we denote a Transformer layer $\mathbf{y} = \text{Transformer}(\mathbf{x}; \text{MSA}, \text{LN1}, \text{LN2}, \text{MLP})$ as:

$$\mathbf{x}' = \text{MSA}(\text{LN}_1(\mathbf{x})) + \mathbf{x}; \quad \mathbf{y} = \text{MLP}(\text{LN}_2(\mathbf{x}')) + \mathbf{x}' \tag{1}$$

where MSA computes dot-product attention of each element of $\mathbf{x}$ and thus has a quadratic complexity w.r.t. to the size of $\mathbf{x}$. Please refer to Vaswani et al. (2017) for further details on Transformers.

2.1.3   CONTRASTIVE AUDIO-VISUAL LEARNING (CAV)

The natural pairing of audio and visual information in videos is a useful signal for learning audio-visual representations through self-supervision. A conventional CAV model is shown in Figure 1.B (top), for a mini-batch of N audio-visual pair samples, we first pre-process and tokenize the audios

Figure 1: An illustration of our method. A) We tokenize audio spectrograms and RGB images into 16×16 square patches and use them as the input to all models. B) Conventional contrastive audio-visual learning model (top) and vanilla audio-visual masked auto-encoder (bottom, also novel and first introduced in this paper). C) Our proposed contrastive audio-visual masked auto-encoder (CAV-MAE) model. CAV-MAE integrates two major self-supervised frameworks: contrastive audio-visual learning and cross-modal masked data modeling, which learns a *joint and coordinate* representations and performs well on both multi-modal joint classification tasks and cross-modal retrieval tasks.

and images and get a sequence of audio and visual tokens $\{\mathbf{a}_i, \mathbf{v}_i\}$ for each sample i. We then input $\mathbf{a}_i$ and $\mathbf{v}_i$ to independent audio and visual Transformer encoders $\mathrm{E}_a(\cdot)$ and $\mathrm{E}_v(\cdot)$, respectively, and get the mean pooled audio and visual representation c_i^a and c_i^v, i.e., $c_i^a = \mathrm{MeanPool}(\mathrm{E}_a(\mathrm{Proj}_a(\mathbf{a}_i))$ and $c_i^v = \mathrm{MeanPool}(\mathrm{E}_v(\mathrm{Proj}_v(\mathbf{v}_i))$, where Proj_a and Proj_v are linear projections that maps each audio and visual token to $\mathbb{R}^{768}$. We then apply a contrastive loss (Equation 7) on c_i^a and c_i^a.

2.1.4 Single Modality Masked Autoencoder (MAE)

Another line of major self-supervised frameworks is masked data modeling (MDM). Among numerous variants of MDM (e.g., Bao et al. (2021); Wei et al. (2022)), the masked auto-encoder (MAE) is a simple yet effective approach. For an input sample $\mathbf{x}$ that can be tokenized as $\mathbf{x} = [x^1, x^2, ..., x^n]$, MAE *masks* a portion of the input $\mathbf{x}_{\mathrm{mask}}$ and only inputs the unmasked tokens $\mathbf{x} \setminus \mathbf{x}_{\mathrm{mask}}$ to a Transformer based encoder-decoder model. The model is asked to *reconstruct* the masked tokens with the goal of minimizing the mean square error (MSE) loss. During this process, the model learns a meaningful representation of the input data. The advantages of MAE are multifold. First, MAE directly uses the original input as the prediction target, which greatly simplifies the training pipeline. Second, MAE only inputs *unmaksed* tokens to the encoder, and combined with a high masking ratio, MAE noticeably lowers the computational overhead. Third, MAE demonstrated strong performance in single-modal tasks for both audio and visual modality. Due to the space limitation, please refer to He et al. (2022); Xu et al. (2022) for single-modal MAEs.

2.2 Vanilla Audio-Visual Masked Autoencoder (AV-MAE)

While MAE has been applied to both audio and visual modality individually, it has never been applied to audio-visual multi-modality learning. As the first contribution of this work, we extend MAE from a single modality to audio-visual multi-modality and build a "vanilla" audio-visual autoencoder (AV-MAE). As shown in Figure 1.B (bottom), for a pair of audio and image inputs, we first tokenize them to $\mathbf{a} = [a^1, ..., a^{512}]$ and $\mathbf{v} = [v^1, ..., v^{196}]$ and project them to $\mathbb{R}^{768}$ with two modal-specific linear projection layer as well as add a modality type embedding $\mathbf{E_a}$ and $\mathbf{E_v}$ and modality

specific 2-D sinusoidal positional embedding $\mathbf{E}_\mathbf{a}^\mathbf{P}$ and $\mathbf{E}_\mathbf{v}^\mathbf{P}$, i.e., $\mathbf{a}' = \text{Proj}_\text{a}(\mathbf{a}) + \mathbf{E}_\mathbf{a} + \mathbf{E}_\mathbf{a}^\mathbf{P}$ and $\mathbf{v}' = \text{Proj}_\text{v}(\mathbf{v}) + \mathbf{E}_\mathbf{v} + \mathbf{E}_\mathbf{v}^\mathbf{P}$. We concatenate $\mathbf{a}'$ and $\mathbf{v}'$ and construct a joint embedding $\mathbf{x} = [\mathbf{a}', \mathbf{v}']$. We then mask a portion (75%) of $\mathbf{x}$ and only input unmasked tokens $\mathbf{x}_\text{unmask} = \mathbf{x} \setminus \mathbf{x}_\text{mask}$ to an audio-visual joint encoder $\text{E}_\text{j}(\cdot)$ and get the output $\mathbf{x}'_\text{unmask}$. After that, we pad $\mathbf{x}'_\text{unmask}$ with trainable masked tokens at their original position as $\mathbf{x}'$. Again, we also add modality type embedding $\mathbf{E}'_\mathbf{a}$ and $\mathbf{E}'_\mathbf{v}$ and modality-specific 2-D sinusoidal positional embedding $\mathbf{E}_\mathbf{a}^{\mathbf{P}'}$ and $\mathbf{E}_\mathbf{v}^{\mathbf{P}'}$ before feeding $\mathbf{x}'$ to a joint audio-visual decoder $\text{D}_\text{j}(\cdot)$ to reconstruct the input, i.e., $\hat{\mathbf{a}}, \hat{\mathbf{v}} = \text{D}_\text{j}(\mathbf{x}' + [\mathbf{E}'_\mathbf{a}, \mathbf{E}'_\mathbf{v}] + [\mathbf{E}_\mathbf{a}^{\mathbf{P}'}, \mathbf{E}_\mathbf{v}^{\mathbf{P}'}])$ Finally, we minimize the mean square error (MSE) between $\hat{\mathbf{a}}, \hat{\mathbf{v}}$ and normalized $\mathbf{a}, \mathbf{v}$.

Compared with single-modal MAEs, the AV-MAE features a *cross-modal masked data modeling* objective that allows the model to reconstruct one modality based on the information of another modality, which potentially helps the model learn audio-visual correlation. However, without an explicit objective of encouraging paired audio-visual correspondence, to which extent the vanilla AV-MAE leverages the audio-visual pairing information is unknown. In addition, using a joint encoder for two modalities allows cross-modal attention, but it also means the two very different modalities are processed with the same weights, which could lead to a sub-optimal solution.

2.3 CONSTRASTIVE AUDIO-VISUAL MASKED AUTOENCODER (CAV-MAE)

As discussed in Section 2.1.3 and 2.2, contrastive audio-visual learning and AV-MAE each has its advantages and disadvantages. Can we integrate the complementary advantages of CAV and AV-MAE? With this goal, we design the Contrastive Audio-Visual Masked Autoencoder (CAV-MAE) (shown in Figure 1.C). For a mini-batch of N audio-visual pair samples, we first pre-process and tokenize the audios and images and get a sequence of audio and visual tokens $\{\mathbf{a}_i, \mathbf{v}_i\}$ for each sample i and project them to $\mathbb{R}^{768}$ with two modal-specific linear projection layer. We also add a modality type embedding $\mathbf{E}_\mathbf{a}$ and $\mathbf{E}_\mathbf{v}$ and modality-specific 2-D sinusoidal positional embedding $\mathbf{E}_\mathbf{a}^\mathbf{P}$ and $\mathbf{E}_\mathbf{v}^\mathbf{P}$. After that, we uniformly mask 75% of tokens of each modality, i.e.,

$$\mathbf{a}_i^\text{unmask} = \text{Mask}_{0.75}(\text{Proj}_\text{a}(\mathbf{a}_i) + \mathbf{E}_\mathbf{a} + \mathbf{E}_\mathbf{a}^\mathbf{P}) \tag{2}$$

$$\mathbf{v}_i^\text{unmask} = \text{Mask}_{0.75}(\text{Proj}_\text{v}(\mathbf{v}_i) + \mathbf{E}_\mathbf{v} + \mathbf{E}_\mathbf{v}^\mathbf{P}) \tag{3}$$

We then input $\mathbf{a}_i^\text{unmask}$ and $\mathbf{v}_i^\text{unmask}$ to independent audio and visual Transformer encoders $\text{E}_\text{a}(\cdot)$ and $\text{E}_\text{v}(\cdot)$ and get $\mathbf{a}'_i$ and $\mathbf{v}'_i$, respectively. After that, we apply *multi-stream* forward passes to input $\mathbf{a}'_i, \mathbf{v}'_i$ to a joint audio-visual encoder $\text{E}_\text{j}(\cdot; \text{MSA}, \text{LN1}, \text{LN2}, \text{MLP})$. Specifically, we input audio tokens $\mathbf{a}'_i$, video tokens $\mathbf{v}'_i$, and concatenated audio-visual tokens $[\mathbf{a}'_i, \mathbf{v}'_i]$ in three independent forward passes to E_j. For each stream, we use different layer normalization layers $\text{LN1}_{\{\text{a,v,av}\}}$ and $\text{LN2}_{\{\text{a,v,av}\}}$, all other weights (i.e., weights of the MSA and MLP) of E_j are shared for all three streams. Formally,

$$c_i^a = \text{MeanPool}(\text{E}_\text{j}(\text{E}_\text{a}(\mathbf{a}_i^\text{unmask})); \text{LN1}_\text{a}, \text{LN2}_\text{a})) \tag{4}$$

$$c_i^v = \text{MeanPool}(\text{E}_\text{j}(\text{E}_\text{v}(\mathbf{v}_i^\text{unmask})); \text{LN1}_\text{v}, \text{LN2}_\text{v})) \tag{5}$$

$$\mathbf{x_i} = \text{E}_\text{j}([\text{E}_\text{a}(\mathbf{a}_i^\text{unmask}), \text{E}_\text{v}(\mathbf{v}_i^\text{unmask})]; \text{LN1}_\text{av}, \text{LN2}_\text{av}) \tag{6}$$

We use the output of the audio and visual single modality stream c_i^a and c_i^v for contrastive learning and the output of the audio-visual multi-modal stream $\mathbf{x_i}$ for the reconstruction task.

For contrastive audio-visual learning, we use the contrastive loss $\mathcal{L}_\text{c}$:

$$\mathcal{L}_\text{c} = -\frac{1}{N} \sum_{i=1}^N \log \left[\frac{\exp(s_{i,i}/\tau)}{\sum_{k \neq i} \exp(s_{i,k}/\tau) + \exp(s_{i,i}/\tau)} \right] \tag{7}$$

where $s_{i,j} = \|c_i^v\|^T \|c_j^a\|$ and τ is the temperature.

For the reconstruction task, we pad $\mathbf{x_i}$ with trainable masked tokens at their original position as $\mathbf{x'_i}$. We also add modality type embedding $\mathbf{E}'_\mathbf{a}$ and $\mathbf{E}'_\mathbf{v}$ and modality-specific 2-D sinusoidal positional embedding $\mathbf{E}_\mathbf{a}^{\mathbf{P}'}$ and $\mathbf{E}_\mathbf{v}^{\mathbf{P}'}$ before feeding $\mathbf{x'_i}$ to a joint audio-visual decoder $\text{D}_\text{j}(\cdot)$ to reconstruct the input audio and image. $\text{D}_\text{j}(\cdot)$ processes audio and visual tokens with a same set of weights except the last modal-specific projection layer, it outputs $\hat{\mathbf{a}}_i$ and $\hat{\mathbf{v}}_i$. We then apply a mean square error reconstruction loss $\mathcal{L}_\text{r}$:

$$\hat{\mathbf{a}}_i, \hat{\mathbf{v}}_i = \text{D}_\text{j}(\mathbf{x}' + [\mathbf{E}'_\mathbf{a}, \mathbf{E}'_\mathbf{v}] + [\mathbf{E}_\mathbf{a}^{\mathbf{P}'}, \mathbf{E}_\mathbf{v}^{\mathbf{P}'}]) \tag{8}$$

$$\mathcal{L}_{\mathrm{r}} = \frac{1}{N} \sum_{i=1}^{N} \left[\frac{\sum (\hat{\mathbf{a}}_i^{\mathrm{mask}} - \mathrm{norm}(\mathbf{a}_i^{\mathrm{mask}}))^2}{|\mathbf{a}_i^{\mathrm{mask}}|} + \frac{\sum (\hat{\mathbf{v}}_i^{\mathrm{mask}} - \mathrm{norm}(\mathbf{v}_i^{\mathrm{mask}}))^2}{|\mathbf{v}_i^{\mathrm{mask}}|} \right] \tag{9}$$

where N is the mini-batch size; $\mathbf{a}^{\mathrm{mask}}$, $\mathbf{v}^{\mathrm{mask}}$, $\hat{\mathbf{a}}^{\mathrm{mask}}$, $\hat{\mathbf{v}}^{\mathrm{mask}}$ denote the original and predicted masked patches (we only calculate the loss based on the masked portion of the input); $|\mathbf{a}^{\mathrm{mask}}|$ and $|\mathbf{v}^{\mathrm{mask}}|$ denote the number of masked audio and visual patches, respectively.

Finally, we sum up the contrastive loss $\mathcal{L}_{\mathrm{c}}$ (multiplied by a weight λ_c) and the reconstruction loss $\mathcal{L}_{\mathrm{r}}$ as the loss for CAV-MAE, i.e., $\mathcal{L}_{\mathrm{CAV-MAE}} = \mathcal{L}_{\mathrm{r}} + \lambda_c \cdot \mathcal{L}_{\mathrm{c}}$.

After pretraining, we abandon the decoder and only keep the encoders of the model for downstream tasks. We can use the sum of the single-modality stream output and the multi-modal modality stream output, or just the multi-modal stream output for finetuning. They perform similarly in our experiments.

Discussion: we next discuss the motivation of some key designs of CAV-MAE:

1. Multi-stream forward passes of the joint encoder. We find it important to restrict the representations used for contrastive audio-visual learning, so that c^a only comes from the audio input and c^v only comes from the visual input, otherwise the contrastive objective will collapse. In the meantime, we hope the encoder fuses the audio and visual information for the reconstruction task and downstream tasks. Therefore, we design the multi-stream forward pass strategy for CAV-MAE.

2. Modality-specific encoders and LN *layers.* While there are a few recent attempts (Akbari et al., 2021; Dai et al., 2022) to process audio and visual modalities with a unified network, due to the very different nature of audio and visual modalities, the general conclusion is that modality-specific networks are still optimal in terms of performance. Therefore, we choose to encode audio and visual inputs with modality-specific encoders before the joint encoder. For the same reason, we also use different normalization statistics for each stream of the joint encoder. Efficiency-wise, having two modality-specific encoders increases the model size, but lowers the computation as the Transformer has a quadratic complexity w.r.t. the input sequence length.

3. Masked contrastive audio-visual learning. Unlike single-modality contrastive learning, conventional contrastive audio-visual learning does not typically apply augmentation or masking. In this work, we propose to use *masked contrastive audio-visual learning*, i.e., we randomly mask a portion of the input before conducting contrastive learning. This design not only allows us to combine CAV with AV-MAE, but also helps to avoid overfitting. In practice, when the masking ratio is 75% and the effective contrastive batch size is 27 (108 on 4 GPUs), the audio-visual matching accuracy during pretraining on the evaluation set is about 72%, which shows the masked contrastive audio-visual task is neither trivial nor impossible.

2.3.1 IMPLEMENTATION DETAILS

By default, all encoder Transformer layers are 768-dimensional and have 12 attention heads. The joint encoder of the Vanilla AV-MAE is a 12-layer Transformer; The audio and visual encoders of CAV-MAE are 11-layer Transformers (each is 768- dimensional) and the joint encoder is a single-layer Transformer. I.e., we control the total number of encoder layers of all models as 12, but CAV and CAV-MAE are larger models due to the modality-specific encoders. The decoder of AV-MAE and CAV-MAE are 8-layer Transformers with an embedding dimension of 512 and 16 attention heads. These settings are identical to the original vision MAE He et al. (2022). We fix the contrastive loss temperature $\tau = 0.05$. For CAV-MAE, we use $\lambda_c = 0.01$. Note the relatively small λ_c is due to the scale of the gradient of $\mathcal{L}_{\mathrm{c}}$ being larger than $\mathcal{L}_{\mathrm{r}}$, it does not mean the contrastive objective is unimportant. The encoder and decoder of the default CAV-MAE model have about 164M and 27M parameters, respectively.

Following the common practice of audio-visual learning, we initialize the weights of all models with ImageNet pretrained weights. Specifically, we use the weights of the original vision MAE He et al. (2022). Nevertheless, unlike previous work that uses supervised pretrained weights (e.g., Fayek & Kumar (2020); Nagrani et al. (2021)), we only use the self-supervised pretrained weights (i.e., without finetuning), which does not lead to the best performance but makes our whole training pipeline self-supervised.

3 Self-Supervised Model Pretraining

We pretrain and compare the performance of the following models:

1. `Audio-MAE/Visual-MAE:` Single-modal masked auto-encoder models. The model architecture is the same with `Vanilla AV-MAE` but they are only pretrained with data of a single modality.
2. `CAV:` The contrastive audio-visual learning model that has no reconstruction objective. For a fair comparison, we implement `CAV` using the same encoder architecture (modal-specific encoders + joint encoder) with `CAV-MAE` but remove the reconstruction objective $\mathcal{L}_r$.
3. `Vanilla AV-MAE:` The vanilla audio-visual masked auto-encoder with a joint encoder and no contrastive objective as described in Section 2.2.
4. `AV-MAE:` The audio-visual masked auto-encoder with two modal-specific encoders and a joint encoder. It has the same architecture with `CAV-MAE`, but λ_c is set to 0 (no contrastive loss). We use this model to disentangle the impact of modal-specific encoders (when compared with `Vanilla AV-MAE`) and contrastive objective (when compared with `CAV-MAE`).
5. `CAV-MAE:` Our proposed contrastive masked auto-encoder as described in Section 2.3.
6. `CAV-MAE`$^{scale+}$: The same model with `CAV-MAE`, but trained with a larger batch size=108 (effective contrastive batch size=27) and more epochs=25. We train this model on our best GPUs.

For a fair comparison, all models (except `CAV-MAE`$^{scale+}$) are pretrained with the same pipeline with a batch size of 48 for 12 epochs on the full AudioSet-2M. During pretraining, we intentionally do not use class balanced sampling as that implicitly leverages the label information. Our pretraining process (including the ImageNet pretrained weight initialization) is fully self-supervised. Please refer to the Appendix B for all pretraining details.

4 Audio-Visual Event Classification

We evaluate the representation quality on the audio-visual event classification task, a major audio-visual learning benchmark. Specifically, we fine-tune the pretrained models on three datasets: 1) AudioSet-20K (20K samples, same domain as the pretraining data); 2) AudioSet-2M (2 million samples, same with pretraining data); and 3) VGGSound (200K samples, different domain than the pretraining data), covering various downstream data volume and domain situations.

In the fine-tuning stage, we only keep the encoder of the pretrained models and connect it to a randomly initialized linear classification head. To avoid overriding too much of the knowledge learned in pretraining, we use a smaller learning rate for the pretrained weights and a 10×-100× larger learning rate for the new classification head. We use the standard training pipeline used in prior audio-based and audio-visual event classification work Gong et al. (2021a;b); Nagrani et al. (2021) with mixup Zhang et al. (2018), balanced sampling, label smoothing, and random time shifts. Please refer to the appendix for the details. We fine-tune the model using audio-only data (A), video-only data (V), and audio-visual data (AV) to evaluate the single-modal and multi-modal representation quality. We show the results in Table 1. Key findings are as follows:

1. Contrastive learning and masked data modeling are complementary. While both `AV-MAE` (only with masked data modeling objective) and `CAV` (only with contrastive objective) perform better than ensembling two single-modal MAEs, the proposed `CAV-MAE` that combines the two objectives significantly boosts the performance (e.g., 2.0 and 3.1 mAP boost from `CAV` and `AV-MAE` on AudioSet-20K, respectively). Note `CAV-MAE`, `AV-MAE`, and `CAV` have the same architecture during fine-tuning, the only difference is the objective in the pretraining stage. This demonstrates that the two major self-supervised learning frameworks are complementary in the context of audio-visual learning and CAV-MAE is an effective way to combine their advantages.

2. CAV-MAE multi-modal pretraining improves single-modal performance. We find the `CAV-MAE` model pretrained with paired audio-visual data, when fine-tuned with only a single modality, performs noticeably better than `Audio-MAE` and `Visual-MAE` on single-modal classification tasks (e.g., 34.2→37.7 mAP for audio, 15.7→19.8 mAP for visual on AudioSet-20K). Note for single-modal fine-tuning, `CAV-MAE` only keeps one branch and has the same architecture with `Audio-MAE` and `Visual-MAE`, so the performance improvement can only come from the use of multi-modal data during pretraining. We hypothesize this is due to the two modalities serving as soft labels for each other, providing richer information than the binary human-annotated labels.

Table 1: Comparing audio-visual classification performance on AudioSet and VGGSound. IN SL=ImageNet supervised learning; SSL=self-supervised learning; [†]Industry-level computation. [*]Nonstandard data split; [ens]Ensemble of single-modal models. We bold the best methods without supervised pretraining, and underline the overall best methods.

	Pretrain	AudioSet-20K (mAP)			AudioSet-2M (mAP)			VGGSound (Acc)		
		A	V	A-V	A	V	A-V	A	V	A-V
Existing Audio-Based Models										
PANNs (Kong et al., 2020)	-	27.8	-	-	43.9	-	-	-	-	-
AST (Gong et al., 2021a)	IN SL	34.7	-	-	45.9	-	-	-	-	-
HTS-AT Chen et al. (2022)	IN SL	-	-	-	47.1	-	-	-	-	-
PaSST Koutini et al. (2021)	IN SL	-	-	-	47.1	-	-	-	-	-
SSAST (Gong et al., 2022)	SSL	31.0	-	-	-	-	-	-	-	-
MAE-AST (Baade et al., 2022)	SSL	30.6	-	-	-	-	-	-	-	-
Audio-MAE[†](vanilla) (Xu et al., 2022)	SSL	36.6	-	-	46.8	-	-	-	-	-
Audio-MAE[†] (Xu et al., 2022)	SSL	37.1	-	-	47.3	-	-	-	-	-
Chen et al. (2020)	-	-	-	-	-	-	-	48.8	-	-
AudioSlowFast (Kazakos et al., 2021)	-	-	-	-	-	-	-	50.1	-	-
Existing Audio-Visual Models										
GBlend[†*] (Wang et al., 2020)	-	29.1	**22.1**	37.8	32.4	18.8	41.8	-	-	-
Perceiver[†] (Jaegle et al., 2021)	-	-	-	-	38.4	25.8	44.2	-	-	-
Attn AV (Fayek & Kumar, 2020)	IN SL	-	-	-	38.4	25.7	46.2	-	-	-
MBT[†*] (Nagrani et al., 2021)	IN SL	31.3	27.7	43.9	44.3	32.3	52.1	52.3	51.2	64.1
Our Single-Modal MAE										
Audio-MAE	SSL	34.2	-	36.7[ens]	44.9	-	46.9[ens]	57.7	-	63.1[ens]
Visual-MAE	SSL	-	15.7		-	24.2		-	45.7	
Our Contrastive Audio-Visual Learning										
CAV	SSL	34.6	18.4	38.5	43.6	24.4	48.1	57.3	45.1	64.1
Our Multi-Modal MAE										
Vanilla AV-MAE	SSL	32.7	15.8	36.5	43.7	24.0	48.3	56.4	45.4	63.4
AV-MAE	SSL	33.4	15.1	37.4	44.8	24.0	49.6	57.2	45.3	64.1
CAV-MAE	SSL	36.8	18.7	40.5	45.8	25.6	50.5	59.2	46.6	65.4
CAV-MAE[Scale+]	SSL	**37.7**	19.8	**42.0**	46.6	**26.2**	**51.2**	**59.5**	**47.0**	**65.5**

As a result, `CAV-MAE` achieves a new SOTA performance on audio-based event classification on AudioSet-20K (37.7 mAP) and VGGSound (59.5% accuracy), without supervised pretraining and industry-level computational resources.

3. Fully SSL pretrained CAV-MAE matches or outperforms SOTA models with significantly fewer computational resources. There are two major setting differences between this work and previous SOTA works. First, our pretraining is completely self-supervised so that our model can leverage web-scale unlabeled videos, while supervised ImageNet pretraining is commonly used in previous audio-visual works, e.g., in MBT (Nagrani et al., 2021). ImageNet labels are strong supervision signals that can directly impact the visual branch performance. As a result, our visual branch is worse than SOTA models. Second, we pretrain and fine-tune the model with 4 GPUs, making our work easy to reproduce. Most SOTA models are trained with industry-level resources (e.g., 32 TPUs for Perceiver (Jaegle et al., 2021), 64 GPUs for Audio-MAE (Xu et al., 2022) and MBT), which brings many benefits such as large batch size (particularly useful for contrastive learning), multiple frames input (MBT uses 8 frames as input), and more training epochs (Audio-MAE pretrain the model for 32 epochs).

Even with such setting differences, on the audio-visual event classification task, our `CAV-MAE` performs better than the best existing audio-visual model MBT on VGGSound (even when `CAV-MAE` is only pretrained on VGGSound, see Table 2e) and comparable on AudioSet-20K and AudioSet-2M. On the audio-based event classification task, our `CAV-MAE` performs better than the best existing audio model Audio-MAE on AudioSet-20k and comparable on AudioSet-2M.

Besides, we find modal-specific encoders are helpful as `AV-MAE` outperforms `Vanilla AV-MAE`. `Vanilla AV-MAE` with only a joint encoder does not outperform the ensemble of single-modal `Audio-MAE` and `Visual-MAE`. Scaling up the batch size and training epochs improves the performance as `CAV-MAE`[scale+] generally performs better than `CAV-MAE`. The performance margin is smaller on larger fine-tuning datasets.

Table 2: Ablation studies on audio-visual classification. MM=multi-modal, SM=single-modal.

(a) **Pretrain λ_c**

λ_c	AS-20K
0.1	39.3
0.01	**40.5**
0.001	38.6

(b) **Pretrain epochs**

Epochs	AS-20K
1	37.3
3	39.1
12	40.8
25	**42.0**

(c) **Pretrain batch**

Size	AS-20K
48	40.5
108	**40.8**

(d) **Pretrain target**

Norm	AS-20K
w/o norm	40.5
w/norm	**40.5**

(e) **Pretrain dataset**

Dataset	VGGSound
AS-2M	65.5
VS	64.2
AS-2M+VS	**65.9**

(f) **Finetuning**

Strategy	AS-20K
MM	**42.0**
SM	41.3
MM+SM	41.7

(g) **SM experiment**

Setting	AS-20K A	V
Missing Modality	36.7	14.4
SM Fine-tune	**37.7**	**19.8**

(h) **Inference frame**

Frame Used	AS-20K V	A-V
Middle	17.4	40.9
Aggregation	**19.8**	**42.0**

(i) **Linear probe**

Model	AS-20K
SM Ensemble	24.2
AV-MAE	24.0
CAV-MAE	**29.8**

Ablation Studies: We conduct a series of ablation studies to show the impact of each design factor. For each study, we use `CAV-MAE`$^{\texttt{scale+}}$ or `CAV-MAE` as the base model, change one factor at a time, and report the downstream classification performance of the model on AudioSet-20K or VG-GSound. Our findings are as follows: the weight of the contrastive loss λ_c has a large impact on the performance, too large or too small λ_c leads to a noticeable performance drop (Table 2a); Scaling up the pretraining epochs and batch size consistently leads to a performance improvement (Table 2b and 2c); Normalizing the prediction target only leads to marginal performance improvement (Table 2d); When finetuning on VGGSound, pretraining with the larger out-of-domain AudioSet-2M is better than pretraining with the smaller in-domain VGGSound itself, but pretraining first on AudioSet-2M and then on VGGSound leads to the best result (Table 2e); During fine-tuning, using the output of the multi-modal stream of the encoder leads to better performance than using the concatenated single-modal stream outputs, and summing the output of two streams generally lead to similar result (Table 2f); When only one modality is of interest, it is better to fine-tune the model with single-modal data than fine-tune the model with audio-visual data and do single modality inference. However, the performance gap is small for audio (Table 2g); The frame aggregation strategy boosts the performance without the need to input multiple frames to the model (Table 2h); In the linear probe setting, `CAV-MAE` also noticeably outperform the baselines (Table 2i).

5 AUDIO-VISUAL RETRIEVAL

Table 3: Retrieval results on AudioSet and VGGSound.

Visual → Audio	AudioSet Eval Subset			VGGSound Eval Subset		
	R@1	R@5	R@10	R@1	R@5	R@10
Audio-Visual Models with Only MDM Loss						
Vanilla AV-MAE	0.1	0.3	0.8	0.2	0.7	1.4
AV-MAE	0.1	0.3	0.7	0.1	0.7	1.2
Audio-Visual Models with Only Contrastive Loss						
CAV, $\lambda_c = 0.1$	**17.4**	36.1	47.3	14.2	35.2	**46.2**
CAV, $\lambda_c = 0.01$	14.6	32.9	42.8	10.9	28.7	39.8
Constrastive Audio-Visual Masked Auto-Encoders						
CAV-MAE, $\lambda_c = 0.1$	16.1	**38.6**	**49.3**	**14.7**	**35.3**	45.9
CAV-MAE, $\lambda_c = 0.01$	12.3	31.4	41.9	12.5	28.6	39.1
CAV-MAE$^{\text{Scale+}}$, $\lambda_c = 0.01$	18.8	39.5	50.1	14.8	34.2	44.0

Figure 2: Sample retrieval results.

In the previous section, we show that CAV-MAE learns a good audio-visual *joint* representation that effectively fuses the unimodal signals for the audio-visual event classification task. Next, we study if CAV-MAE also learns a good *coordinated* representation that captures audio-visual correspondences for audio-visual retrieval. Specifically, we uniformly sample a subset of 1,725 and 1,545 audio-visual samples from the AudioSet and VGGSound evaluation set, respectively (about 10%) to make the similarity matrix of a reasonable size. We input audio and image to each model in two independent forward passes and take the mean-pooled encoder outputs as the audio and visual representation, respectively. We then calculate the retrieval recall at rank 1, 5, and 10 (R@1, R@5, R@10) based on the cosine similarity of the audio and visual representation. All models are self-supervised

pretrained but not fine-tuned, i.e., labels are not used. We conduct bi-directional visual→audio and audio→ visual retrieval, but due to the space limitation and the conclusions being similar, we show the quantitative result of visual→audio in Table 3 and leave the result of audio→ visual retrieval in the Appendix C. We also show retrieval samples in Figure 2 and Appendix C.

We find a contrastive objective is necessary for the audio-visual retrieval task as the performance of both `Vanilla-MAE` and `AV-MAE` are close to random guesses. Nevertheless, the cross-modal masked data modeling objective does not hurt, and in many cases, improves the retrieval performance, e.g., when $\lambda_c = 0.1$, `CAV-MAE` generally performs better than `CAV`. Scaling up the batch size and training epoch also leads to a better retrieval performance. When tested on a dataset different from the pretraining dataset (VGGSound), the retrieval performance is still competitive, indicating the audio-visual correspondence transfers well in addition to the audio and visual representations. These results demonstrate that the contrastive and mask data modeling objectives do not conflict, a single pretrained `CAV-MAE` can be applied to both audio-visual fusion and correspondence tasks.

6 RELATED WORK

Contrastive Audio-Visual Learning The natural pairing of audio and visual information in videos has been a useful signal for learning audio-visual representations through self-supervision. Existing methods include knowledge distillation (Aytar et al., 2016; Owens et al., 2016), paired sample discrimination (Arandjelovic & Zisserman, 2017; Korbar et al., 2018; Owens & Efros, 2018), and contrastive learning (Morgado et al., 2021b). To improve contrastive learning, some recent methods sought to mine better negative samples (Ma et al., 2020; Morgado et al., 2021a), while others proposed additional data augmentation (Patrick et al., 2021; Wang et al., 2021) or using global and local video views (Zeng et al., 2021; Recasens et al., 2021). Our approach instead combines the contrastive loss with masked data modeling, which not only leads to an improvement in classification performance but also maintains the compelling ability of audio-visual retrieval (Arandjelovic & Zisserman, 2018; Rouditchenko et al., 2021).

Masked Auto-Encoder. Masking data modeling has a long history (Vincent et al., 2008). Given the success of MAE in the vision domain (He et al., 2022; Bachmann et al., 2022; Girdhar et al., 2022; Tong et al., 2022; Feichtenhofer et al., 2022), several efforts adapt MAE for audio with relatively minor changes to the overall pipeline (Baade et al., 2022; Niizumi et al., 2022; Chong et al., 2022; Xu et al., 2022). There are a few recent works investigating multi-modal MAE for the vision & language multi-modal scenarios (Geng et al., 2022; Kwon et al., 2022), which inspired us to design an audio-visual MAE. To the best of our knowledge, our AV-MAE and CAV-MAE are the first audio-visual masked autoencoders. One closely related concurrent work is CMAE (Huang et al., 2022), which also combines MAE and contrastive loss, but only for single-modal images. Our motivation and implementation are very different from CMAE as we aim to leverage the unique audio-visual pair information and CAV-MAE features a multi-stream joint encoder design. Finally, while we take a modern approach with Transformers, multi-modal autoencoders have been studied more than a decade ago with much simpler models and datasets (Ngiam et al., 2011).

7 CONCLUSION

In this paper, we introduce two novel audio-visual learning models AV-MAE and CAV-MAE. The main idea of this paper is simple: masked data modeling and contrastive learning are a pair of complementary frameworks that should be used together for audio-visual self-supervised learning. Effectively combining the two frameworks and avoiding representation collapse requires some careful design choices such as the multi-stream forward pass strategy, joint-specific encoder architecture, and masked contrastive learning. From the perspective of audio-visual representation learning, CAV-MAE learns a joint *and* coordinated representation and can be used for both audio-visual joint event classification task as well as the audio-visual retrieval task. As a result, on the audio-visual event classification task, CAV-MAE matches or outperforms SOTA models with fully self-supervised pretraining and noticeably fewer computational resources; on the retrieval task, CAV-MAE is comparable to models trained with only the contrastive objective. Finally, we find that CAV-MAE multi-modal pretraining also learns strong single-modal representations, consequently, CAV-MAE achieves new SOTA performance on audio-based event classification.

ETHICS STATEMENT

The data used in this paper are publicly available YouTube videos, we do not use videos that have been removed by the user. The proposed audio-visual model can be applied in a wide range of areas including security related applications. However it can also be used for malicious purposes such as surveillance. We are committed to distributing our code and model carefully.

REPRODUCIBILITY STATEMENT

We document all implementation details in Section 2.3.1 and Appendix B. We will release the code and model upon publication.

REFERENCES

Hassan Akbari, Liangzhe Yuan, Rui Qian, Wei-Hong Chuang, Shih-Fu Chang, Yin Cui, and Boqing Gong. Vatt: Transformers for multimodal self-supervised learning from raw video, audio and text. *Advances in Neural Information Processing Systems*, pp. 24206–24221, 2021.

Relja Arandjelovic and Andrew Zisserman. Look, listen and learn. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 609–617, 2017.

Relja Arandjelovic and Andrew Zisserman. Objects that sound. In *Proceedings of the European conference on computer vision (ECCV)*, pp. 435–451, 2018.

Yusuf Aytar, Carl Vondrick, and Antonio Torralba. Soundnet: Learning sound representations from unlabeled video. *Advances in neural information processing systems*, 29, 2016.

Alan Baade, Puyuan Peng, and David Harwath. Mae-ast: Masked autoencoding audio spectrogram transformer. In *Proc. Interspeech 2022*, 2022.

Roman Bachmann, David Mizrahi, Andrei Atanov, and Amir Zamir. MultiMAE: Multi-modal multi-task masked autoencoders. *arXiv preprint arXiv:2204.01678*, 2022.

Tadas Baltrušaitis, Chaitanya Ahuja, and Louis-Philippe Morency. Multimodal machine learning: A survey and taxonomy. *IEEE transactions on pattern analysis and machine intelligence*, 41(2): 423–443, 2018.

Hangbo Bao, Li Dong, Songhao Piao, and Furu Wei. Beit: Bert pre-training of image transformers. In *International Conference on Learning Representations*, 2021.

Honglie Chen, Weidi Xie, Andrea Vedaldi, and Andrew Zisserman. Vggsound: A large-scale audio-visual dataset. In *IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 721–725, 2020.

Ke Chen, Xingjian Du, Bilei Zhu, Zejun Ma, Taylor Berg-Kirkpatrick, and Shlomo Dubnov. Htsat: A hierarchical token-semantic audio transformer for sound classification and detection. In *ICASSP 2022-2022 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 646–650. IEEE, 2022.

Dading Chong, Helin Wang, Peilin Zhou, and Qingcheng Zeng. Masked spectrogram prediction for self-supervised audio pre-training. *arXiv preprint arXiv:2204.12768*, 2022.

Yong Dai, Duyu Tang, Liangxin Liu, Minghuan Tan, Cong Zhou, Jingquan Wang, Zhangyin Feng, Fan Zhang, Xueyu Hu, and Shuming Shi. One model, multiple modalities: A sparsely activated approach for text, sound, image, video and code. *arXiv preprint arXiv:2205.06126*, 2022.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4171–4186, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1423. URL `https://aclanthology.org/N19-1423`.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations*, 2020.

Haytham M Fayek and Anurag Kumar. Large scale audiovisual learning of sounds with weakly labeled data. *arXiv preprint arXiv:2006.01595*, 2020.

Christoph Feichtenhofer, Haoqi Fan, Yanghao Li, and Kaiming He. Masked autoencoders as spatiotemporal learners. *arXiv preprint arXiv:2205.09113*, 2022.

Jort F Gemmeke, Daniel PW Ellis, Dylan Freedman, Aren Jansen, Wade Lawrence, R Channing Moore, Manoj Plakal, and Marvin Ritter. Audio set: An ontology and human-labeled dataset for audio events. In *IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 776–780, 2017.

Xinyang Geng, Hao Liu, Lisa Lee, Dale Schuurams, Sergey Levine, and Pieter Abbeel. Multimodal masked autoencoders learn transferable representations. *arXiv preprint arXiv:2205.14204*, 2022.

Rohit Girdhar, Alaaeldin El-Nouby, Mannat Singh, Kalyan Vasudev Alwala, Armand Joulin, and Ishan Misra. Omnimae: Single model masked pretraining on images and videos. *arXiv preprint arXiv:2206.08356*, 2022.

Yuan Gong, Yu-An Chung, and James Glass. AST: Audio Spectrogram Transformer. In *Proc. Interspeech 2021*, pp. 571–575, 2021a. doi: 10.21437/Interspeech.2021-698.

Yuan Gong, Yu-An Chung, and James Glass. Psla: Improving audio tagging with pretraining, sampling, labeling, and aggregation. *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, 2021b.

Yuan Gong, Cheng-I Lai, Yu-An Chung, and James Glass. Ssast: Self-supervised audio spectrogram transformer. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36, pp. 10699–10709, 2022.

Kaiming He, Xinlei Chen, Saining Xie, Yanghao Li, Piotr Dollár, and Ross Girshick. Masked autoencoders are scalable vision learners. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 16000–16009, 2022.

Zhicheng Huang, Xiaojie Jin, Chengze Lu, Qibin Hou, Ming-Ming Cheng, Dongmei Fu, Xiaohui Shen, and Jiashi Feng. Contrastive masked autoencoders are stronger vision learners. *arXiv preprint arXiv:2207.13532*, 2022.

Andrew Jaegle, Felix Gimeno, Andy Brock, Oriol Vinyals, Andrew Zisserman, and Joao Carreira. Perceiver: General perception with iterative attention. In *International conference on machine learning*, pp. 4651–4664. PMLR, 2021.

Evangelos Kazakos, Arsha Nagrani, Andrew Zisserman, and Dima Damen. Slow-fast auditory streams for audio recognition. In *ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 855–859. IEEE, 2021.

Qiuqiang Kong, Yin Cao, Turab Iqbal, Yuxuan Wang, Wenwu Wang, and Mark D Plumbley. Panns: Large-scale pretrained audio neural networks for audio pattern recognition. *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, 28:2880–2894, 2020.

Bruno Korbar, Du Tran, and Lorenzo Torresani. Cooperative learning of audio and video models from self-supervised synchronization. *Advances in Neural Information Processing Systems*, 31, 2018.

Khaled Koutini, Jan Schlüter, Hamid Eghbal-zadeh, and Gerhard Widmer. Efficient training of audio transformers with patchout. *arXiv preprint arXiv:2110.05069*, 2021.

Gukyeong Kwon, Zhaowei Cai, Avinash Ravichandran, Erhan Bas, Rahul Bhotika, and Stefano Soatto. Masked vision and language modeling for multi-modal representation learning. *arXiv preprint arXiv:2208.02131*, 2022.

Shuang Ma, Zhaoyang Zeng, Daniel McDuff, and Yale Song. Active contrastive learning of audio-visual video representations. In *International Conference on Learning Representations*, 2020.

Pedro Morgado, Ishan Misra, and Nuno Vasconcelos. Robust audio-visual instance discrimination. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 12934–12945, 2021a.

Pedro Morgado, Nuno Vasconcelos, and Ishan Misra. Audio-visual instance discrimination with cross-modal agreement. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 12475–12486, 2021b.

Arsha Nagrani, Shan Yang, Anurag Arnab, Aren Jansen, Cordelia Schmid, and Chen Sun. Attention bottlenecks for multimodal fusion. *Advances in Neural Information Processing Systems*, 34: 14200–14213, 2021.

Jiquan Ngiam, Aditya Khosla, Mingyu Kim, Juhan Nam, Honglak Lee, and Andrew Y Ng. Multimodal deep learning. In *ICML*, 2011.

Daisuke Niizumi, Daiki Takeuchi, Yasunori Ohishi, Noboru Harada, and Kunio Kashino. Masked spectrogram modeling using masked autoencoders for learning general-purpose audio representation. *arXiv:2204.12260*, 2022. URL `https://arxiv.org/abs/2204.12260`.

Andrew Owens and Alexei A Efros. Audio-visual scene analysis with self-supervised multisensory features. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pp. 631–648, 2018.

Andrew Owens, Jiajun Wu, Josh H McDermott, William T Freeman, and Antonio Torralba. Ambient sound provides supervision for visual learning. In *European conference on computer vision*, pp. 801–816. Springer, 2016.

Mandela Patrick, Yuki M Asano, Polina Kuznetsova, Ruth Fong, João F Henriques, Geoffrey Zweig, and Andrea Vedaldi. On compositions of transformations in contrastive self-supervised learning. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 9577–9587, 2021.

Adria Recasens, Pauline Luc, Jean-Baptiste Alayrac, Luyu Wang, Florian Strub, Corentin Tallec, Mateusz Malinowski, Viorica Pătrăucean, Florent Altché, Michal Valko, et al. Broaden your views for self-supervised video learning. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 1255–1265, 2021.

Andrew Rouditchenko, Angie Boggust, David Harwath, Brian Chen, Dhiraj Joshi, Samuel Thomas, Kartik Audhkhasi, Hilde Kuehne, Rameswar Panda, Rogerio Feris, et al. Avlnet: Learning audio-visual language representations from instructional videos. In *Interspeech*, 2021.

Zhan Tong, Yibing Song, Jue Wang, and Limin Wang. Videomae: Masked autoencoders are data-efficient learners for self-supervised video pre-training. In *NeurIPS*, 2022.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 2017.

Pascal Vincent, Hugo Larochelle, Yoshua Bengio, and Pierre-Antoine Manzagol. Extracting and composing robust features with denoising autoencoders. In *Proceedings of the 25th international conference on Machine learning*, pp. 1096–1103, 2008.

Luyu Wang, Pauline Luc, Adria Recasens, Jean-Baptiste Alayrac, and Aaron van den Oord. Multimodal self-supervised learning of general audio representations. *arXiv preprint arXiv:2104.12807*, 2021.

Weiyao Wang, Du Tran, and Matt Feiszli. What makes training multi-modal classification networks hard? In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 12695–12705, 2020.

Chen Wei, Haoqi Fan, Saining Xie, Chao-Yuan Wu, Alan Yuille, and Christoph Feichtenhofer. Masked feature prediction for self-supervised visual pre-training. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 14668–14678, 2022.

Hu Xu, Juncheng Li, Alexei Baevski, Michael Auli, Wojciech Galuba, Florian Metze, Christoph Feichtenhofer, et al. Masked autoencoders that listen. *arXiv preprint arXiv:2207.06405*, 2022.

Zhaoyang Zeng, Daniel McDuff, Yale Song, et al. Contrastive learning of global and local video representations. *Advances in Neural Information Processing Systems*, 34:7025–7040, 2021.

Hongyi Zhang, Moustapha Cisse, Yann N. Dauphin, and David Lopez-Paz. mixup: Beyond empirical risk minimization. In *International Conference on Learning Representations*, 2018.

A DATASET DETAILS

We use two major audio-visual datasets for our experiments: AudioSet Gemmeke et al. (2017) and VGGSound Chen et al. (2020). AudioSet-2M is a collection of 2M 10-second YouTube video clips labeled with the sounds that the clip contains from a set of 527 labels of audio events, AudioSet-20K is a subset of AudioSet-2M with more balanced class distribution. Due to changes in video availability, we downloaded 1.77M AudioSet-2M training, 19K AudioSet-20K training, and 17K evaluation samples, respectively. VGGSound Chen et al. (2020) is a collection of 200K 10-second YouTube video clips annotated with 309 classes. We download 183K training and 15K test samples. We only use the labels in the fine-tuning stage to make our pretraining pipeline fully self-supervised.

B TRAINING DETAILS

Our training hyper-parameters are listed in Table 4. Most of our experiments are run on 4×NVIDIA GTX Titan X Pascal GPUs with 12GB memory, only the scaled-up CAV-MAE$^{\texttt{Scale+}}$ is pretrained on 4×NVIDIA RTX A5000 GPUs with 24GB memory, making our result easier to reproduce with reasonable resources. Pretraining CAV-MAE takes about one week with 4 GPUs.

Table 4: Our pre-training and fine-tuning hyperparameters.

	Pretraining		Finetuning		
	CAV-MAE$^{\texttt{Scale+}}$	All Other Models	All Models		
Dataset	AS-2M	AS-2M	AS-20K	AS-2M	VGG
Optimizer	Adam, weight decay=5e-7, betas=(0.95, 0.999)				
Backbone learning rate	1e-4	5e-5	5e-5	1e-5	1e-4
Classification head LR	-	-	5e-2	5e-4	1e-3
LR decay start epoch	10	10	5	2	2
LR decay rate	0.5	0.5	0.5	0.5	0.5
LR decay step	5	5	1	1	1
Epochs	25	12	15	10	10
Batch size	4×27	4×12	36	48	48
GPUs	4 A5000	4 Titan X Pascal			
Class Balance Sampling	No	No	No	Yes	Yes
Mixup	No	No	Yes	Yes	Yes
Random Time Shifting	Yes	Yes	Yes	Yes	Yes
Loss Function	-		BCE	BCE	CE
Weight Averaging	No	No	Yes	Yes	Yes
Ensemble	No	No	No	No	No
Input Norm Mean	-5.081	-5.081	-5.081	-5.081	-5.081
Input Norm STD	4.485	4.485	4.485	4.485	4.485

C   ADDITIONAL AUDIO-VISUAL RETRIEVAL RESULTS.

We show additional audio-visual bi-directional retrieval results. All samples in Figure 3 and 4 are from VGGSound, a dataset that is different from the pretraining dataset AudioSet.

Table 5: Audio to visual retrieval results on AudioSet and VGGSound.

Audio→Visual Retrieval	AudioSet Eval Subset			VGGSound Eval Subset		
	R@1	R@5	R@10	R@1	R@5	R@10
Audio-Visual Models with Only MDM Loss						
Vanilla AV-MAE	0.2	0.4	0.9	0.0	0.4	0.8
AV-MAE	0.2	0.4	0.9	0.0	0.2	0.6
Audio-Visual Models with Only Contrastive Loss						
CAV, C=0.1	15.5	32.7	42.8	12.4	33.2	44.7
CAV, C=0.01	11.5	27.5	36.5	10.0	25.6	36.9
Constrastive Audio-Visual Masked Auto-Encoders						
CAV-MAE, C=0.1	13.5	32.5	43.2	12.1	31.6	42.4
CAV-MAE, C=0.01	9.5	22.6	32.4	8.3	23.8	32.4
CAV-MAE(Scale), C=0.01	15.1	34.0	43.0	12.8	30.4	40.3

D   MAE RECONSTRUCTION RESULTS

We show the CAV-MAE reconstruction samples in Figure 5, 6, and 7. All samples are from VG-GSound, a different dataset from the pretraining set. The CAV-MAE model is trained with 75% masking ratio without target normalization. As we show in our experiment, it has similar performance with the one with target normalization. CAV-MAE has strong reconstruction ability even the masking ratio goes to 90%, which makes it potentially can be used for in-painting and enhancement tasks.

Figure 3: Audio to video retrieval results. Since the spectrogram is hard to read, we show its paired image in dashed box just for visualization purpose.

Figure 4: Video to audio retrieval results. Since the spectrogram is hard to read, we show its paired image in dashed box just for visualization purpose.

Figure 5: CAV-MAE reconstruction samples when 50% of the input is masked. Samples are from VGGSound, a different dataset from the pretraining dataset. The model is pretrained on AudioSet with 75% masking ratio without target normalization.

Figure 6: CAV-MAE reconstruction samples when 75% of the input is masked. Samples are from VGGSound, a different dataset from the pretraining dataset. The model is pretrained on AudioSet with 75% masking ratio without target normalization.

Figure 7: CAV-MAE reconstruction samples when 90% of the input is masked. Samples are from VGGSound, a different dataset from the pretraining dataset. The model is pretrained on AudioSet with 75% masking ratio without target normalization.