H-DDx: A Hierarchical Evaluation Framework for Differential Diagnosis

Abstract

An accurate differential diagnosis (DDx) is essential for patient care, shaping therapeutic decisions and influencing outcomes. Recently, Large Language Models (LLMs) have emerged as promising tools to support this process by generating a DDx list from patient narratives. However, existing evaluations of LLMs in this domain primarily rely on flat metrics, such as Top-k accuracy, which fail to distinguish between clinically relevant near-misses and diagnostically distant errors. To mitigate this limitation, we introduce **H-DDx**, a hierarchical evaluation framework that better reflects clinical relevance. H-DDx leverages a retrieval and reranking pipeline to map free-text diagnoses to ICD-10 codes and applies a hierarchical metric that credits predictions closely related to the ground-truth diagnosis. In benchmarking 22 leading models, we show that conventional flat metrics underestimate performance by overlooking clinically meaningful outputs, with our results highlighting the strengths of domain-specialized open-source models. Furthermore, our framework enhances interpretability by revealing hierarchical error patterns, demonstrating that LLMs often correctly identify the broader clinical context even when the precise diagnosis is missed.

1 Introduction

Differential diagnosis (DDx) is a fundamental component of clinical reasoning, involving the systematic consideration of multiple possible conditions that could explain a patient's symptoms. This process is central to comprehensive case evaluation, as it enables the detection of critical yet subtle conditions, guides diagnostic testing, and promotes the efficient use of resources. Moreover, DDx enhances communication, fosters patient trust, and mitigates cognitive biases by compelling clinicians to consider a broad set of plausible explanations (Tierney and Henderson, 2007; Guyatt and Rennie, 2002; Rhoads and Penick, 2022). Despite its importance, medical diagnosis remains a cognitively demanding and high-stakes task, particularly in its early stages when uncertainty is greatest. Recently, Large Language Models (LLMs) have emerged as promising tools to support this process by generating a DDx list from patient narratives (Thirunavukarasu et al., 2023; Nashwan et al., 2023).

To assess how effectively LLMs can assist clinicians in the DDx process, rigorous evaluation is essential. However, existing evaluations of LLMs for DDx rely predominantly on simplistic metrics that inadequately reflect clinical utility, with most prior works (McDuff et al., 2025; Chen et al., 2025; Ríos-Hoyo et al., 2024; Bhasuran et al., 2025) focusing primarily on Top-k accuracy, which merely checks whether the final diagnosis appears in the DDx set. These approaches face two fundamental limitations. First, they reduce evaluation to mere inclusion or surface-level overlap, failing to capture the clinical value of the DDx set as a whole. A list that contains the ground-truth diagnosis but is cluttered with irrelevant or misleading suggestions may erode clinician trust and provide little practical support. Second, when computing Top-k accuracy, the determination of whether a predicted disease matches the ground-truth is often delegated to an LLM judge, introducing ambiguity and a lack of transparency. Because the matching criteria are implicit and prone to variation across different LLM judges or prompts, assessments become subjective and difficult to reproduce. This black-box paradigm fails to differentiate the severity of errors, lacking a principled or hierarchical framework. For instance, suggesting a viral upper respiratory infection for a case of influenza constitutes a clinically minor error, as both are respiratory conditions with overlapping symptoms. In contrast, suggesting a neurological condition like migraine for the same influenza case represents a far more significant diagnostic error, indicating a fundamental misunderstanding of

Figure 1: Comparison of the H-DDx framework and conventional flat metrics. For a patient with Influenza, flat metrics fail to distinguish between the clinically relevant DDx set from Prediction A (related respiratory infections) and the irrelevant list from Prediction B (e.g., Migraine), scoring both poorly. H-DDx uses the ICD-10 taxonomy for a more nuanced evaluation. By expanding differential diagnosis sets into the taxonomy, it identifies Prediction A's outputs as clinically relevant near-misses, while Prediction B's are distant errors. HDF1 score quantifies this distinction, capturing the superior clinical utility of Prediction A that flat metrics overlook.

the clinical presentation. Without such a structure, evaluations struggle to distinguish consistently and interpretably between clinically distinct errors.

To address these limitations, we propose **H-DDx**, a novel hierarchical evaluation framework for a more clinically meaningful assessment of differential diagnosis. As illustrated in Figure 1, conventional flat metrics fail to distinguish between clinically relevant near-misses and distant diagnostic errors, treating all incorrect predictions equally. This is a critical gap our framework aims to fill. By leveraging the structured knowledge within the International Classification of Diseases 10th Revision (ICD-10) taxonomy, H-DDx moves beyond simple accuracy to reward these diagnostically relevant suggestions. This allows for a more nuanced and interpretable analysis of an LLM's true clinical reasoning capabilities, revealing insights that conventional metrics overlook.

Through large-scale evaluation of 22 leading LLMs on a public benchmark, DDX-Plus (Fansi Tchango et al., 2022), we demonstrate the framework's effectiveness in providing a deeper understanding of model performance. Our main contributions are summarized as follows:

- We introduce **H-DDx**, a novel hierarchical evaluation framework that maps free-text diagnoses to the ICD-10 taxonomy and applies

a hierarchical metric for a more clinically nuanced assessment.

- Through a large-scale evaluation of 22 leading LLMs, we demonstrate that conventional flat metrics misrepresent models' differential diagnostic capabilities by penalizing clinically plausible, near-miss diagnoses as severely as entirely incorrect ones, thereby undervaluing domain-specialized models.

- Our framework enhances the interpretability of model behavior by identifying and analyzing hierarchical patterns in diagnostic performance, revealing that LLMs often grasp the correct clinical context even when they fail to pinpoint the exact diagnosis.

2 Related Work

2.1 LLMs for Differential Diagnosis

The application of Large Language Models (LLMs) to augment clinical decision-making has recently gained significant traction, particularly in the domain of differential diagnosis (DDx) (Thirunavukarasu et al., 2023; Nashwan et al., 2023; Dinc et al., 2025). Numerous studies have highlighted the potential of LLMs to generate a comprehensive DDx list from patient narratives

Figure 2: Overview of the H-DDx framework.

and clinical vignettes (McDuff et al., 2025; Zhou et al., 2025). The evaluation of these models has largely relied on conventional flat metrics such as Top-k accuracy, assessing whether the final diagnosis appears within the top predictions. While useful, this approach fails to credit clinically relevant near-misses, treating all diagnostic errors as equally severe. Our work moves beyond this limitation by introducing a hierarchical evaluation framework that captures the nuances of clinical reasoning.

2.2 Automated ICD Coding

Automated assignment of International Classification of Diseases (ICD) codes to clinical documentation is a well-established task in medical natural language processing (Mullenbach et al., 2018). Early approaches often utilized rule-based systems or traditional machine learning models, while more recent work has demonstrated the superior performance of deep learning architectures, including LLMs (Shi et al., 2017; Carberry and Xu, 2024; Li et al., 2018). Our work is distinct from automated coding; rather than predicting codes for billing or administrative purposes, we focus on developing a high-fidelity mapping from LLM-generated free-text diagnoses to a standardized taxonomy. This mapping serves as a foundational step to enable a more sophisticated, semantically aware evaluation of the models' diagnostic capabilities.

2.3 Hierarchical Classification

Hierarchical classification, where class labels are organized in a taxonomy, is a long-standing area of machine learning research (Silla and Freitas, 2011). Recognizing that not all errors are equal, researchers have developed specialized metrics that account for the hierarchical structure, such as hierarchical precision and recall (Kosmopoulos et al., 2015; Riehl et al., 2023; Lanus et al., 2025; Riehl et al., 2023). These metrics assign partial credit for misclassifications that are taxonomically close to the true label, providing a more fine-grained performance assessment than conventional flat metrics. Our framework leverages these established hierarchical evaluation principles, adapting them specifically to the clinical context of differential diagnosis assessment, where both the multi-label nature and the semantic relationships between diagnoses must be considered.

3 The H-DDx Framework

This section presents **H-DDx**, a hierarchical framework for evaluating the DDx capabilities of LLMs. Our framework consists of two steps: (i) a mapping pipeline that combines embedding-based retrieval with LLM reranking for high-accuracy conversion from free-text diagnoses to the ICD-10 codes, and (ii) the Hierarchical DDx F1 (HDF1) metric that performs set-based comparisons using ancestral code expansion within the ICD-10 taxonomy. The overall framework is illustrated in Figure 2.

3.1 Leveraging the ICD-10 Taxonomy

To quantify the clinical distance between predicted and ground-truth differential diagnoses, our H-DDx framework leverages the inherent hierarchy of the ICD-10. This globally adopted taxonomy structures medical conditions into a four-level tree, providing a standardized basis for our evaluation:

- **Chapter:** Groups diseases by major category, such as anatomical system (e.g., J00-J99: Diseases of the Respiratory System).

- **Section:** Clusters related conditions within a

chapter (e.g., J09-J18: Influenza and Pneumonia).

- **Category:** Specifies distinct diseases with a three-character code (e.g., J11: Influenza due to unidentified influenza virus).

- **Subcategory:** Offers the highest granularity for detailed classification (e.g., J11.1: Influenza due to unidentified influenza virus with other respiratory manifestations).

By grounding our evaluation in this structure, H-DDx can measure not just whether a diagnosis is correct, but how close an incorrect diagnosis is to the correct one. This hierarchical organization is not arbitrary but reflects clinical relationships. Conditions within the same branch typically share anatomical systems, pathophysiological mechanisms, or etiological origins. This medical grounding makes the ICD-10 taxonomy an ideal foundation for assessing the clinical quality of DDx predictions beyond binary correct/incorrect judgments.

3.2 Mapping Free-Text Diagnoses to ICD-10 Codes

Hierarchical evaluation requires mapping free-text diagnosis from LLMs to a standardized clinical taxonomy, such as ICD-10. Our mapping pipeline combines embedding-based retrieval and LLM-based reranking for high accuracy. For each free-text diagnosis, we first use the `text-embedding-3-large` model to retrieve the top-k candidate ICD-10 codes. An LLM-based reranker then identifies the best match from these candidates. We validated this approach on a benchmark set of 101 diagnoses, manually mapped by clinicians, achieving a Top-1 accuracy of 93.1%. The reranking stage proved critical, improving upon the retrieval-only accuracy of 71.3%. This multi-step process ensures that the final mapping is not only semantically similar but also clinically appropriate as judged by a state-of-the-art LLM. Detailed performances are provided in Table 1.

To ensure a fair comparison across all models, we first compile a comprehensive set of all unique DDx generated across all models evaluated. This unified set was then mapped to ICD-10 codes to create a single, canonical reference table. By applying this same mapping table to every model's output, we eliminate any potential bias from the mapping process itself.

	Model	Top-1
Top-k Retrieval	biobert-v1.1	0.4653
	BioSimCSE-BioLinkBERT-BASE	0.5446
	Qwen3-Embedding-0.6B	0.5842
	pubmedbert-base-embeddings	0.6436
	text-embedding-3-large	0.7129
LLM Reranking *(on best retriever)*	+ gemini-2.5-flash-lite	0.8317
	+ gpt-4o-mini	0.8614
	+ gemini-2.5-flash	0.8713
	+ gpt-4o	**0.9307**

Table 1: Comparison of models for mapping free-text diagnoses to ICD-10 codes. The table presents the Top-1 accuracy of various embedding models for retrieval and the subsequent improvements from applying LLM rerankers to the best-performing retriever.

An error analysis of the pipeline's failures revealed that they were not random errors, but systematic and clinically adjacent near-misses. Since all observed errors were correct at the immediate parent level in the ICD-10 taxonomy, these minor inaccuracies do not compromise the validity of our hierarchical evaluation. This finding confirms the pipeline's robustness for its intended use. Further details are available in Appendix A.

3.3 A Hierarchical Evaluation Metric

The core of our framework is the Hierarchical DDx F1 (HDF1) metric, an extension of the standard F1-score designed to measure clinical utility by leveraging the ICD-10 taxonomy. Whereas conventional flat metrics treat diagnoses as isolated labels, HDF1 evaluates them within their ancestral context in the ICD-10 taxonomy. This enables a more nuanced and clinically grounded assessment that reflects clinical realities.

HDF1 builds upon established hierarchical precision and recall measures from multi-label hierarchical classification (Kiritchenko et al., 2006). To formalize this, the calculation of HDF1 begins by expanding the sets of ground-truth and predicted DDx to include all their ancestral nodes in the hierarchy. For a given patient case i, let D_i be the ground-truth DDx set and $\hat{D}_i$ be the predicted set. We define an augmentation function, $\text{Augment}(S)$, which augments the set S by adding all ancestral nodes for each diagnosis in S, from its immediate parent up to the chapter level in the ICD-10 taxonomy. The augmented sets for comparison are therefore $C_i = \text{Augment}(D_i)$ and $\hat{C}_i = \text{Augment}(\hat{D}_i)$.

Based on these augmented sets, Hierarchical DDx Precision (HDP) and Hierarchical DDx Recall (HDR) are computed. The scores are calculated

per patient case and then macro-averaged across the dataset to ensure each case contributes equally. HDF1 is the harmonic mean of the resulting HDP and HDR, as defined in eqs. (1) to (3):

$$\text{HDP} = \frac{1}{N} \sum_{i=1}^{N} \frac{|C_i \cap \hat{C}_i|}{|\hat{C}_i|}, \qquad (1)$$

$$\text{HDR} = \frac{1}{N} \sum_{i=1}^{N} \frac{|C_i \cap \hat{C}_i|}{|C_i|}, \qquad (2)$$

$$\text{and HDF1} = \frac{2 \times \text{HDP} \times \text{HDR}}{\text{HDP} + \text{HDR}} \qquad (3)$$

where N is the total number of patient cases.

4 Experimental Setup

4.1 Datasets

Our evaluation utilizes DDXPlus (Fansi Tchango et al., 2022), a large-scale synthetic benchmark dataset for differential diagnosis. Recognized for its complex and diverse medical cases, comprising over 1.3 million synthetic Electronic Health Record (EHR) patient records across 49 distinct pathologies. The research community widely adopts it to benchmark models for diagnosis tasks (Chen et al., 2023; Li and Ruan, 2024; Tam et al., 2024; Xie et al., 2024). The dataset features comprehensive patient information, including socio-demographics, underlying conditions, symptoms, and antecedents (i.e., medical history). Each patient record contains approximately 10 symptoms and 3 antecedents on average, which helps bridge the symptom data gap prevalent in real-world EHR datasets like MIMIC. To create a cost-effective yet representative test set, we selected 730 cases from the full DDXPlus dataset via stratified sampling (Neyman, 1992). This approach ensures that the distribution of pathologies in our subset faithfully reflects that of the original benchmark, providing a robust foundation for our evaluation.

4.2 Models

In this work, we evaluated the performance of 22 LLMs, comprising 11 proprietary and 11 open-source models, focusing on their direct, non-reasoning capabilities. For proprietary models, we covered available versions of OpenAI's GPT series (Hurst et al., 2024), Google's Gemini (Team et al., 2023), and Anthropic's Claude (Anthropic, 2025). The open-source models included leading models such as Google's Gemma (Team et al., 2025), Alibaba's Qwen (Yang et al., 2025), and Microsoft's Phi (Abdin et al., 2024). Additionally, we evaluated models trained for clinical context such as MedGemma (Sellergren et al., 2025) (adapted from Gemma3) and MediPhi (Corbeil et al., 2025) (adapted from Phi). A detailed list of the specific model versions used is available in Appendix B.

4.3 Evaluation Protocol

For each patient case, models were prompted to predict a list of five differential diagnoses based on the chief complaint and history of present illness. We evaluated these predictions using both a hierarchical evaluation with our proposed H-DDx framework and a conventional flat evaluation to benchmark against prior work.

Hierarchical Evaluation Our primary evaluation is based on the HDF1 score, which requires mapping the varied free-text diagnoses to a standardized taxonomy. To illustrate the necessity of this process, we first quantified the scale and diversity of the raw diagnoses generated by the 22 LLMs. For the DDXPlus test set, the models produced 80,300 diagnoses, comprising 4,905 unique free-text strings. This sheer volume of unstructured terms underscores the need for a systematic mapping pipeline to enable a principled, hierarchical comparison. As detailed in Section 3.2, our pipeline standardizes these outputs into 1,507 unique ICD-10 codes. Based on these standardized codes, we calculate the HDF1 score (detailed in Section 3.3) to provide a nuanced assessment of clinical relevance.

Flat Evaluation For comparison, we also computed Top-5 Accuracy, a conventional flat metric. Following prior work (McDuff et al., 2025), we use an LLM to judge the correctness of disease names. Top-5 Accuracy assesses whether the predicted DDx set contains the ground-truth diagnosis. We used `gpt-4o` to judge semantic equivalence between the predicted and ground-truth. The prompt used for this evaluation, adopted from prior work, is detailed below.

Top-5 Accuracy Evaluation Prompt

```
Is our predicted diagnosis correct
(y/n)?
Predicted diagnosis: [diagnosis], True
diagnosis: [label] Answer [y/n].
```

Model	Top-5	HDF1	ΔRank
Proprietary Models			
Claude-Haiku-3.5	0.7630	0.3237	↓ 3
Claude-Sonnet-3.7	0.8360	0.3380	↓ 6
Claude-Sonnet-4	**0.8390**	**0.3673**	–
Gemini-2.5-Flash-Lite	0.7890	0.3496	↑ 2
Gemini-2.5-Flash	0.8320	0.3483	↓ 2
GPT-4o-mini	0.7240	0.3276	↑ 3
GPT-4o	0.8040	0.3499	↑ 1
GPT-4.1-nano	0.7660	0.3213	↓ 9
GPT-4.1-mini	0.7590	0.3232	↓ 2
GPT-4.1	0.8010	0.3387	↓ 2
GPT-5	0.7830	0.3448	↑ 1
Open-source Models			
Phi-3.5-mini	0.6550	0.3187	↑ 1
Gemma3-4B	0.6080	0.2891	–
Gemma3-12B	0.7180	0.3075	↓ 3
Gemma3-27B	0.7460	0.3225	↓ 2
Qwen2.5-72B	0.7420	0.3299	↑ 4
Qwen3-4B	0.6720	0.3291	↑ 6
Qwen3-14B	0.7750	0.3367	–
Qwen3-32B	0.7630	0.3300	↑ 2
Qwen3-235B-A22B	0.7770	0.3215	↓ 10
Medical Fine-tuned Models			
MedGemma-27B	0.7650	0.3310	↑ 1
MediPhi	0.6660	0.3526	↑ 18

Table 2: Main evaluation results. We compare LLMs using Top-5 Accuracy (Top-5) and our proposed Hierarchical DDx F1-score (HDF1). The Δ Rank indicates the change in rank from Top-5 Accuracy to HDF1. The best score for each metric is in **bold**, and the second-best is underlined.

A prediction was marked as correct if the model output 'y'. Full details for reproducibility are provided in Appendix B.

5 Results and Analysis

Our experimental results indicate that H-DDx offers a more effective evaluation of the diagnostic capabilities of various models. The analysis suggests that the proposed HDF1 metric not only identifies hidden strengths of domain-specialized models previously underestimated by conventional flat metrics but also provides interpretable insights into hierarchical diagnostic patterns. Through comprehensive experiments and case studies, our findings suggest that H-DDx produces more clinically meaningful evaluations that better align with practical healthcare needs.

5.1 Strengths of Domain-Specialized Models Identified by H-DDx

The most significant impact of applying HDF1 was a substantial reordering of model rankings. Our hierarchical approach reveals the true capabilities of clinically specialized models that were systematically undervalued by flat metrics.

As shown in Table 2, this approach leads to substantial changes in model rankings, particularly for domain-specialized models whose strengths were previously underestimated. A notable example is MediPhi, which improves by 18 ranks, rising from 20th in Top-5 Accuracy to 2nd in HDF1. However, this effect was not observed uniformly across all specialized models. MedGemma showed more modest gains, highlighting the variable impact of domain-specific fine-tuning, as detailed in Appendix D.

This significant improvement stems from HDF1's ability to reward clinically relevant differential diagnoses, an important aspect of diagnostic reasoning that flat metrics penalize. These domain-specialized models may not always identify the precise subcategory-level diagnosis, but they consistently generate a DDx list that is coherent within the correct medical domain. Our findings demonstrate that conventional benchmarks, by focusing solely on exact-match accuracy, consistently underestimate models that produce diagnostically sound and clinically useful suggestions. This behavioral profile may arise because medical domain-tuning strengthens a model's understanding of broad clinical categories, while the long tail of rare or highly specific sub-diagnoses remains underrepresented in training data. These findings suggest that smaller, domain-focused models could potentially offer a more reliable and effective solution for healthcare institutions than larger, general-purpose models.

The substantial ranking shifts observed above raise important questions about the underlying diagnostic patterns that distinguish these models. To address this, we leverage the hierarchical analysis capabilities of H-DDx to examine how models achieve their diagnostic performance across different levels of specificity.

5.2 Enhanced Interpretability of Model Performance

Beyond providing scores, H-DDx serves as an interpretive framework that reveals the diagnostic reasoning patterns of models. By analyzing perfor-

Figure 3: Hierarchical cascade pattern in diagnostic performance across ICD-10 levels. The overlapping bars show HDF1 scores calculated for each hierarchy level, with models sorted by their performance at the Subcategory level.

mance across hierarchy levels, we identified fundamental limitations shared by all evaluated models.

As shown in Figure 3, HDF1 scores are calculated independently for each ICD-10 taxonomy level (Chapter, Section, Category, and Subcategory) across all models. This visualization reveals a universal hierarchical cascade pattern where all models exhibit consistent performance degradation, with performance at the Chapter level reaching approximately 60%, declining progressively through Section (~40%), Category (~30%), to Subcategory (10-20%).

This hierarchical cascade pattern exposes fundamental limitations in current evaluation practices. This nuanced performance distribution remains invisible to conventional flat metrics. Exact-match approaches fail to recognize diagnostically relevant but inexact answers, while LLM-based judges, despite potentially recognizing partial correctness, lack consistent clinical criteria for evaluation.

In contrast, HDF1 leverages the medically established ICD-10 taxonomy to provide systematic and reproducible partial credit, acknowledging that correctly identifying the broader medical domain represents genuine diagnostic capability even when the specific diagnosis is missed.

Our hierarchical analysis reveals distinct diagnostic profiles and explains the ranking shifts observed in Section 5.1. MediPhi, despite its low flat-metric accuracy, demonstrates strong performance at Chapter, Section, and Category levels, confirming that domain-specific fine-tuning successfully enhances broad clinical reasoning even when rare or highly specific diagnoses remain challenging. Comparing general-purpose models, GPT-4o exhibits a smooth performance degradation across all levels, while GPT-5 shows irregular performance with strong results at Chapter and Subcategory but weaker results at intermediate levels. This pattern suggests that consistent hierarchical reasoning may be more valuable than sporadic accuracy at specific levels.

By decomposing model performance across diagnostic hierarchies, H-DDx transforms evaluation from a binary assessment into a comprehensive analysis of clinical reasoning capabilities. Consequently, H-DDx enables more informed model selection by matching specific clinical requirements with model capabilities, whether for initial diagnostic screening or precise subspecialty identification.

Although these aggregate patterns reveal important insights, individual case studies best illustrate the clinical value of H-DDx.

5.3 Clinical Validation of HDF1 through Case Studies

To demonstrate the clinical significance of our HDF1 score, we present two distinct case studies, with additional cases provided in Appendix F. These cases exemplify how conventional flat met-

Patient Case	Final Diagnosis	Ground-Truth DDx	Model	Top-5 Acc.	HDF1	Predicted DDx Set & ICD-10 Codes
48/F with complex respiratory history	Bronchiectasis (J47)	Bronchitis (J40) Pulm. neoplasm (C34) Tuberculosis (A15) Bronchiectasis (J47) Ac. pulm. edema (J81.0)	GPT-4o	1.0	0.2069	Bronchiectasis (J47) Pulmonary Hemorrhage (R04.89) COPD (J44.9) Pulmonary Embolism (I26) Infectious Pneumonia (J16.8)
			MediPhi	0.0	**0.5714**	Pneumonia (J18) Bronchitis (J40) Tuberculosis (A15-A19) Pulmonary Embolism (I26) Lung Cancer (C34.90)

Table 3: Comparative analysis of model performance on two distinct clinical scenarios. HDF1 reveals nuanced clinical reasoning capabilities that Top-5 Accuracy misses. Higher HDF1 scores are shown in bold.

rics, such as Top-5 Accuracy, can be misleading or uninformative, while HDF1 accurately assesses a model's clinical reasoning. The first case highlights a scenario where a domain-specialized model demonstrates superior clinical reasoning over a general-purpose proprietary model, despite having a lower accuracy score. The second case illustrates an instance where HDF1 reveals the impact of medical fine-tuning by distinguishing between a base model and its specialized counterpart.

Case Study: Specialist Coherence over Generalist Accuracy   Our case involves a 48-year-old female with a complex respiratory history, including cystic fibrosis and rheumatoid arthritis. The ground-truth diagnosis is Bronchiectasis (J47). As detailed in Table 3, the Top-5 Accuracy metric provides a potentially misleading assessment. The general-purpose model, GPT-4o, correctly includes Bronchiectasis and achieves a perfect Top-5 Accuracy of 1.0. In contrast, the domain-specialized model, MediPhi, fails to list the exact term, resulting in an Accuracy of 0.0. Based on this metric alone, GPT-4o's performance appears far superior.

However, HDF1 offers a contrasting evaluation, assigning MediPhi a substantially higher score (0.5714) compared to GPT-4o (0.2069). A clinical review validates this assessment. The list from MediPhi, including diagnoses like Pneumonia and Bronchitis, represents a clinically coherent differential for a patient whose underlying conditions, such as cystic fibrosis, increase susceptibility to respiratory infections. HDF1 captures this clinical relevance by recognizing that these suggestions are taxonomically close to the ground-truth. For instance, Pneumonia (J18) and Bronchitis (J40) fall within the same ICD-10 chapter (J00-J99) as Bronchiectasis (J47), allowing the framework to reward the model for correctly identifying the af-

fected organ system. Conversely, GPT-4o's DDx set, despite containing the correct answer, is less focused, including a symptom (Pulmonary Hemorrhage) rather than a distinct diagnosis. This case illustrates how HDF1 prioritizes the clinical utility of the entire DDx set over a single correct prediction.

6   Conclusion

In this paper, we present **H-DDx**, a novel hierarchical evaluation framework designed to address the limitations of conventional flat metrics in assessing LLMs for DDx. Existing metrics, such as Top-k accuracy, fail to distinguish between clinically relevant near-misses and diagnostically distant errors, thereby providing an incomplete picture of a model's true utility. H-DDx overcomes this by mapping free-text diagnoses to the ICD-10 taxonomy and applying the HDF1 that credits predictions hierarchically close to the ground-truth. Through a large-scale evaluation of 22 leading LLMs, we demonstrated that conventional flat metrics systematically underestimate the performance of clinically coherent models, particularly domain-specialized ones. Furthermore, H-DDx enhances interpretability by enabling a hierarchical analysis of error patterns, revealing that LLMs often correctly identify the broader clinical context even when the precise diagnosis is missed.

Limitation and Future Work

Our study has several limitations. First, our evaluation uses the DDXPlus synthetic dataset. While it is the largest public benchmark with over 1.3 million cases, validation on real-world clinical data remains essential. Second, the H-DDx framework relies on ICD-10, which, despite being the global standard ensuring reproducibility, may not capture

all clinical nuances. Third, we evaluate static differential diagnosis lists rather than the sequential reasoning inherent to clinical practice. Nevertheless, H-DDx demonstrates significant improvements over flat metrics by recognizing clinically relevant near-misses and revealing domain-specialized models' strengths. Our mapping pipeline's high accuracy (93.1%) further validates the approach, establishing a strong baseline that can be iteratively refined with expert clinical review.

Future work will pursue three directions. First, we will validate H-DDx on real-world EHR data to establish correlations between HDF1 scores and clinical utility. Second, we will explore richer ontologies like SNOMED CT and data-driven hierarchies to capture additional clinical nuances. Third, we will extend the framework to evaluate interactive diagnostic agents that iteratively refine diagnoses through information gathering. These advances will support the development of AI systems that meaningfully augment clinical decision-making.

References

Marah Abdin, Jyoti Aneja, Harkirat Behl, Sébastien Bubeck, Ronen Eldan, Suriya Gunasekar, Michael Harrison, Russell J Hewett, Mojan Javaheripi, Piero Kauffmann, et al. 2024. Phi-4 technical report. *arXiv preprint arXiv:2412.08905*.

Anthropic. 2025. Introducing claude 4. https://www.anthropic.com/news/claude-4.

Balu Bhasuran, Qiao Jin, Yuzhang Xie, Carl Yang, Karim Hanna, Jennifer Costa, Cindy Shavor, Wenshan Han, Zhiyong Lu, and Zhe He. 2025. Preliminary analysis of the impact of lab results on large language model generated differential diagnoses. *npj Digital Medicine*, 8(1):166.

Joshua Carberry and Haiping Xu. 2024. Gpt-enhanced hierarchical deep learning model for automated icd coding. *Advances in Science, Technology and Engineering Systems Journal (ASTESJ)*, 9(4):21–34.

Siyuan Chen, Mengyue Wu, Kenny Q Zhu, Kunyao Lan, Zhiling Zhang, and Lyuchun Cui. 2023. Llm-empowered chatbots for psychiatrist and patient simulation: application and evaluation. *arXiv preprint arXiv:2305.13614*.

Xi Chen, Huahui Yi, Mingke You, WeiZhi Liu, Li Wang, Hairui Li, Xue Zhang, Yingman Guo, Lei Fan, Gang Chen, et al. 2025. Enhancing diagnostic capability with multi-agents conversational large language models. *NPJ digital medicine*, 8(1):159.

Jean-Philippe Corbeil, Amin Dada, Jean-Michel Attendu, Asma Ben Abacha, Alessandro Sordoni, Lucas Caccia, François Beaulieu, Thomas Lin, Jens Kleesiek, and Paul Vozila. 2025. A modular approach for clinical slms driven by synthetic data with pre-instruction tuning, model merging, and clinical-tasks alignment. *arXiv preprint arXiv:2505.10717*.

Mehmed T Dinc, Ali E Bardak, Furkan Bahar, and Craig Noronha. 2025. Comparative analysis of large language models in clinical diagnosis: performance evaluation across common and complex medical cases. *JAMIA open*, 8(3).

Arsene Fansi Tchango, Rishab Goel, Zhi Wen, Julien Martel, and Joumana Ghosn. 2022. Ddxplus: A new dataset for automatic medical diagnosis. *Advances in neural information processing systems*, 35:31306–31318.

Gordon Guyatt and Drummond Rennie. 2002. *Users' Guides to the Medical Literature: A Manual for Evidence-Based Clinical Practice*. AMA Press.

Aaron Hurst, Adam Lerer, Adam P Goucher, Adam Perelman, Aditya Ramesh, Aidan Clark, AJ Ostrow, Akila Welihinda, Alan Hayes, Alec Radford, et al. 2024. Gpt-4o system card. *arXiv preprint arXiv:2410.21276*.

Svetlana Kiritchenko, Stan Matwin, Richard Nock, and A Fazel Famili. 2006. Learning and evaluation in the presence of class hierarchies: Application to text categorization. In *Conference of the Canadian society for computational studies of intelligence*, pages 395–406. Springer.

Aris Kosmopoulos, Ioannis Partalas, Éric Gaussier, Georgios Paliouras, and Ion Androutsopoulos. 2015. Evaluation measures for hierarchical classification: a unified view and an analysis. *Data Mining and Knowledge Discovery*, 29:820–865.

Erin Lanus, Daniel Wolodkin, and Laura J Freeman. 2025. Hierarchical scoring for machine learning classifier error impact evaluation. *arXiv preprint arXiv:2508.04489*.

Min Li, Zhihui Fei, Min Zeng, Fang-Xiang Wu, Yaohang Li, Yi Pan, and Jianxin Wang. 2018. Automated icd-9 coding via a deep learning approach. *IEEE/ACM transactions on computational biology and bioinformatics*, 16(4):1193–1202.

Zhiang Li and Tong Ruan. 2024. Knowledge-routed automatic diagnosis with heterogeneous patient-oriented graph. *IEEE Access*, 12:89573–89584.

Daniel McDuff, Mike Schaekermann, Tao Tu, Anil Palepu, Amy Wang, Jake Garrison, Karan Singhal, Yash Sharma, Shekoofeh Azizi, Kavita Kulkarni, et al. 2025. Towards accurate differential diagnosis with large language models. *Nature*, pages 1–7.

James Mullenbach, Sarah Wiegreffe, Jon Duke, Jimeng Sun, and Jacob Eisenstein. 2018. Explainable prediction of medical codes from clinical text. *arXiv preprint arXiv:1802.05695*.

Abdulqadir J Nashwan, Ahmad A AbuJaber, and Ahmad AbuJaber. 2023. Harnessing the power of large language models (llms) for electronic health records (ehrs) optimization. *Cureus*, 15(7).

Jerzy Neyman. 1992. On the two different aspects of the representative method: the method of stratified sampling and the method of purposive selection. In *Breakthroughs in statistics: Methodology and distribution*, pages 123–150. Springer.

Jannifer Rhoads and Jessica Penick. 2022. *Advanced Health Assessment and Differential Diagnosis: Essentials for Clinical Practice*. Springer Publishing Company.

Kevin Riehl, Michael Neunteufel, and Martin Hemberg. 2023. Hierarchical confusion matrix for classification performance evaluation. *Journal of the Royal Statistical Society Series C: Applied Statistics*, 72(5):1394–1412.

Alejandro Ríos-Hoyo, Naing Lin Shan, Anran Li, Alexander T Pearson, Lajos Pusztai, and Frederick M Howard. 2024. Evaluation of large language models as a diagnostic aid for complex medical cases. *Frontiers in medicine*, 11:1380148.

Andrew Sellergren, Sahar Kazemzadeh, Tiam Jaroensri, Atilla Kiraly, Madeleine Traverse, Timo Kohlberger, Shawn Xu, Fayaz Jamil, Cían Hughes, Charles Lau, et al. 2025. Medgemma technical report. *arXiv preprint arXiv:2507.05201*.

Haoran Shi, Pengtao Xie, Zhiting Hu, Ming Zhang, and Eric P. Xing. 2017. Towards automated icd coding using deep learning. *arXiv preprint arXiv:1711.04075*.

Carlos N Silla and Alex A Freitas. 2011. A survey of hierarchical classification across different application domains. *Data Mining and Knowledge Discovery*, 22:31–72.

Zhi Rui Tam, Cheng-Kuang Wu, Yi-Lin Tsai, Chieh-Yen Lin, Hung-yi Lee, and Yun-Nung Chen. 2024. Let me speak freely? a study on the impact of format restrictions on performance of large language models. *arXiv preprint arXiv:2408.02442*.

Gemini Team, Rohan Anil, Sebastian Borgeaud, Jean-Baptiste Alayrac, Jiahui Yu, Radu Soricut, Johan Schalkwyk, Andrew M Dai, Anja Hauth, Katie Millican, et al. 2023. Gemini: a family of highly capable multimodal models. *arXiv preprint arXiv:2312.11805*.

Gemma Team, Aishwarya Kamath, Johan Ferret, Shreya Pathak, Nino Vieillard, Ramona Merhej, Sarah Perrin, Tatiana Matejovicova, Alexandre Ramé, Morgane Rivière, et al. 2025. Gemma 3 technical report. *arXiv preprint arXiv:2503.19786*.

Arun James Thirunavukarasu, Darren Shu Jeng Ting, Kabilan Elangovan, Laura Gutierrez, Ting Fang Tan, and Daniel Shu Wei Ting. 2023. Large language models in medicine. *Nature medicine*, 29(8):1930–1940.

Lawrence M. Tierney and Mark C. Henderson. 2007. The patient history: Evidence-based approach. In Stephen J. McPhee and Maxine A. Papadakis, editors, *Current Medical Diagnosis & Treatment*, 46th edition, pages 1–7. McGraw-Hill Medical.

Yunfei Xie, Juncheng Wu, Haoqin Tu, Siwei Yang, Bingchen Zhao, Yongshuo Zong, Qiao Jin, Cihang Xie, and Yuyin Zhou. 2024. A preliminary study of o1 in medicine: Are we closer to an ai doctor? *arXiv preprint arXiv:2409.15277*.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, et al. 2025. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*.

Shuang Zhou, Zidu Xu, Mian Zhang, Chunpu Xu, Yawen Guo, Zaifu Zhan, Yi Fang, Sirui Ding, Jiashuo Wang, Kaishuai Xu, et al. 2025. Large language models for disease diagnosis: A scoping review. *npj Artificial Intelligence*, 1(1):9.

A Mapping Pipeline Details

This section provides a detailed, step-by-step description of our pipeline for mapping free-text diagnoses to standardized ICD-10 codes. The pipeline is designed for high accuracy by combining efficient embedding-based retrieval with the nuanced understanding of a large language model for reranking.

A.1 Candidate Retrieval

The initial stage focuses on retrieving a set of relevant ICD-10 code candidates for a given free-text diagnosis.

Knowledge Base Construction We first constructed a knowledge base from the official ICD-10 hierarchical data. This process involved parsing the entire taxonomy, including chapters, sections, and individual diagnostic codes. To maximize coverage, we extracted not only the primary descriptive name for each code but also all associated inclusion terms (i.e., synonyms and related conditions). This resulted in a comprehensive set of {ICD Name, ICD Code} pairs that serves as the target for our mapping.

Embedding Model	Top-1 Acc	Top-5 Acc	Top-15 Acc
biobert-v1.1	0.4653	0.6931	0.7525
BioSimCSE-BioLinkBERT-BASE	0.5446	0.7030	0.8218
Qwen3-Embedding-0.6B	0.5842	0.8020	0.9307
pubmedbert-base-embeddings	0.6436	0.8218	0.9109
text-embedding-3-large	**0.7129**	**0.9208**	**0.9901**

Table 4: Embedding model performance

Embedding and Indexing To select the best embedding model for our retrieval task, we benchmarked a diverse set of models. This included models pre-trained on biomedical corpora, such as `biobert-v1.1`, `BioSimCSE-BioLinkBERT-BASE`, and `pubmedbert-base-embeddings`, as well as general-purpose models like `Qwen3-Embedding-0.6B` and OpenAI's `text-embedding-3-large`. As shown in Table 4, `text-embedding-3-large` significantly outperformed the others, achieving the highest Top-1 retrieval accuracy. Consequently, each unique ICD name in our knowledge base was embedded using this model. These high-dimensional vector representations were pre-computed and stored as a NumPy array, creating an efficient index for fast similarity searches. For each free-text diagnosis, we embed it using the same model and perform a cosine similarity search against this index to retrieve the top 15 candidates.

A.2 LLM-based Reranking

The second stage uses a powerful LLM to select the single best match from the candidate list generated in the previous stage.

Model and Prompting We use `gpt-4o` as our reranker. The model is provided with a carefully structured prompt containing the original free-text diagnosis and the list of the 15 candidate ICD names retrieved in the first stage. The prompt, detailed below, instructs the model to act as a deterministic assistant, select exactly one item from the provided candidate list, and return its choice in a structured JSON format. This strict output formatting is crucial for ensuring the reliability and programmatic usability of the model's response.

System Prompt

```
You   are   a   careful,   deterministic
assistant.
Given one pathology/disease name and a
list of candidate disease names,
you   must   select   exactly   one   item
strictly from the given
candidate  list.  Return  JSON  with  a
single key icd_name.
Do not add any other keys.
```

User Prompt Example

```
Patient pathology: Chronic bronchitis

Candidates  (choose  exactly  one  from
these names):
1. Chronic tracheobronchitis
2. Chronic emphysematous bronchitis
3. chronic obstructive bronchitis
4. Unspecified chronic bronchitis
5. Simple chronic bronchitis
6.   Chronic   asthmatic   (obstructive)
bronchitis
7. Chronic bronchitis NOS
8. Acute bronchitis
9. chronic emphysematous bronchitis
10. Mucopurulent chronic bronchitis
11. Chronic cough
12.   chronic   bronchitis   with   airway
obstruction
13. chronic bronchitis with emphysema
14.   Mixed   simple   and   mucopurulent
```

```
chronic bronchitis
15. chronic asthmatic (obstructive)
bronchitis

Instruction: Pick the single best
candidate by name only.
Output JSON only.
```

Final Selection The JSON output from the LLM, which contains the chosen ICD name, is then parsed. We match this name back to the candidate list to identify the corresponding ICD-10 code. This code is considered the final, standardized mapping for the input free-text diagnosis. This multi-step process ensures that the final mapping is not only semantically similar but also clinically appropriate as judged by a state-of-the-art LLM.

A.3 Pipeline Validation and Error Analysis

To validate the pipeline's accuracy, we benchmarked it against a set of 101 diagnoses that were manually mapped to ICD-10 codes by clinicians. The retrieval-only stage achieved a Top-1 accuracy of 71.3%. By adding the LLM reranking stage, the accuracy significantly increased to 93.1%.

A qualitative analysis of the remaining errors revealed that they were not random but consisted of systematic, clinically adjacent near-misses. Table 5 shows incorrect Top-1 predictions from our validation set.

In the majority of observed failure cases, the predicted code was either clinically related or correct at the immediate parent level in the ICD-10 taxonomy. These minor taxonomic shifts do not compromise the integrity of our hierarchical evaluation, confirming the pipeline's robustness for its intended purpose.

B Evaluation Details

To ensure the reproducibility of our results, this section provides comprehensive details of our evaluation setup. This includes the prompts used for querying the models, API parameters, and any data preprocessing steps.

B.1 Models

The following is a comprehensive list of the 22 LLMs evaluated in this study, including their specific versions. We evaluated 11 proprietary models and 11 open-source models. The model checkpoints for open-source models are downloaded from `https://huggingface.co/`. The specific models and their sources are as follows:

Proprietary Models

- **Claude-Haiku-3.5**: `claude-3-5-haiku-20241022`
- **Claude-Sonnet-3.7**: `claude-3-7-sonnet-20250219`
- **Claude-Sonnet-4**: `claude-sonnet-4-20250514`
- **Gemini-2.5-Flash-Lite**: `gemini-2.5-flash-lite`
- **Gemini-2.5-Flash**: `gemini-2.5-flash`
- **GPT-4o-mini**: `gpt-4o-mini-2024-07-18`
- **GPT-4o**: `gpt-4o-2024-08-06`
- **GPT-4.1-nano**: `gpt-4.1-nano-2025-04-14`
- **GPT-4.1-mini**: `gpt-4.1-mini-2025-04-14`
- **GPT-4.1**: `gpt-4.1-2025-04-14`
- **GPT-5**: `gpt-5-chat-latest`

Open-source Models

- **Gemma3-4B**: `https://huggingface.co/google/gemma-3-4b-it`
- **Gemma3-12B**: `https://huggingface.co/google/gemma-3-12b-it`
- **Gemma3-27B**: `https://huggingface.co/ISTA-DASLab/gemma-3-27b-it-GPTQ-4b-128g`
- **Qwen2.5-72B**: `https://huggingface.co/Qwen/Qwen2.5-72B-Instruct-AWQ`
- **Qwen3-4B**: `https://huggingface.co/Qwen/Qwen3-4B`
- **Qwen3-14B**: `https://huggingface.co/Qwen/Qwen3-14B`
- **Qwen3-32B**: `https://huggingface.co/Qwen/Qwen3-32B-AWQ`
- **Qwen3-235B-A22B**: `https://huggingface.co/QuantTrio/Qwen3-235B-A22B-Instruct-2507-AWQ`
- **Phi-3.5-Mini**: `https://huggingface.co/microsoft/Phi-3.5-mini-instruct`

Disease name	ICD-10 code (by clinicians)	Mapped Disease name	Mapped ICD-10 code
Alcoholic steatohepatitis	K70.0	Alcoholic hepatitis	K70.1
Cervical disc herniation	M50.0	Other cervical disc displacement	M50.2
Drug-induced acute kidney injury	N17.0	Drug- and heavy-metal-induced tubulo-interstitial and tubular conditions	N14
Lumbar compression fracture	S32.0	Wedge compression fracture of unspecified lumbar vertebra	S32.000
sleep disorder	G47.9	Sleep disorders	G47
Drug-induced acute kidney injury	N17.0	Drug- and heavy-metal-induced tubulo-interstitial and tubular conditions	N14
Transient fatigue	R53.83	Heat fatigue, transient	T67.6

Table 5: Error Analysis: Incorrect Top-1 Predictions.

Medical Fine-tuned Models

- **MedGemma-27B**: https://huggingface.co/google/medgemma-27b-text-it

- **MediPhi**: https://huggingface.co/microsoft/MediPhi-Instruct

B.2 Prompts for DDx Generation

All models were evaluated using a consistent zero-shot prompting strategy with structured input and output formats.

> **System Prompt**
> ```
> You are a diagnostic assistant.
> Based on the patient's clinical
> information, provide a differential
> diagnosis.
> Return the response in JSON format.
> ```

The user prompt instructed models to provide the top 5 most likely differential diagnoses based on patient information (sex, age, and clinical evidence in question-answer format):

> **User Prompt**
> ```
> Based on the following patient
> information, provide the top 5 most
> likely differential diagnoses in
> probability order.
> For each diagnosis, provide the English
> medical term. Do not include any other
> text in your response without the JSON
> format.
>
> Patient Information:
> {patient_information}
>
> Please provide the response in a JSON
> object with a single key "diagnoses",
> which is a list of text.
> Example format:
> {{
> "diagnoses":          ["Pneumonia",
> "Bronchitis",  "Influenza",  "URTI",
> "Asthma"]
> }}
> ```

ICD-10 Chapter	Number of Diagnosis
Diseases of the respiratory system (J00-J99)	532
Diseases of the circulatory system (I00-I99)	454
Certain infectious and parasitic diseases (A00-B99)	248
Diseases of the nervous system (G00-G99)	189
Injury, poisoning and other consequences of external causes (S00-T88)	168
Diseases of the blood and blood-forming organs (D50-D89)	149
Diseases of the digestive system (K00-K95)	121
Mental and behavioural disorders (F01-F99)	114
Neoplasms (C00-D49)	111
Diseases of the musculoskeletal system and connective tissue (M00-M99)	27
Symptoms, signs and abnormal clinical and laboratory findings (R00-R99)	18
Diseases of the ear and mastoid process (H60-H95)	9

Table 6: Distribution of ground-truth DDx by ICD-10 chapter in the evaluation dataset.

B.3 Inference Configuration

To maintain consistency, we used standardized inference parameters for all models.

- **Temperature:** Set to 0.1 for all models to encourage deterministic and factual responses.

- **Maximum Tokens:** The maximum number of generated tokens was set to 1024 for all models.

- **Reasoning Effort:** For Gemini models, the reasoning_effort parameter was explicitly set to "none".

- **Output Format:** All models were constrained to generate valid JSON objects. For proprietary APIs (OpenAI, Anthropic, Gemini), we utilized their native JSON output modes. For open-source models served via a vLLM-based inference server, we enforced the JSON schema using guided generation.

C Dataset Statistics

ICD-10 Chapter Distribution Table 6 presents the distribution of ground-truth differential diagnosis across ICD-10 chapters in our test set, providing insights into the medical domain coverage of the DDXPlus subset.

D Performance by Medical Specialty

This section examines the impact of medical domain fine-tuning across different ICD-10 chapters, revealing substantial heterogeneity in performance

Table 7: Performance comparison of base and medically-tuned models by ICD-10 Chapter. The values in parentheses indicate the change in HDF1 score after medical domain tuning.

Model	Overall	J00-J99 (n=532)	I00-I99 (n=454)	A00-B99 (n=248)	G00-G99 (n=189)	S00-T88 (n=168)	D50-D89 (n=149)	K00-K95 (n=121)	F01-F99 (n=114)	C00-D49 (n=111)
Gemma-3-27B	32.25	33.31	30.44	10.68	23.75	19.50	10.03	31.36	18.90	33.93
MedGemma-27B	33.10	30.81	31.13	10.66	20.94	20.56	13.58	27.21	21.16	33.47
	(+0.85)	(-2.50)	(+0.69)	(-0.02)	(-2.81)	(+1.06)	(+3.55)	(-4.15)	(+2.26)	(-0.46)
Phi-3.5-mini	31.87	37.72	24.33	11.45	13.86	17.18	10.82	21.58	16.24	28.64
MediPhi	35.26	43.38	25.17	8.01	13.09	15.90	20.97	29.65	18.76	30.55
	(+3.39)	(+5.66)	(+0.84)	(-3.44)	(-0.77)	(-1.28)	(+10.15)	(+8.07)	(+2.52)	(+1.91)

gains across clinical specialties. We analyze all chapters with at least 100 test cases, sorted by patient count in descending order.

Table 7 presents the performance comparison across different ICD-10 chapters. The results demonstrate that medical fine-tuning produces highly variable effects across clinical specialties. MediPhi shows substantial overall improvement (+3.39 HDF1) over its base model, with particularly strong gains in diseases of the blood and blood-forming organs (D50-D89: +10.15), digestive system (K00-K95: +8.07), and respiratory system (J00-J99: +5.66). However, the same fine-tuning process leads to performance degradation in certain infectious and parasitic diseases (A00-B99: –3.44), highlighting that domain specialization can be detrimental for specific medical areas. MedGemma-27B exhibits more modest and mixed results, with a marginal overall gain (+0.85 HDF1). While it improves on blood disorders (D50-D89: +3.55), it shows notable performance drops in key areas, including the digestive system (K00-K95: –4.15), nervous system (G00-G99: –2.81), and respiratory system (J00-J99: –2.50) chapters.

These findings underscore that the effectiveness of medical domain fine-tuning is not universal but rather depends critically on the alignment between the fine-tuning data distribution and the specific knowledge requirements of each medical specialty.

E   Model Ranking Analysis

Figure 4 illustrates how our hierarchical evaluation framework substantially reorders model rankings compared to conventional flat metrics. The transition from Top-5 Accuracy to HDF1 reveals that domain-specialized models like MediPhi achieve marked ranking improvements. This shift demonstrates HDF1's ability to capture clinically meaningful performance characteristics, such as rewarding coherent but inexact diagnoses, a nuance that

Figure 4: Shift in model rankings from flat (Top-5 Accuracy) to hierarchical (HDF1) evaluation. The figure illustrates the rank changes when moving from a conventional accuracy metric (left) to the proposed hierarchical score (right). Models are color-coded as proprietary (yellow), open-source (blue), and medically fine-tuned (green). Note the significant rank improvement of medically fine-tuned models like MediPhi, which highlights HDF1's ability to better capture clinical relevance.

flat metrics consistently overlook.

F   Additional Case Studies on Hierarchical Evaluation

This section presents three additional case studies that further demonstrate the nuanced evaluation capabilities of the H-DDx framework, as shown in Table 8. These cases reveal how HDF1 can differentiate clinical reasoning quality even when flat metrics show identical results.

Case Study 2: Revealing the Impact of Fine-Tuning in Accuracy Failures   Our second case features a 62-year-old female with osteoporosis and intense coughing fits presenting with severe chest pain. The ground-truth is Spontaneous rib

Patient Case	Final Diagnosis	Ground-Truth DDx	Model	Top-5 Acc.	HDF1	Predicted DDx Set & ICD-10 Codes
Case 2

62/F with osteoporosis & severe chest pain | Spontaneous rib fracture (S22.9) | Spont. rib fracture (S22.9)
Bronchitis (J40)
Whooping cough (A37)
Pulm. embolism (I26)
NSTEMI/STEMI (I21) | Gemma3-27B | 0.0 | 0.1935 | Pleurisy (R09.1)
Musculoskeletal Chest Pain (R07.82)
Costochondritis (M94.0)
Pulmonary Embolism (I26)
Pericarditis (I30) |
| | | | MedGemma-27B | 0.0 | **0.5000** | Pulmonary Embolism (I26)
Pleurisy (R09.1)
Costochondritis (M94.0)
Rib Fracture (S22.3)
Myocardial Infarction (I21) |
| **Case 3**

21/F with URI symptoms | URTI (J06.9) | URTI (J06.9)
Influenza (J11.1)
Pneumonia (J18)
Bronchitis (J40)
HIV initial (B20) | Gemma3-4B | 1.0 | 0.1935 | Viral Meningitis (A87)
Sinusitis (J01.9)
Acute Pharyngitis (J02)
COVID-19 (U07.1)
Cellulitis (L03.90) |
| | | | Claude-Sonnet-4 | 1.0 | **0.7692** | Influenza (J11.1)
URTI (J06.9)
Sinusitis (J01.9)
Pneumonia (J18)
Bronchitis (J40) |
| **Case 4**

46/M with joint pain & mouth ulcers | SLE (M34) | NSTEMI/STEMI (I21)
SLE (M34)
Anemia (D64.9)
Pulm. neoplasm (C34)
Acute dystonia (G24.02) | Gemma3-12B | 0.0 | 0.1212 | Fibromyalgia (M79.7)
Hypertension (I10-I1A)
Ankylosing Spondylitis (M45)
Cervical Radiculopathy (M54.12)
TMJ Disorder (M26.6) |
| | | | GPT-4o-mini | 0.0 | **0.1714** | Fibromyalgia (M79.7)
Chronic Fatigue Syndrome (G93.32)
Rheumatoid Arthritis (M06.9)
Polymyalgia Rheumatica (M35.3)
Ankylosing Spondylitis (M45) |

Table 8: Additional comparative analysis demonstrating HDF1's ability to differentiate clinical reasoning quality. Higher HDF1 scores are shown in bold.

fracture (S22.9). In this scenario, both the base model (Gemma3-27B) and its medically fine-tuned version (MedGemma-27B) failed to identify the correct diagnosis, resulting in a Top-5 Accuracy of 0.0 for both. Here, the flat metric fails to differentiate between their performance, suggesting they are equally poor.

However, HDF1 effectively quantifies the significant improvement gained from domain specialization, scoring MedGemma (0.5000) far higher than its base model (0.1935). A clinical review of the outputs reveals why. MedGemma generated a comprehensive differential diagnosis that included critical emergencies like Myocardial Infarction and Pulmonary Embolism, alongside the highly relevant diagnosis of Rib Fracture. While a flat metric would miss this, HDF1's hierarchical approach recognizes that Rib Fracture is taxonomically adjacent to the ground-truth, Spontaneous rib fracture (S22.9), as both belong to the same ICD-10 category (S22). In stark contrast, the base Gemma3 model failed to identify the correct diagnosis and missed a key emergency. This case effectively demonstrates HDF1's ability to measure the qualitative leap in clinical reasoning from fine-

tuning and to reward clinically correct diagnoses that simpler metrics overlook.

Case Study 3: Distinguishing Clinical Coherence Despite Equal Accuracy Our third case involves a 21-year-old female presenting with upper respiratory symptoms. The patient lives in crowded conditions, works at a daycare, and presents with fever, sore throat, productive cough, nasal congestion, and diffuse muscle pain. The ground-truth diagnosis is Upper Respiratory Tract Infection (URTI, J06.9).

In Case 3, both models achieve a perfect Top-5 Accuracy of 1.0. Notably, while Gemma3-4B did not explicitly predict "URTI," the LLM judge deemed "Acute Pharyngitis" (J02) as semantically equivalent to URTI, highlighting the ambiguity inherent in LLM-based matching. This exemplifies a key limitation of flat metrics that rely on subjective semantic matching. Claude-Sonnet-4 directly identifies URTI and generates a coherent differential entirely within the respiratory domain, including Influenza, Sinusitis, Pneumonia, and Bronchitis, all of which are plausible given the patient's presentation.

In contrast, despite receiving the same Top-5 Accuracy score through the judge's lenient interpretation, Gemma3-4B's differential includes Viral Meningitis (A87) and Cellulitis (L03.90), which are clinically inconsistent with the primary respiratory presentation. HDF1 reveals this dramatic difference in clinical reasoning quality (0.1935 vs 0.7692), demonstrating that accuracy alone, especially when determined through ambiguous semantic matching, fails to capture the clinical utility of the entire differential diagnosis set.

Case Study 4: Gradations in Clinical Failure
The fourth case features a 46-year-old male with joint pain, mouth ulcers, shortness of breath, and fatigue. The ground-truth diagnosis is Systemic Lupus Erythematosus (SLE, M34). Both models fail to identify SLE, resulting in a Top-5 Accuracy of 0.0 for both.

While both models fail completely by flat metric standards, HDF1 reveals meaningful differences in their clinical reasoning (0.1212 vs 0.1714). GPT-4o-mini demonstrates marginally better clinical judgment by including systemic rheumatological conditions such as Rheumatoid Arthritis (M06.9) and Polymyalgia Rheumatica (M35.3), which share the autoimmune nature and systemic involvement characteristic of SLE. Both models include musculoskeletal conditions (Fibromyalgia, Ankylosing Spondylitis), but GPT-4o-mini's inclusion of Chronic Fatigue Syndrome acknowledges the systemic nature of the presentation. In contrast, Gemma3-12B includes less relevant diagnoses such as Hypertension and TMJ Disorder. While neither model performs well, HDF1 captures these subtle differences in clinical reasoning that would be invisible to binary accuracy metrics.