UNLOCKING SPEECH INSTRUCTION DATA POTENTIAL WITH QUERY REWRITING

ABSTRACT

End-to-end Large Speech Language Models (**LSLMs**) demonstrate strong potential in response latency and speech comprehension capabilities, showcasing general intelligence across speech understanding tasks. However, the ability to follow speech instructions has not been fully realized due to the lack of datasets and heavily biased training tasks. Leveraging the rich ASR datasets, previous approaches have used Large Language Models (**LLMs**) to continue the linguistic information of speech to construct speech instruction datasets. Yet, due to the gap between LLM-generated results and real human responses, the continuation methods further amplify these shortcomings. Given the high costs of collecting and annotating speech instruction datasets by humans, using speech synthesis to construct large-scale speech instruction datasets has become a balanced and robust alternative. Although modern Text-To-Speech (**TTS**) models have achieved near-human-level synthesis quality, it is challenging to appropriately convert out-of-distribution text instruction to speech due to the limitations of the training data distribution in TTS models. To address this issue, we propose a query rewriting framework with multi-LLM knowledge fusion, employing multiple agents to annotate and validate the synthesized speech, making it possible to construct high-quality speech instruction datasets without relying on human annotation. Experiments show that this method can transform text instructions into distributions more suitable for TTS models for speech synthesis through zero-shot rewriting, increasing data usability from 72% to 93%. It also demonstrates unique advantages in rewriting tasks that require complex knowledge and context-related abilities.

1 INTRODUCTION

LLMs have demonstrated powerful performance in general intelligence, profoundly changing the way humans interact with AI systems (OpenAI et al., 2024; Abdin et al., 2024; Dubey et al., 2024). However, constrained by the text modality, existing LLMs are unable to meet the needs of rich real-world interactive scenarios, making it a natural idea to extend this general capability to more modalities (Fang et al., 2024). Recently, end-to-end LSLMs have shown great potential in terms of response latency and speech understanding, making it possible to extend this general performance to scenarios better suited for verbal interaction (Chu et al., 2023; 2024; Zhang et al., 2023a; Fathullah et al., 2024). However, due to the lack of high-quality speech instruction datasets and heavily biased training tasks, the ability of LSLMs to follow speech instructions is not fully realized, resulting in a lack of intent perception in verbal interaction scenarios. Thus, building a high-quality large-scale speech instruction dataset becomes a crucial foundation for advancing the ability to follow speech instructions.

Benefiting from abundant Automatic Speech Recognition (**ASR**) datasets (Ardila et al., 2020; Pratap et al., 2020; Guoguo Chen, 2021; Wang et al., 2024), early work aligned speech and text modalities by having models repeat or recognize linguistic information in speech through textual instructions (Gong et al., 2023). To enhance the model's understanding of paralinguistic information in speech, traditional tasks in the speech domain (such as speaker classification, speech entity recognition, etc.) were integrated into training (Chu et al., 2023; Tang et al., 2024; Das et al., 2024). These training methods, which treat the speech modality as files rather than instructions, cause the model to lack the ability to follow speech instructions and lead to hallucinations due to the severe bias in

task distribution. To unlock the model's potential to follow speech instructions, previous approaches constructed speech instruction datasets by continuing the linguistic information of speech through LLMs to restore the model's instruction-following capabilities (Fathullah et al., 2024). However, due to the gap between the generated results of LLMs and human-annotated ground truth answers, using such continuation methods may further amplify these shortcomings.

Unlike the image domain, which has abundant human-annotated data (Laurençon et al., 2024; Lin et al., 2015), constructing large-scale, manually narrated, and annotated speech instruction datasets from scratch is challenging due to the high costs of collection and annotation. As a result, using speech synthesis to construct datasets becomes a robust choice after weighing the pros and cons. However, due to differences between TTS models and human speech narration, as well as hallucination issues during the speech synthesis process, it is necessary to verify whether the synthesized speech is linguistically equivalent to the text. On the other hand, since TTS models have a limited vocabulary, they cannot accurately convert out-of-distribution text, such as compound words, abbreviations, or mathematical formulas, into speech, leading to the loss of linguistic information.

Previous work has shown that the semantic similarity between two texts can be calculated using embedding models, demonstrating better robustness compared to methods like WER and more closely aligned with how humans assess textual similarity (Muennighoff et al., 2023). Some high-quality human-annotated datasets achieve superior annotation results by integrating the opinions of multiple annotators, making the sample distribution more representative of real-world scenarios (Deitke et al., 2024; Liu et al., 2021). Meanwhile, query rewriting optimizes the text distribution without significantly altering the semantics, making it better aligned with a specific distribution (Ye et al., 2024).

Inspired by this, we propose a query rewriting method with multi-LLM knowledge fusion, along with multi-agent annotation and data quality validation. Specifically, we leverage LLMs' generalization ability in zero-shot tasks to guide the rewriting of text instructions to fit the training distribution of TTS models. Additionally, we use multiple distinct LLMs to rewrite the text from different perspectives. Next, we automatically extract linguistic information from the speech using multiple models and calculate its average similarity to the original text in the embedding space to avoid annotation errors and achieve semantically optimal results. Finally, we fuse the knowledge of different LLMs in this zero-shot rewriting task to tackle challenging rewrites that require complex knowledge. Experimental results show that our method increased data usability from 71% to 93% and improved the semantic similarity between the linguistic information in speech and the original text by 5%.

The main contribution of this paper can be summarised as follows:

- We propose a query rewriting framework with multi-LLM knowledge fusion, along with a multi-agent annotation and validation method based on embedding space similarity, enabling the low-cost, automated construction of high-quality speech instruction datasets.

- Experiments show that our proposed method demonstrates unique advantages in rule-based query rewriting, context-aware understanding, and complex knowledge integration, increasing the average data usability from 72% to 93%, while maintaining consistent performance across different validation methods.

- By comparing the training results using voice data of varying quality and alignment objectives, we validated the significant advantages of high-quality synthesized speech data in alignment effectiveness and cross-modal consistency. It also demonstrates the importance of learning from real human responses to enhance the model's ability to follow speech instructions.

2 RELATED WORK

Text-To-Speech Text-to-speech models have recently demonstrated impressive performance in terms of synthesis quality and fluency. However, constrained by the reliance on reference speech, they lack diversity in style (Wang et al., 2023; Zhang et al., 2023b; Le et al., 2023). Inspired by the image modality, using natural language descriptions of speaker styles to address this issue has become a promising approach. However, due to the lack of large-scale speech datasets containing natural language descriptions, it is difficult to freely use natural language to control the style of speech synthesis. Lyth & King (2024) constructed a large-scale speech dataset using multiple

attributes for automated labeling, which significantly improved the synthesis diversity of TTS models. In this work, we utilize GPT-4 (OpenAI et al., 2024) to synthesize style descriptions and use Parler-TTS (Lacombe et al., 2024) to synthesize speech.

Speech-text alignment training in LSLMs Aligning speech and text modalities is crucial for building the speech understanding capability of end-to-end LSLMs. Benefiting from abundant ASR datasets (Ardila et al., 2020; Pratap et al., 2020; Guoguo Chen, 2021; Wang et al., 2024), early work aligned the two modalities by instructing the model to repeat or recognize the linguistic information in the speech (Shu et al., 2023; Zhang et al., 2023a; Gong et al., 2023; Chu et al., 2023). However, due to the severely biased task distribution, the model ignored following the instructions in the speech and defaulted to performing language recognition (Fathullah et al., 2024). Recent work has employed a continuation approach to construct speech instruction data, aiming to restore the model's ability to follow spoken instructions (Fathullah et al., 2024; Fang et al., 2024). Due to the gap between the language model's generated outputs and real human responses, using the continuation method to train the model can further amplify this deficiency (Seddik et al., 2024; Chen et al., 2024). In this work, we propose a high-quality speech instruction synthesis method to address this issue.

3 PROBLEM FORMULATION

Figure 1: *Some recognition errors in ASR models. Sentence Pattern Error indicates that the ASR model failed to provide appropriate punctuation based on the user's intent. In the given examples, the original sentence expresses a question, while the ASR-recognized sentence, lacking proper punctuation, conveys a tone of disdain or assertion.*

Our goal is to automatically obtain synthesized speech that is linguistically equivalent to the text. For a given TTS model and text instruction c_o, we can get the synthesized speech s_o.

Ideally, we can get the linguistic information $\bar{c}_o$ in s_o by Automatic Speech Recognition (**ASR**) model, it should satisfies

$$\bar{c}_o = c_o \tag{1}$$

which mean that the s_o is linguistically equivalent to c_o strictly.

As shown in Figure 1, we present some recognition errors in ASR models. Due to the inherent gap between ASR models and humans in speech recognition, it is challenging to get $\bar{c}_o$ that satisfies equation (1), even for speech that contains equivalent linguistic information. Therefore, using the strict linguistic equivalence condition in equation (1) to evaluate the quality of synthesized speech can lead to inappropriate data rejection and cause a shift in the dataset distribution. Inspired by the work on Semantic Textual Similarity (Muennighoff et al., 2023), we use the similarity between $\bar{c}_o$ and c_o as a criterion for judging their linguistic equivalence. Given the similarity calculation method F, our goal is to get s to maximize the number of

$$q = F(\bar{c}, c). \tag{2}$$

where c is the original text and $\bar{c}$ is the linguistic information in s that usually to be the best speech recognition result by ASR model.

Figure 2: The structure of Question Rewriting with Multi-LLM.

4 METHOD

4.1 MULTI-AGENT ANNOTATION AND VERIFICATION

Accurate recognition of linguistic information in speech is fundamental for assessing the quality of speech instruction synthesis, as incorrect recognition can lead to improper filtering of the data. However, achieving accurate assessment is challenging due to the common recognition errors present in ASR models (Radford et al., 2022; Srivastav et al., 2023). Some human-annotated datasets integrate the opinions of multiple annotators to achieve high-quality annotation results (Deitke et al., 2024; Liu et al., 2021). Inspired by this, we propose a Multi-agent annotation and verification method. By using three ASR models and three Embedding models, we simulate multiple annotators and validators to jointly enhance the quality of the evaluation.

Specifically, for an original text instruction c_o and its' synthesized speech s_o, we can obtain multiple recognition results $\bar{C}_o = \{ \bar{c}_{o,j} | j \in \{0, 1, 2\} \}$ through multiple ASR models $A = \{A_0, A_1, A_2\}$. Then we use embedding models $E = \{E_0, E_1, E_2\}$ to get the similarity between the original text instruction and the recognition result by

$$F(c_o, \bar{c}_{o,j}) = \frac{1}{3} \sum_{z=0}^{2} \frac{E_z(c_o) \cdot E_z(\bar{c}_{o,j})}{\|E_z(c_o)\| \|E_z(\bar{c}_{o,j})\|}. \tag{3}$$

where $c_{o,j}^-$ is the recognition result of s_o by $A_j \in A$. The quality for s_o could get by

$$q(A, E) = \max_j (F(c_o, \bar{c}_{o,j})). \tag{4}$$

When using the same similarity calculation method, higher orthogonality in ASR model performance helps to avoid consistent ASR errors, thereby improving the accuracy of the evaluation. Therefore, we use whisper-large-v3 [1] (Radford et al., 2022), canary-1b [2] and parakeet-tdt-1.1b [3] as ASR models, which have similar ASR performance in OpenASR Leaderboard (Srivastav et al., 2023) but different architectures.

4.2 QUESTION REWRITING FOR LINGUISTIC PRESERVATION

Due to the limited vocabulary of the TTS model, it is unable to properly convert out-of-distribution text, such as compound words, abbreviations, and mathematical formulas into speech, resulting in the loss of linguistic information. Previous work mainly relied on manually designed rules to

---

[1] https://huggingface.co/openai/whisper-large-v3
[2] https://huggingface.co/nvidia/canary-1b
[3] https://huggingface.co/nvidia/parakeet-tdt-1.1b

rewrite these contents, which inevitably led to a dependency on manual efforts, making it difficult to construct large-scale speech instruction datasets (Yang et al., 2024b). The strong performance of large language models on zero-shot tasks makes it a natural idea to use this capability for rewriting text as a solution to this problem.

Specifically, we propose a query rewriting framework based on multiple LLMs to avoid the loss of linguistic information during speech synthesis, as shown in Figure 2. For an original text instruction c_o, we use Llama-3-8B-Instruct (Dubey et al., 2024), Phi-3-small-8k-instruct (Abdin et al., 2024) and Qwen2-7B-Instruct (Yang et al., 2024a) to rewrite the instructions, resulting in the candidate text set $C = \{c_o, c_l, c_p, c_q\}$. To enhance the diversity of speech styles, we used GPT-4 to generate descriptions for 192 different speakers $D = \{d_0, d_1, \ldots, d_{191}\}$ to control the speech styles. Then, we can get the candidate speech set $S = \{s_o, s_l, s_p, s_q\}$ by TTS model and randomly selected description text $d \in D$. Following the evaluation and validation methods mentioned in Section 4.1, we can obtain the quality of every synthesized speech through

$$q(A, E|c, c_o) = \max_j(F(c_o, \bar{c}_j)), c \in C. \tag{5}$$

where $\bar{c}_j$ is the speech recognition result of $s \in S$ by ASR model $A_j \in A$ (4.1). Then we can obtain the optimal synthesized speech s and the text $\hat{c} \in C$ which is the optimal input into TTS.

Figure 3: The structure of Knowledge Fusion.

4.3 KNOWLEDGE FUSION FOR CHALLENGING QUERY REWRITING

The performance of the models on challenging zero-shot tasks shows a degree of orthogonality due to differences in their knowledge. However, they exhibit limitations in tasks that require multi-perspective capabilities. Recent studies have shown that knowledge fusion can effectively leverage the knowledge of multiple models (Wan et al., 2024). By learning from data generated by different models with unique perspectives, the model's ability to understand complex tasks is significantly enhanced. Inspired by this, we propose a knowledge fusion method to address challenging rewriting tasks as shown in Figure 3. By integrating the rewriting capabilities of multiple LLMs, we aim to correct failed samples.

Specifically, for a dataset $X = \{c_0, c_1, c_2, \ldots, c_{n-1}\}$, we can obtain the optimal set $X_b = \{\hat{c}_0, \hat{c}_1, \hat{c}_2, \ldots \hat{c}_{n-1}\}$ for input into TTS using the method from Section 4.2. Then, we consider the sample pairs $< c_i, \hat{c}_i >, i \in [0, n-1]$ that satisfy $q(A, E|\hat{c}_i, c_i) > \alpha$ and $q(A, E|c_i, c_i) < \alpha$ as successfully rewritten samples for knowledge fusion training, and the sample pairs $< c_i, \hat{c}_i >, i \in [0, n-1]$ that satisfy $q(A, E|\hat{c}_i, c_i) < \alpha$ as the samples with failed rewrites, α is the hyperparameters used to control data quality, where $q(A, E|c_i, c_i)$ fellow equation (5). In this paper, we set $\alpha = 0.9$.

We use Meta-Llama-3-8B-Instruct (Dubey et al., 2024) as the backbone model and employ LoRA (Hu et al., 2021) to train the model. Our goal is to minimize the

$$\mathcal{L} = -\sum_{i=0}^{M} logP(y_i|x, c, y_{<i}). \tag{6}$$

where $< c, y >$ is the successfully rewritten sample, x is the prompt. Then we can get the new rewrite set $C_n = \{c_{i,n} | q(A, E | \hat{c}_i, c_i) < \alpha\}$ for the samples with failed rewrites by the model with knowledge fusion. Finally, following equation (5), we can obtain the new optimal set X_{nb} for input into TTS.

5 Experiment And Result

5.1 Experiment Settings

Dataset In real user interaction scenarios, it is rare to use lengthy speech to provide a detailed task definition; instead, users often ask brief questions expecting responses that meet their expectations. Therefore, in this paper, we selected several QA datasets with short questions to validate the effectiveness of our method. Specifically, we use DROP (Dua et al., 2019), Quoref (Dasigi et al., 2019), ROPES(Lin et al., 2019), NarrativeQA (Kočiský et al., 2017), TAT-QA (Zhu et al., 2021), SQUAD1.1 (Rajpurkar et al., 2016) and SQUAD2.0 (Rajpurkar et al., 2018) to validate the effectiveness of the proposed method, We provide more information about the dataset in Appendix B.2.

For the training data to train LSLMs, we calculate the data quality using Equation (5) and set a threshold t. The quality of all data used for training the model must exceed t. For data derived from the same original text, only the speech instruction with the highest quality that meets the threshold requirement is included in the training.

Baseline and Aboluetion Method We use the following setup as our baseline: (1) **Original**: Directly using the original text as TTS input for speech synthesis; (2) **TN** (Text Normalization): This is a commonly used method in the industry to optimize TTS inputs. We implement text normalization using the method proposed by (piAI, 2017), which achieved an accuracy of 98.27% in Text Normalization Challenge (Howard et al., 2017).

To evaluate the effectiveness of each component of our proposed method, we adopt the following configurations as ablation methods: (1) **Phi3/Qwen2/Llama3**: Follow the synthesis framework in Figure 2 but only use Phi-3-small-8k-instruct/Qwen2-7B-Instruct/Llama-3-8B-Instruct to rewrite queries; (2) **Ours w/o KF**: Use only the synthesis framework in Figure 2 without knowledge fusion.

Considering that speech style descriptions can impact speech synthesis, we adopt the following two configurations to evaluate the generalization ability of our proposed method across different TTS models: (1) **Multi-Speaker Setting**: Following the framework in Figure 2, we use GPT-4 (OpenAI et al., 2024) to generate diverse speech descriptions and employ Parler-TTS-Large-v1 as the TTS model; (2) **Single-Speaker Setting**: We include two additional widely-used vocoder-based TTS models, MeloTTS (Zhao et al., 2023) and MMS-TTS-ENG (Pratap et al., 2023), to evaluate the effectiveness of our method across three TTS models.

For the training of LSLMs, we adopt the following two alignment target settings: (1) **Golden**: Using high-quality human-annotated answers; (2) **Continue**: Aligning with answers generated by LLM. In this paper, we use Llama-3-8B-Instruct to generate the answers. For the test dataset, We use the MeloTTS to synthesize speech and discard all data with inconsistent linguistic information.

Speech style control For Multi-Speaker Setting, to enhance the diversity of speech styles and make the dataset's style distribution more closely resemble that of human datasets, following the approach of Lacombe et al. (2024), we used six attributes to describe the vocal characteristics and employed GPT-4 to generate natural language descriptions, the prompt is in Appendix A. Table 1 provides examples of speech style descriptions, with additional examples available in the appendix D. During the speech synthesis process, we randomly selected a speech description for each text. To maintain consistency, the rewritten text and the original text used the same vocal style description.

For Single-Speaker Setting, each TTS model uses a fixed speech style. For Parler-TTS-Large-v1, we use *Jon's voice is monotone yet slightly fast in delivery, with a very close recording that almost has no background noise* as the speaker style descriptions. For MeloTTS (Zhao et al., 2023), we

Table 1: Examples of speech style descriptions generated by GPT-4 (OpenAI et al., 2024).

Name	Description
Luminous	A male voice with an American accent speaks slowly, enunciating each word clearly. The speaker's voice is close-sounding and quite clean, maintaining a monotone pitch throughout. The recording captures his voice with good clarity.
Timothy	A male voice with an American accent speaks slowly, with a close-sounding and quite clean delivery. The speaker's pitch is very monotone, and the recording captures his voice with good clarity.
Jocelyn	A female voice with a Canadian accent speaks slowly. The speaker's voice is close-sounding and quite clean, with a monotone pitch. The recording captures the voice with a clear and precise quality.
Nadine	A female voice with an American accent speaks normally. The voice is close-sounding and quite clean, with a slightly expressive and animated pitch. The recording captures a subtly engaging tone.

Table 2: Evaluation results on SIM for different datasets under the Multi-Speaker Setting.

Method	DROP	Quoref	ROPES	NarrativeQA	TAT-QA	SQUAD1.1	SQUAD2.0	Average
Original	93.71	96.25	97.07	95.87	82.24	93.40	93.42	93.14
TN	95.95	97.18	97.63	97.75	89.07	94.88	94.93	95.34
Phi3	97.24	98.07	98.32	97.64	95.29	96.39	96.39	97.05
Qwen2	96.45	97.64	98.05	97.08	90.31	95.68	95.69	95.84
Llama3	97.30	97.88	98.25	97.22	95.27	96.35	96.34	96.94
Ours w/o KF	98.02	98.57	98.79	98.14	97.12	97.37	97.36	97.91
Ours	**98.11**	**98.62**	**98.82**	**98.24**	**97.18**	**97.47**	**97.49**	**97.99**

use the officially provided *EM-US* setting. For MMS-TTS-ENG, no additional speaker style control measures are provided by the official implementation, so we follow the default settings.

Implementation Details   We provide implementation details in Appendix B.1.

5.2 EVALUATION METRICS

Synthetic data quality evaluation   We use the following metrics to evaluate the performance of our proposed method in terms of data synthesis quality: (1) **SIM**: The similarity in the embedding space between the linguistic information in the speech and the original text, calculated following the method we proposed in Section 4.1; (2) **WER** (Word Error Rate): This metric is commonly used to assess the accuracy of speech recognition and is similar to the strict linguistic equivalence judgment in Equation (1); (3) **Pass**: The proportion of speech in the dataset with a quality higher than $\alpha = 0.9$, calculated according to Equation (5).

Generative evaluation   To evaluate the quality of the generated results in DROP, Quoref, ROPES and NarrativeQA, we use ROUGE-L (Lin, 2004) as evaluation metrics.

5.3 MAIN RESULT

Synthetic data quality   For the Multi-Speaker Setting, we present the evaluation results of the SIM and Pass in Table 2 and Table 3. The experimental results demonstrate that our proposed method consistently shows effectiveness across all datasets, increasing the similarity between the

Table 3: Evaluation results on Pass for different datasets under the Multi-Speaker Setting.

Method	DROP	Quoref	ROPES	NarrativeQA	TAT-QA	SQUAD1.1	SQUAD2.0	Average
Original	74.40	84.78	89.80	83.63	25.85	73.39	73.45	72.19
TN	84.94	89.29	91.18	93.29	50.49	82.66	82.52	82.05
Phi3	89.82	92.69	94.60	91.04	79.46	85.91	85.84	88.48
Qwen2	87.28	91.70	94.09	89.38	56.63	83.46	83.53	83.72
Llama3	90.40	92.23	94.44	89.37	80.21	85.92	85.96	88.36
Ours w/o KF	93.43	95.24	96.32	93.54	88.72	90.20	90.19	92.52
Ours	**94.11**	**95.59**	**96.71**	**94.29**	**89.12**	**90.78**	**90.93**	**93.07**

Table 4: Evaluation results for different training methods.

Training Target	Threshold (t)	Data Construction Method	Drop	Quoref	Ropes	NarrativeQA	Average
-	-	-	17.40	55.98	42.69	43.02	39.77
Golden	0.00	Original	29.25	76.01	55.42	48.34	52.26
LLM Continue	0.00	Ours	30.08	75.05	57.15	47.88	52.54
Golden	0.00	Ours	42.78	86.58	60.48	52.15	60.50
Golden	85.00	Ours	42.95	85.18	56.47	53.61	59.55
Golden	90.00	Ours	**44.35**	**86.81**	**64.24**	**56.76**	**68.43**
Golden	95.00	Ours	41.86	86.73	58.55	54.61	60.44

Table 5: Evaluation results of different ASR methods under the Multi-Speaker Setting. Using WER as the evaluation metric.

ASR Method	DROP	Quoref	ROPES	NarrativeQA	TAT-QA	SQUAD1.1	SQUAD2.0	Average
canary	10.93	5.46	6.97	8.88	18.61	10.19	9.55	10.08
whisper	11.18	5.32	7.09	8.53	19.98	9.67	9.71	10.21
parakeet	10.42	5.08	6.21	8.39	18.44	9.79	9.14	9.64
Ours	**9.19**	**4.14**	**5.18**	**6.21**	**18.31**	**7.74**	**7.74**	**8.36**

linguistic information of the synthetic speech and the original text in the embedding space from 93.06% to 97.98%. For the Single-Speaker Setting, we present the evaluation results of the SIM and Pass in Table 14 and Table 15. The experimental results on multiple TTS models demonstrate the excellent generalization ability of our proposed method. Using our method, the absolute difference in embedding space quality between MeloTTS and Parler-TTS-Large-v1 is reduced from 3.96% to 0.09%, and the gap in data usability is narrowed from 13.95% to 0.9%. This bridges the quality gap in synthesized data between vocoder-based TTS models and autoregressive TTS models.

Use Synthetic data finetune LSLMs   As shown in Table 4, we present the evaluation results of models trained under different experimental settings. The experimental results demonstrate that using *Golden* as the alignment target exhibits significant superiority compared to the *Continue* approach. This provides new insights into the training of LSLMs, indicating that in the process of aligning speech instructions, continuation data generated by LLMs cannot replace high-quality human-annotated data. On the other hand, training the model with training sets obtained using different sampling thresholds achieved the best performance at a threshold of 0.90. This validates the rationality of our threshold setting in the *Pass* metric. It also demonstrates that discarding low-quality samples through an appropriate threshold can effectively improve the model's performance.

5.4 ABLATION EXPERIMENT

Orthogonality of LLM performance   As mentioned in Section 4.2, the degree of orthogonality among different LLMs in this zero-shot task is positively correlated with the improvement in quality. We present more detailed evaluation results across multiple datasets in Tables 2 and 14. The experimental results show that the performance of using a single LLM is inferior to that of using multiple LLMs together, and there are subtle differences in the performance of different LLMs on this task.

The effectiveness of multi-agent annotation and validation   As shown in Tables 5, we present the evaluation results of using different ASR models for speech recognition. The experimental results demonstrate that the combined use of multiple different ASR models consistently improves WER, showcasing the advantages of this approach in reducing automatic annotation errors and avoiding inappropriate data filtering. Meanwhile, additional evaluation results under various similarity calculation methods are provided in Appendix C.2, consistently verifying the effectiveness of the approach. As shown in Table 6, we provide the performance of different similarity calculation methods in selecting recognition results based on synthesized speech from original text. We use WER as the evaluation metric here, primarily because the original text was directly used for synthesizing speech, without altering the text distribution. WER is more suitable than semantic similarity for assessing data quality in this context. The experiments show that using the average semantic

Table 6: Results using different word embedding models on various datasets, without LLM-based rewriting. All datasets are evaluated using WER as the metric.

Embedding Model	DROP↓	ROPES↓	Ropes↓	NarrativeQA↓	Tat-Qa↓	SQUAD1.1↓	SQUAD2.0↓	Average↓
gte	9.289	4.144	5.193	6.296	18.980	7.857	7.869	8.518
mxbai	9.256	4.170	5.205	6.221	18.331	7.792	7.786	8.394
stella	**9.129**	4.211	5.326	6.330	**18.212**	**7.765**	7.768	8.392
gte+mxbai+stella	9.188	**4.143**	**5.176**	**6.209**	18.312	7.741	**7.738**	**8.358**

Table 7: Estimated results of the experimental cost.

Speech Collection Method	Quality Validation	Speakers Num	Human Time Cost	Gpu Time Cost	Money Cost
Human	Human	∞	562	0	4215
Human	Single ASR	∞	281	6	2110.02
Human	Multi ASR + Emb	∞	281	16	2114.22
MeloTTS+Original	Single ASR	1	0	14	5.88
Parler+Original	Single ASR	192	0	127	53.34
MeloTTS+Ours w/o KF	Multi ASR + Emb	1	0	82	34.44
Parler+Ours w/o KF	Multi ASR + Emb	192	0	534	224.28
Parler+Ours	Multi ASR + Emb	192	0	558	234.36

similarity of multiple embedding models, compared to a single model, offers certain advantages in terms of average WER across various datasets.

5.5 EXPERIMENTAL COST COMPARISON

To thoroughly demonstrate the advantages of our proposed method in terms of efficiency and experimental costs, we present the experimental expenses calculated based on the lowest standard, as shown in Table 7. For labor costs, we calculate the time for speech collection and data annotation at a 1:1 ratio, using a labor rate of $7.50 per hour, which is the minimum wage mandated by the USA government. In reality, the minimum wage across states is generally higher than this. Meanwhile, we calculate GPU costs using the lowest rate for a single NVIDIA A40 GPU card from cloud service providers, which is $0.42 per hour per device, excluding any additional time costs related to data transfer and other operations. The experimental results show that the cost of our method is less than one-tenth of that of high-quality human datasets, achieving a good balance between expense and dataset quality.

Figure 4: Examples of successfully rewritten queries.

5.6 CASE STUDY

As shown in Figure 4, we present some examples of successful rewrites. We demonstrate the unique advantages of our proposed method through three typical rewriting scenarios: (1) Rule-based rewriting, (2) Context-aware rewriting, and (3) Rewriting requiring complex comprehension abilities. In the Rule-based rewriting example, the LLM follows the rule of converting numbers into English words. In the Context-aware rewriting scenario, Llama-3-8B-Instruct combines information from the context to infer that *EU* is the abbreviation for European Union and correctly completes the rewrite. In the Rewriting requiring complex comprehension abilities, Phi-3-small-8k-instruct successfully combines context and inference to deduce that *2019/18* in the original text refers to the period from 2017 to 2018, and rewrites the text into a form more suitable for speech synthesis. These examples illustrate the unique advantages of our proposed method in both adhering to established rules and leveraging comprehension to tackle complex rewrites.

As shown in Table 8, we provide response examples from models trained with different speech data and alignment objectives. The results indicate that the model trained with high-quality speech data aligned with human responses accurately perceived the speech instructions and produced results that closely matched human responses.

Table 8: Example of responses from different models.

Context	
System Prompt	This is a chat between a user and an artificial intelligence assistant. The assistant gives helpful, detailed, and polite answers to the user's questions based on the context. The assistant should also indicate when the answer cannot be found in the context.
Document	The story follows a dinner party given by Bertha Young and her husband, Harry. The writing shows Bertha depicted as a happy soul, though quite naive about the world she lives in and those closest to her. The story opened up a lot of questions, about deceit, about knowing oneself and also about the possibility of homosexuality at the start of the 20th century. The story gives us a bird's eye view of the dinner party, which is attended by a couple, Mr. and Mrs. Norman Knight, who are close friends to Bertha and Harry. Guest, Eddie Warren, is an effeminate character, who adds an interesting mix to the party. The only other guest, Pearl Fulton, is someone who Bertha is mysteriously drawn to for reasons unknown to her at the start. The interesting thing is that Bertha's husband is presented to the reader as Bertha perceives him in her mind. Because Bertha is so naive, the reader first gets the impression that Harry is a crude, disinterested person who has a strong dislike for Pearl by his conversational tone and curtness towards her as the conversation unfolds. As the dinner party progresses, Bertha questions her own interest and fascination towards Pearl. The fact that Eddie, who is most likely homosexual, is present, lends an air to the possibility that Bertha's interest in Pearl is more than a platonic feeling one has towards a friend of the same sex. It is only after Bertha analyzes her feelings towards Pearl that she realizes that the connection she feels with Pearl is their mutual attraction for Harry, and coming out of her "blissful" reverie she makes the discovery that Harry and Pearl are having an affair. The title to this story alludes to the sentiment that ignorance is bliss. The story leaves the question about whether it is best to live blissfully ignorant of the truth or live with the knowledge of a harsh reality.
Prompt	Answer the following question with a short span. The answer needs to be just in a few words. What is Bertha's downfall when it comes to observing life and people?
Speech Instruction	What is Bertha's downfall when it comes to observing life and people?
Response	
Reference	She is naive.
Original+Golden	Harry.
Ours+Continue	Bertha's downfall comes from her naivety and inability to see the truth.
Ours+Golden	Bertha is naive.

6 CONCLUSION

In this paper, we propose a query rewriting method based on multi-LLM knowledge fusion, with multi-agent annotation and validation for data quality. Experiments demonstrate that this method consistently performs well across multiple datasets, improving the average data usability from 72% to 93%. Through ablation studies, we analyzed the effectiveness of each component, and the results show that different LLMs exhibit a certain degree of orthogonality in this zero-shot task. Moreover, using multiple annotation agents helps to better reduce data quality evaluation errors and improper data filtering caused by recognition and annotation errors of a single model. Our work enables the automated construction of high-quality language instruction datasets.

REPRODUCIBILITY STATEMENT

Implementation details   We give the Implementation details in Section 5.1.

Code And Dataset   We provide the main code of this paper in the supplementary materials, along with some data examples. The complete project files will be compiled in thenear future and open sourced in the github repository after the paper is accepted.

Assets and licenses   We have provided assets and licenses on all the open-source datasets, open-source models, and key open-source project used in this paper in Appendix E, along with download URL.

ETHICS STATEMENT

This study adheres to relevant ethical standards. The research team is committed to ensuring thetransparency and reproducibility of the code while taking measures to avoid potential discrimi-nationand bias. The findings of this study aim to advance scientific understanding while ensuring noharmful impacts on society.

REFERENCES

Marah Abdin, Jyoti Aneja, Hany Awadalla, Ahmed Awadallah, Ammar Ahmad Awan, Nguyen Bach, Amit Bahree, Arash Bakhtiari, Jianmin Bao, Harkirat Behl, Alon Benhaim, Misha Bilenko, Johan Bjorck, Sébastien Bubeck, Martin Cai, Qin Cai, Vishrav Chaudhary, Dong Chen, Dongdong Chen, Weizhu Chen, Yen-Chun Chen, Yi-Ling Chen, Hao Cheng, Parul Chopra, Xiyang Dai, Matthew Dixon, Ronen Eldan, Victor Fragoso, Jianfeng Gao, Mei Gao, Min Gao, Amit Garg, Allie Del Giorno, Abhishek Goswami, Suriya Gunasekar, Emman Haider, Junheng Hao, Russell J. Hewett, Wenxiang Hu, Jamie Huynh, Dan Iter, Sam Ade Jacobs, Mojan Javaheripi, Xin Jin, Nikos Karampatziakis, Piero Kauffmann, Mahoud Khademi, Dongwoo Kim, Young Jin Kim, Lev Kurilenko, James R. Lee, Yin Tat Lee, Yuanzhi Li, Yunsheng Li, Chen Liang, Lars Liden, Xihui Lin, Zeqi Lin, Ce Liu, Liyuan Liu, Mengchen Liu, Weishung Liu, Xiaodong Liu, Chong Luo, Piyush Madan, Ali Mahmoudzadeh, David Majercak, Matt Mazzola, Caio César Teodoro Mendes, Arindam Mitra, Hardik Modi, Anh Nguyen, Brandon Norick, Barun Patra, Daniel Perez-Becker, Thomas Portet, Reid Pryzant, Heyang Qin, Marko Radmilac, Liliang Ren, Gustavo de Rosa, Corby Rosset, Sambudha Roy, Olatunji Ruwase, Olli Saarikivi, Amin Saied, Adil Salim, Michael Santacroce, Shital Shah, Ning Shang, Hiteshi Sharma, Yelong Shen, Swadheen Shukla, Xia Song, Masahiro Tanaka, Andrea Tupini, Praneetha Vaddamanu, Chunyu Wang, Guanhua Wang, Lijuan Wang, Shuohang Wang, Xin Wang, Yu Wang, Rachel Ward, Wen Wen, Philipp Witte, Haiping Wu, Xiaoxia Wu, Michael Wyatt, Bin Xiao, Can Xu, Jiahang Xu, Weijian Xu, Jilong Xue, Sonali Yadav, Fan Yang, Jianwei Yang, Yifan Yang, Ziyi Yang, Donghan Yu, Lu Yuan, Chenruidong Zhang, Cyril Zhang, Jianwen Zhang, Li Lyna Zhang, Yi Zhang, Yue Zhang, Yunan Zhang, and Xiren Zhou. Phi-3 technical report: A highly capable language model locally on your phone, 2024. URL https://arxiv.org/abs/2404.14219.

R. Ardila, M. Branson, K. Davis, M. Henretty, M. Kohler, J. Meyer, R. Morais, L. Saunders, F. M. Tyers, and G. Weber. Common voice: A massively-multilingual speech corpus. In *Proceedings of the 12th Conference on Language Resources and Evaluation (LREC 2020)*, pp. 4211–4215, 2020.

Jie Chen, Yupeng Zhang, Bingning Wang, Wayne Xin Zhao, Ji-Rong Wen, and Weipeng Chen. Unveiling the flaws: Exploring imperfections in synthetic data and mitigation strategies for large language models, 2024. URL https://arxiv.org/abs/2406.12397.

Yunfei Chu, Jin Xu, Xiaohuan Zhou, Qian Yang, Shiliang Zhang, Zhijie Yan, Chang Zhou, and Jingren Zhou. Qwen-audio: Advancing universal audio understanding via unified large-scale audio-language models, 2023. URL https://arxiv.org/abs/2311.07919.

Yunfei Chu, Jin Xu, Qian Yang, Haojie Wei, Xipin Wei, Zhifang Guo, Yichong Leng, Yuanjun Lv, Jinzheng He, Junyang Lin, Chang Zhou, and Jingren Zhou. Qwen2-audio technical report, 2024. URL https://arxiv.org/abs/2407.10759.

Nilaksh Das, Saket Dingliwal, Srikanth Ronanki, Rohit Paturi, Zhaocheng Huang, Prashant Mathur, Jie Yuan, Dhanush Bekal, Xing Niu, Sai Muralidhar Jayanthi, Xilai Li, Karel Mundnich, Monica Sunkara, Sundararajan Srinivasan, Kyu J Han, and Katrin Kirchhoff. Speechverse: A large-scale generalizable audio language model, 2024. URL https://arxiv.org/abs/2405.08295.

Pradeep Dasigi, Nelson F. Liu, Ana Marasović, Noah A. Smith, and Matt Gardner. Quoref: A reading comprehension dataset with questions requiring coreferential reasoning. In Kentaro Inui, Jing Jiang, Vincent Ng, and Xiaojun Wan (eds.), *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 5925–5932, Hong Kong, China, November 2019. Association for Computational Linguistics. doi: 10.18653/v1/D19-1606. URL https://aclanthology.org/D19-1606.

Matt Deitke, Christopher Clark, Sangho Lee, Rohun Tripathi, Yue Yang, Jae Sung Park, Mohammadreza Salehi, Niklas Muennighoff, Kyle Lo, Luca Soldaini, Jiasen Lu, Taira Anderson, Erin Bransom, Kiana Ehsani, Huong Ngo, YenSung Chen, Ajay Patel, Mark Yatskar, Chris Callison-Burch, Andrew Head, Rose Hendrix, Favyen Bastani, Eli VanderBilt, Nathan Lambert, Yvonne Chou, Arnavi Chheda, Jenna Sparks, Sam Skjonsberg, Michael Schmitz, Aaron Sarnat, Byron

Bischoff, Pete Walsh, Chris Newell, Piper Wolters, Tanmay Gupta, Kuo-Hao Zeng, Jon Borchardt, Dirk Groeneveld, Jen Dumas, Crystal Nam, Sophie Lebrecht, Caitlin Wittlif, Carissa Schoenick, Oscar Michel, Ranjay Krishna, Luca Weihs, Noah A. Smith, Hannaneh Hajishirzi, Ross Girshick, Ali Farhadi, and Aniruddha Kembhavi. Molmo and pixmo: Open weights and open data for state-of-the-art multimodal models, 2024. URL https://arxiv.org/abs/2409.17146.

Dheeru Dua, Yizhong Wang, Pradeep Dasigi, Gabriel Stanovsky, Sameer Singh, and Matt Gardner. Drop: A reading comprehension benchmark requiring discrete reasoning over paragraphs, 2019. URL https://arxiv.org/abs/1903.00161.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, Anirudh Goyal, Anthony Hartshorn, Aobo Yang, Archi Mitra, Archie Sravankumar, Artem Korenev, Arthur Hinsvark, Arun Rao, Aston Zhang, Aurelien Rodriguez, Austen Gregerson, Ava Spataru, Baptiste Roziere, Bethany Biron, Binh Tang, Bobbie Chern, Charlotte Caucheteux, Chaya Nayak, Chloe Bi, Chris Marra, Chris McConnell, Christian Keller, Christophe Touret, Chunyang Wu, Corinne Wong, Cristian Canton Ferrer, Cyrus Nikolaidis, Damien Allonsius, Daniel Song, Danielle Pintz, Danny Livshits, David Esiobu, Dhruv Choudhary, Dhruv Mahajan, Diego Garcia-Olano, Diego Perino, Dieuwke Hupkes, Egor Lakomkin, Ehab AlBadawy, Elina Lobanova, Emily Dinan, Eric Michael Smith, Filip Radenovic, Frank Zhang, Gabriel Synnaeve, Gabrielle Lee, Georgia Lewis Anderson, Graeme Nail, Gregoire Mialon, Guan Pang, Guillem Cucurell, Hailey Nguyen, Hannah Korevaar, Hu Xu, Hugo Touvron, Iliyan Zarov, Imanol Arrieta Ibarra, Isabel Kloumann, Ishan Misra, Ivan Evtimov, Jade Copet, Jaewon Lee, Jan Geffert, Jana Vranes, Jason Park, Jay Mahadeokar, Jeet Shah, Jelmer van der Linde, Jennifer Billock, Jenny Hong, Jenya Lee, Jeremy Fu, Jianfeng Chi, Jianyu Huang, Jiawen Liu, Jie Wang, Jiecao Yu, Joanna Bitton, Joe Spisak, Jongsoo Park, Joseph Rocca, Joshua Johnstun, Joshua Saxe, Junteng Jia, Kalyan Vasuden Alwala, Kartikeya Upasani, Kate Plawiak, Ke Li, Kenneth Heafield, Kevin Stone, Khalid El-Arini, Krithika Iyer, Kshitiz Malik, Kuenley Chiu, Kunal Bhalla, Lauren Rantala-Yeary, Laurens van der Maaten, Lawrence Chen, Liang Tan, Liz Jenkins, Louis Martin, Lovish Madaan, Lubo Malo, Lukas Blecher, Lukas Landzaat, Luke de Oliveira, Madeline Muzzi, Mahesh Pasupuleti, Mannat Singh, Manohar Paluri, Marcin Kardas, Mathew Oldham, Mathieu Rita, Maya Pavlova, Melanie Kambadur, Mike Lewis, Min Si, Mitesh Kumar Singh, Mona Hassan, Naman Goyal, Narjes Torabi, Nikolay Bashlykov, Nikolay Bogoychev, Niladri Chatterji, Olivier Duchenne, Onur Çelebi, Patrick Alrassy, Pengchuan Zhang, Pengwei Li, Petar Vasic, Peter Weng, Prajjwal Bhargava, Pratik Dubal, Praveen Krishnan, Punit Singh Koura, Puxin Xu, Qing He, Qingxiao Dong, Ragavan Srinivasan, Raj Ganapathy, Ramon Calderer, Ricardo Silveira Cabral, Robert Stojnic, Roberta Raileanu, Rohit Girdhar, Rohit Patel, Romain Sauvestre, Ronnie Polidoro, Roshan Sumbaly, Ross Taylor, Ruan Silva, Rui Hou, Rui Wang, Saghar Hosseini, Sahana Chennabasappa, Sanjay Singh, Sean Bell, Seohyun Sonia Kim, Sergey Edunov, Shaoliang Nie, Sharan Narang, Sharath Raparthy, Sheng Shen, Shengye Wan, Shruti Bhosale, Shun Zhang, Simon Vandenhende, Soumya Batra, Spencer Whitman, Sten Sootla, Stephane Collot, Suchin Gururangan, Sydney Borodinsky, Tamar Herman, Tara Fowler, Tarek Sheasha, Thomas Georgiou, Thomas Scialom, Tobias Speckbacher, Todor Mihaylov, Tong Xiao, Ujjwal Karn, Vedanuj Goswami, Vibhor Gupta, Vignesh Ramanathan, Viktor Kerkez, Vincent Gonguet, Virginie Do, Vish Vogeti, Vladan Petrovic, Weiwei Chu, Wenhan Xiong, Wenyin Fu, Whitney Meers, Xavier Martinet, Xiaodong Wang, Xiaoqing Ellen Tan, Xinfeng Xie, Xuchao Jia, Xuewei Wang, Yaelle Goldschlag, Yashesh Gaur, Yasmine Babaei, Yi Wen, Yiwen Song, Yuchen Zhang, Yue Li, Yuning Mao, Zacharie Delpierre Coudert, Zheng Yan, Zhengxing Chen, Zoe Papakipos, Aaditya Singh, Aaron Grattafiori, Abha Jain, Adam Kelsey, Adam Shajnfeld, Adithya Gangidi, Adolfo Victoria, Ahuva Goldstand, Ajay Menon, Ajay Sharma, Alex Boesenberg, Alex Vaughan, Alexei Baevski, Allie Feinstein, Amanda Kallet, Amit Sangani, Anam Yunus, Andrei Lupu, Andres Alvarado, Andrew Caples, Andrew Gu, Andrew Ho, Andrew Poulton, Andrew Ryan, Ankit Ramchandani, Annie Franco, Aparajita Saraf, Arkabandhu Chowdhury, Ashley Gabriel, Ashwin Bharambe, Assaf Eisenman, Azadeh Yazdan, Beau James, Ben Maurer, Benjamin Leonhardi, Bernie Huang, Beth Loyd, Beto De Paola, Bhargavi Paranjape, Bing Liu, Bo Wu, Boyu Ni, Braden Hancock, Bram Wasti, Brandon Spence, Brani Stojkovic, Brian Gamido, Britt Montalvo, Carl Parker, Carly Burton, Catalina Mejia, Changhan Wang, Changkyu Kim, Chao Zhou, Chester Hu, Ching-Hsiang Chu, Chris Cai, Chris Tindal, Christoph Feichtenhofer, Damon Civin, Dana Beaty, Daniel Kreymer, Daniel Li, Danny Wyatt, David Adkins, David Xu, Davide Testuggine, Delia David, Devi Parikh, Diana Liskovich, Didem Foss, Dingkang Wang, Duc Le, Dustin Holland, Edward Dowling, Eissa Jamil,

Elaine Montgomery, Eleonora Presani, Emily Hahn, Emily Wood, Erik Brinkman, Esteban Arcaute, Evan Dunbar, Evan Smothers, Fei Sun, Felix Kreuk, Feng Tian, Firat Ozgenel, Francesco Caggioni, Francisco Guzmán, Frank Kanayet, Frank Seide, Gabriela Medina Florez, Gabriella Schwarz, Gada Badeer, Georgia Swee, Gil Halpern, Govind Thattai, Grant Herman, Grigory Sizov, Guangyi, Zhang, Guna Lakshminarayanan, Hamid Shojanazeri, Han Zou, Hannah Wang, Hanwen Zha, Haroun Habeeb, Harrison Rudolph, Helen Suk, Henry Aspegren, Hunter Goldman, Ibrahim Damlaj, Igor Molybog, Igor Tufanov, Irina-Elena Veliche, Itai Gat, Jake Weissman, James Geboski, James Kohli, Japhet Asher, Jean-Baptiste Gaya, Jeff Marcus, Jeff Tang, Jennifer Chan, Jenny Zhen, Jeremy Reizenstein, Jeremy Teboul, Jessica Zhong, Jian Jin, Jingyi Yang, Joe Cummings, Jon Carvill, Jon Shepard, Jonathan McPhie, Jonathan Torres, Josh Ginsburg, Junjie Wang, Kai Wu, Kam Hou U, Karan Saxena, Karthik Prasad, Kartikay Khandelwal, Katayoun Zand, Kathy Matosich, Kaushik Veeraraghavan, Kelly Michelena, Keqian Li, Kun Huang, Kunal Chawla, Kushal Lakhotia, Kyle Huang, Lailin Chen, Lakshya Garg, Lavender A, Leandro Silva, Lee Bell, Lei Zhang, Liangpeng Guo, Licheng Yu, Liron Moshkovich, Luca Wehrstedt, Madian Khabsa, Manav Avalani, Manish Bhatt, Maria Tsimpoukelli, Martynas Mankus, Matan Hasson, Matthew Lennie, Matthias Reso, Maxim Groshev, Maxim Naumov, Maya Lathi, Meghan Keneally, Michael L. Seltzer, Michal Valko, Michelle Restrepo, Mihir Patel, Mik Vyatskov, Mikayel Samvelyan, Mike Clark, Mike Macey, Mike Wang, Miquel Jubert Hermoso, Mo Metanat, Mohammad Rastegari, Munish Bansal, Nandhini Santhanam, Natascha Parks, Natasha White, Navyata Bawa, Nayan Singhal, Nick Egebo, Nicolas Usunier, Nikolay Pavlovich Laptev, Ning Dong, Ning Zhang, Norman Cheng, Oleg Chernoguz, Olivia Hart, Omkar Salpekar, Ozlem Kalinli, Parkin Kent, Parth Parekh, Paul Saab, Pavan Balaji, Pedro Rittner, Philip Bontrager, Pierre Roux, Piotr Dollar, Polina Zvyagina, Prashant Ratanchandani, Pritish Yuvraj, Qian Liang, Rachad Alao, Rachel Rodriguez, Rafi Ayub, Raghotham Murthy, Raghu Nayani, Rahul Mitra, Raymond Li, Rebekkah Hogan, Robin Battey, Rocky Wang, Rohan Maheswari, Russ Howes, Ruty Rinott, Sai Jayesh Bondu, Samyak Datta, Sara Chugh, Sara Hunt, Sargun Dhillon, Sasha Sidorov, Satadru Pan, Saurabh Verma, Seiji Yamamoto, Sharadh Ramaswamy, Shaun Lindsay, Shaun Lindsay, Sheng Feng, Shenghao Lin, Shengxin Cindy Zha, Shiva Shankar, Shuqiang Zhang, Shuqiang Zhang, Sinong Wang, Sneha Agarwal, Soji Sajuyigbe, Soumith Chintala, Stephanie Max, Stephen Chen, Steve Kehoe, Steve Satterfield, Sudarshan Govindaprasad, Sumit Gupta, Sungmin Cho, Sunny Virk, Suraj Subramanian, Sy Choudhury, Sydney Goldman, Tal Remez, Tamar Glaser, Tamara Best, Thilo Kohler, Thomas Robinson, Tianhe Li, Tianjun Zhang, Tim Matthews, Timothy Chou, Tzook Shaked, Varun Vontimitta, Victoria Ajayi, Victoria Montanez, Vijai Mohan, Vinay Satish Kumar, Vishal Mangla, Vítor Albiero, Vlad Ionescu, Vlad Poenaru, Vlad Tiberiu Mihailescu, Vladimir Ivanov, Wei Li, Wenchen Wang, Wenwen Jiang, Wes Bouaziz, Will Constable, Xiaocheng Tang, Xiaofang Wang, Xiaojian Wu, Xiaolan Wang, Xide Xia, Xilun Wu, Xinbo Gao, Yanjun Chen, Ye Hu, Ye Jia, Ye Qi, Yenda Li, Yilin Zhang, Ying Zhang, Yossi Adi, Youngjin Nam, Yu, Wang, Yuchen Hao, Yundi Qian, Yuzi He, Zach Rait, Zachary DeVito, Zef Rosnbrick, Zhaoduo Wen, Zhenyu Yang, and Zhiwei Zhao. The llama 3 herd of models, 2024. URL https://arxiv.org/abs/2407.21783.

Qingkai Fang, Shoutao Guo, Yan Zhou, Zhengrui Ma, Shaolei Zhang, and Yang Feng. Llama-omni: Seamless speech interaction with large language models, 2024. URL https://arxiv.org/abs/2409.06666.

Yassir Fathullah, Chunyang Wu, Egor Lakomkin, Ke Li, Junteng Jia, Yuan Shangguan, Jay Mahadeokar, Ozlem Kalinli, Christian Fuegen, and Mike Seltzer. Audiochatllama: Towards general-purpose speech abilities for llms, 2024. URL https://arxiv.org/abs/2311.06753.

Yuan Gong, Alexander H. Liu, Hongyin Luo, Leonid Karlinsky, and James Glass. Joint audio and speech understanding, 2023. URL https://arxiv.org/abs/2309.14405.

Guanbo Wang Jiayu Du Wei-Qiang Zhang Chao Weng Dan Su Daniel Povey Jan Trmal Junbo Zhang Mingjie Jin Sanjeev Khudanpur Shinji Watanabe Shuaijiang Zhao Wei Zou Xiangang Li Xuchen Yao Yongqing Wang Yujun Wang Zhao You Zhiyong Yan Guoguo Chen, Shuzhou Chai. Gigaspeech: An evolving, multi-domain asr corpus with 10,000 hours of transcribed audio. In *Proc. Interspeech 2021*, 2021.

Addison Howard, RichardSproat, wellformedness, and Will Cukierski. Text normalization challenge - english language. https://kaggle.com/competitions/text-normalization-challenge-english-language, 2017. Kaggle.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. Lora: Low-rank adaptation of large language models, 2021. URL `https://arxiv.org/abs/2106.09685`.

Tomáš Kočiský, Jonathan Schwarz, Phil Blunsom, Chris Dyer, Karl Moritz Hermann, Gábor Melis, and Edward Grefenstette. The narrativeqa reading comprehension challenge, 2017. URL `https://arxiv.org/abs/1712.07040`.

Yoach Lacombe, Vaibhav Srivastav, and Sanchit Gandhi. Parler-tts. `https://github.com/huggingface/parler-tts`, 2024.

Hugo Laurençon, Andrés Marafioti, Victor Sanh, and Léo Tronchon. Building and better understanding vision-language models: insights and future directions., 2024.

Matthew Le, Apoorv Vyas, Bowen Shi, Brian Karrer, Leda Sari, Rashel Moritz, Mary Williamson, Vimal Manohar, Yossi Adi, Jay Mahadeokar, and Wei-Ning Hsu. Voicebox: Text-guided multilingual universal speech generation at scale, 2023. URL `https://arxiv.org/abs/2306.15687`.

Chin-Yew Lin. ROUGE: A package for automatic evaluation of summaries. In *Text Summarization Branches Out*, pp. 74–81, Barcelona, Spain, July 2004. Association for Computational Linguistics. URL `https://aclanthology.org/W04-1013`.

Kevin Lin, Oyvind Tafjord, Peter Clark, and Matt Gardner. Reasoning over paragraph effects in situations, 2019. URL `https://arxiv.org/abs/1908.05852`.

Tsung-Yi Lin, Michael Maire, Serge Belongie, Lubomir Bourdev, Ross Girshick, James Hays, Pietro Perona, Deva Ramanan, C. Lawrence Zitnick, and Piotr Dollár. Microsoft coco: Common objects in context, 2015. URL `https://arxiv.org/abs/1405.0312`.

Siyang Liu, Chujie Zheng, Orianna Demasi, Sahand Sabour, Yu Li, Zhou Yu, Yong Jiang, and Minlie Huang. Towards emotional support dialog systems, 2021. URL `https://arxiv.org/abs/2106.01144`.

Dan Lyth and Simon King. Natural language guidance of high-fidelity text-to-speech with synthetic annotations, 2024. URL `https://arxiv.org/abs/2402.01912`.

Niklas Muennighoff, Nouamane Tazi, Loïc Magne, and Nils Reimers. Mteb: Massive text embedding benchmark, 2023. URL `https://arxiv.org/abs/2210.07316`.

OpenAI, Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, Red Avila, Igor Babuschkin, Suchir Balaji, Valerie Balcom, Paul Baltescu, Haiming Bao, Mohammad Bavarian, Jeff Belgum, Irwan Bello, Jake Berdine, Gabriel Bernadett-Shapiro, Christopher Berner, Lenny Bogdonoff, Oleg Boiko, Madelaine Boyd, Anna-Luisa Brakman, Greg Brockman, Tim Brooks, Miles Brundage, Kevin Button, Trevor Cai, Rosie Campbell, Andrew Cann, Brittany Carey, Chelsea Carlson, Rory Carmichael, Brooke Chan, Che Chang, Fotis Chantzis, Derek Chen, Sully Chen, Ruby Chen, Jason Chen, Mark Chen, Ben Chess, Chester Cho, Casey Chu, Hyung Won Chung, Dave Cummings, Jeremiah Currier, Yunxing Dai, Cory Decareaux, Thomas Degry, Noah Deutsch, Damien Deville, Arka Dhar, David Dohan, Steve Dowling, Sheila Dunning, Adrien Ecoffet, Atty Eleti, Tyna Eloundou, David Farhi, Liam Fedus, Niko Felix, Simón Posada Fishman, Juston Forte, Isabella Fulford, Leo Gao, Elie Georges, Christian Gibson, Vik Goel, Tarun Gogineni, Gabriel Goh, Rapha Gontijo-Lopes, Jonathan Gordon, Morgan Grafstein, Scott Gray, Ryan Greene, Joshua Gross, Shixiang Shane Gu, Yufei Guo, Chris Hallacy, Jesse Han, Jeff Harris, Yuchen He, Mike Heaton, Johannes Heidecke, Chris Hesse, Alan Hickey, Wade Hickey, Peter Hoeschele, Brandon Houghton, Kenny Hsu, Shengli Hu, Xin Hu, Joost Huizinga, Shantanu Jain, Shawn Jain, Joanne Jang, Angela Jiang, Roger Jiang, Haozhun Jin, Denny Jin, Shino Jomoto, Billie Jonn, Heewoo Jun, Tomer Kaftan, Łukasz Kaiser, Ali Kamali, Ingmar Kanitscheider, Nitish Shirish Keskar, Tabarak Khan, Logan Kilpatrick, Jong Wook Kim, Christina Kim, Yongjik Kim, Jan Hendrik Kirchner, Jamie Kiros, Matt Knight, Daniel Kokotajlo, Łukasz Kondraciuk, Andrew Kondrich, Aris Konstantinidis, Kyle Kosic, Gretchen Krueger, Vishal Kuo, Michael Lampe, Ikai Lan, Teddy Lee, Jan Leike, Jade Leung, Daniel

Levy, Chak Ming Li, Rachel Lim, Molly Lin, Stephanie Lin, Mateusz Litwin, Theresa Lopez, Ryan Lowe, Patricia Lue, Anna Makanju, Kim Malfacini, Sam Manning, Todor Markov, Yaniv Markovski, Bianca Martin, Katie Mayer, Andrew Mayne, Bob McGrew, Scott Mayer McKinney, Christine McLeavey, Paul McMillan, Jake McNeil, David Medina, Aalok Mehta, Jacob Menick, Luke Metz, Andrey Mishchenko, Pamela Mishkin, Vinnie Monaco, Evan Morikawa, Daniel Mossing, Tong Mu, Mira Murati, Oleg Murk, David Mély, Ashvin Nair, Reiichiro Nakano, Rajeev Nayak, Arvind Neelakantan, Richard Ngo, Hyeonwoo Noh, Long Ouyang, Cullen O'Keefe, Jakub Pachocki, Alex Paino, Joe Palermo, Ashley Pantuliano, Giambattista Parascandolo, Joel Parish, Emy Parparita, Alex Passos, Mikhail Pavlov, Andrew Peng, Adam Perelman, Filipe de Avila Belbute Peres, Michael Petrov, Henrique Ponde de Oliveira Pinto, Michael, Pokorny, Michelle Pokrass, Vitchyr H. Pong, Tolly Powell, Alethea Power, Boris Power, Elizabeth Proehl, Raul Puri, Alec Radford, Jack Rae, Aditya Ramesh, Cameron Raymond, Francis Real, Kendra Rimbach, Carl Ross, Bob Rotsted, Henri Roussez, Nick Ryder, Mario Saltarelli, Ted Sanders, Shibani Santurkar, Girish Sastry, Heather Schmidt, David Schnurr, John Schulman, Daniel Selsam, Kyla Sheppard, Toki Sherbakov, Jessica Shieh, Sarah Shoker, Pranav Shyam, Szymon Sidor, Eric Sigler, Maddie Simens, Jordan Sitkin, Katarina Slama, Ian Sohl, Benjamin Sokolowsky, Yang Song, Natalie Staudacher, Felipe Petroski Such, Natalie Summers, Ilya Sutskever, Jie Tang, Nikolas Tezak, Madeleine B. Thompson, Phil Tillet, Amin Tootoonchian, Elizabeth Tseng, Preston Tuggle, Nick Turley, Jerry Tworek, Juan Felipe Cerón Uribe, Andrea Vallone, Arun Vijayvergiya, Chelsea Voss, Carroll Wainwright, Justin Jay Wang, Alvin Wang, Ben Wang, Jonathan Ward, Jason Wei, CJ Weinmann, Akila Welihinda, Peter Welinder, Jiayi Weng, Lilian Weng, Matt Wiethoff, Dave Willner, Clemens Winter, Samuel Wolrich, Hannah Wong, Lauren Workman, Sherwin Wu, Jeff Wu, Michael Wu, Kai Xiao, Tao Xu, Sarah Yoo, Kevin Yu, Qiming Yuan, Wojciech Zaremba, Rowan Zellers, Chong Zhang, Marvin Zhang, Shengjia Zhao, Tianhao Zheng, Juntang Zhuang, William Zhuk, and Barret Zoph. Gpt-4 technical report, 2024. URL https://arxiv.org/abs/2303.08774.

piAI. Text normalization. https://www.kaggle.com/code/econdata/text-normalization, 2017. Accessed: 2024-11-27.

Vineel Pratap, Qiantong Xu, Anuroop Sriram, Gabriel Synnaeve, and Ronan Collobert. Mls: A large-scale multilingual dataset for speech research. *ArXiv*, abs/2012.03411, 2020.

Vineel Pratap, Andros Tjandra, Bowen Shi, Paden Tomasello, Arun Babu, Sayani Kundu, Ali Elkahky, Zhaoheng Ni, Apoorv Vyas, Maryam Fazel-Zarandi, Alexei Baevski, Yossi Adi, Xiaohui Zhang, Wei-Ning Hsu, Alexis Conneau, and Michael Auli. Scaling speech technology to 1,000+ languages. *arXiv*, 2023.

Alec Radford, Jong Wook Kim, Tao Xu, Greg Brockman, Christine McLeavey, and Ilya Sutskever. Robust speech recognition via large-scale weak supervision, 2022. URL https://arxiv.org/abs/2212.04356.

Pranav Rajpurkar, Jian Zhang, Konstantin Lopyrev, and Percy Liang. Squad: 100,000+ questions for machine comprehension of text, 2016. URL https://arxiv.org/abs/1606.05250.

Pranav Rajpurkar, Robin Jia, and Percy Liang. Know what you don't know: Unanswerable questions for squad, 2018. URL https://arxiv.org/abs/1806.03822.

Mohamed El Amine Seddik, Suei-Wen Chen, Soufiane Hayou, Pierre Youssef, and Merouane Debbah. How bad is training on synthetic data? a statistical analysis of language model collapse, 2024. URL https://arxiv.org/abs/2404.05090.

Yu Shu, Siwei Dong, Guangyao Chen, Wenhao Huang, Ruihua Zhang, Daochen Shi, Qiqi Xiang, and Yemin Shi. Llasm: Large language and speech model, 2023. URL https://arxiv.org/abs/2308.15930.

Vaibhav Srivastav, Somshubra Majumdar, Nithin Koluguri, Adel Moumen, Sanchit Gandhi, et al. Open automatic speech recognition leaderboard. https://huggingface.co/spaces/hf-audio/open_asr_leaderboard, 2023.

Changli Tang, Wenyi Yu, Guangzhi Sun, Xianzhao Chen, Tian Tan, Wei Li, Lu Lu, Zejun Ma, and Chao Zhang. Salmonn: Towards generic hearing abilities for large language models, 2024. URL https://arxiv.org/abs/2310.13289.

Fanqi Wan, Longguang Zhong, Ziyi Yang, Ruijun Chen, and Xiaojun Quan. Fusechat: Knowledge fusion of chat models, 2024. URL https://arxiv.org/abs/2408.07990.

Chengyi Wang, Sanyuan Chen, Yu Wu, Ziqiang Zhang, Long Zhou, Shujie Liu, Zhuo Chen, Yanqing Liu, Huaming Wang, Jinyu Li, Lei He, Sheng Zhao, and Furu Wei. Neural codec language models are zero-shot text to speech synthesizers, 2023. URL https://arxiv.org/abs/2301.02111.

Wenbin Wang, Yang Song, and Sanjay Jha. Globe: A high-quality english corpus with global accents for zero-shot speaker adaptive text-to-speech, 2024.

An Yang, Baosong Yang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Zhou, Chengpeng Li, Chengyuan Li, Dayiheng Liu, Fei Huang, Guanting Dong, Haoran Wei, Huan Lin, Jialong Tang, Jialin Wang, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Ma, Jianxin Yang, Jin Xu, Jingren Zhou, Jinze Bai, Jinzheng He, Junyang Lin, Kai Dang, Keming Lu, Keqin Chen, Kexin Yang, Mei Li, Mingfeng Xue, Na Ni, Pei Zhang, Peng Wang, Ru Peng, Rui Men, Ruize Gao, Runji Lin, Shijie Wang, Shuai Bai, Sinan Tan, Tianhang Zhu, Tianhao Li, Tianyu Liu, Wenbin Ge, Xiaodong Deng, Xiaohuan Zhou, Xingzhang Ren, Xinyu Zhang, Xipin Wei, Xuancheng Ren, Xuejing Liu, Yang Fan, Yang Yao, Yichang Zhang, Yu Wan, Yunfei Chu, Yuqiong Liu, Zeyu Cui, Zhenru Zhang, Zhifang Guo, and Zhihao Fan. Qwen2 technical report, 2024a. URL https://arxiv.org/abs/2407.10671.

Qian Yang, Jin Xu, Wenrui Liu, Yunfei Chu, Ziyue Jiang, Xiaohuan Zhou, Yichong Leng, Yuanjun Lv, Zhou Zhao, Chang Zhou, and Jingren Zhou. Air-bench: Benchmarking large audio-language models via generative comprehension, 2024b. URL https://arxiv.org/abs/2402.07729.

Linhao Ye, Zhikai Lei, Jia-Peng Yin, Qin Chen, Jie Zhou, and Liang He. Boosting conversational question answering with fine-grained retrieval-augmentation and self-check. *ArXiv*, abs/2403.18243, 2024. URL https://api.semanticscholar.org/CorpusID:268724200.

Dong Zhang, Shimin Li, Xin Zhang, Jun Zhan, Pengyu Wang, Yaqian Zhou, and Xipeng Qiu. Speechgpt: Empowering large language models with intrinsic cross-modal conversational abilities, 2023a. URL https://arxiv.org/abs/2305.11000.

Ziqiang Zhang, Long Zhou, Chengyi Wang, Sanyuan Chen, Yu Wu, Shujie Liu, Zhuo Chen, Yanqing Liu, Huaming Wang, Jinyu Li, Lei He, Sheng Zhao, and Furu Wei. Speak foreign languages with your own voice: Cross-lingual neural codec language modeling, 2023b. URL https://arxiv.org/abs/2303.03926.

Wenliang Zhao, Xumin Yu, and Zengyi Qin. Melotts: High-quality multi-lingual multi-accent text-to-speech, 2023. URL https://github.com/myshell-ai/MeloTTS.

Fengbin Zhu, Wenqiang Lei, Youcheng Huang, Chao Wang, Shuo Zhang, Jiancheng Lv, Fuli Feng, and Tat-Seng Chua. Tat-qa: A question answering benchmark on a hybrid of tabular and textual content in finance, 2021. URL https://arxiv.org/abs/2105.07624.

A   THE PROMPTS USED

Table 9: Prompts input to GPT-4 for generating speech descriptions.

> # Task Define #
> Generate a description of the speaker's voice in English according to the description and rules below.
>
> # The rules #
> (1) Six characteristics are given below to describe the speaker's voice
> (2) Please refer to the features and examples to give corresponding descriptions
>
> # Example #
>
> A female voice with an American accent enunciates every word with precision. The speaker's voice is very close-sounding and clean, and the recording is excellent, capturing her voice with crisp clarity.

Table 10: Prompt for query rewriting.

> # Task Define # Please express the non-word parts of the text as English words without changing the original meaning of the text. Follow the format of the example and output the result directly without any output that is not related to the result.
>
> # The rules #
>
> (1) For the year, month and other parts containing numbers, please use English words to express these numbers.
>
> (2) For Roman numerals and Greek symbols. Please convert the same form to the corresponding English word.
>
> (3) For the symbols of chemistry, physics and other fields, please express these symbols in the form of English words.

Table 11: The prompts used for fine-tuning LSLMs. *Document* refers to the text associated with the *Speech*, *Speech* represents the user's query, and *Response* refers to the reference reply, which serves as the alignment target for training.

```
<|im_start|>system

This is a chat between a user and an artificial intelligence assistant. The assistant gives help-
ful, detailed, and polite answers to the user's questions based on the context. The assistant
should also indicate when the answer cannot be found in the context.

{document}
<|im_end|>
<|im_start|>user
Answer the following question with a short span. The answer needs to be just in a few
words.
{Speech} <|im_end|>
<|im_start|>assistant
{Response}
<|im_end|>
```

Table 12: Prompts for consistency verification.

```
# Task #

Please evaluate whether the following two sentences convey identical meanings in content.
Use yes or no to give your verdict.

# Sentence 1 #

{original_text}

# Sentence 2 #

{rewrite_text}
```

B   MORE EXPERIMENT SETTINGS

B.1   IMPLEMENTATION DETAILS

In this paper, we use LoRA (Hu et al., 2021) for training. For the training in Knowledge Fusion, we setting $r = 8$ and $a = 16$. The peak learning rate was set to 3e-4, and the cosine scheduler was used for learning rate adjustment. For the training in LSLMs Finetune, we set $r = 8$ and $a = 32$. The peak learning rate was set to 3e-5, and the cosine scheduler was used for learning rate adjustment. During training, we utilized 4 NVIDIA A40 GPUs, enabled gradient checkpointing to save memory, and applied gradient accumulation with backward occurring every 64 samples. The batch size per device was set to 1. For the generative evaluation phase, we evaluated our results on a single NVIDIA A40 GPU, setting top-p to 0.5, top-k to 20, repetition penalty to 1.1, and temperature to 0.7. For speech synthesis, we use a single NVIDIA A40 GPU with the batch size set to 1.

B.2   MORE INFORMATION ABOUT THE DATASET

In Table 13, we provide more information about the dataset we used.

Table 13: Description and num of the datasets used in this paper. *Num* refers to the number of samples in the dataset.

Dataset Name	Description	Num
DROP	A reading comprehension dataset that requires systems to perform discrete reasoning.	29k
Quoref	A reading comprehension dataset that focuses on coreference resolution.	11k
ROPES	A reading comprehension dataset requires reasoning about the effects of causes in unfamiliar situations using provided passages.	10k
NarrativeQA	A reading comprehension dataset requires answering questions based on understanding long, complex narrative texts.	40k
TAT-QA	A tabular and textual question-answering dataset requiring numerical reasoning over tables and text.	11k
SQUAD1.1	A reading comprehension dataset where models answer questions based on Wikipedia passages.	87k
SQUAD2.0	It extends SQuAD1.1 by adding unanswerable questions, requiring models to not only answer questions based on Wikipedia passages but also determine when no answer is possible.	87k

B.3   THE EMBEDDING MODELS USED IN THIS PAPER

gte-large-en-v1.5   is a text embedding model from the GTE-v1.5 series, developed by the Institute for Intelligent Computing at Alibaba Group. The model supports a context length of up to 8192 and is built on a Transformer++ encoder backbone, which combines BERT, RoPE, and GLU technologies.

mxbai-embed-large-v1   is a text embedding model which developed by Mixedbread.

stella_en_400M_v5   is a text embedding model that is based on the Alibaba-NLP/gte-large-en-v1.5 and Alibaba-NLP/gte-Qwen2-1.5B-instruct models. The model simplifies the use of prompts, providing two main prompts for general tasks: one for sentence-to-paragraph (s2p) and another for sentence-to-sentence (s2s) tasks.

C   MORE EXPERIMENTAL RESULTS

C.1   EXPERIMENTAL RESULTS UNDER THE SINGLE-SPEAKER SETTING

Table 14: Evaluation results on SIM for different datasets under the Single-Speaker Setting.

TTS Model	Method	Drop	narrativeqa	Quoref	ropes	squad1.1	squad2.0	tatqa	Average
MeloTTS	Original	96.61	95.13	97.27	98.22	95.75	93.48	97.43	96.27
	TN	97.50	96.36	98.00	98.83	94.86	95.54	97.96	97.01
	Phi3	97.57	95.82	97.81	98.70	96.74	95.71	98.29	97.23
	Qwen2	97.59	96.42	98.01	98.85	96.98	95.68	98.19	97.39
	Llama3	97.65	96.32	98.01	98.91	97.10	95.78	98.30	97.44
	Ours w/o KF	**98.19**	**97.02**	**98.37**	**99.12**	**97.59**	**96.80**	**98.53**	**97.94**
MMS-TTS-ENG	Original	92.05	91.46	93.77	93.42	91.28	91.23	84.61	91.12
	TN	94.22	**93.82**	95.64	95.14	93.86	93.26	90.75	93.81
	Phi3	95.06	93.00	95.46	94.97	93.90	93.86	92.52	94.11
	Qwen2	95.18	91.47	95.51	95.04	94.32	94.62	91.81	93.99
	Llama3	94.52	91.47	95.51	94.98	94.85	94.82	94.30	94.35
	Ours w/o KF	**96.86**	93.01	**96.51**	**95.95**	**95.96**	**96.07**	**96.17**	**95.79**
Parler-TTS-Large-v1	Original	93.04	95.26	95.51	96.01	92.75	91.99	81.63	92.31
	TN	96.41	97.39	97.63	98.06	95.89	95.61	89.07	95.72
	Phi3	97.21	97.40	97.95	97.97	96.49	96.19	93.80	96.72
	Qwen2	97.17	97.51	97.93	98.05	96.29	95.64	91.63	96.32
	Llama3	97.41	97.41	97.78	96.74	96.74	96.44	96.01	96.93
	Ours w/o KF	**98.09**	**98.19**	**98.52**	**98.30**	**97.31**	**97.32**	**97.21**	**97.85**

Table 15: Evaluation results on Pass for different datasets under the Single-Speaker Setting.

TTS Model	Method	Drop	narrativeqa	Quoref	ropes	squad1.1	squad2.0	tatqa	Average
MeloTTS	Original	86.12	79.21	88.57	93.21	82.91	74.87	90.25	85.02
	TN	90.04	84.60	92.19	95.84	83.53	82.38	92.46	88.72
	Phi3	90.51	82.16	91.08	95.41	87.20	83.30	93.79	89.07
	Qwen2	90.59	85.27	92.20	96.17	88.32	83.32	93.42	89.90
	Llama3	90.84	84.63	92.12	96.48	88.74	83.58	93.93	90.05
	Ours w/o KF	**93.27**	**87.89**	**93.96**	**97.37**	**90.86**	**87.69**	**94.70**	**92.25**
MMS-TTS-ENG	Original	64.55	63.18	72.36	73.53	64.58	64.28	31.22	61.96
	TN	76.63	**72.99**	81.00	81.84	74.56	71.95	59.02	74.00
	Phi3	80.50	69.30	80.37	81.11	75.01	74.80	66.08	75.31
	Qwen2	81.38	63.24	80.83	81.51	77.14	78.34	61.32	74.82
	Llama3	81.48	63.18	80.56	81.24	79.13	78.97	73.09	76.81
	Ours w/o KF	**86.98**	69.33	**85.76**	**86.49**	**84.08**	**96.07**	**84.19**	**84.70**
Parler-TTS-Large-v1	Original	73.56	82.91	83.68	88.04	72.83	70.41	26.07	71.07
	TN	85.52	90.54	91.05	94.44	83.13	82.43	49.38	82.36
	Phi3	90.25	90.47	92.92	94.10	86.74	85.91	75.21	87.94
	Qwen2	90.40	91.16	92.42	94.64	86.24	83.92	63.68	86.07
	Llama3	91.34	90.59	92.16	93.61	87.88	87.14	85.22	89.71
	Ours w/o KF	**94.37**	**94.32**	**95.61**	**96.39**	**90.37**	**90.85**	**90.12**	**93.15**

C.2 RESULTS EVALUATED BY DIFFERENT WORD EMBEDDING MODELS

Table 16: The quality evaluation results of our proposed method in datasets. The similarity here is the average of the results calculated by gte-large-en-v1.5 (Appendix B.3).

Method	ASR Model	DROP			Quoref			ROPES		
		WER↓	SIM↑	Pass↑	WER↓	SIM↑	Pass↑	WER↓	SIM↑	Pass↑
-	canary	10.928	91.301	67.491	5.455	93.745	76.792	6.971	95.572	82.754
-	whisper	11.175	91.568	69.139	5.322	93.964	77.965	7.087	95.458	82.726
-	parakeet	10.416	90.881	67.717	5.084	93.632	77.656	6.208	95.419	84.237
-	Ours	**9.289**	**93.488**	**74.396**	**4.144**	**95.836**	**84.058**	**5.193**	**97.122**	**89.290**
phi3	Ours	4.967	97.225	89.169	2.533	97.877	91.788	3.602	98.368	94.150
llama3	Ours	5.458	97.299	89.772	3.219	97.683	91.188	4.071	98.295	94.077
qwen2	Ours	7.902	96.633	87.577	3.884	97.507	90.806	5.238	98.161	93.757
Ours w/o KF	Ours	**4.683**	**98.078**	**92.896**	**2.518**	**98.475**	**94.352**	**3.467**	**98.833**	**96.146**

Method	ASR Model	NarrativeQA			TAT-QA		
		WER↓	SIM↑	Pass↑	WER↓	SIM↑	Pass↑
-	canary	8.880	93.011	72.518	18.608	75.349	21.685
-	whisper	8.527	93.149	73.500	19.981	75.993	22.259
-	parakeet	8.387	91.975	71.255	18.441	76.808	21.146
-	Ours	6.296	95.572	82.375	18.980	79.366	24.633
phi3	Ours	4.326	97.432	89.725	7.784	94.583	77.193
llama3	Ours	5.637	97.017	88.140	9.398	94.593	78.263
qwen2	Ours	6.532	97.008	88.593	17.817	89.507	52.456
Ours w/o KF	Ours	4.451	98.035	92.527	6.894	96.675	86.923

Rewrite LLM	ASR Model	SQUAD1.1			SQUAD2.0		
		WER↓	SIM↑	Pass↑	WER↓	SIM↑	Pass↑
-	canary	10.186	89.936	64.974	9.553	90.634	65.544
-	whisper	9.672	90.760	66.432	9.711	90.810	66.478
-	parakeet	9.788	89.588	65.401	9.139	90.257	65.762
-	Ours	7.857	93.054	72.938	7.869	93.080	73.043
phi3	Ours	5.575	96.189	85.164	5.532	96.185	85.101
llama3	Ours	7.014	96.184	85.218	6.996	96.177	85.252
qwen2	Ours	8.659	95.633	83.233	8.641	95.638	83.334
Ours w/o KF	Ours	6.051	97.299	89.662	6.049	97.284	89.612

Table 17: The quality evaluation results of our proposed method in datasets. The similarity here is the average of the results calculated by mxbai-embed-large-v1 (Appendix B.3).

Method	ASR Model	DROP			Quoref			ROPES		
		WER↓	SIM↑	Pass↑	WER↓	SIM↑	Pass↑	WER↓	SIM↑	Pass↑
-	canary	10.928	90.239	64.929	5.455	93.874	76.701	6.971	95.069	81.930
-	whisper	11.175	90.490	66.607	5.322	94.061	77.583	7.087	94.796	81.866
-	parakeet	10.416	89.920	66.056	5.084	93.209	76.973	6.208	94.836	83.422
-	Ours	9.256	92.677	71.714	4.170	95.836	83.467	5.205	96.732	88.594
phi3	Ours	4.977	96.565	87.032	2.563	97.782	91.306	3.653	98.127	93.867
llama3	Ours	5.466	96.628	87.649	3.152	97.602	90.879	4.078	98.026	93.537
qwen2	Ours	7.836	95.913	85.114	3.917	97.481	90.951	5.332	97.890	93.436
Ours w/o KF	Ours	4.756	97.508	91.012	2.497	98.387	94.171	3.480	98.656	95.817

Method	ASR Model	NarrativeQA			TAT-QA		
		WER↓	SIM↑	Pass↑	WER↓	SIM↑	Pass↑
-	canary	8.880	92.451	70.950	18.608	77.890	22.076
-	whisper	8.527	92.676	71.990	19.981	78.071	22.355
-	parakeet	8.387	92.030	71.198	18.441	79.429	21.972
-	Ours	6.221	95.256	81.240	18.331	81.174	24.954
phi3	Ours	4.258	97.221	88.945	7.857	94.705	76.863
llama3	Ours	5.474	96.764	87.197	9.136	94.636	76.941
qwen2	Ours	6.353	96.785	87.873	17.150	89.297	54.143
Ours w/o KF	Ours	4.300	97.844	91.843	6.443	96.815	86.566

Rewrite LLM	ASR Model	SQUAD1.1			SQUAD2.0		
		WER↓	SIM↑	Pass↑	WER↓	SIM↑	Pass↑
-	canary	10.186	89.429	64.035	9.553	90.112	64.475
-	whisper	9.672	90.215	65.480	9.711	90.264	65.553
-	parakeet	9.788	89.013	64.434	9.139	89.661	64.881
-	Ours	7.792	92.632	71.678	7.786	92.647	71.726
phi3	Ours	5.517	95.923	84.290	5.488	95.919	84.210
llama3	Ours	6.910	95.855	84.071	6.903	95.847	84.071
qwen2	Ours	8.494	95.290	82.023	8.484	95.300	82.162
Ours w/o KF	Ours	5.986	97.030	88.820	5.950	97.020	88.790

Table 18: The quality evaluation results of our proposed method in datasets. The similarity here is the average of the results calculated by stella_en_400M_v5 (Appendix B.3).

Method	ASR Model	DROP			Quoref			ROPES		
		WER↓	SIM↑	Pass↑	WER↓	SIM↑	Pass↑	WER↓	SIM↑	Pass↑
-	canary	10.928	93.968	76.376	5.455	96.079	84.804	6.971	96.398	87.294
-	whisper	11.175	93.806	76.232	5.322	96.009	84.876	7.087	95.967	86.012
-	parakeet	10.416	93.251	75.242	5.084	95.272	84.895	6.208	95.545	87.596
-	Ours	9.129	95.394	82.028	4.211	97.311	90.342	5.326	97.581	92.411
phi3	Ours	4.929	98.228	95.177	2.590	98.727	96.708	3.849	98.663	96.192
llama3	Ours	5.359	98.259	95.592	3.139	98.580	96.490	4.223	98.623	96.476
qwen2	Ours	7.426	97.283	92.201	3.663	98.230	95.298	5.356	98.388	95.798
Ours w/o KF	Ours	4.490	98.787	97.503	2.399	99.075	98.081	3.656	99.061	97.620

Method	ASR Model	NarrativeQA			TAT-QA		
		WER↓	SIM↑	Pass↑	WER↓	SIM↑	Pass↑
-	canary	8.880	95.257	82.498	18.608	85.716	30.345
-	whisper	8.527	95.180	82.428	19.981	85.661	31.241
-	parakeet	8.387	94.083	81.247	18.441	84.981	27.911
-	Ours	6.330	97.009	89.823	18.212	87.321	35.562
phi3	Ours	4.342	98.461	95.740	7.528	97.012	89.740
llama3	Ours	5.523	98.146	94.857	8.836	96.989	90.210
qwen2	Ours	6.075	97.837	93.648	16.726	92.936	72.959
Ours w/o KF	Ours	4.230	98.826	97.343	6.058	98.214	94.748

Rewrite LLM	ASR Model	SQUAD1.1			SQUAD2.0		
		WER↓	SIM↑	Pass↑	WER↓	SIM↑	Pass↑
-	canary	10.186	92.488	72.194	9.553	93.203	72.817
-	whisper	9.672	93.012	72.568	9.711	93.053	72.555
-	parakeet	9.788	91.678	71.369	9.139	92.353	71.717
-	Ours	7.765	94.869	79.243	7.768	94.893	79.299
phi3	Ours	5.415	97.372	90.391	5.387	97.381	90.379
llama3	Ours	6.732	97.327	90.619	6.742	97.326	90.586
qwen2	Ours	8.022	96.574	87.689	7.992	96.579	87.733
Ours w/o KF	Ours	5.676	98.121	93.862	5.654	98.107	93.746

Table 19: The quality evaluation results of our proposed method in datasets. The similarity here is the average of the results calculated by gte-large-en-v1.5 and mxbai-embed-large-v1 (Appendix B.3).

Method	ASR Model	DROP			Quoref			ROPES		
		WER↓	SIM↑	Pass↑	WER↓	SIM↑	Pass↑	WER↓	SIM↑	Pass↑
-	canary	10.928	90.770	65.679	5.455	93.810	76.619	6.971	95.320	82.479
-	whisper	11.175	91.029	67.501	5.322	94.012	77.410	7.087	95.127	82.314
-	parakeet	10.416	90.401	66.501	5.084	93.420	77.155	6.208	95.127	84.044
-	Ours	9.254	92.980	72.540	4.152	95.777	83.439	5.157	96.876	88.887
phi3	Ours	4.930	96.830	87.905	2.513	97.785	91.324	3.590	98.204	93.876
llama3	Ours	5.419	96.902	88.443	3.136	97.591	90.933	4.035	98.117	93.601
qwen2	Ours	7.828	96.179	85.977	3.857	97.431	90.697	5.236	97.973	93.510
Ours w/o KF	Ours	4.661	97.734	91.766	2.455	98.386	94.180	3.456	98.704	95.844

Method	ASR Model	NarrativeQA			TAT-QA		
		WER↓	SIM↑	Pass↑	WER↓	SIM↑	Pass↑
-	canary	8.880	92.731	71.408	18.608	76.620	21.285
-	whisper	8.527	92.913	72.425	19.981	77.032	21.781
-	parakeet	8.387	92.003	70.888	18.441	78.119	20.989
-	Ours	6.214	95.363	81.463	18.410	80.022	23.989
phi3	Ours	4.255	97.283	89.105	7.740	94.520	76.124
llama3	Ours	5.519	96.836	87.405	9.092	94.501	76.376
qwen2	Ours	6.347	96.832	87.958	17.274	89.209	52.795
Ours w/o KF	Ours	4.320	97.891	91.970	6.510	96.652	85.949

Rewrite LLM	ASR Model	SQUAD1.1			SQUAD2.0		
		WER↓	SIM↑	Pass↑	WER↓	SIM↑	Pass↑
-	canary	10.186	89.682	64.276	9.553	90.373	64.787
-	whisper	9.672	90.488	65.755	9.711	90.537	65.790
-	parakeet	9.788	89.301	64.652	9.139	89.959	65.044
-	Ours	7.799	92.755	71.883	7.787	92.777	71.992
phi3	Ours	5.509	95.983	84.439	5.473	95.982	84.305
llama3	Ours	6.938	95.947	84.358	6.898	95.941	84.364
qwen2	Ours	8.510	95.368	82.319	8.513	95.378	82.385
Ours w/o KF	Ours	5.972	97.094	88.972	5.937	97.083	88.862

Table 20: The quality evaluation results of our proposed method in datasets. The similarity here is the average of the results calculated by gte-large-en-v1.5 and stella_en_400M_v5 (Appendix B.3).

Method	ASR Model	DROP			Quoref			ROPES		
		WER↓	SIM↑	Pass↑	WER↓	SIM↑	Pass↑	WER↓	SIM↑	Pass↑
-	canary	10.928	92.635	70.300	5.455	94.912	79.502	6.971	95.985	84.722
-	whisper	11.175	92.687	71.317	5.322	94.987	80.047	7.087	95.713	83.916
-	parakeet	10.416	92.066	70.108	5.084	94.452	79.984	6.208	95.482	85.655
-	Ours	9.191	94.344	76.890	4.141	96.511	85.858	5.203	97.304	90.525
phi3	Ours	4.834	97.657	91.588	2.524	98.251	93.725	3.663	98.471	95.029
llama3	Ours	5.318	97.707	92.249	3.118	98.070	93.243	4.110	98.412	95.103
qwen2	Ours	7.510	96.827	89.049	3.726	97.781	92.370	5.202	98.209	94.590
Ours w/o KF	Ours	4.421	98.352	94.907	2.373	98.714	95.999	3.509	98.902	96.723

Method	ASR Model	NarrativeQA			TAT-QA		
		WER↓	SIM↑	Pass↑	WER↓	SIM↑	Pass↑
-	canary	8.880	94.134	76.648	18.608	80.533	23.363
-	whisper	8.527	94.165	77.020	19.981	80.827	24.241
-	parakeet	8.387	93.029	74.910	18.441	80.895	22.407
-	Ours	6.246	96.233	85.490	18.406	83.036	27.163
phi3	Ours	4.255	97.891	92.533	7.607	95.700	83.149
llama3	Ours	5.484	97.508	91.083	8.929	95.704	83.975
qwen2	Ours	6.173	97.312	90.745	17.060	91.020	60.569
Ours w/o KF	Ours	4.198	98.352	94.730	6.241	97.362	90.644

Rewrite LLM	ASR Model	SQUAD1.1			SQUAD2.0		
		WER↓	SIM↑	Pass↑	WER↓	SIM↑	Pass↑
-	canary	10.186	91.212	67.328	9.553	91.919	67.956
-	whisper	9.672	91.886	68.469	9.711	91.932	68.413
-	parakeet	9.788	90.633	67.245	9.139	91.305	67.735
-	Ours	7.759	93.870	74.947	7.754	93.897	74.958
phi3	Ours	5.460	96.701	87.152	5.404	96.705	87.093
llama3	Ours	6.825	96.674	87.268	6.816	96.671	87.255
qwen2	Ours	8.248	95.982	84.654	8.249	95.988	84.734
Ours w/o KF	Ours	5.802	97.624	91.259	5.791	97.610	91.219

Table 21: The quality evaluation results of our proposed method in datasets. The similarity here is the average of the results calculated by mxbai-embed-large-v1 and stella_en_400M_v5 (Appendix B.3).

Method	ASR Model	DROP			Quoref			ROPES		
		WER↓	SIM↑	Pass↑	WER↓	SIM↑	Pass↑	WER↓	SIM↑	Pass↑
-	canary	10.928	92.104	68.601	5.455	94.977	79.902	6.971	95.734	84.282
-	whisper	11.175	92.148	69.580	5.322	95.035	80.384	7.087	95.381	83.733
-	parakeet	10.416	91.585	68.971	5.084	94.241	80.102	6.208	95.190	85.427
-	Ours	9.091	93.926	75.143	4.164	96.520	86.077	5.186	97.094	90.287
phi3	Ours	4.876	97.313	90.420	2.526	98.209	93.707	3.689	98.343	94.901
llama3	Ours	5.332	97.358	90.940	3.110	98.037	93.389	4.073	98.269	94.929
qwen2	Ours	7.527	96.458	87.577	3.707	97.773	92.816	5.251	98.056	94.443
Ours w/o KF	Ours	4.479	98.056	93.859	2.352	98.673	95.980	3.483	98.805	96.732

Method	ASR Model	NarrativeQA			TAT-QA		
		WER↓	SIM↑	Pass↑	WER↓	SIM↑	Pass↑
-	canary	8.880	93.854	75.658	18.199	83.984	27.980
-	whisper	8.527	93.928	76.183	19.981	81.866	24.833
-	parakeet	8.387	93.056	74.910	18.441	82.205	23.554
-	Ours	6.213	96.071	84.898	18.608	81.803	24.094
phi3	Ours	4.243	97.784	92.123	7.662	95.750	81.619
llama3	Ours	5.394	97.381	90.575	8.962	95.706	82.141
qwen2	Ours	6.084	97.200	90.335	16.919	90.915	59.847
Ours w/o KF	Ours	4.145	98.257	94.463	6.205	97.434	90.270

Rewrite LLM	ASR Model	SQUAD1.1			SQUAD2.0		
		WER↓	SIM↑	Pass↑	WER↓	SIM↑	Pass↑
-	canary	10.186	90.958	66.916	9.553	91.657	67.379
-	whisper	9.672	91.614	67.941	9.711	91.659	67.922
-	parakeet	9.788	90.346	66.793	9.139	91.007	67.177
-	Ours	7.723	93.661	74.226	7.726	93.682	74.242
phi3	Ours	5.424	96.565	86.757	5.378	96.570	86.638
llama3	Ours	6.765	96.505	86.738	6.766	96.501	86.706
qwen2	Ours	8.155	95.810	84.055	8.158	95.817	84.126
Ours w/o KF	Ours	5.733	97.487	90.908	5.719	97.476	90.841

D MORE SPEAKER INFORMATION

As shown in Table 22, we provide more examples of speaker descriptions. These descriptions are presented to Parler in a variety of speech styles.

Table 22: Additional examples of speaker descriptions.

Name	Gender	Position	Speech Rate	Clarity	Accent	Speaker Pitch	Description
Melvin	male	close-sounding	slowly	quite clean	English	very expressive and animated	A male voice with an English accent speaks slowly, with a close-sounding and quite clean delivery. The speaker's pitch is very expressive and animated, adding a vibrant and dynamic quality to the recording while maintaining good clarity.
Igor	male	close-sounding	slowly	quite clean	Pakistani	very expressive and animated	A male voice with a Pakistani accent speaks slowly, with a close-sounding and quite clean delivery. The speaker's pitch is very expressive and animated, adding a vibrant and dynamic quality to the recording while maintaining good clarity
Samuel	male	close-sounding	slowly	quite clean	Italian	very expressive and animated	A male voice with an Italian accent speaks slowly, with a close-sounding and quite clean delivery. The speaker's pitch is very expressive and animated, infusing the recording with a dynamic and lively quality while maintaining good clarity.
Joey	male	close-sounding	slowly	quite clean	Canadian	slightly expressive and animated	A male voice with a Canadian accent speaks slowly. The speaker's voice is close-sounding and quite clean, with a slightly expressive and animated pitch. The recording captures the speaker's subtle vocal nuances with good clarity.
Sherard	male	close-sounding	slowly	quite clean	Chinese	monotone	A male voice with a Chinese accent speaks slowly. The speaker's voice is close-sounding and quite clean, with a monotone pitch. The recording captures the speaker's steady, unvaried tone with clear definition.
Wyman	male	close-sounding	normally	quite clean	American	very expressive and animated	A male voice with an American accent speaks normally. The speaker's voice is close-sounding and quite clean, with a very expressive and animated pitch. The recording captures the speaker's dynamic vocal quality with clear, engaging detail.
Beatrix	female	close-sounding	slowly	quite clean	English	slightly expressive and animated	A female voice with an English accent speaks slowly. The speaker's voice is close-sounding and quite clean, with a slightly expressive and animated pitch. The recording captures the voice with a clear and engaging quality.
Jeanne	female	close-sounding	normally	quite clean	South African	slightly expressive and animated	A female voice with a South African accent speaks at a normal rate. The speaker's voice is close-sounding and quite clean, with a slightly expressive and animated pitch. The recording is clear and lively.
Amiable	female	close-sounding	quickly	quite clean	Pakistani	slightly expressive and animated	A female voice with a Pakistani accent speaks quickly. The speaker's voice is close-sounding and quite clean, with a slightly expressive and animated pitch. The recording is clear and lively.
Harmony	female	close-sounding	quickly	quite clean	Indian	slightly expressive and animated	A female voice with an Indian accent speaks quickly. The speaker's voice is close-sounding and quite clean, with a slightly expressive and animated pitch. The recording is clear and lively.
Alanna	female	close-sounding	slowly	quite clean	South African	very expressive and animated	A female voice with a South African accent speaks slowly. The speaker's voice is close-sounding and quite clean, with a very expressive and animated pitch. The recording captures the voice with a clear and vibrant quality.
Kirstyn	female	close-sounding	slowly	quite clean	Indian	very expressive and animated	A female voice with an Indian accent speaks slowly. The voice is close-sounding and quite clean, with a very expressive and animated pitch. The recording captures a dynamic and lively tone.

E ASSETS AND LICENSES

Below, we provide the access links and open-source licenses for the models, datasets and main code used in this paper.

E.1 MODELS

- Qwen2-7B-Instruct

    - Download URL:
      `https://huggingface.co/Qwen/Qwen2-7B-Instruct`
    - License: Apache-2.0
      `https://choosealicense.com/licenses/apache-2.0/`

- Phi-3-small-8k-instruct

    - Download URL:
      `https://huggingface.co/microsoft/Phi-3-small-8k-instruct`
    - License: MIT
      `https://choosealicense.com/licenses/mit/`

- Meta-Llama-3-8B-Instruct

    - Download URL:
      `https://huggingface.co/meta-llama/Meta-Llama-3-8B-Instruct`
    - License: llama3
      `https://llama.meta.com/llama3/license`

- parler-tts-large-v1

    - Download URL:
      `https://huggingface.co/parler-tts/parler-tts-large-v1`
    - License: Apache-2.0
      `https://choosealicense.com/licenses/apache-2.0/`

- whisper-large-v3

    - Download URL:
      `https://huggingface.co/openai/whisper-large-v3`
    - License: Apache-2.0
      `https://choosealicense.com/licenses/apache-2.0/`

- canary-1b

    - Download URL:
      `https://huggingface.co/nvidia/canary-1b`
    - License: CC-BY-NC-4.0
      `https://spdx.org/licenses/CC-BY-NC-4.0`

- parakeet-tdt-1.1b

    - Download URL:
      `https://huggingface.co/nvidia/parakeet-tdt-1.1b`
    - License: CC-BY-4.0
      `https://choosealicense.com/licenses/cc-by-4.0/`

- gte-large-en-v1.5

    - Download URL:
      `https://huggingface.co/Alibaba-NLP/gte-large-en-v1.5`
    - License: Apache-2.0
      `https://choosealicense.com/licenses/apache-2.0/`

- mxbai-embed-large-v1

    - Download URL:
      `https://huggingface.co/mixedbread-ai/`
      `mxbai-embed-large-v1`

   – License: Apache-2.0
     `https://choosealicense.com/licenses/apache-2.0/`
 • stella_en_400M_v5
   – Download URL:
     `https://huggingface.co/dunzhang/stella_en_400M_v5`
   – License: MIT
     `https://choosealicense.com/licenses/mit/`

E.2 DATASETS

 • TAT-QA
   – Download URL:
     `https://github.com/NExTplusplus/TAT-QA/tree/master/`
     `dataset_raw`
   – License: CC-BY-4.0
     `https://creativecommons.org/licenses/by/4.0/`
 • DROP
   – Download URL:
     `https://huggingface.co/datasets/ucinlp/DROP`
   – License: CC-BY-SA-4.0
     `https://choosealicense.com/licenses/cc-by-sa-4.0/`
 • SQUAD1.1
   – Download URL:
     `https://huggingface.co/datasets/rajpurkar/squad`
   – License: CC-BY-SA-4.0
     `https://choosealicense.com/licenses/cc-by-sa-4.0/`
 • SQUAD2.0
   – Download URL:
     `https://rajpurkar.github.io/SQuAD-explorer/`
   – License: CC-BY-SA-4.0
     `https://choosealicense.com/licenses/cc-by-sa-4.0/`
 • ROPES
   – Download URL:
     `https://huggingface.co/datasets/allenai/ropes`
   – License: CC-BY-SA-4.0
     `https://choosealicense.com/licenses/cc-by-4.0/`
 • NarrativeQA
   – Download URL:
     `https://huggingface.co/datasets/deepmind/narrativeqa`
   – License: Apache-2.0
     `https://choosealicense.com/licenses/apache-2.0/`
 • Quoref
   – Download URL:
     `https://huggingface.co/datasets/allenai/quoref`
   – License: CC-BY-4.0
     `https://creativecommons.org/licenses/by/4.0/`

E.3 CODE

 • VLLM
   – Download URL:
     `https://github.com/vllm-project/vllm`

- License: Apache-2.0
  `https://choosealicense.com/licenses/apache-2.0/`
- Transformers
  - Download URL:
    `https://github.com/huggingface/transformers`
  - License: Apache-2.0
    `https://choosealicense.com/licenses/apache-2.0/`
- pyTorch
  - Download URL:
    `https://github.com/pytorch/pytorch`
  - License: PyTorch
    `https://github.com/pytorch/pytorch?tab=`
    `License-1-ov-file#readme`