Dense RGB SLAM with Neural Implicit Maps

Abstract

There is an emerging trend of using neural implicit functions for map representation in Simultaneous Localization and Mapping (SLAM). Some pioneer works have achieved encouraging results on RGB-D SLAM. In this paper, we present a dense RGB SLAM method with neural implicit map representation. To reach this challenging goal without depth input, we introduce a hierarchical feature volume to facilitate the implicit map decoder. This design effectively fuses shape cues across different scales to facilitate map reconstruction. Our method simultaneously solves the camera motion and the neural implicit map by matching the rendered and input video frames. To facilitate optimization, we further propose a photometric warping loss in the spirit of multi-view stereo to better constrain the camera pose and scene geometry. We evaluate our method on commonly used benchmarks and compare it with modern RGB and RGB-D SLAM systems. Our method achieves favorable results than previous methods and even surpasses some recent RGB-D SLAM methods. Our source code will be publicly available.

1 Introduction

Visual SLAM is a fundamental task in 3D computer vision with many applications in AR/VR and robotics. The goal of visual SLAM is to estimate the camera poses and build a 3D map of the environment simultaneously from visual inputs. Visual SLAM methods can be primarily divided into sparse or dense according to their reconstructed 3D maps. Sparse methods (Mur-Artal & Tardós, 2017; Engel et al., 2017) focus on recovering camera motion with a set of sparse or semi-dense 3D points. Dense works (Newcombe et al., 2011b) seek to recover the depth of every observed pixel and are often more desirable for many downstream applications such as occlusion in AR/VR or obstacle detection in robotics. Earlier methods (Newcombe et al., 2011a; Whelan et al., 2012) often resort to RGB-D cameras for dense map reconstruction. However, RGB-D cameras are limited to indoor scenes and are much less energy efficient for mobile devices.

Another important problem in visual SLAM is map representation. Sparse SLAM methods (Mur-Artal & Tardós, 2017; Engel et al., 2017) typically use point clouds for map representation, while dense methods (Newcombe et al., 2011b;a) usually adopt triangle meshes. As observed in many recent geometry processing works (Mescheder et al., 2019; Park et al., 2019; Chen & Zhang, 2019), neural implicit function offers a promising presentation for 3D data processing. The pioneer work, iMAP (Sucar et al., 2021), introduces an implicit map representation for dense visual SLAM. This map representation is more compact, continuous, and allowing for prediction of unobserved areas, which could potentially benefit applications like path planning (Shrestha et al., 2019) and object manipulation (Sucar et al., 2020). However, as observed in NICE-SLAM (Zhu et al., 2022), iMAP (Sucar et al., 2021) is limited to room-scale scenes due to the restricted representation power of MLPs. NICE-SLAM (Zhu et al., 2022) introduces a hierarchical feature volume to facilitate the map reconstruction and generalize the implicit map to larger scenes. However, both iMAP (Sucar et al., 2021) and NICE-SLAM (Zhu et al., 2022) are limited to RGB-D cameras.

This paper presents a novel dense visual SLAM method with regular RGB cameras based on the implicit map representation. We also adopt a hierarchical feature volume like NICE-SLAM (Zhu et al., 2022) to deal with larger scenes. But our feature volume is fundamentally different. Firstly, the decoders in NICE-SLAM (Zhu et al., 2022) are pretrained, which might cause problems when generalizing to different scenes, while our method learns the scene features and decoders together on the fly. Secondly, NICE-SLAM (Zhu et al., 2022) computes the occupancy at each point from features at different scales respectively and then sums these occupancies together, while we fuse

features from all scales to compute the occupancy at once. In this way, we save many unnecessary occupancy evaluations and thus can afford to have much more layers of feature hierarchy. In experiments, we find the number of feature hierarchy is important to enhance the system accuracy and robustness. Intuitively, features from fine volumes capture geometry details, while features from coarse volumes enforce geometry regularity like smoothness or planarity. While NICE-SLAM (Zhu et al., 2022) only optimizes two feature volumes with voxel sizes of 32cm and 16cm, our method solves six feature volumes from 8cm to 64cm. Our fusion of features across many different scales leads to more robust and accurate tracking and mapping as demonstrated in experiments.

Another challenge in our setting is that there are no input depth observations. Therefore, we design a sophisticated warping loss to further constrain the camera motion and scene map in the same spirit of multi-view stereo. Specifically, we warp one frame to other nearby frames according to the estimated scene map and camera poses and optimize the solution to minimize the warping loss. However, this warping loss is subject to view-dependent intensity changes such as specular reflections. To address this problem, we carefully sample image pixels visible in multiple video frames and evaluate the structural similarity of their surrounding patches to build a robust system.

We perform extensive evaluations on three different datasets and achieve state-of-the-art performance on both mapping and camera tracking. Our method even surpasses recent RGB-D based methods like iMAP (Sucar et al., 2021) and NICE-SLAM (Zhu et al., 2022) on camera tracking.

Our contributions can be summarized as the following:

• We design the first dense RGB SLAM with neural implicit map representation,

• We introduce a hierarchical feature volume, which fuses coarse-to-fine information for better occupancy evaluation, and a multiscale patch-based warping loss to boost system performance with only RGB inputs,

• We achieve strong results on benchmark datasets and even surpass some recent RGB-D methods.

2 RELATED WORK

Visual SLAM Many visual SLAM algorithms and systems have been developed the last two decades. We only quickly review some of the most relevant works, and more comprehensive surveys can be found at (Cadena et al., 2016; Macario Barros et al., 2022). Sparse visual SLAM algorithms (Klein & Murray, 2007; Mur-Artal & Tardós, 2017) focus on solving accurate camera poses and only recover a sparse set of 3D landmarks serving for camera tracking. Semi-dense methods like LSD-SLAM (Engel et al., 2014) and DSO (Engel et al., 2017) achieve more robust tracking in textureless scenes by reconstructing the semi-dense pixels with strong image gradients. In comparison, dense visual SLAM algorithms (Newcombe et al., 2011b) aim to solve the depth of every observed pixel, which is very challenging, especially in featureless regions.

In the past, dense visual SLAM is often solved with RGB-D sensors. KinectFusion (Newcombe et al., 2011a) and the follow-up works (Whelan et al., 2012; 2021; Dai et al., 2017) register the input sequence of depth images through Truncated Signed Distance Functions (TSDFs) to track camera motion and recover a clean scene model at the same time. Most recently, iMAP (Sucar et al., 2021) and NICE-SLAM (Zhu et al., 2022), introduce neural implicit functions as the map presentation and achieve better scene completeness, especially for unobserved regions. All these methods are limited to RGB-D cameras.

More recently, deep neural networks are employed to solve dense depth from regular RGB cameras. Earlier methods (Zhou et al., 2017; Ummenhofer et al., 2017; Zhou et al., 2018) directly regress camera ego-motion and scene depth from input images. Later, multi-view geometry constraints are enforced in (Bloesch et al., 2018; Tang & Tan, 2019; Teed & Deng, 2020; Wei et al., 2020; Teed & Deng, 2021) for better generalization and accuracy. But they all only recover depth maps instead of complete scene models. Our method also employs deep neural networks to solve the challenging dense visual SLAM problem. Unlike these previous methods that only recover a depth map per frame, we follow iMAP (Sucar et al., 2021) and NICE-SLAM (Zhu et al., 2022) to compute a neural implicit function for map representation.

Figure 1: Pipeline of our framework. Given a camera pose, our method sample the multi-scale features along view rays and pass the concatenated features through an MLP decoder to compute the depth and color at each pixel. In this way, we can solve the camera motion and a 3D scene map (captured by the feature volume and MLP decoder) simultaneously by matching the rendered images with observed ones. We further include warping loss across different views to enhance the system performance.

Neural Implicit Representations Neural implicit functions have been widely adopted for many different tasks in recent years. It has been introduced for 3D shape modeling (Mescheder et al., 2019; Park et al., 2019; Chen & Zhang, 2019), novel view synthesis (Mildenhall et al., 2020; Zhang et al., 2020; Martin-Brualla et al., 2021; Barron et al., 2021; Müller et al., 2022), clothed human reconstruction (Saito et al., 2019; 2020), scene reconstruction (Murez et al., 2020; Sun et al., 2021), and object reconstruction (Yariv et al., 2020; Niemeyer et al., 2020; Wang et al., 2021), etc. But all these works typically require precisely known camera poses. There are only a few works (Jeong et al., 2021; Zhang et al., 2022; Lin et al., 2021) trying to deal with uncalibrated cameras. Furthermore, all these methods require a long optimization process, and hence, are unsuitable for real-time applications like visual SLAM.

Recently, the two pioneer works, iMAP (Sucar et al., 2021) and NICE-SLAM (Zhu et al., 2022), both adopt neural implicit functions to represent the scene map in visual SLAM. These works can solve camera poses and 3D scene maps in real-time by enforcing the rendered depth and color images to match with the input ones. However, they both require RGB-D sequences as input, which limits their application in outdoor scenes or mobile devices with a tight power budget. In comparison, our visual SLAM method works with regular RGB cameras and solves camera poses and the 3D scene simultaneously in real-time.

3 APPROACH

The overall pipeline of our framework is shown in Figure 1. Given an RGB video as input, our method aims to recover a 3D scene map and the camera motions simultaneously. We represent the scene map by a neural implicit function with a learnable multi-resolution feature volume. By sampling features from the volume grid along view rays and querying the sampled feature with the MLP decoder, we can render the depth and color of each pixel given the estimated camera parameters. Since this rendering process is differentiable, we can simultaneously optimize the neural implicit map as well as the camera poses by minimizing an objective function defined on photometric rendering loss and warping loss.

3.1 IMPLICIT MAP REPRESENTATION

This section introduces the formulation of our implicit map representation that combines a learnable multi-resolution volume encoding $\{V_l\}$ and an MLP decoder Φ for depth and color prediction.

Multi-resolution Volume Encoding Directly representing the scene map with MLPs, which maps a 3D point to its occupancy and color, confronts a forgetting problem because the MLP is globally updated for any frame. To address this, we equip the MLP with multi-resolution volumes $\{V_l\}_{l=1}^L$, which are updated locally on seen regions of each frame. The input point is encoded by the feature $\mathcal{F}$ sampled from the volumes $\{V_l\}$, which could also explicitly store the geometric information. We adopt a combination of L volumes, whose resolution arrange from the voxel size of v_{max} to the voxel size of v_{min}. This hierarchical structure works better than a single-scale volume because the

gradient-based camera optimization on high-resolution volume is susceptible to a suboptimal solution if without a good initialization. In contrast, in a coarse-to-fine architecture, the low-resolution volume could enforce the smoothness in 3D space in early registration, while the high-resolution volume could encode the shape details. To compute this encoding of a given 3D point $\mathbf{p} = (x, y, z)$, we first interpolate feature $V_l(\mathbf{p})$ at the point $\mathbf{p}$ by trilinear sampling. Then the 3D feature encoding $\mathcal{F}(\mathbf{p})$ is obtained by concatenating the features from all levels. Notably, the feature channel of each volume is set to 1. The small feature channel reduces memory consumption without losing performance, which is demonstrated in the ablation study.

Color and Depth Prediction The MLP decoder Φ consists of three hidden layers with a feature channel of 32 and two heads that output the color $\mathbf{c_p}$ and density $o_\mathbf{p}$ as,

$$(o_\mathbf{p}, \mathbf{c_p}) = \Phi(\mathcal{F}(\mathbf{p})). \tag{1}$$

However, extracting scene geometry from the computed density requires careful tuning of the density threshold and leads to artifacts due to the ambiguity present in the density field. To address this problem, following (Oechsle et al., 2021), a sigmoid function is added on the output of $o_\mathbf{p}$ to regularize it to $[0, 1]$, in which case a fixed level set of 0.5 could be used to extract the mesh. Also, the ray termination probability of point $\mathbf{p}_i$ is now computed as,

$$w_i = o_{p_i} \prod_{j=0}^{i-1} (1 - o_{p_j}). \tag{2}$$

During volume rendering, a hierarchical sampling strategy similar to NeuS (Wang et al., 2021) is adopted. We first uniformly sample 32 points on a view ray and then subsequently conducts importance sampling of additional 16 points for 4 times based on the previously estimated weights. $N = 96$ points are sampled in total. For each point, we compute its depth $\tilde{D}$ and color $\tilde{\mathbf{I}}$ as,

$$\tilde{D} = \sum_{i=0}^{N} w_i z_i, \tilde{\mathbf{I}} = \sum_{i=0}^{N} w_i \mathbf{c}_i, \tag{3}$$

where z_i and $\mathbf{c}_i$ are the depth and color of the point $\mathbf{p}_i$ along the viewing ray. Notice that since the rendering equation is differentiable, the camera pose, multi-resolution volume encoding, and the parameters of the MLP decoder could be optimized together from the gradient back-propagation.

3.2 JOINT OPTIMIZATION

In this section, we present the objective function for optimization. Unlike iMAP (Sucar et al., 2021) and NICE-SLAM (Zhu et al., 2022), which split mapping and tracking into two different threads, our framework constantly optimizes the scene and camera pose simultaneously. The implicit scene representation and the camera poses are jointly optimized in a set of frames $\mathcal{W}$ with corresponding poses $\tilde{\mathcal{P}} : \{\tilde{\mathbf{P}}_k = [\tilde{\mathbf{R}}_k, \tilde{\mathbf{t}}_k], k \in \mathcal{W}\}$, where $\mathbf{R}$ and $\mathbf{t}$ are the rotation and translation camera parameters respectively. The frame selection strategy is explained later in section 3.3.

Photometric Rendering Loss To optimize the scene map and the camera poses, we compute the L1 loss between the rendered and observed color for a set of randomly sampled pixels $\mathcal{M}$:

$$L_{\text{render}} = \frac{1}{|\mathcal{M}|} \sum_{\mathbf{q} \in \mathcal{M}} ||\mathbf{I_q} - \tilde{\mathbf{I}_q}||_1. \tag{4}$$

Here, $|\mathcal{M}|$ denotes the number of sampled pixels. This rendering loss alone is insufficient to determine the scene geometry and could lead to ambiguous solutions, where the rendered image matches the observation well but the depth estimation is completely wrong. To overcome this problem, we introduce a photometric warping loss to further constrain the optimization problem.

Photometric Warping Loss We define the photometric warping loss in a similar spirit as multi-view stereo to enforce the geometry consistency. Let $\mathbf{q}_k$ denotes a 2D pixel in frame k, we first lift it into 3D space and then project it to another frame l as:

$$\mathbf{q}_{k \rightarrow l} = \mathbf{K}_l \tilde{\mathbf{R}}_l^\top (\tilde{\mathbf{R}}_k \mathbf{K}_k^{-1} (\mathbf{q}_k^{\text{homo}} \tilde{D}_{\mathbf{q}_k} + \tilde{\mathbf{t}}_k - \tilde{\mathbf{t}}_l)), \tag{5}$$

where $\mathbf{q}_k^{\text{homo}} = (u, v, 1)$ is the homogeneous coordinate of $\mathbf{q}_k$, and $\tilde{D}_{\mathbf{q}_k}$ denotes its estimated depth. We minimize the warping loss defined as the following,

$$L_{\text{warping}} = \frac{1}{|\mathcal{M}|} \sum_{\mathbf{q}_k \in \mathcal{M}} \sum_{l \in \mathcal{W}, k \neq l} ||\tilde{\mathbf{I}}_{\mathbf{q}_k} - \tilde{\mathbf{I}}_{\mathbf{q}_{k \to l}}||_1. \tag{6}$$

However, minimizing the warping loss on a single pixel does not model the view-dependent intensity changes, e.g., specularities, and could create artifacts in the scene map. We thus define the warping loss over image patches instead of individual pixels to address this issue. For an image patch $\mathcal{N}_{\mathbf{q}_k}^s$ centered on pixel $\mathbf{q}_k$ and with size of $s \times s$, we assume all pixels on the patch have the same depth value as $\mathbf{q}_k$. Similar to the case of a single pixel, we project all pixels in this patch to another frame l and obtain $\mathcal{N}_{\mathbf{q}_{k \to l}}^s$. Thus, we extend the pixel-wise warping loss to patch-wise as,

$$L_{\text{warping}} = \frac{1}{|\mathcal{M}|} \sum_{\mathbf{q}_k \in \mathcal{M}} \sum_{l \in \mathcal{W}, k \neq l} \sum_{s \in \mathcal{S}} B_{\mathbf{q}_k} \text{SSIM}(\mathcal{N}_{\mathbf{q}_k}^s, \mathcal{N}_{\mathbf{q}_{k \to l}}^s), \tag{7}$$

where $B_{\mathbf{q}_k}$ denotes a visibility mask which will be explained later, and $\mathcal{S} = \{1, 5, 11\}$ denotes the patch size. In practice, we find that the structure similarity loss (SSIM) (Wang et al., 2004) achieves better results than the L1 loss. Note that this formulation degenerates to pixel-wise when a patch of size 1 is used.

Visibility Mask We define a binary visibility mask $B_{\mathbf{q}_k}$ to filter pixels with low visibility. For any pixel $\mathbf{q}_k$, we count the number of its visible frames by projecting it to all other frames in the set $\mathcal{W}$. The projection is counted as valid if the projected pixel is within the frame boundary. Only pixels with more than 5 valid projections is regarded as visible, whose visibility value is set to 1.

Regularization Loss To deal with textureless regions, we enforce an edge-preserving regularization term to smooth the rendered depth $\tilde{D}$ as,

$$L_{\text{smooth}} = \sum_{k \in \mathcal{W}} e^{-||\nabla \tilde{\mathbf{I}}||_2} ||\nabla \tilde{D}||_1, \tag{8}$$

where $\nabla \tilde{\mathbf{I}}, \nabla \tilde{D}$ are the first-order gradients of the computed color and depth images, respectively.

Thus, the final objective is obtained by a weighted sum as,

$$\underset{\Theta, \mathcal{P}_k, k \in \mathcal{W}}{\arg \min} \alpha_{\text{warping}} L_{\text{warping}} + \alpha_{\text{render}} L_{\text{render}} + \alpha_{\text{smooth}} L_{\text{smooth}}, \tag{9}$$

where α denotes the weighting factors, and Θ denotes the parameters of the implicit scene representation, including the multi-resolution volumes and the MLP decoder. Since the neural rendering is fully differentiable, the camera poses and the parameters of the implicit scene could be optimized from the gradient back-propagation.

3.3 SYSTEM

In this section, we introduce several crucial components to build our complete visual SLAM system.

Initialization The initialization is performed when a small set of frames (13 frames in all our experiments) are collected. The pose of the first frame is set to the identity matrix. Then the poses of the remaining frames are optimized from the objective function for N_i iterations. After the initialization, the first frame is added to the global keyframe set and fixed. The parameters of MLP decoders are also fixed after initialization.

Window Optimization During the window optimization, our method always maintains a window of active frames (21 frames in all our experiments). The active frames include two different types: local window frames and global keyframes. For a frame k, we regard the frames with index from $k-5$ to $k+5$ as the local window frames. We further sample 10 keyframes from the global keyframe set. Specifically, we randomly draw 100 pixels on frame k and project them to all keyframes using estimated camera poses $\tilde{\mathbf{P}}$ and depths $\tilde{D}$. We then evaluate the view overlap ratio by counting the percentage of the pixels projected inside the boundary of those keyframes. Afterward, we randomly select 10 keyframes from those with an overlap ratio over 70% to form the global keyframe set. Then, all these active frames are used to optimize the implicit scene representation and the poses for

		o-0	o-1	o-2	o-3	o-4	r-0	r-1	r-2	Avg.
NICE-SLAM		1.02	3.91	1.76	6.10	11.9	4.37	2.76	3.54	4.4
DROID-SLAM	ATE RMSE[cm]↓	**0.25**	0.45	**0.32**	0.44	0.37	**0.35**	**0.33**	**0.28**	**0.35**
Ours		0.67	**0.37**	0.36	**0.33**	**0.36**	0.48	0.78	0.35	0.46
iMAP	**Acc.**[cm]↓	5.87	3.71	4.81	4.27	4.83	3.58	3.69	4.68	4.43
	Comp.[cm]↓	6.11	5.26	5.65	5.45	6.59	5.06	4.87	5.51	5.56
	Comp. Ratio[≤ 5cm%]↑	77.71	79.64	77.22	77.34	77.63	83.91	83.45	75.53	79.06
NICE-SLAM	**Acc.**[cm]↓	**2.26**	2.50	3.82	3.50	2.77	2.73	**2.58**	**2.65**	**2.85**
	Comp.[cm]↓	**2.02**	2.36	**3.57**	**3.83**	**3.84**	2.87	2.47	**3.00**	**3.00**
	Comp. Ratio[≤ 5cm%]↑	**94.93**	**92.61**	**85.20**	**82.98**	**86.14**	**90.93**	**92.80**	**89.07**	**89.33**
DI-Fuison	**Acc.**[cm]↓	70.56	**1.42**	2.11	2.11	2.02	**1.79**	49.00	26.17	19.40
	Comp.[cm]↓	3.58	**2.20**	4.83	4.71	5.84	3.57	39.40	17.35	10.19
	Comp. Ratio[≤ 5cm%]↑	87.17	91.85	80.13	79.94	80.21	87.77	32.01	45.61	72.96
DROID-SLAM	**Acc.**[cm]↓	3.26	2.92	4.90	**4.47**	5.35	4.01	4.53	**4.40**	4.23
	Comp.[cm]↓	4.22	5.54	7.97	7.77	6.80	7.10	5.72	9.43	6.82
	Comp. Ratio[≤ 5cm%]↑	77.57	72.95	59.85	62.30	66.50	68.35	71.68	68.76	68.50
Ours	**Acc.**[cm]↓	**2.60**	**2.02**	**4.50**	5.43	**4.57**	**3.68**	**3.64**	5.84	**4.03**
	Comp.[cm]↓	**2.65**	**3.31**	**6.09**	**5.98**	**5.81**	**5.32**	**4.72**	**5.70**	**4.20**
	Comp. Ratio[≤ 5cm%]↑	**89.57**	**84.9**	**75.3**	**73.48**	**76.62**	**82.2**	**80.4**	**74.44**	**79.6**

Table 1: Quantitative results on the *Replica* dataset. Here, 'o-x' and 'r-x' denote `office-x` and `room-x` sequence respectively. The top part shows the results of tracking, and the lower part shows the results of mapping. DROID-SLAM and our method work with the RGB inputs, while the others are all based on RGB-D data. The best results in RGB and RGB-D SLAMs are **bolded** respectively.

N_w iterations. After the window optimization, the oldest local frame $k - 5$ is removed, and a new incoming frame of $k + 6$ with a constant velocity motion model is added to the set of local window frames. During the window optimization, the camera poses of all global keyframes are fixed.

Keyframe Selection We maintain a global keyframe set similar to other SLAM systems. Specifically, a new keyframe is added if the field of view changes substantially. This view change is measured by the mean square f of the optical flow between the last keyframe and the current frame with estimated poses and depths. A new keyframe is added if $f > T_{kf}$, where $T_{kf} = 10$ pixels in all our experiments.

4 EXPERIMENTS

Datasets We evaluate our method on three widely used datasets: *TUM RGB-D* (Sturm et al., 2012a), *EuRoC* (Burri et al., 2016), and *Replica* (Straub et al., 2019) dataset. The *TMU RGB-D* and *EuRoC* dataset are captured in small to medium-scale indoor environments. Each scene in the *TUM* dataset contains a video stream from a handheld RGB-D camera associated with the ground-truth trajectory. The *EuRoC* dataset captures stereo images using a drone, and their ground-truth 6D poses are provided with a Vicon System. We use only the monocular setting in the *EuRoC* dataset. The *Replica* dataset contains high-quality 3D scene models. We use the camera trajectories provided by iMAP (Sucar et al., 2021) to render the input RGB sequences.

Implementation Details Our method is implemented with PyTorch (Paszke et al., 2017) and runs on a server with two NVIDIA 2080Ti GPUs. The voxel sizes of the multi-resolution volumes are set to $\{64, 48, 32, 24, 16, 8\}$cm, where $v_{max} = 64$cm and $v_{min} = 8$cm. In all our experimetns, we fix the iteration number of initialization N_i to 1500, the iteration number of window optimization N_w to 100, the number of sampling pixels $|\mathcal{M}|$ to 3000, the windows size $|\mathcal{W}|$ to 21. We use the Adam (Kingma & Ba, 2014) optimizer to optimize both the implicit map representation and the camera poses, with learning rates of 0.001 and 0.01, respectively. The $\alpha_{\text{warping}}, \alpha_{\text{render}}, \alpha_{\text{smooth}}$ is $0.5, 0.1, 0.01$, respectively. We apply a post-optimization on *Replica* at the end of the sequence to improve the quality of the mesh. Note a similar optimization is included in iMAP (Sucar et al., 2021) and NICE-SLAM (Zhu et al., 2022). All metrics reported in this paper are an average of the results for 5 runs.

Figure 2: Visual comparison of the reconstructed meshes on the *Replica* datasets. Our results are more complete and have sharper textures, which indicate more precise surface shapes. More examples are in the appendix.

Method	fr1/desk	fr2/xyz	fr3/office	Mean
iMAP(Sucar et al., 2021)	4.9	2.0	5.8	4.2
iMAP*(Sucar et al., 2021)	7.2	2.1	9.0	6.1
DI-FusionHuang et al. (2021)	4.4	2.3	15.6	7.4
NICE-SLAMZhu et al. (2022)	2.7	1.8	3.0	2.5
BAD-SLAM(Schöps et al., 2019)	1.7	1.1	1.7	1.5
Kintinuous(Whelan et al., 2012)	3.7	2.9	3.0	3.2
ORB-SLAM2(Mur-Artal & Tardós, 2017)	**1.6**	**0.4**	**1.0**	**1.0**
DROID-SLAMTeed & Deng (2021)	**1.8**	**0.5**	2.8	1.7
Ours	2.0	0.6	**2.3**	**1.6**

Table 2: Camera tracking results on the *TUM-RGBD* dataset. The upper part shows RGB-D SLAM methods, while the lower part shows RGB SLAM methods. "∗" denotes the version reproduced by NICE-SLAM. The best results are **bolded**.

4.1 EVALUATION OF MAPPING AND TRACKING

Mapping To compare the quality of the reconstructed scene maps, we first evaluate the RGB-D methods on the *Replica* dataset, including NICE-SLAM (Zhu et al., 2022), iMAP (Sucar et al., 2021), and DI-Fusion (Huang et al., 2021). Note all these methods use additional depth image inputs. We further compare with the RGB-only method, DROID-SLAM (Teed & Deng, 2021), where the TSDF-Fusion (Curless & Levoy, 1996) is employed to compute a mesh model of the scene map with a voxel grid resolution of 256^3 using the estimated depth maps.

We use three metrics to evaluate the recovered scene map on *Replica* (Straub et al., 2019) with $200,000$ sampled points from both the ground-truth and the reconstructed mesh. (i) *Accuracy* (cm), the mean Euclidean distance between sampled points from the reconstructed mesh to their nearest

Method	V101	V102	V103	V201	V202	V203
TartanVO(Wang et al., 2020)	0.389	0.622	0.433	0.749	1.152	0.680
SVO(Forster et al., 2014)	0.070	0.210	X	0.110	0.110	1.080
DSO(Engel et al., 2017)	0.089	0.107	0.903	**0.044**	0.132	1.152
DROID-VO(Teed & Deng, 2021)	0.103	0.165	0.158	0.102	0.115	0.204
DPVO(Teed et al., 2022)	0.123	**0.053**	0.158	0.095	**0.063**	0.310
Ours	**0.068**	0.079	X	0.053	0.178	X

Table 3: Camera Tracking Results on EuRoC. The best results are **bolded**. The failure cases are marked as X

points on the GT mesh. (ii) *Completion* (cm), the mean Euclidean distance between sampled points from the GT mesh to their nearest points on the reconstructed mesh. (iii) *Completion Ratio* (%), the percentage of points in the reconstructed mesh whose nearest points on the GT mesh is within 5 cm. The unseen region is removed if it is not inside any camera viewing frustum.

As shown in the lower part of Table 1, our method outperforms iMAP (Sucar et al., 2021) and DROID-SLAM (Teed & Deng, 2021) on mapping. Although our results are slightly inferior to those of NICE-SLAM (Zhu et al., 2022) and DI-Fusion (Huang et al., 2021), this is reasonable since they have additional depth images as input. A visual comparison with iMAP and DROID-SLAM is provided in Figure 2. From the zoomed regions, we can tell that our method generates more complete and accurate models than iMAP and DROID-SLAM. Additional visual comparisons are provided in the appendix.

Tracking To evaluate the quality of camera tracking, we compare our method with many recent visual SLAM methods with RGB or RGB-D inputs. For a fair comparison, we use the official implementation of DROID-SLAM (Teed & Deng, 2021) to produce its result and cite other results from NICE-SLAM (Zhu et al., 2022) and DPVO (Teed et al., 2022). As for the evaluation metric, we adopt the RMSE of Absolute Trajectory Error (ATE RMSE) (Sturm et al., 2012b). The estimated trajectory is aligned with the ground truth with scale correction before evaluation.

The upper part of Table 1 shows the tracking results on the *Replica* dataset. Our method clearly outperforms NICE-SLAM (Zhu et al., 2022), though it has additional depth input. Our tracking performance is similar to DROID-SLAM (Teed & Deng, 2021) on this dataset.

Table 2 shows our results on the *TMU RGB-D* dataset. We report results on the same three examples as iMAP (Sucar et al., 2021). As shown in the table, our method outperforms all previous learning-based methods, including iMAP (Sucar et al., 2021), NICE-SLAM (Zhu et al., 2022), DI-Fusion (Huang et al., 2021), and has comparable performance with robust conventional methods like BAD-SLAM (Schöps et al., 2019), Kintinuous (Whelan et al., 2012), and ORB-SLAM2 (Mur-Artal & Tardós, 2017). Note that only DROID-SLAM (Teed & Deng, 2021) and our method are evaluated with RGB inputs. Furthermore, our method does not include global bundle adjustment or loop closure, which is common in the conventional SLAM system. Our method achieves reasonable tracking performance while enjoying the benefits of neural implicit map representation, which can produce a watertight scene model or predict unobserved regions.

Table 3 shows experiment results on the *EuRoC* dataset. We compare the tracking results with several strong baselines including TartanVO (Wang et al., 2020), SVO (Forster et al., 2014), DSO (Engel et al., 2017), DROID-VO (Teed & Deng, 2021), and DPVO (Teed et al., 2022). Our method generates comparable results in successful cases. Note there are two failure cases, where our method loses camera tracking due to the fast camera motion which leads to small view overlap between neighboring frames.

4.2 ABLATION STUDY

To inspect the effectiveness of the components in our framework, we perform the ablation studies on the `office-0` sequence of the *Replica* dataset.

Hierarchical Feature Volume To evaluate the effectiveness of our hierarchical feature volume, we experiment with different levels of hierarchies. We vary the number of hierarchies L and the number of feature channels C to keep the total number of learnable parameters similar. Table 4 shows the

Configurations		(L,C)								w/o MLP
		(6,1)	(4,4)	(2,8)	(1,16)	(6,2)	(6,4)	(6,8)	(6,16)	
ATE RMSE(cm)↓	MEAN	0.67	0.76	2.27	X	0.63	0.69	0.61	0.66	8.92
	STD	0.14	0.18	0.25	X	0.12	0.08	0.11	0.09	1.49
Accuacry(cm)↓	MEAN	2.60	3.39	6.78	X	2.86	2.35	2.96	2.48	11.43
	STD	0.56	0.91	0.95	X	0.49	0.33	0.40	0.12	3.17

Table 4: Ablation study of different configurations of the feature volume. The parameters L and C are the numbers of hierarchies and the number of the feature channel, respectively. We test on `office-0` for 5 times and calculate the mean and standard deviation of the camera tracking error and map accuracy.

Method	Memory(MB)↓	FLOPs($\times 10^3$)↓	runtime(ms)↓
iMAP	1.02	443.91	448
NICE-SLAM	12.0	104.16	130
Ours	29.1	18.76	335

Table 5: Memory, computation, and running time.

results of different settings. Clearly, the system performs worse when there are less hierarchies of feature volumes, even though a longer feature is learned to compromise it. Note the system fails to track camera motion at textureless regions when L is set to 1. This experiment demonstrates the effectiveness of fusing features from different scales to better capture scene geometry.

Number of Feature Channel We further vary the number of feature channel C with L fixed at 6. Table 4 shows similar system performance is achieved for $C = 2, 4, 8, 16$. Therefore, to keep our method simple, we select $C = 1$ in experiments to reduce computation cost.

MLP Decoder To study the impact of the MLP decoder, we also experiment without the MLP decoder, where the 1-channel feature can be regarded as the occupancy directly. At a 3D point, we sum the occupancies from all hierarchies for the final result. The color is computed similarly with another 6-level volume of 3 channels. As shown in the right of Table 4, the system performance drops significantly without the MLP decoder.

4.3   MEMORY AND COMPUTATION ANALYSIS

Table 5 analyzes the memory and computation expenses. The memory cost is evaluated on the `office-0` sequence of the *Replica* dataset. We use the same bounding box size of the feature volume in both NICE-SLAM (Zhu et al., 2022) and our method. iMAP (Sucar et al., 2021) is the most memory efficient with only 1.02MB map size. However, as discussed in NICE-SLAM (Zhu et al., 2022), it cannot deal with larger scenes. Our map size is larger than NICE-SLAM (Zhu et al., 2022) because we recover the scene map at a higher resolution of 8cm while NICE-SLAM (Zhu et al., 2022) is at a resolution of 16cm.

Table 5 also reports the number of FLOPs for computing the color and occupancy at a single 3D point. Our method requires much less FLOPS, benefiting from our short features and shallow MLP decoder. Table 5 further reports the computation time of processing one input frame. Note here we sample $|\mathcal{M}| = 3000$ pixels with an iteration number $N_w = 100$, while NICE-SLAM and iMAP use much less samples and iterations (i.e. $|\mathcal{M}| = 1000$, $N_w = 10$) since their optimization problem is simpler with additional depth input. Our running time is reported with an RTX 2080TI GPU, while the running time of NICE-SLAM and iMAP are cited from their papers with an RTX 3090 GPU.

5   CONCLUSION

This paper introduces a dense visual SLAM method working with regular RGB cameras with neural implicit map representation. The scene map is encoded with a hierarchical feature volume together with an MLP decoder, which are both optimized with the camera poses simultaneously through back-propagation. To deal with regular RGB cameras, a sophisticated warping loss is designed to enforce multi-view geometry consistency during the optimization. The proposed method compares favorably with the widely used benchmark datasets, and even surpasses some recent methods with RGB-D inputs.

REFERENCES

Jonathan T. Barron, Ben Mildenhall, Matthew Tancik, Peter Hedman, Ricardo Martin-Brualla, and Pratul P. Srinivasan. Mip-nerf: A multiscale representation for anti-aliasing neural radiance fields. In *Proceedings of the International Conference on Computer Vision (ICCV)*, 2021.

Michael Bloesch, Jan Czarnowski, Ronald Clark, Stefan Leutenegger, and Andrew J. Davison. Codeslam – learning a compact, optimisable representation for dense visual slam. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2018.

Michael Burri, Janosch Nikolic, Pascal Gohl, Thomas Schneider, Joern Rehder, Sammy Omari, Markus W Achtelik, and Roland Siegwart. The euroc micro aerial vehicle datasets. *The International Journal of Robotics Research*, 2016. URL http://ijr.sagepub.com/content/early/2016/01/21/0278364915620033.abstract.

Cesar Cadena, Luca Carlone, Henry Carrillo, Yasir Latif, Davide Scaramuzza, Jose Neira, Ian Reid, and John J. Leonard. Past, present, and future of simultaneous localization and mapping: Toward the robust-perception age. *IEEE Transactions on Robotics (TRO)*, 32:1309—-1332, 2016.

Zhiqin Chen and Hao Zhang. Learning implicit fields for generative shape modeling. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2019.

Brian Curless and Marc Levoy. A volumetric method for building complex models from range images. In *Proceedings of the 23rd Annual Conference on Computer Graphics and Interactive Techniques*, SIGGRAPH '96, pp. 303–312, 1996.

Angela Dai, Matthias Nießner, Michael Zollhofer, Shahram Izadi, and Christian Theobalt. Bundle-fusion: Real-time globally consistent 3d reconstruction using online surface re-integration. *ACM Transactions on Graphics (TOG)*, 2017.

Jakob Engel, Thomas Schops, and Daniel Cremers. Lsd-slam: Large-scale direct monocular slam. In *Proceedings of the European Conference on Computer Vision (ECCV)*, 2014.

Jakob Engel, Vladlen Koltun, and Daniel Cremers. Direct sparse odometry. *IEEE Transactions on Pattern Analysis and Machine Intelligence (TPAMI)*, 40(3):611–625, 2017.

Christian Forster, Matia Pizzoli, and Davide Scaramuzza. Svo: Fast semi-direct monocular visual odometry. In *2014 IEEE international conference on robotics and automation (ICRA)*, pp. 15–22. IEEE, 2014.

Jiahui Huang, Shi-Sheng Huang, Haoxuan Song, and Shi-Min Hu. Di-fusion: Online implicit 3d reconstruction with deep priors. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2021.

Yoonwoo Jeong, Seokjun Ahn, Christopher Choy, Anima Anandkumar, Minsu Cho, and Jaesik Park. Self-calibrating neural radiance fields. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 5846–5854, 2021.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Georg Klein and David Murray. Parallel tracking and mapping for small ar workspaces. In *Proceedings of the International Symposium on Mixed and Augmented Reality (ISMAR)*, 2007.

Chen-Hsuan Lin, Wei-Chiu Ma, Antonio Torralba, and Simon Lucey. Barf: Bundle-adjusting neural radiance fields. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 5741–5751, 2021.

William E Lorensen and Harvey E Cline. Marching cubes: A high resolution 3d surface construction algorithm. *ACM siggraph computer graphics*, 21(4):163–169, 1987.

Andréa Macario Barros, Maugan Michel, Yoann Moline, Gwenolé Corre, and Frédérick Carrel. A comprehensive survey of visual slam algorithms. *Robotics*, 11(1), 2022. ISSN 2218-6581. URL https://www.mdpi.com/2218-6581/11/1/24.

Ricardo Martin-Brualla, Noha Radwan, Mehdi S. M. Sajjadi, Jonathan T. Barron, Alexey Dosovitskiy, and Daniel Duckworth. Nerf in the wild: Neural radiance fields for unconstrained photo collections. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2021.

Lars Mescheder, Michael Oechsle, Michael Niemeyer, Sebastian Nowozin, and Andreas Geiger. Occupancy networks: Learning 3d reconstruction in function space. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2019.

Ben Mildenhall, Pratul P. Srinivasan, Matthew Tancik, Jonathan T. Barron, Ravi Ramamoorthi, and Ren Ng. Nerf: Representing scenes as neural radiance fields for view synthesis. In *Proceedings of the European Conference on Computer Vision (ECCV)*, 2020.

Thomas Müller, Alex Evans, Christoph Schied, and Alexander Keller. Instant neural graphics primitives with a multiresolution hash encoding. *ACM Trans. Graph.*, 41(4):102:1–102:15, July 2022. doi: 10.1145/3528223.3530127. URL https://doi.org/10.1145/3528223.3530127.

Raúl Mur-Artal and Juan D. Tardós. Orb-slam2: An open-source slam system for monocular, stereo, and rgb-d cameras. *IEEE Transactions on Robotics (TRO)*, 33(5):1255–1262, 2017.

Zak Murez, Tarrence van As, James Bartolozzi, Ayan Sinha, Vijay Badrinarayanan, and Andrew Rabinovich. Atlas: End-to-end 3d scene reconstruction from posed images. In *Proceedings of the European Conference on Computer Vision (ECCV)*, 2020.

Richard A. Newcombe, Shahram Izadi, Otmar Hilliges, David Molyneaux, David Kim, and Andrew J. Davison. Kinectfusion: Real-time dense surface mapping and tracking. In *Proceedings of the International Symposium on Mixed and Augmented Reality (ISMAR)*, 2011a.

Richard A. Newcombe, Steven J. Lovegrove, and Andrew J. Davison. Dtam: Dense tracking and mapping in real-time. In *Proceedings of the International Conference on Computer Vision (ICCV)*, 2011b.

Michael Niemeyer, Lars Mescheder, Michael Oechsle, and Andreas Geiger. Differentiable volumetric rendering: Learning implicit 3d representations without 3d supervision. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020.

Michael Oechsle, Songyou Peng, and Andreas Geiger. Unisurf: Unifying neural implicit surfaces and radiance fields for multi-view reconstruction. In *International Conference on Computer Vision (ICCV)*, 2021.

Jeong Joon Park, Peter Florence, Julian Straub, Richard Newcombe, and Steven Lovegrove. Deepsdf: Learning continuous signed distance functions for shape representation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2019.

Adam Paszke, Sam Gross, Soumith Chintala, Gregory Chanan, Edward Yang, Zachary DeVito, Zeming Lin, Alban Desmaison, Luca Antiga, and Adam Lerer. Automatic differentiation in pytorch. 2017.

Shunsuke Saito, Zeng Huang, Ryota Natsume, Shigeo Morishima, Angjoo Kanazawa, and Hao Li. Pifu: Pixel-aligned implicit function for high-resolution clothed human digitization. In *Proceedings of the International Conference on Computer Vision (ICCV)*, 2019.

Shunsuke Saito, Tomas Simon, Jason Saragih, and Hanbyul Joo. Pifuhd: Multi-level pixel-aligned implicit function for high-resolution 3d human digitization. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020.

Thomas Schöps, Torsten Sattler, and Marc Pollefeys. Bad slam: Bundle adjusted direct rgb-d slam. In *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 134–144, 2019.

Rakesh Shrestha, Fei-Peng Tian, Wei Feng, Ping Tan, and Richard Vaughan. Learned map prediction for enhanced mobile robot exploration. In *Proceedings of the IEEE International Conference on Robotics and Automation (ICRA)*, 2019.

Julian Straub, Thomas Whelan, Lingni Ma, Yufan Chen, Erik Wijmans, Simon Green, Jakob J. Engel, Raul Mur-Artal, Carl Ren, Shobhit Verma, Anton Clarkson, Mingfei Yan, Brian Budge, Yajie Yan, Xiaqing Pan, June Yon, Yuyang Zou, Kimberly Leon, Nigel Carter, Jesus Briales, Tyler Gillingham, Elias Mueggler, Luis Pesqueira, Manolis Savva, Dhruv Batra, Hauke M. Strasdat, Renzo De Nardi, Michael Goesele, Steven Lovegrove, and Richard Newcombe. The Replica dataset: A digital replica of indoor spaces. 2019.

J. Sturm, N. Engelhard, F. Endres, W. Burgard, and D. Cremers. A benchmark for the evaluation of rgb-d slam systems. In *Proc. of the International Conference on Intelligent Robot Systems (IROS)*, Oct. 2012a.

Jürgen Sturm, Nikolas Engelhard, Felix Endres, Wolfram Burgard, and Daniel Cremers. A benchmark for the evaluation of rgb-d slam systems. In *2012 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pp. 573–580, 2012b.

Edgar Sucar, Kentaro Wada, and Andrew Davison. Nodeslam: Neural object descriptors for multi-view shape reconstruction. In *3*, 2020.

Edgar Sucar, Shikun Liu, Joseph Ortiz, and Andrew Davison. iMAP: Implicit mapping and positioning in real-time. In *Proceedings of the International Conference on Computer Vision (ICCV)*, 2021.

Jiaming Sun, Yiming Xie, Linghao Chen, Xiaowei Zhou, and Hujun Bao. Neuralrecon: Real-time coherent 3d reconstruction from monocular video. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2021.

Chengzhou Tang and Ping Tan. Ba-net: Dense bundle adjustment networks. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2019.

Zachary Teed and Jia Deng. Deepv2d: Video to depth with differentiable structure from motion. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2020.

Zachary Teed and Jia Deng. DROID-SLAM: Deep Visual SLAM for Monocular, Stereo, and RGB-D Cameras. *Advances in neural information processing systems*, 2021.

Zachary Teed, Lahav Lipson, and Jia Deng. Deep patch visual odometry. *arXiv preprint arXiv:2208.04726*, 2022.

Benjamin Ummenhofer, Huizhong Zhou, Jonas Uhrig, Nikolaus Mayer, Eddy Ilg, Alexey Dosovitskiy, and Thomas Brox. Demon: Depth and motion network for learning monocular stereo. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2017.

Peng Wang, Lingjie Liu, Yuan Liu, Christian Theobalt, Taku Komura, and Wenping Wang. Neus: Learning neural implicit surfaces by volume rendering for multi-view reconstruction. *Advances in Neural Information Processing Systems (NeurIPS)*, 34, 2021.

Wenshan Wang, Yaoyu Hu, and Sebastian Scherer. Tartanvo: A generalizable learning-based vo. 2020.

Zhou Wang, A.C. Bovik, H.R. Sheikh, and E.P. Simoncelli. Image quality assessment: from error visibility to structural similarity. *IEEE Transactions on Image Processing*, 13(4):600–612, 2004. doi: 10.1109/TIP.2003.819861.

Xingkui Wei, Yinda Zhang, Zhuwen Li, Yanwei Fu, and Xiangyang Xue. Deepsfm: Structure from motion via deep bundle adjustment. In *Proceedings of the European Conference on Computer Vision (ECCV)*, 2020.

T. Whelan, J. McDonald, Michael Kaess, Maurice Fallon, Hordur Johannsson, and John J. Leonard. Kintinuous: Spatially extended kinectfusion. In *RSS Workshop on RGB-D: Advanced Reasoning with Depth Cameras*, July 2012.

Thomas Whelan, Stefan Leutenegger, Renato F. Salas-Moreno, Ben Glocker, and Andrew J. Davison. Elasticfusion: Dense slam without a pose graph. In *Proceedings of Robotics: Science and Systems (RSS)*, 2021.

Lior Yariv, Yoni Kasten, Dror Moran, Meirav Galun, Matan Atzmon, Basri Ronen, and Yaron Lipman. Multiview neural surface reconstruction by disentangling geometry and appearance. *Advances in Neural Information Processing Systems (NeurIPS)*, 33, 2020.

Jiahui Zhang, Fangneng Zhan, Rongliang Wu, Yingchen Yu, Wenqing Zhang, Bai Song, Xiaoqin Zhang, and Shijian Lu. Vmrf: View matching neural radiance fields. *arXiv preprint arXiv:2207.02621*, 2022.

Kai Zhang, Gernot Riegler, Noah Snavely, and Vladlen Koltun. Nerf++: Analyzing and improving neural radiance fields. *arXiv:2010.07492*, 2020.

Huizhong Zhou, Benjamin Ummenhofer, and Thomas Brox. Deeptam: Deep tracking and mapping. In *Proceedings of the European Conference on Computer Vision (ECCV)*, 2018.

Tinghui Zhou, Matthew Brown, Noah Snavely, and David Lowe. Unsupervised learning of depth and ego-motion from video. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2017.

Zihan Zhu, Songyou Peng, Viktor Larsson, Weiwei Xu, Hujun Bao, Zhaopeng Cui, Martin R. Oswald, and Marc Pollefeys. Nice-slam: Neural implicit scalable encoding for slam. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2022.

A APPENDIX

In the appendix, we present the following:

A.1 FEATURE VOLUME INITIALIZATION

We initialize the parameters of all feature volumes under a normal distribution, while the mean and the standard deviation of the distribution are 0 and 0.001, respectively.

A.2 POST OPTIMIZATION

To enhance the geometry and color consistency throughout the entire scene, we also introduce a post-optimization module similar to the one in NICE-SLAM (Zhu et al., 2022) and iMAP (Sucar et al., 2021). This module is optional at the end of processing an input video clip to improve the final mesh quality without heavy computation. This post-optimization module optimizes the implicit scene representation with the camera poses fixed using all keyframes in an alternative way. In each iteration, we sample a random keyframe k and choose all other keyframes with at least 70% overlap with frame k. We optimize the implicit function using all keyframes $1,000$ iterations.

A.3 ABLATION ON WARPING LOSS

To see the impact of utilizing multi-scale patch warping photometric loss, we run an ablation study on different settings of the warping loss. We evaluate different configurations during the initialization stage. We mark our default configuration as the baseline: using a multi-scale patch warping loss defined as Equation 7 where $\mathcal{S} = \{1, 5, 11\}$. We then compare it with two different patch size configurations, where $\mathcal{S} = \{1\}$ and $\mathcal{S} = \{1, 11\}$, respectively. Note that the setting of $\mathcal{S} = \{1\}$ degrades to the pixel-wise warping loss as Equation 5. As shown in Table 6, our default configuration achieves 1.85cm in terms of the average depth error. The setting of $\mathcal{S} = \{1, 11\}$ is slightly inferior to the baseline, while the setting of pixel-wise warping fails to recover an accurate depth. This is also illustrated in the qualitative comparison in Figure 3.

A.4 MORE ABLATION ON FEATURE CHANNEL

We further verify the number of feature channels with the initialization stage. As shown in the right of Table 6, increasing the number of features C does not improve the quality of the initialized depth. Note that while the setting ($L = 1, c = 16$) can still initialize the reconstruction, the camera tracking soon fails in textureless regions. This ablation further justifies our choice of $C = 1$.

Figure 3: The visualization of the initialized depth map during optimization iterations. (a) The default configuration with multiple patch-wise warping loss, $\mathcal{S} = \{1, 5, 11\}$. (b) The pixel-wise warping loss, $\mathcal{S} = \{1\}$.

Depth Error(cm)↓	$\mathcal{S}$			(L, C)			
	$\{1, 5, 11\}^*$	$\{1, 11\}$	$\{1\}$	$(6, 1)^*$	$(6, 4)$	$(6, 16)$	$(1, 16)$
MEAN	1.85	3.73	35	1.85	1.72	1.93	1.83
STD	0.15	0.85	3.65	0.15	0.09	0.16	0.19

Table 6: Mean depth errors of initialized map for different settings in the ablation study. The configuration of our method is marked with *. We report the mean and std of depth error on 5 runs of `office-0` on *Replica*.

A.5 MESH EXTRACTION AND VISUALIZATION

Our implicit map representation contains a hierarchical feature volume and an MLP decoder. For each point in the 3D space, we can compute its occupancy from our implicit map representation. Our method can easily predict the occupancy for unseen points. We use the marching cubes algorithm (Lorensen & Cline, 1987) to create a mesh for visualization and evaluation.

We provides visualization of all reconstructed scenes in *Replica* (Straub et al., 2019) in Figure 5 and 6. To see more shape details, we also render these extracted meshes at a close viewpoint and compare our results with those from iMAP (Sucar et al., 2021) and DROID-SLAM (Teed & Deng, 2021) in Figure 4. It is clear that our method recovers more shape details and can fill in unobserved regions with the neural implicit map.

(a) Hole-Filling   (b) Fine-Geometry

Figure 4: Rendering of the reconstructe mesh from close viewpoint. Our results are more complete and accurate than those from iMAP and DROID-SLAM.

Ours   Ground Truth

Figure 5: Visual comparison of the reconstructed meshes on the *Replica* datasets.

Figure 6: Visual comparison of the reconstructed meshes on the *Replica* datasets.