A Character-Level Neural Approach to Sinhala Sandhi Splitting

Abstract

Sinhala Sandhi splitting recovers the constituent words or morphemes hidden inside a phonologically merged surface form. The task is important for Sinhala NLP because Sandhi obscures lexical boundaries, but no prior published work has established a neural benchmark for Sinhala Sandhi splitting. We present a character-level sequence-to-sequence study based on SandhiLex, using native Sinhala Unicode input and evaluating recurrent encoder-decoder models for affixational and more complex lexicalized, derivational, and etymological Sandhi. A bidirectional LSTM encoder with a unidirectional LSTM decoder yields the best results on the hard subset, achieving 68.40% exact-match accuracy and 82.08% character-level accuracy. On the full affixational subset, the same model achieves 94.00% exact-match accuracy. Ablations show that bidirectional encoding is the largest contributor to performance, while native Sinhala script improves exact match accuracy over romanized input. Qualitative analysis indicates that many errors are near misses involving boundary adjacent characters or plausible but incorrect phonological substitutions. These results establish an empirical baseline for Sinhala Sandhi splitting and identify data scale, Sandhi type conditioning, and attention-based decoding as the main directions for future work.

1 Introduction

Most natural language processing pipelines assume that whitespace-delimited tokens correspond to meaningful lexical units. This assumption fails in morphologically complex languages where phonological processes at morpheme boundaries produce surface forms whose constituents are no longer recoverable by direct lexical lookup (Liyanage and Pushpananda, 2024). Sandhi, prevalent across South Asian languages, is a clear instance: adjacent words undergo vowel coalescence, consonant assimilation, or sound deletion upon combi-

nation, and the resulting errors propagate through downstream tasks, including morphological analysis, information retrieval, and machine translation (Ekanayaka et al., 2023).

Sinhala, an Indo-Aryan language spoken by over 16 million people in Sri Lanka, exhibits productive Sandhi across four linguistically distinct categories: affixational, lexicalized, derivational, and etymological (Liyanage and Pushpananda, 2024). For example, කලා kalā (art) and ආයතනය āyatanaya (institution) merge into කලායතනය kalāyatanaya (art institute), entirely obscuring the original word boundary. As Sinhala digital content continues to grow, the inability to correctly segment such forms increasingly limits the accuracy of downstream language technologies serving this community.

Existing computational approaches to Sinhala Sandhi rely on rule-based methods (Priyanga et al., 2017) that struggle with ambiguous surface forms, require ongoing expert maintenance, and generalize poorly beyond predefined rule inventories (Devadath et al., 2014; Ghosh et al., 2022). Neural sequence-to-sequence models offer a data-driven alternative, achieving over 95% accuracy on Sanskrit Sandhi splitting (Aralikatte et al., 2018; Dave et al., 2020) with analogous successes for Tamil, Telugu, and Malayalam (Dasari et al., 2025; Premjith et al., 2018). Despite the availability of SandhiLex (Liyanage and Pushpananda, 2024), a structured Sinhala Sandhi lexicon, and prior evidence that character-level neural models are effective for Sinhala morphological processing (Ekanayaka et al., 2023), no neural benchmark for Sinhala Sandhi splitting exists.

This gap raises three questions: which neural architectures are most effective for Sinhala Sandhi splitting; which factors, including encoder directionality, script representation, and data scale, most influence performance; and how quantitative metrics correlate with qualitative linguistic accu-

racy in this setting.

The present study addresses these questions by framing Sinhala Sandhi splitting as character-level sequence transduction (Dave et al., 2020; Dasari et al., 2025), training recurrent encoder-decoder models on both SandhiLex subsets. A bidirectional LSTM encoder with a unidirectional LSTM decoder proves most effective, achieving 68.40% exact match and 82.08% character-level accuracy on the hard subset and 94.00% on the affixational subset, with bidirectional encoding and native Sinhala Unicode identified as the largest contributors to performance. The contributions of this work are as follows:

1. The first neural benchmarks for Sinhala Sandhi splitting are established on both the affixational and hard subsets of SandhiLex.
2. Six recurrent encoder-decoder configurations alongside double-decoder and transformer variants are systematically compared under controlled conditions.
3. The first controlled comparison of native Sinhala Unicode versus romanized input is provided, showing that native script preserves orthographic distinctions critical for exact form recovery.

The remainder of this paper is structured as follows. Related works are reviewed, followed by the dataset and methodology. Results and analysis are then presented, and the paper concludes with a discussion of limitations and future directions.

2 Related Work

Sinhala Sandhi and Sinhala NLP. Sinhala Sandhi includes boundary changes such as vowel coalescence, consonant assimilation, insertion, and deletion (Liyanage and Pushpananda, 2024). SandhiLex distinguishes affixational, lexicalized, derivational, and etymological Sandhi. Affixational Sandhi is more regular because it occurs at root affix boundaries; for instance, අසනීපයක asanipayaka (in an illness) splits cleanly into අසනීප asanipa (ill) + ය ya (ya) + ක ka (ka), where the boundary is transparent and components are recoverable by direct inspection. By contrast, etymological forms such as කම්මල kammala (smithy) offer no phonological cue to the correct split කම් kam (work) + හල hala (hall/place), as boundary consonants are assimilated and constituents no longer appear in their original form; rule based systems fail here by generating compet-

ing candidates without a principled selection mechanism. Sinhala morphological analysis has previously benefited from character-level neural models, including bidirectional GRU architectures, and identifies Sandhi splitting as an important next task (Ekanayaka et al., 2023). Similar character-level neural modelling has also been explored for Malayalam morphology and Sandhi-related suffix separation (Premjith et al., 2018; Priya and Kumar, 2020).

Rule-based Sandhi processing. Traditional Sandhi systems rely on manually specified phonological rules, finite-state analyses, or related rule-driven procedures (Devadath et al., 2014; Ghosh et al., 2022). Sinhala rule-based work has addressed word joining rather than data-driven splitting (Priyanga et al., 2017). Related rule-based studies in other South Asian languages show that linguistic rules are interpretable, but they require expert maintenance and struggle when multiple underlying forms can produce similar surface strings (Devadath et al., 2014; Kallur and Anami, 2025).

Neural Sandhi splitting. Most neural Sandhi work has focused on Sanskrit. Double Decoder RNNs, hybrid recurrent convolutional systems, and sequence-to-sequence models have reported strong results when trained on much larger Sanskrit resources (Aralikatte et al., 2018; Dave et al., 2020). Transformer and sequence-to-sequence approaches have also been explored for other Indian languages and technical lexicon generation settings (Dasari et al., 2025; J et al., 2025). These studies motivate a neural approach to Sinhala, but their data scale and linguistic settings differ from those of SandhiLex. This study therefore evaluates simple, data efficient recurrent transducers before assuming that larger transformer style models are appropriate.

These observations motivate the experimental design of the present study. Character-level sequence-to-sequence modeling is adopted because it has proven effective for analogous morphophonological tasks in related low-resource languages (Premjith et al., 2018; Dave et al., 2020). Bidirectional encoding is prioritized given evidence that two way context is critical for Sinhala morphological processing (Ekanayaka et al., 2023), and that Sandhi boundary transformations depend on characters on both sides of the merge point (Liyanage and Pushpananda, 2024). The

Table 1: Sinhala Sandhi categories used in SandhiLex, with transliteration and English glosses.

Type	Description	Example input	Split
Affixational	Root affix boundary; comparatively regular	අසනීපයක asanipayaka (in an illness)	අසනීප ය ක asanipa ya ka (ill + suffixes)
Lexicalized	Word combination whose meaning remains related to its components	දකුණත dakunata (right hand)	දකුණු අත dakunu ata (right + hand)
Derivational	Boundary change creates a derived lexical form	ලේඛනාගාර lekhanāgāra (archives)	ලේඛන ආගාර lekhana āgāra (writings + house)
Etymological	Historically fused form with less transparent components	කම්මල kammala (smithy)	කම් හල kam hala (work + hall/place)

186 evaluation is conducted separately on affixational
187 and hard subsets to isolate the effects of linguis-
188 tic complexity and data scale, following practices
189 established in Sanskrit Sandhi research (Aralikatte
190 et al., 2018; Sreedeepa et al., 2024).

191 ## 3 Task and Data

192 Given an input Sandhi form $x = x_1, \ldots, x_n$,
193 the task is to generate a target sequence $y =$
194 $y_1, \ldots, y_m$ containing the split constituents. For
195 instance, විහාරාධිකාර viharādhikāra (temple au-
196 thorities) is mapped to විහාර vihāra (temple) +
197 අධිකාර adhikāra (authority). The output may be
198 longer than the input because splitting can require
199 restoring characters that were changed or deleted
200 during Sandhi formation. Table 1 summarizes the
201 Sandhi categories used in the dataset with exam-
202 ples.

203 The experiments use SandhiLex, a Sinhala
204 Unicode Sandhi lexicon developed to formalize
205 Sinhala morphophonology for computational use
206 (Liyanage and Pushpananda, 2024). The resource
207 is distributed as plain text tab-separated files in
208 which each row pairs one merged Sandhi form with
209 its segmented constituent form. In this study, each
210 row is treated as a supervised sequence pair: the
211 Sandhi word is the encoder input, and the split
212 form is the decoder target.

213 Following the experimental setup, we evaluate
214 two subsets. The *easy* subset contains Affixational
215 Sandhi, where the boundary occurs between a lex-
216 eme and an attached prefix or suffix. This sub-
217 set contains more than 300,000 available pairs;
218 150,000 are sampled for the full data experiment
219 (Table 2). Because Affixational Sandhi is compar-
220 atively systematic, it is used to test how the model
221 behaves when many regular examples are avail-
222 able.

Table 2: SandhiLex subsets used in the experiments. The easy subset is affixational; the hard subset combines lexicalized, derivational, and etymological forms.

Subset	Sandhi types	Size
Easy	Affixational	>300k pairs; 150k sampled
Hard	Lexicalized, derivational, etymological	~4.5k pairs

223 The *hard* subset contains approximately 4,500
224 Lexicalized, Derivational, and Etymological
225 Sandhi forms collected through semi automatic
226 manual and corpus based extraction (Liyanage
227 and Pushpananda, 2024). These forms are harder
228 because the original boundary is often less trans-
229 parent and the surface form may not preserve all
230 characters from the underlying constituents. The
231 hard subset is therefore the main benchmark for
232 evaluating whether the model can handle opaque
233 Sinhala Sandhi. Examples include දකුණත
234 dakunata (right hand), split as දකුණු dakunu
235 (right) + අත ata (hand), and කම්මල kammala
236 (smithy), split as කම් kam (work) + හල hala
237 (hall/place).

238 **Data format** SandhiLex entries follow the for-
239 mat <sandhi word>\t<split form>. For ex-
240 ample, a row contains a single merged input token
241 on the left and a whitespace-separated sequence of
242 recovered components on the right.

243 **Romanized counterpart.** For the script repre-
244 sentation experiment, every native Unicode pair
245 is converted into a romanized pair while preserv-
246 ing the same input target alignment. The translit-
247 eration module uses a character-level mapping in
248 which Sinhala symbols are categorized as conso-
249 nants, modifiers, or vowels. Consonants carry an
250 implicit *a* vowel unless a modifier changes or sup-
251 presses it. For example, the native pair අක්ෂාංශ
252 akshāmsha (latitude/part) → අක්ෂ අංශ aksha

amsha (axis/letter + part) is represented in the romanized data with the same segmentation boundary. This controlled pairing allows differences in performance to be attributed to script representation rather than to a different train-test split (Ekanayaka et al., 2023).

4 Methodology

4.1 Preprocessing

Before training, the raw SandhiLex files are cleaned by removing empty and duplicate entries. The Sandhi word is used as the encoder input, and the segmented form is used as the decoder target. The target sequence is bounded by a start token ($) and an end token (¶). Character-level tokenisation is applied separately to encoder and decoder sequences, and sequences are post-padded to uniform lengths for batch training.

Native Sinhala Unicode is the primary representation. However, romanized transliteration is sometimes used in low resource NLP to reduce character vocabulary size and simplify tokenization, motivating a controlled comparison. A romanized version of the same data is prepared using a character-level mapping that categorizes Sinhala symbols as consonants, modifiers, or vowels, preserving identical Sandhi and split pairings so that any performance difference is attributable to script choice rather than dataset variation. The key concern is that romanzation may merge phonologically distinct Sinhala characters into identical Roman forms, losing the orthographic contrasts that mark Sandhi boundaries. This follows evidence that native Sinhala script preserves orthographic distinctions important for morphological processing (Ekanayaka et al., 2023).

4.2 Encoder-Decoder Model

Figure 1 illustrates the overall Architecture of the encoder-decoder system.

A merged Sinhala Sandhi form is tokenised at the character level and fed into the encoder as a sequence of integer indices. The bidirectional LSTM encoder processes the sequence in both forward and backward directions with latent dimensionality 512 per direction; the resulting forward and backward hidden and cell states are concatenated to form a 1024 dimensional context vector that summarises the full input. This context vector initialises the unidirectional LSTM decoder, which autoregressively generates one output char-

acter per step through a dense softmax projection until the end token or maximum length is reached, producing the whitespace separated split form.

The model is compiled with the Adam optimizer and sparse categorical loss. During inference, separate encoder and decoder models are instantiated: the encoder produces the initial decoder states, and the decoder generates the segmented output autoregressively until the end token or maximum output length is reached.

4.3 Training Protocol

Separate models are trained for the easy and hard data settings. The easy dataset is trained for 10 epochs with batch size 32. The hard dataset is trained for 25 epochs owing to its smaller size and greater linguistic complexity. A 10% validation split is used during training, and final evaluation follows an 80:20 train-test setup. Tokenizers, vocabulary mappings, model parameters, and sequence length settings are serialized for reproducible inference. The model and training settings are summarized in Table 3.

Table 3: Implementation settings for the main model.

Component	Setting
Input unit	Sinhala Unicode character
Output unit	Sinhala Unicode character plus space
Encoder	Bidirectional LSTM, 512 units per direction
Decoder	Unidirectional LSTM, 1024 units
Loss	Sparse categorical cross-entropy
Optimizer	Adam
Easy training	10 epochs, batch size 32
Hard training	25 epochs, batch size 32
Validation	10% validation split
Final split	80:20 train-test
Decoding	Autoregressive

4.4 Compared Systems and Metrics

The study compares RNN, GRU, and LSTM encoder-decoder models with both unidirectional and bidirectional encoders, following recurrent modeling choices in Malayalam and Sanskrit work (Premjith et al., 2018; Hellwig and Nehrdich, 2018). Additional experiments include a manually configured LSTM encoder-decoder, Double Decoder LSTM variants inspired by Sanskrit work (Aralikatte et al., 2018), and a SinBERT Large transformer fine-tuning experiment.

Exact match (EM) measures the percentage of predictions that exactly match the reference split. Character-level accuracy (CLA) measures the agreement between predictions and references

Figure 1: Architecture of the bidirectional LSTM encoder-decoder for Sinhala Sandhi splitting

at the character level. Word-level precision, recall, and F1 are reported on a randomly selected 500-sample hard set test subset to provide a more fine-grained evaluation of token-level prediction quality, particularly for partially correct outputs and boundary-sensitive errors.

5 Results

Table 4 shows the main hard subset architecture comparison. Bidirectional encoders outperform unidirectional encoders for all recurrent cells. The best model is the bidirectional LSTM encoder-decoder, with 68.40% EM and 82.08% CLA. Relative to the unidirectional LSTM, bidirectionality adds 26.0 EM points, confirming that two-way context is critical for resolving Sinhala Sandhi boundaries, where the correct split depends on characters on both sides of the merge point (Liyanage and Pushpananda, 2024).

Table 4: Architecture comparison on the SandhiLex hard subset. Scores are percentages.

Encoder	Cell	EM	CLA
Unidirectional	RNN	20.40	56.44
Unidirectional	GRU	33.40	66.53
Unidirectional	LSTM	42.40	71.50
Bidirectional	RNN	24.40	62.01
Bidirectional	GRU	50.50	74.59
Bidirectional	LSTM	**68.40**	**82.08**

To assess whether the BiLSTM improvement over BiGRU is statistically reliable rather than an artefact of test set variation, McNemar's test is applied to the paired predictions on the randomly selected 500 sample hard set subset. McNemar's test is appropriate here because the two models are evaluated on the same examples, making the errors dependent rather than independent, which violates the assumptions of standard proportion tests.

The result is significant 3.076×10^{-7} ($p < 0.05$), confirming that the BiLSTM's advantage over Bi-GRU reflects a genuine difference in predictive behaviour and is not attributable to chance, as summarized in Table 5.

Table 5: Significance test reported for the two strongest recurrent encoders.

Comparison	Result
BiLSTM vs. BiGRU	3.076×10^{-7} ($p < 0.05$)
Test subset	500 examples
Test type	McNemar

Gap between EM and CLA. The consistent gap between EM and CLA across all models indicates that many incorrect predictions are near misses rather than complete failures. For instance, දකුණාත dakunata (right hand) is predicted as දකුණ අත dakuna ata (right hand) instead of the correct දකුණු අත dakunu ata (right hand), recovering the correct constituents and boundary position but missing a single final vowel. Similarly සිංහසුන sihasuna (the throne), the model produced සිහු අසුන sihu asuna (lion seat) instead of the correct සිහ අසුන siha asuna (lion seat), again preserving the boundary and overall structure while omitting a final vowel. Such errors score zero under exact match yet achieve high character-level overlap, a pattern consistent with observations in Sanskrit Sandhi segmentation (Sreedeepa et al., 2024). This motivates reporting both metrics rather than relying on a single aggregate score.

Table 6 compares native Sinhala Unicode with romanized input for bidirectional encoders. The best exact-match score is obtained with native-script LSTM input. Romanization gives higher CLA for LSTM, but lower EM, suggesting that romanized forms may ease local character prediction

while losing distinctions needed for complete form recovery.

Table 6: Script representation comparison for bidirectional encoders on the hard subset. Scores are percentages.

Script	Cell	EM	CLA
Romanized	RNN	31.80	73.78
Romanized	GRU	58.75	81.92
Romanized	LSTM	64.00	**86.27**
Native Unicode	RNN	24.40	62.01
Native Unicode	GRU	50.50	74.59
Native Unicode	LSTM	**68.40**	82.08

Table 7 separates data scale from linguistic difficulty. With the full affixational subset, the bidirectional LSTM reaches 94.00% EM and 98.24% CLA. When the easy subset is size matched to the hard training regime, EM falls to 68.40%. This supports the study conclusion that the hard subset is constrained not only by linguistic opacity, but also by limited data volume, a recurring concern in low resource and Sandhi specific research (de Silva, 2019; Sreedeepa et al., 2024).

Table 7: Effect of data volume and Sandhi type on bidirectional LSTM performance.

Dataset	Condition	EM	CLA
Easy	Size matched	68.40	78.85
Easy	Full 150k sample	**94.00**	**98.24**
Hard	Full ∼4.5k	68.40	82.08

Figure 2 summarizes the additional model families evaluated on the hard subset. The Double Decoder LSTM was implemented following the architecture proposed by (Aralikatte et al., 2018) for Sanskrit, and adapted to Sinhala by training separate encoder and decoder components on SandhiLex, using the same 80:20 train-test split and 25-epoch training protocol as for the main models.

Figure 2: Additional architecture results on the hard subset. Scores are percentages.

The SinBERT Large experiment fine-tuned the pre-trained SinBERT Large transformer on the hard subset using the same character-level formulation. Neither SinBERT Large nor the Double Decoder LSTM outperformed the recurrent encoder-decoder baseline, achieving only 2.00% and 1.00% EM, respectively.

These results suggest limited transferability of the Sanskrit-oriented Double Decoder architecture to Sinhala under low-resource conditions, while the SinBERT Large result is consistent with findings that transformer models can be less data-efficient in small-data settings (Sreedeepa et al., 2024). However, these findings should be interpreted only within the current dataset and implementation setup (Aralikatte et al., 2018; Dasari et al., 2025).

On the randomly selected 500 sample hard subset test set, word level exact match precision, recall, and F1 are all 63.60%. This equality follows from the exact match evaluation setup, where predictions are counted as either fully correct or incorrect.

6 Analysis and Discussion

The results identify the bidirectional LSTM encoder with a unidirectional LSTM decoder as the strongest architecture for Sinhala Sandhi splitting, consistent with earlier evidence supporting bidirectional character-level modelling for Sinhala morphology (Ekanayaka et al., 2023). The model achieves 68.40% EM, 82.08% CLA, and 63.60% F1 on the hard subset, outperforming both the unidirectional LSTM and bidirectional GRU baselines. Native Sinhala Unicode input also improves exact recovery compared to the romanized LSTM setting.

The comparison between unidirectional and bidirectional encoders shows that two-way context is the most important design factor in the experiments. This matches the linguistic nature of Sandhi, where boundary transformations depend on characters on both sides of the merge (Liyanage and Pushpananda, 2024). The script experiment also supports the conclusion that native Sinhala Unicode is preferable for exact form recovery, even though romanized input can sometimes achieve higher character-level accuracy.

The easy and hard comparison highlights the role of both data volume and Sandhi type. Affixational Sandhi reaches 94.00% EM in the full

150,000 sample setting because its boundary patterns are highly regular. In contrast, the hard subset reaches 68.40% EM because lexicalized and etymological forms involve more irregular phonological changes and are trained on only ∼4,500 examples. When the easy subset is size matched to the hard setting, its EM also drops substantially, confirming that data volume contributes significantly to the performance gap (Liyanage and Pushpananda, 2024).

The additional architecture experiments show that the tested SinBERT Large and Double Decoder LSTM settings do not outperform the bidirectional LSTM encoder-decoder under the available data conditions, despite the success of transformer and double-decoder approaches in other Sandhi settings (Aralikatte et al., 2018; Dasari et al., 2025). These findings are interpreted as results specific to the current dataset and implementation setup rather than as a general limitation of such architectures.

7 Ablation Studies

Table 8 reports the ablation experiments. The results reveal a clear hierarchy of contribution across the four design factors.

Table 8: Ablation study on the hard subset. Each row changes one component of the full model.

Variant	EM	CLA
Full model: BiLSTM, $d = 512$, Unicode, tuned	**68.40**	82.08
− bidirectional encoder	42.40	71.50
− native script	64.00	**86.27**
− latent dimension $512 \rightarrow 256$	61.20	78.43
− hyperparameter tuning	64.60	78.19

Bidirectional encoding is the most critical component in the ablation study, with its removal causing the largest performance drop of 26.0 EM points (68.40% to 42.40%). This supports the linguistic nature of Sinhala Sandhi, where correct boundary recovery depends on context from both sides of the merge point.

Model capacity is the second most influential factor. Reducing the latent dimension from 512 to 256 lowers EM by 7.2 points, suggesting that the hard subset's irregular phonological patterns require sufficient representational capacity. Hyperparameter tuning and script choice also contribute meaningfully: removing tuning reduces EM by 3.8 points, while replacing native Unicode with romanized input reduces EM by 4.4 points. Although romanization improves CLA, native Sinhala Unicode remains preferable for exact segmentation because it preserves orthographic distinctions needed for complete form recovery.

8 Error Analysis

The error analysis identifies three recurring error types. First, minor boundary shifts occur when the model finds the approximate split location but changes a nearby character. For example, සිංහසුන sihasuna (throne) may be predicted as සිහු අසුන sihu asuna (lion seat), instead of සිංහ අසුන siha asuna (lion seat). Second, phonological substitutions produce plausible but wrong decompositions; සමීකරණ samīkarana (equation) is predicted as සං කරණ sam karana (co-doing/formation) rather than සම කරණ sama karana (equal making). Third, complete segmentation failures occur mostly for low-frequency etymological compounds.

Table 9 gives representative predictions. Every Sinhala form is accompanied by transliteration and an English gloss so that the examples remain readable to non-Sinhala readers.

The examples illustrate two important properties of the errors. First, many wrong predictions remain linguistically close to the target. For දකුණාත dakunata (right hand), the prediction recovers the noun අත ata (hand) and the approximate modifier, but misses the final vowel in දකුණ dakunu (right). Second, etymological forms can be misleading because a plausible surface split may not match the historically correct decomposition. The කම්මල kammala (smithy) example shows this: කම් මල kam mala (work flower) is orthographically plausible but semantically wrong relative to කම් හල kam hala (work hall/place).

8.1 Qualitative Translation Impact

The study also evaluates downstream translation qualitatively. Without splitting, merged forms are sometimes mistranslated or left untranslated by a general-purpose translator; after splitting, their English meanings become recoverable. Table 10 summarizes the examples reported in the study. This is not a controlled extrinsic benchmark, but it illustrates why Sandhi splitting matters for practical Sinhala NLP (Liyanage and Pushpananda, 2024; Ekanayaka et al., 2023).

Table 9: Representative correct and incorrect predictions from the qualitative analysis.

Input	Prediction	Reference
විහාරාධිකාර viharādhikāra (temple authorities)	විහාර අධිකාර vihāra adhikāra (temple authority)	විහාර අධිකාර vihāra adhikāra (temple authority)
කලායතනය kalāyatanaya (art institute)	කලා ආයතනය kalā āyatanaya (art institution)	කලා ආයතනය kalā āyatanaya (art institution)
දකුණාත dakunata (right hand)	දකුණ අත dakuna ata (right hand)	දකුණු අත dakunu ata (right hand)
කම්මල kammala (smithy)	කම් මල kam mala (work flower)	කම් හල kam hala (work hall/place)

Table 10: Qualitative translation examples from the study.

Input	Without split	After split
ස්වරාදේශ svarādesha (vowel substitution)	Homeland (wrong)	Vowel substitution
විහාරාධිකාර viharādhikāra (temple authorities)	Untranslated	Temple authorities

9 Prototype Implementation

Beyond offline evaluation, the study implements a local prototype for Sinhala Sandhi splitting. The backend is built with FastAPI, selected for its asynchronous request handling and Pydantic based request validation. The service exposes two endpoints: `/easy` and `/hard`, corresponding to the trained model variants. CORS middleware is configured so that the frontend can communicate with the backend during local deployment.

The frontend is implemented in React. It allows a user to submit a Sinhala Sandhi word and view the predicted split, romanized output, and English translation. The transliteration module uses the same character-level mapping described in the preprocessing pipeline, while the translation component is used to make the output more readable for users who do not read Sinhala. Model weights, tokenizer objects, vocabulary mappings, and sequence length settings are serialized so that the deployed inference pipeline uses the same configuration as training. The thesis implementation also uses NumPy and scikit-learn utilities during data processing and splitting.

The prototype is included as an implementation demonstration rather than as a user study. The study reports functional validation in a local environment, but it does not evaluate usability, latency, or accuracy under real world deployment conditions. For this reason, the prototype supports the practical feasibility of the approach but does not replace the quantitative benchmark.

10 Conclusion

This paper frames Sinhala Sandhi splitting as character-level sequence-to-sequence transduction and establishes a first neural benchmark on SandhiLex. The strongest model, a bidirectional LSTM encoder with a unidirectional LSTM decoder, reaches 68.40% exact match and 82.08% character-level accuracy on the hard subset, and 94.00% exact match accuracy on the full affixational subset. The results show that bidirectional context, native Sinhala Unicode, and sufficient training data are central to performance. Future work should expand the hard subset, evaluate by Sandhi type, add attention or constrained decoding, and measure downstream gains in controlled NLP tasks.

Limitations

The hard subset contains only about 4,500 pairs, limiting the model's ability to learn rare lexicalized and etymological Sandhi patterns (Liyanage and Pushpananda, 2024). In addition, lexicalized, derivational, and etymological Sandhi are grouped into a single hard category, preventing separate analysis across linguistically distinct Sandhi types.

The encoder-decoder model also lacks attention mechanisms and relies on greedy decoding during inference. Techniques such as beam search and Sandhi-type conditioned decoding, which have shown promise in related tasks (Dave et al., 2020), remain future work. Furthermore, evaluation is fully automatic and based on a single reference split, despite the possibility of multiple linguistically valid Sandhi analyses, meaning expert linguistic review would be necessary to better assess prediction quality and practical translation impact.

References

Rahul Aralikatte, Naveen Panwar, and Senthil Mani. 2018. Sanskrit sandhi splitting using seq2(seq) 2 seq2(seq) 2 seq2(seq) 2. Technical report.

Priyanka Dasari, Nagaraju Vuppala, Mupparapu Sohan Gupta, Pruthwik Mishra, and Parameswari Krishnamurthy. 2025. Sandhi splitting in tamil and telugu: A sequence-to-sequence approach leveraging transformer models. Technical report.

Sushant Dave, Arun Kumar Singh, Prathosh A. P., and Brejesh Lall. 2020. Neural compound-word (sandhi) generation and splitting in sanskrit language.

Nisansa de Silva. 2019. Survey on publicly available sinhala natural language processing tools and research. *arXiv preprint arXiv:1906.02358*.

V. V. Devadath, Litton J. Kurisinkel, Dipti Misra Sharma, and Vasudeva Varma. 2014. A sandhi splitter for malayalam. In *Proceedings of the NLP Association of India Conference*. NLPAI.

Yasas Ekanayaka, Randil Pushpananda, Viraj Welgama, and Chamila Liyanage. 2023. Applying deep learning for morphological analysis in the sinhala language. *International Journal on Advances in ICT for Emerging Regions (ICTer)*, 16:2–10.

Samarjit Ghosh, Souvik Mukherjee, Debojyoti Roy, Sumit Sarkar, and Debranjan Sarkar. 2022. Bangla language processing: Sandhi. In *Proceedings - 3rd IEEE India Council International Subsections Conference: Impactful Innovations for Benefits of Society and Industry, INDISCON 2022*. Institute of Electrical and Electronics Engineers Inc.

Oliver Hellwig and Sebastian Nehrdich. 2018. Sanskrit word segmentation using character-level recurrent and convolutional neural networks. Technical report.

Karthika N J, Krishnakant Bhatt, Ganesh Ramakrishnan, and Preethi Jyothi. 2025. Levos: Leveraging vocabulary overlap with sanskrit to generate technical lexicons in indian languages.

Shanta Kallur and Basavaraj S Anami. 2025. A word-splitting approach to kannada sanskrit sandhi words useful in effective english translation. Technical report.

Chamila Liyanage and Randil Pushpananda. 2024. Developing a sandhi lexicon (sandhilex) for sinhala: Understanding and formalizing morphophonology of sinhala language. Technical report.

B. Premjith, K. P. Soman, and M. Anand Kumar. 2018. A deep learning approach for malayalam morphological analysis at character level. In *Procedia Computer Science*, volume 132, pages 47–54. Elsevier B.V.

Mary Priya and Santhosh Kumar. 2020. Machine learning approach to suffix separation on a sandhi rule annotated malayalam data set. *South Asia Research*, 40:231–249.

Rajith Priyanga, Surangika Ranatunga, and Gihan Dias. 2017. A sinhala word joiner. Technical report.

Sreedeepa, Alok Nath M, Ajay K Mani, Arun Kumar C, and Sumam Mary Idicula. 2024. Review on sanskrit sandhi splitting using deep learning techniques. *Journal of Information Technology and Digital World*, 6:136–152.