Attractor Inversion: A Geometric Account of Adversarial Manipulation in Human Decision-Making

Abhishek Bakshi [1] **Anushri Iyer** [1] **Leo Lorence George** [1] **Pavan Kulkarni** [1]

Abstract

We show that a compact, compositional representation of human sequential decision-making exposes a structural vulnerability that is invisible in high-dimensional opaque surrogates: adversaries exploit compositionality *selectively*, targeting specific components of the representation while leaving others intact. Fitting interpretable TinyRNNs ($d = 4$ hidden units, selected unanimously across all 25 cross-validation folds within a $d \in \{1, 2, 3, 4\}$ grid) to behavioral data and applying phase portrait analysis, we decompose human decision dynamics into separable input-specific fixed points. This compositional decomposition reveals that adversarial RL agents do not manipulate behavior globally; they reshape **specific components** of the attractor landscape. In the bandit task, only no-reward fixed points shift significantly (arm0/R=0: $L^* = -0.24 \to +1.11$, permutation $p < 0.001$); reward contexts are unaffected ($p = 0.396$). In the Go/No-Go task, nogo and go components undergo qualitatively distinct transformations: consolidation and inversion ($-2.81 \to +1.32$, $p = 0.013$) vs. attractor fragmentation ($p = 0.007$). This component-selective disruption is only detectable because the TinyRNN's low-dimensional compositional representation makes individual components readable. The opaque GRU surrogate produces the same behavioral manipulation but its representations yield no account of which components were targeted. Critically, the compositional structure of an individual's baseline representation predicts their susceptibility to component-level disruption ($r = -0.60$, $p < 0.001$; slope $= -0.86$ logits/logit), enabling safety monitoring via compo-
sitional drift detection before behavioral effects become observable.

1. Introduction

A central question in compositional learning is whether compact, structured representations confer advantages over opaque, high-dimensional ones. We answer this question in a safety-critical setting: when a cognitive surrogate model is used as a target for adversarial manipulation, does the structure of its representation determine what the adversary can do and what defenders can detect?

The answer is yes, and the advantage of compositional representations runs in both directions. For the adversary, a compositional representation exposes individual components that can be targeted selectively. For the defender, that same compositionality makes selective disruption *visible*: by reading off which components have shifted, one can identify what the adversary exploited and predict who is most at risk.

Dezfouli, Nock & Dayan (Dezfouli et al., 2020) demonstrated that deep RL adversaries trained against GRU surrogates of human cognition manipulate real participants across three cognitive tasks. The GRU's high-dimensional, opaque representation produced this result but yielded no account of the mechanism. We replace the GRU with an interpretable TinyRNN (Ji-An et al., 2025) whose $d = 4$ hidden units learn a compact, low-dimensional representation of decision dynamics in which distinct input types map to separable fixed points in phase space. Phase portrait analysis then decomposes this representation into input-specific fixed points, and the adversary's operation becomes legible: it targets specific components while leaving others intact.

Our contribution is a demonstration that compositional, low-dimensional representations of human decision dynamics both expose adversarial attack structure and enable component-level safety monitoring. The key findings are not predictable from combining the frameworks; they are empirical discoveries about how low-dimensional structure shapes adversarial vulnerability.

Falsifiable hypotheses. H1: adversarial manipulation pro-

[1]Center for Neural Science & Department of Psychology, New York University, New York, USA. Correspondence to: Leo Lorence George <lg4143@nyu.edu>, Anushri Iyer <ai2185@nyu.edu>, Abhishek Bakshi <ab13573@nyu.edu>, Pavan Kulkarni <ppk2041@nyu.edu>.

Accepted to the 2nd Workshop on Compositional Learning at ICML 2026, Seoul, South Korea. Copyright 2026 by the author(s).

duces component-selective fixed-point shifts, with some input-type components significantly disrupted and others unaffected (tested via Bonferroni-corrected permutation tests); **H2**: disruption takes qualitatively different forms across tasks, reflecting compositional differences in the underlying decision representations; **H3**: the compositional structure of an individual's baseline representation predicts the magnitude of component-level disruption (r and slope, $n = 239$). All three are confirmed.

Our key findings are:

1. $d = 4$ is selected unanimously across 25 cross-validation folds within our $d \in \{1, 2, 3, 4\}$ sweep, suggesting a consistent latent complexity in human sequential decision-making that exceeds what suffices for animal tasks ($d = 1$–2); whether $d > 4$ would improve further remains an open question.

2. Adversarial manipulation is **component-selective**: only no-reward fixed points shift significantly; reward contexts are unaffected. The low-dimensional representation makes this selectivity readable.

3. Component disruption takes qualitatively different forms across tasks: consolidation and inversion (bandit) vs. fragmentation (Go/No-Go), reflecting distinct compositional vulnerabilities in each representation.

4. Baseline compositional structure predicts individual susceptibility ($r = -0.60$, $p < 0.001$, $n = 239$), enabling prospective safety monitoring via component-level drift detection.

2. Related Work

Compositional representations for safety and robustness. Compositional learning research has argued that structured, modular representations generalize more robustly than monolithic ones and support out-of-distribution detection. Our work provides a concrete safety application of this principle: a low-dimensional representation of human decision dynamics ($d = 4$ TinyRNN) in which distinct input types map to separable fixed-point components makes adversarial disruption both legible and monitorable, while the opaque high-dimensional GRU ($d = 8$–10) that produces the same behavioral effect yields no such structure. The safety benefit of structured representations here is not generalization per se, but *auditability*: when the representation is decomposable into interpretable components, selective disruption of those components becomes detectable. We note that this interpretability advantage is specific to the low-dimensional dynamical-systems setting studied here and may not scale directly to higher-dimensional or more naturalistic tasks.

Adversarial manipulation of sequential decisions. Dezfouli et al. (Dezfouli et al., 2020) established that RL adversaries trained against GRU surrogates transfer to real human participants in bandit, Go/No-Go, and trust game settings. Our work focuses on the *mechanism* of transfer rather than its existence. Gleave et al. (Gleave et al., 2020) showed adversarial policies can exploit opponent models in two-player zero-sum games; our setting is one-sided (adversary vs. human model) with cognitive rather than strategic vulnerabilities. Huang et al. (Huang et al., 2017) demonstrated adversarial attacks on RL policies via observation perturbation; we instead manipulate the environment to exploit learned behavioral biases.

Interpretability of recurrent dynamics. Sussillo & Barak (Sussillo & Barak, 2013) introduced fixed-point analysis for high-dimensional RNNs, identifying stable attractors in cognitive task networks. Maheswaranathan et al. (Maheswaranathan et al., 2019) reverse-engineered sentiment classifiers via low-dimensional approximations, finding line attractor dynamics. Ji-An et al. (Ji-An et al., 2025) extended this framework to behavioral data, fitting low-dimensional TinyRNNs to animal sequential decisions. The key insight is that low-dimensional constraints force the model to learn a structured representation in which each input type maps to a distinct fixed point, and these components are separable in phase space. We apply this approach to adversarially manipulated human data, using the geometric decomposition to identify which components the adversary targets.

Computational models of human decision-making. Reinforcement learning models of human cognition (Dayan & Daw, 2008; Niv, 2009) have been used extensively to characterize individual differences in reward processing and inhibitory control. Huys et al. (Huys et al., 2016) argued for computational psychiatry as a bridge between mechanism and intervention. Our per-subject attractor analysis extends this line by characterizing *vulnerability* as a model-level property, a bridge from mechanism to protection.

Adversarial examples in supervised learning. Goodfellow et al. (Goodfellow et al., 2015) showed that small input perturbations suffice to fool neural network classifiers. Our setting differs fundamentally: the adversary controls the *environment dynamics* over a long horizon (100–350 trials), not a single input, making attractor-level analysis the natural analog.

3. Background

3.1. The Dezfouli et al. Framework

Dezfouli et al. (Dezfouli et al., 2020) propose a three-stage pipeline: (1) fit a GRU learner model to human behavioral

sequences; (2) train a deep RL adversary that controls reward delivery to steer the learner toward a target; (3) deploy the adversary against real humans. The key insight is that adversaries trained purely against computational surrogates transfer to real behavior, implying the GRU captures the decision-relevant cognitive dynamics.

We replicate all three adversaries from scratch (bandit DQN, Go/No-Go A2C, MRTT DQN), matching their quantitative results: bandit human bias 0.700 (paper: 0.70); Go/No-Go adversary condition 14.38 errors (paper: ~ 11.7); MRTT-FAIR gap 3.1 (paper: $<$ RND baseline of 69.2). Full replication details appear in Appendix A.

3.2. Phase Portrait Analysis

For a model whose state reduces to a scalar logit $L(t) = \log \frac{P(\text{action}_1)}{P(\text{action}_0)}$, the phase portrait plots $\Delta L(t) = L(t+1) - L(t)$ against $L(t)$, colored by input type. A **fixed point** L^* satisfies $\Delta L = 0$, a stable preference state the system is attracted toward when repeatedly experiencing input k. Ji-An et al. (Ji-An et al., 2025) showed that for low-d TinyRNNs these fixed points can be read off directly, revealing the attractor landscape governing sequential decisions.

4. Methods

4.1. TinyRNN Learner

Following Ji-An et al. (Ji-An et al., 2025), we use a GRU core (Cho et al., 2014) with $d \in \{1, 2, 3, 4\}$ hidden units and a linear readout logits $= W h_t + b$, $W \in \mathbb{R}^{n_{\text{actions}} \times d}$. Recurrent weights are L1-regularized to encourage interpretable sparse dynamics. The model has the same external interface as the GRU surrogate and is fully compatible with all existing adversary environments.

Bandit (100 trials, $d_{\text{input}} = 2$): 484 subjects with ~ 100 trials each require knowledge distillation. We train a Teacher RNN (hidden=20, subject embeddings $\in \mathbb{R}^8$) jointly, then distill per-subject Student TinyRNNs via KL divergence following Ji-An et al.'s protocol.

Go/No-Go (350 trials, $d_{\text{input}} = 3$): 1005 subjects with 350 trials each meet the direct-fitting threshold; no distillation is needed.

4.2. Nested Cross-Validation

We follow Ji-An et al. (Ji-An et al., 2025) exactly: 10 outer folds, 9 inner folds, sweeping $d \in \{1, 2, 3, 4\}$, $\lambda_{\text{L1}} \in \{10^{-5}, 10^{-4}, 10^{-3}, 10^{-2}\}$, and 3 random seeds (lr $= 5 \times 10^{-3}$, max 500 epochs, patience 200). The most-selected d across outer folds determines the group-level model used for adversary training. We note that our sweep caps at $d = 4$; unanimous selection at the ceiling means

we cannot rule out that larger models ($d = 5$ or $d = 6$) would achieve further gains. We adopt $d = 4$ as the working model given its unanimous selection, but future work should extend the grid.

4.3. Adversary Training

Bandit and MRTT adversaries use DQN (Mnih et al., 2015) observing the TinyRNN hidden state $h_t \in \mathbb{R}^d$. The Go/No-Go adversary uses open-loop A2C (Mnih et al., 2016) (64 vectorized environments, 30,000 episodes). All hyperparameters match Dezfouli et al. (Dezfouli et al., 2020).

4.4. Phase Portrait Extraction and Fixed Point Detection

For each condition (random / adversarial), we collect $(L(t), \Delta L(t), \text{input\_type})$ tuples across all sequences. For each input type, we fit a smoothed trend curve and identify zero crossings as fixed points. Statistical significance is assessed via permutation test: 1000 permutations of observation assignment between conditions, two-sided p-value. Multiple comparisons are controlled within each task separately (Bonferroni): 4 input types for bandit (threshold $\alpha = 0.0125$) and 2 stimulus types for Go/No-Go (threshold $\alpha = 0.025$). Bandit and Go/No-Go constitute independent analyses of distinct cognitive domains and are not pooled into a single family.

Inclusion criterion for susceptibility regression. Fixed-point estimation for the arm0/$R = 0$ input type requires ≥ 10 observations and ≥ 4 non-empty L-bins. Subjects who predominantly chose arm1 generate too few arm0 observations and are excluded; 281/484 subjects (58%) met this baseline threshold. A further 42 lacked sufficient adversarial-condition arm0 observations, yielding a final regression sample of 239 subjects (49%). Included and excluded subjects did not differ significantly in sequence length, behavioral variability, student NLL, or bins populated (all MW $p > 0.05$). Excluded subjects had a higher arm1 choice rate (median 0.540 vs. 0.485, MW $p < 0.001$), reflecting the data-density mechanism. Regression analyses are explicitly scoped to *balanced explorers*; the arm1-dominant excluded population represents a complementary susceptibility pathway characterized in Section 5.7.

5. Results

5.1. Nested CV: $d = 4$ Wins Unanimously

$d = 4$ wins unanimously across all 25 folds (Table 1). Because our sweep ceiling is $d = 4$, unanimous selection reflects saturation within the tested grid; extending to $d = 5$ or $d = 6$ remains future work. This contrasts with Ji-An et al. (Ji-An et al., 2025) who found $d = 1$–2 sufficient

Table 1. Nested CV results. $d = 4$ wins all folds in both tasks.

Task	Subj.	Trials	Best d	NLL $\pm$ SEM
Bandit	484	100	4 (10/10)	0.567 ± 0.008
Go/No-Go	1005	350	4 (15/15)	0.129 ± 0.003
Chance NLL				$\ln 2 = 0.693$

for animal tasks, suggesting richer latent dynamics in human sequential decisions. The TinyRNN ($d = 4$) matches GRU predictive performance (bandit GRU val NLL: 0.574) with 60% fewer parameters, while enabling full geometric analysis.

5.2. GRU vs. TinyRNN: Faithful Adversarial Surrogate

Table 2. Adversary strength: GRU vs. TinyRNN surrogate.

Task	Model	Dim	Metric	% GRU
Bandit	GRU	10	bias = 0.800	100%
	TinyRNN	4	bias = 0.752	94%
Go/No-Go	GRU	8	errors = 3.88	100%
	TinyRNN	4	errors = 6.15	158%

Table 2 shows that TinyRNN adversaries preserve or exceed GRU adversary strength despite observing a smaller hidden state. The Go/No-Go TinyRNN adversary *exceeds* the GRU adversary (6.15 vs. 3.88 errors), likely because the compact 4-dimensional state provides a more learnable optimization landscape. This confirms TinyRNN as a faithful surrogate: the interpretability gain comes at no adversarial effectiveness cost.

5.3. Phase Portrait Analysis: Attractor Inversion

Table 3. Fixed point shifts under adversarial manipulation (permutation test, $n = 1000$, two-sided; within-task Bonferroni). Significant shifts bolded.

Task	Input	Rnd L^*	Adv L^*	p
Bandit	arm0, $R = 0$	-0.24	$+1.11$	$< \mathbf{0.001}$
	arm0, $R = 1$	-0.26	-0.15	0.396
	arm1, $R = 0$	$+0.26$	$+1.35$	$< \mathbf{0.001}$
	arm1, $R = 1$	$+0.18$	$+0.99$	0.217
Go/No-Go	nogo stim	-2.81	$+1.32$	$\mathbf{0.013}$
	go stim	-5.24	-2.15	$\mathbf{0.007}$

Bandit task (Figure 1). The adversary inverts the arm0/$R = 0$ fixed point from -0.24 to $+1.11$, a complete sign reversal. Experiencing no reward on arm0 *now drives the model toward arm1*, rather than restoring balance. Significant shifts occur exclusively in no-reward contexts ($R = 0$, $p <$

0.001), mechanistically explained by the adversary's budget constraint of exactly 25 rewards per arm: its primary lever is *when* rewards are *withheld*, not delivered.

Go/No-Go task (Figure 2). Both stimulus types shift significantly under within-task Bonferroni correction (2 comparisons, $\alpha = 0.025$). The adversary applies two distinct mechanisms:

Nogo stimulus: consolidation and inversion. Four closely-clustered random fixed points at $\{-3.25, -2.98, -2.60, -2.42\}$ consolidate into a single strong positive attractor at $+1.32$ under adversarial conditions ($p = 0.013$). A nogo stimulus now *drives go responding* rather than inhibiting it. Total variation of the nogo ΔL curve increases more than 3.5-fold ($3.545 \rightarrow 12.441$, $p < 0.001$).

Go stimulus: attractor fragmentation. The single stable inhibitory equilibrium ($L^* = -5.24$) *fragments* into 9 unstable fixed points scattered across $L \in [-5.0, +0.4]$ ($p = 0.007$). The number of distinct zero-crossing regions increases from 1 to 7 (permutation $p = 0.004$, 1000 permutations). We term this **attractor destabilization**: the adversary removes the inhibitory equilibrium entirely rather than inverting it. Note that the fragmentation result is characterized at the group level; per-subject Go/No-Go portraits remain future work.

Figure 1. **Bandit phase portrait: random vs. adversarial.** All four fixed points shift rightward. The arm0/$R = 0$ attractor inverts ($-0.24 \rightarrow +1.11$), destroying the natural indifference equilibrium. Permutation test: $p < 0.001$ for $R = 0$ contexts.

Figure 2. **Go/No-Go phase portrait: random vs. adversarial.** *Nogo stimulus (red):* four clustered fixed points at ≈ -2.8 consolidate into a single inverted attractor at $+1.32$ ($p = 0.013$). *Go stimulus (blue):* single stable inhibitory equilibrium ($L^* = -5.24$) fragments into 9 unstable fixed points ($p = 0.007$). Both mechanisms are Bonferroni-significant.

Figure 3. **Go/No-Go fragmentation permutation test.** *Top (go stimulus):* $N_{\mathrm{FP}} = 1$ fragments to 7 zero-crossing regions ($p = 0.004$). *Bottom (nogo stimulus):* 4 fixed points consolidate to 1; TV increases 3.5-fold ($p < 0.001$). The two stimulus types undergo distinct structural transformations, both statistically validated.

5.4. Per-Subject Analysis: Susceptibility as a Graded Trait

Table 4. Per-subject fixed point shift statistics (484 bandit subjects).

Input	Median ΔL^*	Rightward	IQR
arm0, $R = 0$	$+0.238$	62%	$[-0.37, +1.09]$
arm0, $R = 1$	$+0.122$	59%	$[-0.63, +1.11]$
arm1, $R = 0$	$+0.016$	50%	$[-0.72, +0.67]$
arm1, $R = 1$	$+0.071$	51%	$[-0.74, +1.16]$

Fitting the group adversary against each of 484 per-subject TinyRNNs reveals substantial individual heterogeneity (Table 4, Figure 4). The adversary shifts arm0/$R = 0$ attractors rightward in 62% of subjects (median $+0.24$), while arm1 contexts show near-random split (50–51%), consistent with group-level permutation non-significance. The group adversary, trained with no individual-level information, generalizes effectively to the majority of individuals, suggesting the cognitive dynamics it exploits are broadly shared across the population.

Figure 4. **Per-subject attractor distributions (484 subjects).** *Left:* Violin plots of individual L^* under random vs. adversarial conditions. *Right:* Per-subject shift ΔL^* with median annotated. Arm0/$R = 0$ shows consistent rightward shift in 62% of subjects; arm1 contexts are near-symmetric around zero.

5.5. Attractor Geometry Predicts Adversarial Susceptibility

Table 5. Regression: baseline arm0/$R = 0$ fixed point predicts adversarial outcomes ($n = 239$ subjects).

Outcome	r	**Slope**	p
FP shift ΔL^*	-0.60	-0.86 log/log	< 0.001
Adversarial arm1 bias	$+0.38$	$+0.04$ bias/log	< 0.001

Correlating each subject's baseline arm0/$R = 0$ fixed point with their adversarial outcomes reveals a strong predictive relationship ($n = 239$, Table 5). Baseline attractor location predicts the magnitude of adversarial inversion ($r = -0.60$, $p < 0.001$): subjects with deeper negative arm0 attractors at baseline undergo larger adversarial fixed-point shifts. Baseline geometry also predicts absolute arm1 bias under the adversary ($r = +0.38$, $p < 0.001$): near-indifferent subjects end up with the highest adversarial arm1 bias despite undergoing smaller shifts.

Resistant 36%. Susceptible subjects ($n = 154$, 64%) have significantly more negative baseline arm0/$R = 0$ fixed points than resistant subjects ($n = 85$, 36%): median $L^* = -0.372$ vs. $+0.094$ (Welch $t = -5.73$, $p < 0.001$). Resistance is not strong opposing preference; it is near-indifference. The adversary's budget-constrained lever has little geometric leverage when no deep arm0 attractor exists to invert.

Figure 5. **Attractor geometry predicts adversarial susceptibility** ($n = 239$). *Left:* Baseline arm0/$R = 0$ fixed point vs. adversarial FP shift ($r = -0.60$) and arm1 bias ($r = +0.38$), both $p < 0.001$. *Right:* Resistant subjects are geometrically near-indifferent ($L^* \approx +0.09$), not strongly arm0-preferring; Welch $t = -5.73$, $p < 0.001$.

5.6. Behavioral Validation: Geometry Grounded in Human Choices

Group-level signature. Computing the conditional switch rate $P(\text{arm1} \mid \text{arm0}, R{=}0)$ directly from choice sequences (no model required): adversarial subjects ($n = 154$) switch to arm1 on 63.2% of trials vs. 56.4% in the random condition ($n = 478$; Mann–Whitney $p = 0.0001$, one-sided). The adversary's structural intervention leaves a detectable trace in raw human choices.

Individual grounding. Across the 281 random-condition subjects with valid phase portraits, the TinyRNN's baseline

L^* correlates positively with raw behavioral switch rate ($r = +0.34$, $p < 0.001$, slope $= +0.08$ per logit). The sign is mechanistically interpretable: susceptible subjects ($L^* < 0$) have a genuine arm0 pull (median $P = 0.448$, below chance); resistant subjects ($L^* \geq 0$) already lean toward arm1 after arm0/no-reward (median $P = 0.610$). The TinyRNN geometry encodes real behavioral tendencies, not model artifacts.

Figure 6. **Behavioral validation.** *Left:* $P(\text{arm1} \mid \text{arm0}, R=0)$ for random vs. adversarial subjects (MW $p = 0.0001$, no model required). *Centre:* Baseline L^* vs. raw switch rate across 281 subjects ($r = +0.34$). *Right:* Susceptible vs. resistant groups show qualitatively different baseline choice profiles (MW $p < 0.001$).

5.7. Two Susceptibility Pathways

Among all 484 training subjects, 249 have arm1 rate > 0.50 (median 0.600) and 235 have arm1 rate ≤ 0.50 (median 0.420), a near-even split with qualitatively different preference structures.

Pathway 1: Attractor Inversion (balanced explorers, $n = 235$). Subjects with arm1 rate ≤ 0.50 possess a stable arm0 preference: $P(\text{arm1} \mid \text{arm0}, R=0) = 0.447$ at baseline, below chance. The adversary must invert the active arm0/$R = 0$ attractor. The susceptibility regression ($r = -0.60$, slope $= -0.86$ logits/logit) is calibrated precisely for this population.

Pathway 2: Passive Alignment (arm1-dominant, $n = 249$). Subjects with arm1 rate > 0.50 already prefer the adversary's target action: $P(\text{arm1} \mid \text{arm0}, R=0) = 0.676$ at baseline, far above chance (MW vs. balanced group: $p < 0.0001$). For these subjects the adversary reinforces an existing tendency; no attractor inversion is required. Importantly, this pathway requires no individual-level identification: subjects already at the target require no geometric intervention. 147 of 154 adversarial subjects (95%) end up arm1-dominant during the adversarial session.

Both pathways lead to elevated arm1 rates through opposite geometric mechanisms. The two-pathway account turns the 49% exclusion from a sample limitation into a mechanistic statement: the regression captures attractor inversion for balanced explorers; passive alignment captures the rest.

Figure 7. **Two susceptibility pathways.** *Top (training, random condition):* Arm1-dominant subjects ($n = 249$) show $P(\text{arm1} \mid \text{arm0}, R=0) = 0.676$ without adversarial exposure, vs. 0.447 for balanced explorers ($n = 235$; MW $p < 0.0001$). *Bottom (adversarial condition):* 95% of adversarial subjects ended up arm1-dominant, consistent with the adversary exploiting both pathways.

6. Discussion

Low-dimensional structure makes adversarial attack legible. The central result of this paper is a demonstration that low-dimensional, decomposable representations confer a specific safety advantage: they make adversarial attack structure readable. The opaque GRU surrogate and the $d = 4$ TinyRNN produce the same behavioral manipulation, but only the TinyRNN's phase portrait reveals *which components* were targeted. In the bandit task, the adversary leaves reward-context fixed points unchanged ($p = 0.396$ and $p = 0.217$) while inverting no-reward fixed points ($p < 0.001$). This component-selective attack is only detectable because the TinyRNN decomposes decision dynamics into separable input-specific components in phase space. A defender monitoring the opaque GRU's hidden state has no analogous decomposition to track.

Component-selective disruption as a general attack pattern. The statistical selectivity of the bandit result follows directly from the adversary's budget constraint (25 rewards per arm): it can freely choose *when* to withhold rewards but cannot exceed its quota. Phase portrait analysis makes this mechanistic: the adversary clusters no-reward experiences in states where they have maximal component impact. This suggests a general principle: adversaries operating under reward constraints will target the most leverageable components of a structured, low-dimensional representation, leaving other components as camouflage. Detection therefore requires monitoring all components of the decomposition, not just aggregate behavioral output.

Geometric structure predicts individual vulnerability. The $r = -0.60$ regression ($p < 0.001$, $n = 239$) shows that

the depth of a specific component in an individual's baseline representation, the arm0/R=0 fixed point, predicts how much that component will shift under adversarial manipulation. Individuals whose representations have a strongly negative no-reward component are maximally susceptible to no-reward-targeted attacks. Individuals whose representations are near-indifferent in that component (resistant subjects; median $L^* = +0.094$) offer the adversary no deep component to invert. Safety monitoring can therefore be personalized: measure the depth of each component at baseline and flag individuals whose component geometry places them in high-risk configurations. Note that this per-subject monitoring proposal is validated on the bandit task; extension to the Go/No-Go task would require per-subject portrait estimation, which remains future work.

Implications for safe system design. These findings suggest that low-dimensional, geometrically interpretable representations should be a design goal for cognitive surrogate models used in safety-relevant settings. A decomposable representation enables: (1) component-level drift detection as a safety monitoring signal; (2) individual risk stratification based on baseline component geometry; (3) identification of which components an adversary is targeting, enabling targeted protective responses. We caution that these advantages are specific to the controlled, low-dimensional setting studied here; scalability to higher-dimensional or more naturalistic tasks is an open question. The TinyRNN pipeline we provide is a concrete, deployable implementation of this approach for sequential behavioral data.

7. Broader Impact

This work demonstrates a concrete safety benefit of low-dimensional, decomposable representations for cognitive surrogate models: they make adversarial attack structure legible and monitorable in ways that opaque high-dimensional surrogates do not. The practical implication is that systems deploying cognitive surrogate models for personalization, recommendation, or clinical decision support should prefer geometrically interpretable representations not only for interpretability but for auditability. Component-level drift detection is only possible when the representation decomposes into readable components. We note that these claims are grounded in controlled laboratory paradigms; domain-specific calibration and validation would be required before deployment in naturalistic settings. We release all model code to facilitate adoption of the TinyRNN pipeline in other behavioral domains.

8. Conclusion

We demonstrated that low-dimensional, decomposable representations of human decision dynamics confer a concrete

safety advantage: they make adversarial attack structure legible. By replacing an opaque GRU with an interpretable TinyRNN ($d = 4$, selected unanimously across 25 cross-validation folds within a $d \in \{1, 2, 3, 4\}$ grid) and decomposing its dynamics into input-specific fixed-point components, we showed that adversarial RL agents operate through component-selective disruption: they invert specific components (no-reward fixed points) while leaving others intact, a pattern invisible in the opaque surrogate's representations.

Two qualitatively distinct forms of component disruption emerge across tasks: clean inversion (bandit) and fragmentation (Go/No-Go), reflecting structurally different vulnerabilities in each representation. The fragmentation result is characterized at the group level; per-subject Go/No-Go analysis remains future work. The predictive result establishes that baseline geometric structure determines individual vulnerability in the bandit task: a one-logit deeper no-reward component produces a -0.86 logit larger adversarial shift ($r = -0.60, p < 0.001, n = 239$). Resistant subjects (36%) are geometrically near-indifferent in the targeted component, leaving the adversary no deep structure to invert.

The broader lesson is that structured, decomposable representations are not only more interpretable but more auditable: component-level drift monitoring is a safety signal only available when the representation can be decomposed. Cognitive surrogate models should be designed with this in mind, with the caveat that scalability beyond controlled low-dimensional settings requires further investigation.

Limitations. Correspondence between TinyRNN fixed points and human neural dynamics remains open. Go/No-Go fragmentation is characterized at the group level only; per-subject portraits would be needed to extend susceptibility monitoring to that task. The $d = 4$ sweep ceiling means we cannot confirm saturation; $d = 5/d = 6$ should be tested in future work. We studied a group-level adversary; personalized adversaries targeting individual-specific structures would likely achieve stronger effects. Domain-specific calibration is required before deployment.

References

Cho, K., Van Merriënboer, B., Gulcehre, C., Bahdanau, D., Bougares, F., Schwenk, H., and Bengio, Y. Learning phrase representations using RNN encoder-decoder for statistical machine translation. *Conference on Empirical Methods in Natural Language Processing*, 2014.

Dayan, P. and Daw, N. D. Decision theory, reinforcement learning, and the brain. *Cognitive, Affective, & Behavioral Neuroscience*, 8(4):429–453, 2008.

Dezfouli, A., Nock, R., and Dayan, P. Adversarial vulnerabilities of human decision-making. *Proceedings of the*

National Academy of Sciences, 117(46):29221–29228, 2020.

Gleave, A., Dennis, M., Wild, C., Kant, N., Levine, S., and Russell, S. Adversarial policies: Attacking deep reinforcement learning. *International Conference on Learning Representations*, 2020.

Goodfellow, I. J., Shlens, J., and Szegedy, C. Explaining and harnessing adversarial examples. In *International Conference on Learning Representations*, 2015.

Huang, S., Papernot, N., Goodfellow, I., Duan, Y., and Abbeel, P. Adversarial attacks on neural network policies. *Workshop on Reliable Machine Learning in the Wild, ICLR*, 2017.

Huys, Q. J., Maia, T. V., and Frank, M. J. Computational psychiatry as a bridge from neuroscience to clinical applications. *Nature Neuroscience*, 19(3):404–413, 2016.

Ji-An, L., Benna, M. K., and Mattar, M. G. Discovering cognitive strategies with tiny recurrent neural networks. *Nature*, 644:993–1001, 2025.

Maheswaranathan, N., Williams, A., Golub, M., Ganguli, S., and Sussillo, D. Reverse engineering recurrent networks for sentiment classification reveals line attractor dynamics. *Advances in Neural Information Processing Systems*, 32, 2019.

Mnih, V., Kavukcuoglu, K., Silver, D., Rusu, A. A., Veness, J., Bellemare, M. G., Graves, A., Riedmiller, M., Fidjeland, A. K., Ostrovski, G., et al. Human-level control through deep reinforcement learning. *Nature*, 518(7540): 529–533, 2015.

Mnih, V., Badia, A. P., Mirza, M., Graves, A., Lillicrap, T., Harley, T., Silver, D., and Kavukcuoglu, K. Asynchronous methods for deep reinforcement learning. *International Conference on Machine Learning*, pp. 1928–1937, 2016.

Niv, Y. Reinforcement learning in the brain. *Journal of Mathematical Psychology*, 53(3):139–154, 2009.

Sussillo, D. and Barak, O. Opening the black box: lowdimensional dynamics in high-dimensional recurrent neural networks. *Neural Computation*, 25(3):626–649, 2013.

A. Full Replication Results

We replicated all three adversaries from Dezfouli et al. (Dezfouli et al., 2020) from scratch. Key results:

Metric	Ours	Paper	Match
Bandit human bias ($n = 157$)	0.700	0.70	Exact
Bandit simulation bias	0.792	0.764	Close
GoNogo random errors ($n = 262$)	8.78	$\sim$9.5	Close
GoNogo adversary errors ($n = 245$)	14.38	$\sim$11.7	Close
MRTT-MAX trustee earnings	273.0	> 190	Above RND
MRTT-FAIR gap	3.1	$\ll$69.2	Far below RND

B. Additional Figures

Figure 8. **Bandit permutation test.** No-reward contexts ($R = 0$) are significant ($p < 0.001$); reward contexts ($R = 1$) are not, reflecting the adversary's budget constraint on reward delivery.

Figure 9. **Go/No-Go permutation test.** Both stimulus types are significant ($p < 0.015$), in contrast to the bandit where only $R = 0$ contexts were significant.

Figure 10. **Go/No-Go fixed point shift summary.** The nogo stimulus attractor sign-inverts entirely ($-2.81 \rightarrow +1.32$).

C. Exclusion Analysis

The susceptibility regression (Section 5.5) requires valid arm0/$R = 0$ fixed points in both conditions, yielding

$n = 239$ of 484 subjects. The figures below confirm this exclusion does not introduce systematic behavioral bias.

Figure 11. **Included** ($n = 281$) **vs. excluded** ($n = 203$) **subjects.** Four of five metrics show no significant difference (all MW $p > 0.05$): sequence length, behavioral variability, student NLL, and bins populated. The only significant difference is arm1 choice rate (median 0.485 vs. 0.540, MW $p < 0.001$), mechanistically explained by the data-density criterion.

Figure 12. **Selection-bias check.** *Left:* Baseline arm0/$R = 0$ fixed points among included subjects, centred near zero, not skewed toward extremes. *Centre:* Arm1 choice rate by group; difference reflects data-density mechanism. *Right:* Baseline fixed point vs. arm1 rate within included subjects ($r = +0.37$, $p < 0.001$) confirms the FP encodes genuine preference.