DE NOVO MOLECULAR GENERATION VIA CONNECTION-AWARE MOTIF MINING

ABSTRACT

De novo molecular generation is an essential task for science discovery. Recently, fragment-based deep generative models have attracted much research attention due to their flexibility in generating novel molecules based on existing molecule fragments. However, the *motif vocabulary*, i.e., the collection of frequent fragments, is usually built upon heuristic rules, which brings difficulties to capturing common substructures from large amounts of molecules. In this work, we propose a new method, MiCaM, to generate molecules based on mined connection-aware motifs. Specifically, it leverages a data-driven algorithm to automatically discover motifs from a molecule library by iteratively merging subgraphs based on their frequency. The obtained motif vocabulary consists of not only molecular motifs (i.e., the frequent fragments), but also their connection information, indicating how the motifs are connected with each other. Based on the mined connection-aware motifs, MiCaM builds a connection-aware generator, which simultaneously picks up motifs and determines how they are connected. We test our method on distribution-learning benchmarks (i.e., generating novel molecules to resemble the distribution of a given training set) and goal-directed benchmarks (i.e., generating molecules with target properties), and achieve significant improvements over previous fragment-based baselines. Furthermore, we demonstrate that our method can effectively mine domain-specific motifs for different tasks.

1 INTRODUCTION

Drug discovery, from designing hit compounds to developing an approved product, often takes more that ten years and billions of dollars (Hughes et al., 2011). *De novo* molecular generation is a fundamental task in drug discovery, as it provides novel drug candidates and determines the underlying quality of final products. Recently, with the development of artificial intelligence, deep neural networks, especially graph neural networks (GNNs), have been widely used to accelerate novel molecular generation (Stokes et al., 2020; Bilodeau et al., 2022). Specifically, we can employ a GNN to generate a molecule iteratively: in each step, given an unfinished molecule $\mathcal{G}_0$, we can first determine a new generation unit $\mathcal{G}_1$ to be added; next determine the connecting sites on $\mathcal{G}_0$ and $\mathcal{G}_1$; and finally determine the attachments (e.g., creating new bonds (Liu et al., 2018) or merging shared atoms (Jin et al., 2018)) between the connecting sites. In different methods, the generation units could be either atoms (Li et al., 2018; Mercado et al., 2021) or frequent fragments (referred to as *motifs*) (Jin et al., 2020; Kong et al., 2021; Maziarz et al., 2021).

For fragment-based models, building an effective motif vocabulary is a key factor to the success of molecular generation (Maziarz et al., 2021). Previous works usually rely on heuristic rules or templates to obtain a motif vocabulary. For example, JT-VAE (Jin et al., 2018) decomposes molecules into pre-defined structures like rings, chemical bonds, and individual atoms, while MoLeR (Maziarz et al., 2021) separates molecules into ring systems and acyclic linkers or functional groups. Several other works build motif vocabularies in a similar manner (Jin et al., 2020; Yang et al., 2021). However, heuristic rules cannot cover some chemical structures that commonly occur yet are a bit more complex than pre-defined structures. For example, the subgraph patterns *benzaldehyde* ("O=Cc1ccccc1") and *trifluoromethylbenzene* ("FC(F)(F)c1ccccc1") (as shown in Figure 1(a)) occur 398,760 times and 57,545 times respectively in the 1.8 million molecules in ChEMBL (Mendez et al., 2019), and both of them are industrially useful. Despite their high frequency in molecules, the aforementioned methods cannot cover such common motifs. Moreover, in different concrete genera-

Figure 1: (a) Two substructures that appear frequently in ChEMBL. (b) Different connection modes of sulfur atoms. The "*-S(-*)(-*)=*" is commonly seen while"*#S#*" does not appear in ChEMBL.

tion tasks, different motifs with some domain-specific structures or patterns are favorable, which can hardly be enumerated by existing rules. Another important factor that affects the generation quality is the connection information of motifs. This is because although many connections are valid under a valence check, the "reasonable" connections are predetermined and reflected by the data distribution, which contribute to the chemical properties of molecules (Yang et al., 2021). For example, a *sulfur* atom with two triple-bonds, i.e., "*#S#*" (see Figure 1(b)), is valid under a valence check but is "unreasonable" from a chemical point of view and does not occur in the ChEMBL.

In this work, we propose **MiCaM**, a generative model based on **Mi**ned **C**onnection-**a**ware **M**otifs. It includes a data-driven algorithm to mine a connection-aware motif vocabulary from a molecule library, as well as a connection-aware generator for *de novo* molecular generation. The algorithm mines the most common substructures based on their frequency of appearance in the molecule library. Briefly, across all molecules in the library, we find the most frequent fragment pairs that are adjacent in graphs, and merge them into an entire fragment. We repeat this process for a pre-defined number of steps and collect the fragments to build a motif vocabulary. We preserve the connection information of the obtained motifs, and thus we call them *connection-aware motifs*.

Based on the mined vocabulary, we design the generator to simultaneously pick up motifs to be added and determine the connection mode of the motifs. In each generation step, we focus on a non-terminal connection site in the current generated molecule, and use it to query another connection either from the motif vocabulary, which implies connecting a new motif, or (2) from the current molecule, which implies cyclizing the current molecule.

We evaluate MiCaM on distribution learning benchmarks from GuacaMol (Brown et al., 2019), which aim to resemble the distributions of given molecular sets. We conduct experiments on three different datasets and MiCaM achieves the best overall performance compared with several strong baselines. After that, we also work on goal directed benchmarks, which aim to generate molecules with specific target properties. We combine MiCaM with iterative target augmentation (Yang et al., 2020) by jointly adapting the motif vocabulary and network parameters. In this way, we achieve state-of-the-art results on four different types of goal-directed tasks, and find motif patterns that are relevant to the target properties.

2 OUR APPROACH

2.1 CONNECTION-AWARE MOLECULAR MOTIF MINING

Our motif mining algorithm aims to find the common molecule motifs from a given training data set $\mathcal{D}$, and build a connection-aware motif vocabulary for the follow-up molecular generation. It processes $\mathcal{D}$ with two phases: the merging-operation learning phase and the motif-vocabulary construction phase. Figure 2 presents an example and more implementation details are in Algorithm 1 of Appendix A.1.

Merging-operation Learning Phase In this phase, we aim to learn the top K most common patterns (which correspond to rules indicating how to merge subgraphs) from the training data $\mathcal{D}$, where K is a hyperparameter. Each molecule in $\mathcal{D}$ is represented as a graph $\mathcal{G}(\mathcal{V}, \mathcal{E})$ (the first row in Figure 2(a)), where the nodes $\mathcal{V}$ and edges $\mathcal{E}$ denote atoms and bonds respectively. For each $\mathcal{G}(\mathcal{V}, \mathcal{E}) \in \mathcal{D}$, we use a merging graph $\mathcal{G}_M(\mathcal{V}_M, \mathcal{E}_M)$ (the second row in Figure 2(a)) to track the merging status, i.e., to represent the fragments and their connections. In $\mathcal{G}_M(\mathcal{V}_M, \mathcal{E}_M)$, each node

Figure 2: An example of connection-aware molecular motif mining. Given a training set $\mathcal{D} = \{$"Brc1ccccc1", "Cc1cccc(O)c1"$\}$, it consists of two phases. (a) Merging-operation Learning Phase. The merging graphs are initialized the same as the molecular graphs. In the first iteration, "c:c" (marked in blue) is the most frequent pattern. We merge the patterns "c:c" in all the molecules to update the merging graphs. In the second iteration, "c:c:c:c" (marked in yellow) is the most frequent pattern, so we merge such patterns and update merging graphs. We repeat this process for 3 iterations and record the merging operations in order. (b) Motif-vocabulary Construction Phase. We apply the recorded merging operations sequentially on all molecules. Then the two molecules are fragmentized as motifs. We break the bonds between different motifs while preserving the broken bonds. In this way we construct a connection-aware motif vocabulary as shown in (c).

$\mathcal{F} \in \mathcal{V}_M$ represents a fragment (either an atom or a subgraph) of the molecule, and the edges in $\mathcal{E}_M$ indicate whether two fragments are connected with each other. We initialize each merging graph from the molecule graph by treating each atom as a single fragment and inheriting the bond connections from $\mathcal{G}$, i.e., $\mathcal{G}_M^{(0)}(\mathcal{V}_M^{(0)}, \mathcal{E}_M^{(0)}) = \mathcal{G}(\mathcal{V}, \mathcal{E})$.

We define an operation "$\oplus$" to create a new fragment $\mathcal{F}_{ij} = \mathcal{F}_i \oplus \mathcal{F}_j$ by merging two fragments $\mathcal{F}_i$ and $\mathcal{F}_j$ together. The newly obtained $\mathcal{F}_{ij}$ contains all nodes and edges from $\mathcal{F}_i$, $\mathcal{F}_j$, as well as all edges between them. We iteratively update the merging graphs to learn merging operations. In the merging graph $\mathcal{G}_M^{(k)}(\mathcal{V}_M^{(k)}, \mathcal{E}_M^{(k)})$ at the k^{th} iteration ($k = 0, \cdots, K - 1$), each edge represents a pair of fragments, $(\mathcal{F}_i, \mathcal{F}_j)$, that are adjacent in the molecule. It also gives out a new fragment $\mathcal{F}_{ij} = \mathcal{F}_i \oplus \mathcal{F}_j$. We traverse all edges[1] $(\mathcal{F}_i, \mathcal{F}_j) \in \mathcal{E}_M^{(k)}$ in all merging graphs $\mathcal{G}_M^{(k)}$ to count the frequency of $\mathcal{F}_{ij} = \mathcal{F}_i \oplus \mathcal{F}_j$, and denote the most frequent $\mathcal{F}_{ij}$ as $\mathcal{M}^{(k)}$. [2] Consequently, the k-th *merging operation* is defined as: if $\mathcal{F}_i \oplus \mathcal{F}_j == \mathcal{M}^{(k)}$, the $\mathcal{F}_i$ and $\mathcal{F}_j$ should be merged together. We apply the merging operation on all merging graphs to update them into $\mathcal{G}_M^{(k+1)}(\mathcal{V}_M^{(k+1)}, \mathcal{E}_M^{(k+1)})$. We repeat such a process for K iterations to obtain a merging operation sequence $\{\mathcal{M}^{(k)}\}_{k=0}^{K-1}$.

Motif-vocabulary Construction Phase For each molecule $\mathcal{G}(\mathcal{V}, \mathcal{E}) \in \mathcal{D}$, we apply the merging operations sequentially to obtain the ultimate merging graph $\mathcal{G}_M(\mathcal{V}_M, \mathcal{E}_M) = \mathcal{G}_M^{(K)}(\mathcal{V}_M^{(K)}, \mathcal{E}_M^{(K)})$. We then disconnect all edges between different fragments and add the symbols "$*$" to the disconnected positions (see Figure 2(b, c)). The symbols "$*$" denote the connection sites where we should continue growing the molecules. The fragments with "$*$" symbols are connection-aware, and we denote the connection-aware version of a fragment $\mathcal{F}$ as $\mathcal{F}^*$. The motif vocabulary is the collection of all such connection-aware motifs: Vocab $= \cup_{\mathcal{G}_M(\mathcal{V}_M, \mathcal{E}_M) \in \mathcal{D}} \{\mathcal{F}^* : \mathcal{F} \in \mathcal{V}_M\}$. During generating, our model directly picks connection sites (i.e., the dummy atoms which we denote as "$*$") from the

---

[1] We traverse the edges following the orders given by the `RDKit` library (Landrum et al., 2006).

[2] Different $(\mathcal{F}_i, \mathcal{F}_j)$ can make same $\mathcal{F}_{ij}$. For example, both (CCC, C) and (CC, CC) can make "CCCC".

Figure 3: The Generation Steps. (a) The generation procedure is based on the connection-aware motif vocabulary. We obtain the graph representations $h_{\mathcal{F}^*}$ (yellow) and the node representations h_v (dark blue) via $\text{GNN}_{\text{motif}}$. (b) In the t^{th} generation step, we obtain the graph representation $h_{\mathcal{G}_t}$ (dark green) and node representations h_v (light blue) via GNN_{pmol}. We focus on a connection site v_t and use $[z, h_{\mathcal{G}_t}, h_{v_t}]$ to query another connection site either from the motif vocabulary (which implies adding a motif) or from the partial molecule (which implies cyclizing). The right answers of every steps are marked by red boxes.

motif vocabulary, and then connects the motifs together by merging the dummy atoms to generate new molecules.

Time Complexity The time complexity of learning merging operations is $O(K|\mathcal{D}|e)$, where K is the number of iterations, $|\mathcal{D}|$ is the molecule library size, and $e = \max_{\mathcal{G}(\mathcal{V},\mathcal{E}) \in \mathcal{D}} |\mathcal{E}|$. In practice, the time cost decreases rapidly as the iteration step k increases. It takes less than 10 minutes and about 90 minutes to run $3,000$ iterations on the QM9 ($\sim 133K$ molecules) (Ruddigkeit et al., 2012) and ZINK ($\sim 219K$ molecules) (Irwin et al., 2012) datasets, respectively, using 6 CPU cores (see Appendix A.1). The time complexity of fragmentizing an arbitrary molecule $\mathcal{G}(\mathcal{V}, \mathcal{E})$ into motifs is $O(K|\mathcal{E}|)$, linear with the number of bonds.

2.2 Molecular Generation with Connection-aware Motifs

The framework of MiCaM is shown in Figure 3 and Algorithm 2 (in Appendix A.2). MiCaM generates molecules by gradually adding new motifs to a current partial molecule (denoted as $\mathcal{G}_t$, where t is the generation step), or merging two connection sites in $\mathcal{G}_t$ to form a new ring.

For ease of reference, we define the following notations. We denote the node representation of any atom v (including the connection sites) as h_v, and denote the graph representation of any graph $\mathcal{G}$ (either a molecule or a motif) as $h_{\mathcal{G}}$. Let $\mathcal{C}_{\mathcal{G}}$ denote the connection sites from a graph $\mathcal{G}$ (either a partial molecule or a motif), and let $\mathcal{C}_{\text{Vocab}} = \cup_{\mathcal{F}^* \in \text{Vocab}} \mathcal{C}_{\mathcal{F}^*}$ be the set of all connections sites from the motif vocabulary.

Generation Steps In the t^{th} generation step, MiCaM modifies the partial molecule $\mathcal{G}_t$ as follows:

(1) *Focus on a connection site v_t from $\mathcal{G}_t$.* We use a queue $\mathcal{Q}$ to manage the the orders of connection sites in $\mathcal{C}_{\mathcal{G}_t}$. At the t^{th} step, we pop the head of $\mathcal{Q}$ to get a connection site v_t. The $\mathcal{Q}$ is maintained as follows: after selecting a new motif $\mathcal{F}^*$ to connect with $\mathcal{G}_t$, we use the RDKit library to give a canonical order of the atoms in $\mathcal{F}^*$, and then put the connection sites into $\mathcal{Q}$ following this order. After merging two connection sites together, we just remove them from $\mathcal{Q}$.

(2) *Encode v_t and candidate connections.* We employ a graph neural network GNN_{pmol} to encode the partial molecule $\mathcal{G}_t$ and obtain the representations of all atoms (including the connection sites) and the graph. The node representations h_{v_t} of v_t and the graph representation $h_{\mathcal{G}_t}$ of $\mathcal{G}_t$ will be jointly used to query another connection site. For the motifs $\mathcal{F}^* \in \text{Vocab}$, we use another GNN, denoted as $\text{GNN}_{\text{motif}}$, to encode their atoms and connection sites. In this way we obtain the node

representations $\boldsymbol{h}_v$ of all connection sites $v \in \mathcal{C}_{\text{Vocab}}$ [3]. The candidate connections are either from $\mathcal{C}_{\text{Vocab}}$ or from $\mathcal{C}_{\mathcal{G}_t} \setminus \{v_t\}$.

(3) *Query another connection site.* We employ two neural networks, NN_{query} to make a query vector, and NN_{key} to make key vectors, respectively. Specifically, the probability P_v of picking every connection sites is calculated by:

$$P_v = \underset{v \in \mathcal{C}_{\text{Vocab}} \cup \mathcal{C}_{\mathcal{G}_t} \setminus \{v_t\}}{\text{softmax}} \left(\text{NN}_{\text{query}} \left([\boldsymbol{z}, \boldsymbol{h}_{\mathcal{G}_t}, \boldsymbol{h}_{v_t}] \right) \cdot \text{NN}_{\text{key}}(\boldsymbol{h}_v) \right), \qquad (1)$$

where $\boldsymbol{z}$ is a latent vector as used in variational auto-encoder (VAE) (Kingma & Welling, 2013). Using different $\boldsymbol{z}$ results in diverse molecules. During training, $\boldsymbol{z}$ is sampled from a posterior distribution given by an encoder, while during inference, $\boldsymbol{z}$ is sampled from a prior distribution.

For inference, we make a constraint on the bond type of picked v by only considering the connection sites whose adjacent edges have the same bond type as v_t. This practice guarantees the validity of the generated molecules. We also implement two generation modes, i.e., greedy mode that picks the connection as $\arg\max P_v$, and distributional mode that samples the connection from P_v.

(4) *Connect a new motif or cyclize.* After the model picks a connection v, it turns into a connecting phase or a cyclizing phase, depending on whether $v \in \mathcal{C}_{\text{Vocab}}$ or $v \in \mathcal{C}_{\mathcal{G}_t}$. If $v \in \mathcal{C}_{\text{Vocab}}$, and suppose that $v \in \mathcal{C}_{\mathcal{F}^*}$, then we connect $\mathcal{F}^*$ with $\mathcal{G}_t$ by directly merging v_t and v. Otherwise, when $v \in \mathcal{C}_{\mathcal{G}_t}$, we merge v_t and v together to form a new ring, and thus the molecule cyclizes itself. Notice that, allowing the picked connection site to come from the partial molecule is important, because with this mechanism MiCaM theoretically can generate novel rings that are not in the motif vocabulary.

We repeat these steps until $\mathcal{Q}$ is empty and thus there is no non-terminal connection site in the partial molecule, which indicates that we have generated an entire molecule.

Starting   As in the beginning (i.e., the 0^{th} step), the partial graph is empty, we implement this step exceptionally. Specifically, we use another neural network NN_{start} to pick up the first motif from the vocabulary as $\mathcal{G}_0$. The probability $P_{\mathcal{F}^*}$ of picking every motifs is calculated by:

$$P_{\mathcal{F}^*} = \underset{\mathcal{F}^* \in \text{Vocab}}{\text{softmax}} \left(\text{NN}_{\text{start}}(\boldsymbol{z}) \cdot \text{NN}_{\text{key}}(\boldsymbol{h}_{\mathcal{F}^*}) \right), \quad \boldsymbol{h}_{\mathcal{F}^*} = \text{GNN}_{\text{motif}}(\mathcal{F}^*). \qquad (2)$$

2.3   TRAINING MICAM

We train our model in a VAE (Kingma & Welling, 2013) paradigm.[4] A standard VAE has an encoder and a decoder. The encoder maps the input molecule $\mathcal{G}$ to its representation $\boldsymbol{h}_{\mathcal{G}}$, and then builds a posterior distribution of the latent vector $\boldsymbol{z}$ based on $\boldsymbol{h}_{\mathcal{G}}$. The decoder takes $\boldsymbol{z}$ as input and tries to reconstruct the $\mathcal{G}$. VAE usually has a reconstruction loss term (between the original input $\mathcal{G}$ and reconstructed $\hat{\mathcal{G}}$) and a regularization term (to control the posterior distribution of $\boldsymbol{z}$).

In our work, we use a GNN model GNN_{mol} as the encoder to encode a molecule $\mathcal{G}$ and obtain its representation $\boldsymbol{h}_{\mathcal{G}} = \text{GNN}_{\text{mol}}(\mathcal{G})$. The latent vecotr $\boldsymbol{z}$ is then sampled from a posterior distribution $q(\cdot|\mathcal{G}) = \mathcal{N}(\boldsymbol{\mu}(\boldsymbol{h}_{\mathcal{G}}), \exp(\boldsymbol{\Sigma}(\boldsymbol{h}_{\mathcal{G}})))$, where $\boldsymbol{\mu}$ and $\boldsymbol{\Sigma}$ output the mean and log variance, respectively. How to use $\boldsymbol{z}$ is explained in Equation (1) and (2). The decoder consists of GNN_{pmol}, $\text{GNN}_{\text{motif}}$, NN_{query}, NN_{key} and NN_{start} that jointly work to generate molecules.

The overall training objective function is defined as:

$$\mathbb{E}_{\mathcal{G} \sim \mathcal{D}} \left[\mathcal{L}(\mathcal{G}) \right] = \mathbb{E}_{\mathcal{G} \sim \mathcal{D}} \left[\mathcal{L}_{rec}(\mathcal{G}) + \beta_{prior} \cdot \mathcal{L}_{prior}(\mathcal{G}) + \beta_{prop} \cdot \mathcal{L}_{prop}(\mathcal{G}) \right]. \qquad (3)$$

In Equation (3): (1) $\mathcal{L}_{rec}(\mathcal{G})$ is the reconstruction loss as that in a standard VAE. It uses cross entropy loss to evaluate the likelihood of the reconstructed graph compared with the input $\mathcal{G}$. (2) The loss $\mathcal{L}_{prior}(\mathcal{G}) = D_{\text{KL}}(q(\cdot|\mathcal{G}) \| \mathcal{N}(\boldsymbol{0}, \boldsymbol{I}))$ is used to regularize the posterior distribution in the latent space. (3) Following Maziarz et al. (2021), we add a property prediction loss $\mathcal{L}_{prop}(\mathcal{G})$ to ensure the continuity of the latent space with respect to some simple molecule properties. Specifically, we build another network NN_{prop} to predict the properties from the latent vector $\boldsymbol{z}$. (4) β_{prior} and β_{prop} are hyperparameters to be determined according to validation performances.

---

[3] During inference, the motif representations can be calculated offline to avoid additional computation time.

[4] MiCaM can be naturally paired with other paradigms such as GAN or RL, which we plan to explore in future works.

Here we emphasize two useful details. (1) Since MiCaM is an iterative method, in the training procedure, we need to determine the orders of motifs to be processed. The orders of the intermediate motifs (i.e., $t \geq 1$) are determined by the queue $\mathcal{Q}$ introduced in Section 2.2. The only remaining item is the first motif, and we choose the motif with the largest number of atoms as the first one. The intuition is that the largest motif mostly reflects the molecule's properties. The generation order is then determined according to Algorithm 2. (2) In the training procedure, we provide supervisions for every individual generation steps. We implement the reconstruction loss $\mathcal{L}_{rec}(\mathcal{G})$ by viewing the generation steps as parallel classification tasks. In practice, as the vocabulary size is large due to various possible connections, $\mathcal{L}_{rec}(\mathcal{G})$ is costly to compute. To tackle this problem, we subsample the vocabulary and modify $\mathcal{L}_{rec}(\mathcal{G})$ via constrastive learning (He et al., 2020). More details can be found in Appendix A.4.

2.4 DISCUSSION AND RELATED WORK

Frequent Pattern Mining   This motif mining algorithm is inspired by Byte Pair Encoding (BPE) (Gage, 1994), which is widely adapted in natural language processing (NLP) to tokenize words into subwords (Sennrich et al., 2015). Compared with BPE in NLP, molecules have much more complex structures due to different connections and bond types, which we solve by building the merging graphs. Another related class of algorithms are Frequent Subgraph Mining (FSM) algorithms (Kuramochi & Karypis, 2001; Jiang et al., 2013), which also aim to mine frequent motifs from graphs. However, these algorithms do not provide a "tokenizer" to fragmentize an arbitrary molecule into disjoint fragments, like what is done by BPE. Thus we cannot directly apply them in molecular generation tasks. Kong et al. (2021) also try to mine motifs, but there are two main differences. First, they do not learn sequential merging operations to fragmentize an arbitrary molecule and thus is sub-optimal (further discussions are in Appendix A.1). Second, they do not incorporate the connection information into the motif vocabulary, which is important to the performance (see Appendix B.3).

Molecule Generation   A plethora of existing generative models are available and they fall into two categories: (1) string-based models (Kusner et al., 2017; Gómez-Bombarelli et al., 2018; Sanchez-Lengeling & Aspuru-Guzik, 2018; Segler et al., 2018), which rely on string representations of molecules such as SMILES (Weininger, 1988) and do not utilize the structual information of molecules, (2) and graph-based models (Liu et al., 2018; Guo et al., 2021) that are naturally based on molecule graphs. Graph-based approaches mainly include models that generate molecular graphs (1) atom-by-atom (Li et al., 2018; Mercado et al., 2021), and (2) fragment-by-fragment (Kong et al., 2021; Maziarz et al., 2021).

Different from many prior works that view motifs as discrete tokens, we represent all the motifs in the motif vocabulary as graphs, and we apply the $\text{GNN}_{\text{motif}}$ to obtain the representations of motifs. This novel approach has three advantages. (1) The $\text{GNN}_{\text{motif}}$ obtains similar representations for similar motifs, which thus maintains the graph structure information of the motifs (see Appendix C.3). (2) The $\text{GNN}_{\text{motif}}$, combined with contrastive learning, can handle large size of motif vocabulary in training, which allows us to construct a large motif vocabulary (see Section 2.3 and Apppendix A.4). (3) The model can be easily transferred to another motif vocabulary. Thus we can jointly tune the motif vocabulary and the network parameters on a new dataset, improving the capability of the model to fit new data (see Section 3.2).

3 EXPERIMENTS

3.1 DISTRIBUTIONAL LEARNING RESULTS

To demonstrate the effectiveness of MiCaM, we test it on the benchmarks from GuacaMol (Brown et al., 2019), a commonly used evaluation framework to assess *de novo* molecular generation models. We first consider the distribution learning benchmarks, which assess how well the models learn to generate novel molecules that resemble the distribution of the training set.

Experimental Setup   Following Brown et al. (2019), we consider five metrics for distribution learning: validity, uniqueness, novelty, KL divergence (KL Div) and Fréchet ChemNet Distance

Table 1: Distributional results on QM9, ZINC, and GuacaMol. The higher the better for all metrics. The results of JT-VAE, GCPN and GP-VAE are from Kong et al. (2021). For MoLeR, we use the released code from Maziarz et al. (2021) with no changes. Their vocabulary size is 4096, which is large enough to achieve their best overall performance.

Dadaset	Model	Validity	Uniqueness	Novelty	KL Div	FCD
QM9	JT-VAE	**1.0**	0.549	0.386	0.891	0.588
	GCPN	**1.0**	0.533	0.320	0.552	0.174
	GP-VAE	**1.0**	0.673	**0.523**	0.921	0.659
	MoLeR	**1.0**	**0.940**	0.355	0.969	0.931
	MiCaM (Ours)	**1.0**	0.932	0.493	**0.980**	**0.945**
ZINK	JT-VAE	**1.0**	0.988	0.988	0.882	0.263
	GCPN	**1.0**	0.982	0.982	0.456	0.003
	GP-VAE	**1.0**	0.997	**0.997**	0.850	0.318
	MoLeR	**1.0**	0.996	0.993	0.984	0.721
	MiCaM (Ours)	**1.0**	**0.998**	**0.997**	**0.988**	**0.791**
GuacaMol	MoLeR	**1.0**	**1.000**	**0.991**	0.964	0.625
	MiCaM (Ours)	**1.0**	0.994	0.986	**0.989**	**0.731**

(a) KL Divergence   (b) FCD   (c) Novelty

Figure 4: KL Divergence and FCD scores (higher is better) for different numbers of merging operations and different choices of generation modes.

(FCD). The first three metrics measure if the model can generate chemically valid, unique, and novel candidate molecules, while last two are designed to measure the distributional similarity between the generated molecules and the training set. For the KL Div benchmark, we compare the probability distributions of a variety physicochemial descriptors. A higher KL Div score, i.e., lower KL divergences for the descriptors, means that the generated molecules resemble the training set in terms of these descriptors. The FCD is calculated from the hidden representation of molecules in a neural network called ChemNet (Preuer et al., 2018), which can capture important chemiacal and biological features of molecules. A higher FCD score, i.e., a lower Fréchet ChemNet Distance means that the generated molecules have similar chemical and biological properties to those from the training set.

We evaluate our method on three datasets: QM9 (Ruddigkeit et al., 2012), ZINC (Irwin et al., 2012), and GuacaMol (a post-processed ChEMBL (Mendez et al., 2019) dataset proposed by Brown et al. (2019)). These three datasets cover different molecule complexities and different data sizes. The results across them demonstrate the capability of our model to handle different kinds of data.

Quantitative Results Table 1 presents our experimental results of distribution learning tasks. We compare our model with several state-of-the-art models: JT-VAE (Jin et al., 2018), GCPN (You et al., 2018), GP-VAE (Kong et al., 2021), and MoLeR (Maziarz et al., 2021). Since all the models are graph-based, they obtain 100% validity by introducing chemical valence checks during generation. We can see that MiCaM achieves the best performances on the KL Divergence and FCD scores on all the three datasets, which demonstrates that it can well resemble the distributions of training sets. Meanwhile it keeps high uniqueness and novelty, comparable to previous best results.

Table 2: Goal directed generation results on five GuacaMol benchmarks. The higher the better for all metrics. The results of baselines are from Brown et al. (2019) and Ahn et al. (2020). The benchmarks are: a. Celecoxib Rediscovery; b. Aripiprazole Similarity; c. $C_{11}H_{24}$ Isomers; d. Ranolazine MPO; and e. Sitagliptin MPO.

Benchmark	Dataset	SMILES GA	Graph MCTS	Graph GA	SMILES LSTM	MSO	MiCaM (Ours)
a.	0.505	0.732	0.355	**1.000**	**1.000**	**1.000**	**1.000**
b.	0.595	0.834	0.380	**1.000**	**1.000**	**1.000**	**1.000**
c.	0.684	0.829	0.410	0.971	0.993	0.997	**0.999**
d.	0.792	0.881	0.616	0.920	0.855	0.931	**0.932**
e.	0.509	0.689	0.458	0.891	0.545	0.868	**0.914**

In this experiment, we set the number of merging operations to be 1000 for QM9, due to the results in Figure 4. For ZINC and GuacaMol, we simply set the number to be 500 and find that MiCaM has achieved performances that outperform all the baselines. This indicates that existing methods tend to perform well on the sets of relatively simple molecules such as QM9, while MiCaM performs well on datasets with variant complexity. We further visualize the distributions in Figure 7 of Appendix B.2.

Number of Merging Operations   We conduct experiments on different choices of the number of merging operations. Figure 4 presents the experimental results on QM9. It shows that FCD score and KL Divergence score, which measure the similarity between the generated molecules and the training set, increase as the number of merging operations grows. Meanwhile, the novelty decreases as the number grows. Intuitively, the more merging operations we use for motif vocabulary construction, the larger motifs will be contained in the vocabulary, and thus will induce more structural information from the training set. We can achieve a trade-off between the similarity and novelty by controlling the number of merging operations. Empirically, a medium number (about 500) of operations is enough to achieve a high similarity, which demonstrates the effectiveness of the learnt merging operations.

Generation Modes   We also compare two different generation modes, i.e., the greedy generation mode and the distributional generation mode. In the greedy mode, the model always picks the motif or the connection with the highest probability and thus the radomness only comes from the sampling from the latent space. While the distributional mode allows picking motifs or connections according to a distribution. The results show that the greedy mode leads to a little higher KL Divergence and FCD scores, while the distributional mode leads to a higher novelty.

3.2   GOAL DIRECTED GENERATION RESULTS

We further demonstrate the capability of our model to generate molecules with wanted properties. In such goal directed generation tasks, we aim to generate molecules that have high scores which are predefined by rules.

Iteratively Tuning   We combine MiCaM with iterative target augmentation (ITA) (Yang et al., 2020) and generate optimized molecules by iteratively generating new molecules and tuning the model on molecules with highest scores. Specifically, we first pick out N molecules with top scores from the GuacaMol dataset and store them in a training buffer. Iteratively, we tune our model on the training buffer and generate new molecules. In each iteration, we update the training buffer to store the top N molecules that are either newly generated or from the training buffer in the last iteration. In order to accelerate the model to explore the latent space, we pair MiCaM with Molecular Swarm Optimization (MSO) (Winter et al., 2019), a latent space optimization method, in each iteration to generate new molecules.

A novelty of our approach is that when tuning on a new dataset, we jointly update the motif vocabulary and the network parameters. We can do this because we apply a GNN_{motif} to obtain motif representations, which can be transferred to a newly built motif vocabulary. The representations of

| (a) Generation trajectory | (b) Scores of each properties |

Figure 5: Generation trajectories for Ranolazine MPO benchmark. In each generation step, the query connection is marked in red, and the newly added motif is marked in yellow.

the new motifs are calculated by $\text{GNN}_{\text{motif}}$, and we then optimize the network parameters using both new data and newly constructed motif vocabulary.

Experimental Setup   To demonstrate the performance of our approach, we test it on several goal directed generation tasks from GuacaMol benchmarks. Specifically, we consider four different categories of tasks: a Rediscovery task (Celecoxib Rediscovery), a Similarity task (Aripiprazole Similarity), a Isomers task ($C_{11}H_{24}$ Isomers), and two multi-property objective (MPO) tasks (Ranolazine MPO and Sitagliptin MPO).

Quantitative Results   For each benchmark, we run 7 iterations. In each iteration, we apply MSO to generate $80,000$ molecules, and store $10,000$ molecules with highest scores in the training buffer to tune MiCaM. We tune the model pretrained on the GuacaMol dataset. Table 2 presents our experimental results. We achieve 1.0 scores on some relatively easy tasks like other baselines. We achieve high scores on several difficult tasks like MPO tasks, outperforming the baselines.

Case Studies   There are some domain-specific motifs that are beneficial to the target properties in different goal directed generation tasks, which are likely to be the pharmacophores in drug molecules. We conduct case studies to demonstrate the ability of MiCaM to mine such favorable motifs for domain-specific tasks.

In Figure 5 we present cases for the Ranolazine MPO benchmark, which tries to discover molecules similar to Ranolazine, a known drug molecule, but with additional requirements on some other properties. This benchmark calculates the geometric mean of four scores: Sim (the similarity between the molecule and Ranolazine), logP, TPSA, and Num_Fs (the number of fluorine atoms). We present a generation trajectory as well as the scores in each generation step. Due to the domain-specific motif vocabulary and the connection query mechanism, it requires only a few steps to generate such a complex molecule. Moreover, we can see that the scores increase as some key motifs are added to the molecule, which implies that the picked motifs are relevant to the target properties.

We present another case for the Celecoxib Rediscovery task in Figure 8 of Appendix B.4, which demonstrates that as the number of iterations increases, the motifs learnt by MiCaM tend to be more specific and more adaptive to the target, leading to the model to generate molecules with higher scores while costing fewer generation steps.

4   CONCLUSION

In this work, we proposed MiCaM, a novel model that generates molecules based on mined connection-aware motifs. Specifically, the contributions include (1) a data-driven algorithm to mine motifs by iteratively merging most frequent subgraph patterns and (2) a connection-aware generator for *de novo* molecular generation. It achieve state-of-the-art results on distribution learning tasks and on three different datasets. Combined with iterative target augmentation, it can learn domain-specific motifs related to some properties and performs well on goal directed benchmarks.

5 ETHICS STATEMENT

As our work is fundamental research, there are no direct ethical risks. A plethora of deep generative models have been proposed for *de novo* molecular generation, and MiCaM is a member of them. These models can accelerate the process of drug discovery and bring benefits to modern medical industry. However, though they can generate novel molecules as drug candidates, further medical experiments are necessary to make sure that the final conducts are safe and useful.

6 REPREODUCIBILITY STATEMENT

To ensure reproducibility, we precisely describe the algorithms and necessary implementation details in Appendix A. We provide our codes in supplementary materials, but the current codes lack organization. The codes are also available on https://anonymous.4open.science/r/MiCaM-6CFF, and we will update after reorganizing.

REFERENCES

Sungsoo Ahn, Junsu Kim, Hankook Lee, and Jinwoo Shin. Guiding deep molecular optimization with genetic exploration. *Advances in neural information processing systems*, 33:12008–12021, 2020.

Camille Bilodeau, Wengong Jin, Tommi Jaakkola, Regina Barzilay, and Klavs F Jensen. Generative models for molecular discovery: Recent advances and challenges. *Wiley Interdisciplinary Reviews: Computational Molecular Science*, pp. e1608, 2022.

Samuel R Bowman, Luke Vilnis, Oriol Vinyals, Andrew M Dai, Rafal Jozefowicz, and Samy Bengio. Generating sentences from a continuous space. *arXiv preprint arXiv:1511.06349*, 2015.

Nathan Brown, Marco Fiscato, Marwin HS Segler, and Alain C Vaucher. Guacamol: benchmarking models for de novo molecular design. *Journal of chemical information and modeling*, 59(3): 1096–1108, 2019.

Philip Gage. A new algorithm for data compression. *C Users Journal*, 12(2):23–38, 1994.

Rafael Gómez-Bombarelli, Jennifer N Wei, David Duvenaud, José Miguel Hernández-Lobato, Benjamín Sánchez-Lengeling, Dennis Sheberla, Jorge Aguilera-Iparraguirre, Timothy D Hirzel, Ryan P Adams, and Alán Aspuru-Guzik. Automatic chemical design using a data-driven continuous representation of molecules. *ACS central science*, 4(2):268–276, 2018.

Minghao Guo, Veronika Thost, Beichen Li, Payel Das, Jie Chen, and Wojciech Matusik. Data-efficient graph grammar learning for molecular generation. In *International Conference on Learning Representations*, 2021.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 9729–9738, 2020.

Weihua Hu, Bowen Liu, Joseph Gomes, Marinka Zitnik, Percy Liang, Vijay Pande, and Jure Leskovec. Strategies for pre-training graph neural networks. *arXiv preprint arXiv:1905.12265*, 2019.

James P Hughes, Stephen Rees, S Barrett Kalindjian, and Karen L Philpott. Principles of early drug discovery. *British journal of pharmacology*, 162(6):1239–1249, 2011.

John J Irwin, Teague Sterling, Michael M Mysinger, Erin S Bolstad, and Ryan G Coleman. Zinc: a free tool to discover chemistry for biology. *Journal of chemical information and modeling*, 52 (7):1757–1768, 2012.

Chuntao Jiang, Frans Coenen, and Michele Zito. A survey of frequent subgraph mining algorithms. *The Knowledge Engineering Review*, 28(1):75–105, 2013.

Wengong Jin, Regina Barzilay, and Tommi Jaakkola. Junction tree variational autoencoder for molecular graph generation. In *International conference on machine learning*, pp. 2323–2332. PMLR, 2018.

Wengong Jin, Regina Barzilay, and Tommi Jaakkola. Hierarchical generation of molecular graphs using structural motifs. In *International Conference on Machine Learning*, pp. 4839–4848. PMLR, 2020.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Xiangzhe Kong, Zhixing Tan, and Yang Liu. Graphpiece: Efficiently generating high-quality molecular graph with substructures. *arXiv preprint arXiv:2106.15098*, 2021.

Michihiro Kuramochi and George Karypis. Frequent subgraph discovery. In *Proceedings 2001 IEEE international conference on data mining*, pp. 313–320. IEEE, 2001.

Matt J Kusner, Brooks Paige, and José Miguel Hernández-Lobato. Grammar variational autoencoder. In *International conference on machine learning*, pp. 1945–1954. PMLR, 2017.

Greg Landrum et al. Rdkit: Open-source cheminformatics, 2006.

Yibo Li, Liangren Zhang, and Zhenming Liu. Multi-objective de novo drug design with conditional graph generative model. *Journal of cheminformatics*, 10(1):1–24, 2018.

Qi Liu, Miltiadis Allamanis, Marc Brockschmidt, and Alexander Gaunt. Constrained graph variational autoencoders for molecule design. *Advances in neural information processing systems*, 31, 2018.

Krzysztof Maziarz, Henry Jackson-Flux, Pashmina Cameron, Finton Sirockin, Nadine Schneider, Nikolaus Stiefl, Marwin Segler, and Marc Brockschmidt. Learning to extend molecular scaffolds with structural motifs. *arXiv preprint arXiv:2103.03864*, 2021.

David Mendez, Anna Gaulton, A Patrícia Bento, Jon Chambers, Marleen De Veij, Eloy Félix, María Paula Magariños, Juan F Mosquera, Prudence Mutowo, Michał Nowotka, et al. Chembl: towards direct deposition of bioassay data. *Nucleic acids research*, 47(D1):D930–D940, 2019.

Rocío Mercado, Tobias Rastemo, Edvard Lindelöf, Günter Klambauer, Ola Engkvist, Hongming Chen, and Esben Jannik Bjerrum. Graph networks for molecular design. *Machine Learning: Science and Technology*, 2(2):025023, 2021.

Kristina Preuer, Philipp Renz, Thomas Unterthiner, Sepp Hochreiter, and Gunter Klambauer. Fréchet chemnet distance: a metric for generative models for molecules in drug discovery. *Journal of chemical information and modeling*, 58(9):1736–1741, 2018.

David Rogers and Mathew Hahn. Extended-connectivity fingerprints. *Journal of chemical information and modeling*, 50(5):742–754, 2010.

Lars Ruddigkeit, Ruud Van Deursen, Lorenz C Blum, and Jean-Louis Reymond. Enumeration of 166 billion organic small molecules in the chemical universe database gdb-17. *Journal of chemical information and modeling*, 52(11):2864–2875, 2012.

Benjamin Sanchez-Lengeling and Alán Aspuru-Guzik. Inverse molecular design using machine learning: Generative models for matter engineering. *Science*, 361(6400):360–365, 2018.

Marwin HS Segler, Thierry Kogej, Christian Tyrchan, and Mark P Waller. Generating focused molecule libraries for drug discovery with recurrent neural networks. *ACS central science*, 4(1): 120–131, 2018.

Rico Sennrich, Barry Haddow, and Alexandra Birch. Neural machine translation of rare words with subword units. *arXiv preprint arXiv:1508.07909*, 2015.

Jonathan M Stokes, Kevin Yang, Kyle Swanson, Wengong Jin, Andres Cubillos-Ruiz, Nina M Donghia, Craig R MacNair, Shawn French, Lindsey A Carfrae, Zohar Bloom-Ackermann, et al. A deep learning approach to antibiotic discovery. *Cell*, 180(4):688–702, 2020.

Laurens Van der Maaten and Geoffrey Hinton. Visualizing data using t-sne. *Journal of machine learning research*, 9(11), 2008.

David Weininger. Smiles, a chemical language and information system. 1. introduction to methodology and encoding rules. *Journal of chemical information and computer sciences*, 28(1):31–36, 1988.

Robin Winter, Floriane Montanari, Andreas Steffen, Hans Briem, Frank Noé, and Djork-Arné Clevert. Efficient multi-objective molecular optimization in a continuous latent space. *Chemical science*, 10(34):8016–8024, 2019.

Kevin Yang, Wengong Jin, Kyle Swanson, Regina Barzilay, and Tommi Jaakkola. Improving molecular design by stochastic iterative target augmentation. In *International Conference on Machine Learning*, pp. 10716–10726. PMLR, 2020.

Soojung Yang, Doyeong Hwang, Seul Lee, Seongok Ryu, and Sung Ju Hwang. Hit and lead discovery with explorative rl and fragment-based molecule generation. *Advances in Neural Information Processing Systems*, 34:7924–7936, 2021.

Jiaxuan You, Bowen Liu, Zhitao Ying, Vijay Pande, and Jure Leskovec. Graph convolutional policy network for goal-directed molecular graph generation. *Advances in neural information processing systems*, 31, 2018.

A IMPLEMENTATION DETAILS

A.1 MOTIF MINING ALGORITHM

Algorithm 1: Connection-aware Motif Mining

Input: A set of molecule graphs $\mathcal{D} = \{\mathcal{G}_1, \mathcal{G}_2, \cdots, \mathcal{G}_{|\mathcal{D}|}\}$, the number K of iterations.

Output: The merging operations $\{\mathcal{M}^{(k)}\}_{k=0}^{k-1}$ and the motif vocabulary Vocab = $\{\mathcal{F}^*\}$.

1 $\mathcal{D}_M^{(0)} \leftarrow \{\}$;   // Merging-operation learning phase
2 **for** $\mathcal{G}(\mathcal{V}, \mathcal{E}) \in \mathcal{D}$ **do**
3   $\quad \mathcal{G}_M^{(0)}(\mathcal{V}_M^{(0)}, \mathcal{E}_M^{(0)}) \leftarrow \mathcal{G}(\mathcal{V}, \mathcal{E})$;
4   $\quad \mathcal{D}_M^{(0)} \leftarrow \mathcal{D}_M^{(0)} \cup \{\mathcal{G}_M^{(0)}\}$;
5 **for** $k = 0$ *to* $K - 1$ **do**
6   $\quad$ Reset Count() to 0;
7   $\quad$ **for** $\mathcal{G}_M^{(k)}(\mathcal{V}_M^{(k)}, \mathcal{E}_M^{(k)}) \in \mathcal{D}_M^{(k)}$ **do**
8    $\quad\quad$ **for** $(\mathcal{F}_i, \mathcal{F}_j) \in \mathcal{E}_M^{(k)}$ **do**
9     $\quad\quad\quad \mathcal{M} \leftarrow \mathcal{F}_i \oplus \mathcal{F}_j$;
10     $\quad\quad\quad$ Count($\mathcal{M}$) $\leftarrow$ Count($\mathcal{M}$) + 1;
11   $\quad \mathcal{M}^{(k)} \leftarrow \arg\max$ Count($\mathcal{M}$);
12   $\quad \mathcal{D}_M^{(k+1)} \leftarrow \{\}$;
13   $\quad$ **for** $\mathcal{G}_M^{(k)}(\mathcal{V}_M^{(k)}, \mathcal{E}_M^{(k)}) \in \mathcal{D}_M^{(k)}$ **do**
14    $\quad\quad \mathcal{G}_M^{(k+1)} \leftarrow \mathcal{G}_M^{(k)}$;
15    $\quad\quad$ **for** $(\mathcal{F}_i, \mathcal{F}_j) \in \mathcal{E}_M^{(k)}$ **do**
16     $\quad\quad\quad$ **if** $\mathcal{F}_i \oplus \mathcal{F}_j == \mathcal{M}^{(k)}$ **then**
17      $\quad\quad\quad\quad$ Merge $\mathcal{F}_i$ and $\mathcal{F}_j$ in $\mathcal{G}_M^{(k+1)}$;
18    $\quad\quad \mathcal{D}_M^{(k+1)} \leftarrow \mathcal{D}_M^{(k+1)} \cup \{\mathcal{G}_M^{(k+1)}\}$;
19 Vocab $\leftarrow \{\}$;   // Motif-vocabulary construction phase
20 **for** $\mathcal{G}_M^{(K)}(\mathcal{V}_M^{(K)}, \mathcal{E}_M^{(K)}) \in \mathcal{D}_M^{(K)}$ **do**
21   $\quad \mathcal{G}_M(\mathcal{V}_M, \mathcal{E}_M) \leftarrow \mathcal{G}_M^{(K)}(\mathcal{V}_M^{(K)}, \mathcal{E}_M^{(K)})$;
22   $\quad$ **for** $k = 0$ *to* $K - 1$ **do**
23    $\quad\quad$ **for** $(\mathcal{F}_i, \mathcal{F}_j) \in \mathcal{E}_M$ **do**
24     $\quad\quad\quad$ **if** $\mathcal{F}_i \oplus F_j == \mathcal{M}^{(k)}$ **then**
25      $\quad\quad\quad\quad$ Merge $\mathcal{F}_i$ and $\mathcal{F}_j$ in $\mathcal{G}_M$;
26   $\quad$ Vocab $\leftarrow$ Vocab $\cup \{\mathcal{F}^*$ for $\mathcal{F} \in \mathcal{V}_M\}$;

Our connection-aware motif mining algorithm is in Algorithm 1. In the merging graph $\mathcal{G}_M(\mathcal{V}_M, \mathcal{E}_M)$, each node $\mathcal{F} \in \mathcal{V}_M$ represents a fragment $\mathcal{F}(\hat{\mathcal{V}}, \hat{\mathcal{E}})$ of the molecule graph $\mathcal{G}(\mathcal{V}, \mathcal{E})$, where $\hat{\mathcal{V}} \subset \mathcal{V}$ and $\hat{\mathcal{E}} \subset \mathcal{E}$ are atoms and bonds in $\mathcal{F}$, respectively. The edge set $\mathcal{E}_M$ is defined by: for any two fragments $F_i(\mathcal{V}_i, \mathcal{E}_i), F_j(\mathcal{V}_j, \mathcal{E}_j) \in \mathcal{V}_M$, $(\mathcal{F}_i, \mathcal{F}_j) \in \mathcal{E}_M \iff \exists a \in \mathcal{V}_i, b \in \mathcal{V}_j, (a, b) \in \mathcal{E}$. The merging operation "$\oplus$" is defined to create $\mathcal{F}_{ij}(\mathcal{V}_{ij}, \mathcal{E}_{ij}) = \mathcal{F}_i \oplus \mathcal{F}_j$ by merging two fragments $\mathcal{F}_i(\mathcal{V}_i, \mathcal{E}_i)$ and $\mathcal{F}_j(\mathcal{V}_j, \mathcal{E}_j)$. Formally,

$$\mathcal{V}_{ij} = \mathcal{V}_i \cup \mathcal{V}_j, \quad \mathcal{E}_{ij} = \mathcal{E}_i \cup \mathcal{E}_j \cup \{(a, b) \in \mathcal{E} | a \in \mathcal{V}_i, b \in \mathcal{V}_j\},$$

which means the new fragment $\mathcal{F}_{ij}$ contains all nodes and edges from $\mathcal{F}_i$, $\mathcal{F}_j$, as well as the edges between them. In the motif-vocabulary construction phase, we disconnect bonds between different fragments and add "*" atoms to create connection-aware motifs. Specifically, for each $\mathcal{F}(\hat{\mathcal{V}}, \hat{\mathcal{E}}) \in \mathcal{V}_M$, we define its corresponding connection-aware motif $\mathcal{F}^*(\hat{\mathcal{V}}^*, \hat{\mathcal{E}}^*)$ as

$$\hat{\mathcal{V}}^* = \hat{\mathcal{V}} \cup \{a^* | a \in \mathcal{V}, \exists b \in \hat{\mathcal{V}}, (a, b) \in \mathcal{E}\},$$

$$\hat{\mathcal{E}}^* = \{(a, b) \in \mathcal{E} | a \in \hat{\mathcal{V}}^*, b \in \hat{\mathcal{V}}^*\},$$

where "a^*" denotes that we change the label of the atom a to "$*$". The symbol "$*$" can be seen as a dummy atom or a connection site, which indicates that the bond is non-terminal and we will grow the molecule here.

(a) Accumulative time costs   (b) Time costs of each iteration   (c) Frequencies

Figure 6: Time costs of learning merging operations on QM9. (a) and (b) show the accumulative time costs and time costs of each iteration, respectively. (c) shows the frequencies of the learnt mergingoperations.

Efficiency   Figure 6 presents the time costs of learning operations from QM9, which demonstrates that our algorithm is fast, and the time cost of each iteration decreases rapidly as the motif frequency decreases.

Sequential Merging Operations   The merging operations are useful as they work as a "tokenizer" that can be applied to fragmentize an arbitrary molecule, which is unavailable for other methods like Frequent Subgraph Mining. Another choice of using the merging operations is not applying them sequentially, but traversing the molecule edges to find if there are patterns that appear in the learnt frequent motifs, which is similar to the algorithm proposed by Kong et al. (2021). However, this is sub-optimal as it does not work reasonably on any arbitrary molecule outside the dataset to learn the operations. For example, consider a trivial dataset $\mathcal{D} = \{\text{CC, CN, CNN, CN=O, CC=O}\}$. When we run two iterations, the learnt merging operations are $\{\text{CN, CC}\}$. Then we use them to fragmentize a new molecule "CCN". If we apply the merging operations sequentially, the molecule will be decomposed into $\{\text{C, CN}\}$. However, if we traverse the molecule edges to find the patterns, the molecule will be decomposed into $\{\text{CC, N}\}$, which is sub-optimal because "CN" appears with a higher frequency in the dataset.

A.2   GENERATING PROCEDURE

Algorithm 2 presents the pseudo code of our generation procedure.

A.3   NETWORKS

The backbone of MiCaM is VAE. The encoder is GNN_{mol}, followed by three MLPs: $\boldsymbol{\mu}$ and $\boldsymbol{\Sigma}$ for resampling, and NN_{prop} for property prediction. The decoder consists of GNN_{pmol}, $\text{GNN}_{\text{motif}}$, which are GNNs, and NN_{start}, NN_{query}, NN_{key}, which are MLPs. All MLPs have 3 layers and use ReLU as the activation function. The latent size and the hidden size are both 256.

We employ GINE (Hu et al., 2019) with a virtual node as the GNN structures, and in each GNN layer we employ a 3-layer MLP for messaage aggregation. For all GNNs, we use five atom-level features as inputs: atom symbol, is_aromatic, formal charge, num_explicit_Hs, num_implicit_Hs. The features are embedded with the dimension $192, 16, 16, 16, 16$, respectively, and thus the node embedding size is 256. Four edges, we consider four types of bonds (single bonds, double bonds, triple bonds and aromatic bond), and the embedding size is 256. GNN_{mol} and GNN_{pmol} have 15 layers and $\text{GNN}_{\text{motif}}$ has 6 layers.

A.4   EXPERIMENT DETAILS

Learning Merging Operations   For QM9, we apply 1000 merging operations due to the comparative results in 4. For ZINK and GuacaMol, we simply use 500 merging operations without elaborate searching, and find that it has achieved good results. Due to the large size of GuacaMol dataset, we randomly sample $100,000$ molecules from it to learn merging operations, and then apply these merging operations on all molecules to obtain the motif vocabulary.

Algorithm 2: Generating a molecule

Input: A connection-aware motif vocabulary Vocab $= \{\mathcal{F}^*\}$. A latent vector $\boldsymbol{z}$.
Output: A molecule graph $\mathcal{G}$.

1   $\mathcal{C}_{\text{Vocab}} \leftarrow \bigcup_{\mathcal{F}^* \in \text{Vocab}} \{connection\ sites\ v\ in\ \mathcal{F}^*\}$;
2   Calculate $P(\mathcal{F}^*)$ by Equation 2 and sample $\mathcal{F}^* \sim P_{\mathcal{F}^*}$;
3   $\mathcal{G} \leftarrow \mathcal{F}^*, \mathcal{Q} \leftarrow \emptyset$;   `// Pick the starting motif`
4   **for** *connection sites v in $\mathcal{F}^*$* **do**
5 | $\mathcal{Q}.put(v)$;
6   **while** $\mathcal{Q} \neq \emptyset$ **do**   `// Connection querying step`
7 | $v_t \leftarrow \mathcal{Q}.get(), \mathcal{C} \leftarrow \mathcal{Q}$;
8 | $\mathcal{C} \leftarrow \mathcal{C}_{\text{Vocab}} \cup \mathcal{C}_{\text{mol}}$;
9 | Calculate $P(v)$ over $\mathcal{C}$ by Equation 1 and sample $v \sim P(v)$;
10 | **if** $v \in \mathcal{C}_{Vocab}$ *and* v *in* $\mathcal{F}^* \in Vocab$ **then**
11 | | $\mathcal{G} \leftarrow \mathcal{G}.\text{AddMotif}(\mathcal{F}^*)$;   `// Connecting a new motif`
12 | | Merge(v_t, v);
13 | | **for** *connection sites $v' \in \mathcal{F}^* \setminus \{v\}$* **do**
14 | | | $\mathcal{Q}.put(v')$;
15 | **else**
16 | | Assert $v \in \mathcal{C}_{\text{mol}}$;
17 | | Merge(v_t, v);   `// Cyclizing itself`
18 | | $\mathcal{Q} \leftarrow \mathcal{Q} \setminus \{v\}$

Training MiCaM   We preprocess all the molecules to provide supervision signals for decoder to rebuild the molecules. We provide the true indices of picked connections in every steps so that the model can learn the ground truth. We set the batch size to be 128. Specifically, in each optimization step, we update the network parameters by optimizing the loss function on a batch $\mathcal{B}$ of 128 molecules:

$$\mathcal{L}_{\mathcal{B}} = \mathbb{E}_{\mathcal{G} \sim \mathcal{B}} \left[\beta_{prior} \cdot \mathcal{L}_{prior}(\mathcal{G}) + \mathcal{L}_{rec}(\mathcal{G}) + \beta_{prop} \cdot \mathcal{L}_{prop}(\mathcal{G}) \right].$$

Specifically, the reconstruction loss $\mathcal{L}_{rec}$ is written as a sum over the negative log probabilities of the partial graphs $\mathcal{G}_t$ at each step t, conditioned on $\boldsymbol{z}$ and the last steps:

$$\mathcal{L}_{rec}(\mathcal{G}) = -\mathbb{E}_{z \sim q(\cdot | \mathcal{G})} \left[\log p(\mathcal{G}_0 | \boldsymbol{z}) + \sum_t \log p(\mathcal{G}_{t+1} | \boldsymbol{z}, \mathcal{G}_t) \right]$$

$$= -\mathbb{E}_{z \sim q(\cdot | \mathcal{G})} \left[\log p(\mathcal{F}_0^* | \boldsymbol{z}) + \sum_t \log p(u_t | \boldsymbol{z}, \mathcal{G}_t, v_t) \right],$$

where $\mathcal{F}_0^*$, v_t and u_t are the first motif, the focused query connection site and the picked connection at the t^{th} step, respectively. In practice, since the motif vocabulary is large due to different connections, we modify the loss via contrastive learning for efficient training:

$$\log p(\mathcal{F}_0^* | \boldsymbol{z}) \approx \log \frac{\exp(\text{NN}_{\text{start}}(\boldsymbol{z}) \cdot \text{NN}_{\text{key}}(\boldsymbol{h}_{\mathcal{F}_0^*}))}{\sum_{\mathcal{F}^* \in \mathcal{I}_{\mathcal{F}^*}} \exp(\text{NN}_{\text{start}}(\boldsymbol{z}) \cdot \text{NN}_{\text{key}}(\boldsymbol{h}_{\mathcal{F}^*}))},$$

$$\log p(u_t | \boldsymbol{z}, \mathcal{G}_t, v_t) \approx \log \frac{\exp(\text{NN}_{\text{query}}([\boldsymbol{z}, \boldsymbol{h}_{\mathcal{G}_t}, \boldsymbol{h}_{v_t}]) \cdot \text{NN}_{\text{key}}(\boldsymbol{h}_{u_t}))}{\sum_{v \in \mathcal{I}_v} \exp(\text{NN}_{\text{query}}([\boldsymbol{z}, \boldsymbol{h}_{\mathcal{G}_t}, \boldsymbol{h}_{v_t}]) \cdot \text{NN}_{\text{key}}(\boldsymbol{h}_v))},$$

where $\mathcal{I}_{\mathcal{F}^*}$ and $\mathcal{I}_v$ are the sets of motifs and connections, respectively, containing a positive sample and random negative samples.

We find that a proper choice of β_{prior} is essentially important to the performances on distribution learning benchmarks, especially for FCD scores. For QM9, we use a short warm-up $(3,000 \text{ steps})$, and use a long sigmoid schedule $(400,000 \text{ steps})$ (Bowman et al., 2015) to let β_{prior} to reach 0.4.

For property prediction, we predict four simple properties of molecules, including molecular weight, synthetic accessibility (SA) score, octanol-water partition coefficient (logP) and quantitative estimate of drug-likeness (QED). The target values are computed using the RDKit library. Empirically, for distribution learning benchmarks, a small β_{prop} (about 0.3) is beneficial.

B ADDITIONAL RESULTS

B.1 EFFICIENCY

Thanks to the mined motifs and the connection-aware decoder, MiCaM is very efficient. We measure the training and sampling speed on a single GeForce RTX 3090. For training, it trains on 325.7 molecules per second. For inference, it samples 54.4 molecules per second.

B.2 DISTRIBUTION VISUALIZATION

(a) Training sets   (b) Results on QM9   (c) Results on ZINK   (d) Results on GuacaMol

Figure 7: Visualization of the probability distributions of training sets (QM9, ZINK and GuacaMol) and the generated molecules. The postfix "_ref" means reference, i.e., the training sets (shown in green, blue and red, respectively), and the postfix "_gen" means the sets of molecules generated by our model (shown in grey). We obtain the representations of molecules by calculating their molecular fingerprints, and we then apply t-SNE dimensionality reduction for visualization. The curves represent the contour lines of the probability distributions of the datasets. (a) shows the distributional shift over the three training sets. (b), (c) and (d) demonstrate that our generative model can properly fit the different distributions respectively.

We visualize the distributional results on the three datasets in Figure 7. Specifically, we first calculate the Morgan fingerprints of all molecules. Morgan figerprint has been used for a long time in drug discovery, as it can represents the structual information of molecules (Rogers & Hahn, 2010). For visualization, we apply the t-distributed stochastic neighbor embedding (t-SNE) algorithm (Van der Maaten & Hinton, 2008)—a nonlinear dimensionality reduction technique to keep the similar high-dimensional vectors close in lower-dimensional space—to represent molecules in the two-dimensional plane, and then plot the distributions of molecules.

B.3 ABLATION STUDY

Table 3: Ablation studies on different versions of MiCaM. The results are from a set of $100,000$ molecules randomly sampled from GuacaMol.

Model	Validity	Uniqueness	Novelty	KL Div	FCD
MiCaM(v1)	1.0	1.000	0.993	0.926	0.685
MiCaM(v2)	1.0	0.989	0.989	0.965	0.617
MiCaM	1.0	0.998	0.995	0.957	0.754

Two components contribute to the performance of MiCaM. First is the GNN_{motif}, which captures he graph structures of motifs, and allows efficient training on a large motif vocabulary via contrastive learning. Second is the connection-aware motif vocabulary and corresponding connection-aware decoder. We conduct ablation studies to demonstrate the importance of the two components. Specifically, we implement three different versions of MiCaM. MiCaM(v1) does not apply NN_{motif} and does not use connection information for generation. In each step, it first picks up the motif (without connection information) by viewing them as discrete tokens, and then determines the connecting points and bonds. MiCaM(v2) employs the NN_{motif} to pick up motifs, but does not directly query

Figure 8: Generation trajectories for Celecoxib Rediscovery. We show the trajectories of the best molecules in three different iterations. In each generation step, the query connection is marked in red, and the newly added motif is marked in yellow.

the connection sites. The results demonstrate that leveraging connection information and employing the GNN_{motif} actually bring performance improvements.

B.4 CASE STUDY

In Figure 8 we present cases for the Celecoxib Rediscovery task, which aims to discover molecules similar to Celecoxid, a known drug molecule. Specifically, we present the trajectories to generate molecules with the highest scores in the 1st, 3rd and 5th iterations. As the number of iterations increases, the motifs learnt by MiCaM tend to be more specific and more adaptive to the target, leading to the model to generate molecules with higher scores while costing fewer generation steps.

B.5 GENERATED MOLECULES

Figure 9: Samples from molecules randomly generated by a MiCaM model, trained on GuacaMol.

C MOTIF VOCABULARY

C.1 MERGING OPERATIONS

We present the learnt merging operations from QM9 and GuacaMol in Figure 10. The merging operations can efficiently merge molecules into a few disjoint units. For statistics, each molecule in GuacaMol has 27.899 atoms on average. After applying 500 merging operations, each of they is represented as only 8.499 subgraphs on average. After applying 1000 merging operations, the number is 8.282. As a comparison, MoLeR decomposes each molecule into 9.667 fragments on average, when taking 4096 as the vocabulary size.

(a) Learnt merging operations for QM9.

(b) Learnt merging operations for GuacaMol.

Figure 10: Merging operations. Note that instead of kekulizing all molecules, we maintain the aromaticity of atoms and bonds. Thus some of the patters seem half-baked.

(a) Mined motifs for QM9.

(b) Mined motifs for GuacaMol.

(c) Mind motifs in the last iteration for Ranolazine MPO benchmark.

Figure 12: Motifs sampled for the Ranolazine MPO benchmark.

C.2 MINED MOTIFS

Our algorithm is able to mine common graph motifs with high frequency in a large number of molecules, including some motifs with complex structures, and domain specific motifs. We present some mined motifs in Figure 12.

C.3 MOTIF REPRESENTATIONS

Since we apply GNN$_{motif}$ to encode motif representations, instead of viewing motifs as discrete tokens, the learnt motif representations can maintain structural information in the sense that similar motifs have close representations. To show this, we visualize some motif representations in Figure 11.

Figure 11: The t-SNE visualization of Motif representations.