GUI-WORLD: A GUI-ORIENTED DATASET FOR MULTIMODAL LLM-BASED AGENTS

Figure 1: GUI-WORLD: A comprehensive dataset for GUI-oriented capabilities encompasses six scenarios and diverse tasks, offering significant potential for real-world applications. All screenshots presented are sampled from our dataset.

ABSTRACT

Recently, Multimodal Large Language Models (MLLMs) have been used as agents to control keyboard and mouse inputs by directly perceiving the Graphical User Interface (GUI) and generating corresponding commands. However, current agents primarily demonstrate strong understanding capabilities in static environments and are mainly applied to relatively simple domains, such as Web or mobile interfaces. We argue that a robust GUI agent should be capable of perceiving temporal information on the GUI, including dynamic Web content and multi-step tasks. Additionally, it should possess a comprehensive understanding of various GUI scenarios, including desktop software and multi-window interactions. To this end, this paper introduces a new dataset, termed GUI-WORLD, which features meticulously crafted Human-MLLM annotations, extensively covering six GUI scenarios and eight types of GUI-oriented questions in three formats. We evaluate the capabilities of current state-of-the-art MLLMs, including Image LLMs and Video LLMs, in understanding various types of GUI content, especially dynamic and sequential content. Our findings reveal that vision LLMs struggle with dynamic GUI content without manually annotated keyframes or operation history. On the other hand, video LLMs fall short in all GUI-oriented tasks given the sparse GUI video dataset. Therefore, we take the initial step of leveraging a fine-tuned video LLM as a GUI agent based on GUI-WORLD, demonstrating an improved understanding of various GUI tasks. However, due to the limitations in the performance of base LLMs, we conclude that using video LLMs as GUI agents remains a significant challenge. We believe our work provides valuable insights for future research in dynamic GUI content understanding.

1 INTRODUCTION

Multimodal Large Language Models (MLLMs), such as GPT-4V(ision) (OpenAI, 2023) and LLaVA (Liu et al., 2023b), have significantly contributed to the development of both vision and

Figure 2: Comparative performance of different MLLMs in six scenarios of GUI-WORLD. (a) Performance of four mainstream Image LLMs. (b) Performance of three video LLMs and our **GUI-Vid**. (c) Performance among six methods. See subsection 3.2 for more details.

language domains (Yin et al., 2024). These models bring forth innovative solutions and paradigms for traditional visual tasks, including visual reasoning (Yang et al., 2023b), medical image interpretation (Li et al., 2024b), and applications in embodied agents (Huang et al., 2023). One particularly promising area is Graphical User Interface (GUI) understanding, which holds significant potential for real-world applications, such as webpage comprehension (Hong et al., 2024; Lai et al., 2024) and navigation by GUI agents (Yang et al., 2023a; Niu et al., 2024; Wang et al., 2024). The key challenges of GUI understanding are twofold: effective GUI agents are expected to (1) possess a deep understanding of GUI elements, including webpage icons, text identified through Optical Character Recognition (OCR), and page layouts, and (2) exhibit an exceptional ability to follow instructions within GUI contexts, such as conducting searches through search engines.

Despite significant progress, as illustrated in Table 1, prior studies on GUI-related datasets and benchmarks suffer from the following limitations: (1) *Inability to Handle Dynamic Environments.* Most studies predominantly focus on the static features of GUI scenarios, neglecting the need for MLLMs to effectively process sequential information and dynamic operations. For instance, an agent's task performance can be disrupted by unexpected elements such as pop-up advertisements, underscoring a gap in handling dynamic sequential tasks. (2) *Limited Scenarios.* Current research is typically restricted to Web-based environments, which limits the models' generalization and robustness. For instance, GUI agents may need to operate across diverse platforms such as Windows, macOS, Linux, iOS, Android, and XR environments. Additionally, operations may sometimes involve multiple windows. Therefore, expanding the scope of research to encompass these varied environments will enhance the adaptability and effectiveness of GUI agents.

To mitigate these gaps, this paper introduces GUI-WORLD, a comprehensive dataset containing 12,379 GUI videos, specifically designed to evaluate and enhance the capabilities of GUI agents. This dataset encompasses a wide range of GUI scenarios, including popular websites, desktop and mobile applications across various operating systems, multi-window interactions, as well as XR environments. The data collection process involves sourcing GUI videos from screen recordings and instructional videos on YouTube. Subsequently, we utilize a Human-MLLM collaborative approach to generate a diverse set of captions, complex queries, and multi-round conversation and finally construct GUI-WORLD.

Likewise, we also establish a comprehensive benchmark for GUI understanding, which encompasses nine mainstream MLLMs, five keyframe selection strategies, and six GUI scenarios, aiming to provide a thorough evaluation of the MLLMs' GUI-oriented capabilities. As shown in Figure 2, the assessment results indicate that most MLLMs struggle with GUI-WORLD, highlighting their limited dynamic understanding of graphical interfaces and underscoring the need for further enhancement.

Leveraging this dataset, we take the first step to fine-tune a video GUI agent adept at handling dynamic and sequential GUI tasks, leading to substantial enhancements in the general capabilities of GUI agents and showcasing the utility and effectiveness of GUI-WORLD. Additionally, we delve into discussing various factors critical to GUI understanding, including the integration of textual information, the number of keyframes, image resolutions, and vision perception for a pioneer comprehensive study in the GUI domain.

Overall, the key contributions of this paper are three-fold:

Table 1: Comparison of GUI datasets and benchmarks. 'Sem.': semantic instruction level, 'VL': Vision-Language, 'Seq.': Tasks for sequential images, 'Cro.': Cross-app or multi-window tasks, 'Dyn.': Tasks for dynamic GUI content.

Dataset	Size	Sem.	VL	Video	Env Type				Task Coverage			Task
					Web.	Mob.	Desk.	XR	Seq.	Cro.	Dyn.	
Rico (Deka et al., 2017)	72,219	Low	✔	✔	✗	✔	✗	✗	✔	✔	✗	UI Code/Layout Generation
MiniWoB++ (Liu et al., 2018)	100	Low	✔	✗	✔	✗	✗	✗	✗	✗	✗	Web Navigation
Screen2Words (Wang et al., 2021)	22,417	High	✔	✗	✗	✗	✗	✗	✗	✗	✗	UI Summarization
MetaGUI (Sun et al., 2022)	1,125	Low	✔	✗	✗	✔	✗	✗	✔	✗	✗	Mobile Navigation
UGIF (Venkatesh et al., 2022)	523	High	✔	✗	✗	✔	✗	✗	✔	✗	✗	Instruction Following
AITW (Rawles et al., 2023)	715,142	High	✔	✗	✗	✔	✗	✗	✔	✔	✗	GUI Understanding
Ferret-UI (You et al., 2024)	123,702	Low	✔	✗	✗	✔	✗	✗	✗	✗	✗	UI Grounding & Understanding
Spotlight (Li & Li, 2022)	2.5M	Low	✔	✗	✗	✔	✗	✗	✗	✗	✗	GUI Understanding
WebArena (Zhou et al., 2023)	812	Low	✔	✗	✔	✗	✗	✗	✔	✗	✗	Web Navigation
Mind2Web (Deng et al., 2024)	2,350	Both	✔	✗	✔	✗	✗	✗	✔	✗	✗	Web Navigation
OmniAct (Kapoor et al., 2024)	9,802	Low	✔	✗	✔	✗	✔	✗	✔	✗	✗	Code Generation
GUICourse (Chen et al., 2024c)	10.7M	Both	✔	✗	✔	✔	✗	✗	✔	✔	✗	GUI Understanding
MMINA (Zhang et al., 2024e)	1,050	Low	✔	✗	✔	✗	✗	✗	✔	✔	✗	Web Navigation
AgentStudio (Zheng et al., 2024b)	304	High	✔	✗	✔	✗	✔	✗	✔	✔	✗	General Control
OSWorld (Xie et al., 2024)	369	High	✔	✗	✔	✗	✔	✗	✔	✔	✗	General Control
GUI-WORLD (Ours)	12,379	Both	✔	✔	✔	✔	✔	✔	✔	✔	✔	GUI Understanding Instruction Following

- **A New Dataset.** We propose GUI-WORLD, a comprehensive GUI dataset comprising 12,379 videos specifically designed to assess and improve GUI-oriented capabilities of MLLMs, spanning a range of categories and scenarios, including desktop, mobile, and eXtended Reality (XR), and representing the first GUI-oriented instruction-tuning dataset in video domain.

- **Comprehensive Experiments and Valuable Insights.** Our experiments indicate that most existing MLLMs continue to face challenges with GUI-oriented tasks, particularly in sequential and dynamic GUI content. Empirical findings suggest that improvements in vision perception, along with an increase in the number of keyframes and higher resolution, can boost performance in GUI tasks.

- **A Explorative GUI Agent.** Based on GUI-WORLD, we propose GUI-Vid, a GUI-oriented video LLM with enhanced capabilities to handle various and complex GUI tasks. GUI-Vid shows a significant improvement on the benchmark and achieves results comparable to the top-performing models, thereby paving ways for the future of GUI agents.

2 GUI-WORLD: A DATASET FOR GUI UNDERSTANDING

2.1 OVERVIEW

We introduce GUI-WORLD, a comprehensive dataset covering six GUI scenarios including video, human-annotated keyframes, as well as detailed captions and diverse types of QA produced by our data curation framework, aiming at benchmarking and enhancing the general GUI-oriented capabilities. These GUI scenarios encompass desktop operating systems (*e.g.*, macOS, Windows) and mobile platforms (*e.g.*, Android and iOS), websites, software, and even extended-range technologies (XR) (*e.g.*, GUI in Apple Vision Pro (Apple, 2024)). We divide the dataset into a train-test split, each containing 10,702 and 1,677 samples. Discussion for each scenario is in subsection A.1.

As illustrated in Figure 3, the development of GUI-WORLD is structured around a two-stage process. Details regarding video and query statistics are provided in Table 2, which includes distributions of

Figure 3: An overview construction pipeline of GUI-WORLD.

Table 2: The statistics of GUI-WORLD. For Android, we select videos from Rico (Deka et al., 2017) and randomly sample 10 frames. *Avg. Frame* refers to the average number of frames in each clip, and *Avg. Anno.* refers to the average number of manually annotated GUI actions.

Category	Total Videos	Free-form	MCQA	Conversation	Total Frame. (Avg.)	Avg. Anno.
Software	4,720	27,840	9,440	9,440	23,520 (4.983)	7.558
Website	2,499	14,994	4,998	4,998	15,371 (6.151)	6.862
IOS	492	2,952	984	984	2,194 (4.459)	7.067
Multi	475	2,850	950	950	2,507 (5.277)	7.197
XR	393	2,358	786	786	1,584 (4.030)	10.970
Android	3,800	15,199	7,600	7,600	38,000 (10.000)	-
Summary	12,379	76,673	24,758	24,758	83,176 (6.719)	7.463

Figure 4: **Left:** Distribution of the number of keyframes and video lengths. **Right:** Length distribution for each type of question and its golden answer.

the number of keyframes, video lengths, and the lengths of queries and their corresponding golden answers shown in Figure 4 and Figure 5 for case study.

2.2 GUI VIDEO COLLECTION AND KEYFRAME ANNOTATION PROCESS

We describe the pipeline for collecting screen recordings from student workers and GUI-related instructional videos from YouTube for GUI-WORLD and the procedures followed to convert these videos into keyframe sequences.

A significant portion of our video data is derived from screen recordings executed by student workers, which can directly reflect real-life GUI usage scenarios. A typical video collection scenario involves assigning a student worker a specific software task. The student begins by familiarizing themselves with the software, followed by recording a series of operations in a short video clip, such as "Sign up", "Sign in", "Create a New Page", and "Invite Other Collaborators" in the software "Notion[1]".

Despite the high fidelity of these manually recorded videos, we encounter several challenges: (1) Student workers often require substantial time to acquaint themselves with professional software (*e.g.*, MATLAB, Adobe After Effects (Ae)), which can hinder the progress of data collection. (2) The videos may lack comprehensiveness, typically capturing only commonly used operations and overlooking rarer functions crucial for dataset completeness. To address these issues, we also source videos from social media platforms that host a diverse array of GUI videos. Specifically, we download tutorial videos from YouTube—given its prevalence as a video-sharing platform—because they richly detail various GUI operations. These videos are then segmented into shorter clips, each representing a distinct sequence of operations.

The subsequent step involves annotating these video clips with keyframes and textual descriptions of each keyframe using custom-designed annotation software. Although several algorithms exist for keyframe extraction (Zhu et al., 2016; Yan et al., 2018; Mahasseni et al., 2017; OpenCV), they typically underperform with GUI videos where changes between frames might be minimal (*e.g.*, a slight movement in the mouse cursor). To ensure high-quality datasets, we therefore perform manual extraction of these keyframes. Each keyframe is meticulously annotated to include details such as the operation performed, the purpose between two keyframes, the software or website used, mouse actions (*e.g.*, scroll, click), and keyboard inputs (*e.g.*, copy (Ctrl + C), paste (Ctrl + V), specific input). We detail our annotation process in subsection A.3.

---

[1]https://www.notion.so/

Static

Which web browser is used and which website is **prominently featured** before searching for 'office'?

Dynamic 1

After moving the Steam window to the center, what did the user do **next** in the Edge browser?

Dynamic 2

What would be the likely **next action** the user performs after searching for 'office' on the web browser 'Bing'?

Conversation

- **User 1:** Can you minimize the OBS for a better view of the browser?
- **Assistant 1:** Certainly, the OBS application has been minimized, providing a clear view of the Edge browser.
- **User 2:** Great, now can you search for Microsoft Office in the Edge browser?
- **Assistant 2:** Of course, a new tab has been opened in the Edge browser ⋯ The Bing search results for 'office' are now displayed.

Reasoning

If the user needs to record gameplay footage next, which application should they interact with and what would be their first step?
- **A.** They should open the Steam application and click on the 'STORE' tab.
- **B.** They should open the Edge browser and search for 'game recording software'.
- **C.** They should reopen the OBS application and click on 'Start Recording'.
- **D.** They should access the Windows Start menu and search for 'Camera' app.

Figure 5: An example in multi-window GUI scene as a case study.

2.3 GUI Tasks Generation from Human-MLLM Collaboration

Drawing insights from prior research (Dekoninck et al., 2024), we develop a Human-MLLM collaboration pipeline to annotate captions and diverse types of QA specifically tailored for GUI comprehension. The process involves inputting an instructional prompt, a comprehensive description, key information (*e.g.*, system or application), and a sequence of human-annotated keyframes into GPT-4V. As depicted in Table 12, GUI-WORLD features various question types, detailed as follows:

▷ **Detailed and Summarized Captioning:** This task challenges basic GUI knowledge and multimodal perception, also addressing the deficiency of detailed GUI content in video-caption pairs. Initially, GPT-4V generates two distinct descriptions for each video: one concentrating on fine-grained details and the other on overall information. Furthermore, GPT-4V provides a succinct summary, highlighting core operations and overarching objectives in the video.

▷ **Static GUI Content:** This task challenges MLLM with textual, layout, and iconographic analysis of static GUI content. We instruct GPT-4V to generate free-form queries with a golden answer concerning static GUI elements or specific scenes that recur in more than two keyframes, ensuring their consistent presence in the video. Additionally, GPT-4V also crafts QA pairs that evaluate inferential skills in static content, focusing on interrelations among icons or textual information.

▷ **Dynamic and Sequential GUI Content:** This task concentrates on temporal content in GUI video, such as dynamically changing interfaces, and aims to elucidate the sequential information and reasoning chains within GUI content. We direct GPT-4V to identify consistently changing elements to create queries for dynamic content. Moreover, predictive tasks are formulated on order and temporal relation in provided sequential images, challenging agents to anticipate future events or states.

Table 3: The overall performance in six GUI scenarios for MCQA and Free-form queries. 'MC' means Multiple-Choice QA and 'Free' represents the average score of all free-form and conversational queries.

	Models	Software		Website		XR		Multi		IOS		Android		Avg.	
		MC	Free	MC	Free	MC	Free	MC	Free	MC	Free	MC	Free	MC	Free
Image LLMs	LLaVA-OV-7B	56.9%	2.641	48.4%	2.588	59.6%	2.709	52.9%	2.306	58.1%	2.717	24.3%	2.675	50.0%	2.606
	Gemini-Pro-1.5	82.9%	3.385	79.2%	3.412	83.3%	3.108	**83.4%**	3.246	80.3%	3.467	78.5%	3.168	81.3%	3.298
	Qwen-VL-Max	75.8%	2.651	75.5%	2.698	77.6%	2.373	66.9%	2.490	74.3%	2.633	74.2%	2.559	74.0%	2.568
	GPT-4V	86.0%	3.520	79.8%	3.655	83.4%	3.265	76.9%	3.449	79.9%	3.453	81.3%	3.466	81.2%	3.469
	GPT-4o	**86.5%**	**3.644**	**83.3%**	**3.740**	**84.3%**	**3.285**	81.1%	**3.654**	**83.3%**	**3.558**	**90.0%**	**3.561**	**84.8%**	**3.573**
Video LLMs	ChatUnivi	28.4%	2.389	22.2%	2.349	20.6%	2.161	17.5%	2.275	22.6%	2.337	23.0%	2.390	22.4%	2.317
	Minigpt4Video	18.9%	1.475	15.3%	1.520	16.3%	1.362	15.4%	1.457	20.1%	1.501	14.6%	1.342	16.8%	1.443
	VideoChat2	45.5%	2.144	42.6%	2.221	44.0%	2.005	40.4%	2.222	40.2%	2.169	44.7%	2.119	42.9%	2.147
	Video-LLaVA	52.9%	2.290	52.4%	2.410	44.2%	2.258	45.9%	2.329	49.7%	2.319	51.3%	2.259	49.4%	2.311
	GUI-Vid	**59.9%**	**2.847**	**54.1%**	**2.957**	**55.6%**	**2.764**	**52.9%**	**2.861**	**51.8%**	**2.773**	**53.4%**	**2.572**	**54.6%**	**2.796**

In the last stage, human annotators will follow the guideline in subsection A.3 and carefully review the entire video and MLLM-generated QA pairs to correct inaccuracies and hallucinations, as well as supplement information for both questions and answers to **make these tasks more challenging**.

3 EXPERIMENTS AND ANALYSIS

3.1 EXPERIMENTAL SETUPS

Models.[2]   We conduct evaluations on four of the most popular vision LLMs: GPT-4V(ision) (OpenAI, 2023), GPT-4o (OpenAI, 2024), Qwen-VL-Max (Bai et al., 2023), LLaVA-OV-7B (Li et al., 2024a), and Gemini-Pro-1.5 (Team et al., 2023). Additionally, we test the effect of different vision inputs on GPT-4o, using no input, low and high-resolution settings, as well as without providing images, to further assess how resolution influences performance. Each model's responses employ a three-step Chain-of-Thought (CoT) (Wei et al., 2022) process, i.e., *'Describe-Analyze-Answer'*, to evaluate their peak performance. Additionally, we assessed four advanced video LLMs—ChatUnivi (Jin et al., 2023), Minigpt4-video (Ataallah et al., 2024), Videochat2 (Li et al., 2023c), VideoLLaVA (Lin et al., 2023a) —for their performance on GUI content. Detailed experimental setups are referred to Appendix C.

Evaluation Metrics.   To assess free-form questions and multiple-round conversations, we utilize the LLM-as-a-Judge methodology, which assigns a similarity score ranging from 1 to 5 between MLLM's response and a predefined golden answer, already validated by previous studies (Zheng et al., 2023; Liu et al., 2023d; Chen et al., 2024a). For multiple-choice questions, we measure performance using accuracy as the primary evaluation metric.

Keyframe Extraction.   We benchmark on three keyframe selection settings: (1) *Linspave*, where frames are evenly sampled at fixed time intervals within a video; (2) *Program*, with programmatic method Katna (KeplerLab, 2023); (3) *Model-based*, where leverage pre-trained vision representation from VIP (Ma et al., 2022) and R3M (Nair et al., 2022) to form UVD (Zhang et al., 2024d); and (4) *Human*, where humans select keyframes during the annotation process. **We use *Human* setting for ImageLLMs in our main experiment with an average of 6.719 frames (Table 2). For all other settings, we input 10 frames into each MLLM.**

Additional Information Integration.   To investigate the effectiveness of integrating image-caption models for LLMs—typically employed in natural videos—and the helpfulness of textual GUI content in accomplishing GUI-oriented tasks, we implement three experimental settings: Detailed Caption, Concise Caption, and Vision + Detailed Caption. GPT-4V is utilized to provide captions of these keyframes, integrating human annotators' operational intents to more accurately describe each frame, being validated in subsection A.3.

---

[2]Given that GPT-4V was announced to be deprecated, we used GPT-4o to conduct some ablation studies instead of GPT-4V, aiming to ensure our results provide longer-term reference value.

Table 4: Overall performance in six GUI scenarios for MCQA and Free-form queries. 'D.C.' means detailed caption, and 'C.C.' means concise caption, and ✘ means no vision input.

Models	Setting		Software		Website		XR		Multi		IOS		Android		Avg.	
	Vision	Text	MC	Free	MC	Free	MC	Free	MC	Free	MC	Free	MC	Free	MC	Free
GPT-4V	✘	D.C.	**85.0%**	3.350	83.1%	3.380	82.3%	3.056	**84.2%**	3.358	**81.6%**	2.751	81.7%	3.427	83.0%	3.316
	✘	C.C.	80.7%	3.028	72.2%	3.025	82.8%	2.809	81.3%	3.160	76.5%	2.868	76.4%	2.939	78.3%	2.971
	✔	D.C.	82.5%	**3.494**	83.2%	**3.682**	85.9%	**3.191**	83.9%	**3.617**	80.9%	**3.516**	84.9%	**3.758**	**83.5%**	**3.543**

Table 5: Detailed scores for free-form tasks in the software-related scenarios. 'Dyn.' refers to queries on dynamic GUI content.

	Models	Caption		Complex Tasks		Conversation		Average
		Concise	Detailed	Static	Dyn.	Round 1	Round 2	
Image LLMs	LLaVA-OV-7B	2.149	1.762	1.868	2.448	2.947	3.492	2.641
	Gemini-Pro-1.5	3.306	**3.035**	2.945	3.093	3.573	3.790	3.298
	Qwen-VL-Max	2.474	1.711	2.137	2.433	3.223	3.257	2.651
	GPT-4V	3.352	2.509	3.053	3.229	3.928	4.163	3.520
	GPT-4o	**4.048**	3.028	**3.125**	**3.340**	**4.129**	**4.318**	**3.644**
Video LLMs	ChatUnivi	1.587	1.240	1.705	2.090	2.698	**3.366**	2.389
	Minigpt4Video	1.246	1.073	1.249	1.455	1.494	1.719	1.475
	VideoChat2	1.992	1.312	1.812	1.920	2.342	2.720	2.144
	Video-LLaVA	1.519	1.241	1.657	1.959	2.587	3.293	2.290
	GUI-Vid	**3.562**	**2.058**	**2.376**	**2.763**	**3.080**	3.260	**2.847**

Figure 6: Fine-grained performance of GPT-4V in each GUI scenario (w.o. Android).

3.2 EMPIRICAL RESULTS

Commercial Vision LLMs outperform Open-source Video LLMs in Zero-shot Settings. Commercial vision LLMs, notably GPT-4V and GPT-4o, consistently outperform open-source video LLMs in zero-shot settings. As detailed in Table 3, GPT-4o exhibits superior performance across all GUI scenarios in complex tasks, reflected in its high scores in both multiple-choice and free-form queries, with an average of 84.8% and 3.573. Similarly, Gemini demonstrates strong capabilities in captioning and descriptive tasks within software and iOS environments, scoring 2.836 and 2.936, respectively, as shown in Table 22. Further analysis (Figure 6) reveals that GPT-4V excels in applications with minimal textual content and simple layouts, such as TikTok, health apps, and GitHub. In contrast, its performance drops in more intricate applications like Microsoft ToDo and XR software. As for video LLMs, their significantly poorer performance is attributed to two main factors: their inability to accurately interpret GUI content from user inputs and a lack of sufficient GUI-oriented pre-training, which is evident from their inadequate performance in basic captioning and description tasks. See Appendix D for other metrics and detailed fine-grained performance.

Dynamic GUI Tasks Continue to Challenge MLLMs. In the fine-grained tasks depicted in Table 5, GPT-4V and GPT-4o excel with dynamic GUI content and conversational tasks but struggle with providing detailed descriptions for entire videos and static content. This discrepancy is attributed to minor variations in GUI that significantly impact its semantic meaning. Enhancing the number of keyframes and the granularity of perception might mitigate these issues. Among video LLMs, ChatUnivi excels in conversational tasks by effectively leveraging contextual nuances, particularly in subsequent rounds, yet it underperforms in caption tasks. In contrast, GUI-Vid demonstrates proficiency in dynamic tasks but falls short in both captioning and static content. This gap is linked to

Table 6: Performance comparison of keyframe selection methods for GPT-4o: *Model-based* keyframe identifiers from embodied AI demonstrate comparable performance to *human-selected* keyframes.

Settings	Caption		Complex Tasks		Conversation		Average
	Concise	Detailed	Static	Dyn.	Round 1	Round 2	
Human	3.911	3.031	3.131	**3.318**	**3.981**	**4.132**	3.573
Program	3.643	2.764	2.872	3.052	3.702	3.837	3.300
Linspace	3.749	2.941	3.000	3.077	3.687	3.843	3.440
UVD+vip	3.954	3.105	3.321	3.219	3.944	4.107	3.581
UVD+r3m	**3.972**	**3.121**	**3.352**	3.243	3.975	4.119	**3.612**

Table 7: The improved performance with higher resolution inputs demonstrates the critical role of vision input in GUI-related tasks.

Setting	Caption		Complex Tasks		Conversation		Average
	Concise	Detailed	Static	Dyn.	Round 1	Round 2	
w/o Vision	2.187	1.872	2.486	2.979	3.760	4.059	2.891
Low Resolution	3.672	2.794	2.869	3.150	3.783	4.041	3.394
High Resolution	**3.911**	**3.031**	**3.131**	**3.318**	**3.981**	**4.132**	**3.574**

deficiencies in backbone pretraining, which lacked comprehensive GUI content crucial for effective vision-text alignment, as evidenced by its poor performance in simple caption task shown in Table 22 and an instruction tuning process failed to fully address these shortcomings.

Vision Perception is Important to Dynamic GUI content. As demonstrated in Table 7, integrating detailed textual information slightly outperforms purely vision-based inputs or detailed captions, akin to a Chain of Thought (CoT) (Wei et al., 2022) setting. Surprisingly, GPT-4V excels in caption tasks with just detailed captions, providing insights on enhancing specific GUI-oriented tasks through additional textual information. However, it still falls short in more challenging tasks, such as retrieving static or dynamic content. This underscores the critical role of visual perception in GUI environments, where even minor changes can significantly impact outcomes.

Keyframe Selection is Important for GUI-oriented Tasks. Our experiments demonstrate that *model-based* keyframe identifiers, originally developed for embodied AI applications, perform competitively with *human-selected* across both basic tasks (*e.g.*, caption) and complex tasks (static and dynamic analysis). As shown in Table 6, GPT-4o exhibits significant performance improvements when utilizing these robotics-inspired model-based keyframe identifiers, with the UVD+VIP approach achieving optimal results. These findings suggest the potential to replace manual keyframe selection with automated approaches. Further analysis reveals that embodied AI keyframe identifiers successfully capture semantic transitions in GUI content, while *linspace* and *program*-based selection methods fail to do so, highlighting their particular suitability for GUI-oriented tasks. The substantial performance gaps observed between different selection methods underscore the critical importance of keyframe selection in this domain.

4 EXPLORING AND IMPROVING VIDEOLLMS GUI AGENT

4.1 METHOD: PROGRESSIVE ENHANCEMENT

We introduce our strategy to enhance the GUI-oriented capabilities of current MLLMs on both static and dynamic GUI content. Inspired by previous studies (Lai et al., 2024; Li et al., 2023b), we structure our methodology into two distinct fine-tuning stages, as illustrated in Figure 7. Initially, we fine-tune the MLLM on simpler tasks, such as description queries and captioning exercises, to instill a basic understanding of GUI elements. Subsequently, building on this foundation, the second stage aims to augment the MLLM's proficiency with more complex and challenging tasks. Our fine-tuning is all based on the Supervised Fine-Tuning (SFT): $\mathcal{L}_{\text{SFT}}(\pi_\theta) = -\mathbb{E}_{(x,y)\sim\mathcal{D}}[\log \pi_\theta(y \mid x)]$, where x is the input, y is LLMs' output, and π_θ denotes the model parameters that need to be optimized.

Stage-1: Learning Preliminary for GUI Content. The initial phase focuses on aligning GUI content with a pre-trained vision encoder and a base LLM, utilizing GUI videos accompanied by detailed descriptions and captions. This phase aims to embed a robust understanding of fundamental GUI concepts and terminology within the MLLM. By engaging the model in basically captioning various GUI components, the model learns to recognize and articulate the functionalities and visual characteristics of these elements, thereby laying a solid groundwork for GUI knowledge.

Figure 7: An overview of our fine-tuning architecture, focusing on *1)* GUI content alignment and *2)* GUI-oriented tasks instruction tuning.

Table 8: The overall results for ablation study on GUI-Vid finetuning. F.K. and E.K. mean keyframes during the finetuning and evaluation process respectively. **I.**: Image, **V.**: Video.

Baseline	F.K.	E.K.	Data I.	V.	Software MC	Free	Website MC	Free	XR MC	Free	Multi MC	Free	IOS MC	Free	Android MC	Free	Avg. MC	Free
Baseline	-	8	-	-	45.5%	2.144	42.6%	2.221	44.0%	2.005	40.4%	2.222	40.2%	2.169	44.7%	2.119	42.9%	2.147
	-	16	-	-	45.1%	2.144	41.8%	2.240	41.0%	2.007	40.7%	2.238	39.9%	2.138	44.7%	2.147	42.2%	2.154
GUI-Vid	8	8	✘	✔	58.3%	2.709	53.6%	2.817	62.2%	2.626	**54.2%**	2.627	53.1%	2.708	54.9%	2.501	56.0%	2.665
			✔	✔	**59.9%**	**2.856**	54.1%	2.925	59.0%	2.751	52.1%	2.837	50.0%	2.756	54.0%	2.571	54.8%	2.782
	16		✘	✔	59.0%	2.709	**55.1%**	2.821	**62.8%**	2.645	53.3%	2.624	**55.5%**	2.727	**55.7%**	2.501	**56.9%**	2.671
			✔	✔	**59.9%**	2.847	54.1%	**2.957**	55.6%	**2.764**	52.9%	**2.861**	51.8%	**2.772**	53.4%	**2.572**	54.6%	**2.796**

Stage-2: Mastering Advanced GUI Capability. Building on the foundational knowledge established in Stage 1, the second stage focuses on advancing the MLLM's proficiency in interacting with GUI elements through more complex tasks. These tasks are designed to simulate real-world scenarios that the MLLM might encounter in GUI environments, which include predicting based on image sequences, engaging in conversations, retrieving both static and dynamic GUI elements, and performing reasoning tasks.

As illustrated in Figure 7, We employ the two-stage training architecture utilizing VideoChat2 (Li et al., 2023b) as our foundational model. Initially, videos and images are encoded using the UMT-L visual encoder (Li et al., 2023d). Subsequently, a QFormer compresses visual tokens into a smaller set of query tokens. Drawing inspiration from (Dai et al., 2023), we enhance the QFormer (Zhang et al., 2024c) by integrating instructions to enable it to extract visual representations pertinent to the given instructions. Additionally, we apply low-rank adaptation (LoRA (Hu et al., 2021)) to base LLM. This model is concurrently fine-tuned with the visual encoder and QFormer using a Vision-grounded Text Generation (VTG) loss: $\mathcal{L}_{\text{VTG}}(\theta) = -\mathbb{E}\left[\log p(y|v;\theta)\right]$, where v represents the visual tokens derived from the QFormer, and y represents the text output grounded in the visual context.

4.2 EXPERIMENT

Experiment Setups. We use two dataset settings to fine-tune GUI-Vid, one with video only, and the other with video and image, detailed in Appendix C. We also vary the number of keyframes (8, 16) fed into GUI-Vid. All our experiments were conducted on a server equipped with dual A800 and dual 4090 GPUs.

Supreme Enhancement of GUI-Vid on Graphic-based Interface After Fine-tuning on GUI-WORLD. As a pioneering study in training video LLMs as screen agents, GUI-Vid significantly outperforms the baseline model, showing an average improvement of 30% across various tasks and GUI scenarios, even surpassing the commercial vision LLM, Qwen-VL-Max. This enhancement is particularly notable in captioning and dynamic task that reason over image sequences, where GUI-Vid matches the performance of GPT-4V and Gemini-Pro. As depicted in Table 8, our two ablation studies during the fine-tuning phase demonstrate that utilizing GUI image-text captioning data significantly enhances the model's preliminary understanding of GUI elements, outperforming training that relies solely on videos. Additionally, an increased number of keyframes correlates with improved performance across various scenarios, notably in environments featuring multiple windows and software applications. As shown in Figure 8, our two-stage progressive fintuning significantly enhances the performance in all GUI scenarios.

Figure 8: Two stages of progressive training enhance GUI ability.

Correlation between GUI understanding and other mainstream GUI tasks. In our explorative experiments, GUI-Vid still fails in GUI operating tasks via code generation like GPT-4o performing in Cradle (Tan et al., 2024), which is due to the baseline LLM's weak performance and the challenges of code generation instruction fine-tuning. To further demonstrate how GUI understanding capability enhances mainstream GUI-related tasks, including generating operational code (Cheng et al., 2024) and providing chat assistance (Hong et al., 2024), we conduct analysis as follows (detailed in Appendix D):

Table 9: GUI-vid wins more user selection in GUI-related chat assistant experiment.

Scenarios	GUI-Vid	Tie	VideoChat2
Software	**82.7%**	13.3%	4.0%
Website	**86.0%**	12.0%	2.0%
XR	**88.0%**	8.7%	3.3%
Multi	**85.3%**	10.0%	8.7%
IOS	**92.0%**	6.0%	2.0%
Android	**82.0%**	16.0%	2.0%
Average	**86.0%**	11.0%	3.7%

- Comparing GUI-world benchmark results with existing benchmarks (Xie et al., 2024; Qinghong Lin et al., 2024; Liu et al., 2024c) shows that stronger understanding ability correlates with better agent performance (Table 17).
- In a human evaluation study using 180 videos across 6 scenarios, annotators preferred responses from GUI-understanding-trained models when acting as GUI agents (Table 9).

5 RELATED WORK

MLLM-based Agents for GUI. Building upon the significant advancements in LLMs (Achiam et al., 2023; Meta, 2023a;b; ai, 2024) and advanced modality-mixing technologies (Li et al., 2023a; Alayrac et al., 2022), groundbreaking MLLMs such as GPT-4V (OpenAI, 2023) and Gemini-Pro (Team et al., 2023), along with open-source MLLMs like the LLaVA-1.6 series (Liu et al., 2023b;a), CogVLM (Wang et al., 2023b), and Qwen-VL series (Bai et al., 2023), have shown outstanding performance across various tasks (Yu et al.; Liu et al., 2023e; Chen et al., 2024b; Wu et al., 2023; Wake et al., 2023; Zhang et al., 2024b; Zhao et al., 2024; Gui et al., 2024). Venturing beyond text and single image, several studies are now exploring the integration of video modalities for tasks requiring dynamic or sequential visual content (Jin et al., 2023; Li et al., 2023b; Maaz et al., 2023; Lin et al., 2023a). In the GUI domain, leveraging the robust vision perception capabilities of MLLMs, applications such as WebAgents (Hong et al., 2024; Zhang et al., 2024a; Zheng et al., 2024b) and Mobile Agents (Wang et al., 2023a; You et al., 2024; Wang et al., 2021; Li et al., 2020b) have gained popularity for handling everyday tasks like navigation and VQA. Frontier research is also investigating the use of MLLMs as general control agents, such as in playing computer games (Tan et al., 2024; Lin et al., 2023b) and serving as OS co-pilots (Song et al., 2024; Xie et al., 2024), paving the way for more complex GUI operations.

GUI Benchmark & Dataset. Building upon the foundational work of Rico (Deka et al., 2017), the first mobile GUI video dataset, and AitW (Rawles et al., 2023), which features 715k episodes of sequential images, research has extensively covered mobile (Sun et al., 2022; Li et al., 2020a; Zhang et al., 2023) and web GUI environments (Lù et al., 2024; Zhou et al., 2023; Yao et al., 2022; Koh et al., 2024; Liu et al., 2024b). Mind2Web (Deng et al., 2024) stands out in web-based datasets with over 2,000 tasks from 137 websites across 31 domains. Advances continue into desktop GUIs with new toolkits (Zheng et al., 2024b), benchmarks (Kapoor et al., 2024; Mialon et al., 2023), and frameworks (Zheng et al., 2024a; Liu et al., 2023c; Niu et al., 2024). Research on GUI also transfers from comprehending single images in a static workspace (Hong et al., 2024) to sequential operations or multi-hop scenarios (Xie et al., 2024; Zhang et al., 2024e), challenging the understanding and operation capability of these powerful models.

6 CONCLUSION

In this paper, we have introduced GUI-WORLD, a comprehensive GUI-oriented video dataset designed to benchmark and enhance understanding of virtual interfaces, especially sequential and dynamic tasks. This dataset extensively covers six scenarios and various tasks, addressing the previous research gap in comprehensively evaluating models' capabilities in graphic-based understanding. We conduct extensive benchmarks on leading MLLMs and the first video-LLM-based Agent 'GUI-Vid' fine-tuned on GUI-WORLD specifically for GUI-oriented content, achieving results comparable to top-performing models, providing detailed insights into enhancing GUI-related capabilities. We believe our work offers valuable insights for future research in dynamic GUI content understanding.

REFERENCES

Meta quest 3: New mixed reality vr headset. https://www.meta.com/quest/quest-3.

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*, 2023.

Mistral ai. Mistral ai, 2024. https://mistral.ai/company/.

Jean-Baptiste Alayrac, Jeff Donahue, Pauline Luc, Antoine Miech, Iain Barr, Yana Hasson, Karel Lenc, Arthur Mensch, Katherine Millican, Malcolm Reynolds, et al. Flamingo: a visual language model for few-shot learning. *Advances in neural information processing systems*, 35:23716–23736, 2022.

Apple. Apple vision pro. https://www.apple.com/apple-vision-pro/, 2024.

Kirolos Ataallah, Xiaoqian Shen, Eslam Abdelrahman, Essam Sleiman, Deyao Zhu, Jian Ding, and Mohamed Elhoseiny. Minigpt4-video: Advancing multimodal llms for video understanding with interleaved visual-textual tokens. *arXiv preprint arXiv:2404.03413*, 2024.

Jinze Bai, Shuai Bai, Shusheng Yang, Shijie Wang, Sinan Tan, Peng Wang, Junyang Lin, Chang Zhou, and Jingren Zhou. Qwen-vl: A frontier large vision-language model with versatile abilities. *arXiv preprint arXiv:2308.12966*, 2023.

Tony Beltramelli. pix2code: Generating code from a graphical user interface screenshot. In *Proceedings of the ACM SIGCHI symposium on engineering interactive computing systems*, pp. 1–6, 2018.

Dongping Chen, Ruoxi Chen, Shilin Zhang, Yinuo Liu, Yaochen Wang, Huichi Zhou, Qihui Zhang, Yao Wan, Pan Zhou, and Lichao Sun. Mllm-as-a-judge: Assessing multimodal llm-as-a-judge with vision-language benchmark. *arXiv preprint arXiv:2402.04788*, 2024a.

Lin Chen, Jinsong Li, Xiaoyi Dong, Pan Zhang, Yuhang Zang, Zehui Chen, Haodong Duan, Jiaqi Wang, Yu Qiao, Dahua Lin, et al. Are we on the right way for evaluating large vision-language models? *arXiv preprint arXiv:2403.20330*, 2024b.

Wentong Chen, Junbo Cui, Jinyi Hu, Yujia Qin, Junjie Fang, Yue Zhao, Chongyi Wang, Jun Liu, Guirong Chen, Yupeng Huo, et al. Guicourse: From general vision language models to versatile gui agents. *arXiv preprint arXiv:2406.11317*, 2024c.

Kanzhi Cheng, Qiushi Sun, Yougang Chu, Fangzhi Xu, Yantao Li, Jianbing Zhang, and Zhiyong Wu. Seeclick: Harnessing gui grounding for advanced visual gui agents. *arXiv preprint arXiv:2401.10935*, 2024.

Wenliang Dai, Junnan Li, Dongxu Li, Anthony Meng Huat Tiong, Junqi Zhao, Weisheng Wang, Boyang Albert Li, Pascale Fung, and Steven C. H. Hoi. Instructblip: Towards general-purpose vision-language models with instruction tuning. *ArXiv*, abs/2305.06500, 2023. URL https://api.semanticscholar.org/CorpusID:258615266.

Biplab Deka, Zifeng Huang, Chad Franzen, Joshua Hibschman, Daniel Afergan, Yang Li, Jeffrey Nichols, and Ranjitha Kumar. Rico: A mobile app dataset for building data-driven design applications. In *Proceedings of the 30th annual ACM symposium on user interface software and technology*, pp. 845–854, 2017.

Jasper Dekoninck, Marc Fischer, Luca Beurer-Kellner, and Martin Vechev. Understanding large language models through the lens of dataset generation, 2024. URL https://openreview.net/forum?id=miGpIhquyB.

Xiang Deng, Yu Gu, Boyuan Zheng, Shijie Chen, Sam Stevens, Boshi Wang, Huan Sun, and Yu Su. Mind2web: Towards a generalist agent for the web. *Advances in Neural Information Processing Systems*, 36, 2024.

Yi Gui, Zhen Li, Yao Wan, Yemin Shi, Hongyu Zhang, Yi Su, Shaoling Dong, Xing Zhou, and Wenbin Jiang. Vision2ui: A real-world dataset with layout for code generation from ui designs. *arXiv preprint arXiv:2404.06369*, 2024.

Wenyi Hong, Weihan Wang, Qingsong Lv, Jiazheng Xu, Wenmeng Yu, Junhui Ji, Yan Wang, Zihan Wang, Yuxiao Dong, Ming Ding, et al. Cogagent: A visual language model for gui agents. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 14281–14290, 2024.

Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. Lora: Low-rank adaptation of large language models. *arXiv preprint arXiv:2106.09685*, 2021.

Jiangyong Huang, Silong Yong, Xiaojian Ma, Xiongkun Linghu, Puhao Li, Yan Wang, Qing Li, Song-Chun Zhu, Baoxiong Jia, and Siyuan Huang. An embodied generalist agent in 3d world. *arXiv preprint arXiv:2311.12871*, 2023.

Peng Jin, Ryuichi Takanobu, Caiwan Zhang, Xiaochun Cao, and Li Yuan. Chat-univi: Unified visual representation empowers large language models with image and video understanding. *arXiv preprint arXiv:2311.08046*, 2023.

Rodrigo Funabashi Jorge, Márcio Eduardo Delamaro, Celso Gonçalves Camilo-Junior, and Auri Marcelo Rizzo Vincenzi. Test data generation based on gui: A systematic mapping. In *International Conference on Software Engineering Advances*, 2014. URL https://api.semanticscholar.org/CorpusID:64041598.

Raghav Kapoor, Yash Parag Butala, Melisa Russak, Jing Yu Koh, Kiran Kamble, Waseem Alshikh, and Ruslan Salakhutdinov. Omniact: A dataset and benchmark for enabling multimodal generalist autonomous agents for desktop and web. *arXiv preprint arXiv:2402.17553*, 2024.

KeplerLab. Katna - video to keyframes and video to image crops utility. https://github.com/keplerlab/katna, 2023. Accessed: 2024-09-07.

Jing Yu Koh, Robert Lo, Lawrence Jang, Vikram Duvvur, Ming Chong Lim, Po-Yu Huang, Graham Neubig, Shuyan Zhou, Ruslan Salakhutdinov, and Daniel Fried. Visualwebarena: Evaluating multimodal agents on realistic visual web tasks. *arXiv preprint arXiv:2401.13649*, 2024.

Ambreen Kousar, Saif Ur Rehman Khan, Shahid Hussain, M. Abdul Basit Ur Rahim, Wen-Li Wang, and Naseem Ibrahim. A systematic review on pattern-based gui testing of android and web apps: State-of-the-art, taxonomy, challenges and future directions. In *2023 25th International Multitopic Conference (INMIC)*, pp. 1–7, 2023. doi: 10.1109/INMIC60434.2023.10465949.

Ivans Kulesovs. ios applications testing. 2015. URL https://api.semanticscholar.org/CorpusID:59015994.

Hanyu Lai, Xiao Liu, Iat Long Iong, Shuntian Yao, Yuxuan Chen, Pengbo Shen, Hao Yu, Hanchen Zhang, Xiaohan Zhang, Yuxiao Dong, et al. Autowebglm: Bootstrap and reinforce a large language model-based web navigating agent. *arXiv preprint arXiv:2404.03648*, 2024.

Bo Li, Yuanhan Zhang, Dong Guo, Renrui Zhang, Feng Li, Hao Zhang, Kaichen Zhang, Yanwei Li, Ziwei Liu, and Chunyuan Li. Llava-onevision: Easy visual task transfer. *arXiv preprint arXiv:2408.03326*, 2024a.

Chunyuan Li, Cliff Wong, Sheng Zhang, Naoto Usuyama, Haotian Liu, Jianwei Yang, Tristan Naumann, Hoifung Poon, and Jianfeng Gao. Llava-med: Training a large language-and-vision assistant for biomedicine in one day. *Advances in Neural Information Processing Systems*, 36, 2024b.

Gang Li and Yang Li. Spotlight: Mobile ui understanding using vision-language models with a focus. *arXiv preprint arXiv:2209.14927*, 2022.

Junnan Li, Dongxu Li, Silvio Savarese, and Steven Hoi. Blip-2: Bootstrapping language-image pre-training with frozen image encoders and large language models. In *International conference on machine learning*, pp. 19730–19742. PMLR, 2023a.

KunChang Li, Yinan He, Yi Wang, Yizhuo Li, Wenhai Wang, Ping Luo, Yali Wang, Limin Wang, and Yu Qiao. Videochat: Chat-centric video understanding. *arXiv preprint arXiv:2305.06355*, 2023b.

Kunchang Li, Yali Wang, Yinan He, Yizhuo Li, Yi Wang, Yi Liu, Zun Wang, Jilan Xu, Guo Chen, Ping Luo, et al. Mvbench: A comprehensive multi-modal video understanding benchmark. *arXiv preprint arXiv:2311.17005*, 2023c.

Kunchang Li, Yali Wang, Yizhuo Li, Yi Wang, Yinan He, Limin Wang, and Yu Qiao. Unmasked teacher: Towards training-efficient video foundation models. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 19948–19960, 2023d.

Yang Li, Jiacong He, Xin Zhou, Yuan Zhang, and Jason Baldridge. Mapping natural language instructions to mobile ui action sequences. *arXiv preprint arXiv:2005.03776*, 2020a.

Yang Li, Gang Li, Luheng He, Jingjie Zheng, Hong Li, and Zhiwei Guan. Widget captioning: Generating natural language description for mobile user interface elements. *arXiv preprint arXiv:2010.04295*, 2020b.

Bin Lin, Yang Ye, Bin Zhu, Jiaxi Cui, Munan Ning, Peng Jin, and Li Yuan. Video-llava: Learning united visual representation by alignment before projection. *arXiv preprint arXiv:2311.10122*, 2023a.

Kevin Lin, Faisal Ahmed, Linjie Li, Chung-Ching Lin, Ehsan Azarnasab, Zhengyuan Yang, Jianfeng Wang, Lin Liang, Zicheng Liu, Yumao Lu, et al. Mm-vid: Advancing video understanding with gpt-4v (ision). *arXiv preprint arXiv:2310.19773*, 2023b.

Evan Zheran Liu, Kelvin Guu, Panupong Pasupat, Tianlin Shi, and Percy Liang. Reinforcement learning on web interfaces using workflow-guided exploration. In *International Conference on Learning Representations (ICLR)*, 2018. URL https://arxiv.org/abs/1802.08802.

Haotian Liu, Chunyuan Li, Yuheng Li, and Yong Jae Lee. Improved baselines with visual instruction tuning, 2023a.

Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning. In *NeurIPS*, 2023b.

Haotian Liu, Chunyuan Li, Yuheng Li, Bo Li, Yuanhan Zhang, Sheng Shen, and Yong Jae Lee. Llava-next: Improved reasoning, ocr, and world knowledge, January 2024a. URL https://llava-vl.github.io/blog/2024-01-30-llava-next/.

Junpeng Liu, Yifan Song, Bill Yuchen Lin, Wai Lam, Graham Neubig, Yuanzhi Li, and Xiang Yue. Visualwebbench: How far have multimodal llms evolved in web page understanding and grounding? *arXiv preprint arXiv:2404.05955*, 2024b.

Xiao Liu, Hanyu Lai, Hao Yu, Yifan Xu, Aohan Zeng, Zhengxiao Du, Peng Zhang, Yuxiao Dong, and Jie Tang. Webglm: Towards an efficient web-enhanced question answering system with human preferences. In *Proceedings of the 29th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, pp. 4549–4560, 2023c.

Xiao Liu, Xuanyu Lei, Shengyuan Wang, Yue Huang, Zhuoer Feng, Bosi Wen, Jiale Cheng, Pei Ke, Yifan Xu, Weng Lam Tam, et al. Alignbench: Benchmarking chinese alignment of large language models. *arXiv preprint arXiv:2311.18743*, 2023d.

Xiao Liu, Tianjie Zhang, Yu Gu, Iat Long Iong, Yifan Xu, Xixuan Song, Shudan Zhang, Hanyu Lai, Xinyi Liu, Hanlin Zhao, et al. Visualagentbench: Towards large multimodal models as visual foundation agents. *arXiv preprint arXiv:2408.06327*, 2024c.

Yuan Liu, Haodong Duan, Yuanhan Zhang, Bo Li, Songyang Zhang, Wangbo Zhao, Yike Yuan, Jiaqi Wang, Conghui He, Ziwei Liu, et al. Mmbench: Is your multi-modal model an all-around player? *arXiv preprint arXiv:2307.06281*, 2023e.

Xing Han Lù, Zdeněk Kasner, and Siva Reddy. Weblinx: Real-world website navigation with multi-turn dialogue. *arXiv preprint arXiv:2402.05930*, 2024.

Yecheng Jason Ma, Shagun Sodhani, Dinesh Jayaraman, Osbert Bastani, Vikash Kumar, and Amy Zhang. Vip: Towards universal visual reward and representation via value-implicit pre-training. *arXiv preprint arXiv:2210.00030*, 2022.

Muhammad Maaz, Hanoona Rasheed, Salman Khan, and Fahad Shahbaz Khan. Video-chatgpt: Towards detailed video understanding via large vision and language models. *arXiv preprint arXiv:2306.05424*, 2023.

Behrooz Mahasseni, Michael Lam, and Sinisa Todorovic. Unsupervised video summarization with adversarial lstm networks. In *Proceedings of the IEEE conference on Computer Vision and Pattern Recognition*, pp. 202–211, 2017.

Meta. Llama 2, 2023a. https://llama.meta.com/llama2.

Meta. Llama 3, 2023b. https://llama.meta.com/llama3.

Grégoire Mialon, Clémentine Fourrier, Craig Swift, Thomas Wolf, Yann LeCun, and Thomas Scialom. Gaia: a benchmark for general ai assistants. *arXiv preprint arXiv:2311.12983*, 2023.

Suraj Nair, Aravind Rajeswaran, Vikash Kumar, Chelsea Finn, and Abhinav Gupta. R3m: A universal visual representation for robot manipulation. *arXiv preprint arXiv:2203.12601*, 2022.

Hajime Nakajima, Takeshi Masuda, and Ikuya Takahashi. Gui ferret: Gui test tool to analyze complex behavior of multi-window applications. *2013 18th International Conference on Engineering of Complex Computer Systems*, pp. 163–166, 2013. URL https://api.semanticscholar.org/CorpusID:837553.

Runliang Niu, Jindong Li, Shiqi Wang, Yali Fu, Xiyu Hu, Xueyuan Leng, He Kong, Yi Chang, and Qi Wang. Screenagent: A vision language model-driven computer control agent. *arXiv preprint arXiv:2402.07945*, 2024.

OpenAI. Chatgpt, 2023. https://openai.com/product/chatgpt.

OpenAI. Openai models - gpt-4-vision. https://openai.com/research/gpt-4v-system-card, 2023.

OpenAI. Hello gpt-4o, May 2024. URL https://openai.com/index/hello-gpt-4o/. Accessed: 2024-06-06.

OpenCV. Opencv. https://opencv.org/.

Kevin Qinghong Lin, Linjie Li, Difei Gao, Qinchen WU, Mingyi Yan, Zhengyuan Yang, Lijuan Wang, and Mike Zheng Shou. Videogui: A benchmark for gui automation from instructional videos. *arXiv e-prints*, pp. arXiv–2406, 2024.

Philipp A. Rauschnabel, Reto Felix, Christian Hinsch, Hamza Shahab, and Florain Alt. What is xr? towards a framework for augmented and virtual reality. *Comput. Hum. Behav.*, 133:107289, 2022. URL https://api.semanticscholar.org/CorpusID:247861674.

Christopher Rawles, Alice Li, Daniel Rodriguez, Oriana Riva, and Timothy Lillicrap. Android in the wild: A large-scale dataset for android device control. *arXiv preprint arXiv:2307.10088*, 2023.

Brian K. Sanders, Yuzhong Shen, and Dennis A. Vincenzi. Understanding user interface preferences for xr environments when exploring physics and engineering principles. In *International Conference on Applied Human Factors and Ergonomics*, 2019. URL https://api.semanticscholar.org/CorpusID:197940610.

Zirui Song, Yaohang Li, Meng Fang, Zhenhao Chen, Zecheng Shi, and Yuan Huang. Mmac-copilot: Multi-modal agent collaboration operating system copilot. *arXiv preprint arXiv:2404.18074*, 2024.

Liangtai Sun, Xingyu Chen, Lu Chen, Tianle Dai, Zichen Zhu, and Kai Yu. Meta-gui: towards multi-modal conversational agents on mobile gui. *arXiv preprint arXiv:2205.11029*, 2022.

Weihao Tan, Ziluo Ding, Wentao Zhang, Boyu Li, Bohan Zhou, Junpeng Yue, Haochong Xia, Jiechuan Jiang, Longtao Zheng, Xinrun Xu, et al. Towards general computer control: A multimodal agent for red dead redemption ii as a case study. *arXiv preprint arXiv:2403.03186*, 2024.

Gemini Team, Rohan Anil, Sebastian Borgeaud, Jean-Baptiste Alayrac, Jiahui Yu, Radu Soricut, Johan Schalkwyk, Andrew M Dai, Anja Hauth, Katie Millican, et al. Gemini: a family of highly capable multimodal models. *arXiv preprint arXiv:2312.11805*, 2023.

Sagar Gubbi Venkatesh, Partha Talukdar, and Srini Narayanan. Ugif: Ui grounded instruction following. *arXiv preprint arXiv:2211.07615*, 2022.

Naoki Wake, Atsushi Kanehira, Kazuhiro Sasabuchi, Jun Takamatsu, and Katsushi Ikeuchi. Gpt-4v (ision) for robotics: Multimodal task planning from human demonstration. *arXiv preprint arXiv:2311.12015*, 2023.

Bryan Wang, Gang Li, Xin Zhou, Zhourong Chen, Tovi Grossman, and Yang Li. Screen2words: Automatic mobile ui summarization with multimodal learning. In *The 34th Annual ACM Symposium on User Interface Software and Technology*, pp. 498–510, 2021.

Bryan Wang, Gang Li, and Yang Li. Enabling conversational interaction with mobile ui using large language models. In *Proceedings of the 2023 CHI Conference on Human Factors in Computing Systems*, pp. 1–17, 2023a.

Junyang Wang, Haiyang Xu, Jiabo Ye, Ming Yan, Weizhou Shen, Ji Zhang, Fei Huang, and Jitao Sang. Mobile-agent: Autonomous multi-modal mobile device agent with visual perception. *arXiv preprint arXiv:2401.16158*, 2024.

Weihan Wang, Qingsong Lv, Wenmeng Yu, Wenyi Hong, Ji Qi, Yan Wang, Junhui Ji, Zhuoyi Yang, Lei Zhao, Xixuan Song, et al. Cogvlm: Visual expert for pretrained language models. *arXiv preprint arXiv:2311.03079*, 2023b.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, et al. Chain-of-thought prompting elicits reasoning in large language models. *Advances in neural information processing systems*, 35:24824–24837, 2022.

Chaoyi Wu, Jiayu Lei, Qiaoyu Zheng, Weike Zhao, Weixiong Lin, Xiaoman Zhang, Xiao Zhou, Ziheng Zhao, Ya Zhang, Yanfeng Wang, et al. Can gpt-4v (ision) serve medical applications? case studies on gpt-4v for multimodal medical diagnosis. *arXiv preprint arXiv:2310.09909*, 2023.

Tianbao Xie, Danyang Zhang, Jixuan Chen, Xiaochuan Li, Siheng Zhao, Ruisheng Cao, Toh Jing Hua, Zhoujun Cheng, Dongchan Shin, Fangyu Lei, et al. Osworld: Benchmarking multimodal agents for open-ended tasks in real computer environments. *arXiv preprint arXiv:2404.07972*, 2024.

An Yan, Zhengyuan Yang, Wanrong Zhu, Kevin Qinghong Lin, Linjie Li, Jianfeng Wang, Jianwei Yang, Yiwu Zhong, Julian J. McAuley, Jianfeng Gao, Zicheng Liu, and Lijuan Wang. Gpt-4v in wonderland: Large multimodal models for zero-shot smartphone gui navigation. *ArXiv*, abs/2311.07562, 2023. URL https://api.semanticscholar.org/CorpusID:265149992.

Xiang Yan, Syed Zulqarnain Gilani, Hanlin Qin, Mingtao Feng, Liang Zhang, and Ajmal Mian. Deep keyframe detection in human action videos. *arXiv preprint arXiv:1804.10021*, 2018.

Zhao Yang, Jiaxuan Liu, Yucheng Han, Xin Chen, Zebiao Huang, Bin Fu, and Gang Yu. Appagent: Multimodal agents as smartphone users. *arXiv preprint arXiv:2312.13771*, 2023a.

Zhengyuan Yang, Linjie Li, Jianfeng Wang, Kevin Lin, Ehsan Azarnasab, Faisal Ahmed, Zicheng Liu, Ce Liu, Michael Zeng, and Lijuan Wang. Mm-react: Prompting chatgpt for multimodal reasoning and action. *arXiv preprint arXiv:2303.11381*, 2023b.

Shunyu Yao, Howard Chen, John Yang, and Karthik Narasimhan. Webshop: Towards scalable real-world web interaction with grounded language agents. *Advances in Neural Information Processing Systems*, 35:20744–20757, 2022.

Shukang Yin, Chaoyou Fu, Sirui Zhao, Ke Li, Xing Sun, Tong Xu, and Enhong Chen. A survey on multimodal large language models. *National Science Review*, pp. nwae403, 2024.

Keen You, Haotian Zhang, Eldon Schoop, Floris Weers, Amanda Swearngin, Jeffrey Nichols, Yinfei Yang, and Zhe Gan. Ferret-ui: Grounded mobile ui understanding with multimodal llms. *arXiv preprint arXiv:2404.05719*, 2024.

Weihao Yu, Zhengyuan Yang, Linjie Li, Jianfeng Wang, Kevin Lin, Zicheng Liu, Xinchao Wang, and Lijuan Wang. Mm-vet: Evaluating large multimodal models for integrated capabilities. In *Forty-first International Conference on Machine Learning*.

Haolan Zhan, Yujin Huang, Di Liu, et al. Pairwise gui dataset construction between android phones and tablets. *Advances in Neural Information Processing Systems*, 36, 2024.

Chaoyun Zhang, Liqun Li, Shilin He, Xu Zhang, Bo Qiao, Si Qin, Minghua Ma, Yu Kang, Qingwei Lin, Saravan Rajmohan, et al. Ufo: A ui-focused agent for windows os interaction. *arXiv preprint arXiv:2402.07939*, 2024a.

Danyang Zhang, Hongshen Xu, Zihan Zhao, Lu Chen, Ruisheng Cao, and Kai Yu. Mobile-Env: An evaluation platform and benchmark for llm-gui interaction. *CoRR*, abs/2305.08144, 2023. URL https://arxiv.org/abs/2305.08144.

Qihui Zhang, Chujie Gao, Dongping Chen, Yue Huang, Yixin Huang, Zhenyang Sun, Shilin Zhang, Weiye Li, Zhengyan Fu, Yao Wan, and Lichao Sun. LLM-as-a-coauthor: Can mixed human-written and machine-generated text be detected? In Kevin Duh, Helena Gomez, and Steven Bethard (eds.), *Findings of the Association for Computational Linguistics: NAACL 2024*, pp. 409–436, Mexico City, Mexico, June 2024b. Association for Computational Linguistics. URL https://aclanthology.org/2024.findings-naacl.29.

Qiming Zhang, Jing Zhang, Yufei Xu, and Dacheng Tao. Vision transformer with quadrangle attention. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2024c.

Zichen Zhang, Yunshuang Li, Osbert Bastani, Abhishek Gupta, Dinesh Jayaraman, Yecheng Jason Ma, and Luca Weihs. Universal visual decomposer: Long-horizon manipulation made easy. In *2024 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 6973–6980. IEEE, 2024d.

Ziniu Zhang, Shulin Tian, Liangyu Chen, and Ziwei Liu. Mmina: Benchmarking multihop multimodal internet agents. *arXiv preprint arXiv:2404.09992*, 2024e.

Wei Zhao, Zhitao Hou, Siyuan Wu, Yan Gao, Haoyu Dong, Yao Wan, Hongyu Zhang, Yulei Sui, and Haidong Zhang. NL2Formula: Generating spreadsheet formulas from natural language queries. In Yvette Graham and Matthew Purver (eds.), *Findings of the Association for Computational Linguistics: EACL 2024*, pp. 2377–2388, St. Julian's, Malta, March 2024. Association for Computational Linguistics. URL https://aclanthology.org/2024.findings-eacl.158.

Boyuan Zheng, Boyu Gou, Jihyung Kil, Huan Sun, and Yu Su. Gpt-4v (ision) is a generalist web agent, if grounded. *arXiv preprint arXiv:2401.01614*, 2024a.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric Xing, et al. Judging llm-as-a-judge with mt-bench and chatbot arena. *Advances in Neural Information Processing Systems*, 36:46595–46623, 2023.

Longtao Zheng, Zhiyuan Huang, Zhenghai Xue, Xinrun Wang, Bo An, and Shuicheng Yan. Agentstudio: A toolkit for building general virtual agents. *arXiv preprint arXiv:2403.17918*, 2024b.

Shuyan Zhou, Frank F Xu, Hao Zhu, Xuhui Zhou, Robert Lo, Abishek Sridhar, Xianyi Cheng, Yonatan Bisk, Daniel Fried, Uri Alon, et al. Webarena: A realistic web environment for building autonomous agents. *arXiv preprint arXiv:2307.13854*, 2023.

Wangjiang Zhu, Jie Hu, Gang Sun, Xudong Cao, and Yu Qiao. A key volume mining deep framework for action recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 1991–1999, 2016.

Part I

Appendix

Table of Contents

Table 10: **Summary of main experiments and results.** *Task* and *Scenario* is two primary axis that we consider most important to show the evaluation results. The *task-specific* analysis shows performance across different capabilities such as image captioning, complex QA, and conversation; *scenario-specific* analysis evaluates performance across various application domains such as XR, iOS, etc.

Table	Objective	Category
Table 3	Comparative analysis of model performance across six GUI scenarios	Scenario-specific
Table 4	Impact of textual information incorporation on GUI understanding	Scenario-specific
Table 5	Fine-grained evaluation of free-form responses in software tasks	Task-specific
Table 6	Assessment of different keyframe selection strategies	Task-specific
Table 7	Analysis of vision input modalities and quality effects	Task-specific
Table 8	Comprehensive evaluation of GUI-Vid and its components	Scenario-specific

A DETAILS OF DATASET CONSTRUCTION

A.1 SIX MAIN GUI CATEGORIES

In earlier endeavors pertaining to GUI, such as those involving GUI testing (Kousar et al., 2023; Jorge et al., 2014; Kulesovs, 2015), the focus was segmented into GUIs for Website, Software, IOS and Android platforms. However, as a comprehensive GUI dataset, we include all potential GUI scenarios in our dataset to ensure that our data is the most comprehensive knowledge that the GUI Agent needs to learn; we divide these scenarios into six categories:

- **Android.** This category focuses on the GUI scenarios that occur within the Android operating system, which is predominantly used on smartphones. Android's ubiquity in the mobile market has led to a wide variety of GUI designs and interaction patterns, making it a rich field for study. This category has been the subject of extensive scrutiny in scholarly works such as (Deka et al., 2017; Li et al., 2020a; Rawles et al., 2023; Cheng et al., 2024).

- **Software.** This category encapsulates the GUI scenarios arising within software applications, whether they are standalone programs or components of a larger suite. The diversity of software applications, from productivity tools to creative suites, offers a wide range of GUI scenarios for exploration. The literature is rich with research in this area, such as (Zhan et al., 2024).

- **Website.** This category is concerned with the GUI scenarios that manifest within a web browser. Given the ubiquity of web browsing in modern digital life, this category holds significant relevance. It holds a substantial representation in academic literature, with pioneering papers such as (Deng et al., 2024; Kapoor et al., 2024) proposing excellent GUI datasets for websites.

- **IOS.** This category zeroes in on the GUI scenarios that transpire within the iOS operating system, the proprietary system for Apple devices like the iPhone and iPad. The iOS platform is known for its distinct design aesthetics and interaction patterns, providing a unique context for GUI research. A number of studies, such as (Beltramelli, 2018; Yan et al., 2023) make use of GUI information in IOS.

- **Multi Windows.** This category is dedicated to GUI scenarios that necessitate simultaneous interaction with multiple windows, a common occurrence in desktop environments where users often juggle between several applications or documents. Despite the common use of multi-window interaction in everyday GUI usage, there has been relatively little research into this area (Nakajima et al., 2013). The need for efficient multitasking in such scenarios presents unique challenges and opportunities for GUI design and interaction research. As of our knowledge, there are no specific datasets catering to these multi-window GUI scenarios.

- **XR.** XR encompasses Virtual Reality (VR), Augmented Reality (AR), and Mixed Reality (MR) (Rauschnabel et al., 2022). Given the advancements in XR technology and the growing accessibility of commercial-grade head-mounted displays (Apple, 2024; Met), XR has emerged as a novel medium for human-computer interaction. This necessitates the exploration of GUI within XR environments. In these scenarios, the GUI takes on a 3D, immersive form (Sanders et al., 2019), demanding the agent to comprehend and navigate a 3D space. The emerging field of XR presents a new frontier for GUI research, with unique challenges and opportunities due to its immersive and interactive nature. To date, as far as we are aware, there are no datasets that specifically address GUI in the realm of XR.

```
{
    "system": "Windows",
    "app": [
        "edge, bing, steam"
    ],
    "region": "partial",
    "goal": "View the submission interface for the dataset and benchmark track of nip
    "keyframes": [
        {
            "frame": 32,
            "sub_goal": "Click to start downloading, restart downloading lethal compa
            "mouse": "click",
            "keyboard": "none",
            "keyboardOperation": ""
        },
        {
            "frame": 176,
            "sub_goal": "Click on edge, edge returns to the top of the screen.",
            "mouse": "click",
            "keyboard": "none",
            "keyboardOperation": ""
        },
        {
            "frame": 781,
            "sub_goal": "Click on the hyperlink for dataset and benchmark, preparing
            "mouse": "click",
            "keyboard": "none",
            "keyboardOperation": ""
        },
        {
            "frame": 839,
            "sub_goal": "Jump to openreview, loading.",
            "mouse": "click",
            "keyboard": "none",
            "keyboardOperation": ""
        },
        {
            "frame": 1079,
            "sub_goal": "The webpage loaded the submission interface for dataset and
            "mouse": "none",
            "keyboard": "none",
            "keyboardOperation": ""
        },
        {
            "frame": 1131,
            "sub_goal": "Place the mouse on \"add a submission\"",
            "mouse": "hover",
            "keyboard": "none",
            "keyboardOperation": ""
        }
    ]
}
```

Figure 9: Metadata of annotation.

Figure 10: Detailed breakdown of each app, software, website in GUI-WORLD.

A.2 SELECTED WEBSITE/SOFTWARE

In our study, we select a diverse range of websites and software to comprehensively evaluate GUI understanding capabilities across various user scenarios. These selections cover essential categories such as social media, productivity tools, online shopping, and educational platforms, providing a broad spectrum of GUI environments.

Figure 10 shows an overall distribution and our selected app, software, and website in GUI-WORLD.

These selections ensure that our study encompasses a wide array of user interactions and GUI complexities, thereby providing a robust evaluation of the current state-of-the-art methods in GUI understanding by MLLMs and comprehensively constructing a high-quality dataset.

A.3 Human Keyframes Annotation Process

Annotator's Information The annotation is conducted by 16 authors of this paper and 8 volunteers independently. As acknowledged, the diversity of annotators plays a crucial role in reducing bias and enhancing the reliability of the benchmark. These annotators have knowledge in the GUI domain, with different genders, ages, and educational backgrounds. The education backgrounds of annotators are above undergraduate. To ensure the annotators can proficiently mark the data, we provide them with detailed tutorials, teaching them how to use software to record videos or edit video clips. We also provide them with detailed criteria and task requirements in each annotation process.

Recording Video. For self-recording videos, we employ OBS[3] on the Windows system for screen capturing and the official screen recording toolkit on the Mac/IOS system. This process necessitates human annotators to execute a series of targeted actions within specific websites or applications, which are subsequently captured as raw video footage. **We provide a list of software and website for each annotator to first get familiar with then record video that operating on them. For some popular software or website such as *chrome*, we ask several annotator to record video of it.** These actions, commonplace in everyday usage, enhance the reliability of our dataset. Subsequently, the raw videos are segmented into sub-videos, each encapsulating multiple actions (e.g., clicking a button) to achieve a specific objective (e.g., image search). The videos are then processed to extract keyframes annotated with detailed descriptions.

Edition Based on YouTube Videos. For sourcing videos from YouTube, we utilize a search protocol formatted as "`[website name/application name] + tutorial`" to compile relevant video lists. Human annotators first review these videos to understand the primary operations they depict. These videos are then divided into sub-videos, each containing several actions directed towards a single goal (e.g., image search). Like the self-recorded footage, these segments are processed to isolate keyframes and furnish them with descriptive annotations.

Keyframes Annotation. After obtaining the GUI video clips, human annotators will filter out the keyframes of the operations based on the video content and the mouse and keyboard actions at that time. They will also label the sub-operations or targets between the two keyframes. Once the annotation is complete, the annotators will provide an overall description of the entire video, summarizing the main goal of the human operations in the video. After all the information is annotated, we will use an LLM to refine the text content, reducing any errors made by human annotators and adjusting the sentence structure. The prompt we use for the LLM to polish the human annotations is shown in Figure 11 and Figure 12.

Human-LLM Cooperated Instruction Generation. To curate and refine the golden answer of each video-instruction pair generated by GPT-4V, given that the raw response from GPT-4V may contain harmful content or hallucinations. The role of humans in the golden answer generation process is to enhance the difficulty of the questions and remove harmful and incorrect content, as shown in Table 11.

Table 11: Comparison of raw answer from GPT-4V and golden answer from humans.

Raw response from GPT-4V	Golden answer from humans
"Q": "What subcategories are visible under the 'Lifestyle' section in the static GUI content of the video?"	"Q": "What subcategories are visible under the 'Lifestyle' section in the static GUI content of the video?"
"A": "In the 'Lifestyle' section of the telegram.com website, the visible subcategories are 'Worcester Living', 'Faith', and 'Food'. These are clearly displayed in a horizontal list just below the main 'Lifestyle' category header, indicating different areas of content that users can explore within the lifestyle section."	"A": "The 'Lifestyle' section of the telegram.com website features visible subcategories such as 'Worcester Living', 'Faith', and 'Food'. These are prominently shown in a horizontal list beneath the main 'Lifestyle' header, offering users various content areas to explore within the section."

Human verifying GPT-4V annotated captions. We evaluate the quality of annotations from GPT-4V by selecting 1,000 detailed descriptions and captions generated by GPT-4V, which are then assessed by human annotators. The high satisfaction rate of 98% underscores the quality and relevance of the GPT-4V annotations.

---

[3]https://obsproject.com/

Figure 11: The overall preview of our annotating software.

Figure 12: The interface for annotating a keyframe, consists of mouse action, keyboard action, and a short sub-action purpose.

B   DATASET ANALYSIS

In this section, we provide an analysis of the length distribution of QA in each GUI scenario, as illustrated in Figure 13 and Figure 14. Questions focused on sequential and predictive tasks are slightly longer than other types, while the golden answer of static tasks tends to be longer. Length of

Table 12: Examples of diverse question types in GUI-WORLD.

T.	Question	Examples
Caption	Detailed Description	**Q:** *Please provide a detailed description of what occurs throughout these sequential GUI images.*
A: The video shows a user taking the 16 Personalities test on a Windows desktop using the Edge browser...
Caption	Summarized Caption	**Q:** *Write a clear description of the video, make sure the key features are well covered.*
A: Creating a new IT team in Todoist by selecting industry, job function, role, team size, and inviting members.
Static	Layout, Icon Retrieval	**Q:** *What related searches are suggested on the right side of the Bing results for 'emnlp 2024'?*
A: The suggested related searches shown include 'emnlp 2024 miami', 'eacl 2024 call for papers'...
Static	Textual Retrieval	**Q:** *What is the estimated time to complete the content for Week 2 of the course?*
A: The estimated time to complete the content for Week 2 of the course is 1 hour...
Static	Interrelations in GUI Content	**Q:** *What is the name of the browser and the tab where the user performs the product search?*
A: The browser is Microsoft Edge, and the user performs the product search in the eBay tab.
Dynamic	Content Retrieval	**Q:** *What specific action does the user take after turning their head to the left to view the left side of the page?*
A: After turning their head to the left to view the left side of the page, the user performs...
Dynamic	Prediction	**Q:** *Given the mouse is over 'Add NeurIPS 2024 DB Track Submission,' what's the likely next step?*
A: It would be to click on the 'Add NeurIPS 2024 Datasets and Benchmarks Track Submission' button...
Dynamic	Sequential Reasoning	**Q:** *Scrolls down from the 'Moon Gravity', which of the following cheats? A. Change Weather B. Skyfall ...*
A: [[B]]

Question-answer pair in various GUI scenarios is similarly distributed, with questions in Android environment being slightly shorter, and answers in XR environment being longer.

Figure 13: Length distribution of free-form questions.

Figure 14: Length distribution of answers to free-form questions.

C DETAILS OF EXPERIMENTS SETUPS

C.1 FINE-TUNE DATASET CONSTRUCTION

We use two settings to fine-tune GUI-Vid, one with video-text pairs only, and the other with video-text and image-text pairs, which are all GUI content:

- **Video Only.** In this setting, we only train GUI-Vid with video-text pairs in GUI-WORLD, as shown in Table 13.

Figure 15: Statistic of different GUI scenarios in GUI-WORLD.

- **Video-Image.** Inspired by the pre-trained process of Videochat2, we include image-text pairs to help the visual encoder align GUI knowledge. These images are selected from our GUI-WORLD, MetaGUI (Sun et al., 2022), and OmniAct (Kapoor et al., 2024) for high-quality GUI content. Subsequently, we use GPT-4V to generate a detailed description and a concise caption for each image. Finally, we construct a dataset consisting of video-text and image-text pairs for gaining comprehensive GUI-oriented capabilities.

Table 13: Video-only fine-tune dataset.

Stage	Data types	Amount
1	Detailed Description	14,276
	Concise Caption	7,138
2	GUI VQA	21,414
	Multiple-Choice QA	14,276
	Conversation	7,138

Table 14: Video-image fine-tune dataset.

Stage	Data types	Source	Type	Amount
1	GUI-WORLD	Video	Detailed Description	14,276
			Concise Caption	7,138
		Image	Detailed Description	5,555
			Concise Caption	5,555
	METAGUI	Image	Detailed Description	19,626
			Concise Caption	19,626
	OmniAct		Detailed Description	260
			Concise Caption	260
2	GUI-WORLD	Video	GUI VQA	21,414
			Multiple-Choice QA	14,276
			Conversation	7,138

C.2 HYPERPARAMETER SETTINGS

In this section, we will introduce the hyperparameters of MLLMs to facilitate experiment reproducibility and transparency. We divide them into three parts: the inference phase during benchmark and dataset construction, the LLM-as-a-Judge phase, and the fine-tuning phase. All our experiments were conducted on a server equipped with dual A800 and dual 4090 GPUs.

Inference. We empirically study 7 MLLMs, involving 4 Image-LLMs and 3 Video-LLMs, with their hyperparameters detailed as follows:

- **GPT-4V (OpenAI, 2023) & GPT-4o (OpenAI, 2024):** We set the temperature and top-p as 0.9, max-token as 2048, and both all images input are set as high quality in *Instruction Dataset Construction* and benchmarking.
- **Gemini-Pro-1.5 (Team et al., 2023):** We use the default settings, which set temperature as 0.4, top-p as 1, and max-token as 2048. It should be noted that during our project, Gemini-Pro-1.5 is still under the user request limit, which only provides 100 requests per day, making our benchmark difficult. Given that Gemini hasn't launched Pay-as-you-go[4], we will include benchmark results on 'Human' setting as soon as possible.
- **Qwen-VL-Max (Bai et al., 2023):** We use the default settings for Qwen-VL-Max, with top-p as 0.8 and max-token as 2048. Given that the input context window is merely 6,000 for Qwen, we scale the resolution for all images to 0.3.
- **ChatUnivi (Jin et al., 2023):** We use ChatUnivi-7B built upon Vicuna-v0-7B and set the max frame as 100, temperature as 0.2, and max-token as 1024.
- **Minigpt4video (Ataallah et al., 2024):** We use the suggested settings[5] for this model and the max-frame are set as 45, with only the max-token being modified to 1024.
- **VideoChat2 & GUI-Vid (Li et al., 2023c):** For a fair comparison, we set the same hyperparameters for VideoChat2 & GUI-Vid. We set the max-token as 1024, top-p as 0.9, temperature as 1.0, max-frame as 8/16, repetition penalty as 1.2, and length penalty as 1.2.

LLM-as-a-Judge. We investigate four LLM-as-a-Judge in giving a similarity score for the MLLM's response and ground truth, namely GPT-4 (Achiam et al., 2023), ChatGPT (OpenAI, 2023), LLaMA-3-70b-instruct (Meta, 2023b), and Mixtral-8x22b-instruct-v0.1 (ai, 2024). Hyperparameter settings are detailed as follows:

- **GPT-4 & ChatGPT.** We set the temperature as 0.6 and others as default.
- **LLaMA-3-70b-instruct.** We set the temperature as 0.6, top-p as 0.9, top-k as 50.
- **Mixtral-8x22b-instruct-v0.1.** We set top-p as 0.7, top-k as 50, and temperature as 0.7.

Fine-tune. We include several hyperparameter settings in experiment settings and ablation studies, as shown in Table 15.

Table 15: Configuration settings for fine-tuning.

Config	Setting
input frame	8
input resolution	224
max text length	512
input modal	I. + V.
optimizer	AdamW
optimizer momentum	$\beta_1, \beta_2 = 0.9, 0.999$
weight decay	0.02
learning rate schedule	cosine decay
learning rate	2e-5
batch size	4
warmup epochs	0.6
total epochs	3
backbone drop path	0
QFormer drop path	0.1
QFormer dropout	0.1
QFormer token	96
flip augmentation	yes
augmentation	MultiScaleCrop [0.5, 1]

C.3 EVALUATION.

Given the complexity of free-form answers in GUI scenarios, the evaluation includes specific positions of GUI elements, textual content, and comparing the response to the golden answer. LLM-as-a-Judge has been widely used in previous studies for complex evaluation tasks (Zheng et al., 2023; Liu et al.,

---

[4]https://ai.google.dev/pricing
[5]https://github.com/Vision-CAIR/MiniGPT4-video

Table 16: Evaluating LLM-as-a-Judge as a replacement for human judging in the scoring setting.

Models	Pearson(↑)	Spearman(↑)	Kendall(↑)	$ per Benchmark(↓)
GPT-4	**0.856**	**0.853**	**0.793**	120$
ChatGPT	0.706	0.714	0.627	**12$**
Llama-3-70b-instruct	0.774	0.772	0.684	**12$**
Mixtral-8x22b-instruct-v0.1	0.759	0.760	0.670	15$

Table 17: Strong Correlation Between Our Benchmark (GUI Understanding) and Other GUI Agent Benchmarks.

Model	GUI-World	VisualAgentBench	VideoGUI	OS-World
GPT-4o	**1**	**1**	**1**	2
GPT-4V	**2**	**2**	**2**	1
Gemini-1.5-Pro	**3**	**3**	**3**	3
Qwen-VL-Max	**4**	**4**	**4**	/

2023d). Therefore, we leverage LLM-as-a-Judge (Zheng et al., 2023) in a similar setting to MM-vet (Yu et al.), which compares the MLLM's response to the golden answer. We carefully evaluate the accessibility of leveraging LLM-as-a-Judge, selecting 1,000 samples covering 6 free-form questions mentioned in our dataset. As shown in Table 16, GPT-4 outperforms other LLMs, exhibiting a better human alignment on providing a similarity score for the response compared to the golden answer, although it is approximately 10 times more expensive than other models.

D ADDITIONAL EXPERIMENTS RESULTS

In this section, we first provide an ablation study on keyframe selection methods. Then, we conduct statistics and human preference experiments on correlations of GUI understanding capability to other mainstream GUI-related tasks. Furthermore, we provide detailed, performance on newly released models after our submission of the first version, followed by very detailed results on each task in each GUI scenario.

Ablation study on keyframe identify methods. Firstly, we show performance on model-based keyframe identify methods in Table 6, with details of UVD+VIP and UVD+R3M in Table 20 and Table 21.

Correlation between GUI understanding and other mainstream GUI tasks. Furthermore, we conduct additional analysis and experiments to show how GUI understanding capability helps mainstream GUI-related tasks, including generating code to operate GUI (Cheng et al., 2024) and assist people through chat (Hong et al., 2024). Both demonstrate the strong correlation between GUI understanding capability and specific tasks for GUI agents.

- We compare the benchmark results on GUI-world with existing benchmarks (Xie et al., 2024; Qinghong Lin et al., 2024; Liu et al., 2024c) for operating on GUI as shown in Table 17, and find that the results generally match, i.e., the stronger the understanding ability, the stronger the agent performance.

- For the definition of chat helping humans, we select 180 videos from the benchmark, choosing 30 videos for each scenario. We ask 5 human annotators to pose the question they most wanted to ask after watching each video. We then use GUI-Vid, both before and after fine-tuning, to answer these questions. The human annotators who ask the questions are then asked to indicate which answer is more helpful. The results are shown in Table 9, demonstrating that models trained in GUI understanding are more favored by people when acting as GUI agents.

Performance of newly released models in GUI-WORLD test set. We evaluate two latest models, LLaVA-Next-Video-7B-DPO (Liu et al., 2024a) and Video-LLaVA (Lin et al., 2023a). We show their performance in Table 19 and Table 18. Our model outperforms these in most tasks, except conversation, likely due to their use of DPO during training.

Table 18: The Performance of Video-LLaVA.

Scene	MCQA	Description	Conversation	Dynamic	Static	Caption	Average
XR	0.442	1.100	2.686	2.055	1.808	1.654	2.258
Android	0.513	1.162	2.952	1.858	1.673	1.763	2.259
IOS	0.497	1.143	2.966	1.992	1.680	1.654	2.319
Multi	0.459	1.106	2.863	2.069	1.781	1.772	2.329
Website	0.524	1.183	3.059	2.102	1.736	1.371	2.410
Software	0.529	1.241	2.942	1.958	1.657	1.519	2.290
Average	0.494	1.156	2.911	2.005	1.722	1.622	2.311

Table 19: LLaVA-Next-Video-7B-DPO Performance

File	MCQA	Description	Conversation	Dynamic	Static	Caption	Average
XR	0.596	1.867	3.123	2.580	2.147	1.987	2.709
Android	0.243	1.675	3.338	2.360	1.980	2.189	2.675
IOS	0.581	1.762	3.229	2.536	2.051	2.017	2.717
Multi	0.355	1.069	2.982	2.437	1.870	2.541	2.541
Website	0.484	1.729	3.123	2.422	1.854	2.004	2.588
Software	0.569	1.762	3.220	2.448	1.868	2.149	2.641
Average	0.471	1.644	3.169	2.464	1.961	2.148	2.645

For captioning tasks, Table 22 shows comprehensive experimental results among six scenarios. For scores of LLM-as-a-Judge in a specific task, see Table 23, Table 24, Table 25, Table 26, and Table 27. For performance in fine-grain (application level), see Figure 16 for Gemini-Pro and Figure 17 for Qwen-VL-Max.

E PROMPTS

In this section, we provide detailed prompts for models and human annotators. Figure 19 shows the guideline of human annotation, Figure 18 shows the prompt for leveraging LLMs to refine grammarly mistakes and polish sentence for human annotations. Figure 20, Figure 21, and Figure 22 present the prompt for Human-MLLM collaboration method to generate GUI-orientaed tasks. Figure 23 illustrate the prompt for benchmarking MLLMs, different GUI scenarios and different QA type has different prompt. Figure 24 and Figure 25 show prompt for LLM-as-a-Judge for free-form as well as conversational tasks and multiple-choice QA respectively.

Table 20: Detailed Performance of GPT-4o using UVD+ViP Keyframe Identification Method.

Scenario	MCQA	Description	Conversation	Dynamic	Static	Caption	Average
Software	**86.2%**	3.297	**4.282**	3.354	3.478	**4.112**	**3.749**
Website	82.0%	3.248	4.155	3.415	**3.567**	4.074	3.744
XR	84.2%	2.980	3.775	3.034	3.122	3.587	3.347
Multi	82.1%	**3.391**	4.165	**3.466**	3.404	3.868	3.659
IOS	86.0%	3.157	4.017	3.353	3.492	4.050	3.648
Mobile	80.7%	2.827	3.871	2.970	3.014	3.844	3.340
Average	83.5%	3.150	4.044	3.265	3.346	3.923	3.581

Table 21: Detailed Performance of GPT-4o using UVD+R3M Keyframe Identification Method.

Scenario	MCQA	Description	Conversation	Dynamic	Static	Caption	Average
Software	85.8%	**3.290**	**4.273**	3.352	3.458	**4.134**	3.741
Website	82.7%	3.282	4.114	3.460	**3.591**	4.065	3.746
XR	**87.7%**	3.010	3.861	3.142	3.161	3.600	3.433
Multi	83.6%	3.237	4.129	**3.503**	3.417	3.897	3.737
IOS	86.4%	3.165	4.094	3.328	3.480	4.078	3.663
Android	80.6%	2.835	3.876	2.968	3.072	3.865	3.353
Average	84.5%	3.136	4.058	3.292	3.363	3.940	**3.612**

Table 22: Scores of Caption (Cap.) and Description (Des.) tasks in six GUI scenarios.

Models	Setting	Software		Website		XR		Multi		IOS		Android		Avg.	
		Cap.	Des.	Cap.	Des.	Cap.	Des.	Cap.	Des.	Cap.	Des.	Cap.	Des.	Cap.	Des.
Gemini-Pro-1.5	R.	3.659	2.837	3.613	2.860	2.995	2.590	3.276	2.470	3.678	2.936	-	-	3.444	2.739
	E.	3.350	2.468	3.159	2.422	2.837	2.279	2.824	2.109	3.394	2.519	3.185	2.312	3.125	2.351
Qwen-VL-Max	R.	2.381	1.758	2.326	1.681	2.172	1.772	2.035	1.463	2.513	1.662	2.141	1.565	2.261	1.650
	E.	2.459	1.693	2.317	1.599	2.167	1.638	2.190	1.438	2.189	1.615	2.002	1.429	2.221	1.569
	H.	2.474	1.711	2.457	1.698	2.383	1.777	1.910	1.346	2.577	1.795	2.474	1.711	2.360	1.665
GPT-4V	R.	3.579	2.676	3.612	2.699	2.975	2.525	3.281	2.661	3.757	2.775	3.655	2.755	3.479	2.682
	E.	3.141	2.301	3.293	2.380	2.471	2.085	3.063	2.324	3.624	2.611	3.201	2.312	3.132	2.335
	H.	3.352	2.509	3.702	2.750	3.050	**3.556**	3.524	2.673	3.670	2.588	-	-	3.460	2.614
GPT-4o	H.	**4.048**	**3.028**	**4.067**	**3.233**	**3.398**	2.729	**3.869**	**3.111**	**4.014**	**2.993**	**4.071**	**3.095**	**3.911**	**3.869**
ChatUnivi	-	1.587	1.240	1.569	1.254	1.417	1.148	1.575	1.267	1.480	1.146	1.778	1.249	1.568	1.217
Minigpt4Video	-	1.246	1.073	1.200	1.057	1.320	1.106	1.130	1.034	1.190	1.076	1.184	1.061	1.212	1.068
VideoChat2	-	1.992	1.312	1.817	1.307	1.838	1.426	2.222	1.433	2.169	1.270	2.119	1.294	1.900	1.340
GUI-Vid	-	3.562	2.085	3.655	2.167	**3.747**	2.153	3.370	1.742	3.566	2.071	2.662	1.248	3.427	1.911

Figure 16: Fine-grained performance of Gemini-Pro-1.5 in each software and website.

Table 23: Detailed scores for each tasks in **Website** scenarios.

Models	Setting	Static	Sequential	Prediction	Conversation1	Conversation2	Average
Gemini-Pro-1.5	R.	3.279	3.050	3.560	3.579	3.796	3.452
	E.	2.983	2.491	3.432	3.405	3.760	3.215
Qwen-VL-Max	R.	2.317	2.271	2.802	2.995	3.069	2.656
	E.	2.256	2.198	2.821	2.861	3.144	2.627
	H.	2.308	2.078	2.832	3.061	3.358	2.698
GPT-4V	R.	3.461	3.214	3.754	3.778	4.029	3.648
	E.	3.197	2.808	3.487	3.717	3.954	3.433
	H.	**3.498**	3.255	3.727	3.731	4.061	3.655
	C.C.	1.746	2.738	3.645	3.363	3.632	3.025
	D.C.	2.704	2.917	3.686	3.680	3.901	3.380
	H.+D.C.	3.313	3.221	**3.852**	3.850	**4.171**	3.682
GPT-4o	H.	3.443	**3.373**	3.672	**4.086**	4.122	**3.740**
ChatUnivi	-	1.701	1.668	2.524	2.514	3.338	2.349
Minigpt4Video	-	1.309	1.233	1.766	1.439	1.854	1.520
VideoChat2	-	1.771	1.777	2.288	2.461	2.812	2.221
GUI-Vid	-	2.406	2.341	3.544	3.135	3.355	2.957

Table 24: Detailed scores for each tasks in **XR** scenarios.

Models	Setting	Static	Sequential	Prediction	Conversation1	Conversation2	Average
Gemini-Pro-1.5	R.	2.892	2.505	3.543	3.222	3.611	3.154
	E.	2.814	2.163	3.510	3.108	3.455	3.006
Qwen-VL-Max	R.	2.047	1.968	2.712	2.879	3.132	2.469
	E.	2.125	1.973	2.658	2.760	3.029	2.499
	H.	1.886	1.920	2.656	2.727	3.012	2.373
GPT-4V	R.	**2.934**	2.668	3.392	3.291	3.714	3.200
	E.	2.222	2.153	3.310	3.151	3.618	2.892
	H.	2.893	2.778	3.538	**3.364**	3.747	**3.265**
	C.C.	1.744	2.412	3.327	3.080	3.485	2.809
	D.C.	2.427	2.409	3.518	3.176	**3.749**	3.056
	H.+D.C.	2.775	2.635	**3.580**	3.235	3.734	3.191
GPT-4o	H.	2.871	**2.745**	3.370	3.596	3.836	3.285
ChatUnivi	-	1.660	1.420	2.205	2.250	3.270	2.161
Minigpt4Video	-	1.225	1.161	1.610	1.347	1.465	1.362
VideoChat2	-	1.654	1.547	2.192	2.099	2.529	2.005
GUI-Vid	-	2.444	2.147	3.347	2.836	3.036	2.764

Table 25: Detailed scores for each tasks in **Multi-windows** scenarios.

Models	Setting	Static	Sequential	Prediction	Conversation1	Conversation2	Average
Gemini-Pro-1.5	R.	2.538	2.410	3.296	3.152	3.402	2.959
	E.	2.545	2.049	2.972	2.930	3.389	2.777
Qwen-VL-Max	R.	1.793	1.872	2.770	2.897	3.122	2.432
	E.	1.866	1.780	2.730	2.627	3.105	2.362
	H.	1.884	1.969	2.913	2.689	3.104	2.490
GPT-4V	R.	**3.185**	2.655	3.745	3.699	3.973	3.452
	E.	2.902	2.406	3.636	3.420	3.729	3.219
	H.	3.000	2.952	3.801	3.597	3.889	3.449
	C.C.	2.097	2.973	3.774	3.331	3.621	3.160
	D.C.	2.671	2.979	3.849	3.466	3.822	3.358
	H.+D.C.	3.037	**3.162**	**4.079**	3.748	4.036	3.617
GPT-4o	H.	3.108	3.106	3.829	**4.043**	**4.188**	**3.654**
ChatUnivi	-	1.658	1.623	2.514	2.384	3.199	2.275
Minigpt4Video	-	1.205	1.186	1.690	1.400	1.801	1.457
VideoChat2	-	1.754	1.774	2.479	2.420	2.699	2.222
GUI-Vid	-	2.485	2.067	3.537	2.954	3.247	2.861

Table 26: Detailed scores for each tasks in **IOS** scenarios.

Models	Setting	Static	Sequential	Prediction	Conversation1	Conversation2	Average
Gemini-Pro-1.5	R.	3.076	2.637	3.370	3.366	3.615	3.213
	E.	2.852	2.356	3.137	3.126	3.566	3.007
Qwen-VL-Max	R.	2.438	2.244	2.923	3.102	3.273	2.779
	E.	2.303	2.150	2.614	3.145	3.264	2.659
	H.	1.884	1.969	2.913	2.689	3.104	2.490
GPT-4V	R.	**3.364**	**3.080**	**3.684**	3.766	**4.184**	**3.614**
	E.	3.209	2.774	3.545	3.611	4.006	3.427
	H.	3.107	2.830	3.631	3.680	4.011	3.453
	C.C.	1.788	2.291	3.511	3.212	3.542	2.868
	D.C.	2.751	2.732	3.654	3.642	3.842	3.324
	H.+D.C.	3.090	2.965	3.740	3.786	3.994	3.516
GPT-4o	H.	3.183	2.993	3.460	**4.050**	4.141	3.558
ChatUnivi	-	1.771	1.642	2.408	2.559	3.307	2.337
Minigpt4Video	-	1.291	1.219	1.698	1.556	1.737	1.501
VideoChat2	-	1.955	1.803	2.145	2.315	2.626	2.169
GUI-Vid	-	2.262	2.133	3.401	2.843	3.224	2.773

Table 27: Detailed scores for each tasks in **Android** scenarios.

Models	Setting	Static	Sequential	Prediction	Conversation1	Conversation2	Average
Gemini-Pro-1.5	E.	2.703	2.460	3.157	3.642	3.881	3.168
Qwen-VL-Max	R.	1.887	1.804	2.398	2.823	3.056	2.309
	E.	1.785	1.630	2.311	2.605	3.233	2.277
GPT-4V	R.	**3.116**	3.047	**3.477**	3.924	4.008	3.515
	E.	2.705	2.470	3.175	3.647	3.885	3.176
	C.C.	2.092	2.243	3.139	3.443	3.782	2.939
	D.C.	3.015	2.890	3.357	3.883	3.990	3.427
GPT-4o	H.	3.057	**3.220**	3.373	**3.981**	**4.186**	**3.561**
ChatUnivi	-	1.835	1.654	2.317	2.712	3.433	2.390
Minigpt4Video	-	1.183	1.159	1.507	1.342	1.521	1.342
VideoChat2	-	1.732	1.754	2.125	2.340	2.645	2.119
GUI-Vid	-	2.010	1.928	3.053	2.755	3.105	2.572

Figure 17: Fine-grained performance of Qwen-VL-Max in each software and website.

Refining Human Annotation on Goal and Sub-goal

```
As an expert in English, please refine the following English
instructions (or objectives) into a polished phrase or a
concise sentence.
Avoid including irrelevant content and provide the polished
output directly.
Here is the English sentence:  {string}
```

Figure 18: Refining Human Annotation on Goal and Sub-goal.

Guideline for Human Annotation

Main Interface
1. Video List Panel (Left Panel): Displays a list of loaded video files. Each video file is shown with its name for identification.
2. Video Display Area (Center Panel): Shows the currently selected video for playback and annotation.
3. Control Settings (Right Panel):
Operating System: Select the operating system of the machine where the video was recorded.
Full Screen: Toggle full screen mode for the video display.
Multi-application?: Indicate if multiple applications in the video.
Application/Website: Enter the name of the application or website being used in the video.
User Goal: Enter the goal of the user performing the annotation.
4. Playback and Annotation Controls (Bottom Panel)
Annotate: Open a annotation window to add a new keyframe annotation.
Play: Starts or pauses the video playback.
Load Video: Allows you to load a single video file.
Load Video Folder: Allows to load multiple video files from a folder.
Previous Video / Next Video: Navigate through the loaded video files.
Save to JSON: Save the annotations in a JSON format.
Annotation Window
1. Mouse Action: Select a type of mouse action (e.g. click, drag).
2. Keyboard Action: Select the type of keyboard action (e.g., typing, key press).
3. Keyboard Operation Record: Enter details of the keyboard operation, if any.
4. sub-action Purpose: Describe the purpose of the action being annotated.
How to Use
Loading Videos
1. Load Multiple Videos
Click on the Load Video Folder button.
Select the folder containing your video files.
All video files in the folder will be loaded and listed in the Video List Panel.
Playing Videos
Select a video from the Video List Panel. Click the Play button to start or pause the video.
Annotating Videos
1. Start Annotation
Pause the video at the desired frame.
Click the Annotate button to open the annotation window.
2. Annotation Window
Select the Mouse Action Type and Keyboard Action Type from the dropdown menus.
If there is a keyboard action, enter the details in the Keyboard Operation Record field.
Describe the action's purpose in the Sub-action Purpose field.
Click OK to save the annotation.
Saving Annotations
Once all annotations are completed, click the Save to JSON button.

32

Figure 19: Guideline for Human Annotation

(Part 1) GPT-4V Generating GUI-oriented Tasks

```
You are an AI visual assistant. This is a video of a mobile
GUI, which I've divided into multiple frames and sent to
you. Please provide a detailed description of what occurs
throughout the entire video, focusing on the changes in the
GUI elements or scenes rather than static aspects of a single
frame. The detailed description should be placed under the
key 'Description'. Based on your description, please design
the following tasks:
Generate a precise caption for the video. This caption
should encapsulate the main activities or changes observed
throughout the video sequence. Place this caption under the
key 'Caption'.
Create a free-form QA question related to the video's static
GUI content, along with its answer. The question should
delve into the details or changes in the static GUI elements
or scenes captured in the video. The QA task should be
nested under the key 'static QA', with 'Question' and 'Answer'
as subkeys.
Develop a multiple-choice QA question about the video,
with four options: one correct answer and three incorrect
or irrelevant options. This task should assess the
understanding of specific elements retieval or changes
depicted in the video. Structure this task under the key
'MCQA', with 'Question' detailing the query, 'Options' listing
the four choices including one correct answer, and 'Correct
Answer' specifying the correct option, denoted, for example,
as {[[B]]}.
Here are some key information of the video to help you
understand the video comprehensively:
System: {item['system']}
Application: {item['app']}
Summary of the video: {item['goal']}
Key Operation/Sub goal in the video: {[i['sub_goal'] for i in
item['keyframes']]}
Notice: Ensure that the questions you design for these tasks
are answerable and the answers can be deduced from the GUI
video content. The answerable question should be designed
as difficult as possible. The tasks should be unambiguous
and the answers must be definitively correct based on your
understanding of the video content. Only include questions
that have definite answers: (1) one can see the content
in the image that the question asks about and can answer
confidently; (2) one can determine confidently from the image
that it is not in the image. Do not ask any question that
cannot be answered confidently.
Each of these tasks should focus on the dynamic aspect of
the GUI elements or scenes. Provide detailed answers when
answering complex questions. For example, give detailed
examples or reasoning steps to make the content more
convincing and well-organized. The answers should be in
a tone that a visual AI assistant is seeing the image and
answering the question.
For the free-form QA tasks, please ensure that the answers
are as detailed and lengthy as possible, with no concern for
length. You can include multiple paragraphs if necessary
to provide a comprehensive and thorough response. Please
structure your response using JSON format and specific keys
mentioned in the task requirements.
```

33

Figure 20: (Part 1) GPT-4V Generating GUI-oriented Tasks.

(Part 2) GPT-4V Generating GUI-oriented Tasks.

```
You are an AI visual assistant.  This is a video of a <Scene
Name> GUI, which I've divided into multiple frames and sent
to you.  Please provide a detailed description of what occurs
throughout the entire video, focusing on the changes in the
GUI elements or scenes rather than static aspects of a single
frame.  The detailed description should be placed under the
key 'Description'.  Based on your description, please design
the following tasks:
A Sequential QA task:  Design a question that requires
understanding the sequence of GUI element changes or scene
transformations in the video.  The question should be
free-form and necessitate the use of temporal information
from the sequential images.  The task should be structured
under the key 'Sequential-QA' with subkeys 'Question' and
'Answer'.
A Next Stage Prediction task:  Formulate a question that asks
about the subsequent state or event following a certain frame
in the video.  The question should be designed in a free-form
manner and predict future GUI elements or scene changes,
structured under the key 'Prediction' with subkeys 'Question'
and 'Answer'.
A two-round dialogue task:  Create a dialogue with two rounds
of interaction.  The first round includes a user instruction
and an assistant response, and the second round's user
instruction should be based on the response from the first
round.  Both rounds should be free-form and nested under the
key 'Conversation', with subkeys 'User 1', 'Assistant 1',
'User 2', and 'Assistant 2'.
A reasoning task:  Design a multi-choice QA task that
requires reasoning to identify the correct answer from four
options.  This task should test the reasoning ability to
infer or deduce information that is not explicitly provided.
It should be structured under the key 'Reasoning', with
subkeys 'Question', 'Options', and 'Correct Answer'.
Here are some key information of the video to help you
understand the video comprehensively:
System: {item['system']}
Application: {item['app']}
Summary of the video: {item['goal']}
Key Operation/Sub goal in the video: {[i['sub_goal'] for i in
item['keyframes']]}
```

Figure 21: (Part 2) GPT-4V Generating GUI-oriented Tasks.

1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889

(Part 3) GPT-4V Generating GUI-oriented Tasks.

```
 Notice:  Ensure that the questions you design for these
tasks are answerable and the answers can be deduced from
the GUI video content.  The answerable question should be
designed as difficult as possible.  The tasks should be
unambiguous and the answers must be definitively correct
based on your understanding of the video content.  Only
include questions that have definite answers:  (1) one can
see the content in the image that the question asks about
and can answer confidently; (2) one can determine confidently
from the image that it is not in the image.  Do not ask any
question that cannot be answered confidently.
Each of these tasks should focus on the dynamic aspect
of the GUI elements or scenes, with each answerable task
as difficult as possible.  Provide detailed answers when
answering complex questions.  For example, give detailed
examples or reasoning steps to make the content more
convincing and well-organized.  The answers should be in
a tone that a visual AI assistant is seeing the image and
answering the question.
For the free-form QA tasks, please ensure that the answers
are as detailed and lengthy as possible, with no concern for
length.  You can include multiple paragraphs if necessary
to provide a comprehensive and thorough response.  Please
structure your response using JSON format and specific keys
mentioned in the task requirements.
```

Figure 22: (Part 3) GPT-4V Generating GUI-oriented Tasks.

Prompts for Benchmarking MLLMs

"XR": "You are an AI visual assistant. Here are sequential images of Mixed-Reality combining GUI interface and real world, which are selected from a GUI video.",
"software": "You are an AI visual assistant. Here are sequential GUI interface images of a specific software, which are selected from a GUI video.",
"website": "You are an AI visual assistant. Here are sequential GUI interface images of a desktop website, which are selected from a GUI video.",
"mobile": "You are an AI visual assistant. Here are sequential GUI mobile interface images, which are selected from a GUI video.",
"multi": "You are an AI visual assistant. Here are sequential GUI interface images of interaction among multiple softwares and websites, which are selected from a GUI video.",
"IOS": "You are an AI visual assistant. Here are sequential GUI IOS interface images, which are selected from a GUI video.",

"Sequential-QA": "This is a question about sequential information in sequential images.",
"Prediction": "This is a question about predicting the next action base on the previous actions in the sequential images.",
"Reasoning": "This is a multiple choice question with only one correct answer. This question may need multiple steps of reasoning according to the vision information in sequential images.",
"Description1": "Please give me a detail description of these sequential images.",
"Description2": "Offer a thorough analysis of these sequential images",
"Caption": "Please give me a concise caption of these sequential images.",
"static QA": "This is a question about static information such as text, icon, layout in these sequential images.",
"MCQA": "This is a multiple choice question with only one correct answer. This question may require sequential analysis ability to the vision information in these sequential images.",
"Conversation1": "Act as an assistant to answer the user's question in these sequential images.",
"Conversation2": "This is a multi-turn conversation task. You will be provide the first round conversation and act as an assistant to answer the user's question in the second round according to these sequential images."
Notice = "You can first provide an overall description of these sequential images, and then analyze the user's question according to the sequential images and description. Finally, give an answer based on this description and the image information. Please format your output in a Json format, with key 'Description' for the description of these sequential images, key 'Analysis' for your analysis on the user's question and key 'Answer' for your answer to the User's question."

Figure 23: Prompts for Benchmarking MLLMs.

Prompt for LLM-as-a-Judge: Judging Free-form and Conversational Tasks

You are an impartial judge. I will provide you with a
question, a 'gold standard' answer, and a response that
needs evaluation. Your task is to assess the quality of the
response in comparison to the 'gold standard' answer. Please
adhere to the following guidelines:

1. Start your evaluation by comparing the response to
the 'gold standard' answer. Offer a brief explanation
highlighting similarities and differences, focusing on
relevance, accuracy, depth, and level of detail.
2. Conclude your evaluation with a score from 1 to 5, where
1 indicates the response is mostly irrelevant to the 'gold
standard' answer, and 5 indicates it is very similar or
equivalent.
3. Present your findings in JSON format, using 'Evaluation'
for your textual analysis and 'Score' for the numerical
assessment.
4. Ensure objectivity in your evaluation. Avoid biases and
strive for an even distribution of scores across the spectrum
of quality. Your scoring must be as rigorous as possible and
adhere to the following rules:
- Overall, the higher the quality of the model's response,
the higher the score, with factual accuracy and meeting user
needs being the most critical dimensions. These two factors
largely dictate the final composite score.
- If the model's response is irrelevant to the question,
contains fundamental factual errors, or generates harmful
content, the total score must be 1.
- If the model's response has no severe errors and is
essentially harmless, but of low quality and does not meet
user needs, the total score should be 2.
- If the model's response generally meets user requirements
but performs poorly in certain aspects with medium quality,
the total score should be 3.
- If the model's response is close in quality to the reference
answer and performs well in all dimensions, the total score
should be 4.
- Only when the model's response surpasses the reference
answer, fully addresses the user's problem and all needs,
and nearly achieves a perfect score in all dimensions, can
it receive a score between 5.
- As an example, the golden answer could receive a 4-5.

Here is the response for you to judge:
Question: {question}
Golden Answer: {golden_answer}
Response: {response}
Now, directly output your response in json format.

Figure 24: Prompt for LLM-as-a-Judge: Judging Free-form and Conversational Tasks .

1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051

Prompt for LLM-as-a-Judge: Judging Multiple-Choice QA Tasks

```
 You are a helpful assistant tasked with judging a Multiple
Choice Question Answering exercise.
I will provide a correct answer with only one option, and a
response that requires evaluation.
If the response matches the correct answer, simply output
"Yes"; If it does not, output "No".
Please avoid including any irrelevant information.
Here are some examples:

Example 1:
Question:  Based on the GUI video, why might the 'Loading'
animation continue without reaching the next stage?  A. The
user has not yet entered their login credentials.  B. There
is a system update being installed.  C. The server is taking
time to authenticate the login credentials.  D. The 'Log In'
button is malfunctioning.
Answer:  C
Response:  C. The server is taking time to authenticate the
login credentials.
Output:  Yes

Example 2:
Question:  If the user wants to resume the group video call
after checking messages, what action should they take?  A.
Turn their head to the right.  B. Close the messaging app
interface.  C. Say a voice command to switch applications.  D.
Turn their head to the left.
Answer:  A
Response:  B
Output:  No

Example 3:
Question:  What action does the user take to start playing
music in the video?  A. Closed the music player application B.
Moved the music player to a new position C. Clicked the play
button D. Adjusted the system volume
Answer:  [[B]]
Response:  C
Output:  No

Here is the question, answer, and response for you to judge:
Question:  {question}
Answer:  {answer}
Response:  {response}
Now, directly output "Yes" or "No".
```

Figure 25: Prompt for LLM-as-a-Judge: Judging Multiple-Choice QA Tasks.

F CASE STUDY

In this section, we provide detailed case studies for six GUI scenarios, each divided into two parts. Figure 26 and Figure 27 show example frames and various tasks associated with them. Figure 28 and Figure 29 for IOS, Figure 30 and Figure 31 for multiple-windows interaction, Figure 34 and Figure 35 for website, and Figure 36 and Figure 37 for XR respectively.

(Part 1) Android

'Description1': "The video starts with a view of a mobile app interface, specifically an Al-Qur'an Indonesia app with a list of Surahs. A user scrolls through the Surah list, selects a specific Surah, and the view transitions to a page displaying the verses in Arabic and their Indonesian translation. The user then returns to the Surah list. Following this, a pop-up appears indicating a configuration process that takes approximately 10-20 seconds. After the configuration, another pop-up notifies of an available update from the Google Play Store, which the user can accept or postpone. The user dismisses this pop-up. The main menu is accessed, showing options such as 'Baca Quran', 'Terakhir Baca', 'Pencarian', 'Jadwal Sholat', and 'Pengaturan'. The user selects the 'Pencarian' option, which leads to a search page. Here, the user is instructed to enter a keyword to search in the translation database. Finally, the user navigates back to the main menu and then to the Surah list once more."

'Sequential-QA': 'Question': 'After selecting a specific Surah from the list, what does the user do next before a pop-up notification appears?'
'Answer': 'After selecting a Surah, the user views the verses in Arabic and their Indonesian translation. Then, the user returns to the Surah list before a pop-up notification appears.'

'Prediction': 'Question': 'What would likely be the next step in the app interface after the user is directed to the search page?'
'Answer': "After being directed to the search page, the likely next step would be for the user to enter a keyword into the search bar to find a translation or meaning within the app's database."

'Conversation': 'User 1': 'I need to find a specific verse in the Quran. How do I search for it?'
'Assistant 1': "You can search for a specific verse by tapping on the 'Pencarian' option in the main menu, which will take you to a search page where you can enter a keyword."
'User 2': 'I see. And how do I get back to the main menu from the search page?'
'Assistant 2': 'To return to the main menu from the search page, you can tap on the back arrow located at the top left corner of the screen.'

'Reasoning': 'Question': "If the user wants to read the verses of Surah 'Al-Infitar', what should they do after launching the app?"
'Options': ["A. Go to the settings and select 'Al-Infitar'.", "B. Scroll through the Surah list and select 'Al-Infitar'.", "C. Choose the 'Pencarian' option and type 'Al-Infitar'.", "D. Wait for a pop-up and select 'Al-Infitar' from there."]
'Correct Answer': "B. Scroll through the Surah list and select 'Al-Infitar'."

(Part 2) Android

'Description2': "The video begins by displaying a mobile GUI with a list of chapters from the Quran in Indonesian. Each chapter has a downward arrow suggesting expandable content. As the video progresses, a popup appears with a loading icon and a message in Indonesian indicating a configuration is in progress, which takes about 10-20 seconds. After this, another popup appears notifying of a new update available on the Google Play Store with options to update or postpone. Subsequently, the screen shows a search interface where users can input keywords for searching within the Quran's translated database. The main menu is then accessed, with options such as 'Read Quran', 'Last Read', 'Search', 'Prayer Schedule', and 'Settings'. The GUI transitions back to the list of chapters, and a specific chapter, At-Takwir, is selected. The video then displays the verses of this chapter, both in Arabic and Indonesian translation, with an option to listen to the audio. Finally, it navigates back to the list of chapters."

'Caption': "Navigating through a Quran app's GUI, interacting with chapter lists, update notifications, search function, and viewing specific verses with translations."

'static QA': 'Question': 'What options are available in the main menu of the mobile Quran application?'
'Answer': "The main menu of the mobile Quran application provides several options for the user to choose from. These include 'BACA QURAN' (Read Quran) for accessing the chapters to read, 'TERAKHIR BACA' (Last Read) to resume reading from where the user left off last time, 'PENCARIAN' (Search) to search the Quran's database for specific keywords, 'JADWAL SHOLAT' (Prayer Schedule) to check the prayer times, and 'PENGATURAN' (Settings) to modify app settings. This menu provides a simple and efficient way for users to navigate through the app's features and customize their reading and learning experience."

'MCQA': 'Question': 'What happens after the user is notified about the new update available on the Google Play Store?'
'Options': 'A': 'The app closes automatically.', 'B': 'The search interface is displayed.', 'C': 'The list of chapters disappears.', 'D': 'An advertisement for shopping deals is shown.'
'Correct Answer': '[[B]] The search interface is displayed.'

Figure 27: Case study for Android (part 2).

(Part 1) IOS

'Description1': "The video demonstrates a user navigating through the Khan Academy mobile application under the 'Computing' category. Initially, the user scrolls through the 'Computers and the Internet' section, viewing topics such as 'Digital information,' 'Bits and bytes,' 'The Internet,' and 'Online data security.' The user then scrolls to the bottom, revealing the 'Computing innovations' section and the 'Take Course Challenge' button. Subsequently, the user returns to the previous screen, displaying other computing sections like 'AP®/College Computer Science Principles' and 'Computer science theory.' The user clicks to enter the 'Computer science theory' interface; the content is loading. After the content has loaded, revealing topics like 'Cryptography' and 'Information theory,' the user returns to the previous page and clicks on 'Code.org.'"

'Caption': "Navigating through computing courses on Khan Academy's mobile application, viewing sections, and attempting to enter 'Computer science theory.'"

'static QA': 'Question': "Which topic appears directly below 'Online data security' in the 'Computers and the Internet' section before scrolling down?"
'Answer': "Before scrolling down, the topic that appears directly below 'Online data security' is 'Computing innovations.' This can be confirmed from the initial frames of the video where the 'Computing innovations' section is partially visible, indicating that it is the next topic in the sequence after 'Online data security.' As the video progresses and the user scrolls down, the full 'Computing innovations' section comes into view, affirming its position in the GUI layout."

'MCQA': 'Question': "What action does the user take after viewing the 'Computing innovations' section?"
'Options': ["A) Scrolls up to view 'Digital information' again.", "B) Returns to the previous screen showing different computing sections.', "C) Clicks on the 'Take Course Challenge' button.", "D) Taps on the 'Explore' tab at the bottom of the screen."]
'Correct Answer': '[[B]] Returns to the previous screen showing different computing sections.'

Figure 28: Case study for IOS (part 1).

(Part 2) IOS

'**Description2**': "The video begins with the user viewing the 'Computers and the Internet' course section within the Khan Academy application. The user scrolls through various subsections such as 'Digital information,' 'Computers,' 'The Internet,' and 'Online data security,' each with a list of topics and a status of possible mastery points. The user continues to scroll down to the 'Computing innovations' section and then further down to a 'Course challenge' prompt. The user then scrolls back up, revealing previously seen sections in reverse order. The user eventually navigates back to the main 'Computing' category screen, showing an overview of all computing-related courses. From there, the user selects 'Computer science theory,' which briefly loads before displaying topics within that course such as 'Cryptography' and 'Information theory.' Following this, the user returns to the main 'Computing' category screen."

'**Sequential-QA**': 'Question': "What action does the user take after scrolling through the 'Online data security' section, and what is displayed as a result of this action?", 'Answer': "After scrolling through the 'Online data security' section, the user scrolls down to the 'Computing innovations' section. As a result of this action, topics such as 'Communication innovations', 'Collaboration innovations', ·Crowdsourcing innovations', and ·Monitoring innovations' are displayed, followed by a ·Course challenge' prompt."

'**Prediction**': 'Question': "If the user were to select the 'Cryptography' section after it was displayed, what kind of content could you predict will be shown next?"
'Answer': "If the user selects the 'Cryptography' section, one could predict that the next content shown would be detailed topics under Cryptography, such as 'Ancient cryptography,' 'Ciphers,' 'Cryptography challenge 101,' 'Modern cryptography,' 'Modular arithmetic,' 'Primality test,' and 'Randomized algorithms,' along with the status of possible mastery points for that section."

'**Conversation**': 'User 1': 'Can you take me to the section about user authentication methods?'
'Assistant 1': "Sure, you will need to scroll down the 'Computers and the Internet' course section until you reach the 'Online data security' subsection, where you will find the topic 'User authentication methods.'"
'User 2': "I scrolled too far down and reached the course challenge. How do I find 'User authentication methods' from here?"
'Assistant 2': "No problem, you'll need to scroll back up past the 'Computing innovations' section until you see the 'Online data security' subsection again. 'User authentication methods' is listed there among other topics."

'**Reasoning**': 'Question': "After browsing through the course topics in 'Computers and the Internet,' the user returns to a broader category view. Based on this behavior, what could be the reason for the user returning to the broader category view?"
'Options': ['A. The user wants to take a course challenge.', 'B. The user is looking for a different computing-related course.', 'C. The application automatically redirected the user.', 'D. The user intends to log out of the Khan Academy application.']
'Correct Answer': 'B'

Figure 29: Case study for IOS (part 2).

(Part 1) Multiple-Windows Interaction

`Description1`: "The video begins with a Windows desktop
displaying multiple open applications, including Steam, OBS
Studio, and a web browser with NVIDIA's website loaded. The
user starts by clicking on the back page of the browser,
which partially obscures the OBS window. Then, the user
clicks on the OBS application, bringing it to the forefront.
The user minimizes OBS, followed by dragging the Steam window
to the center of the screen and minimizing it as well. A
new web page is opened in the Edge browser's navigation
bar, and the user types 'office' into the search bar. The
browser navigates to the Bing search interface, and 'office'
is successfully searched."
`Caption`: 'Navigating and Managing Multiple Applications on
Windows Including Steam, OBS Studio, and Edge Browser'
`static QA`: `Question`: "Which web browser is used in the
video and which website is prominently featured before the
search for 'office'?"
`Answer`: "The web browser used in the video is Microsoft
Edge. The prominently featured website before the search
for 'office' is NVIDIA's official website where the 'Download
Drivers' page is displayed."
`MCQA`: `Question`: 'What action is taken after the OBS
application is minimized?', `Options`: ['A. The Steam window
is closed.'
`B. The Steam window is moved to the center of the screen and
minimized.', `C. The Edge browser is closed.', `D. A file is
opened from the desktop.']
`Correct Answer`: '[[B]] The Steam window is moved to the
center of the screen and minimized.'

Figure 30: Case study for multiple-windows interaction (part 1).

(Part 2) Multiple-Windows Interaction

'Description2': "The video shows a Windows desktop with several application windows open, including Steam, OBS, and Edge. Initially, the OBS window is partially covering the Edge browser. The user clicks on the Edge browser, bringing it to the foreground, and then minimizes the OBS window, clearing the view. Next, the user moves the Steam window to the center of the screen and minimizes it as well. Afterward, the user opens a new tab in Edge and enters 'office' into the search bar, which leads to a Bing search results page for 'office'. The video ends with the user on the Bing search page with 'office' results displayed."

'Sequential-QA': 'Question': 'After moving the Steam window to the center, what did the user do next in the Edge browser?'
'Answer': "After moving the Steam window to the center, the user minimized the Steam application. Then, they opened a new tab in the Edge browser and entered 'office' into the search bar, which led them to the Bing search results page for 'office'."

'Prediction': 'Question': "What would be the likely next action the user performs after searching for 'office' on Bing?"
'Answer': "The likely next action the user would perform after searching for 'office' on Bing would be to click on one of the search results to find more information or to visit the Microsoft Office website to purchase or learn more about the office suite."

'Conversation': 'User 1': 'Can you minimize the OBS application for a better view of the browser?'
'Assistant 1': 'Certainly, the OBS application has been minimized, providing a clear view of the Edge browser.'
'User 2': 'Great, now can you search for Microsoft Office in the Edge browser?'
'Assistant 2': "Of course, a new tab has been opened in the Edge browser and 'office' has been entered into the search bar. The Bing search results for 'office' are now displayed."

'Reasoning': 'Question': 'If the user needs to record gameplay footage next, which application should they interact with and what would be their first step?'
'Options': ["A. They should open the Steam application and click on the 'STORE' tab.", "B. They should open the Edge browser and search for 'game recording software'.", "C. They should reopen the OBS application and click on the 'Start Recording' button.", "D. They should access the Windows Start menu and search for the 'Camera' app."]
'Correct Answer': 'C'

Figure 31: Case study for multiple-windows interaction (part 2).

(Part 1) Software

'Description1': "The video shows a Python 3.7.4 Shell window on a Windows system. The user begins by typing the 'print' function followed by a pair of parentheses. Inside the parentheses, the user types a string, 'Hello World', which is enclosed in double quotes. Upon pressing Enter, the Python Shell executes the command and outputs the text 'Hello World' below the command line, indicating that the code ran successfully without any errors."

'Caption': "Executing the print command in Python Shell to display 'Hello World'"

'static QA': "Question": "What version of Python is shown running in the video?"
"Answer": "The version of Python running in the video is Python 3.7.4, as indicated by the text at the top of the Python Shell window."

'MCQA': "Question": "What operation does the user perform after typing the print command?"
"Options": ["A. The user saves the file.", "B. The user compiles the code.", "C. The user executes the print command.", "D. The user closes the Python Shell."]
"Correct Answer": "[[C]] The user executes the print command."

Figure 32: Case study for software (part 1).

(Part 2) Software

'De

scription2': "The video shows a sequence of a user interacting
with the Python Shell on a Windows system. Initially, the shell
is open and waiting for input. The user begins by typing 'print*'
and then corrects the typo by removing the asterisk, typing 'print'.
They then type two quotation marks to prepare for a string input.
Subsequently, the user moves the cursor between the quotation marks
and types 'Hello World' to complete the 'print(Ḧello World)̈' command.
After pressing enter, the shell executes the command, and the phrase
'Hello World' is outputted below the command prompt."
'Sequential-QA': "Question": "Can you describe the sequence of
actions the user took to correct the command and output 'Hello
World'?"
"Answer": "Certainly. Initially, the user typed 'print*' but
realized the asterisk was a mistake. They deleted the asterisk to
correct the command to 'print'. Next, they entered two quotation
marks to indicate the start of a string. The user then placed
the cursor between the quotation marks and typed the string 'Hello
World'. Finally, upon pressing enter, the Python Shell executed the
command and displayed the output 'Hello World' beneath the command
prompt."
'Prediction': "Question": "What would be the expected GUI change
if the user were to type another command after the 'Hello World'
output?"
"Answer": "If the user were to type another command after the
'Hello World' output, the expected GUI change would be that the
command prompt indicator '>>>' would appear on a new line below the
'Hello World' output, signaling readiness for the next command input.
Any subsequent command typed by the user would appear after this new
prompt, awaiting execution."
'Conversation': "User 1": "I want to print a different message in
Python. How can I do that?", "Assistant 1": "To print a different
message, you can simply type 'print(Ÿour Message Here)̈' where
'Your Message Here' is the text you wish to print. Make sure you
enclose your message in quotation marks and hit enter to execute the
command."
"User 2": "What if I want to print 'Goodbye, World' instead?"
"Assistant 2": "To print 'Goodbye, World', you would type
'print(Ḧoodbye, World)̈' and press enter. The Python Shell will
execute the command and display 'Goodbye, World' as the output below
the command prompt."
'Reasoning': "Question": "What command did the user execute to get
the output in the Python Shell?"
"Options": ["A. print(Hello World)", "B. print(Ḧello World)", "C.
print(Ḧello World)̈", "D. echo(Ḧello World)̈"]
"Correct Answer": "C",

47

Figure 33: Case study for software (part 2).

(Part 1) Website

'Description1': "The video begins with the Google search results page visible on a Windows system browser, displaying the query 'is oatmeal a healthy breakfast'. The mouse cursor scrolls down the page, revealing additional search results, and the 'People also ask' section with related questions. The user then scrolls back up to the top of the page. Next, the cursor moves to the search bar, and the 'X' button is clicked to clear the previous search content, leaving an empty search bar. The browser's suggested searches drop-down menu appears with various related search queries. Finally, the video fades to black, indicating the end of the sequence."

'Caption': 'Navigating Google Search Results and Clearing the Search Query on a Windows System Browser'

'static QA': 'Question': "What feature snippet is displayed at the top of the Google search results for the query 'is oatmeal a healthy breakfast'?"

'Answer': "The featured snippet at the top of the Google search results for the query 'is oatmeal a healthy breakfast' is from the Harvard T.H. Chan School of Public Health website. It includes an excerpt stating 'Whether it's steel-cut or rolled, quick-cooking or instant, oatmeal is good for you, experts say|with a few caveats. Oatmeal is rich in fiber, which promotes fullness, eases the insulin response, and benefits gut health. It's also a source of vitamins B and E, and minerals such as magnesium.' This snippet provides a concise summary of the health benefits of oatmeal, according to experts, highlighting its nutritional value and potential impact on fullness and insulin response. The presence of this snippet offers a quick and authoritative answer to the user's query, showcasing Google's ability to extract relevant information from web pages and present it prominently for ease of access."

'MCQA': 'Question': 'What action did the user take after reviewing the search results?'

'Options': ['A. The user clicked on one of the search results.', "B. The user scrolled through the 'People also ask' section.", 'C. The user cleared the search content in the search bar.', 'D. The user navigated to a different website.']

'Correct Answer': '[[C]] The user cleared the search content in the search bar.',

Figure 34: Case study for website (part 1).

(Part 2) Website

'Description2': "The video shows a sequence of actions on a Google search results page within a web browser on a Windows system. Initially, the mouse cursor moves over a search result discussing the health benefits of oatmeal. Next, the user scrolls down, revealing a 'People also ask' section with questions related to oatmeal and a 'Videos' section showcasing related content. Subsequently, the user scrolls back up to the original position, highlighting the same search result about oatmeal's health benefits. Finally, the user moves the cursor to the search bar and clicks the 'X' to clear the previous search content, resulting in a blank search bar with suggestions and related searches listed below it. The screen then goes black, indicating the end of the video."

'Sequential-QA': 'Question': "After reading about oatmeal's health benefits, what section of the page did the user explore next and did they return to read more about the health benefits afterward?" 'Answer': "After reading about the health benefits of oatmeal, the user scrolled down to explore the 'People also ask' section and the 'Videos' section related to oatmeal. Following this, the user scrolled back up to revisit the original search result that discussed the health benefits of oatmeal."

'Prediction': 'Question': 'Based on the sequence of events, what action is the user likely to perform after clearing the search bar?' 'Answer': 'After clearing the search bar, the user is likely to type in a new search query or select one of the suggested searches that appear below the search bar.'

'Conversation': 'User 1': "I want to find more articles on oatmeal's health benefits. Can you scroll back up?"
'Assistant 1': "I've scrolled back up and the article on oatmeal's health benefits from the Harvard T.H. Chan School of Public Health is highlighted again."
'User 2': 'Great, now can you clear the search and look for something else?'
'Assistant 2': 'The search content has been cleared, and the search bar is now empty, showing a list of related searches and previous search history suggestions for a new query.'

'Reasoning': 'Question': 'If the user wants to perform a new search after clearing the search bar, which of the following actions would they need to take next?', 'Options': ['A. Scroll down to view more search results'
'B. Type a new query into the search bar', "C. Click on one of the 'People also ask' questions", 'D. Close the browser window']
'Correct Answer': 'B',

Figure 35: Case study for website (part 2).

(Part 1) XR

'Description1': "The video showcases a user navigating through various pages within the Apple Vision Pro browser on a Windows system. Initially, the browser displays the start page with Favorites and Reading List. The user then turns their head to the right, which triggers the transition to view a webpage on the right side. Following this, the user pinches with both hands to exit the page and then pinches with both hands and fingers moving towards the middle to expand the browser's various pages. This reveals multiple open browser tabs side by side. The user continues to turn their head left and right to view different pages on each side. Lastly, the user selects and expands a specific tab to fill the screen, displaying its content."

'Caption': 'Navigating through multiple browser pages using head movement and hand gestures in Apple Vision Pro on Windows'

'static QA': 'Question': "What is the main category listed under the Favorites section on the browser's start page?"
'Answer': "The main category listed under the Favorites section on the browser's start page is 'Perplexity', denoted by a unique icon, followed by other favorites like Instagram and various websites."

'MCQA': 'Question': 'How does the user switch between different open tabs in the Apple Vision Pro browser?'
'Options': ['A. Using keyboard shortcuts', 'B. Turning their head left and right', 'C. Scrolling with a mouse', 'D. Typing the tab number']
'Correct Answer': '[[B]] Turning their head left and right'

Figure 36: Case study for XR (part 1).

(Part 2) XR

'Description2': "The video starts with a full-screen view of a browser interface titled 'Apple Vision Pro' displaying various website thumbnails and bookmarks. The user then turns their head to the right, causing the right side of the browser to come into view. Next, the user looks at a dot at the bottom of the page and pinches with both hands, which causes the browser to exit the full-screen view and shrink to a smaller, windowed mode. The user then performs a pinching motion with both hands, bringing the fingers towards the middle, which causes the browser's various pages to expand, giving an overview of multiple open tabs. The user again turns their head to the right to view the right side page and then to the left to view the left side page. Throughout the video, the GUI elements such as tabs, the address bar, and website thumbnails respond dynamically to the user's head movements and hand gestures."

'Sequential-QA': 'Question': 'What action did the user take immediately after turning their head to the right to view the right side page?'
'Answer': 'After turning their head to the right to view the right side page, the user looked at a dot at the bottom of the page and pinched with both hands, which caused the browser to exit full-screen mode and shrink to a smaller windowed interface.'

'Prediction': 'Question': 'If the user pinches with both hands and moves their fingers towards the middle after the browser shrinks to a smaller window, what will happen next?'
'Answer': "If the user pinches with both hands and moves their fingers towards the middle after the browser shrinks, the action will cause the browser's various pages to expand, providing an overview of multiple open tabs."

'Conversation': 'User 1': 'How do I view all the pages I have open in the browser?'
'Assistant 1': 'You can view all the open pages by pinching with both hands and moving your fingers towards the middle. This will expand the browser and show an overview of all the open tabs.'
'User 2': 'Great, and how can I exit this overview?'
'Assistant 2': 'To exit the overview of open pages, you can look at the dot at the bottom of the page and pinch with both hands. This will exit the overview and return you to the individual page view.'

'Reasoning': 'Question': 'How can the user access the options to open a new tab or window from the current state?'
'Options': ['A. Turn their head to the left and select the plus sign.', 'B. Swipe left on the touchpad.', 'C. Turn their head to the right and select the 'Done' button.', 'D. Pinch with both hands to exit the current view and access the toolbar.']
'Correct Answer': 'D'

Figure 37: Case study for XR (part 2).