LASSO: LATENT SUB-SPACES ORIENTATION FOR DOMAIN GENERALIZATION

ABSTRACT

To achieve a satisfactory generalization performance on prediction tasks in an unseen domain, existing domain generalization (DG) approaches often rely on the assumption on the existence of fixed domain-invariant features and common hypotheses learned from a set of training domains. While it is a natural and important premise to ground generalization capacity on the target domain, we argue that this assumption could be overly strict and sub-optimal. It is particularly evident when source domains share little information or the target domains leverages information from selective source domains in a compositional way instead of relying on a unique invariant hypothesis across all source domains. Unlike most existing approaches, instead of constructing a single hypothesis shared among domains, we propose a LAtent Sub-Space Orientation (LASSO) method that explores diverse latent sub-spaces and learning individual hypotheses on those sub-spaces. Moreover, in LASSO, since the latent sub-spaces are formed by the label-informative features captured in source domains, they allow us to project target examples onto appropriate sub-spaces, while preserving crucial label-informative features for the label prediction task. Finally, we empirically evaluate our method on several well-known DG benchmarks, where it achieves state-of-the-art results.

1 INTRODUCTION

One of the most challenging problems in applying machine learning to real-world problems is to address the domain shift encountered when test data at inference time come from different distributions compared to training data, often causing unexpectedly imperfect generalization performance. To handle this issue, many out-of-distribution learning settings have been investigated, notably domain adaptation (DA) and domain generalization (DG). In particular, DA setting (Mansour et al., 2009; Ben-David et al., 2010; Daumé III, 2009) takes the assumption that both labeled source data and unlabeled target data are available at the training phase, while DG setting (Muandet et al., 2013; Ganin et al., 2016) is much more challenging due to the complete absence of any target data at training time, and the learned model is expected to perform a zero-shot prediction on test samples. While being more challenging than DA, DG is arguably more versatile and applicable to real-world scenarios where there is a need to rapidly deploy a prediction model on a new target domain without any access to target data.

A common premise on which most of existing DG approaches rely to address the domain shift problem is to learn a shared set of features among different source domains, e.g., domain-invariant features (Muandet et al., 2013; Ganin et al., 2016; Motiian et al., 2017; Ghifary et al., 2015; Xie et al., 2017; Wang et al., 2019; Piratla et al., 2020; Zhao et al., 2020). By learning domain-invariant features these approaches identify a latent representation from multiple source domains, which is also expected encompass unseen target domains, hence reducing the domain shift. However, since this latent space is often high-dimensional and unseen target domains could vary greatly and unexpectedly, these domain invariance approaches could become ineffective. We argue that using a single hypothesis which requires to be optimal for all source and target domains is rather a strong assumption which might not have an effective algorithmic solution, hence presenting a key weakness to these existing approaches.

In this paper, we propose a new approach to efficiently reduce the domain shift. Our idea is to optimally decompose the high-dimensional latent feature space to lower-dimensional sub-spaces,

after which an individual hypothesis is learned (optimally) for each latent sub-space. In particular, these latent sub-spaces are formed by label-informative features learned from source latent representations so that sub-space latent representations can capture sufficient and necessary information to effectively train sub-space hypotheses. We then perform extensive experimental evaluations to demonstrate the merits of our methodology and framework. In sum, our contributions are as follows:

- We propose LAtent SubSpace Orientation (LASSO), a novel approach for DG, which aims to learn label-informative latent sub-spaces from source latent representations, preserving crucial label information for training qualified individual sub-space hypotheses.

- We develop a rigorous theoretical analysis to explain how our approach can learn meaningful sub-spaces by learning an indicator function Γ that helps to reduce latent domain shift. Moreover, by linking to information theory (cf. Theorem 3), we theoretically justify the rationale behind learning the sub-space indicator function Γ as a mechanism for element-wise selection of latent features to gather sufficient label information.

- Finally, we empirically demonstrate that our proposed method can achieve favorable results when evaluating on domain generalization benchmarks in the comparison with state-of-the-art methods.

2 RELATED WORK

Domain generalization (DG) approaches can be categorized into several groups: *domain-invariant representation learning*, *meta-learning*, and *augmentation/self-supervision*. The works in the first group aim to learn a domain-invariant representation with the hope of transferring well to unseen domains. Notably, Muandet et al. (2013) construct shared components by minimizing the discrepancy of the source domain marginal distributions using a kernel-based algorithm. Xie et al. (2017) employ an adversarial training strategy to preserve the desired invariance and eliminate variations of domain factors from features. Seo et al. (2020) combine batch normalization and instance normalization to removes domain-specific style while preserving semantic category information. Other works (Ghifary et al., 2015; Li et al., 2018b; Ilse et al., 2020) employ auto-encoders to support domain-invariant feature extraction.

Another efficient approach for DG is meta-learning. For example, the studies in (Li et al., 2018a; Balaji et al., 2018) use source domains to stimulate meta-train/ meta-test, which encourages the trained model to generalize better on the meta-test data, leading to a more plausible global generalization performance on the unseen target domain. Dou et al. (2019) then extend the work of Li et al. (2018a) by combining it with metric learning loss to encourage domain-independent semantic feature space.

Self-supervised learning and data augmentation have been also applied to DG. Typically, Carlucci et al. (2019) propose to solve the pretext task of Jigsaw Puzzles to improve the generalization performance on unseen domains. Shankar et al. (2018) augment training data with instances perturbed along with directions of domain change. In addition, Zhou et al. (2020a) employs a classifier that can learn the generalization on additional augmented samples of diversity pseudo-novel domains by leveraging with optimal transport theory. Zhou et al. (2020b) augment the original training data of source domains with synthetic data from unseen domains such that augmented data are correctly classified by the classifier while fooling the domain classifier to make the task model intrinsically more domain-generalizable. Zhou et al. (2021) propose to mix the styles of different source domains based on normalization-based style-transfer techniques to effectively increase diversity of domains during training.

Recently, learning domain-specific information to boost classification performance in domain generalization has attracted more attention. For example, Huang et al. (2020) iteratively discard the dominant features to exploit all useful features (including both invariant and specific feature) that highly correlate with labels. Chattopadhyay et al. (2020) propose a domain-specific mask learned from the domain label to balance domain-invariant and domain-specific features. As a result, source domain classification can benefit from the specialized features while retaining the generalizing applicability of domain-invariant features.

3 PROPOSED METHOD

3.1 PROBLEM SETTING

Let $\mathbb{D}_k^S = \{(x_i^k, y_i^k)\}_{i=1}^{N_k^S}$, $k = 1, ..., K$ be the source labeled datasets, where k is the domain index, N_k^S is the number of examples in $\mathbb{D}_k^S$ and $y_i^k \in \mathcal{Y} := \{1, ..., C\}$ is the set of C classes. Let $\mathbb{P}_k^S$ and p_k^S be the (marginal) data distribution and corresponding density of the source domain k. Similarly, let $p_k^S(y \mid x)$ denote the probabilistic labeling distribution of this domain. A domain is then defined by a pair of data distribution and labeling function, in which its data (x_i^k, y_i^k) is generated by first sampling $x_i^k \sim p_k^S(\cdot)$ and subsequently $y_i^k \sim p_k^S(\cdot \mid x_i^k)$. With a little abuse of notation, let us also denote k-th domain by $\mathbb{D}_k^S$, and the data generation process is $(x, y) \sim \mathbb{D}_k^S$. For target domain $\mathbb{D}^T$, $\mathbb{P}^T$ and p^T are its data distribution and density respectively, while $p^T(y \mid x)$ is the target labeling distribution.

A mixture of the source domains is denoted by $\mathbb{D}_\pi^S := \sum_{k=1}^K \pi_k \mathbb{D}_k^S$. In order to sample data from this mixture, one first sample a domain index from the categorical distribution k $\mathrm{Cat}(\pi)$, where π specifies the mixture weights, and then sample the actual data from the corresponding domain k. The empirical datasets obtained could hint us to estimate $\pi_k = \left[\frac{N_k^S}{N^S}\right]_{k=1}^K$ with $N^S = \sum_{k=1}^K N_k^S$. Finally, a mixture of data distribution is defined by $\mathbb{P}_\pi^S = \sum_{k=1}^K \pi_k \mathbb{P}_k^S$.

A hypothesis $f : \mathcal{X} \to \Delta_C$ is a map from the common data space $\mathcal{X}$ to the the C-simplex label space $\Delta_C := \{\alpha \in \mathbb{R}^C : \|\alpha\|_1 = 1 \wedge \alpha \geq 0\}$. Let $\ell(f(x), y)$ be the loss incurred by using this hypothesis to predict $x \in \mathcal{X}$, given its ground-truth label $y \in \mathcal{Y}$. Therefore, the general loss of the hypothesis f w.r.t. the joint distribution $\mathbb{D}$ is:

$$\mathcal{L}(f, \mathbb{D}) = \mathbb{E}_{(x,y) \sim \mathbb{D}}[\ell(f(x), y)]. \tag{1}$$

We examine the composite hypothesis $f = h \circ g$ where $g : \mathcal{X} \to \mathcal{Z}$ is the feature extractor mapping the data space to a latent space and $h : \mathcal{Z} \to \mathcal{Y}$ is the classifier on this latent space. With respect to the latent space, given a probabilistic labeling distribution $p(y \mid x)$, let denote $p^g(y \mid z)$ as the probabilistic labeling distribution induced by $p(y \mid x)$ and g, that is, for any $z \in g(\mathcal{X})$, $p^g(y \mid z) = \frac{\int_{g^{-1}(z)} p(y|x)p(x)dx}{\int_{g^{-1}(z)} p(x)dx}$ (Johansson et al., 2019). Basically, $p^g(y \mid z)$ can be regarded as a weighted sum of $p(y \mid x)$ for $x \in g^{-1}(z)$. We further define $p_k^{S,g}(y = c \mid z)$ and $p^{T,g}(y = c \mid z)$ with $z \in g(\mathcal{X}) \subset \mathcal{Z}$ as the induced conditional labeling distributions of source and target domains on the latent space via the feature extractor g. Finally, we consider the DG setting, in which we only possess the source labeled data and do not have any prior information of any target data during the training process.

In what follows, we develop a rigorous theory to promote our LASSO, whose proofs can be found in the Appendix A.

3.2 SINGLE HYPOTHESIS AND FULL SPACE FOR DOMAIN GENERALIZATION

Most existing works in DG use a single hypothesis acting on the entire latent space $\mathcal{Z}$ for predicting unseen target domains. In what follows, we develop an upper-bound which is relevant to the data shift on the latent space of the target loss $\mathcal{L}(f, \mathbb{D}^T)$ with $f = h \circ g$.

Theorem 1. *If the loss function ℓ is upper-bounded by a positive constant L, for any hypothesis $f : \mathcal{X} \to \Delta_C$ where $f = h \circ g$ with $g : \mathcal{X} \to \mathcal{Z}$ and $h : \mathcal{Z} \to \Delta_C$, the target general loss is upper-bounded by:*

$$\mathcal{L}(f, \mathbb{D}^T) \leq \exp\left\{R^\alpha\left(g_\# \mathbb{P}^T, g_\# \mathbb{P}_\pi^S\right)\right\}^{\frac{\alpha-1}{\alpha}} L^{\frac{1}{\alpha}}\left[\mathcal{L}\left(f, \mathbb{D}_\pi^S\right) + L \max_k \mathbb{E}_{\mathbb{P}_k^S}\left[\|\Delta p_k(y \mid x)\|_1\right]\right]^{\frac{\alpha-1}{\alpha}},$$

$$\tag{2}$$

where $g_\# \mathbb{P}_\pi^S$ and $g_\# \mathbb{P}^T$ are pushed-forward distributions induced by applying g on $\mathbb{P}_\pi^S$ and $\mathbb{P}^T$, R^α is the α-divergence ($\alpha > 1$), and $\Delta p_k(y \mid x) := \left[|p_k^S(y = c \mid x) - p^T(y = c \mid x)|\right]_{c=1}^C$ represents the label shift between the labeling assignment mechanisms of an individual source domain and target domain on the input space.

The bound developed in Theorem 1 supports us in characterizing the factors influencing the loss on the target domain of a hypothesis f: (i) *the label shift*: $\mathbb{E}_{\mathbb{P}_k^S}\left[\|\Delta p_k\left(y \mid x\right)\|_1\right]$, (ii) *the source loss*: $\mathcal{L}\left(f, \mathbb{D}_\pi^S\right)$, and (iii) *the latent data shift*: $R^\alpha\left(g_\#\mathbb{P}^T, g_\#\mathbb{P}_\pi^S\right)$. Based on this theorem, we aim to find the hypothesis f such that the upper bound of target loss is minimized. Note that the *label shift term* is a natural characteristic of domains, hence it is almost unchangeable. Therefore, one seeks to minimize the source loss, or the discrepancy between latent distributions, or both of them. Certainly, if we know target data (e.g., samples from $\mathbb{P}^T$), we can minimize the divergence between $g_\#\mathbb{P}_\pi^S$ and $g_\#\mathbb{P}^T$ directly. However, this is almost impossible for the DG setting because the target domain is unknown beforehand when training.

To address this problem, a large number of works relying on the beneficial domain-invariance assumption, i.e., simultaneous minimization of latent distribution divergence between source domains and learning low loss hypothesis, have been proposed. We argue that learning a single beneficial domain-invariant hypothesis is rather implausible for some reasons. Firstly, a group of a few source domains could share a different set of useful features compared to other groups, and they, therefore, should be classified differently. Enforcing domain-invariant learning on all source domains could risk discarding usefulness and richness of features which might be beneficial for test time. A few works have tackled this issue by using domain-specific information (Huang et al., 2020; Chattopadhyay et al., 2020) to improve the generalization capability of the latent representation. However, enriching the representation space might be insufficient if only a single classifier is learned to classify that space, due to the possible conflict between different feature components. Therefore, we expect different sets of features are projected to different spaces for corresponding further classification.

To this end, we claim that there are two aspects that should be considered to improve the performance of a DG framework: (1) diversity of latent representations and (2) appropriate classifiers. We, therefore, aim to learn a set of hypotheses which utilize different and sufficient sets of useful features for different domains (or groups of samples that have similar characteristics). In particular, we propose to project a full latent presentation z onto many *sub-spaces*, each is characterized by a different set of *label-informative dimensions* of z. Our motivation is that by eliminating irrelevant features and projecting source and target latent representations z to appropriate label-informative sub-spaces, we can naturally reduce the latent data shift, whereas preserving *sufficient label-information* for training *good hypotheses* on those *latent sub-spaces*.

3.3 LATENT SUB-SPACES WITH INDIVIDUAL HYPOTHESES FOR DOMAIN GENERALIZATION

For a data sample $(x, y) \sim \mathbb{D}_\pi^S$, we consider latent representation $z = g(x) \in \mathbb{R}^D$ and propose to learn a *sub-space indicator* Γ which renders $\Gamma(z) \in \{0, 1\}^D$. Specifically, $\Gamma(z)$ specifies the *sub-space* which we project z onto via $\Pi_\Gamma(z) = z \odot \Gamma(z)$, where $\odot$ is the element-wise product operator. Our intuition is that Γ is able to keep the most label informative features of latent vector z (.i.e d^{th} element of $\Gamma(z)$: $\Gamma_d(z) = 1$ means that z_d is label-informative and should be selected when projecting z onto its sub-space).

Given a sub-space index $m \in \{0, 1\}^D$, we denote the region on data space having the same index m as $A_m = \{x : \Gamma(g(x)) = m\} \subset \mathcal{X}$. Let $\mathbb{P}_m^S$ be the distribution restricted by $\mathbb{P}_\pi^S$ over the set A_m and $\mathbb{P}_m^T$ as the distribution restricted by $\mathbb{P}^T$ over A_m. Eventually, we define $p_m^S(y \mid x)$ as the probabilistic labeling distribution on the sub-space $\left(A_m, \mathbb{P}_m^S\right)$, meaning that if $x \sim \mathbb{P}_m^S$, $p_m^S(y \mid x) = \sum_{k=1}^K \pi_k p_k^S(y \mid x)$. Similarly, we define if $x \sim \mathbb{P}_m^T$, $p_m^T(y \mid x) = p^T(y \mid x)$.

Due to this construction, any data sampled from $\mathbb{P}_m^S$ or $\mathbb{P}_m^T$ will have the same index $m = \Gamma(z) = \Gamma(g(x))$, which specifies the set of relevant feature elements for classifying data coming from A_m. This hints us to employ an individual hypothesis $f_m = h_m \circ g^\Gamma$, where f_m specializes on $\left(A_m, \mathbb{P}_m^S\right)$ and h_m specializes on the sub-space $\left(g^\Gamma(A_m), g^\Gamma_\#\mathbb{P}_m^S\right)$ with $g^\Gamma := \Pi_\Gamma \circ g$ for each m. We note that h_m operates on the sub-space indexed by m, while f_m operates on its induced data space. Additionally, since each data point $x \in \mathcal{X}$ corresponds to only a single $\Gamma(g(x))$, the data space is partitioned into disjoint sets, i.e., $\mathcal{X} = \bigcup_{m=1}^{\mathcal{M}} A_m$, where $A_m \cap A_n = \emptyset, \forall m \neq n$. Therefore, these different hypotheses h_m make use of different features, as reflected in the different sub-space index m.

We now present the way to efficiently formulate sub-space hypotheses. Let $\mathcal{F} :=$ $\{f = h \circ g : g \in \mathcal{G} \wedge h \in \mathcal{H}\}$ be a hypothesis class of $f : \mathcal{X} \to \Delta_C$, where $f = h \circ g$ with $g : \mathcal{X} \to \mathcal{Z} \in \mathcal{G}$ and $h : \mathcal{Z} \to \Delta_C \in \mathcal{H}$. Each hypothesis $f = h \circ g$ induces the sub-space hypotheses $f_{\mathcal{M}} = [f_m]_{m \in \mathcal{M}}$ for which $f_m(x) = h_m(\Gamma(g(x)) \odot g(x))$ for $x \in A_m$ with $h_m(m \odot g(x)) = h(m \odot g(x))$ can be viewed as a hypothesis on the sub-space indexed by m. We define the general loss of $f_{\mathcal{M}} = [f_m]_{m \in \mathcal{M}}$ on the target domain as

$$\mathcal{L}\left(f_{\mathcal{M}}, \mathbb{D}^T\right) := \frac{1}{|\mathcal{M}|} \sum_{m \in \mathcal{M}} \mathcal{L}\left(f_m, \mathbb{D}_m^T\right), \tag{3}$$

where $\mathcal{M} \subset \{0,1\}^D$ is the set of all feasible sub-space indices m conducted from the observed data, $|\mathcal{M}|$ specifies the cardinality of $\mathcal{M}$, and $\mathbb{D}_m^T$ is the joint distribution of (x, y) where $x \sim \mathbb{P}_m^T$ and $y \sim p_m^T(\cdot \mid x)$.

The following theorems explain the intuition that matching source and target domains on good sub-spaces helps reduce the latent data shift w.r.t. a general unseen target domain; and offer us the training process of the *sub-space indicator* Γ, which extracts the most label informative features of latent representations z.

Theorem 2. *Given a sub-space indicator Γ, if the loss function ℓ is upper-bounded by a positive constant L, the sub-space target general loss is upper-bounded by:*

$$\mathcal{L}\left(f_{\mathcal{M}}, \mathbb{D}^T\right) \leq \frac{L^{\frac{1}{\alpha}}}{|\mathcal{M}|} \sum_{m \in \mathcal{M}} \exp\left\{R^\alpha\left(g^\Gamma_{\#}\mathbb{P}_m^T, g^\Gamma_{\#}\mathbb{P}_m^S\right)\right\}^{\frac{\alpha-1}{\alpha}} \left[\mathcal{L}\left(f_m, \mathbb{D}_m^S\right) + L\Delta p_m\right]^{\frac{\alpha-1}{\alpha}}, \tag{4}$$

where $\mathbb{D}_m^S$ is the joint distribution of (x, y) with $x \sim \mathbb{P}_m^S$ and $y \sim p_m^S(\cdot \mid x)$, and $\Delta p_m := \mathbb{E}_{x \sim \mathbb{P}_m^S}\left[\left\|p_m^S(\cdot \mid x) - p_m^T(\cdot \mid x)\right\|_1\right]$.

Theorem 2 shows an upper-bound of the sub-space target loss which consists of three terms: (i) *the sub-space label shift*: Δp_m, (ii) *the source sub-space hypothesis losses*: $\mathcal{L}\left(f_m, \mathbb{D}_m^S\right)$, and (iii) *the sub-space latent data shift*: $R^\alpha\left(g^\Gamma_{\#}\mathbb{P}_m^T, g^\Gamma_{\#}\mathbb{P}_m^S\right)$. Since the sub-space label shift depends on the natural characteristics of domains and the source sub-space hypothesis losses are trainable, the *sub-space latent data shift* (i.e., the divergence between the mixture of source domains: $g^\Gamma_{\#}\mathbb{P}_m^S$ and target domain: $g^\Gamma_{\#}\mathbb{P}_m^T$ on a sub-space) is essential to lower the upper-bound in (4). Notice that Theorem 2 is not a simple ensemble average of Theorem 1, because the *sub-space hypothesis loss* $\mathcal{L}\left(f_m, \mathbb{D}_m^S\right)$ is evaluated on the sub-space induced distribution $\mathbb{D}_m^S$, rather than the original $\mathbb{D}^S$. This has a profoundly different impact. Specifically, learning a single hypothesis over the entire data space, i.e., simultaneous minimization of both source loss $\mathcal{L}(f, \mathbb{D}_\pi^S)$ and feature discrepancy $R^\alpha(g^\Gamma_{\#}\mathbb{P}^T, g^\Gamma_{\#}\mathbb{P}^S)$ as described in the previous section, might not be possible. In contrast, the sub-space versions of source loss and feature discrepancy take only data in the set $A_m \subset \mathcal{X}$ into account, and therefore they might be simultaneously minimized. The reason is that in such case, samples in the same region A_m have their features extracted and classified in a specific way for that region, regardless of the source of samples.

Our motivation is that if we can learn a qualified *sub-space indicator* Γ, we can simultaneously project source and target examples onto appropriate sub-spaces preserving crucial label-informative features for training a qualified sub-space hypothesis f_m, while reducing the latent data shift due to the sub-space's compactness compared to the entire latent space. The next arising question is how to train a qualified *sub-space indicator* Γ together with the *sub-space hypotheses* $f_{\mathcal{M}} = [f_m]_{m \in \mathcal{M}}$ addressed in the following theorem.

Theorem 3. *Let X is a random variable of source sample (i.e., drawn from $\mathbb{P}_\pi^S$) and Y is a random variable of ground-truth labels. Denote $N = \sum_{m' \in \mathcal{M}} \mathbb{P}_\pi^S(A_{m'})$, we then have*

$$\mathbb{I}\left(\Gamma(g(X)) \odot g(X), Y\right) \geq - \sum_{m \in \mathcal{M}} \frac{\mathbb{P}_\pi^S(A_m)}{N} \mathcal{L}\left(f_m, \mathbb{D}_m^S\right) + const, \tag{5}$$

where $\mathcal{L}\left(f_m, \mathbb{D}_m^S\right)$ is defined based on the cross-entropy loss and $\mathbb{I}$ denotes mutual information.

Theorem 3 gives us a hint of how to train a *sub-space indicator* Γ together with the *sub-space hypotheses* $f_{\mathcal{M}} = [f_m]_{m \in \mathcal{M}}$. As suggested by Theorem 3, we minimize the *source sub-space*

hypothesis losses $\mathcal{L}\left(f_m, \mathbb{D}_m^S\right)$ by

$$\min_{\Gamma, g, h} \sum_{m \in \mathcal{M}} \frac{\mathbb{P}_\pi^S(A_m)}{N} \mathcal{L}\left(f_m, \mathbb{D}_m^S\right) = \min_{\Gamma, g, h} \sum_{m \in \mathcal{M}} \frac{\mathbb{P}_\pi^S(A_m)}{N} \mathbb{E}_{\mathbb{D}_m^S}\left[\ell\left(h\left(m \odot g\left(x\right)\right), y\right)\right]$$

$$= \min_{\Gamma, g, h} \mathbb{E}_{\mathbb{D}_\pi^S}\left[\ell\left(h\left(m \odot g\left(x\right)\right), y\right)\right]. \quad (6)$$

Furthermore, Theorem 3 indicates that by solving the optimization problem in (6), we implicitly learn Γ, g to maximize the mutual information $\mathbb{I}\left(\Gamma\left(g(X)\right) \odot g\left(X\right), Y\right)$, which enables the *sub-space indicator* Γ to preserve the label-informative features of $z = g\left(x\right)$.

3.4 LATENT SUB-SPACES LEARNING FRAMEWORK

In what follows, we present the technical details of our proposed method which solves the optimization problem in equation 6. In particular, we discuss the way to formulate and learn the sub-space indicator Γ, the feature extractor $g : \mathcal{X} \to \mathcal{Z}$, and the classifier $h : \mathcal{Z} \to \Delta_C$, in which Γ and (g, h) are updated alternatively.

3.4.1 SUB-SPACE INDICATOR

We employ a probabilistic *sub-space indicator* $\Gamma\left(z\right) \in [0, 1]^D$ in which $\Gamma_d\left(z\right) \in [0, 1]$ represents the probability that z_d is a label-informative feature. Additionally, in our implementation, we consider a 2D tensor $z \in \mathbb{R}^{D' \times D}$, whereas each $z_d \in \mathbb{R}^{D'}$ known as *an attribute* consists of D' features which are simultaneously selected or unselected as the dimensions of the projection sub-space. The probabilistic sub-space indicator is formulated as $\Gamma\left(z\right) = \left[\Gamma_1\left(z_1\right), ..., \Gamma_D\left(z_D\right)\right] \in [0, 1]^D$. The element-wise product $\Gamma\left(z\right) \odot z$ is defined as $z\mathrm{diag}\left(\Gamma\left(z\right)\right)$, wherein we multiply each element in $\Gamma\left(z\right)$ to a column of z to select or unselect the group of features in this column. (The detail implementation of *sub-space indicator* Γ is presented in Appendix B.3).

Note that $\Gamma_d\left(z\right) = \Gamma_d\left(z_d\right)$ is computed based solely on the group of D' features in the attribute z_d. Our principle is to encourage $\Gamma_d\left(z\right), d = 1, ..., D$ to becomes more independent. This would help generalize better when predicting an unseen target example. The reason is that for an unseen target example x with the latent representation $z = g\left(x\right)$, if z contains some useful attributes for predicting its label y, the selection of the attributes depends only on themselves and is not interfered by other noisy attributes. We believe that this would increase the chance of good attributes being selected for the classifier h. Finally, we minimize the following loss for updating Γ:

$$\mathcal{L}_I\left(\Gamma | g, h\right) = \mathbb{E}_{(x, y) \sim \mathbb{D}_\pi^S}\left[\ell\left(h\left(\Gamma\left(z\right) \odot z\right), y\right)\right]_{|z = g(x)}. \quad (7)$$

3.4.2 SUB-SPACE HYPOTHESES

To encourage the sub-space exploration and strengthen the sub-space hypotheses, given a data-label pair $(x, y) \sim \mathbb{D}_\pi^S$, we sample mask indicators from the Berboulli distribution with parameter $\Gamma_d\left(z_d\right)$, i.e,. $m_d \sim Ber\left(\Gamma_d\left(z_d\right)\right)$ to gather $m = \left[m_d\right]_{d=1}^D$, and then project onto a sub-space by $m \odot z$. Then, g, h are updated by minimizing the following loss function:

$$\mathcal{L}_H\left(g, h | \Gamma\right) = \mathbb{E}_{(x, y) \sim \mathbb{D}_\pi^S}\left[\mathbb{E}_{m \sim Ber(\Gamma(z))}\left[\ell\left(h\left(m \odot z\right), y\right)\right]\right]_{|z = g(x)}, \quad (8)$$

where $m \sim Ber\left(\Gamma\left(z\right)\right)$ means $m_d \sim Ber\left(\Gamma_d\left(z_d\right)\right), d = 1, ..., D$.

Finally, the pseudocode of our LASSO is summarized in Algorithm 1.

3.4.3 INFERENCE PROCESS

At the testing phase, we use two inference strategies: threshold and ensemble strategies

- **Ensemble**: for each target example x, we could compute $z = g\left(x\right)$, then sample T masks $m_1, ..., m_T \sim Ber\left(\Gamma\left(z\right)\right)$, and ensemble as $h_{\mathrm{En}} = \frac{1}{T} \sum_{t=1}^T h\left(m_t \odot z\right)$. However, for efficient computation, we approximate the ensemble prediction by: $h_{\mathrm{En}} \approx h\left(\Gamma\left(z\right) \odot z\right)$.
- **Threshold:** we employ a threshold $\tau \in [0, 1]$ to compute the mask. Specifically, for each target example x, we compute $z = g\left(x\right)$, then evaluate the mask $m = \left[\mathbf{1}_{\Gamma_d(z_d) > \tau}\right]_{d=1}^D$, where $\mathbf{1}$ is the indicator function, and predict as $h\left(m \odot z\right)$.

Algorithm 1 LASSO: Latent Sub-space Orientation for DG.

1: Initialize: encoder g, classifier h, *Sub-space indicator* Γ and dataset $\mathbb{D}_\pi^S$.
2: **for** epoch $= 1 \rightarrow$ epochs **do**
3:     **for** ite **in** iterations **do**
4:         Sample Mini-batch: $\mathbb{B} = \left\{ (x_i, y_i) \sim \mathbb{D}_\pi^S \right\}$
5:         Optimize $\mathcal{L}_I$ in Eq. (7) w.r.t Γ on $\mathbb{B}$.
6:         Optimize $\mathcal{L}_H$ in Eq. (8) w.r.t. h and g on $\mathbb{B}$.
7:     **end for**
8: **end for**
9: **Return:** The optimal: g^*, h^* and Γ^*.

---

4 EXPERIMENTS

4.1 EVALUATION ON BENCHMARK DATASETS

4.1.1 DATASETS

To evaluate the effectiveness of the proposed method, we utilize three datasets: PACS Li et al. (2017), VLCS Torralba & Efros (2011), and Office-Home Venkateswara et al. (2017), which are the common DG benchmarks with multi-source domains.

4.1.2 EVALUATION PROTOCOL

For PACS and VLCS, we follow the setting of Li et al. (2017) as these two datasets provide specific "train" and "validation" splits for each domain to ensure a fair comparison. We use the validation subsets from all training domains to create an overall validation set. On the target domain, we evaluate on the entire dataset. Office-Home also follows the leave-one-domain-out protocol in Li et al. (2017). In addition, the generalization of our method is based on the accuracy of the *sub-space indicator* Γ. Therefore, we choose the model when the sub-space indicator Γ converged. In particular, we train all models for the same fixed number of steps and consider only the final checkpoint. Finally, we report the average performance with error bars over 5 runs for all experimental settings and compare two variants of our proposed method LASSO$-\tau$ (the threshold variant) and LASSO-En (the ensemble variant) with the recent domain generalization baselines. Due to the paper space limit, we leave the details of experimental settings, our implementation and hyper-parameters in Appendix B.

4.1.3 RESULTS

We report the empirical results on PACS, VLCS, and Office-Home datasets using standard backbones such as AlexNet, ResNet18, and ResNet50 for the feature extractor. The results on VLCS using AlexNet are reported in Table 1, the results on Office-Home using ResNet18 and ResNet50 are reported in Table 2 and the results on PACS using three backbones are reported in Table 3 respectively. Those empirical results clearly show that our LASSO provides competitive classification accuracy compared to the baselines. Especially, the average results on Office-Home and PACS in Table 2 and Table 3 consistently show that our proposed method LASSO outperforms the ERM baseline with large margins on both backbones ResNet18 and ResNet50. Meanwhile, some other baselines also get comparative or better gains than ours with ResNet18, but the gains shrink with ResNet50 since larger ResNet backbones are known to generalize better (Gulrajani & Lopez-Paz, 2021).

Table 1: Classification Accuracy on VLCS.

Method	Backbone	PASCAL VOC	LabelMe	Caltech	Sun	Average
ERM Vapnik (1999)	AlexNet	70.58±0.00	59.72±0.00	96.25±0.00	64.51±0.00	72.56
MASF Dou et al. (2019)	AlexNet	69.14±0.00	**64.90±0.00**	94.78±0.00	**67.64±0.00**	74.11
JiGen Carlucci et al. (2019)	AlexNet	70.62±0.00	60.90±0.00	96.93±0.00	64.30±0.00	73.19
LASSO-τ	AlexNet	**71.55±0.21**	62.42±0.42	**97.33±0.22**	65.15±0.22	**74.15**
LASSO-En	AlexNet	71.37±0.08	62.26±0.19	97.17±0.31	65.25±0.26	74.01

Table 2: Classification Accuracy on Office-Home

Method	Backbone	Art	Clipart	Product	RealWorld	Average
ERM Vapnik (1999)	ResNet18	52.15±0.00	45.86±0.00	70.86±0.00	73.15±0.00	60.51
JiGen Carlucci et al. (2019)	ResNet18	53.04±0.00	47.51±0.00	71.47±0.00	72.79±0.00	61.20
RSC Huang et al. (2020)	ResNet18	58.42±0.00	47.90±0.00	71.63±0.00	74.54±0.00	63.12
L2A-OT Zhou et al. (2020a)	ResNet18	**60.60±0.00**	50.10±0.00	**74.80±0.00**	**77.00±0.00**	**65.60**
LASSO-τ	ResNet18	59.29±0.92	50.77±0.27	73.28±0.16	74.48±0.30	64.46
LASSO-En	ResNet18	58.63±0.27	**51.48±0.96**	72.99±0.15	74.46±0.30	64.39
ERM Vapnik (1999)	ResNet50	61.30±0.70	52.40±0.30	75.80±0.10	76.60±0.30	66.50
MLDG Li et al. (2018a)	ResNet50	61.50±0.90	53.20±0.60	75.00±1.20	77.50±0.40	66.80
RSC Huang et al. (2020)	ResNet50	60.70±1.40	51.40±0.30	74.80±1.10	75.10±1.3 0	65.50
LASSO-τ	ResNet50	66.56±0.04	**58.21±0.19**	**78.69±0.01**	**79.27±0.42**	**70.70**
LASSO-En	ResNet50	**67.07±0.38**	58.13±0.31	78.27±0.02	79.19±0.41	70.66

Table 3: Classification Accuracy on PACS.

Method	Backbone	Photo	Art-painting	Cartoon	Sketch	Average
ERM Vapnik (1999)	AlexNet	88.47±0.63	67.21±0.72	66.12±0.51	55.32±0.44	69.28
MLDG Li et al. (2018a)	AlexNet	88.00±0.00	66.23±0.00	66.88±0.00	58.96±0.00	70.01
MASF Dou et al. (2019)	AlexNet	90.68±0.12	**70.35±0.33**	**72.46±0.19**	67.33±0.12	**75.21**
JiGen Carlucci et al. (2019)	AlexNet	89.00±0.00	67.63±0.00	71.71±0.00	65.18±0.00	73.38
MetaReg Balaji et al. (2018)	AlexNet	**91.07±0.41**	69.82±0.76	70.35±0.63	59.26±0.31	72.62
DMG Chattopadhyay et al. (2020)	AlexNet	87.31±0.00	64.65±0.00	69.88±0.00	**71.42±0.00**	73.32
LASSO-τ	AlexNet	89.45±0.03	69.34±0.64	70.91±0.25	69.01±0.54	74.68
LASSO-En	AlexNet	89.12±0.06	69.19±0.48	70.49±0.21	68.92±0.67	74.43
ERM Vapnik (1999)	ResNet18	95.84±0.27	77.86±1.29	76.91±0.64	75.43±0.37	81.51
MLDG Li et al. (2018a)	ResNet18	94.30±0.00	79.50±0.00	77.30±0.00	71.50±0.00	80.70
MASF Dou et al. (2019)	ResNet18	94.99±0.09	80.29±0.18	77.17±0.08	71.69±0.22	81.04
JiGen Carlucci et al. (2019)	ResNet18	96.03±0.00	79.42±0.00	75.25±0.00	71.35±0.00	79.14
MetaReg Balaji et al. (2018)	ResNet18	95.50±0.24	**83.70±0.19**	77.20±0.31	70.30±0.28	81.70
DMG Chattopadhyay et al. (2020)	ResNet18	93.35±0.00	76.90±0.00	**80.38±0.00**	75.21±0.00	81.46
L2A-OT Zhou et al. (2020a)	ResNet18	**96.20±0.00**	83.30±0.00	78.20±0.00	73.60±0.00	82.80
RSC Huang et al. (2020)	ResNet18	93.52±0.00	78.40±0.00	78.80±0.00	79.78±0.00	82.63
LASSO-τ	ResNet18	94.76±0.03	82.17±0.60	78.37±0.55	77.34±0.37	**83.16**
LASSO-En	ResNet18	94.76±0.03	82.02±0.75	77.65±0.76	77.07±0.42	82.87
ERM Vapnik (1999)	ResNet50	97.2±0.30	84.7±0.40	80.8±0.60	79.3±1.00	85.50
MLDG Li et al. (2018a)	ResNet50	97.4±0.30	85.5±1.40	80.1±1.70	76.6±1.10	84.90
MetaReg Balaji et al. (2018)	ResNet50	**97.6±0.31**	87.2±0.13	79.2±0.27	70.3±0.18	83.60
DMG Chattopadhyay et al. (2020)	ResNet50	95.0±0.00	82.9±0.00	80.5±0.00	72.3±0.00	82.67
RSC Huang et al. (2020)	ResNet50	97.6±0.30	85.4±0.80	79.7±1.80	78.2±1.20	85.20
LASSO-τ	ResNet50	96.62±0.56	**87.81±0.69**	**82.99±0.71**	**82.33±0.20**	**87.43**
LASSO-En	ResNet50	96.93±0.65	87.23±0.57	82.55±1.09	81.95±0.37	87.15

4.2 ABLATION STUDY

(a) Latent visualization of **all four domains**, different colors represent different domains.

(b) Latent visualization of **target domain only**, different colors represent different classes.

Figure 1: The t-SNE feature visualization of two methods ERM and LASSO-τ for experiment on PACS dataset with "Sketch" (represented by blue in 1a) as target domain using ResNet50.

Sub-space representation: To better understand the benefits of learning latent sub-spaces, we visualize the distribution of the learned features to analyze the latent space generated by ERM and LASSO-τ using t-SNE van der Maaten & Hinton (2008) in Figure 1. Furthermore, we decide to choose "sketch" which contains only colorless images as the target domain. This domain can be considered as the most distant domain from the others and hence results in the largest source-target divergence. Figure 1a shows feature distributions of different domains on latent space, in which samples are colored accordingly to domain label, with source domains are in red, green and back, while target domain is in blue. As it can be clearly seen, ERM training results in representations with high cross-domain separation for both target and source domains. On the other hands, the domain representations on a sub-latent space of LASSO is more homogeneously mixed, since samples

from different domains are hardly distinguished. Figure 1b further shows that features from different classes are more compact and clearly separated on LASSO's sub-latent space than on full single latent space. These results indicate that feature distributions are better aligned on latent sub-space with our proposed LASSO approach.

Additionally, we further verify the data shift reduction on sub-spaces by measuring the divergence between the source and target distributions of ERM and LASSO-τ via Jensen-Shannon (JS) divergence ($\mathcal{R}_{JS}$). We employ a domain discriminator h_d which distinguishes the source domain:

$$\mathcal{L}(h_d) = \mathbb{E}_{x \sim P_\pi^S}\left[\log(h_d(G(x)))\right] + \mathbb{E}_{x \sim P^T}\left[\log(1 - h_d(G(x)))\right], \tag{9}$$

where G is the feature extractor, which is g for ERM and g^Γ for LASSO-τ. It is well-known that if we search h_d in a family with infinite capacity then $\mathcal{R}_{JS}(G_\# P_\pi^S || G_\# P^T) = \max_{h_d} \frac{\mathcal{L}(h_d) + 2\log 2}{2}$ (Goodfellow et al., 2014). The empirical results $\mathcal{R}_{JS}^{\text{ERM}} = 0.247$ and $\mathcal{R}_{JS}^{\text{LASSO-}\tau} = 0.164$ show that the latent distribution divergence between sources and target domains is decreased on sub-spaces. This observation once again provides supporting evidences for our approach.

Effect of τ: we present the performance on validation set (Val) of source domains and target domain with different thresholds τ to analyze its effect along with the average number of selected features. The Table 4 demonstrates that by choosing reasonable τ, the model performance can be improved since latent is mapped to appropriate sub-space (i.e sub-space being compact to reduce the data shift while preserving sufficient informative features for label prediction). Alternatively, in the case of large τ, the performance can be dropped since very few features remain. It also can be seen that with $\tau = 0.6$ and $\tau = 0.7$, the model utilizes

Table 4: Average number of selected features (SF) based on τ and its performance (a trial on PACS dataset with "sketch" as target domain using ResNet50).

τ	val-SF	Val	target-SF	Target
$0 \to 0.5$	2048	97.24	2048	82.86
0.6	64.8	97.63	59.9	83.38
0.7	20.9	96.75	15.4	83.63
0.8	7.8	84.23	3.4	79.30
0.9	2.7	61.52	1.4	45.58

only a small number of features (.i.e 59.9 and 14.4 on target domain) but nonetheless still yields good results. This indicates that *sub-indicator* Γ is able to identify essential label-informative features.

Table 5: Performance LASSO-τ with different Γ_d settings.

Method	Backbone	Photo	Art-painting	Cartoon	Sketch	Average
LASSO-τ $\Gamma_d(z)$	ResNet50	97.01$\pm$0.16	87.30$\pm$0.52	81.91$\pm$0.46	80.02$\pm$0.45	86.56
LASSO-τ $\Gamma_d(z_d)$	ResNet50	96.62$\pm$0.56	87.81$\pm$0.69	82.99$\pm$0.71	82.33$\pm$0.20	87.43

Effect of the attribute-based Γ_d: In order to analyze the benefit of attribute-based Γ_d, we examine the performance on the setting of $\Gamma_d(z)$ which uses full latent z as input for Γ_d and $\Gamma_d(z_d)$ which uses only attribute z_d as input for Γ_d. As can be seen from Table 5, both $\Gamma_d(z_d)$ and $\Gamma_d(z)$ achieve competitive performances on target domain: "Photo", "Art-painting" and "cartoon" domain but $\Gamma_d(z_d)$ setting outperform on "sketch" domain. Remind that using "sketch" as target domain results in the largest source-target divergence. The results in "sketch" demonstrate that $\Gamma_d(z)$ becomes less efficient when source-target divergence. In contrast, $\Gamma_d(z)$ shows its better generalization as not be interfered by other noisy attributes.

5 CONCLUSION

In this paper, we first theoretically analyze the upper bound of target loss on latent space in domain generalization settings and the main factor that affects the performance. Then we point out that learning on appropriate latent sup-space can derive better generalization performance for domain generalization task. Motivated by this, we have proposed a novel LASSO framework which can: (1) learn diverse latent sub-spaces and corresponding individual hypotheses and (2) project source and target examples onto appropriate sub-spaces preserving crucial label-informative features for label prediction, while reducing the latent data shift due to the sub-spaces compactness compared to the entire latent space. Experiments on benchmark datasets verify that LASSO achieves competitive and even state-of-the-art performances.

REFERENCES

Yogesh Balaji, Swami Sankaranarayanan, and Rama Chellappa. Metareg: Towards domain generalization using meta-regularization. In *Advances in Neural Information Processing Systems*, pp. 998–1008, 2018.

Shai Ben-David, John Blitzer, Koby Crammer, Alex Kulesza, Fernando Pereira, and Jennifer Wortman Vaughan. A theory of learning from different domains. *Machine learning*, 79(1-2):151–175, 2010.

Fabio M Carlucci, Antonio D'Innocente, Silvia Bucci, Barbara Caputo, and Tatiana Tommasi. Domain generalization by solving jigsaw puzzles. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2229–2238, 2019.

Prithvijit Chattopadhyay, Yogesh Balaji, and Judy Hoffman. Learning to balance specificity and invariance for in and out of domain generalization. In *European Conference on Computer Vision*, pp. 301–318. Springer, 2020.

Hal Daumé III. Frustratingly easy domain adaptation. *arXiv preprint arXiv:0907.1815*, 2009.

Qi Dou, Daniel Coelho de Castro, Konstantinos Kamnitsas, and Ben Glocker. Domain generalization via model-agnostic learning of semantic features. In *Advances in Neural Information Processing Systems*, pp. 6450–6461, 2019.

Yaroslav Ganin, Evgeniya Ustinova, Hana Ajakan, Pascal Germain, Hugo Larochelle, François Laviolette, Mario Marchand, and Victor Lempitsky. Domain-adversarial training of neural networks. *The Journal of Machine Learning Research*, 17(1):2096–2030, 2016.

Muhammad Ghifary, W Bastiaan Kleijn, Mengjie Zhang, and David Balduzzi. Domain generalization for object recognition with multi-task autoencoders. In *Proceedings of the IEEE international conference on computer vision*, pp. 2551–2559, 2015.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. *Advances in neural information processing systems*, 27, 2014.

Ishaan Gulrajani and David Lopez-Paz. In search of lost domain generalization. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=lQdXeXDoWtI.

Zeyi Huang, Haohan Wang, Eric P. Xing, and Dong Huang. Self-challenging improves cross-domain generalization. In *ECCV*, 2020.

Maximilian Ilse, Jakub M Tomczak, Christos Louizos, and Max Welling. Diva: Domain invariant variational autoencoders. In *Medical Imaging with Deep Learning*, pp. 322–348. PMLR, 2020.

F. D. Johansson, D. Sontag, and R. Ranganath. Support and invertibility in domain-invariant representations. In *Proceedings of Machine Learning Research*, volume 89, pp. 527–536, 2019.

Da Li, Yongxin Yang, Yi-Zhe Song, and Timothy M Hospedales. Deeper, broader and artier domain generalization. In *Proceedings of the IEEE international conference on computer vision*, pp. 5542–5550, 2017.

Da Li, Yongxin Yang, Yi-Zhe Song, and Timothy Hospedales. Learning to generalize: Meta-learning for domain generalization. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32, 2018a.

Haoliang Li, Sinno Jialin Pan, Shiqi Wang, and Alex C Kot. Domain generalization with adversarial feature learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 5400–5409, 2018b.

Yishay Mansour, Mehryar Mohri, and Afshin Rostamizadeh. Domain adaptation: Learning bounds and algorithms. *arXiv preprint arXiv:0902.3430*, 2009.

Saeid Motiian, Marco Piccirilli, Donald A Adjeroh, and Gianfranco Doretto. Unified deep supervised domain adaptation and generalization. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 5715–5725, 2017.

Krikamol Muandet, David Balduzzi, and Bernhard Schölkopf. Domain generalization via invariant feature representation. In *International Conference on Machine Learning*, pp. 10–18, 2013.

Vihari Piratla, Praneeth Netrapalli, and Sunita Sarawagi. Efficient domain generalization via common-specific low-rank decomposition. In *International Conference on Machine Learning*, pp. 7728–7738. PMLR, 2020.

Seonguk Seo, Yumin Suh, Dongwan Kim, Geeho Kim, Jongwoo Han, and Bohyung Han. Learning to optimize domain specific normalization for domain generalization. In *Computer Vision–ECCV 2020: 16th European Conference, Glasgow, UK, August 23–28, 2020, Proceedings, Part XXII 16*, pp. 68–83. Springer, 2020.

Shiv Shankar, Vihari Piratla, Soumen Chakrabarti, Siddhartha Chaudhuri, Preethi Jyothi, and Sunita Sarawagi. Generalizing across domains via cross-gradient training. *arXiv preprint arXiv:1804.10745*, 2018.

Antonio Torralba and Alexei A Efros. Unbiased look at dataset bias. In *CVPR 2011*, pp. 1521–1528. IEEE, 2011.

Laurens van der Maaten and Geoffrey Hinton. Visualizing data using t-sne, 2008.

Vladimir N Vapnik. An overview of statistical learning theory. *IEEE transactions on neural networks*, 10(5):988–999, 1999.

Hemanth Venkateswara, Jose Eusebio, Shayok Chakraborty, and Sethuraman Panchanathan. Deep hashing network for unsupervised domain adaptation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 5018–5027, 2017.

Haohan Wang, Zexue He, Zachary C Lipton, and Eric P Xing. Learning robust representations by projecting superficial statistics out. *arXiv preprint arXiv:1903.06256*, 2019.

Qizhe Xie, Zihang Dai, Yulun Du, Eduard Hovy, and Graham Neubig. Controllable invariance through adversarial feature learning. In *Advances in Neural Information Processing Systems*, pp. 585–596, 2017.

Shanshan Zhao, Mingming Gong, Tongliang Liu, Huan Fu, and Dacheng Tao. Domain generalization via entropy regularization. *Advances in Neural Information Processing Systems*, 33, 2020.

Kaiyang Zhou, Yongxin Yang, Timothy Hospedales, and Tao Xiang. Learning to generate novel domains for domain generalization. In *European Conference on Computer Vision*, pp. 561–578. Springer, 2020a.

Kaiyang Zhou, Yongxin Yang, Timothy M Hospedales, and Tao Xiang. Deep domain-adversarial image generation for domain generalisation. In *AAAI*, pp. 13025–13032, 2020b.

Kaiyang Zhou, Yongxin Yang, Yu Qiao, and Tao Xiang. Domain generalization with mixstyle. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=6xHJ37MVxxp.

A THEORETICAL DEVELOPMENT

In this Section, we present all proofs relevant to theory developed in our paper. We begin with a crucial proposition for our theory development.

Proposition A.1. Let $f : \mathcal{X} \mapsto \mathcal{Y}_\Delta$ where $f = h \circ g$ with $g : \mathcal{X} \mapsto \mathcal{Z}$ and $h : \mathcal{Z} \mapsto \mathcal{Y}_\Delta$.

i) We have

$$\sum_{y=1}^{C} \int \ell\left(h\left(z\right), y\right) p^{g}\left(y \mid z\right) p^{g}\left(z\right) dz = \sum_{y=1}^{C} \int \ell\left(f\left(x\right), y\right) p\left(y \mid x\right) p\left(x\right) dx,$$

where $p^{g}\left(y \mid z\right) = \frac{\int_{g^{-1}(z)} p(y|x)p(x)dx}{\int_{g^{-1}(z)} p(x)dx}$ for any $z \in g\left(\mathcal{X}\right)$ and $p^{g}\left(z\right) = \int_{g^{-1}(z)} p\left(x\right) dx$ is the density of the push-forward distribution $\mathbb{P}^{g} = g_{\#}\mathbb{P}$.

ii) We have

$$\sum_{y=1}^{C} \int \left|p^{1,g}\left(y \mid z\right) - p^{2,g}\left(y \mid z\right)\right| p^{g}\left(z\right) dz \leq \sum_{y=1}^{C} \int \left|p^{1}\left(y \mid x\right) - p^{2}\left(y \mid x\right)\right| p\left(x\right) dx,$$

where $p^{g}\left(z\right) = \int_{g^{-1}(z)} p\left(x\right) dx$ is the density of the push-forward distribution $\mathbb{P}^{g} = g_{\#}\mathbb{P}$ and $p^{1,g}\left(y \mid z\right) = \frac{\int_{g^{-1}(z)} p^{1}(y|x)p(x)dx}{\int_{g^{-1}(z)} p(x)dx}$ and $p^{2,g}\left(y \mid z\right) = \frac{\int_{g^{-1}(z)} p^{2}(y|x)p(x)dx}{\int_{g^{-1}(z)} p(x)dx}$ for any $z \in g\left(\mathcal{X}\right)$.

Proof. i) We first prove for any $y \in [C]$ that

$$\int \ell\left(h\left(z\right), y\right) p^{g}\left(y \mid z\right) p^{g}\left(z\right) dz = \int \ell\left(f\left(x\right), y\right) p\left(y \mid x\right) p\left(x\right) dx.$$

In fact, we have

$$
\begin{aligned}
\int \ell\left(h\left(z\right), y\right) p^{g}\left(y \mid z\right) p^{g}\left(z\right) dz &= \int_{\mathcal{Z}} \ell\left(h\left(z\right), y\right) \frac{\int_{g^{-1}(z)} p\left(y \mid x\right) p\left(x\right) dx}{\int_{g^{-1}(z)} p\left(x\right) dx} \int_{g^{-1}(z)} p\left(x\right) dx dz \\
&= \int_{\mathcal{Z}} \ell\left(h\left(z\right), y\right) \int_{g^{-1}(z)} p\left(y \mid x\right) p\left(x\right) dx dz \\
&= \int_{\mathcal{Z}} \int_{g^{-1}(z)} \ell\left(h\left(z\right), y\right) p\left(y \mid x\right) p\left(x\right) dx dz \\
&= \int_{\mathcal{Z}} \int_{\mathcal{X}} \mathbf{1}_{x \in g^{-1}(z)} \ell\left(h\left(z\right), y\right) p\left(y \mid x\right) p\left(x\right) dx dz \\
&\overset{(1)}{=} \int_{\mathcal{X}} \int_{\mathcal{Z}} \mathbf{1}_{x \in g^{-1}(z)} \ell\left(h\left(z\right), y\right) p\left(y \mid x\right) p\left(x\right) dz dx \\
&= \int_{\mathcal{X}} \int_{\mathcal{Z}} \mathbf{1}_{z = g(x)} \ell\left(h\left(z\right), y\right) p\left(y \mid x\right) p\left(x\right) dz dx \\
&= \int_{\mathcal{X}} \ell\left(h\left(g\left(x\right)\right), y\right) p\left(y \mid x\right) p\left(x\right) dx \\
&= \int \ell\left(f\left(x\right), y\right) p\left(y \mid x\right) p\left(x\right) dx.
\end{aligned}
$$

where note that $\mathbf{1}_{\text{condition}}$ is the indicator function which returns 1 if condition is true and 0 otherwise, the equality in $\overset{(1)}{=}$ due to Fubini theorem.

Finally, we reach

$$\sum_{y=1}^{C} \int \ell\left(h\left(z\right), y\right) p^{g}\left(y \mid z\right) p^{g}\left(z\right) dz = \sum_{y=1}^{C} \int \ell\left(f\left(x\right), y\right) p\left(y \mid x\right) p\left(x\right) dx.$$

ii) We then prove that

$$\int \left|p^{1,g}\left(y \mid z\right) - p^{2,g}\left(y \mid z\right)\right| p^{g}\left(z\right) dz \leq \int \left|p^{1}\left(y \mid x\right) - p^{2}\left(y \mid x\right)\right| p\left(x\right) dx, \forall y \in [C].$$

We derive as

$$
\int_{\mathcal{Z}} \left| p^{1,g} \left(y \mid z \right) - p^{2,g} \left(y \mid z \right) \right| p^g \left(z \right) dz
$$

$$
= \int_{\mathcal{Z}} \left| \frac{\int_{g^{-1}(z)} p^1 \left(y \mid x \right) p \left(x \right) dx}{\int_{g^{-1}(z)} p \left(x \right) dx} - \frac{\int_{g^{-1}(z)} p^2 \left(y \mid x \right) p \left(x \right) dx}{\int_{g^{-1}(z)} p \left(x \right) dx} \right| \int_{g^{-1}(z)} p \left(x \right) dx dz
$$

$$
= \int_{\mathcal{Z}} \left| \int_{g^{-1}(z)} p^1 \left(y \mid x \right) p \left(x \right) dx - \int_{g^{-1}(z)} p^2 \left(y \mid x \right) p \left(x \right) dx \right| dz
$$

$$
= \int_{\mathcal{Z}} \left| \int_{g^{-1}(z)} \left[p^1 \left(y \mid x \right) - p^2 \left(y \mid x \right) \right] p \left(x \right) dx \right| dz
$$

$$
\leq \int_{\mathcal{Z}} \int_{g^{-1}(z)} \left| p^1 \left(y \mid x \right) - p^2 \left(y \mid x \right) \right| p \left(x \right) dx dz
$$

$$
= \int_{\mathcal{Z}} \int_{\mathcal{X}} \mathbf{1}_{x \in g^{-1}(z)} \left| p^1 \left(y \mid x \right) - p^2 \left(y \mid x \right) \right| p \left(x \right) dx dz
$$

$$
\overset{(1)}{=} \int_{\mathcal{X}} \int_{\mathcal{Z}} \mathbf{1}_{z = g(x)} \left| p^1 \left(y \mid x \right) - p^2 \left(y \mid x \right) \right| p \left(x \right) dz dx
$$

$$
= \int_{\mathcal{X}} \left| p^1 \left(y \mid x \right) - p^2 \left(y \mid x \right) \right| p \left(x \right) dx.
$$

where in the derivation of $\overset{(1)}{=}$, we use Fubini theorem again. $\qquad \square$

.

Theorem 4. *(Theorem 1 in the main paper)* *If the loss function ℓ is upper-bounded by a positive constant L, the target general loss is upper-bounded by:*

$$
\mathcal{L}(f, \mathbb{D}^T) \leq \exp \left\{ R^\alpha \left(g_\# \mathbb{P}^T, g_\# \mathbb{P}^S_\pi \right) \right\}^{\frac{\alpha-1}{\alpha}} L^{\frac{1}{\alpha}} \left[\mathcal{L} \left(f, \mathbb{D}^S_\pi \right) + L \max_k \mathbb{E}_{\mathbb{P}^S_k} \left[\| \Delta p_k \left(y \mid \boldsymbol{x} \right) \|_1 \right] \right]^{\frac{\alpha-1}{\alpha}},
$$
(10)

where $g_\# \mathbb{P}^S_\pi$ and $g_\# \mathbb{P}^T$ are pushed-forward distributions induced by applying g on $\mathbb{P}^S_\pi$ and $\mathbb{P}^T$, R^α is the α-divergence ($\alpha > 1$), and $\Delta p_k \left(y \mid \boldsymbol{x} \right) := \left[\left| p^S_k \left(y = c \mid x \right) - p^T \left(y = c \mid x \right) \right| \right]_{c=1}^C$ represents the label shift between the labeling assignment mechanisms of an individual source domain and target domain on the input space.

Proof. Let $\mathbb{D}^{S,g}_\pi$ be the joint distribution including the pairs (y, z) where $k \sim Cat \left(\pi \right)$, $z \sim p^{S,g}_k \left(z \right)$, and $y \sim p^{S,g}_k \left(y \mid z \right)$. The density $p^{S,g}_\pi \left(y, z \right)$ of this distribution is as follows:

$$
p^{S,g}_\pi \left(y, z \right) = \sum_{k=1}^K \pi_k p^{S,g}_k \left(z \right) p^{S,g}_k \left(y \mid z \right) = \sum_{k=1}^K \pi_k p^{S,g}_k \left(y, z \right).
$$

Let $\mathbb{D}^{T,g}$ be the joint distribution including the pairs (y, z) where $z \sim p^{T,g} \left(z \right)$ and $y \sim p^{T,g} \left(y \mid z \right)$. The density $p^{T,g}(y, z)$ of this distribution is as follows:

$$
p^{T,g}(y, z) = p^{T,g} \left(z \right) p^{T,g} \left(y \mid z \right).
$$

Eventually, we denote $\mathbb{D}^{h,g}$ as the joint distribution including the pairs (y, z) where $z \sim p^{S,g}_\pi \left(z \right) := \sum_{k=1}^K \pi_k p^{S,g}_k \left(z \right)$ and $y \sim p^{T,g} \left(y \mid z \right)$. The density $p^{h,g} \left(y, z \right)$ of this distribution is as follows:

$$
p^{h,g} \left(y, z \right) = p^{S,g}_\pi \left(z \right) p^{T,g} \left(y \mid z \right) = \sum_{k=1}^K \pi_k p^{S,g}_k \left(z \right) p^{T,g} \left(y \mid z \right).
$$

With the above equipment, we have

$$
\begin{aligned}
\mathcal{L}\left(h, \mathbb{D}^{h,g}\right) &= \int \ell\left(h\left(z\right), y\right) p^{h,g}\left(z, y\right) dzdy \\
&= \mathcal{L}\left(h, \mathbb{D}_\pi^{S,g}\right) + \int \ell\left(h\left(z\right), y\right) \left[p^{h,g}\left(z, y\right) - p_\pi^{S,g}\left(z, y\right)\right] dzdy \\
&\leq \mathcal{L}\left(h, \mathbb{D}_\pi^{S,g}\right) + \int \ell\left(h\left(z\right), y\right) |p^{h,g}\left(z, y\right) - p_\pi^{S,g}\left(z, y\right)| dzdy \\
&\leq \mathcal{L}\left(h, \mathbb{D}_\pi^{S,g}\right) + L \int |p^{h,g}\left(z, y\right) - p_\pi^{S,g}\left(z, y\right)| dzdy \\
&= \mathcal{L}\left(h, \mathbb{D}_\pi^{S,g}\right) + L \int \sum_{k=1}^{K} \pi_k p_k^{S,g}\left(z\right) |p^{T,g}\left(y \mid z\right) - p_k^{S,g}\left(y \mid z\right)| dzdy \\
&= \mathcal{L}\left(h, \mathbb{D}_\pi^{S,g}\right) + L \sum_{y=1}^{C} \sum_{k=1}^{K} \pi_k \int |p^{T,g}\left(y \mid z\right) - p_k^{S,g}\left(y \mid z\right)| p_k^{S,g}\left(z\right) dz.
\end{aligned}
$$

We further note that

$$
\begin{aligned}
\mathcal{L}\left(h, \mathbb{D}_\pi^{S,g}\right) &= \sum_{y=1}^{C} \int \ell\left(h(z), y\right) p_\pi^{S,g}\left(y, z\right) dz \\
&= \sum_{y=1}^{C} \sum_{k=1}^{K} \pi_k \int \ell\left(h(z), y\right) p_k^{S,g}\left(y \mid z\right) p_k\left(z\right) dz \\
&= \sum_{k=1}^{K} \pi_k \sum_{y=1}^{C} \int \ell\left(h(z), y\right) p_k^{S,g}\left(y \mid z\right) p_k\left(z\right) dz \\
&\stackrel{(1)}{=} \sum_{k=1}^{K} \sum_{y=1}^{C} \pi_k \int \ell\left(f(x), y\right) p_k^{S}\left(y \mid x\right) p_k\left(x\right) dx = \mathcal{L}\left(f, \mathbb{D}_\pi^{S}\right),
\end{aligned}
$$

where we have $\stackrel{(1)}{=}$ by using Proposition A.1 (i).

$$
\begin{aligned}
&\sum_{y=1}^{C} \sum_{k=1}^{K} \pi_k \int |p^{T,g}\left(y \mid z\right) - p_k^{S,g}\left(y \mid z\right)| p_k^{S,g}\left(z\right) dz \\
&= \sum_{k=1}^{K} \pi_k \sum_{y=1}^{C} \int |p^{T,g}\left(y \mid z\right) - p_k^{S,g}\left(y \mid z\right)| p_k^{S,g}\left(z\right) dz \\
&\stackrel{(2)}{\leq} \sum_{k=1}^{K} \pi_k \sum_{y=1}^{C} \int |p^{T}\left(y \mid x\right) - p_k^{S}\left(y \mid x\right)| p_k^{S}\left(x\right) dx \\
&= \sum_{k=1}^{K} \pi_k \int \sum_{y=1}^{C} |p^{T}\left(y \mid x\right) - p_k^{S}\left(y \mid x\right)| p_k^{S}\left(x\right) dx \\
&= \sum_{k=1}^{K} \pi_k \mathbb{E}_{\mathbb{P}_k^S}\left[\|\Delta p_k\left(y \mid \mathbf{x}\right)\|_1\right] \leq \max_k \mathbb{E}_{\mathbb{P}_k^S}\left[\|\Delta p_k\left(y \mid \mathbf{x}\right)\|_1\right],
\end{aligned}
$$

where we have $\stackrel{(2)}{=}$ by using Proposition A.1 (ii).

Therefore, we obtain

$$
\mathcal{L}\left(h, \mathbb{D}^{h,g}\right) \leq \mathcal{L}\left(f, \mathbb{D}_\pi^{S}\right) + \max_k \mathbb{E}_{\mathbb{P}_k^S}\left[\|\Delta p_k\left(y \mid \mathbf{x}\right)\|_1\right]. \tag{11}
$$

Finally, we manipulate $\mathcal{L}\left(h, \mathbb{D}^{T,g}\right)$ as

$$\mathcal{L}\left(h, \mathbb{D}^{T,g}\right) = \int_{\mathcal{Y} \times \mathcal{Z}} \ell\left(h\left(z\right), y\right) p^{T,g}\left(z, y\right) dz dy$$

$$= \int_{\mathcal{Y} \times \mathcal{Z}} \frac{p^{T,g}\left(z, y\right)}{p^{h,g}\left(z, y\right)^{\frac{\alpha-1}{\alpha}}} p^{h,g}\left(z, y\right)^{\frac{\alpha-1}{\alpha}} \ell\left(h\left(z\right), y\right) dz dy.$$

The Holder inequality gives us

$$\mathcal{L}\left(h, \mathbb{D}^{T,g}\right) \le \left[\int_{\mathcal{Y} \times \mathcal{Z}} \frac{p^{T,g}\left(z, y\right)^{\alpha}}{p^{h,g}\left(z, y\right)^{\alpha-1}} dz dy\right]^{\frac{1}{\alpha}} \left[\int_{\mathcal{Y} \times \mathcal{Z}} p^{h,g}\left(z, y\right) \ell\left(h\left(z\right), y\right)^{\frac{\alpha}{\alpha-1}} dz dy\right]^{\frac{\alpha-1}{\alpha}}.$$

Referring to the definition of the Rényi divergence and note that $\ell\left(h\left(z\right), y\right) \le L$, we obtain

$$\mathcal{L}\left(h, \mathbb{D}^{T,g}\right) \le \left[\exp\left\{R^{\alpha}\left(\mathbb{D}^{T,g} \| \mathbb{D}^{h,g}\right)\right\} \mathcal{L}\left(h, \mathbb{D}^{h,g}\right)\right]^{\frac{\alpha-1}{\alpha}} L^{\frac{1}{\alpha}}. \tag{12}$$

We further derive

$$R^{\alpha}\left(\mathbb{D}^{T,g} \| \mathbb{D}^{h,g}\right) = \frac{1}{\alpha-1} \log\left(\int \left[\frac{p^{T,g}\left(z, y\right)}{p^{h,g}\left(z, y\right)}\right]^{\alpha-1} p^{T,g}\left(z, y\right) dz dy\right)$$

$$= \frac{1}{\alpha-1} \log\left(\int \left[\frac{p^{T,g}\left(z\right) p^{T,g}\left(y \mid z\right)}{p_{\pi}^{S,g}\left(z\right) p^{T,g}\left(y \mid z\right)}\right]^{\alpha-1} p^{T,g}\left(z, y\right) dz dy\right)$$

$$= \frac{1}{\alpha-1} \log\left(\int \left[\frac{p^{T,g}\left(z\right)}{p_{\pi}^{S,g}\left(z\right)}\right]^{\alpha-1} p^{T,g}\left(z, y\right) dz dy\right)$$

$$= \frac{1}{\alpha-1} \log\left(\int \left[\frac{p^{T,g}\left(z\right)}{p_{\pi}^{S,g}\left(z\right)}\right]^{\alpha-1} \sum_{y=1}^{C} p^{T,g}\left(z, y\right) dz\right)$$

$$= \frac{1}{\alpha-1} \log\left(\int \left[\frac{p^{T,g}\left(z\right)}{p_{\pi}^{S,g}\left(z\right)}\right]^{\alpha-1} p^{T,g}\left(z\right) dz\right)$$

$$= R^{\alpha}\left(g_{\#}\mathbb{P}^{T} \| g_{\#}\mathbb{P}_{\pi}^{S}\right). \tag{13}$$

Therefore, combining (12) and (13), we reach the following inequality:

$$\mathcal{L}\left(h, \mathbb{D}^{T,g}\right) \le \left[\exp\left\{R^{\alpha}\left(g_{\#}\mathbb{P}^{T} \| g_{\#}\mathbb{P}_{\pi}^{S}\right)\right\} \mathcal{L}\left(h, \mathbb{D}^{h,g}\right)\right]^{\frac{\alpha-1}{\alpha}} L^{\frac{1}{\alpha}}.$$

Subsequently, by noting that

$$\mathcal{L}\left(h, \mathbb{D}_{\pi}^{T,g}\right) = \sum_{y=1}^{C} \int \ell\left(h(z), y\right) p^{T,g}\left(y \mid z\right) p^{T,g}\left(z\right) dz$$

$$\overset{(1)}{=} \sum_{y=1}^{C} \int \ell\left(f\left(x\right), y\right) p^{T}\left(y \mid x\right) p^{T}\left(x\right) dx = \mathcal{L}\left(f, \mathbb{D}^{T}\right),$$

we reach

$$\mathcal{L}\left(f, \mathbb{D}^{T}\right) \le \left[\exp\left\{R^{\alpha}\left(g_{\#}\mathbb{P}^{T} \| g_{\#}\mathbb{P}_{\pi}^{S}\right)\right\} \mathcal{L}\left(h, \mathbb{D}^{h,g}\right)\right]^{\frac{\alpha-1}{\alpha}} L^{\frac{1}{\alpha}}.$$

Finally, referring to the inequality in (11), we reach the conclusion. $\square$

Remark: We would like to highlight that our Theorem 1 despite developing in a general context of DG is also novel due to two following reasons: (i) it proposes the target loss upper-bound in a

general setting of multi-class classification with a sufficiently general loss, which can be viewed as a non-trivial generalization of existing works in DA and DG (Mansour et al., 2009; Ben-David et al., 2010; Daumé III, 2009) and (ii) our bound is interweaving both input and latent spaces, which is novel and appropriate for theoretical analyses in deep learning, while the bounds in previous works only involve input space.

Theorem 5. *(Theorem 2 in the main paper) Given a deterministic sub-space indicator Γ, if the loss function ℓ is upper-bounded by a positive constant L, the sub-space target general loss is upper-bounded by:*

$$\mathcal{L}\left(f_{\mathcal{M}}, \mathbb{D}^T\right) \leq \frac{L^{\frac{1}{\alpha}}}{|\mathcal{M}|} \sum_{m \in \mathcal{M}} \exp\left\{R^\alpha\left(g^\Gamma{}_{\#}\mathbb{P}_m^T, g^\Gamma{}_{\#}\mathbb{P}_m^S\right)\right\}^{\frac{\alpha-1}{\alpha}} \left[\mathcal{L}\left(f_m, \mathbb{D}_m^S\right) + L\Delta p_m\right]^{\frac{\alpha-1}{\alpha}}, \quad (14)$$

where $\mathbb{D}_m^S$ is the joint distribution of (x,y) with $x \sim \mathbb{P}_m^S$ and $y \sim p_m^S(\cdot \mid x)$, and $\Delta p_m :=$ $\mathbb{E}_{x \sim \mathbb{P}_m^S}\left[\left\|p_m^S(\cdot \mid x) - p_m^T(\cdot \mid x)\right\|_1\right]$. sub-space indices m.

Proof. Given a sub-space index $m \in \mathcal{M}$, by noting that $f_m(x) = h\left(g^\Gamma(x)\right)$ with $x \sim \mathbb{P}_m^S$ over A_m, using the same proof for a single space in Theorem 4, we obtain

$$\mathcal{L}\left(f_m, \mathbb{D}^T\right) \leq L^{\frac{1}{\alpha}} \exp\left\{R^\alpha\left(g^\Gamma{}_{\#}\mathbb{P}_m^T, g^\Gamma{}_{\#}\mathbb{P}_m^S\right)\right\}^{\frac{\alpha-1}{\alpha}} \left[\mathcal{L}\left(f_m, \mathbb{D}_m^S\right) + L\Delta p_m\right]^{\frac{\alpha-1}{\alpha}}.$$

Finally, taking average over $m \in \mathcal{M}$, we reach

$$\mathcal{L}\left(f_{\mathcal{M}}, \mathbb{D}^T\right) \leq \frac{L^{\frac{1}{\alpha}}}{|\mathcal{M}|} \sum_{m \in \mathcal{M}} \exp\left\{R^\alpha\left(g^\Gamma{}_{\#}\mathbb{P}_m^T, g^\Gamma{}_{\#}\mathbb{P}_m^S\right)\right\}^{\frac{\alpha-1}{\alpha}} \left[\mathcal{L}\left(f_m, \mathbb{D}_m^S\right) + L\Delta p_m\right]^{\frac{\alpha-1}{\alpha}}.$$

$\square$

Theorem 6. *(Theorem 3 in the main paper) Let X is a random variable of source sample (i.e., drawn from $\mathbb{P}_\pi^S$) and Y is a random variable of ground-truth labels. Denote $N = \sum_{m' \in \mathcal{M}} \mathbb{P}_\pi^S(A_{m'})$, we then have*

$$\mathbb{I}\left(\Gamma\left(g\left(X\right)\right) \odot g\left(X\right), Y\right) \geq -\sum_{m \in \mathcal{M}} \frac{\mathbb{P}_\pi^S(A_m)}{N} \mathcal{L}\left(f_m, \mathbb{D}_m^S\right) + const, \quad (15)$$

where the loss $\mathcal{L}\left(f_m, \mathbb{D}_m^S\right)$ is defined based on the cross-entropy loss and $\mathbb{I}$ denotes the mutual information.

Proof. Denote $T = \Gamma\left(g\left(X\right)\right) \odot g\left(X\right)$, we have

$$\mathbb{I}(T,Y) = \int p(t,y) \log \frac{p(t,y)}{p(t)p(y)} dtdy$$

$$= \int p(t,y) \log \frac{p(y \mid t)}{p(y)} dtdy$$

$$= \int p(t,y) \log p(y \mid t) dtdy + \mathbb{H}(Y)$$

$$= \int p(t,y) \log h(y \mid t) \frac{p(y \mid t)}{h(y \mid t)} dtdy + \mathbb{H}(Y)$$

$$= \int p(t,y) \log h(t \mid y) dtdy + D_{KL}\left(p(y \mid t) \| h(y \mid t)\right) + \mathbb{H}(Y)$$

$$\geq \int p(t,y) \log h(t \mid y) dtdy + \text{const},$$

where $\mathbb{H}$ specifies the entropy, D_{KL} is Kullback-Leibler (KL) divergence, $h(y \mid t) = h(t,y) = h\left(\Gamma\left(g\left(x\right)\right) \odot g\left(x\right), y\right)$ for any $h: \mathcal{Z} \to \mathcal{Y}_\Delta$, and $h(t,y)$ returns the y-th element of $h(t)$.

We further derive

$$\int p(t,y) \log h(t \mid y)\, dt dy = \sum_{i=1}^{C} \mathbb{E}_{p(t)} \left[p(y=i \mid t) \log h(t \mid y=i) \right]$$

$$\overset{(1)}{=} \sum_{i=1}^{C} \mathbb{E}_{p_\pi^S(x)} \left[p(y=i \mid \Gamma(g(x)) \odot g(x)) \log h(\Gamma(g(x)) \odot g(x), i) \right]$$

$$= \sum_{i=1}^{C} \mathbb{E}_{\mathbb{P}_\pi^S} \left[p(y=i \mid \Gamma(g(x)) \odot g(x)) \log h(\Gamma(g(x)) \odot g(x), i) \right].$$

Note that we have $\overset{(1)}{=}$ because $\Gamma(g(x)) \odot g(x)$ pushes forward $X \sim p_\pi^S(x)$ to $T \sim p(t)$. Moreover, according to our definitions: $\mathbb{P}_\pi^S = \sum_{m \in \mathcal{M}} \frac{\mathbb{P}_\pi^S(A_m)}{N} \mathbb{P}_m^S$, we hence obtain

$$\int p(t,y) \log h(t \mid y)\, dt dy = \sum_{m \in \mathcal{M}} \frac{\mathbb{P}_\pi^S(A_m)}{N} \sum_{i=1}^{C} \mathbb{E}_{\mathbb{P}_m^S} \left[p(y=i \mid m \odot g(x)) \log h(m \odot g(x)), i \right]$$

$$= - \sum_{m \in \mathcal{M}} \frac{\mathbb{P}_\pi^S(A_m)}{N} \sum_{i=1}^{C} \mathbb{E}_{\mathbb{P}_m^S} \left[-p_m^S(y=i \mid x) \log f_m(x,i) \right]$$

$$= - \sum_{m \in \mathcal{M}} \frac{\mathbb{P}_\pi^S(A_m)}{N} \mathcal{L}\left(f_m, \mathbb{D}_m^S \right).$$

$\square$

B EXPERIMENTAL SETTINGS

B.1 DATASET DETAILS

To evaluate the effectiveness of the proposed method, we utilize three datasets: PACS Li et al. (2017), VLCS Torralba & Efros (2011), and Office-Home Venkateswara et al. (2017), which are the common DG benchmarks with multi-source domains.

- **PACS** Li et al. (2017): 9991 images of seven classes in total, over four domains:Art_painting (A), Cartoon (C), Sketches (S), and Photo (P).
- **VLCS** Torralba & Efros (2011): five classes over four domains with a total of 10729 samples. The domains are defined by four image origins, i.e., images were taken from the PASCAL VOC 2007 (V), LabelMe (L), Caltech (C) and Sun (S) datasets.
- **Office-Home** Venkateswara et al. (2017): 65 categories of 15500 daily objects from 4 domains: Art, Clipart, Product (vendor website with white-background) and Real-World (real-object collected from regular cameras).

B.2 BASELINES

We compare with the following recent domain generalization baselines (with reproducible public codes):

- **ERM** Vapnik (1999):minimizes the sum of errors across domains and examples. For our experiments, we employ the implementation from Gulrajani & Lopez-Paz (2021), a strong baseline that can achieve competitive accuracies on DG benchmarks.
- **MLDG** Li et al. (2018a): Learning to generalize: Meta-learning for domain generalization.
- **MetaReg** Balaji et al. (2018): Metareg: Towards domain generalization using meta-regularization.
- **MASF** Dou et al. (2019): Domain generalization via model-agnostic learning of semantic features.

- **JiGen** Carlucci et al. (2019): Domain Generalization by Solving Jigsaw Puzzles.
- **DMG** Chattopadhyay et al. (2020): Learning to balance specificity and invariance for in and out of domain generalization.
- **L2A-OT** Zhou et al. (2020a): Learning to Generate Novel Domains for Domain Generalization.
- **RSC** Huang et al. (2020): Self-challenging improves cross-domain generalization.

B.3 IMPLEMENTATION DETAILS

We detail our algorithm's implementation *sub-space Indicator* Γ: given latent vector $z = g(x) \in \mathbb{R}^{D \times D'}$ (i.e. $z = [z_1, .., z_D] | z_d \in \mathbb{R}^{D'}$), we model $\Gamma(.)$ as a composition of independent indicator on each attribute: $\Gamma(\cdot) = \{\Gamma_d(\cdot)\}_{d=1...D}$ where each Γ_d is neural network. In current work, we model Γ_d as a Full-Connected (FC) layer $[D' \times 1]$ prior to a sigmoid function σ and Γ_d takes z_d as input. (Code for experiments is available in Supplementary Material.)

The following are adapted versions on backbones, in which the last FC layer is used as the classification network. The summary of the additional parameter is presented in Table.6.

AlexNet: For AlexNet backbone, the extracted feature dimensions are $z \in \mathbb{R}^{4096}$. In current implementation, we partition z into 256 features $z_d \in \mathbb{R}^{16}$ as input for Γ_d.

ResNet18 & ResNet50: For ResNet18 & ResNet50 backbones, instead of partitioning the feature tensor, we utilize direcly feature tensor before avepooling layer. In particular, the extracted feature are $z \in \mathbb{R}^{512 \times 7 \times 7}$ for ResNet18 and $z \in \mathbb{R}^{2048 \times 7 \times 7}$ for ResNet50. We use $z_d \in \mathbb{R}^{7 \times 7 = 49}$ as input for Γ_d.

Table 6: Additional parameters summary

Backbones	Partitions	Original	Additional
AlexNet	256	61M	4352 (0.007%)
ResNet18	512	11M	25600 (0.230%)
ResNet50	2048	23M	0.1M (0.440%)

Table 7: Hyperparameters search space.

Dataset	Backbone	$\mathrm{lr}_{h,g}$	lr_Γ
VLCS	AlexNet	$1.0e^{-3}$	$1.0e^{-2}$
Office-Home	ResNet18	$6.5e^{-4}$	1.0
	ResNet50	$6.5e^{-4}$	1.0
PACS	AlexNet	$1.0e^{-3}$	$1.0e^{-2}$
	ResNet18	$1.0e^{-2}$	1.0
	ResNet50	$1.0e^{-2}$	1.0

Optimization: We adopt the SDG optimizer for training with: the model learning-rate ($\mathrm{lr}_{h,g}$) and *sub-space indicator* Γ learning-rate (lr_Γ) for different bacbones and datasets presented in Table 7, mini-batch size of 64 for 100 epochs. The learning rate ($\mathrm{lr}_{h,g}$ and lr_Γ) decayed by 0.1 after every 80% epochs. The values of hyper-parameters $\mathrm{lr}_{h,g}$, lr_Γ and τ are chosen based on the performance on source validation set. Additionally, in order to the *sub-space indicator* Γ quickly adapt to features induced by h, g, lr_Γ is set much larger than $\mathrm{lr}_{h,g}$.

The number of sampling times in Eq. 8 is also a hyper-parameter in our LASSO. When trying with several possible values of this hyper-parameter, we observed that (i) when increasing the number of sampling times, the performance slightly improves but the training time more significantly increases, and (ii) when setting this hyper-parameter to 1, the performance consistently is satisfactory for all experimental datasets. Therefore, in all experiments, we choose to sample once per mini-batch for

computation efficiency. Additionally, at inference time, we use $\tau = 0.6$ for ResNet18&ResNet18 and $\tau = 0.5$ for AlexNet on all datasets.

Data augmentation: We follow the image augmentation protocol introduced in (Gulrajani & Lopez-Paz, 2021) which is increasingly standard in state-of-the-art DG work: crops of random size and aspect ratio, resizing to 224×224 pixels, random horizontal flips, random color jitter, grayscaling the image with 10% probability, and normalization using the ImageNet channel statistics.

Finally, we use system of GPU NVIDIA Tesla V100 with dual CPUs Intel Xeon E5-2698 v4 to conduct our experiments.