On the convergence of policy gradient methods to Nash equilibria in general stochastic games

Abstract

Multi-agent learning in stochastic N-player games is a notoriously difficult problem because, in addition to their changing strategic decisions, the players of the game must also contend with the fact that the game itself evolves over time, possibly in a very complicated manner. Because of this, the equilibrium convergence properties of popular learning algorithms – like policy gradient and its variants – are poorly understood, except in specific classes of games (such as potential or two-player, zero-sum games). In view of all this, we examine the long-run behavior of policy gradient methods with respect to Nash equilibrium policies that are second-order stationary (SOS) in a sense similar to the type of KKT sufficiency conditions used in optimization. Our analysis shows that SOS policies are locally attracting with high probability, and we show that policy gradient trajectories with gradient estimates provided by the REINFORCE algorithm achieve an $\mathcal{O}(1/\sqrt{n})$ convergence rate to such equilibria if the method's step-size is chosen appropriately. On the other hand, when the equilibrium in question is *deterministic*, we show that this rate can be improved dramatically and, in fact, policy gradient methods converge within a *finite* number of iterations in that case.

1 Introduction

Ever since they were introduced by Shapley [46] in the 1950's, stochastic games have comprised one of the staples of non-cooperative game theory, with a range of pioneering applications to multi-agent reinforcement learning [8, 24, 61], unmanned vehicles [11, 32, 43, 45, 58], general game-playing [6, 7, 35, 48, 54], etc. Informally, a stochastic game evolves in discrete time as follows: at each point in time, the players are at a given state which determines the rules of the game for that stage; the actions of the players in this state determine not only their instantaneous payoffs (as defined by the stage game), but also the transition probabilities towards the next state of the process. In this way, each player has to balance two distinct – and often competing – objectives: optimizing the payoffs of *today* versus picking a possibly suboptimal action which could yield significant benefits *tomorrow* (i.e., by influencing the transitions of the process towards a more favorable state for the player).

At the same time, all other players in the game are involved in a similar dilemma, making the decision problem for each player a very complicated affair. In particular, in addition to their changing strategic decisions, the players of the game must also contend with the fact that the game itself evolves over time. Because of this, even the existence of a Nash equilibrium policy – viz. a stationary Markovian policy that is stable to unilateral deviations [19] – is far more difficult to prove compared to standard, stateless normal form games; for a comprehensive survey, see [39, 49, 63] and references therein.

The question we seek to address in this paper is whether an ensemble of boundedly rational players can reach an equilibrium policy in a stochastic game. Specifically, if players do not have sufficient information – or the computational resources required – to solve a Bellman equation in very high

37 dimensions [51, 55], it is not at all clear if they would somehow end up playing a Nash policy in the
38 long run. After all, the complexity of most games increases exponentially with the number of players,
39 so the identification of a game's equilibria quickly becomes prohibitively difficult [16, 25, 33].

40 **Our contributions in the context of related work.** This issue has sparked a vigorous literature with
41 important implications for the series of applications mentioned above [3, 50, 60]. On the downside,
42 these efforts also have to grapple with a series of strong lower bounds for computing weaker solution
43 concepts like coarse correlated equilibria in turn-based stochastic games [15, 25]. On that account, a
44 recent line of work has instead focused on understanding specific sub-classes of stochastic games, like
45 *min-max* [12, 14, 44, 56] and common interest *potential* games [17, 29, 64], or computing relaxed
46 solution concepts where either the stationarity or the Markov property has been dropped [15].

47 Our paper focuses on episodic playing in random stopping games – in lieu of ergodic stochastic games
48 with an infinite horizon [31, 46] – and considers the general class of policy gradient methods, first
49 introduced by [26, 27, 52, 57] and subsequently popularized in single-agent reinforcement learning
50 by [2, 10, 23, 59]. Concretely, this means that the sequence of play evolves episode-by-episode:
51 within each episode, the players commit a policy and play the game, and from one episode to the
52 next, they use an iterative gradient step to update their policy.

53 Our main contributions in this general context may then be summarized as follows:

54 1. We introduce a flexible algorithmic template for the analysis of policy gradient methods which
55 accounts for different information and update frameworks – from perfect policy gradients to
56 value-based estimates obtained per episode, e.g., via the REINFORCE algorithm [4, 52, 57].

57 2. Within this framework, we show that Nash policies that satisfy a certain strategic stability
58 condition are locally attracting with arbitrarily high probability. Moreover, to estimate the
59 method's rate of convergence, we focus on Nash policies that satisfy a second-order sufficiency
60 condition similar to the type of KKT conditions used in optimization, and we show that such
61 policies enjoy an $\mathcal{O}(1/\sqrt{n})$ convergence rate in terms of squared distance.

62 3. Finally, we also consider the method's convergence to *deterministic* Nash policies and we show
63 that, generically, the above rate can be improved dramatically. By a simple tweak to the method's
64 projection step, we are able to show that the induced sequence of play converges to equilibrium
65 in a *finite* number of iterations, despite all the noise and uncertainty in the process.

66 It is worth mentioning that our results focus squarely on the convergence of the actual, inter-episode
67 trajectory of play – as opposed to "best-iterate" or ergodic convergence results. In addition, obtaining
68 guarantees using stochastic estimators (cf. REINFORCE) greatly alleviate the burden of exact gradient
69 computations that are otherwise beyond reach in low-compute / low-memory practical environments.
70 This aspect of our results is especially relevant for multi-agent reinforcement learning scenarios where
71 agents learn "on the fly", and is a property with important ramifications for many of the practical
72 applications of stochastic games.

2 Preliminaries

74 **2.1. Game formulation.** Throughout this work we consider N-player generic stochastic games,
75 where players repeatedly select actions in a shared Markov decision process (MDP) with the goal of
76 maximizing their individual value functions. Formally, we study the tabular version with random
77 stopping of general stochastic games, which is specified by a tuple $\mathcal{G} = (\mathcal{S}, \mathcal{N}, \{\mathcal{A}_i, R_i\}_{i \in \mathcal{N}}, P, \zeta, \rho)$
78 with the following primitives:

79 • A finite set of *agents* $i \in \mathcal{N} = \{1, 2, \ldots, N\}$ and a finite set of *states* $\mathcal{S} = \{1, \ldots, S\}$.
80 • For each $i \in \mathcal{N}$, a finite space of *actions* (or *pure strategies*) $\mathcal{A}_i$ indexed by $\alpha_i = 1, \ldots, A_i = |\mathcal{A}_i|$.
81 We will write $\mathcal{A} = \prod_{i \in \mathcal{N}} \mathcal{A}_i$ and $\mathcal{A}_{-i} = \prod_{j \neq i} \mathcal{A}_j$ for the action space of all agents and that of all
82 agents other than i respectively. In a similar vein, we will also write $\alpha = (\alpha_i, \alpha_{-i})$ when we want
83 to highlight the action α_i of player i against the action profile α_{-i} of i's opponents.

- For each $i \in \mathcal{N}$, we will write $R_i \colon \mathcal{S} \times \mathcal{A} \to [-1, 1]$ for the *reward function* of agent $i \in \mathcal{N}$, i.e., $R_i(s, \alpha_i, \alpha_{-i})$ will denote the value of the reward of agent i when the game is at state $s \in \mathcal{S}$, the focal agent $i \in \mathcal{N}$ plays $\alpha_i \in \mathcal{A}_i$, and all other agents take actions $\alpha_{-i} \in \mathcal{A}_{-i}$.

- The game transits from one state to another according to a Markov transition process, so that $P(s' \mid s, \alpha)$ denotes the probability of transitioning from s to s' when $\alpha \in \mathcal{A}$ is the action profile chosen by the agents.

- Given an action profile α at state s, the process terminates with probability $\zeta_{s,a} > 0$, i.e., $\zeta_{s,a} = 1 - \sum_{s' \in \mathcal{S}} P(s' \mid s, \alpha)$; for convenience, we will write $\zeta := \min_{s,a}\{\zeta_{s,a}\}$.

- $\rho \in \Delta(\mathcal{S})$ is the distribution for the initial state of the game.

Episodic Setting. We consider an episodic setting, where in each episode a realization of the game is completed. At every time step $t \geq 0$ of each episode, all agents observe the common state $s_t \in \mathcal{S}$, select actions α_t and receive rewards $\{R_i(s_t, \alpha_t)\}_{i \in \mathcal{N}}$. Then, with probability ζ_{s_t, α_t} the game terminates, and with probability $1 - \zeta_{s_t, \alpha_t}$, it moves to the state s_{t+1}, which is drawn according to $P(\cdot \mid s_t, \alpha_t)$. Denoting the realized reward of player i at time t as $r_{i,t} := R_i(s_t, \alpha_t)$, we will write $\tau = (s_t, \alpha_t, r_t)_{t \leq T(\tau)}$ to denote the trajectory of the episode, where $r_t := (r_{i,t})_{i \in \mathcal{N}}$, and $T(\tau)$ the time the episode terminates.

Policies and value functions. We consider *stationary Markovian* policies, i.e., policies that do not depend on the time-step and the history, given the current state of the game. More specifically, for each agent $i \in \mathcal{N}$, a *policy* $\pi_i \colon \mathcal{S} \to \Delta(\mathcal{A}_i)$ specifies a probability distribution over the actions of agent i in state $s \in \mathcal{S}$, i.e., $\alpha_i \sim \pi_i(\cdot \mid s)$ denotes the (random) action drawn by agent i at state $s \in \mathcal{S}$ according to π_i, viewed here as an element of $\Pi_i := \Delta(\mathcal{A}_i)^{\mathcal{S}}$. In addition, we will also write $\pi = (\pi_i)_{i \in \mathcal{N}} \in \Pi := \prod_i \Pi_i$ and $\pi_{-i} = (\pi_j)_{j \neq i} \in \Pi_{-i} := \prod_{j \neq i} \Pi_j$ for the policy profile of all agents and all agents other than i, respectively.

The expected reward of agent $i \in \mathcal{N}$ if agents follow policy π, starting from initial state $s \in \mathcal{S}$, defines the *value function* of agent i, denoted as $V_{i,s}(\pi)$, and is equal to

$$V_{i,s}(\pi) := \mathbb{E}_{\tau \sim \mathrm{MDP}}\left[\sum_{t=0}^{T(\tau)} R_i(s_t, a_t) \Big| s_0 = s\right] \tag{1}$$

where $\tau \sim \mathrm{MDP}$ denotes the randomness induced by the policy profile π, and the state-transition probabilities of the MDP. Overloading the notation, we set $V_{i,\rho}(\pi) := \mathbb{E}_{s \sim \rho}[V_{i,s}(\pi)]$. Although value functions are, in general, non-convex, they share similar smoothness properties with the payoff functions of normal form games, namely bounded and Lipschitz gradients. For precise statements, we defer to the paper's supplement.

Visitation distribution and the mismatch coefficient. For a policy profile $\pi \in \Pi$ and an arbitrary initial state distribution $s_0 \sim \rho$, we define the discounted state visitation measure/distribution as

$$\tilde{d}_\rho^\pi(s) = \mathbb{E}_{\tau \sim \mathrm{MDP}}\left[\sum_{t=0}^{T(\tau)} \mathbb{1}\{s_t = s\} \Big| s_0 \sim \rho\right], \quad d_\rho^\pi(s) := \tilde{d}_\rho^\pi(s)/Z_\rho^\pi$$

In the appendix, we prove formally that the above definition is well-posed for the random stopping episodic framework described above, i.e., $\tilde{d}_\rho^\pi(s) < \infty$, so $Z_\rho^\pi := \mathbb{E}_{s \sim \mathrm{Unif}(\mathcal{S})}[\tilde{d}_\rho^\pi(s)]$ is well-defined. In our proofs, we will leverage a standard property of visitation distributions, namely the equivalence of the expected value of state-action function and the expected cumulative value over a random trajectory. More precisely, we have:

Lemma 1 (Conversion Lemma). *For an arbitrary state-action function $f \colon \mathcal{S} \times \mathcal{A} \to \mathbb{R}$, a policy profile π and an initial state distribution $s_0 \sim \rho$, we have*

$$\mathbb{E}_{\tau \sim \mathrm{MDP}}\left[\sum_{t=0}^{T(\tau)} f(\alpha_t, s_t)\right] = Z_\rho^\pi \, \mathbb{E}_{s \sim d_\rho^\pi} \mathbb{E}_{\alpha \sim \pi(\cdot \mid s)}[f(\alpha, s)] \tag{2}$$

Finally, to quantify the difficulty of hard-to-reach states via a policy gradient method, we will follow the standard approach of [13, 18, 36, 37, 64] and use an appropriately-defined distribution "mismatch coefficient", generalizing the single-agent counterpart of Agarwal et al. [1]. More precisely, for a stochastic game $\mathcal{G}$, we define the *minimax mismatch coefficient* as $\mathcal{C}_{\mathcal{G}} := \max_{\pi, \pi' \in \Pi}\{\|d_\rho^\pi/d_\rho^{\pi'}\|_\infty\}$. Similar to prior work in this direction [1, 5, 14], we will assume $\mathcal{C}_{\mathcal{G}}$ is finite, which, equivalently, means that $d_\rho^\pi(s) > 0$ for any policy π and state s.

2.2. Solution Concepts. The most widely used solution concept in game theory is that of a Nash equilibrium i.e., a strategy profile $\pi^* \in \Pi$ that discourages unilateral deviations. However, in stochastic games, the definition of a Nash policy is much more involved because of the existence of multiple states and steps, cf. [19, 47, 49, 53]. Formally, we have the following definition:

Definition 1 (Nash Policy). A policy $\pi^* = (\pi_i^*)_{i \in \mathcal{N}} \in \Pi$ is said to be a *Nash policy* for a given distribution of initial states $\rho \in \Delta(\mathcal{S})$ if, for every player $i \in \mathcal{N}$, we have

$$V_{i,\rho}(\pi_i^*; \pi_{-i}^*) \geq V_{i,\rho}(\pi_i; \pi_{-i}^*) \qquad \forall i \in \mathcal{N}, \forall \pi_i \in \Delta(\mathcal{A}_i)^{\mathcal{S}} \tag{NE}$$

In contrast to general non-convex continuous games, stochastic games satsify a version of the well-known Polyak-Łojasiewicz condition [42] but with linear gradient growth, also known as a *gradient dominance property* (GDP) [1, 5]. For the multi-agent case, [14, 64] showed that a similar property holds even in an episodic setting:

Lemma 2 (Gradient dominance property). *For any policy profile $\pi = (\pi_i)_{i \in \mathcal{N}} \in \Pi$, we have that*

$$V_{i,\rho}(\pi_i'; \pi_{-i}) - V_{i,\rho}(\pi_i; \pi_{-i}) \leq \mathcal{C}_{\mathcal{G}} \max_{\bar{\pi}_i \in \Pi_i} \langle \nabla_i V_{i,\rho}(\pi), \bar{\pi}_i - \pi_i \rangle \tag{GDP}$$

for any unilateral deviation $\pi_i' \in \Pi_i$ of each player $i \in \mathcal{N}$.

Remark. In the above and throughout our paper, we will write ∇_i to denote the gradient of the quantity in question with respect to π_i, i.e., when π_{-i} is kept fixed and only π_i is varied. For concision, we will write $v_i(\pi) = \nabla_i V_{i,\rho}(\pi)$ for the individual gradient of player i's value function, and $v(\pi) = (v_i(\pi))_{i \in \mathcal{N}}$ for the ensemble thereof. ¶

Thanks to (GDP), it is straightforward to check that first-order stationary (FOS) points of V are Nash policies. Formally, as in [14, 29, 64], we have the following characterization:

Lemma 3 (First-order stationary policies are Nash). *A profile $\pi^* = (\pi_i^*)_{i \in \mathcal{N}} \in \Pi$ is a Nash policy profile if and only if it satisfies the first-order stationary condition*

$$\langle v(\pi^*), \pi - \pi^* \rangle \leq 0 \quad \text{for all } \pi \in \Pi. \tag{FOS}$$

Leonardos et al. [29] and Zhang et al. [64] proved a relaxation of the above lemma to the effect that policies that satisfy (FOS) up to ε (i.e., in lieu of 0 in the RHS) are $\mathcal{O}(\varepsilon)$-Nash. Going in the other direction, we will consider the following series of refinements of Nash policies which are particularly important from a learning standpoint [28, 34, 49]:

Definition 2. Let $\pi^* = (\pi_i^*)_{i \in \mathcal{N}} \in \Pi$ be a Nash policy. Then:

- π^* is *stable* if $\langle v(\pi), \pi - \pi^* \rangle < 0$ for all $\pi \neq \pi^*$ close to π^*.

- π^* is *second-order stationary* if it satisfies the sufficiency condition

$$(\pi - \pi^*)^\top \text{Jac}_v(\pi^*)(\pi - \pi^*) < 0 \quad \text{for al } \pi \in \Pi \setminus \{\pi^*\}, \tag{SOS}$$

  where $\text{Jac}_v(\pi^*) = (\nabla_j v_i(\pi^*))_{i,j \in \mathcal{N}} = (\nabla_j \nabla_i V_i(\pi^*))_{i,j \in \mathcal{N}}$ denotes the Jacobian of v at π^*.

- π^* is *deterministic* if it induces a deterministic selection rule $\pi_i^* \colon \mathcal{S} \to \mathcal{A}_i$ for all $i \in \mathcal{N}$.

- π^* is *strict* if it is deterministic and (NE) holds as a strict inequality whenever $\pi \neq \pi^*$.

Intuitively, the condition for equilibrium stability is the game-theoretic analogue of a first-order KKT sufficiency condition, while the condition for second-order stationarity is the second-order version thereof. In this regard, the distinction between first-order stationary, stable and second-order stationary points is formally analogous to the distinction between critical points, minimizer, and second-order minimum points in optimization. As for deterministic policies, we should mention that, generically – i.e., except on a set which is meager in the sense of Baire [20, 28] – deterministic policies are also strict, so we will use the two terms interchangeably.

Importantly, as we show in the appendix, these refinements admit the following characterizations:

Proposition 1. *Let $\pi^* = (\pi_i^*)_{i \in \mathcal{N}} \in \Pi$ be a Nash policy. Then:*

a) π^* is second-order stationary if and only if there exists some $\mu > 0$ such that

$$\langle v(\pi), \pi - \pi^* \rangle \leq -\mu \|\pi - \pi^*\|^2 \qquad \text{for all } \pi \text{ sufficiently close to } \pi^*. \tag{3a}$$

b) π^* is strict if and only if there exists some $\mu > 0$ such that

$$\langle v(\pi), \pi - \pi^* \rangle \leq -\mu \|\pi - \pi^*\| \qquad \text{for all } \pi \text{ sufficiently close to } \pi^*. \tag{3b}$$

In view of all the above, we get the following string of implications for equilibria in generic games:

$$\text{strict/deterministic} \implies \text{SOS} \implies \text{stable} \implies \text{FOS} = \text{Nash} \tag{4}$$

For posterity, we only note here that it is plausible to except that more refined solution concepts should enjoy stronger convergence properties; we will confirm this intuition in the sequel.

3 Policy gradient methods

We now proceed to describe our general model for learning in stochastic games. In tune with the episodic framework described in the previous section, we will likewise consider a learning framework where agents follow a specific policy profile π_n within each episode, and update it from one episode to the next with the objective of increasing their individual rewards.

Formally, our approach will adhere to the following inter-episode sequence of events:

1. At the beginning of each episode $n = 1, 2, \ldots$, every agent $i \in \mathcal{N}$ chooses a policy $\pi_{i,n} \in \Pi_i$.

2. Within the n-th episode, each player executes their chosen policy $\pi_{i,n}$, inducing in this way an intra-episode trajectory of play $\tau_n = (s_t^{(n)}, \alpha_t^{(n)}, r_t^{(n)})_{t \leq T(\tau_n)}$.

3. Once the episode terminates, agents update their policies, and the process repeats.

In terms of feedback, we will treat several models, depending on what type of information is available to the agents during play. To that end, we will focus on the generic policy gradient (PG) template

$$\pi_{n+1} = \text{proj}_\Pi(\pi_n + \gamma_n \hat{v}_n) \tag{PG}$$

where:

1. $\pi_n = (\pi_{i,n})_{i \in \mathcal{N}} \in \Pi$ denotes the player's policy profile at each episode $n = 1, 2, \ldots$

2. $\hat{v}_n = (\hat{v}_{i,n})_{i \in \mathcal{N}} \in \prod_i \mathbb{R}^{\mathcal{A}_i \times \mathcal{S}}$ is an estimate for the agents' inidividual policy gradients.

3. $\gamma_n > 0$ is the method's step-size, for which we will assume throughout that $\sum_n \gamma_n = \infty$ (typically the method is run with a step-size of the form $\gamma_n \propto 1/n^p$ for some $p \geq 0$).

4. $\text{proj}_\Pi \colon \prod_i \mathbb{R}^{\mathcal{A}_i \times \mathcal{S}} \to \Pi$ denotes the Euclidean projection to the agents' policy space Π.

Regarding the gradient signal $\hat{v}_n$, we will decompose it as

$$\hat{v}_n = v(\pi_n) + U_n + b_n \tag{5}$$

where

$$U_n = \hat{v}_n - \mathbb{E}[\hat{v}_n \mid \mathcal{F}_n] \quad \text{and} \quad b_n = \mathbb{E}[\hat{v}_n \mid \mathcal{F}_n] - v(\pi_n). \tag{6}$$

In the above, we treat π_n as a stochastic process on some complete probability space $(\Omega, \mathcal{F}, \mathbb{P})$, and we write $\mathcal{F}_n := \mathcal{F}(\pi_1, \ldots, \pi_n) \subseteq \mathcal{F}$ for the history (adapted filtration) of π_n up to – and including – stage n.

By definition, $\mathbb{E}[U_n \mid \mathcal{F}_n] = 0$ and b_n is $\mathcal{F}_n$-measurable, so U_n can be intepreted as a random, zero-mean error relative to $v(\pi_n)$, whereas b_n captures all systematic (non-zero-mean) errors. To make this precise, we will further assume that b_n and U_n are bounded as

$$\mathbb{E}[\|b_n\| \mid \mathcal{F}_n] \leq B_n \qquad \text{and} \qquad \mathbb{E}[\|U_n\|^2 \mid \mathcal{F}_n] \leq \sigma_n^2 \tag{7}$$

Algorithm 1: REINFORCE	**Algorithm 2:** ε-GREEDY POLICY GRADIENT
1: **Input:** $\hat{\pi} \in \Pi, \tau = (s_t, \alpha_t, r_t)_{t \leq T(\tau)} \in \mathcal{T}$	1: **Input:** $\pi_1, \{\gamma_n\}_{n \in \mathbb{N}}, \{\varepsilon_n\}_{n \in \mathbb{N}}$
2: **for** $i = 1, \ldots, N$ **do**	2: **for** $n = 1, 2, \ldots$ **do**
3: $\quad R_i(\tau) \leftarrow \sum_{t=0}^{T(\tau)} r_{i,t}$	3: $\quad \hat{\pi}_n \leftarrow (1 - \varepsilon_n)\pi_n + \frac{\varepsilon_n}{|\mathcal{A}|}$
4: $\quad \Lambda_i(\tau) \leftarrow \sum_{t=0}^{T(\tau)} \nabla_i(\log \hat{\pi}_i(a_{i,t}|s_t))$	4: $\quad$ Sample $\tau_n \sim \text{MDP}(\hat{\pi}_n|s_0)$
5: $\quad \hat{v}_i \leftarrow R_i(\tau) \cdot \Lambda_i(\tau)$	5: $\quad \hat{v}_n \leftarrow \text{REINFORCE}(\hat{\pi}_n, \tau_n)$
6: **end for**	6: $\quad \pi_{n+1} \leftarrow \text{proj}_\Pi(\pi_n + \gamma_n \hat{v}_n)$
7: **return** $\{\hat{v}_i\}_{i \in \mathcal{N}}$	7: **end for**

where the sequences B_n and σ_n, $n = 1, 2, \ldots$, are to be construed as deterministic upper bounds on the bias, fluctuations, and magnitude of the gradient signal $\hat{v}_n$. Depending on these bounds, a gradient signal with $B_n = 0$ will be called *unbiased*, and an unbiased signal with $\sigma_n = 0$ will be called *perfect*. More generally, we will assume that the above statistics are bounded as

$$B_n = \mathcal{O}(1/n^{\ell_b}) \qquad \text{and} \qquad \sigma_n = \mathcal{O}(n^{\ell_\sigma}) \tag{8}$$

for some $\ell_b, \ell_\sigma > 0$ which depend on the specific model under consideration. For concreteness, we describe below three basic models that adhere to the above template for $\hat{v}_n$ in order of decreasing information requirements:

Model 1 (Full gradient information). The first model we will consider assumes that agents observe their *full policy gradients*, i.e.,

$$\hat{v}_n = v(\pi_n) \tag{9}$$

implying in particular that $U_n = b_n = 0$. This model is fully deterministic across episodes (though intra-episode play remains stochastic). In particular, it tacitly assumes that agents know the game (and can observe their opponents' policies) sufficiently well so as to calculate the full gradients of their individual value functions $V_{i,\rho}$, cf. [2, 29, 64] and references therein. ¶

Model 2 (Learning with stochastic gradients). A relaxation of the above model which is particularly relevant when the game involves training over datasets concerns the case where the player have access to stochastic policy gradients, i.e., unbiased gradient estimates of the form

$$\hat{v}_n = v(\pi_n) + U_n \tag{10}$$

with $\mathbb{E}[U_n | \mathcal{F}_n] = 0$ (so we can formally take $\ell_b = \infty$ and $\ell_\sigma = 0$ in Eq. (8) above). This case is considered in [62] and [40]. ¶

Model 3 (Value-based learning). The last model we will consider concerns the case where agents only have access to their realized values and need to reconstruct their individual gradients based on this information. A widely used method to achieve this is via the REINFORCE subroutine, which we describe in pseudocode form in Algorithm 1. In words, when employing REINFORCE, each agent $i \in i$ commits to a sampling policy $\hat{\pi}_i \in \Pi_i$ and executes it in an episode of the stochastic game in play. Then, at the end of the episode, players gather the total reward $R_i(\tau) \leftarrow \sum_{t=0}^{T(\tau)} r_{i,t}$ associated to the intra-episode trajectory of play τ, and they estimate their policy gradients via the so-called "log-trick" [57] as

$$\hat{v}_i = R_i(\tau) \cdot \sum_{t=0}^{T(\tau)} \nabla_i(\log \hat{\pi}_i(a_{i,t}|s_t)). \tag{11}$$

Lemma 4 below provides the vital statistics of the REINFORCE estimator:

Lemma 4. *Suppose that each agents $i \in \mathcal{N}$ follows a stationary policy $\pi_i \in \Pi_i$. Then, letting $\kappa_i = \min_{s \in \mathcal{S}, \alpha_i \in \mathcal{A}_i} \pi_i(\alpha_i|s)$ for each $i \in \mathcal{N}$, we have*

$$a) \quad \mathbb{E}_{\tau \sim \text{MDP}}[\text{REINFORCE}(\pi)] = v(\pi). \tag{12a}$$

$$b) \quad \mathbb{E}_{\tau \sim \text{MDP}}\left[\|\text{REINFORCE}_i(\pi) - v_i(\pi)\|^2\right] \leq \frac{24|\mathcal{A}_i|}{\kappa_i \zeta^4}. \tag{12b}$$

Thus, if Reinforce is executed at $\hat{\pi} \leftarrow \pi_n$ at each episode $n = 1, 2, \ldots$, we will have

$$\mathbb{E}[\hat{v}_{i,n}] = v_i(\pi_n) \qquad \text{and} \qquad \mathbb{E}[\|U_{i,n}\|^2 \,|\, \mathcal{F}_n] \leq \frac{24|\mathcal{A}_i|}{\zeta^4 \min_{s \in \mathcal{S}, \alpha_i \in \mathcal{A}_i} \pi_{i,n}(\alpha_i|s)}. \tag{13}$$

This means that we will always have $B_n = 0$ for the bias of the estimator, but its variance could be unbounded if π_n gets close to the boundary of Π. For this reason, Reinforce is typically paired with an explicit exploration step that modifies the sampling policy of the n-th episode to

$$\hat{\pi}_{i,n} = (1 - \varepsilon_n)\pi_{i,n} + \varepsilon_n \, \text{Unif}_{\mathcal{A}_i}. \tag{14}$$

i.e., $\hat{\pi}_{i,n}$ is the mixture between $\pi_{i,n}$ and the uniform distribution $\text{Unif}_{\mathcal{A}_i}$ over $\mathcal{A}_i$. The resulting algorithm is known as ε-Greedy Policy Gradient; for a pseudocode, see Algorithm 2.

Importantly, by calling Reinforce at $\hat{\pi}_n$, $\hat{v}_n$ becomes biased (because of the difference between $\hat{\pi}_n$ and π_n), but its variance is bounded; in particular, by invoking Lemma 4, we have

$$\mathbb{E}[\|b_{i,n}\| \,|\, \mathcal{F}_n] \leq G\varepsilon_n \qquad \text{and} \qquad \mathbb{E}[\|U_{i,n}\|^2 \,|\, \mathcal{F}_n] \leq \frac{24|\mathcal{A}_i|^2}{\varepsilon_n \zeta^4} \tag{15}$$

where G is a constant that depends on the smoothness of V and the cardinalities of $\mathcal{A}$ and $\mathcal{S}$. In this way, ε-Greedy Policy Gradient can be seen as a special case of the generic policy gradient template (PG) with $B_n = \mathcal{O}(\varepsilon_n)$ and $\sigma_n = \mathcal{O}(1/\sqrt{\varepsilon_n})$. ¶

4 Convergence analysis and results

We are now in a position to state and discuss our main results. For convenience, we will present our results in order of increasing structure, starting with stable policies, and then moving on to second-order stationary and deterministic Nash policies. All proofs are deferred to the appendix.

4.1. Asymptotic convergence to stable Nash policies. Our first convergence result concerns Nash policies that satisfy the stability requirement $\langle v(\pi), \pi - \pi^* \rangle < 0$ of Definition 2. In this case, we have the following guarantee:

Theorem 1. *Let π^* be a stable Nash policy, and let π_n be the sequence of play generated by* (PG) *with step-size and policy gradient estimates such that $p + \ell_b > 1$ and $p - \ell_\sigma > 1/2$ as per* (8)*. Then there exists a neighborhood $\mathcal{U}$ of π^* in Π such that, for any given $\delta > 0$, we have*

$$\mathbb{P}(\pi_n \text{ converges to } \pi^* \,|\, \pi_1 \in \mathcal{U}) \geq 1 - \delta \tag{16}$$

provided that $\gamma > 0$ is small enough relative to δ.

Corollary 1. *Suppose that Models 1–3 are run with a step-size of the form $\gamma_n = \gamma/n^p$, $p \in (1/2, 1]$, and if applicable, an exploration parameter $\varepsilon_n = \varepsilon/n^r$ such that $1 - p < r/2 < p - 1/2$. Then the conclusions of Theorem 1 hold.*

We note here that Theorem 1 provides a trajectory convergence guarantee which is otherwise quite difficult to obtain even in structured stochastic games. For example, if we zoom in on the class of stochastic potential (or min-max) games, the existing guarantees in the literature concern the "best iterate" of the algorithm, cf. [30, 64] and references therein. Because of this, said guarantees do not apply to the actual trajectory of play generated by (PG); this makes them less suitable for agent-based learning where the players involved are learning "as they go", as opposed to *simulating* the game in order to approximately compute an equilibrium policy offline.

We should also note that the convergence guarantees of Theorem 1 hold locally with arbitrarily high probability. Without further assumptions, it is not possible to obtain global trajectory convergence guarantees that hold with probability 1, even in the simple case where the game only has a single state – that is, the case of learning in finite normal form games. In this (much simpler) setting, the well-known impossibility result of Hart and Mas-Colell [21, 22] shows that it is not possible to expect convergence to Nash equilibrium in all games – not even locally. In this regard, the local convergence caveat in Theorem 1 cannot be lifted without further structural properties in place – such as the existence of a potential function in the spirit of [30].

4.2. Convergence to second-order stationary policies. Albeit valuable as an asymptotic convergence guarantee, Theorem 1 does not provide an indication of how long it will take players to actually converge to a Nash policy. Of course, in full generality, it is not plausible to expect to be able to derive such a convergence rate because the stability requirement provides no indication on how fast the players' policy gradients stabilize near a solution. This kind of estimate is provided by the second-order sufficient condition (SOS), which allows us to establish sufficient control over the sequence of play as indicated by the following theorem.

Theorem 2. *Let π^* be a Nash policy such that* (SOS) *holds on some neighborhood $\mathcal{U}$ of π^*, and let π_n be the sequence of play generated by* (PG) *with step-size $\gamma_n = \gamma/(n+m)^p$, $p \in (1/2, 1]$, and policy gradient estimates such that $p + \ell_b > 1$ and $p - \ell_\sigma > 1/2$ as per* (8). *Then:*

1. *There exists a neighborhood $\mathcal{U}_1$ of π^* in Π such that, for any confidence level $\delta > 0$, the event*

$$\mathcal{E}_{\mathcal{U}} = \{\pi_n \in \mathcal{U} \text{ for all } n = 1, 2, \dots\} \tag{17}$$

   occurs with probability $\mathbb{P}(\mathcal{E}_{\mathcal{U}} \mid \pi_1 \in \mathcal{U}_1) \geq 1 - \delta$ if m is large enough relative to δ.

2. *Conditioned on $\mathcal{E}_{\mathcal{U}}$, the sequence π_n converges to π^* with probability 1; in particular, we have*

$$\mathbb{P}(\pi_n \text{ converges to } \pi^* \mid \pi_1 \in \mathcal{U}_1) \geq 1 - \delta \tag{18}$$

   if m is large enough relative to δ. Moreover, maintaining the same conditioning, we have

$$\mathbb{E}[\|\pi_n - \pi^*\|^2 \mid \mathcal{E}_{\mathcal{U}}] = \begin{cases} \mathcal{O}(1/n^{2\mu\gamma}) & \text{if } p = 1 \text{ and } 2\mu\gamma < q, \\ \mathcal{O}(1/n^q) & \text{otherwise,} \end{cases} \tag{19}$$

   where $q = \min\{\ell_b, p - 2\ell_\sigma\}$.

Corollary 2. *Suppose that Models 1–3 are run with a step-size of the form $\gamma_n = \gamma/(n+m)^p$, $p > 1/2$, and if applicable, an exploration parameter $\varepsilon_n = \varepsilon/n^{p/2}$. Then:*

- *For Models 1 and 2: the conclusions of Theorem 2 hold with $q = p$; in particular,* (19) *gives an $\mathcal{O}(1/n)$ rate of convergence if $p = 1$ and $2\mu\gamma > q$.*

- *For Model 3: the conclusions of Theorem 2 hold for $p > 2/3$ with $q = p/2$; in particular,* (19) *gives an $\mathcal{O}(1/\sqrt{n})$ rate of convergence if $p = 1$ and $2\mu\gamma > q$.*

Besides providing the conditions that need to be satisfied under (SOS) in the general framework for achieving trajectory convergence, this theorem gives the exact rates of convergence of the sequence of play to the Nash policy in question. In particular, with this result in hand, one can confidently argue about the distance of the iterates of (PG) from equilibrium in a series of different environments. More to the point, this convergence guarantee allows the algorithm designer to adapt the parameters of the learning process according to the complexity and limitations of the environment, a feature which further highlights the significance of this result.

We should also note the delicate interplay between the method's step-size and the achieved convergence rate. In the case of Model 1, Corollary 2 suggests a step-size of the form $\gamma_n = \Theta(1/n)$, leading to a $\mathcal{O}(1/n)$ convergence rate. As we show in the appendix, this rate can be improved: in the deterministic case with perfect gradient information, (PG) with a suitably chosen constant step-size achieves a *geometric* convergence rate, i.e., $\|\pi_n - \pi^*\| = \mathcal{O}(\exp(-\rho n))$ for some $\rho > 0$. By contrast, in the case of Model 2, the $\mathcal{O}(1/n)$ rate we provide cannot be improved, even if the quadratic minorant (3a) that characterizes SOS policies holds *globally* – and this because the learning process is running against standard lower bounds from convex optimization [9, 38].

Perhaps the most significant guarantee from a practical point of view is the $\mathcal{O}(1/\sqrt{n})$ convergence rate attained in Model 3 (cf. Algorithms 1 and 2). This guarantee amounts to a $\mathcal{O}(1/n^{1/4})$ convergence rate in terms of the (non-squared) distance to equilibrium which, mutatis mutandis, represents a notable improvement over the $\mathcal{O}(1/n^{1/6})$ guarantee of Leonardos et al. [30] (expressed in norm values). Of course, the latter guarantee is global – because the focus of [30] is stochastic *potential* games – but it also concerns the "best iterate" of the process (not its "last iterate"), so the two results are not

immediately comparable. However, a useful "best-of-both-worlds" heuristic that can be inferred by the combination of these works is that, given a budget of training episodes, Algorithm 2 can be run with a constant step-size as per [30] for a sufficient fraction of this budget, and then with a $\mathcal{O}(1/n)$ "cooldown" schedule for the rest. In this way, after an aggressive "exploration" phase, the algorithm's $\mathcal{O}(1/n^{1/4})$ rate would kick in and supply faster stabilization to an SOS policy.

4.3. Convergence to deterministic Nash policies. Our last series of results concerns the rate of convergence to deterministic Nash policies in generic stochastic games. As we discussed in Section 2, deterministic Nash policies also satisfy (SOS), so the rate of convergence of (PG) to such policies can be harvested directly from Theorem 2. However, as we show below, a simple projection tweak in (SOS) can improve this rate dramatically.

The tweak in question is inspired by the geometry of Π around a deterministic policy: by definition, such policies are corner points of Π, so any consistent drift towards them will cause π_n to hit the boundary of Π in finite time. Of course, under (PG), the process may rebound from the boundary and return to the interior of Π if the policy gradient estimate is not particularly good at a given iteration of the algorithm. However, if we replace the projection step of (PG) with a "lazy projection" in the spirit of Zinkevich [65], the aggregation of gradient steps will eventually push the process far inside the normal cone of Π at π^*, so rebounds of this type can no longer occur.

Formally, we will consider the following *lazy policy gradient* (LPG) scheme:

$$y_{n+1} = y_n + \gamma_n \hat{v}_n \qquad \pi_{n+1} = \text{proj}_\Pi(y_{n+1}) \qquad \text{(LPG)}$$

where $y_n = (y_{i,n})_{i \in \mathcal{N}} \in \prod_i \mathbb{R}^{\mathcal{A}_i \times \mathcal{S}}$ is an auxiliary variable that maintains an aggregate of gradient steps *before* projecting them back to Π. We then have the following convergence result:

Theorem 3. *Let π_n be the sequence of play under* (LPG) *with step-size and policy gradient estimates such that $p + \ell_b > 1$ and $p - \ell_\sigma > 1/2$ as per* (8). *If π^* is a deterministic Nash policy, there exists an unbounded open set $\mathcal{W} \subseteq \prod_i \mathbb{R}^{\mathcal{A}_i \times \mathcal{S}}$ of initializations such that, for any $\delta > 0$, we have*

$$\mathbb{P}(\pi_n \text{ converges to } \pi^* \mid y_1 \in \mathcal{U}) \geq 1 - \delta, \qquad (20)$$

provided that $\gamma > 0$ is small enough. Moreover, conditioned on this event, π_n converges to π^* at a finite number of iterations, i.e., there exists some n_0 such that $\pi_n = \pi^*$ for all $n \geq n_0$.

Corollary 3. *Suppose that Models 1–3 are run with parameters $\gamma_n = \gamma/n^p$, $p \in (1/2, 1]$, and if applicable, $\varepsilon_n = \varepsilon/n^r$ with $1 - p < r < 2p - 1$. Then the conclusions of Theorem 3 hold.*

Theorem 3 – and, by extension, Corollary 3 – are fairly unique because they provide a guarantee for convergence to an *exact* Nash equilibrium in a *finite* number of iterations. To the best of our knowledge, the only comparable result in the literature is that of [64], where the authors provide a finite-time convergence guarantee to strict equilibria with *perfect* policy gradients (as per Model 1). The result of Zhang et al. [64] echoes the convergence properties of deterministic first-order algorithms around sharp minima of convex functions [41], but the fact that Theorem 3 applies to models with *stochastic* gradient feedback of *unbounded* variance (Models 2 and 3 respectively) is a major difference. As far as we are aware, this is the first guarantee of its kind in the literature on learning in stochastic games.

Concluding remarks. A key roadblock encountered by practical applications of multi-agent reinforcement learning is the lack of universal equilibrium convergence guarantees. While the impossibility results of [21, 22] imply that unconditional convergence is not a reasonable aspiration without further assumptions on the game, the existence of local convergence results mitigates this deficiency as it provides a range of theoretically grounded stability and runtime guarantees. In this regard, second-order stationary and deterministic policies acquire particular importance, as the convergence of policy gradient methods is especially rapid and robust and this case. Of course, this leaves open the question of non-tabular settings and parametrically encoded policies, e.g., as in the case of deep reinforcement learning; we defer these investigations to future work.

References

[1] Alekh Agarwal, Sham M. Kakade, Jason D. Lee, and Gaurav Mahajan. Optimality and approximation with policy gradient methods in markov decision processes. In Jacob D. Abernethy and Shivani Agarwal, editors, *Conference on Learning Theory, COLT 2020, 9-12 July 2020, Virtual Event [Graz, Austria]*, volume 125 of *Proceedings of Machine Learning Research*, pages 64–66. PMLR, 2020. URL http://proceedings.mlr.press/v125/agarwal20a.html.

[2] Alekh Agarwal, Sham M Kakade, Jason D Lee, and Gaurav Mahajan. On the theory of policy gradient methods: Optimality, approximation, and distribution shift. *Journal of Machine Learning Research*, 22 (98):1–76, 2021.

[3] Yu Bai and Chi Jin. Provable self-play algorithms for competitive reinforcement learning. In *International conference on machine learning*, pages 551–560. PMLR, 2020.

[4] Jonathan Baxter and Peter L Bartlett. Infinite-horizon policy-gradient estimation. *Journal of Artificial Intelligence Research*, 15:319–350, 2001.

[5] Jalaj Bhandari and Daniel Russo. Global optimality guarantees for policy gradient methods. *arXiv preprint arXiv:1906.01786*, 2019.

[6] Noam Brown and Tuomas Sandholm. Superhuman ai for heads-up no-limit poker: Libratus beats top professionals. *Science*, 359(6374):418–424, 2018. doi: 10.1126/science.aao1733.

[7] Noam Brown and Tuomas Sandholm. Superhuman ai for multiplayer poker. *Science*, 365(6456):885–890, 2019. doi: 10.1126/science.aay2400.

[8] Noam Brown, Anton Bakhtin, Adam Lerer, and Qucheng Gong. Combining deep reinforcement learning and search for imperfect-information games. In *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020*, 2020.

[9] Sébastien Bubeck. Convex optimization: Algorithms and complexity. *Foundations and Trends in Machine Learning*, 8(3-4):231–358, 2015.

[10] Qi Cai, Zhuoran Yang, Chi Jin, and Zhaoran Wang. Provably efficient exploration in policy optimization. In Hal Daumé III and Aarti Singh, editors, *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pages 1283–1294. PMLR, 13–18 Jul 2020. URL https://proceedings.mlr.press/v119/cai20d.html.

[11] Zhangjie Cao, Erdem Bıyık, Woodrow Z Wang, Allan Raventos, Adrien Gaidon, Guy Rosman, and Dorsa Sadigh. Reinforcement learning based control of imitative policies for near-accident driving. *arXiv preprint arXiv:2007.00178*, 2020.

[12] Shicong Cen, Yuting Wei, and Yuejie Chi. Fast policy extragradient methods for competitive games with entropy regularization. In *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021*, pages 27952–27964, 2021.

[13] Jinglin Chen and Nan Jiang. Information-theoretic considerations in batch reinforcement learning. In *International Conference on Machine Learning*, pages 1042–1051. PMLR, 2019.

[14] Constantinos Daskalakis, Dylan J Foster, and Noah Golowich. Independent policy gradient methods for competitive reinforcement learning. *Advances in neural information processing systems*, 33:5527–5540, 2020.

[15] Constantinos Daskalakis, Noah Golowich, and Kaiqing Zhang. The complexity of markov equilibrium in stochastic games. *arXiv preprint arXiv:2204.03991*, 2022.

[16] Xiaotie Deng, Yuhao Li, David Henry Mguni, Jun Wang, and Yaodong Yang. On the complexity of computing markov perfect equilibrium in general-sum stochastic games. *arXiv preprint arXiv:2109.01795*, 2021.

[17] Dongsheng Ding, Chen-Yu Wei, Kaiqing Zhang, and Mihailo R Jovanović. Independent policy gradient for large-scale markov potential games: Sharper rates, function approximation, and game-agnostic convergence. *arXiv preprint arXiv:2202.04129*, 2022.

[18] Jianqing Fan, Zhaoran Wang, Yuchen Xie, and Zhuoran Yang. A theoretical analysis of deep q-learning. In *Learning for Dynamics and Control*, pages 486–489. PMLR, 2020.

[19] Arlington M Fink. Equilibrium in a stochastic *n*-person game. *Journal of science of the hiroshima university, series ai (mathematics)*, 28(1):89–93, 1964.

[20] Drew Fudenberg and Jean Tirole. *Game Theory*. The MIT Press, 1991.

[21] Sergiu Hart and Andreu Mas-Colell. A simple adaptive procedure leading to correlated equilibrium. *Econometrica*, 68(5):1127–1150, September 2000.

[22] Sergiu Hart and Andreu Mas-Colell. Uncoupled dynamics do not lead to Nash equilibrium. *American Economic Review*, 93(5):1830–1836, 2003.

[23] Chi Jin, Zeyuan Allen-Zhu, Sebastien Bubeck, and Michael I Jordan. Is q-learning provably efficient? *Advances in neural information processing systems*, 31, 2018.

[24] Chi Jin, Qinghua Liu, Yuanhao Wang, and Tiancheng Yu. V-learning–a simple, efficient, decentralized algorithm for multiagent rl. *arXiv preprint arXiv:2110.14555*, 2021.

[25] Yujia Jin, Vidya Muthukumar, and Aaron Sidford. The complexity of infinite-horizon general-sum stochastic games, 2022.

[26] Sham M Kakade. A natural policy gradient. *Advances in neural information processing systems*, 14, 2001.

[27] Vijay Konda and John Tsitsiklis. Actor-critic algorithms. *Advances in neural information processing systems*, 12, 1999.

[28] Rida Laraki, Jérôme Renault, and Sylvain Sorin. *Mathematical Foundations of Game Theory*. Universitext. Springer, 2019.

[29] Stefanos Leonardos, Will Overman, Ioannis Panageas, and Georgios Piliouras. Global convergence of multi-agent policy gradient in markov potential games. 2021.

[30] Stefanos Leonardos, Will Overman, Ioannis Panageas, and Georgios Piliouras. Global convergence of multi-agent policy gradient in markov potential games. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=gfwON7rAm4.

[31] Sridhar Mahadevan. Average reward reinforcement learning: Foundations, algorithms, and empirical results. *Machine learning*, 22(1):159–195, 1996.

[32] Konstantinos Makantasis, Maria Kontorinaki, and Ioannis Nikolos. A deep reinforcement learning driving policy for autonomous road vehicles, 2019. URL https://arxiv.org/abs/1905.09046.

[33] Eric Mazumdar, Lillian J Ratliff, Michael I Jordan, and S Shankar Sastry. Policy-gradient algorithms have no guarantees of convergence in linear quadratic games. *arXiv preprint arXiv:1907.03712*, 2019.

[34] Panayotis Mertikopoulos and Zhengyuan Zhou. Learning in games with continuous action sets and unknown payoff functions. *Mathematical Programming*, 173(1-2):465–507, January 2019.

[35] Matej Moravčík, Martin Schmid, Neil Burch, Viliam Lisý, Dustin Morrill, Nolan Bard, Trevor Davis, Kevin Waugh, Michael Johanson, and Michael Bowling. Deepstack: Expert-level artificial intelligence in heads-up no-limit poker. *Science*, 356(6337):508–513, 2017. doi: 10.1126/science.aam6960.

[36] Rémi Munos. Error bounds for approximate policy iteration. In *ICML*, volume 3, pages 560–567, 2003.

[37] Rémi Munos. Error bounds for approximate value iteration. In *Proceedings of the National Conference on Artificial Intelligence*, volume 20, page 1006. Menlo Park, CA; Cambridge, MA; London; AAAI Press; MIT Press; 1999, 2005.

[38] Yurii Nesterov. *Introductory Lectures on Convex Optimization: A Basic Course*. Number 87 in Applied Optimization. Kluwer Academic Publishers, 2004.

[39] Abraham Neyman and Sylvain Sorin, editors. *Stochastic Games and Applications*. NATO ASI. Kluwer Academic Publishers, 2003.

[40] Santiago Paternain. *Stochastic control foundations of autonomous behavior*. PhD thesis, University of Pennsylvania, 2018.

[41] Boris Teodorovich Polyak. *Introduction to Optimization*. Optimization Software, New York, NY, USA, 1987.

[42] B.T. Polyak. Gradient methods for the minimisation of functionals. *USSR Computational Mathematics and Mathematical Physics*, 3(4):864–878, 1963. ISSN 0041-5553.

[43] Ahmad EL Sallab, Mohammed Abdou, Etienne Perot, and Senthil Yogamani. Deep reinforcement learning framework for autonomous driving. *Electronic Imaging*, 29(19):70–76, jan 2017. doi: 10.2352/issn.2470-1173.2017.19.avm-023. URL https://doi.org/10.2352%2Fissn.2470-1173.2017.19.avm-023.

[44] Muhammed O Sayin, Francesca Parise, and Asuman Ozdaglar. Fictitious play in zero-sum stochastic games. *arXiv preprint arXiv:2010.04223*, 2020.

[45] Shai Shalev-Shwartz, Shaked Shammah, and Amnon Shashua. Safe, multi-agent, reinforcement learning for autonomous driving. *arXiv preprint arXiv:1610.03295*, 2016.

[46] Lloyd S. Shapley. Stochastic games. *Proceedings of the National Academy of Sciences of the USA*, 39: 1095–1100, 1953.

[47] Lloyd S Shapley. Stochastic games. *Proceedings of the national academy of sciences*, 39(10):1095–1100, 1953.

[48] David Silver, Julian Schrittwieser, Karen Simonyan, Ioannis Antonoglou, Aja Huang, Arthur Guez, Thomas Hubert, Lucas Baker, Matthew Lai, Adrian Bolton, Yutian Chen, Timothy P. Lillicrap, Fan Hui, Laurent Sifre, George van den Driessche, Thore Graepel, and Demis Hassabis. Mastering the game of go without human knowledge. *Nat.*, 550(7676):354–359, 2017. doi: 10.1038/nature24270.

[49] Eilon Solan and Nicolas Vieille. Stochastic games. *Proceedings of the National Academy of Sciences*, 112 (45):13743–13746, 2015.

[50] Ziang Song, Song Mei, and Yu Bai. When can we learn general-sum markov games with a large number of players sample-efficiently? *arXiv preprint arXiv:2110.04184*, 2021.

[51] Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction*. MIT press, 2018.

[52] Richard S Sutton, David McAllester, Satinder Singh, and Yishay Mansour. Policy gradient methods for reinforcement learning with function approximation. *Advances in neural information processing systems*, 12, 1999.

[53] Masayuki Takahashi. Stochastic games with infinitely many strategies. *Journal of Science of the Hiroshima University, Series AI (Mathematics)*, 26(2):123–134, 1962.

[54] Oriol Vinyals, Igor Babuschkin, Wojciech M. Czarnecki, Michaël Mathieu, Andrew Dudzik, Junyoung Chung, David H. Choi, Richard Powell, Timo Ewalds, Petko Georgiev, Junhyuk Oh, Dan Horgan, Manuel Kroiss, Ivo Danihelka, Aja Huang, Laurent Sifre, Trevor Cai, John P. Agapiou, Max Jaderberg, Alexander Sasha Vezhnevets, Rémi Leblond, Tobias Pohlen, Valentin Dalibard, David Budden, Yury Sulsky, James Molloy, Tom Le Paine, Çaglar Gülçehre, Ziyu Wang, Tobias Pfaff, Yuhuai Wu, Roman Ring, Dani Yogatama, Dario Wünsch, Katrina McKinney, Oliver Smith, Tom Schaul, Timothy P. Lillicrap, Koray Kavukcuoglu, Demis Hassabis, Chris Apps, and David Silver. Grandmaster level in starcraft II using multi-agent reinforcement learning. *Nat.*, 575(7782):350–354, 2019. doi: 10.1038/s41586-019-1724-z.

[55] Okko Jan Vrieze. Stochastic games with finite state and action spaces. *CWI tracts*, 1987.

[56] Chen-Yu Wei, Chung-Wei Lee, Mengxiao Zhang, and Haipeng Luo. Last-iterate convergence of decentralized optimistic gradient descent/ascent in infinite-horizon competitive markov games. In Mikhail Belkin and Samory Kpotufe, editors, *Proceedings of Thirty Fourth Conference on Learning Theory*, volume 134 of *Proceedings of Machine Learning Research*, pages 4259–4299. PMLR, 15–19 Aug 2021.

[57] Ronald J Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine learning*, 8(3):229–256, 1992.

[58] Markus Wulfmeier, Dushyant Rao, Dominic Zeng Wang, Peter Ondruska, and Ingmar Posner. Large-scale cost function learning for path planning using deep inverse reinforcement learning. *The International Journal of Robotics Research*, 36(10):1073–1087, 2017.

[59] Lin Xiao. On the convergence rates of policy gradient methods. *arXiv preprint arXiv:2201.07443*, 2022.

[60] Qiaomin Xie, Yudong Chen, Zhaoran Wang, and Zhuoran Yang. Learning zero-sum simultaneous-move markov games using function approximation and correlated equilibrium. In *Conference on learning theory*, pages 3674–3682. PMLR, 2020.

[61] Kaiqing Zhang, Zhuoran Yang, Han Liu, Tong Zhang, and Tamer Basar. Fully decentralized multi-agent reinforcement learning with networked agents. In Jennifer Dy and Andreas Krause, editors, *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pages 5872–5881. PMLR, 10–15 Jul 2018. URL https://proceedings.mlr.press/v80/zhang18n.html.

[62] Kaiqing Zhang, Alec Koppel, Hao Zhu, and Tamer Basar. Global convergence of policy gradient methods to (almost) locally optimal policies. *SIAM Journal on Control and Optimization*, 58(6):3586–3612, 2020.

[63] Kaiqing Zhang, Zhuoran Yang, and Tamer Başar. Multi-agent reinforcement learning: A selective overview of theories and algorithms. *Handbook of Reinforcement Learning and Control*, pages 321–384, 2021.

[64] Runyu Zhang, Zhaolin Ren, and Na Li. Gradient play in multi-agent markov stochastic games: Stationary points and convergence. *arXiv e-prints*, pages arXiv–2106, 2021.

[65] Martin Zinkevich. Online convex programming and generalized infinitesimal gradient ascent. In *ICML '03: Proceedings of the 20th International Conference on Machine Learning*, pages 928–936, 2003.