The Effect of Data Encoding on Relation Triplet Identification

Affiliation / Address line 1
Affiliation / Address line 2
Affiliation / Address line 3
email@domain

Anonymouser Author
Affiliation / Address line 1
Affiliation / Address line 2
Affiliation / Address line 3
email@domain

Anonymousest Author
Affiliation / Address line 1
Affiliation / Address line 2
Affiliation / Address line 3
email@domain

Abstract

This paper presents a novel method for creating relation extraction data for low-resource languages. Relation extraction (RE) is a task in natural language processing that involves identifying and extracting meaningful relationships between entities in text. Despite the increasing need to extract relationships from unstructured text, the limited availability of annotated data in low-resource languages presents a significant challenge to the development of high-quality relation extraction models. Our method leverages existing methods for high-resource languages to create training data for low-resource languages. The proposed method is simple, efficient and has the potential to significantly improve the performance of relation extraction models for low-resource languages, making it a promising avenue for future research.

1 Introduction

Relation extraction (RE) is a task in the field of natural language processing, aimed at identifying and extracting semantically meaningful relationships between entities present in text. A relation is generally extracted as an ordered triple (E_1, R, E_2) where E_1 and E_2 refer to the entity identifiers and R refers to the relation type. This task holds great significance in several practical applications, including information retrieval, knowledge management, and question-answering systems, among others (for a recent review, see (Yan et al., 2021)). The increasing availability of unstructured text data on the web has only served to underline the importance of relation extraction, as there is a pressing need to convert this data into structured information that can be eas-ily accessed and analyzed. This challenge is especially pertinent for low-resource languages like Icelandic, where the limited availability of annotated data presents a significant impediment to the development of high-quality relation extraction models.

Relation extraction methods for English have evolved over the years, with early methods relying on hand-crafted rules, patterns, and statistical analyses (Soderland et al., 1995; Carlson et al., 2010; Kambhatla, 2004; Jiang and Zhai, 2007). With the advent of deep learning and the availability of large annotated corpora, more sophisticated methods have emerged (Liu et al., 2013; Xu et al., 2016; dos Santos et al., 2015). Deep learning models have shown promising results in extracting relationships between entities, outperforming traditional methods. Current state-of-the-art model, ReBEL (Cabot and Navigli, 2021), performs joint relation extraction[1]. The progress in relation extraction for English has demonstrated the potential for using advanced techniques to extract meaningful relationships from large amounts of text data.

The challenge of developing effective RE methods for languages like Icelandic lies in the scarcity of annotated data. The performance of machine learning models heavily relies on the availability of large amounts of annotated training data. The limited availability of annotated text in low-resource languages creates a major challenge for training high-quality relation extraction models. To overcome this challenge, one way is to study methods to efficiently create training data based on existing methods for English. Our main question is whether models from high-resource languages can be used to efficiently create training and testing data for low-resource languages.

In this paper, we present a novel method for efficiently creating relation extraction data for low-

---

[1]That is, entity extraction and relation extraction are not two separate processes.

resource languages like Icelandic. Our method is based on replacing entities in the text with unique identifiers, translating the text to a high-resource language using machine translation, and then replacing the entities back in the translated text. Finally, we perform relation extraction on the translated text to obtain the relationships between entities. Our method is simple and only requires the location of entities in the text and a machine translation model. This approach leverages the availability of specialized models in high-resource languages to create training data for low-resource languages, thereby addressing the challenge posed by the scarcity of annotated data. Our method has the potential to significantly improve the performance of relation extraction models for low-resource languages, making it a promising avenue for future research.

2 Purpose

In a recent paper, Friðriksdóttir et al. proposed a way of bootstrapping RE training data for low-resource languages (LRL) using a combination of machine translation and open RE methods. By automatically translating the LRL data into English, they were able to feed it directly into the high-resource language SOTA model before translating the relation triplets back to the LRL where it can serve as training data for a new LRL model.

While this method showed potential, the resulting data was jumbled by errors in translation. Some examples of this include people's names being perturbed by the multilingual translation model (resulting in *Alfreð* being changed into *Alfredo*, *Sveinn* into *Sweene* etc.), entities getting directly translated and thereby loosing their meaning (such as when the Icelandic name *Erlendur* gets directly translated as *foreign*) and unfortunate translation mishaps (such as when *Dauðarósir*, a novel by the Icelandic author Arnaldur Indriðason, gets translated as *Deathly Hallows*, a real novel by a different author).

In this paper, we hypothesize that these translation errors can be ameliorated by encoding the entities within the data before it gets translated, and then decoding them before they get sent into the high-resource RE model. Whereas the proposed method remains the same, this extra step in preprocessing the input data should result in more accurate predictions made by the RE model, which in turn makes for better training data.

3 Previous Work

Machine-translation has previously been used to create cross-lingual named entity recognition (NER) datasets, which led to improvement in NER for several languages (Dandapat and Way, 2016; Jain et al., 2019). In these earlier works, the text was translated directly, without any modifications, and the entities in the resulting text were matched heuristically to the entities in the untranslated text using word alignment methods. This works well for entities that translate correctly or change little in the translation process but can be limited by the translation system, specifically if the system translates entities incorrectly.

For RE in low-resource languages, there has been limited focus on building training and testing data efficiently. However, crosslingual transfer methods have been applied to improve RE models, such as using multilingual BERT (Nag et al., 2021). Universal dependencies and sequence-to-sequence approaches have also been employed for RE in low-resource languages (Taghizadeh and Faili, 2022). Finally, recent sequence-to-sequence approaches for English have focused on extracting both relations and relation types (Cabot and Navigli, 2021).

Annotation process

1 **Input:** Anna fór í Hörpu

2 **Entities are replaced**
E1 fór í E2

3 **Translation**
E1 went to E2

4 **Entities recovered**
Anna went to Harpa

5 **ReBEL applied**
(Anna, located in, Harpa)

Figure 1: Summary of the annotation process for relation extraction studied in this paper.

4 Methodology

A general overview of the annotation approach is demonstrated in Figure 1. Below, we outline the methods used in the process.

4.1 Models

For translation, we use the model from Facebook AI's WMT21 submission (Tran et al., 2021). The model is multilingual and has well-performing Icelandic to English translation capabilities.

For relation extraction, we use REBEL (Cabot and Navigli, 2021) a sequence-to-sequence relation extraction model that achieves a micro-F1 score of 75.4 on the well-studied CONLL4 corpus (Roth and Yih, 2004) and 93.4 on the NYT corpus (Riedel et al., 2010).

4.2 Data

For evaluating the relation extraction method, we use the first 200 sentences of each category from the MIM-GOLD-EL corpus (Friðriksdóttir et al., 2022). The number of unique and lemmatized entities for each category are shown in Table 4 in the Appendix.

4.3 Encoding Entities

Each entity receives its own identifier and is replaced by it. The first occurring entity in the text receives the identifier E0, the next one E1, et cetera. For the sake of clarity, we note that if an entity appears multiple times in the text, it receives the same entity for all occurrences. This makes it clear which encoding refers to which original entity when decoded.

5 Results

Our results indicate that using the encoding method proposed can increase the number of correctly identified relation triplets by 3-15% (Table 1) when the Books category is excluded. It is evident that a higher number of relation triplets is proposed by REBEL when the data is not encoded (Table 2) and we suspect this is due to the text being more fluently English, i.e. it contains less foreign (in our case, Icelandic) words within the English translation which should make it more natural for the monolingually English RE model. On the other hand, having a higher number of relation triplets proposed introduces significantly more noise, making the percentage of correctly identified relation triplets in fact lower. Additionally, encoding the data reduces the number of translation inconsistencies and errors. Conjugation of nouns tends to be mangled by the translation model, creating examples such as *Steingríms [genitive] Davíðsson [nominative]*, accents

get dropped (Ása becomes Asa) and Icelandic letters modified (Þorgrímur becomes Thorgrímur). Summary statistics can be seen in Table 3 and by category in Table 4 in the Appendix.

It is interesting to note that the text categories from our corpora that contain news, and have therefore been translated using WMT21's newsdomain parameter which should theoretically make them better translated, actually receive significantly lower proportions of correctly identified relation triplets than those that do not. The highest scoring categories are those who should supposedly be the more difficult ones, such as the law and adjudications categories. This might be due to the number of proposed relations being higher within the news categories as they contain a higher number of entities being introduced for the first time. All categories score higher in correctly identified relation triplets when using the encoding method except one, the books category.

Category	Encoded	Not
Adjudications	67%	53%
Blog	74%	59%
Books	40%	42%
Emails	42%	38%
Newspaper 1	37%	31%
Newspaper 2	39%	36%
Laws	52%	39%
Radio/TV news	31%	28%
School essays	53%	41%
Scienceweb	37%	33%
Webmedia	38%	32%
Websites	31%	26%
Written to be spoken	46%	38%

Table 1: Results per category. The reported numbers are the percentage of relation triplets labelled as correct per text category within our corpus.

5.1 Qualitative Evaluation of Errors

We note that while technically correct, the machine translation model tends to give various different translations to a single entity which certainly influences the higher number of unique relation triplets proposed by the RE model when working with data that has not been encoded. For instance, the Icelandic political party Samfylkingin gets translated in four different ways (Confederation, Alliance, Social democrats and

	Encoded	Not
Total relations extracted	8870	8910
Entities in translation	4368	3476
Correct relations	2078	2450
Correct with entities	541	135

Table 2: Results on the overall data. Entities in translation refers to the number of times that entities from MIM-GOLD-EL appear lemmatized in the resulting translation. Correct relations refers to the total number of relations labelled as correct, regardless of whether or not they contain established entities. Correct with entities refers to relation triplets that contain established entities as both head and tail.

Social democratic party) as well as the rescue worker association Landsbjörg (translated as either accident insurance company, accident prevention association, emergency rescue association or accident prevention society). Encoding the data avoids the problem of having to backtrack the translations in order to figure out whether or not they refer to the same original entity.

Using the encoding method, we can additionally ensure that all extracted relation triplets contain entities that include the entire, lemmatized mention of the entity. As per Icelandic naming conventions, a person is generally only referred to by their full name the first time they are mentioned in a given text and afterwards only referred to by their first name. When working with data that has not been encoded, we therefore get relation triplets that include only the first name of a person, potentially conjugated, while the encoded data always ensures that the person's entire, lemmatized name is present within the triple. This creates more consistency and avoids ambiguity in the output data.

It should, however, be noted that REBEL itself occasionally jumbles entity mentions itself even though the data has been encoded. Examples of this include when REBEL proposes that a person is a part of a family by that person's last name (i.e. *Ingibjörg Sólrún Gísladóttir, is a member of, Gísladóttir*) but this is not how things work in Icelandic where patronyms are used instead of traditional last names. Another example is when REBEL adds international endings to websites that already include their Icelandic endings (such as when *tonlist.is* becomes *tonlist.is.com*).

6 Discussion

Our approach addresses the low-performance of modern machine translation systems in translating entities correctly. Therefore, we would expect that improvements in machine translation would make our approach obsolete. However, that would require better translations of named entities. Unfortunately, for Icelandic, we do not have a corpus of entities translated to other languages such as English. Transliteration of named entities is the process of translating entities across languages and has been performed for English and several other languages (Grundkiewicz and Heafield, 2018). Transliterating named entities could be an approach to improve machine translation for Icelandic and would possibly make it more reliable to translate without any modifications to the source text and use word alignment to match entities between the source text and the translated text.

For creating data on relation extraction, we use machine-translation as an aid. However, to build a good relation extraction system for Icelandic, it might not be necessary to fine-tune the system on Icelandic. As an example, multilingual QA systems have shown good performance on Icelandic although they were not fine-tuned in QA for the language (Snæbjarnarson and Einarsson, 2022). We expect to see similar results for Icelandic and the data from this work can serve as a test set to measure the performance.

7 Conclusion

In conclusion, the proposed encoding method shows great potential for LRL, improving the percentage of correctly identified relation triplets by up to 15% for various categories of text. The method is simple and does not require any additional cost, making it ideal for languages where data is scarce and budget is limited. We note that this method can only be as good as the quality of the machine translation models as well as the RE methods for higher resourced languages. However, the encoding avoids several issues introduced by the bootstrapping method, making it more efficient with minimal effort.

References

Pere-Lluís Huguet Cabot and Roberto Navigli. 2021. REBEL: Relation extraction by end-to-end language generation. In *Findings of the Association for Computational Linguistics: EMNLP 2021*, pages 2370–2381, Punta Cana, Dominican Republic. Association for Computational Linguistics.

Andrew Carlson, Justin Betteridge, Bryan Kisiel, Burr Settles, Estevam Hruschka, and Tom Mitchell. 2010. Toward an architecture for never-ending language learning. In *Proceedings of the AAAI conference on artificial intelligence*, volume 24, pages 1306–1313.

Sandipan Dandapat and Andy Way. 2016. Improved named entity recognition using machine translation-based cross-lingual information. *Computación y Sistemas*, 20(3):495–504.

Steinunn Rut Friðriksdóttir, Valdimar Ágúst Eggertsson, Benedikt Geir Jóhannesson, Hjalti Daníelsson, Hrafn Loftsson, and Hafsteinn Einarsson. 2022. Building an Icelandic Entity Linking Corpus. In *Proceedings of the workshop 'Dataset Creation for Lower-Resourced Languages', at the 13th International Conference on Language Resources and Evaluation (LREC 2022).*, Marseille, France.

Roman Grundkiewicz and Kenneth Heafield. 2018. Neural machine translation techniques for named entity transliteration. In *Proceedings of the Seventh Named Entities Workshop*, pages 89–94, Melbourne, Australia. Association for Computational Linguistics.

Alankar Jain, Bhargavi Paranjape, and Zachary C. Lipton. 2019. Entity projection via machine translation for cross-lingual NER. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 1083–1092, Hong Kong, China. Association for Computational Linguistics.

Jing Jiang and ChengXiang Zhai. 2007. A systematic exploration of the feature space for relation extraction. In *Human Language Technologies 2007: The Conference of the North American Chapter of the Association for Computational Linguistics; Proceedings of the Main Conference*, pages 113–120, Rochester, New York. Association for Computational Linguistics.

Nanda Kambhatla. 2004. Combining lexical, syntactic, and semantic features with maximum entropy models for information extraction. In *Proceedings of the ACL Interactive Poster and Demonstration Sessions*, pages 178–181, Barcelona, Spain. Association for Computational Linguistics.

ChunYang Liu, WenBo Sun, WenHan Chao, and Wanxiang Che. 2013. Convolution neural network for relation extraction. In *Advanced Data Mining and Applications: 9th International Conference, ADMA 2013, Hangzhou, China, December 14-16, 2013, Proceedings, Part II 9*, pages 231–242. Springer.

Arijit Nag, Bidisha Samanta, Animesh Mukherjee, Niloy Ganguly, and Soumen Chakrabarti. 2021. A data bootstrapping recipe for low-resource multilingual relation classification. In *Proceedings of the 25th Conference on Computational Natural Language Learning*, pages 575–587, Online. Association for Computational Linguistics.

Sebastian Riedel, Limin Yao, and Andrew McCallum. 2010. Modeling relations and their mentions without labeled text. In *Machine Learning and Knowledge Discovery in Databases*, pages 148–163, Berlin, Heidelberg. Springer Berlin Heidelberg.

Dan Roth and Wen-tau Yih. 2004. A linear programming formulation for global inference in natural language tasks. In *Proceedings of the Eighth Conference on Computational Natural Language Learning (CoNLL-2004) at HLT-NAACL 2004*, pages 1–8, Boston, Massachusetts, USA. Association for Computational Linguistics.

Cícero dos Santos, Bing Xiang, and Bowen Zhou. 2015. Classifying relations by ranking with convolutional neural networks. In *Proceedings of the 53rd Annual Meeting of the Association for Computational Linguistics and the 7th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 626–634, Beijing, China. Association for Computational Linguistics.

Vésteinn Snæbjarnarson and Hafsteinn Einarsson. 2022. Cross-Lingual QA as a Stepping Stone for Monolingual Open QA in Icelandic. In *Proceedings of the Workshop on Multilingual Information Access (MIA)*, pages 29–36, Seattle, USA. Association for Computational Linguistics.

Stephen Soderland, David Fisher, Jonathan Aseltine, and Wendy Lehnert. 1995. Crystal inducing a conceptual dictionary. In *Proceedings of the 14th international joint conference on Artificial intelligence-Volume 2*, pages 1314–1319.

Nasrin Taghizadeh and Heshaam Faili. 2022. Cross-lingual transfer learning for relation extraction using universal dependencies. *Computer Speech & Language*, 71:101265.

Chau Tran, Shruti Bhosale, James Cross, Philipp Koehn, Sergey Edunov, and Angela Fan. 2021. Facebook AI's WMT21 news translation task submission. In *Proceedings of the Sixth Conference on Machine Translation*, pages 205–215, Online. Association for Computational Linguistics.

Yan Xu, Ran Jia, Lili Mou, Ge Li, Yunchuan Chen, Yangyang Lu, and Zhi Jin. 2016. Improved relation classification by deep recurrent neural networks

with data augmentation. In *Proceedings of COLING 2016, the 26th International Conference on Computational Linguistics: Technical Papers*, pages 1461–1470, Osaka, Japan. The COLING 2016 Organizing Committee.

Yu Yan, Haolin Sun, and Jie Liu. 2021. A review and outlook for relation extraction. In *Proceedings of the 5th International Conference on Computer Science and Application Engineering*, CSAE '21, New York, NY, USA. Association for Computing Machinery.

A   Summary Statistics

To highlight the scope of this work, we list important summary statistics in Table 3 and by category in Table 4.

	Encoded	Not Encoded
Total relations extracted	8870	8910
Unique triplets	1558	1805
Unique relation types	128	141

Table 3: Results on the overall data. Total relations refers to the total number of relations retrieved by REBEL. Unique triplets refer to the total number of unique relation triplets.

Category	# Unique Entities	# Not encoded	# Encoded
Adjudications	50	731	734
Blog	75	689	757
Books	118	752	740
Emails	89	355	343
Newspaper 1	207	696	676
Newspaper 2	213	722	690
Laws	96	694	651
Radio/TV news	132	708	686
School essays	89	747	753
Scienceweb	180	707	702
Webmedia	202	712	729
Websites	184	699	678
Written to be sp.	184	728	731

Table 4: The first column shows the number of unique, lemmatized entities in the first 200 sentences of each category. The second column depicts the number of relations where the data has not been encoded and the third the number of relations where the data has been encoded.