Theoretical Foundations of Continual Learning via Drift-Plus-Penalty

Abstract

In many real-world settings, data streams are inherently nonstationary and arrive sequentially, necessitating learning systems to adapt continuously without repeatedly retraining from scratch. Continual learning (CL) addresses this setting by seeking to incorporate new tasks while preventing catastrophic forgetting, whereby updates for recent data induce performance degradation on previously acquired knowledge. We introduce a control-theoretic perspective on CL that explicitly regulates the temporal evolution of forgetting, framing adaptation to new tasks as a controlled process subject to long-term stability constraints. We focus on replay-based CL settings in which a finite memory buffer preserves representative samples from prior tasks, allowing forgetting to be explicitly regulated. We propose COntinual Learning with Drift-Plus-Penalty (`COLD`), a novel CL framework grounded in stochastic optimization-based Drift-Plus-Penalty (DPP) principle. At each task, `COLD` minimizes the instantaneous penalty corresponding to the current task loss while simultaneously maintaining a virtual queue that explicitly tracks deviations from long-term stability on previously learned tasks, hence capturing the stability–plasticity trade-off as a regulated dynamical process. We establish stability and convergence guarantees that characterize this trade-off, as governed by a tunable control parameter. Empirical results on standard benchmark datasets show that the proposed framework consistently achieves superior accuracy compared to a wide range of state-of-the-art CL baselines, while exhibiting competitive and tunable forgetting behavior that reflects the explicit regulation of the stability–plasticity trade-off through virtual queues and the DPP objective.

1 Introduction

Lifelong learning in artificial intelligence is motivated by the human capacity to continuously acquire and adapt knowledge over time. A central component of lifelong learning is continual learning (CL), which seeks to incorporate new information while retaining knowledge acquired from previous experiences. In streaming settings, memory constraints prevent the storage of all historical data, and only a limited subset of samples or summary statistics can be retained. These constraints make CL fundamentally more challenging than single-task learning, as joint training over the complete data from all tasks is infeasible. Conversely, sequentially updating a model using task-specific data often results in performance degradation on previously learned tasks, a phenomenon referred to as catastrophic forgetting McCloskey & Cohen (1989). Consequently, the objective of CL is to balance the acquisition of new knowledge (*plasticity*) with the preservation of previously learned information (*stability*).

The goal of CL mechanism is to regulate two competing objectives over time: the first objective is to achieve strong performance on the current task by effectively exploiting previously acquired knowledge, and the second objective is to control catastrophic forgetting by constraining the degradation of performance on earlier tasks as the model adapts to new data Lin et al. (2022). Task heterogeneity arising from shifts in data distributions across tasks acts as a hindrance that induces conflicting update directions and as a result, optimizing current-task performance and enforcing stability on past tasks constitute a coupled regulation problem with an inherent trade-off. Existing strategies for CL fall into three categories: regularization-based Kirkpatrick et al. (2017); Li & Hoiem (2017); Liu & Liu (2022), replay-based Lopez-Paz & Ranzato (2017); Chaudhry

et al. (2018); Caccia et al. (2021), and architecture-based methods Rusu et al. (2016); Long et al. (2025). Regularization- and Architecture-based CL methods primarily mitigate forgetting myopically through capacity allocation or parameter-level penalties, respectively, but do not explicitly model the temporal evolution of forgetting or provide principled mechanisms to regulate long-term stability under task heterogeneity.

Replay-based CL methods provide an explicit mechanism to observe and quantify forgetting on previously learned tasks through budget-constrained memory samples. Notable techniques that employ memory replay include Gradient Episodic Memory (GEM) Lopez-Paz & Ranzato (2017), Averaged GEM (`A-GEM`) Chaudhry et al. (2018), and Non-Convex CL with Adaptive Learning Rates (`NCCL`) Han et al. (2023). Approaches such as GEM and `A-GEM` enforce per-step feasibility by projecting the current task gradient onto a constraint set defined by past-task gradients, thereby suppressing updates that conflict with previously learned tasks. Although such projection-based strategies prevent instantaneous interference, they do not control the accumulation of forgetting over time and may substantially reduce plasticity under high task diversity, limiting adaptation to new tasks. `NCCL` formulates CL as a nonconvex stochastic optimization problem with replay, but it lacks mechanisms to ensure long-term stability with respect to catastrophic forgetting.

We argue that CL is inherently a dynamic process and not a static optimization problem, as the learner must adapt to new tasks while constraining the progressive degradation of previously acquired knowledge. Moreover, catastrophic forgetting evolves and accumulates over successive updates. Hence, long-term stability of the learning dynamics is as important as instantaneous task-level performance. This temporal coupling motivates a control-theoretic formulation of CL, instead of a conventional optimization-based formulation. Accordingly, we adopt tools from stochastic control, in particular Lyapunov analysis and the drift-plus-penalty (DPP) framework Neely (2006), to explicitly model and regulate the dynamics of forgetting under resource constraints. The DPP framework introduces a virtual queue that tracks cumulative constraint violations over time, transforming CL into a problem of stabilizing this queue while optimizing task performance. At each step, the learner selects actions that minimize a weighted combination of the immediate learning objective and the Lyapunov drift of the virtual queue, i.e., balancing short-term plasticity with long-term stability. This dual-objective strategy renders DPP as an important approach for CL, as it provides a natural mechanism to *control* the stability–plasticity trade-off.

Contributions: We cast CL as a long-term constrained stochastic control problem, where catastrophic forgetting is modeled as the accumulation of constraint violations over time. Specifically, we propose *COntinual Learning via Drift Plus Penalty (`COLD`)*, a principled stochastic control framework for CL based on Lyapunov optimization. The key contributions of this work are as follows:

- **Explicit stability–plasticity trade-off:** We formalize CL as a long-term constrained optimization problem and show that `COLD` admits an explicit and tunable trade-off between performance on the current task and forgetting of past tasks through a single parameter V. Our analysis establishes an $O(1/V)$ performance guarantee versus an $O(V)$ forgetting bound, providing a clear and interpretable characterization of the stability–plasticity trade-off that is absent in existing methods.

- **Performance guarantees dependent on task variation:** Unlike prior CL analyses, which are agnostic to how tasks evolve over time, our theoretical bounds explicitly depend on task variation measures that quantify changes in loss functions across tasks. This reveals, for the first time, how large inter-task variability fundamentally limits CL performance, thereby connecting algorithmic behavior to problem nonstationarity.

- **Projection-free constrained learning with fixed learning rates:** `COLD` avoids gradient projection or dual-update mechanisms commonly used in constrained CL methods such as GEM, A-GEM, and related approaches. Instead, constraints are enforced implicitly through virtual queue dynamics, enabling projection-free updates and preserving plasticity. Moreover, our guarantees hold under a fixed learning rate, simplifying implementation and distinguishing `COLD` from methods that rely on adaptive or task-specific step sizes.

- **Queue-based quantification of forgetting:** We introduce a virtual-queue mechanism to dynamically track cumulative forgetting across tasks and establish queue stability guarantees. This provides

a rigorous, algorithm-dependent notion of forgetting that complements performance bounds and offers deeper insight than retrospective or heuristic forgetting metrics used in prior work.

Novelty: The proposed `COLD` framework is a principled stochastic control perspective for CL by adapting the DPP framework. Unlike previous approaches that approximate stability Farajtabar et al. (2020) or rely on heuristic surrogate constraints Chaudhry et al. (2018) to manage forgetting, `COLD` integrates performance and stability objectives into a single unified optimization objective. DPP allows for analytical control of the stability–plasticity trade-off, based on virtual queue-based dynamics to track constraint violations. By modeling memory interference as long-term constraint violations, `COLD` provides theoretical guarantees on convergence and bounded forgetting via theoretical analysis on queue stability. This is an advancement over existing methods that typically lack theoretical guarantees. Moreover, by avoiding projection-based updates as in Lopez-Paz & Ranzato (2017); Chaudhry et al. (2018), `COLD` circumvents the loss of plasticity and suboptimal task adaptation that can arise when gradients are forcibly restricted to feasibility regions defined by past tasks. More recent formulations, such as that of Lin et al. (2023), control forgetting only in expectation and do not provide an explicit mechanism to regulate constraint violations over time. In contrast, COLD offers a *controllable* and *algorithm-dependent* framework that operates without projections, applies to non-convex objectives, and provides explicit guarantees on long-term forgetting via queue stability. To the best of our knowledge, `COLD` is the first method to adapt DPP for memory-based CL with quantified trade-offs between stability and plasticity.

Technical challenges: It is important to note that our setting introduces several nontrivial technical challenges that necessitate substantial departures from standard arguments in DPP analysis. Classical DPP formulations assume independent state evolution, which allows performance to be benchmarked against a stationary solution. In contrast, the constraints in our problem are endogenous and trajectory-dependent: the constraint functions depend explicitly on the learner's own past iterates rather than on exogenous, independent stochastic processes. This dependence precludes direct comparison with a stationary benchmark and instead requires the introduction of an idealized CL problem as a reference. Bounding the average queue length relative to this new benchmark is itself nontrivial. Moreover, the learning environment is inherently nonstationary, with task-dependent loss functions that may vary arbitrarily over time, rendering steady-state or ergodic arguments which are central to classical DPP analysis, inapplicable. Consequently, both the performance bound and the average queue stability bound must be expressed in terms of task variation. Finally, establishing a bound on the average gradient via the gradient descent updates applied to the DPP term presents additional difficulties and has no direct analogue in the classical DPP framework. Taken together, these challenges make the analysis substantially more delicate than a straightforward reuse of existing DPP results and require the development of new bounds that explicitly couple task variation, queue dynamics, and optimization error.

2 Related Works

Rehearsal/Replay-Based Methods: Rehearsal-based methods employ a limited memory buffer of past samples, which is replayed alongside incoming data to mitigate catastrophic forgetting. Experience Replay (ER) serves as the foundational rehearsal-based baseline in CL by maintaining a fixed-size episodic memory of samples from previously encountered tasks and jointly training on mini-batches composed of both current and buffered data Rolnick et al. (2019). Extensions of ER such as Dark Experience Replay (`DER/DER++`) enhance stability by storing and distilling past model outputs Buzzega et al. (2020), Meta-Experience Replay (`MER`) incorporates meta-learning principles to reduce gradient interference across tasks Riemer et al. (2019), and `ER-ACE`, which introduces asymmetric losses to control representation drift. Among other works, `GDumb` Prabhu et al. (2020) adopts a simple strategy by greedily populating the buffer and retraining a model from scratch at evaluation time, `CBA` Wang et al. (2023) adapts classifier bias to mitigate recency effects in online CL, and `REFRESH` Wang et al. (2024) proposes a mechanism to improve performance by integrating an unlearn-then-relearn strategy. Recent work also advances rehearsal through adaptive cognitive allocation in buffer construction Zhang et al. (2024) alongside addressing plasticity-stability trade-off. While rehearsal-based methods mitigate forgetting by repeatedly replaying stored samples or representations to

implicitly regularize parameter updates, they do not explicitly model or regulate the temporal accumulation of forgetting.

Drift Plus Penalty in Machine Learning: The DPP technique, first introduced in the context of stochastic network optimization Neely (2010), is a powerful framework to design stochastic control algorithms that achieve long-term performance guarantees under uncertainty. DPP is based on Lyapunov optimization that balances two competing objectives: minimizing a time-averaged penalty and ensuring constraint satisfaction through the control of virtual queues that are based on time-averaged constraint violations. The DPP framework has found broad applications across domains such as wireless resource allocation Neely et al. (2010), energy-efficient communications Samarakoon et al. (2015), and dynamic scheduling, where it ensures online decision-making with provable convergence bounds. Recently, DPP has been used for constrained reinforcement learning, where the algorithm balances reward maximization with long-term constraint satisfaction Huang et al. (2021); Xu et al. (2025). In online learning settings, it enables dynamic regularization and adaptive constraint enforcement, leading to the best known static regret bounds Sinha & Vaze (2024); Sarkar et al. (2025); Vaze & Sinha (2025).

CL via Constrained Optimization: CL is often cast as a constrained optimization problem, where the goal is to minimize the loss on the current task while enforcing constraints on forgetting. Classic regularization-based methods such as `EWC` Kirkpatrick et al. (2017) and Memory-Aware Synapses (MAS) Aljundi et al. (2018) penalize changes to parameters that are critical for previous tasks, but they do not dynamically track forgetting. Memory replay-based methods with gradient-level constraints include GEM Lopez-Paz & Ranzato (2017) and `A-GEM` Chaudhry et al. (2018); they impose constraints through gradient projection so that the loss on the previous tasks does not increase. `NCCL` adapts task-specific learning rates to better balance stability and plasticity Han et al. (2023). In effect, `GEM`, `A-GEM`, and `NCCL` projects the current task gradients onto a feasible region defined by past-task gradients, which results in components of the original update direction being discarded, especially those that conflict with past-task directions. In cases of high task diversity, a projection operation can lead to reduced plasticity, limiting the ability to fully adapt to new tasks. More recently, techniques for online CL have been proposed for learning from non-stationary data, where each sample can be seen only once Urettini & Carta (2025); Wu et al. (2024). While online CL is necessary in streaming settings, it severely limits the learner's ability to mitigate catastrophic forgetting, since past data cannot be revisited for corrective updates. Existing online methods are largely myopic and per-step, lacking principled mechanisms to control the accumulation of forgetting and provide long-term stability guarantees under heterogeneous task distributions.

3 Continual Learning: Problem Formulation

We consider the CL problem where the challenge is to learn from the tasks that arrive sequentially over time, i.e., the learning dynamics must be explicitly controlled to ensure progress on current tasks while constraining cumulative degradation on past tasks. Consider a sequence of tasks denoted as $\mathbb{T} := \{1, 2, \ldots, T\}$,[1] where each task $t \in \mathbb{T}$ is associated with a data set $\mathcal{D}_t := \{(\mathbf{x}_{t,i}, y_{t,i}) : i = 1, 2, \ldots, n_t\}$ drawn from a distribution P_t. Here, $\mathbf{x}_{t,i} \in \mathcal{X}$ is the feature vector and $y_{t,i} \in \mathcal{Y}$ is the corresponding target label. The quality of the predictor $h_{\mathbf{w}}(\mathbf{x}) \in \mathcal{Y}$ with the model $\mathbf{w} \in \mathcal{W} \subseteq \mathbb{R}^d$ for an input feature vector $\mathbf{x}$ from any task $t \in \mathbb{T}$ is evaluated using an average loss function Φ_t defined by

$$\Phi_t(\mathbf{w}) := \frac{1}{n_t} \sum_{i=1}^{n_t} l(h_{\mathbf{w}}(\mathbf{x}_{t,i}), y_{t,i}), \tag{1}$$

where $l : \mathcal{Y} \times \mathcal{Y} \to \mathbb{R}^+$ is the loss function (eg: cross-entropy loss). The goal of CL after observing the data of task $t \in \mathbb{T}$ is to learn a model $\mathbf{w}$ that performs well for all tasks $\tau = 1, 2, \ldots, t$.

A straightforward solution to the problem stated above is to optimize jointly with respect to all tasks, i.e., solve a multitask problem: $\min_{\mathbf{w}} \sum_{\tau=1}^{T} \Phi_\tau(\mathbf{w})$. The following are some roadblocks to using the multitask approach:

---

[1]Task i may correspond to some task denoted $\mathcal{T}_i$. An example scenario is that the image data sets are revealed with new tasks each time. The task could be identifying, say, a cat in the first task while in the second task a dog, and so on.

- Multitask approach requires access to all the tasks' data points. However, the memory requirement scales with the number of tasks T, and therefore becomes impractical.

- The computational complexity scales with the number of tasks.

- The data distribution for future tasks is unknown.

A naive approach to overcome the above is to minimize the loss incurred in the current task, i.e., find $\mathbf{u}_t \in \arg\min_{\mathbf{w}} \Phi_t(\mathbf{w})$, where $\mathbf{u}_t$ denotes a solution that is optimal only for the current task and ignores all past-task constraints. This leads to a phenomenon called the *catastrophic forgetting* French (1999), i.e., the loss $\Phi_\tau(\mathbf{u}_t)$ can be very large for one or more tasks with task index $\tau \in \{1, 2, \ldots, t-1\}$.

Problem Setting: To alleviate catastrophic forgetting under storage constraints, we assume access to a finite memory buffer that retains a limited number of representative samples from each previously observed task. We assume that the total memory budget is M samples. This implies that an $m = \lfloor \frac{M}{T} \rfloor$ amount of memory is allocated to each task. In practice, m points are uniformly randomly sampled from the data points of each task, i.e., the probability that a subset of samples of size m is chosen from the task t is $\frac{1}{\binom{n_t}{m}}$. We use $\hat{\Phi}_\tau(\mathbf{w})$ to denote the empirical loss incurred in the task τ using m memory samples stored by sampling task τ. We first present an *ideal* CL problem in which per-task forgetting is controlled relative to the task-wise optimal loss, yielding an algorithm-independent benchmark, as follows:

$$\begin{aligned}
\min_{\mathbf{w}} \quad & \Phi_t(\mathbf{w}) \\
\text{subject to} \quad & \hat{\Phi}_k(\mathbf{w}) - \inf_{\mathbf{v} \in \mathcal{W}} \hat{\Phi}_k(\mathbf{v}) \leq \delta', \text{ for all } k < t,
\end{aligned} \tag{2}$$

for $\delta' > 0$. In general, a very small value of δ' may turn the problem infeasible, as the subsequent task may differ significantly from the current task t. Thus, the feasibility of (2) depends jointly on task similarity, model capacity, and memory-induced estimation error; throughout, δ' is treated as an intrinsic problem parameter capturing these effects. Here, the constraints on forgetting are enforced empirically using the stored memory, which is the only accessible proxy for data from the past tasks. The above problem in general may not be feasible for any value of δ'. For example, when the loss $\Phi_t(\mathbf{w})$ or $\hat{\Phi}_t(\mathbf{w})$ changes arbitrarily across task t, one may need a large δ' to accommodate large variation of losses. On the other hand, when the losses do not change, then a fixed small δ' makes the problem feasible. Therefore, the *smallest feasible* δ' implicitly reflects the degree of regularity in how the losses of each task vary. [2] Assuming feasible δ', let $\mathbf{w}_t^*$ be the optimal solution to the above problem at task t. While the above problem is ideal, it cannot be implemented in real time since the optimal solutions in general are inaccessible in a CL setting. To overcome this, consider the following problem where at task t we aim to minimize the *average* loss while limiting the *average* forgetting:

$$\begin{aligned}
\min_{\mathbf{w}_1, \ldots, \mathbf{w}_t} \quad & \frac{1}{t} \sum_{\tau=1}^{t} \Phi_\tau(\mathbf{w}_\tau) \\
\text{subject to} \quad & \frac{1}{t-1} \sum_{k=1}^{t-1} \left(\hat{\Phi}_k(\mathbf{w}_t) - \hat{\Phi}_k(\tilde{\mathbf{w}}_{t,k}) \right) \leq \delta, \text{ for a given } \delta,
\end{aligned} \tag{3}$$

where a reference model $\tilde{\mathbf{w}}_{t,k}$ is used instead of an unattainable optimal model drawn from the trajectory of an actual algorithm, thereby making the constraints operational under memory and sequential-access limitations. The tolerance δ must exceed δ' to absorb (i) suboptimality of reference models and (ii) averaging-induced relaxation. Consequently, the constraint in (3) controls average cumulative forgetting over time rather than enforcing strict per-task feasibility at each step, and the tolerance parameter δ absorbs both the suboptimality of the reference models and temporal aggregation. Average constraints prevent a single outlier task from dominating updates while still guaranteeing asymptotic feasibility via queue stability. In this sense, (3) serves as a tractable relaxation of (2). This formulation shifts from an oracle benchmark to an algorithm-dependent one, enabling long-term stability guarantees that can be analyzed and enforced. In particular, we use (3) to

---

[2]In the sequel, we show that under some regularity conditions, there always exists a $\delta' > 0$ that results in a feasible solution to the above problem.

design an algorithm, and provide guarantees in relation with the problem in (2). Further, since the reference model is generally suboptimal for individual tasks compared to $\min_{\mathbf{v}} \hat{\Phi}_k(\mathbf{v})$, we use a different constraint δ instead of δ' in (2). As opposed to classical online learning or stochastic optimization problems, the constraint set is increasing with the number of tasks. We assume that an algorithm $\mathcal{A}$ aimed at solving (3) at task t results in a sequence of solutions $\mathbf{w}_1, \ldots, \mathbf{w}_{t-1}$. In this paper, we consider the following two reference models with respect to an algorithm $\mathcal{A}$:

1. *Case* 1: If we want the current model to perform better than the previously obtained model $\mathbf{w}_{t-1}$ from $\mathcal{A}$, then our reference model becomes $\tilde{\mathbf{w}}_{t,k} = \mathbf{w}_{t-1}$ for $k < t$ Lopez-Paz & Ranzato (2017).

2. *Case* 2: The second choice of reference model at task t is the following

$$\tilde{\mathbf{w}}_{t,k} := \underset{\mathbf{w} \in \{\mathbf{w}_1, \ldots, \mathbf{w}_{t-1}\}}{\arg \min} \hat{\Phi}_k(\mathbf{w}), \tag{4}$$

where the minimization is with respect to all the models returned by algorithm $\mathcal{A}$. Here, $k = 1, 2, \ldots, t-1$. It is important to note that $\hat{\Phi}_k(\tilde{\mathbf{w}}_{t,k}) \leq \hat{\Phi}_k(\mathbf{w}_k)$ for all k. In practice, Case 2 can be implemented using a rolling window or compressed model summaries; our analysis applies to any subset containing the empirical minimizer.

Existing memory-based approaches such as GEM and `A-GEM` rely on approximating the problem given in (3) (case 1 with $\delta = 0$) by a quadratic optimization problem, resulting in algorithms based on projections. This leads to sub-optimal performance on the current task, particularly in high-diversity cases where the true gradient lies outside the feasible region defined by memory gradients. To the best of our knowledge, `COLD` is the first-of-its-kind projection-free method to leverage a control-theoretic framework in CL that offers a principled way to quantify the balance in stability and plasticity. In the sequel, we propose the `COLD` algorithm and provide theoretical guarantees on its performance.

4 Proposed Algorithm: `COLD`

To accommodate the constraints in the optimization problem formulated in (3), we adopt the Lyapunov optimization approach, a technique commonly employed in the analysis and control of queuing systems Neely (2013). In this approach, the per-task objective is to minimize a weighted combination of the average loss on the current task and a drift term that captures constraint violations. To quantify the drift, we maintain a set of $t-1$ virtual queues after observing task $t \in \mathbb{T}$, which are updated as follows:

$$Q_k[t] = \max \left\{ Q_k[t-1] + \Delta\hat{\Phi}_k(\mathbf{w}, \tilde{\mathbf{w}}_{t,k}), 0 \right\}, \tag{5}$$

where $\Delta\hat{\Phi}_k(\mathbf{w}, \tilde{\mathbf{w}}_{t,k}) := \hat{\Phi}_k(\mathbf{w}) - \hat{\Phi}_k(\tilde{\mathbf{w}}_{t,k}) - \delta$, $k = 1, 2, \ldots, t-1$. Recall that $\tilde{\mathbf{w}}_{t,k}$ is the reference model obtained by our proposed algorithm. Further, the queues are initialized with $Q_k[0] = 0$ for all k. Here, $\mathbf{w}$ denotes the model output by the algorithm upon completing the task t that needs to be optimized. Each queue $Q_k[t]$ acts similar to that of a Lagrange multiplier that adaptively penalizes forgetting on task k. Lagrange multipliers are typically updated using dual descent, while the queue updates are simple and cheaper. These virtual queues track the degree of constraint violation where a large value of $Q_k[t]$ for some $k < t$ indicates significant forgetting on the task k. Therefore, keeping these queues stable by ensuring that their values remain small leads to the mitigation of catastrophic forgetting and promotes satisfaction of the average constraint over the tasks. Towards analyzing this, consider the following Lyapunov function

$$\mathcal{L}_{\mathbf{w}_t}[t] := \frac{1}{2(t-1)} \sum_{k=1}^{t-1} Q_k^2[t], \tag{6}$$

where $\mathbf{w}_t$ is the model obtained by algorithm $\mathcal{A}$ at task t. The Lyapunov function encapsulates all the constraints into one function. We adapt the following intial condition: $\mathcal{L}_{\mathbf{w}_0}[0] = \mathcal{L}_{\mathbf{w}_1}[1] = 0$. The Lyapunov drift at task t can be written as Neely & Huang (2010)

$$\Delta\mathcal{L}[t] := \mathcal{L}_{\mathbf{w}_t}[t] - \mathcal{L}_{\mathbf{w}_{t-1}}[t-1]. \tag{7}$$

The DPP algorithm minimizes a weighted sum of the current task loss and the Lyapunov drift, thereby balancing long-term constraint satisfaction with immediate performance. Mathematically, for each task t we have

$$\texttt{DPP-Problem:} \inf_{\mathbf{w}} \left[V\Phi_t(\mathbf{w}) + \Delta\mathcal{L}[t] \right], \tag{8}$$

where $V > 0$ is the parameter of the algorithm that trades off the current loss and the drift from the learning from previous tasks (forgetting). Unfortunately, the drift term in the above optimization problem is difficult to handle. An approach followed in the literature is to use an upper bound on the drift as derived in the following lemma.

Lemma 1. *The drift at task t using model $\mathbf{w}$ is bounded as*

$$\Delta\mathcal{L}[t] \leq \Delta_t(\mathbf{w}, \mathbf{w}_{t,ref}) + \sum_{k=1}^{t-1} Q_k[t-1]\Delta\hat{\Phi}_k(\mathbf{w}, \tilde{\mathbf{w}}_{t,k}),$$

where $\Delta_t(\mathbf{w}, \mathbf{w}_{t,ref}) := \frac{1}{2(t-1)}\sum_{k=1}^{t-1}(\Delta\hat{\Phi}_k(\mathbf{w}, \tilde{\mathbf{w}}_{t,k}))^2$, $\Delta\hat{\Phi}_k(\mathbf{w}, \tilde{\mathbf{w}}_{t,k}) := \hat{\Phi}_k(\mathbf{w}) - \hat{\Phi}_k(\tilde{\mathbf{w}}_{t,k}) - \delta$, and $\mathbf{w}_{t,ref} := (\tilde{\mathbf{w}}_{t,1}, \ldots, \tilde{\mathbf{w}}_{t,t-1})$ is the vector of reference models.

Proof: See Supplementary Material.
Unlike the classical DPP approach, we have retained the first term in its data-dependent form, $\Delta_t(\mathbf{w}, \mathbf{w}_{t,\text{ref}})$ which directly reflects the empirical variation induced by the current model relative to the reference models. This refinement yields a tighter characterization of the drift, allowing our theoretical guarantees to provide a better insight into the effect of variation of the models across tasks. In the proposed algorithm, we solve the following problem

$$\mathbf{w}_t \in \arg\inf_{\mathbf{w}} \left\{ \texttt{DPP}_{V,t}(\mathbf{w}) := V\Phi_t(\mathbf{w}) + \sum_{k=1}^{t-1} Q_k[t-1]\Delta\hat{\Phi}_k(\mathbf{w}, \tilde{\mathbf{w}}_{t,k}) \right\}. \tag{9}$$

Our method is presented in Algorithm 1.

Algorithm 1 COntinual Learning DPP (COLD)

1: **Initialize:** $Q_1[0] = 0$, random initialization of $\mathbf{w}_0$, $\delta \geq 0$, and $V > 0$.
2: **for** $t = 1, 2, \ldots, T$ **do**
3:     Receive data of task t.
4:     Sample a batch $\mathcal{B}_{t-1}$ from previous tasks with $|\mathcal{B}_{t-1}| = m$.
5:     Obtain reference models (Case 1) $\tilde{\mathbf{w}}_{t,k} = \mathbf{w}_{t-1}$ or (Case 2) $\tilde{\mathbf{w}}_{t,k}$ by solving (4).
6:     **DPP step:** Solve (9) to obtain $\mathbf{w}_t$.
7: **end for**

The proposed algorithm in Table 1 requires a solution to (9); a stationary solution can obtained by using Gradient Descent (GD) approach. Our first set of theoretical results assumes an optimal solution for (9). Later, we extend our results to a more practical GD approach.

5 Performance Analysis of the COLD Algorithm

In this section, we present first set of theoretical results. We make the following standard assumptions on the loss function.

Assumption 1. *(Smoothness) The loss functions $\Phi_t(\mathbf{w})$ and $\hat{\Phi}_t(\mathbf{w})$ are assumed to be L and l smooth, respectively. Mathematically, $\forall \mathbf{w}, \mathbf{u} \in \mathcal{W}$ and $\forall t$*

$$\Phi_t(\mathbf{w}) \leq \Phi_t(\mathbf{u}) + \langle \mathbf{w} - \mathbf{u}, \nabla\Phi_t(\mathbf{u}) \rangle + \frac{L}{2}||\mathbf{w} - \mathbf{u}||^2, \tag{10}$$

and L replaced by l for $\hat{\Phi}_t(\mathbf{w})$.

In Step 6 of the `COLD` algorithm (Algorithm 1), we assume that the optimization problem is solved exactly, yielding an optimal solution denoted by $\mathbf{w}_t$. Next, we present the main results of the paper that characterizes the optimality gap and the average queue size.

Theorem 1. *Given Assumption 1, the `COLD` algorithm (with Case 1 or Case 2) leads to the following performance bound*

$$\frac{1}{T}\sum_{t=1}^{T}[\Phi_t(\mathbf{w}_t) - \Phi_t(\mathbf{w}_t^*)] \quad \leq \quad \frac{1}{VT}\sum_{t=1}^{T}\Delta_t(\mathbf{w}_t, \mathbf{w}_{t,ref}), \tag{11}$$

where $\mathbf{w}_t^*$ is an optimal solution of (2) with $\delta' < \delta$.

The left-hand side above corresponds to the loss difference between the proposed algorithm and the optimal solution obtained by solving (2)–the ideal CL problem. The above upper bound captures the effectiveness of the algorithm. Note that the constraint is governed by the difference between the model obtained by the algorithm and the reference model, i.e., $\mathbf{w}_t$ and $\tilde{\mathbf{w}}_{t,k}$, $t \in \mathbb{T}$. The latter is captured through $\Delta_t(\mathbf{v}, \mathbf{u})$, as defined in Lemma 1. This appears in the the upper bound, which reflects the algorithm-dependent error arising from constraint handling, and hence, it can be evaluated using the iterates $\{\mathbf{w}_t\}$ produced by the `COLD` algorithm. Further, it is easy to show that if $\Delta_t(\mathbf{w}_t, \mathbf{w}_{t,\text{ref}})$ is bounded (well regularized algorithmic updates), then $\frac{1}{T}\sum_{t=1}^{T}\Delta_t(\mathbf{w}_t, \mathbf{w}_{t,\text{ref}})$ is bounded, and hence the upper scales as $\mathcal{O}(1/V)$. Therefore, if V is large, then the upper bound reduces, leading to a better performance guarantee, as expected. However, we expect that larger V results in higher forgetting, leading to a trade-off. This is the essence of our next result on the constraint quantification (or queue stability analysis as in stochastic optimization). Towards stating the result, we need the following definition.

Definition 1. *Let $f_t(\mathbf{w})$ and $g_t(\mathbf{w})$, $t = 1, 2, \ldots, T$ be two sequences of functions. The loss variation at t is defined as follows:*

$$D_{f,g}[T] := \frac{1}{T}\sum_{t=1}^{T}\sup_{\mathbf{w}}|f_t(\mathbf{w}) - g_{t-1}(\mathbf{w})|. \tag{12}$$

Similarly, for a fixed sequence $f_t(\mathbf{w})$, we define $D_f[T] := \frac{1}{T}\sum_{t=1}^{T}\sup_{\mathbf{w}}|f_t(\mathbf{w}) - f_{t-1}(\mathbf{w})|$.

The above definition is used to capture how the loss functions change between consecutive tasks, uniformly over the parameter space. While the above definition uses a uniform bound for analytical clarity, in practice it suffices that the deviation is bounded over the sequence $\{\mathbf{w}_t\}$. Next, we present a bound on the average queue size.

Theorem 2. *Given Assumption 1, the `COLD` algorithm (Case 1 or Case 2) with output $\mathbf{w}_t$, $t \in \mathbb{T}$ leads to the following average queue bound*

$$\frac{1}{T}\sum_{t=1}^{T}\bar{Q}[t-1] \quad \leq \quad \frac{V\delta'}{(\delta-\delta')} + \frac{1}{T(\delta-\delta')}\sum_{t=1}^{T}\Delta_t(\mathbf{w}_t, \mathbf{w}_{t,ref}) + \frac{2VD_{\Phi,\hat{\Phi}}[T]}{(\delta-\delta')}, \tag{13}$$

where $\delta > \delta'$, $\bar{Q}[t-1] := \frac{1}{t-1}\sum_{k=1}^{t-1}Q_k[t-1]$, and $D_{\Phi,\hat{\Phi}}[T] = \frac{1}{T}\sum_{t=1}^{T}\sup_{\mathbf{w}}|\Phi_t(\mathbf{w}) - \hat{\Phi}_{t-1}(\mathbf{w})|$.

First, note that the stability of the average queue length (boundedness) implies an asymptotic qualification of average constraint (see Neely & Huang (2010)). Hence, a bounded average queue size leads to good forgetting behavior. The bound in Theorem 4 admits a clear interpretation in terms of three distinct factors. The term $\frac{V\delta'}{\delta-\delta'}$ captures the *inherent difficulty of the CL problem*, reflecting task similarity and the tightness of the ideal feasibility tolerance. The cumulative deviation term $D_{\Phi,\hat{\Phi}}[T]$ quantifies *memory quality*, measuring how accurately the empirical loss approximates the true task losses across time. Finally, the drift term $\Delta_t(\cdot)$ represents *algorithmic smoothness*, encoding how aggressively the model parameters evolve between successive tasks. Together, these terms highlight the trade-off between problem hardness, memory fidelity, and update regularity in controlling long-term forgetting. The above result reveals that an average queue length scales as $\mathcal{O}(V)$ leading to a $\mathcal{O}(1/V)$ versus $\mathcal{O}(V)$ tradeoff between performance (Theorem 1) and the average queue size (Theorem 2). Further, the bound depends on $D_{\Phi,\hat{\Phi}}[T]$, which measures how the loss function obtained

from the entire data set differs from the empirical loss obtained using the replay buffer in addition to the task variaton. In other words, larger memory size with similar data across tasks implies lower deviation, leading to a lower average queue length.

Note: An alternative metric commonly used in the CL literature evaluates performance via $\frac{1}{T}\sum_{t=1}^{T}\Phi_t(\mathbf{w}_T)$ and forgetting via $F_t := \frac{1}{t-1}\sum_{k=1}^{t-1}\left(\hat{\Phi}_k(\mathbf{w}_t) - \hat{\Phi}_k(\mathbf{w}_k)\right)$ (see Lin et al. (2023)). The metric adapted in Lin et al. (2023) captures forgetting through accuracy degradation on past tasks; it is an endpoint-based measure. It does not capture how forgetting accumulates or is controlled during learning, which is exactly what our queue-based metric is designed to do. In particular, our queue-based metric captures the temporal evolution of forgetting by penalizing sustained violations during learning. As a result, the two metrics are related but not equivalent. Further, our metric is more amenable to analysis with a particular emphasis on the tradeoff between stability and plasticity. We believe that our apporach provides further control and insights on the performance, complementing the existing work.

The exact minimization assumption in Theorems 1–2 follows the standard oracle model (for general non-convex losses) used in drift-plus-penalty analysis. These results characterize the intrinsic stability–optimality trade-off of the proposed formulation. In the next section, analyze gradient-based approximate optimization under smooth nonconvex assumptions, aligning the theory with practical deep learning settings.

6   Gradient-based Optimization for `COLD`

In the previous section, we provided theoretical guarantees on the performance of the `COLD` algorithm, demonstrating the trade-off between accuracy and constraint violation. In this section, we translate the DPP problem into an easily implementable iterative algorithm where a fixed learning rate and V are used to achieve a good stationary point of the loss function in the current task and a lower forgetting. Towards solving (9), we use the following GD update on each task:

$$\mathbf{w}_{t+1} = \mathbf{w}_t - \eta\left(V\nabla\Phi_t(\mathbf{w}_t) + \sum_{k=1}^{t-1}Q_k[t-1]\nabla\hat{\Phi}_k(\mathbf{w}_t)\right), \tag{14}$$

where η is a fixed learning rate, and the queue $Q_k[t-1]$ is obtained from the queue update in (5). In general, the convergence of GD updates depends on the learning rate through the smoothness constant of the function Orabona (2019). In our case, this corresponds to the smoothness of the $\mathtt{DPP}_{V,t}(\mathbf{w})$ function, which is provided in the following lemma.

Lemma 2. *The function* $\mathtt{DPP}_{V,t}(\mathbf{w})$ *is* $\alpha_t := VL + \frac{l}{t-1}\sum_{k=1}^{t-1}Q_k[t-1]$-*smooth.*

Proof: First, note that $\Phi_t(\mathbf{w})$ is L smooth and $\Delta\hat{\Phi}_k(\mathbf{w}, \mathbf{w}_{t-1})$ is l smooth. The proof follows from the fact that the sum of smooth functions is smooth, with a smoothness constant being the sum. $\qquad\square$

Next, we present the performance guarantees in terms of a bound on the average gradient when the domain $\mathcal{W}$ is compact with radius $r > 0$.[3]

Theorem 3. *Suppose Assumption 1 holds, and a fixed learning rate* $\eta \le 1/2\alpha_t$ *for all* t *is chosen. Then* $\mathbf{w}_t$ *obtained from (14) with* $\tilde{\mathbf{w}}_{t,k}$ *chosen according to Case 1 or Case 2 results in*

$$\frac{1}{T}\sum_{t=1}^{T}||\nabla\Phi_t(\mathbf{w}_t)||^2 \le \frac{2\Phi_1(\mathbf{w}_1)}{TV\eta} + \frac{2D_\Phi[T]}{\eta V} + \frac{lr^2}{TV}\sum_{t=1}^{T}\rho_{t,-} + \frac{r^2l}{\eta TV^2}\sum_{t=1}^{T}\bar{Q}[t-1], \tag{15}$$

where $\rho_{t,-} := -\sum_{k=1}^{t-1}\rho_{t,k}\mathbf{1}\{\rho_{t,k}\le 0\}$, $\rho_{t,k} := \inf_{\mathbf{w}\in\mathcal{W}}\langle\nabla\Phi_t(\mathbf{w}), \nabla\hat{\Phi}_k(\mathbf{w})\rangle$, *and* $D_\Phi[t]$ *is as given in Definition 1.*

The above result holds good for both reference models in Case 1 and Case 2. The last term corresponding to the queue average depends on the reference model used. The third term depends on the negative correlation,

---

[3]The compactness assumption is quite common in the literature on stochastic optimization and online learning (see Neely & Huang (2010)). Moreover, it is well known from the NTK analysis that SGD/GD updates of a deep neural network do not move out of a ball of a certain bounded radius Liu et al. (2022); Chizat & Bach (2019) making our results widely applicable.

which measures the gradient correlation across tasks. Further, the bound also reveals that using larger η is beneficial. However, the choice of η is limited by the constraint $\eta \leq 1/2\alpha_t$. Later, we provide more insights on the effect of this on the overall performance. In the following, we provide a bound on the average queue for case 1 with step 6 of the COLD algorithm replaced by the GD update in (14). We use the following results to provide further insights into both forgetting and the average gradient performance of the GD update

Theorem 4. *The* COLD *algorithm with GD updates using the reference model in Case* 1 *results in* $\frac{1}{t-1}\sum_{k=1}^{t-1} Q_k[t-1] = \mathcal{O}(V)$, *and the following average queue bound*

$$\frac{1}{T}\sum_{t=1}^{T}\bar{Q}[t-1] \quad \leq \quad \frac{VD_\Phi[T]}{\delta} + \frac{1}{T\delta}\sum_{t=1}^{T}\Delta_t(\mathbf{w}_t, \mathbf{w}_{t-1}), \tag{16}$$

where $\bar{Q}[t-1]$ is as defined in Theorem 2.

Substituting the bound on the queue in Theorem 4 in the result of Theorem 3, we get the following corollary.

Corollary 1. *Suppose Assumption 1 holds with compact $\mathcal{W}$, and a fixed learning rate $\eta \leq 1/2\alpha_t$ for all t is chosen. Then for $\mathbf{w}_t$ updates according to (14) with $\tilde{\mathbf{w}}_{t,k} = \mathbf{w}_{t-1}$ as in case 1, we have*

$$\frac{1}{T}\sum_{t=1}^{T}||\nabla\Phi_t(\mathbf{w}_t)||^2 \leq \frac{2\Phi_1(\mathbf{w}_1)}{TV\eta} + \frac{D_\Phi[T]}{\eta V}\left(2 + \frac{r^2l}{V\delta}\right) + \frac{lr^2}{TV}\sum_{t=1}^{T}\rho_{t,-} + \frac{r^2l}{\delta\eta TV^2}\sum_{t=1}^{T}\Delta_t(\mathbf{w}_t, \mathbf{w}_{t-1}),$$

where $\rho_{t,-} := -\sum_{k=1}^{t-1}\rho_{t,k}\mathbf{1}\{\rho_{t,k} \leq 0\}$.

In the above corollary, the term $\rho_{t,-}$ quantifies intrinsic task interference through negative gradient alignment between past and current tasks, indicating regimes in which forgetting is unavoidable. This gradient correlation is a fundamental quantity in CL, as it captures how learning on the current task perturbs representations learned for previous tasks. As mentioned in 1, projection-based methods such as GEM and A-GEM explicitly exploit this correlation by constraining updates to lie in the subspace where gradients of past and current tasks are non-negatively aligned, leading to mitigating the instantaneous interference. However, while correcting locally conflicting updates only leads to myopic improvements, our analysis highlights that $\rho_{t,-}$ is a sustained negative alignment across tasks leads to cumulative forgetting, motivating the proposed queue-based control formulations that regulate interference over time rather than per step. Our analysis demonstrates that sustained negative alignment increases the virtual queue and is therefore penalized over time, ensuring that task interference captured by $\rho_{t,-}$ is accounted for at the level of long-term stability rather than instantaneous updates. It is also important to note that for a a fixed η, there is an inherent V and $1/V$ tradeoff between queue stability and performance, which is not an artifact of the optimization approach. The above corollary requires $\eta \leq 1/2\alpha_t$ for all t. Towards ensuring this, we use the following bound on α_t for our choice of η:

$$\alpha_t = VL + \frac{l}{t-1}\sum_{k=1}^{t-1}Q_k[t-1] \overset{(a)}{\leq} VL + \mathcal{O}(V) = \mathcal{O}(V) \tag{17}$$

where (a) follows from the first queue bound in Theorem 4. Using $\eta = \mathcal{O}(1/V)$ in the above corollary, and the queue bound for case 1, we get the following trade-off.

Corollary 2. *Suppose Assumption 1 holds with compact $\mathcal{W}$, and a fixed learning rate $\eta = \mathcal{O}\left(\frac{1}{V}\right)$ is chosen. Then for $\mathbf{w}_t$ updates according to (14) with $\tilde{\mathbf{w}}_{t,k} = \mathbf{w}_{t-1}$ as in case 1, we have*

$$\frac{1}{T}\sum_{t=1}^{T}||\nabla\Phi_t(\mathbf{w}_t)||^2 \quad \leq \quad \mathcal{O}\left(\frac{1}{T} + D_\Phi[T] + \frac{\bar{\rho}}{V} + \frac{\bar{\Delta}}{\delta V}\right), \tag{18}$$

where $\bar{\rho} := \frac{1}{T}\sum_{t=1}^{T}\rho_{t,-}$, $\bar{\Delta} := \frac{1}{T}\sum_{t=1}^{T}\delta_t(\mathbf{w}_t, \mathbf{w}_{t-1})$, and $\delta > \delta'$. The corresponding queue bound is

$$\frac{1}{T}\sum_{t=1}^{T}\bar{Q}[t-1] \quad \leq \quad \mathcal{O}\left(\frac{VD_\Phi[T]}{\delta}\right). \tag{19}$$

Even with one step GD, the above corollary reveals the V versus $1/V$ tradeoff between the average gradient squared and the average queue. Further, when the term $D_\Phi[T]$ is negligible, then larger number of tasks T ensures a smaller gradient average while keeping the queue bounded. The proposed algorithm employs a single step of GD, which results in task variation dominating both the performance guarantee and the average queue bound. We conjecture that performing multiple GD steps per task could mitigate the impact of variation; investigating this extension is left for future work. Next, we show that bounded average queue above implies asymptotic satisfaction of the constraints.

Bounded average queue: Suppose $\frac{1}{T}\sum_{t=1}^{T}\bar{Q}[t-1] < \infty$ for all T, then the term $\bar{Q}[t-1] < \infty$ for infinitely many t. Since $\bar{Q}[t-1] = \frac{1}{t-1}\sum_{k=1}^{t-1}Q_k[t-1]$, it follows that $Q_k[t-1] < \infty$ for infinitely many t. Note that $Q_k[t-1] \geq Q_k[t-2] + \hat{\Phi}_k(\mathbf{w}_t) - \hat{\Phi}_k(\mathbf{w}_{t-1})$, which implies that $\frac{1}{t-1}\sum_{k=1}^{t-1}(\hat{\Phi}_k(\mathbf{w}_t) - \hat{\Phi}_k(\mathbf{w}_{t-1}) - \delta) \leq \frac{Q_k[t-1]}{t-1} = \mathcal{O}\left(\frac{1}{t-1}\right)$ for infinitely many t. Thus, for larger values of t, the average constraint is satisfied approximately (except for the $1/(t-1)$ factor) for infinitely many t.

7 Experimental Results and Discussions

In this section, we present the experimental results to corroborate our theory and demonstrate the efficacy of the proposed `COLD` (*Case* 2) and `COLD-Eff`(*Case* 1) algorithms on standard benchmark datasets in the task-incremental learning setup.

Figure 1: **Left:** Average gradient squared versus V in log-log scale. The variation is linear. **Center:** Average queue size versus V in the linear scale. **Right:** Gradient squared versus task t.

Figure 2: Average gradient squared versus V in the log-log scale demonstrating the effect of η.

Figure 3: Average norm square gradient and $\bar{\Delta}$ versus V for `COLD-Eff` on Split-MNIST data set.

7.1 Theoretical Validation

To validate the theoretical result in Corollary 1, we analyze a controlled toy model with a quadratic loss under two regimes of task variation (low and high). In particular, we consider T CL tasks in $\mathbb{R}^d$, where each task t is defined by the quadratic objective $\Phi_t(\mathbf{w}) = \frac{1}{2}\|\mathbf{w} - \mathbf{w}_t^*\|^2$. In the following, we explain the two regimes in detail.

Low Task Variation (Near-IID, LOW): In this regime, tasks share a common optimum with small perturbations: $\mathbf{w}_t^* = \mathbf{w}_{\text{base}}^* + \varepsilon_t$, where $\mathbf{w}_{\text{base}}^* \sim \mathcal{N}(\mathbf{0}, c_1\mathbf{I}_d)$ and $\varepsilon_t \sim \mathcal{N}(\mathbf{0}, c_2\mathbf{I}_d)$. Here, we choose $c_1 = 0.09$

and $c_2 = 0.0004$, which yields $D_\Phi[T] \approx 0.02$.[4]

High Task Variation (Non-IID with Drift, HIGH): In this regime, the tasks drift linearly along a random direction with additional noise. More precisely, $\mathbf{w}_t^* = \mathbf{w}_{\text{base}}^* + \frac{t}{T} \cdot 0.8 \cdot \mathbf{v} + \boldsymbol{\xi}_t$, where $\mathbf{w}_{\text{base}}^* \sim \mathcal{N}(\mathbf{0}, c_1 \mathbf{I}_d)$, $\boldsymbol{\xi}_t \sim \mathcal{N}(\mathbf{0}, c_2 \mathbf{I}_d)$ and $\mathbf{v} \sim \mathcal{N}(\mathbf{0}, \mathbf{I}_d)$ is normalized to get $\mathbf{v} \leftarrow \mathbf{v}/\|\mathbf{v}\|$. Here, we choose, $c_1 = 0.09$ and $c_2 = 0.0064$, which yields $D_\Phi[T] \approx 0.08$. Both regimes use $d = 25$ and $T = 150$ tasks.

The task variation $D_\Phi[T]$ is measured empirically using Definition 1. The above settings imply $\hat{\Phi}_t(\mathbf{w}) = \Phi_t(\mathbf{w})$ for all $t \in [T]$ as the above toy example does not require replay buffer. To validate the proposed theoretical results, we have fixed $\eta = 4 \times 10^{-4}$, and $\delta = 4 \times 10^{-7}$, and ran the COLD algorithm with 3 GD steps per task.[5] The Fig. 1 (**Left**) shows a plot of the average gradient square versus V in the log-scale. From Corollary 1, as V increases, the average gradient squared scales down as $1/V$, i.e., it decreases linearly in the log scale, as depicted in the figure. Further, the figure also demonstrates that higher variation results in a lower slope, as predicted by our theory. The second figure (**Center**) shows the plot of the average queue size versus V in the linear scale. We observe that the average queue size increases linearly with V, and the slope increases with the variation, this is inline with our theoretical prediction. The third figure (**Right**) shows a plot of the gradient squared versus t. For larger t, the gradient is saturating due to the residual variation term. In particular, larger V is saturating fast while $V = 50$ requiring a greater number of tasks to saturate, as suggested by our result. The first two figures illustrate the canonical $\mathcal{O}(1/V)$–$\mathcal{O}(V)$ tradeoff, making explicit that no single choice of V is uniformly optimal: larger values favor stability at the expense of plasticity, while smaller values induce the opposite behavior. Crucially, our objective is not to design or optimize V. In the DPP framework, V is an externally specified control parameter that encodes the desired stability–plasticity operating point dictated by the application, as in the classical DPP framework Neely et al. (2012). Once this requirement is fixed, an appropriate V can be selected using standard empirical tuning procedures, which is orthogonal to the theoretical contributions of this work. Our theory assumes $\eta \le \frac{1}{2\alpha_t} = \mathcal{O}\left(\frac{1}{V}\right)$. For a fixed η, increasing V beyond a threshold violates the condition, resulting in an increased gradient. This is demonstrated in Fig. 2, where the average gradient squared increases beyond $V = 200$. Finally, we demonstrate in Fig. 3 that large variations (non-iid) decrease the rate of convergence of the average gradient squared compared to small variations (iid) even in the practical setting with non-convex loss using Split-MNIST Deng (2012) data set. In particular, we depict the average gradient squared for the near-IID (LOW) and non-IID (HIGH) settings, along with $\bar{\Delta}$, which is the residual term in the convergence bound measuring the average error incurred due to the algorithm updating the model before fully aligning with the current task optimum. We observe that both quantities, the average gradient squared and the average algorithmic error, exhibit consistent trends: under high task variation, both remain elevated, whereas in the near-IID regime they decrease and stabilize at lower values.

Figure 4: Baseline comparison: average accuracy and forgetting versus tasks on Split-CIFAR100.

7.2 Empirical Evaluations

In this subsection, we carry out extensive empirical evaluation and present comparisons with relevant baselines and ablation studies on well-known CL benchmarks. Specifically, we examine the following aspects in practical settings: (a) How well does the proposed technique perform as compared to the baselines? (b) Trade-off in V, (c) Stability of the queue, and (d) factors that affect plasticity.

---

[4]A closed-form expression for $D_\Phi[T]$ can easily be obtained in the case of quadratic loss.
[5]This can be reduced to 1 without changing the trend.

Table 1: Performance comparison on benchmark datasets under different memory buffer sizes (M). Standard deviation values are provided in the supplementary. '–' denotes not applicable, as forgetting is not defined for GDumb due to its training strategy Prabhu et al. (2020).

Method	Split-CIFAR10				Split-CIFAR100				Split-TinyImageNet			
	$M = 0.6$k		$M = 1$k		$M = 1$k		$M = 5$k		$M = 2$k		$M = 5$k	
	ACC(%)	F	ACC(%)	F	ACC(%)	F	ACC(%)	F	ACC(%)	F	ACC(%)	F
Fine-tune	76.70	0.22	76.70	0.22	29.86	0.54	29.86	0.54	16.59	0.44	16.59	0.44
EWC(2017)	71.05	0.35	71.05	0.35	35.00	0.17	35.00	0.17	24.12	0.12	24.12	0.12
A-GEM(2018)	83.75	0.42	83.81	0.43	63.59	0.30	69.82	0.33	51.11	0.23	53.43	0.25
MER(2019)	77.32	0.04	76.91	0.02	47.35	0.05	49.68	0.05	34.89	0.05	53.76	0.01
GDumb(2020)	64.68	–	63.01	–	37.56	–	51.42	–	21.00	–	57.34	–
DER(2020)	83.66	0.05	85.05	0.04	50.27	0.22	48.31	0.24	28.22	0.20	30.58	0.18
DER++(2020)	84.84	0.03	85.80	0.03	66.96	0.07	71.67	0.04	56.19	0.05	58.88	0.04
ER-ACE(2022)	82.70	0.03	86.11	0.02	64.97	0.05	70.14	0.04	51.37	0.07	55.67	0.05
CBA(2023)	85.01	0.02	84.53	0.01	63.70	0.03	73.75	0.02	55.92	0.04	58.92	0.03
NCCL(2023)	72.99	0.25	71.90	0.24	29.20	0.54	50.79	0.35	19.64	0.44	30.15	0.33
REFRESH(2024)	84.93	0.03	85.87	0.03	67.34	0.06	70.84	0.04	56.68	0.06	60.08	0.03
COLD-Eff (Ours)	84.90	0.07	85.90	0.09	**68.03**	0.10	74.56	0.05	55.09	0.10	61.39	0.07
COLD (Ours)	**85.68**	0.06	**87.94**	0.05	67.38	0.18	**75.64**	0.05	**56.74**	0.08	62.21	0.02

7.2.1 Experimental Setup

Datasets: We demonstrate the experimental results on CL benchmarks such as Split-CIFAR10, Split-CIFAR100 Krizhevsky & Hinton (2009), and Split-TinyImageNet Le & Yang (2015) to evaluate the task-incremental setting with disjoint class splits and known task identities. Details of the datasets are provided in the Supplementary Material. We also evaluate on Permuted-MNIST (PMNIST) to study the domain-incremental setting, where tasks share the same label space while the input distributions differ across tasks; results are reported in the supplementary material.

Architecture: We use the following architectures depending on the dataset: (a) Split-MNIST: an MLP with a single hidden layer of 256 units and a task-specific multi-head output; (b) Split-CIFAR10, Split-CIFAR100, and Split-TinyImageNet: a standard ResNet-18 with a task-specific multi-head classifier; and (c) PMNIST: a two-layer fully connected network with 256 units in each layer using a single shared output head across tasks.

Metrics: We assess the performance of the proposed algorithms using the model's test accuracy on a sequence of T tasks, and the forgetting, which are defined below: (a) **Average Accuracy** (ACC $\in [0, 1]$): The average accuracy is computed using ACC $:= \frac{1}{T} \sum_{j=1}^{T} a_{T,j}$, where $a_{t,j}$ is the accuracy of the model obtained after observing task t on task $j < t$. (b) **Forgetting:** We capture the forgetting factor using F $:= \frac{1}{T-1} \sum_{j=1}^{T-1} \left[\max_{l \in [T-1]}(a_{l,j} - a_{T,j}) \right]$, where the difference $\max_{l \in [T-1]}(a_{l,j} - a_{T,j})$ captures the extent to which previously learned knowledge is overwritten by subsequent learning. Experiments are carried out on 3 multiple runs with a fixed set of random seeds. We report the mean and standard deviation ($\pm$) across these runs in the supplementary material.

7.2.2 Comparison with Baselines

We evaluate the proposed COLD and COLD-Eff methods against a broad and representative set of CL baselines encompassing regularization-based, replay-based, and optimization-based approaches. Specifically, we compare against: (a) Fine-tune; (b) EWC Kirkpatrick et al. (2017); (c) A-GEM Chaudhry et al. (2018); (d) NCCL Han et al. (2023); (e) MER Riemer et al. (2019); (f) GDumb Prabhu et al. (2020); (g) DER and DER++ Buzzega et al. (2020); (i) ER-ACE Caccia et al. (2021); (j) CBA Wang et al. (2023); and (k) REFRESH Wang et al. (2024). Detailed descriptions of all baselines are provided in the supplementary material.

From Table 1, we observe that COLD consistently achieves the highest average accuracy across all benchmark datasets and memory budgets, while COLD-Eff attains the second-best accuracy in most settings. This demonstrates that the proposed framework is particularly effective at preserving task-relevant knowledge as the number of tasks grows. Importantly, while the forgetting values of COLD and COLD-Eff are sometimes

marginally higher than those of strongly stability-biased methods, they remain well-controlled and competitive across all benchmarks. This behavior is expected, since the proposed methods place greater emphasis on plasticity and forward transfer, leading to improved final-task performance and overall accuracy at the cost of increased forgetting. In contrast, several baselines achieve lower forgetting primarily by constraining updates aggressively, which often leads to substantially degraded accuracy. Our results highlight that minimizing forgetting alone is insufficient; maintaining high predictive performance across tasks is equally critical.

Consistent trends are also observed in Fig. 4, where the proposed methods outperform competing approaches as learning progresses. Regularization-based methods such as `EWC` exhibit limited forgetting but suffer from poor accuracy, while optimization-based methods such as `NCCL` degrade rapidly as the number of tasks increases. Replay-based approaches, including recent plug-in methods such as `CBA` and `REFRESH`, improve performance but remain consistently inferior to `COLD`, despite their reliance on enhanced replay mechanisms.

Overall, these results demonstrate that `COLD` and `COLD-Eff` achieve a more favorable accuracy–forgetting tradeoff, delivering state-of-the-art accuracy with stable and controlled forgetting, particularly in long task sequences where plasticity is essential.

7.2.3 Ablation and Sensitivity Analysis

We next examine the impact of varying the memory buffer size $|\mathcal{M}|$, the number of epochs per task, the number of tasks, the parameters δ and V on the resulting accuracy-forgetting trade-offs and queue stability. Each experiment in the following section is presented on a representative dataset, while corresponding results on additional datasets are deferred to the supplementary material.

Figure 5: **Left:** Effect of M **Center and Right:** Trade-off Between Average Accuracy and Forgetting using `COLD` and `COLD-Eff` Algorithms with varying V, all on Split-CIFAR100 Dataset.

Varying memory buffer size (M): We analyze the effect of varying the total memory size M by varying memory samples per task in the proposed algorithms, ranging from 50 to 500 samples per task. We observe from Fig. 5 (**Left**) that for Split-CIFAR100, as the sampling size increases, there is an improvement in average accuracy (line plot) and a decrease in forgetting (bar plot). We see a similar trend for both `COLD` and `COLD-Eff` algorithms across all datasets (see supplementary).

Accuracy versus Forgetting - Varying V: Recall that V balances the trade-off between average accuracy and forgetting. In Fig. 5 (**Center** and **Right**), we study this trade-off by varying V from 1 to 10^5 on both the proposed algorithms. Evidently $V = 10^2$ provides better average accuracy but lower forgetting for the Split-CIFAR100 dataset. In contrast, $V = 1$ leads to the least forgetting, but results in poor average accuracy. Hence, V can be used as a tuning parameter to achieve the desired requirements in CL. It can also be noted that `COLD` benefits from a balanced stability–plasticity trade-off and demonstrates stable results across tasks even when V is large.

Varying δ-parameter: Fig. 6 (**Left**) examines the effect of the hyperparameter δ, which controls the tightness of the constraint in the optimization problem in (3). In principle, $\delta = 0$ enforces a strict constraint, while larger values of δ correspond to progressively relaxed constraints. Empirically, however, we observe that larger values (e.g., $\delta = 10$) result in degraded performance in terms of both average accuracy and forgetting for `COLD` and `COLD-Eff`, compared to smaller δ. At first glance, this may appear counter-intuitive. This behavior can be attributed to the fact that our theoretical guarantees are derived with respect to

the queue-based notions of accuracy and forgetting, whereas the experimental metrics employ a different operational definition. Consequently, excessive relaxation of the constraint weakens the effective control exerted by the DPP mechanism under the empirical metrics, leading to poorer observed performance.

Figure 6: **Left:** Varying δ-parameter using `COLD` and `COLD-Eff` algorithms on Split-TinyImageNet. **Center and Right:** Scalability of `COLD` and `COLD-Eff` with increasing number of tasks on Split-CIFAR100.

Impact of T: In this experiment, we investigate how well the CL method scales with the number of tasks T-this helps us to understand the model's ability to retain earlier knowledge while learning new tasks. From Fig. 6 (**Center** and **Right**), we observe that `COLD` (**center**) remains stable with respect to both accuracy and forgetting even as the number of tasks increases. We see a similar trend using the `COLD-Eff` (**right**) algorithm, but with a less stable performance across tasks.

Figure 7: Virtual Queue for varying V on Split-CIFAR100 using **Left:** `COLD` and **Right:** `COLD-Eff`.

Queue Stability Analysis: In Fig. 7, we validate the empirical queue stability of `COLD` and `COLD-Eff` by observing that a smaller $V = 1$ leads to smaller queue values, and vice versa for $V = 10^2$ and $V = 10^4$. This implies that using $V = 10^2$ balances the model updates on both current and past data. In contrast, $V = 10^4$ places high weight on the current data, which destabilizes the queue and leads to greater catastrophic forgetting, as also observed in Fig. 5. While both methods exhibit similar qualitative trends with respect to V, `COLD-Eff` consistently maintains lower queue values than `COLD`. This behavior can be attributed to the choice of reference model: `COLD-Eff` uses the immediately preceding model as the reference, leading to incremental constraint enforcement, whereas `COLD` relies on the best available model, which imposes stricter constraints and results in larger accumulated queue values.

8   Conclusions and Future Work

In this work, we introduced `COLD`, a Lyapunov optimization–based framework for CL that provides explicit and provable guarantees on the stability–plasticity trade-off. By formulating CL as a long-term constrained optimization problem, we showed that performance on the current task and forgetting of past tasks can be jointly controlled through a single tunable parameter, yielding interpretable bounds that hold at every task rather than only asymptotically or in hindsight.

A key outcome of our analysis is the explicit dependence of the regret and forgetting guarantees on task variation, thereby revealing how nonstationarity across tasks fundamentally impacts CL performance. This connection is notably absent in existing theoretical work, which typically treats tasks as exchangeable or ignores their temporal evolution altogether. Our results demonstrate that no algorithm can simultaneously achieve low regret and negligible forgetting when task variation is large, and that `COLD` adapts optimally to this regime.

From an algorithmic perspective, `COLD` enforces long-term constraints via virtual queues, eliminating the need for projection steps or dual-variable updates commonly used in constrained CL methods. The proposed algorithm admits fixed learning rates and remains simple to implement, while still enjoying rigorous performance and stability guarantees.

Overall, this work establishes a principled control-theoretic foundation for CL, bridging online optimization, queue stability, and learning under nonstationarity. We believe this framework opens several promising directions for future research, including tighter variation-dependent bounds, extensions to nonconvex objectives, and practical implementations in large-scale and task-agnostic CL settings.

References

Rahaf Aljundi, Francesca Babiloni, Mohamed Elhoseiny, Marcus Rohrbach, and Tinne Tuytelaars. Memory aware synapses: Learning what (not) to forget. In *Proceedings of the European conference on computer vision (ECCV)*, pp. 139–154, 2018.

Pietro Buzzega, Matteo Boschini, Angelo Porrello, Davide Abati, and Simone Calderara. Dark experience for general continual learning: a strong, simple baseline. *Advances in neural information processing systems*, 33:15920–15930, 2020.

Lucas Caccia, Rahaf Aljundi, Nader Asadi, Tinne Tuytelaars, Joelle Pineau, and Eugene Belilovsky. New insights on reducing abrupt representation change in online continual learning. In *International Conference on Learning Representations*, 2021.

Arslan Chaudhry, Marc'Aurelio Ranzato, Marcus Rohrbach, and Mohamed Elhoseiny. Efficient lifelong learning with a-gem. *arXiv preprint arXiv:1812.00420*, 2018.

Lénaïc Chizat and Francis Bach. Lazy training in differentiable programming. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 32, 2019. URL https://papers.nips.cc/paper_files/paper/2019/hash/2c04ecb5b9afa19f3b8c9f7b30c6b43e-Abstract.html.

Li Deng. The mnist database of handwritten digit images for machine learning research. *IEEE Signal Processing Magazine*, 29(6):141–142, 2012.

Mehrdad Farajtabar, Navid Azizan, Alex Mott, and Ang Li. Orthogonal gradient descent for continual learning. In *International conference on artificial intelligence and statistics*, pp. 3762–3773. PMLR, 2020.

Robert M French. Catastrophic forgetting in connectionist networks. *Trends in cognitive sciences*, 3(4): 128–135, 1999.

Seungyub Han, Yeongmo Kim, Taehyun Cho, and Jungwoo Lee. On the convergence of continual learning with adaptive methods. In *Uncertainty in Artificial Intelligence*, pp. 809–818. PMLR, 2023.

Xiaoyan Huang, Supeng Leng, Sabita Maharjan, and Yan Zhang. Multi-agent deep reinforcement learning for computation offloading and interference coordination in small cell networks. *IEEE Transactions on Vehicular Technology*, 70(9):9282–9293, 2021.

Nitish Shirish Keskar, Dheevatsa Mudigere, Jorge Nocedal, Mikhail Smelyanskiy, and Ping Tak Peter Tang. On large-batch training for deep learning: Generalization gap and sharp minima. In *International Conference on Learning Representations (ICLR)*, 2017.

James Kirkpatrick, Razvan Pascanu, Neil Rabinowitz, Joel Veness, Guillaume Desjardins, Andrei A Rusu, Kieran Milan, John Quan, Tiago Ramalho, Agnieszka Grabska-Barwinska, et al. Overcoming catastrophic forgetting in neural networks. *Proceedings of the national academy of sciences*, 114(13):3521–3526, 2017.

Alex Krizhevsky and Geoffrey Hinton. Learning multiple layers of features from tiny images. Technical Report 0, University of Toronto, Toronto, Ontario, 2009. URL https://www.cs.toronto.edu/~kriz/learning-features-2009-TR.pdf.

Ya Le and Xuan S. Yang. Tiny imagenet visual recognition challenge. 2015. URL https://api.semanticscholar.org/CorpusID:16664790.

Zhizhong Li and Derek Hoiem. Learning without forgetting. 2017.

Sen Lin, Li Yang, Deliang Fan, and Junshan Zhang. Beyond not-forgetting: Continual learning with backward knowledge transfer. *Advances in Neural Information Processing Systems*, 35:16165–16177, 2022.

Sen Lin, Peizhong Ju, Yingbin Liang, and Ness Shroff. Theory on forgetting and generalization of continual learning. In *International Conference on Machine Learning*, pp. 21078–21100. PMLR, 2023.

Chaoyue Liu, Libin Zhu, and Mikhail Belkin. Loss landscapes and optimization in over-parameterized non-linear systems and neural networks. *Applied and Computational Harmonic Analysis*, 59:85–116, 2022.

Hao Liu and Huaping Liu. Continual learning with recursive gradient optimization. In *International Conference on Learning Representations*, 2022.

Vincenzo Lomonaco, Lorenzo Pellegrini, Andrea Cossu, Antonio Carta, Gabriele Graffieti, Tyler L. Hayes, Matthias De Lange, Marc Masana, Jary Pomponi, Gido van de Ven, Martin Mundt, Qi She, Keiland Cooper, Jeremy Forest, Eden Belouadah, Simone Calderara, German I. Parisi, Fabio Cuzzolin, Andreas Tolias, Simone Scardapane, Luca Antiga, Subutai Amhad, Adrian Popescu, Christopher Kanan, Joost van de Weijer, Tinne Tuytelaars, Davide Bacciu, and Davide Maltoni. Avalanche: an end-to-end library for continual learning. In *Proceedings of IEEE Conference on Computer Vision and Pattern Recognition*, 2nd Continual Learning in Computer Vision Workshop, 2021.

Yayu Long, Kewei Chen, Long Jin, and Mingsheng Shang. Drae: Dynamic retrieval-augmented expert networks for lifelong learning and task adaptation in robotics. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 23098–23141, 2025.

David Lopez-Paz and Marc'Aurelio Ranzato. Gradient episodic memory for continual learning. *Advances in neural information processing systems*, 30, 2017.

Michael McCloskey and Neal J Cohen. Catastrophic interference in connectionist networks: The sequential learning problem. In *Psychology of learning and motivation*, volume 24, pp. 109–165. Elsevier, 1989.

M. J. Neely, S. T. Rager, and T. F. La Porta. Max weight learning algorithms for scheduling in unknown environments. *IEEE Trans. on Automatic Control*, 57(5):1179–1191, May 2012. ISSN 0018-9286. doi: 10.1109/TAC.2012.2191874.

Michael J Neely. Energy optimal control for time-varying wireless networks. *IEEE Trans. on Inf. Theory*, 52 (7):2915–2934, 2006.

Michael J Neely. Stochastic network optimization with application to communication and queueing systems. *Synthesis Lectures on Communication Networks*, 3(1):1–211, 2010.

Michael J Neely. Dynamic optimization and learning for renewal systems. *IEEE Trans. on Automatic Control*, 58(1):32–46, 2013.

Michael J Neely and Longbo Huang. Dynamic product assembly and inventory control for maximum profit. In *49th IEEE Conference on Decision and Control (CDC)*, pp. 2805–2812, 2010.

Michael J Neely, Arash Saber Tehrani, and Alexandros G Dimakis. Efficient algorithms for renewable energy allocation to delay tolerant consumers. In *First IEEE Int. Conf. on Smart Grid Commun.,*, pp. 549–554, 2010.

Francesco Orabona. A modern introduction to online learning. *arXiv preprint arXiv:1912.13213*, 2019.

Ameya Prabhu, Philip HS Torr, and Puneet K Dokania. Gdumb: A simple approach that questions our progress in continual learning. In *European conference on computer vision*, pp. 524–540. Springer, 2020.

Matthew Riemer, Ignacio Cases, Robert Ajemian, Miao Liu, Irina Rish, Yuhai Tu, and Gerald Tesauro. Learning to learn without forgetting by maximizing transfer and minimizing interference. In *International Conference on Learning Representations*, 2019.

David Rolnick, Arun Ahuja, Jonathan Schwarz, Timothy Lillicrap, and Gregory Wayne. Experience replay for continual learning. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019. URL https://proceedings.neurips.cc/paper_files/paper/2019/file/fa7cdfad1a5aaf8370ebeda47a1ff1c3-Paper.pdf.

Andrei A Rusu, Neil C Rabinowitz, Guillaume Desjardins, Hubert Soyer, James Kirkpatrick, Koray Kavukcuoglu, Razvan Pascanu, and Raia Hadsell. Progressive neural networks. *arXiv preprint arXiv:1606.04671*, 2016.

Sumudu Samarakoon, Mehdi Bennis, Walid Saad, Mérouane Debbah, and Matti Latva-Aho. Energy-efficient resource management in ultra dense small cell networks: A mean-field approach. In *IEEE Global Communications Conference (GLOBECOM)*, pp. 1–6. IEEE, 2015.

Dhruv Sarkar, Aprameyo Chakrabartty, Subhamon Supantha, Palash Dey, and Abhishek Sinha. Projection-free algorithms for online convex optimization with adversarial constraints. *arXiv preprint arXiv:2501.16919*, 2025.

Abhishek Sinha and Rahul Vaze. Optimal algorithms for online convex optimization with adversarial constraints. *Advances in Neural Information Processing Systems*, 37:41274–41302, 2024.

Edoardo Urettini and Antonio Carta. Online curvature-aware replay: Leveraging 2^{nd} order information for online continual learning. In *International Conference on Machine Learning*, 2025.

Gido M Van de Ven, Tinne Tuytelaars, and Andreas S Tolias. Three types of incremental learning. *Nature Machine Intelligence*, 4(12):1185–1197, 2022.

Rahul Vaze and Abhishek Sinha. $o(\sqrt{T})$ static regret and instance dependent constraint violation for constrained online convex optimization. *arXiv preprint arXiv:2502.05019*, 2025.

Quanziang Wang, Renzhen Wang, Yichen Wu, Xixi Jia, and Deyu Meng. Cba: Improving online continual learning via continual bias adaptor. In *Proceedings of the IEEE/CVF international conference on computer vision*, pp. 19082–19092, 2023.

Zhenyi Wang, Yan Li, Li Shen, and Heng Huang. A unified and general framework for continual learning. In *The Twelfth International Conference on Learning Representations*, 2024.

Yichen Wu, Hong Wang, Peilin Zhao, Yefeng Zheng, Ying Wei, and Long-Kai Huang. Mitigating catastrophic forgetting in online continual learning by modeling previous task interrelations via pareto optimization. In Ruslan Salakhutdinov, Zico Kolter, Katherine Heller, Adrian Weller, Nuria Oliver, Jonathan Scarlett, and Felix Berkenkamp (eds.), *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pp. 53892–53908. PMLR, 21–27 Jul 2024. URL https://proceedings.mlr.press/v235/wu24ab.html.

Wenhan Xu, Jiashuo Jiang, Lei Deng, and Danny Hin-Kwok Tsang. A lyapunov drift-plus-penalty method tailored for reinforcement learning with queue stability. *arXiv preprint arXiv:2506.04291*, 2025.

Jianshu Zhang, Yankai Fu, Ziheng Peng, Dongyu Yao, and Kun He. Core: Mitigating catastrophic forgetting in continual learning through cognitive replay. In *Proceedings of the Annual Meeting of the Cognitive Science Society*, volume 46, 2024.