Model-Based Episodic Memory Induces Dynamic Hybrid Controls

Abstract

Episodic control enables sample efficiency in reinforcement learning by recalling past experiences from an episodic memory. We propose a new model-based episodic memory of trajectories addressing current limitations of episodic control. Our memory estimates trajectory values, guiding the agent towards good policies. Built upon the memory, we construct a complementary learning model via a dynamic hybrid control unifying model-based, episodic and habitual learning into a single architecture. Experiments demonstrate that our model allows significantly faster and better learning than other strong reinforcement learning agents across a variety of environments including stochastic and non-Markovian settings.

1 Introduction

Episodic memory or "mental time travel" [6] allows recreation of past experiences. In reinforcement learning (RL), episodic control (EC) uses this memory to control behavior, and complements forward model based and simpler, habitual (cached) control methods. The use of episodic memory is shown to be very useful in early stages of RL [24, 4] and backed up by cognitive evidence [37, 36]. Using only one or few instances of past experiences to make decisions, EC agents avoid complicated planning computations, exploiting experiences faster than the other two control methods. In hybrid control systems, EC demonstrates excellent performance and better sample efficiency [31, 25].

Early works on episodic control use tabular episodic memory storing a raw trajectory as a sequence of states, actions and rewards over consecutive time steps. To select a policy, the methods iterate through all stored sequences and are thus only suitable for small-scale problems [24, 9]. Other episodic memories store individual state-action pairs, acting as the state-action value table in tabular RL, and can generalize to novel states using nearest neighbor approximations [4, 31]. Recent works [30, 14, 25, 40] leverage both episodic and habitual learning by combining state-action episodic memories with parametric value functions like Deep Q-Network (DQN; [29]). The combination of the "fast" non-parametric episodic and "slow" parametric value facilitates Complementary Learning Systems (CLS) – a theory posits that the brain relies on both slow learning of distributed representations (neocortex) and fast learning of pattern-separated representations (hippocampus) [26].

Existing episodic RL methods suffer from 3 issues: (a) near-deterministic assumption [4] which is vulnerable to noisy or stochastic environments causing ambiguous observations; (b) sample-inefficiency due to storing state-action-value which demands experiencing all actions to make reliable decisions and inadequate memory writings that prevent fast and accurate value propagation inside the memory [4, 31]; and finally, (c) assuming fixed combination between episodic and parametric values [25, 14] that makes episodic contribution weight unchanged for different observations and requires manual tuning of the weight. We tackle these open issues by designing a novel model that flexibly integrates habitual, model-based and episodic control into a single architecture for RL.

To tackle issue (a) the model learns representations of the trajectory by minimizing a self-supervised loss. The loss encourages reconstruction of past observations, thus enforcing a compressive and noise-tolerant representation of the trajectory for the episodic memory. Unlike model-based RL [34, 13] that simulates the world, our model merely captures the trajectories.

To address issue (b), we propose a model-based value estimation mechanism established on the trajectory representations. This allows us to design a memory-based planning algorithm, namely Model-based Episodic Control (MBEC), to compute the action value online at the time of making decisions. Hence, our memory does not need to store actions. Instead, the memory stores trajectory vectors as the keys, each of which is tied to a value, facilitating nearest neighbor memory lookups to retrieve the value of an arbitrary trajectory (memory read). To hasten value propagation inside the memory, we propose using a weighted averaging write operator that writes to multiple memory slots, plus an update operator to refine the written values at any step.

Finally, to address issue (c), we create a flexible CLS architecture, merging complementary systems of learning and memory. An episodic value is combined with a parametric value via dynamic consolidation. Concretely, conditioned on the current observation, a neural network dynamically assigns the combination weight determining how much the episodic memory contributes to the final action value. We choose DQN as the parametric value function and train it to minimize the temporal difference (TD) error (habitual control). The learning of DQN takes episodic values into consideration, facilitating a distillation of the episodic memory into the DQN's weights.

Our contributions are: (i) a new model-based control using episodic memory of trajectories; (ii) a Complementary Learning Systems architecture that addresses limitations of current episodic RL through a dynamic hybrid control unifying model-based, episodic and habitual learning (see Fig. 1); and, (iii) demonstration of our architecture on a diverse test-suite of RL problems from grid-world, classical control to Atari games and 3D navigation tasks. We show that the MBEC is noise tolerant, robust in dynamic grid-world environments. In classical control, we show the advantages of the hybrid control when the environment is stochastic, and illustrate how each component plays a crucial role. For high-dimensional problems, our model also achieves superior performance. Further, we interpret model behavior and provide analytical studies to validate our empirical results.

2   Background

2.1   Deep Reinforcement Learning

Reinforcement learning aims to find the policy that maximizes the future cumulative rewards of sequential decision-making problems [35]. Unlike model-based approaches that build a model of how the environment operates, from which the optimal policy is found through planning [34], Q-learning [38] – a typical model-free method, directly estimates the true state-action value function. The function is defined as $Q(s, a) = \mathbb{E}_\pi \left[\sum_t \gamma^t r_t \mid s, a \right]$, where r_t is the reward at timestep t that the agent receives from the current state s by taking action a, followed policy π. $\gamma \in (0, 1]$ is the discount factor that weights the importance of upcoming rewards. Upon learning the function, the best action can be found as $a_t = \arg\max_a Q(s_t, a)$.

With the rise of deep learning, neural networks have been widely used to improve reinforcement learning. Deep Q-Network (DQN; [29]) learns the value function $Q_\theta(s, a)$ using convolutional and feed-forward neural networks whose parameters are θ. The value network takes an image representation of the state s_t and outputs a vector containing the value of each action a_t. To train the networks, DQN samples observed transition (s_t, a_t, r_t, s_{t+1}) from a replay buffer to minimize the squared error between the value output and target $y_t = r_t + \gamma \max_a Q'_\theta(s_{t+1}, a)$ where Q'_θ is the target network. The parameter of the target network is periodically set to that of the value network, ensuring stable learning. The value network of DQN resembles a semantic memory that gradually encodes the value of state-action pairs via replaying as a memory consolidation in CLS theory [21].

Experience replay is critical for DQN, yet it is slow, requiring a lot of observations since the replay buffer only stores raw individual experiences. Prioritized Replay [32] improves replaying process with non-uniform sampling favoring important transitions. Others overcome the limitation of one-step transition by involving multi-step return in calculating the value [23, 16]. These works require raw trajectories and parallel those using episodic memory that persists across episodes.

Figure 1: Dynamic hybrid control with the episodic memory at its core. The trajectory model, trained with TR loss (Eq. 1), encodes representations for writing (Eq. 2) and updating (Eq. 4) the episodic memory. Model-based Episodic Control (MBEC) plans actions (e.g. a_1 and a_2) and computes future trajectory representations ($\overrightarrow{\tau}'(a_1)$ and $\overrightarrow{\tau}'(a_2)$) for reading the memory's stored values. The read-out, together with the reward model, estimates the episodic value Q_{MBEC} (Eq. 6). The Complementary Learning Systems (CLS) combines Q_{MBEC} and the traditional semantic Q_θ using dynamic consolidation conditioned on $\overrightarrow{\tau}$ (Eq. 7). The parameters of the CLS are optimized with TD loss (Eq. 8; habitual control).

2.2 Other Memory-based Controls

Long Short-Term Memory (LSTM; [17]) and Memory-Augmented Neural Networks (MANNs; [10, 11]) excel at learning long sequences, and thus extend the capability of neural networks in RL. In particular, Deep Recurrent Q-Network (DRQN; [15]) replaces the feed-forward value network with LSTM counterparts, aiming to solve Partially-Observable Markov Decision Process (POMDP). Policy gradient agents are commonly equipped with memories [28, 11, 33]. They capture long-term dependencies across states, enrich state representation and contribute to making decisions that require reference to past events in the same episode. Recent works use memory for reward shaping either via contribution analysis [1] or memory attention [18]. To improve the representation stored in memory, some also construct a model of transitions using unsupervised learning [39, 13, 8]. As these memories are cleared at the end of the episode, they act more like working memory with a limited lifespan [2]. They are all different from the notion of episodic memory, which is the main focus of this paper.

3   Methods

We introduce a novel model that combines habitual, model based and episodic control wherein episodic memory plays a central role. Thanks to the memory storing trajectory representations, we can estimate the value in a model-driven fashion: for a considering action, the future trajectory is computed to query the episodic memory and get the action value. This takes advantage of model-based planning and episodic inference. The episodic value is then fused with a slower, parametric value function to leverage the capability of both episodic and habitual learning. Fig. 1 illustrates these components. We first present the formation of the trajectory representation and the episodic memory. Next, we describe how we estimate the value from this memory and parametric Q networks.

3.1   Episodic Memory Stores Trajectory Representations

In this paper, a trajectory τ_t is a sequence of what happens up to the time step t: $\tau_t = [(s_1, a_1), ..., (s_t, a_t)]$. If we consider τ_t as a piece of memory that encodes events in an episode, from that memory, we must be able to recall any past event. This ability in humans can be examined through the serial recall test wherein a previous item cues to the recall of the next item in a sequence [7]. We aim to represent trajectories as vectors manifesting that property. As such, we employ a recurrent trajectory network $\mathcal{T}_\phi$ to model $\overrightarrow{\tau}_t = \mathcal{T}_\phi([s_t, a_t], \overrightarrow{\tau}_{t-1})$ where $\mathcal{T}_\phi$ is implemented as an LSTM [17] and $\overrightarrow{\tau}_t \in \mathbb{R}^H$ is the vector representation of τ_t and also the hidden state of the LSTM.

We train the *trajectory model* $\mathcal{T}_\phi$ to compute $\overrightarrow{\tau}_t$ such that it is able to reconstruct the *next* observation of any *past* experience, simulating the serial recall test. Concretely, given a noisy version $(\tilde{s}_{t'}, \tilde{a}_{t'})$ of

---

Algorithm 1 MBEC++: Complementary reinforcement learning with MBEC and DQN.

1: $\mathcal{D}$: Replay buffer; $\mathcal{B}$: Trajectory buffer; $\mathcal{C}$: Chunk buffer; $\mathcal{M}$: Episodic memory; $\mathcal{T}_\phi$: Trajectory model; $r_\varphi(s,a)$: Reward model; L: Chunk length
2: **for each** episode **do**
3:     Initialize $\overrightarrow{\tau}_0 = 0$; $\mathcal{B} = \emptyset$; $\mathcal{C} = \emptyset$
4:     **for** $t = 1, T$ **do**
5:         Observe state s_t. Compute $f_\beta(\overrightarrow{\tau}_{t-1})$.
6:         Select action $a_t \leftarrow \epsilon$-greedy policy using Q in Eq. 7
7:         Observe reward r_t. Move to next state s_{t+1}. Compute $\overrightarrow{\tau}_t \leftarrow \mathcal{T}_\phi([s_t, a_t], \overrightarrow{\tau}_{t-1})$
8:         Add $(s_t, a_t, s_{t+1}, r_t, \overrightarrow{\tau}_{t-1}, \overrightarrow{\tau}_t)$ and (s_t, a_t) to $\mathcal{D}$ and $\mathcal{B}$, respectively.
9:         Update memory: $\mathcal{M} \leftarrow \text{update}(s_t, \overrightarrow{\tau}_{t-1} | \mathcal{M})$
10:        Sample $(s_{t'}, a_{t'}, s_{t'+1}, r_{t'}, \overrightarrow{\tau}_{t'-1}, \overrightarrow{\tau}_{t'})$ from $\mathcal{D}$ to update θ and β using $\mathcal{L}_q$ in Eq. 8
11:        Sample $(s_{t'}, a_{t'}, r_{t'})$ from $\mathcal{D}$ to update φ using Eq. 5
12:     **if** $t \mod L == 0$ **then**
13:         Add $(\overrightarrow{\tau}_{t-1}, r_t)$ to $\mathcal{C}$. Sample $(s_{t'}, a_{t'})$ from $\mathcal{B}$ to update ϕ and ω using $\mathcal{L}_{tr}$ in Eq. 1
14:     **if** $t == T$ **then**
15:         **for each** $\overrightarrow{\tau}_i \in \mathcal{C}$ **do**
16:             Compute $R(\overrightarrow{\tau}_i) = \sum_{j=i}^{T-1} \gamma^{j-i} r_{j+1}$. Write $\mathcal{M} \leftarrow \text{write}(\overrightarrow{\tau}_i, R(\overrightarrow{\tau}_i) | \mathcal{M})$

---

a query state-action $(s_{t'}, a_{t'})$ sampled from a trajectory buffer $\mathcal{B}$ at time step $t' < t$, we minimize the *trajectorial recall (TR) loss* as follows,

$$\mathcal{L}_{tr} = \mathbb{E}\left(\| y^*(t) - [s_{t'+1}, a_{t'+1}] \|_2^2 \right) \tag{1}$$

where $y^*(t) = \mathcal{G}_\omega(\mathcal{T}_\phi([\tilde{s}_{t'}, \tilde{a}_{t'}], \overrightarrow{\tau}_t))$, $\mathcal{G}_\omega$ is a reconstruction function, implemented as a feed-forward neural network. The trajectory network $\mathcal{T}_\phi$ must implement some form of associative memory, compressing information of any state-action query in the past in its current representation $\overrightarrow{\tau}_t$ to reconstruct the next observation of the query, keeping the TR loss low. Appendix A.1 theoretically explains why the TR loss is suitable for episodic control.

Our goal is to keep the trajectory representation and its associated value as the key and value of an episodic memory $\mathcal{M} = \{\mathcal{M}^k, \mathcal{M}^v\}$, respectively. $\mathcal{M}^k \in \mathbb{R}^{N \times H}$ and $\mathcal{M}^v \in \mathbb{R}^{N \times 1}$, where N is the maximum number of memory slots. The true value of a trajectory $\overrightarrow{\tau}_t$ is simply defined as the value of the resulting state of the trajectory $V(\overrightarrow{\tau}_t) = V(s_{t+1}) = \mathbb{E}\left(\sum_{i=0}^{T-t-1} \gamma^i r_{t+1+i} \right)$, T is the terminal step. The memory stores estimation of the true trajectory values.

3.2 Memory Operators

Memory reading Given a query key $\overrightarrow{\tau}$, we read from the memory the corresponding value by referring to neighboring representations. Concretely, two reading rules are employed

$$\text{read}(\overrightarrow{\tau} | \mathcal{M}) = \begin{cases} \sum_{i \in \mathcal{N}^{K_r}(\overrightarrow{\tau})} \frac{\langle \mathcal{M}_i^k, \overrightarrow{\tau} \rangle \mathcal{M}_i^v}{\sum_{j \in \mathcal{N}^K(\overrightarrow{\tau})} \langle \mathcal{M}_j^k, \overrightarrow{\tau} \rangle} & (a) \\ \max_{i \in \mathcal{N}^{K_r}(\overrightarrow{\tau})} \mathcal{M}_i^v & (b) \end{cases}$$

where $\langle \cdot \rangle$ is a kernel function and $\mathcal{N}^{K_r}(\cdot)$ retrieves top K_r nearest neighbors of the query in $\mathcal{M}^k$. The read-out is an estimation of the value of the trajectory $\overrightarrow{\tau}$ wherein the weighted average rule (a) is a balanced estimation, while the max rule (b) is optimistic, encouraging exploitation of the best local experience. In this paper, the two reading rules are simply selected randomly with a probability of p_{read} and $1 - p_{read}$, respectively.

Memory writing Given the writing key $\overrightarrow{\tau}$ and its estimated value $R(\overrightarrow{\tau})$, the write operator $\text{write}(\overrightarrow{\tau}, R(\overrightarrow{\tau}) | \mathcal{M})$ consists of several steps. First, we add the value to the memories $\mathcal{M}^v$ if the key cannot be found in the key memory $\mathcal{M}^k$ (this happens frequently since key match is rare). Then, we update the values of the key neighbors such that the updated values are approaching the written value $R(\overrightarrow{\tau})$ with speeds relative to the distances as $\forall i \in \mathcal{N}^{K_w}(\overrightarrow{\tau})$:

$$\mathcal{M}_i^v \leftarrow \mathcal{M}_i^v + \alpha_w \left(R\left(\overrightarrow{\tau}\right) - \mathcal{M}_i^v \right) \frac{\left\langle \mathcal{M}_i^k, \overrightarrow{\tau} \right\rangle}{\sum_{j \in \mathcal{N}^{K_w}(\overrightarrow{\tau})} \left\langle \mathcal{M}_j^k, \overrightarrow{\tau} \right\rangle} \tag{2}$$

where α_w is the writing rate. Finally, the key can be added to the key memory. When it exceeds memory capacity N, the earliest added will be removed. For simplicity, $K_w = K_r = K$.

We note that our memory writing allows multiple updates to multiple neighbor slots, which is unlike single-slot update rule [4, 31, 25]. Here, the written value is the Monte Carlo return collected from $t+1$ to the end of the episode $R\left(\overrightarrow{\tau_t}\right) = \sum_{i=0}^{T-t-1} \gamma^i r_{t+1+i}$. Following [22], we choose to write to the memory periodically after every chunk of L timesteps to save computation while still maintaining good memorization. Appendix A.2 provides a mean convergence analysis of our writing mechanism.

Memory update As the memory writing is only executed after the episode ends, it delays the value propagation inside the memory. Hence, we design the $\mathrm{update}\left(s_t, \overrightarrow{\tau}_{t-1} | \mathcal{M}\right)$ operator that tries to minimize the one-step TD error of the memory's value estimation. As such, at an arbitrary timestep t, we estimate the future trajectory if the agent takes action a using the trajectory model as $\overrightarrow{\tau}'_t(a) = \mathcal{T}_\phi\left([s_t, a], \overrightarrow{\tau}_{t-1}\right)$. Then, we can update the memory values as follows,

$$Q' = \max_a r_\varphi(s_t, a) + \gamma \mathrm{read}\left(\overrightarrow{\tau}'_t(a) | \mathcal{M}\right) \tag{3} \qquad \mathcal{M} \leftarrow \mathrm{write}\left(\overrightarrow{\tau}_{t-1}, Q' | \mathcal{M}\right) \tag{4}$$

where r_φ is a reward model using feed-forward neural network. r_φ is trained by minimizing

$$\mathcal{L}_{re} = \mathbb{E}\left(r - r_\varphi(s, a)\right)^2 \tag{5}$$

The memory update can be shown to converge in finite MDP environments.

Proposition 1. *In a finite MDP $(\mathcal{S}, \mathcal{A}, \mathcal{T}, \mathcal{R})$, given a fixed bounded r_φ and an episodic memory $\mathcal{M}$ with* read *(average rule) and* write *operations, the memory* update *given by Eq. 4 converges to a fixed point with probability 1 as long as $\gamma < 1$, $\sum_{t=1}^{\infty} \alpha_{w,t} = \infty$ and $\sum_{t=1}^{\infty} \alpha_{w,t}^2 < \infty$.*

Proof. See Appendix A.3. □

3.3 Model-based Episodic Control (MBEC)

Our agent relies on the memory at every timestep to choose its action for the current state s_t. To this end, the agent first plans some action and uses $\mathcal{T}_\phi$ to estimate the future trajectory. After that, it reads the memory to get the value of the planned trajectory. This mechanism takes advantage of model-based RL's planning and episodic control's non-parametric inference, yielding a novel hybrid control named Model-based Episodic Control (MBEC). The state-action value then is

$$Q_{MBEC}(s, a) = r_\varphi(s, a) + \gamma \mathrm{read}\left(\overrightarrow{\tau}'(a) | \mathcal{M}\right) \tag{6}$$

The MBEC policy then is $\pi(s) = \mathrm{argmax}_a Q_{MBEC}(s, a)$. Unlike model-free episodic control, we compute on-the-fly instead of storing the state-action value. Hence, the memory does not need to store all actions to get reliable action values.

3.4 Model-based Episodic Control Facilitates Complementary Learning Systems

The episodic value provides direct yet biased estimation from experiences. To compensate for that, we can use a neural network $Q_\theta(s_t, a_t)$ to give an unbiased value estimation [29], representing the slow-learning semantic memory that gradually encodes optimal values. Prior works combine by a weighted summation of the episodic and semantic value wherein the weight is fixed [25, 14]. We believe that depending on the specific observations, we may need different weights to combine the two values. Hence, we propose to combine the two episodic and semantic systems as

$$Q(s_t, a_t) = Q_{MBEC}(s_t, a_t) f_\beta\left(\overrightarrow{\tau}_{t-1}\right) + Q_\theta(s_t, a_t) \tag{7}$$

Figure 2: Maze navigation. (a) Noisy mode: number of steps required to complete 100 episodes with different noise rates (lower is better). (b) Trap mode: average reward (upper) and number of completed episodes (lower) over timesteps (higher is better). (c) Dynamic mode: efficiency improvement over random policy across timesteps (higher is better).

Figure 3: Average reward over learning steps on representative stochastic classical control environments (higher is better, mean and std. over 10 runs).

where f_β is a feed-forward neural network with sigmoid activation that takes the previous trajectory as the input and outputs a consolidating weight for the episodic value integration. This allows dynamic integration conditioned on the trajectory status. The semantic system learns to take episodic estimation into account in making decisions via replaying to minimize one-step TD error,

$$\mathcal{L}_q = \mathbb{E}\left(r + \gamma \max_{a'} Q\left(s', a'\right) - Q\left(s, a\right)\right)^2 \tag{8}$$

We follow [29] using a replay buffer $\mathcal{D}$ to store (s, a, s', r) across episodes. Without episodic contribution, TD or habitual learning is slow [14, 25]. Our episodic integration allows the agent to rely on MBEC whenever it needs to compensate for immature parametric systems. Alg. 1 (MBEC++) summarizes MBEC operations within the complementary learning system.

4 Results

In this section, we examine our proposed episodic control both as a stand-alone (MBEC) and within a complementary learning system (MBEC++). To keep our trajectory model simple, for problems with image state, it learns to reconstruct the feature vector of the image input, rather than the image itself. The main baselines are DQN [29] and recent (hybrid) episodic control methods. Details of the baseline configurations and hyper-parameter tuning for each tasks can be found in Appendix B.

4.1 Grid-world: 2D Maze Exploration

We begin with a simple maze navigation to explore scenarios wherein our proposed memory shows advantages. In this task, an agent is required to move from the starting point $(0, 0)$ to the end point $(n_e - 1, n_e - 1)$ in a maze environment of size $n_e \times n_e$. We create different scenarios for this task $(n_e = 3)$: noisy, trap and dynamic modes wherein our MBEC is compared with both parametric (DQN) and memory-based (MFEC; [4]) models (see Appendix B.2 for details and more results).

Noisy mode In this mode, the state is represented as the location plus an image of the maze. The image is preprocessed by a pretrained ResNet, resulting in a vector of 512 dimensions. We apply

Figure 4: Cart Pole. (Left) Average contribution of episodic and semantic value estimations over timesteps (see Appendix B.3 for contribution definition). The episodic influence is gradually replaced by the semantic's. (Middle) The difference (absolute error) between the stored and true value of the starting state (mean and std. over 5 runs). (Right) Mountain Car. (a) Visualization of the the car moving uphill over 30 timesteps. Due to noise, the next state can be observed as the current state with probability p_{tr}. (b) State and (c) trajectory spaces. Blue denotes the representation at noisy timestep and red the normal ones. Fading color denotes earlier timesteps. (d) Value estimation by the episodic memory for the whole 2-d trajectory space.

dropout to the image vector with different noise levels. We hypothesize that aggregating states into trajectory representation as in MBEC is a natural way to smooth out the noise of individual states.

Fig. 2 (a) measures sample efficiency of the models on noisy mode. Without noise, all models can quickly learn the optimal policy and finish 100 episodes within 1000 environment steps. However, as the increased noise distracts the agents, MFEC cannot find the way out until the episode ends. DQN performance reduces as the noise increases and ends up even worse than random exploration. By contrast, MBEC tolerates noise and performs much better than DQN and the random agent.

Trap mode The state is the position of the agent plus a trap location randomly determined at the beginning of the episode. If the agent falls into the trap, it receives -2 reward. This setting illustrates the advantage of memory-based planning. With MBEC, the agent remembers to avoid the trap by examining the future trajectory to see if it includes the trap. Estimating state-action value (DQN and MFEC) introduces overhead as they must remember all state-action pairs triggering the trap.

We plot the average reward and number of completed episodes over time in Fig. 2 (b). In this mode, DQN always learns a sub-optimal policy, which is staying in the maze. It avoids hitting the wall and trap, however completes a relatively low number of episodes. MFEC initially learns well, quickly completing episodes. However its learning becomes unstable as more observations are written into its memory, leading a lower performance over time. MBEC alone demonstrates stable learning, significantly outperforming other baselines in both reward and sample efficiency.

Dynamic mode The state is represented as an image and the maze structure randomly changes for each episode. A learnable CNN is equipped for each baseline to encode the image into a 64-dimensional vector. In this dynamic environment, similar state-actions in different episodes can lead to totally different outcomes, thereby highlighting the importance of trajectory modeling. In this case, MFEC uses VAE-CNN, trained to reconstruct the image state. Also, to verify the contribution of TR loss, we add two baselines: (i) MBEC without training trajectory model (no TRL) and (ii) MBEC with a traditional model-based transition prediction loss (TPL) (see Appendix B.2 for more details).

We compare the models' efficiency improvement over random policy by plotting the percentage of difference between the models' number of finished episodes and that of random policy in Fig. 2 (c). DQN and MFEC perform worse than random. MBEC with untrained trajectory model performs poorly. MBEC with trajectory model trained with TPL shows better performance than random, yet still underperforms our proposed MBEC with TRL by around 5-10%.

4.2 Stochastic Classical Control

In stochastic environments, taking correct actions can still lead to low rewards due to noisy observations, which negatively affects the quality of episodic memory. We consider 3 classical problems: Cart Pole, Mountain Car and Lunar Lander. For each problem, we examine RL agents in stochastic settings by (i) perturbing the reward with Gaussian (mean 0, std. σ_{re}) or (ii) Bernoulli noise (with probability p_{re}, the agent receives reward $-r$ where r is the true reward) and (iii) noisy transition

Model	All	25 games
Nature DQN	15.7/51.3	83.6/16.0
MFEC	85.0/45.4	77.7/40.9
NEC	99.8/54.6	106.1/53.3
EMDQN*	528.4/92.8	250.6/95.5
EEVA	-	172.2/39.2
ERLAM	-	515.4/103.5
MBEC++	**654.0/117.2**	**518.2/133.4**

Table 1: Human normalized scores (mean/median) at 10 million frames for all and a subset of 25 games. Baselines' numbers are adopted from original papers and [40], respectively. * The baseline is reported with 40 million frames of training. - The exact numbers are not reported.

(with probability p_{tr}, the agent observes the current state as its next state despite taking any action). In this case, we compare MBEC++ with DQN, MFEC and NEC [31].

Fig. 3 shows the performances of the models on representative environments (full results in Appendix B.3). For easy problems like Cart Pole, although MFEC learns quickly, its over-optimistic control is sub-optimal in non-deterministic environments, and thus cannot solve the task. For harder problems, stochasticity makes state-based episodic memories (MFEC, NEC) fail to learn. DQN learns in these settings, albeit slowly, illustrating the disadvantage of not having a reliable episodic memory. Among all, MBEC++ is the only model that can completely solve the noisy Cart Pole within 10,000 steps and demonstrates a superior performance in Mountain Car and Lunar Lander.

Behavior analysis The episodic memory plays a role in MBEC++'s success. At the beginning, the agent mainly relies on the memory, yet later, it automatically learns to switch to the semantic value estimation (see Fig. 4 (left)). That is because in the long run the semantic value is more reliable and already fused with the episodic value through Eq. 7-8. Our write operator also helps MBEC++ in quickly searching for the optimal value. To illustrate that, we track the convergence of the episodic memory's written values for the starting state of the stochastic Cart Pole problem under a fixed policy (Fig. 4 (middle)). Unlike the over-optimistic MFEC's writing rule using max operator, ours enables mean convergence to the true value despite Gaussian reward noise. When using a moderate $K_w > 1$, the estimated value converges better as suggested by our analysis in Appendix A.2. Finally, to verify the contribution of the trajectory model, we examine MBEC++'s ability to counter noisy transition by visualizing the trajectory spaces for Mountain Car in Fig. 4 (right). Despite the noisy states (Fig. 4 (right, b)), the trajectory model can still roughly estimate the trace of trajectories (Fig. 4 (right, c)). That ensures when the agent approaches the goal, the trajectory vectors smoothly move to high-value regions in the trajectory space (Fig. 4 (right, d)). We note that for this problem that ability is only achieved through training with TR loss (comparison in Appendix B.3).

Ablation study We pick the noisy transition Mountain Car problem for ablating components and hyper-parameters of MBEC++ with different neighbors (K), chunk length (L) and memory slots (N). The results in Fig. 5 demonstrate that the performance improves as K increases, which is common for KNN-based methods. We also find that using a too short or too long chunk deteriorates the performance of MBEC++. Short chunk length creates redundancy as the stored trajectories will be similar while long chunk length makes minimizing TR loss harder. Finally, the results confirm that the learning of MBEC++ is hindered significantly with a small memory. A too big memory does not help either since the trajectory model continually refines the trajectory representation, a too big memory slows the replacement of old representations with more accurate newer ones.

We also ablate MBEC++: (i) without TR loss, (ii) with TP loss (iii), without multiple write ($K_w = 1$) and (iv) without memory update. We realize that the first two configurations show no sign of learning. The last two can learn but much slower than the full MBEC++, justifying our neighbor memory writing and update (Fig. 5 (rightmost)). More ablation studies are in Appendix B.6 where we find our dynamic consolidation is better than fixed combinations and optimal p_{read} is 0.7.

4.3 Atari 2600 Benchmark

We benchmark MBEC++ against other strong episodic memory models in playing Atari 2600 video games [3]. The task can be challenging with stochastic and partially observable games [20]. Our

Figure 5: Noisy Transition Mountain Car: ablation study. Each plot varies one hyper-parameter or ablated component while fixing others in default values ($K = 15$, $L = 10$, $N = 3000$).

model adopts DQN [29] with the same setting (details in Appendix B.4). We only train the models within 10 million frames for sample efficiency.

Table 1 reports the average performance of MBEC++ and baselines on all (57) and 25 popular Atari games concerning human normalized metrics [29]. Compared to the vanilla DQN, MFEC and NEC, MBEC++ is significantly faster at achieving high score in the early learning phase. Further, MBEC++ outperforms EMDQN even trained with 40 million frames and achieves the highest median score. Here, state-based value estimations fall short in quickly solving complicated tasks with many actions like playing Atari games as it takes time to visit enough state-action pairs to create useful memory's stored values. By contrast, when the models in MBEC++ are well-learnt (which is often within 5 million frames, see Appendix B.4), its memory starts providing reliable trajectory value estimation to guide the agent to good policies. Remarkably, our episodic memory is much smaller than that of others and our trajectory model size is insignificant to DQN's (Appendix B.4 and Table 2).

In the subset testbed, MBEC++ demonstrates competitive performance against trajectory-utilized models including EEVA [14] and ERLAM [40]. These baselines work with trajectories as raw state-action sequences, unlike our distributed trajectories. In the mean score metric, MBEC++ is much better than EEVA (nearly double score) and slightly better than ERLAM. MBEC++ agent plays consistently well across games without severe fluctuations in performance, indicated by its significantly higher median score. Appendix B.4 provides learning curves and further analyses.

4.4 POMDP: 3D Navigation

To examine MBEC++ on Partially-Observable Markov Decision Process (POMDP) environments, we conduct experiments on a 3D navigation task: Gym Mini-World's Pickup Objects [5]. Here, an agent moves around a big room to collect several objects (+1 reward for each picked object). The location, shape and color of the objects change randomly across episodes. The state is the frontal view-port of the agent and encoded by a common CNN for all baselines (details in Appendix B.5).

We train all models for only 2 million steps and report the results for different number of objects in Appendix's Fig. 12. Among all baselines, MBEC++ demonstrates the best learning progress and consistently improves over time. Other methods either fail to learn (DRQN) or show much slower learning speed (DQN and PPO). That proves our MBEC++ is useful for POMDP.

5 Conclusion

We have introduced a new episodic memory that significantly accelerates reinforcement learning in various problems beyond near-deterministic environments. Its success can be attributed to: (a) storing distributed trajectories produced by a trajectory model, (b) memory-based planning with fast value-propagating memory writing and update, and (c) dynamic consolidation of episodic values to parametric value function. Our experiments demonstrate the superiority of our method to prior episodic controls and strong RL baselines. One limitation of this work is the large amount of hyperparameters, which prevents us from fully tuning MBEC++. Our research aims to improve sample-efficiency of RL and can be trained with common computers. Overall, we do not see any intermediate negative societal impact. In future work, we will extend to continuous action space and explore multi-step memory-based planning capability of our approach.

References

[1] Jose A Arjona-Medina, Michael Gillhofer, Michael Widrich, Thomas Unterthiner, Johannes Brandstetter, and Sepp Hochreiter. Rudder: Return decomposition for delayed rewards. In *Advances in Neural Information Processing Systems*, pages 13566–13577, 2019.

[2] Alan D Baddeley and Graham Hitch. Working memory. In *Psychology of learning and motivation*, volume 8, pages 47–89. Elsevier, 1974.

[3] Marc G Bellemare, Yavar Naddaf, Joel Veness, and Michael Bowling. The arcade learning environment: An evaluation platform for general agents. *Journal of Artificial Intelligence Research*, 47:253–279, 2013.

[4] Charles Blundell, Benigno Uria, Alexander Pritzel, Yazhe Li, Avraham Ruderman, Joel Z Leibo, Jack Rae, Daan Wierstra, and Demis Hassabis. Model-free episodic control. *arXiv preprint arXiv:1606.04460*, 2016.

[5] Maxime Chevalier-Boisvert. gym-miniworld environment for openai gym. `https://github.com/maximecb/gym-miniworld`, 2018.

[6] Yadin Dudai and Mary Carruthers. The janus face of mnemosyne. *Nature*, 434(7033):567–567, 2005.

[7] Simon Farrell. Temporal clustering and sequencing in short-term memory and episodic memory. *Psychological review*, 119(2):223, 2012.

[8] Meire Fortunato, Melissa Tan, Ryan Faulkner, Steven Hansen, Adrià Puigdomènech Badia, Gavin Buttimore, Charlie Deck, Joel Z Leibo, and Charles Blundell. Generalization of reinforcement learners with working and episodic memory. In *NeurIPS*, 2019.

[9] Samuel J Gershman and Nathaniel D Daw. Reinforcement learning and episodic memory in humans and animals: an integrative framework. *Annual review of psychology*, 68:101–128, 2017.

[10] Alex Graves, Greg Wayne, and Ivo Danihelka. Neural turing machines. *arXiv preprint arXiv:1410.5401*, 2014.

[11] Alex Graves, Greg Wayne, Malcolm Reynolds, Tim Harley, Ivo Danihelka, Agnieszka Grabska-Barwińska, Sergio Gómez Colmenarejo, Edward Grefenstette, Tiago Ramalho, John Agapiou, et al. Hybrid computing using a neural network with dynamic external memory. *Nature*, 538(7626):471–476, 2016.

[12] Joseph F Grcar. A matrix lower bound. *Linear algebra and its applications*, 433(1):203–220, 2010.

[13] David Ha and Jürgen Schmidhuber. Recurrent world models facilitate policy evolution. In *Advances in neural information processing systems*, pages 2450–2462, 2018.

[14] Steven Hansen, Alexander Pritzel, Pablo Sprechmann, André Barreto, and Charles Blundell. Fast deep reinforcement learning using online adjustments from the past. In *Advances in Neural Information Processing Systems*, pages 10567–10577, 2018.

[15] Matthew Hausknecht and Peter Stone. Deep recurrent q-learning for partially observable mdps. *arXiv preprint arXiv:1507.06527*, 2015.

[16] Frank S He, Yang Liu, Alexander G Schwing, and Jian Peng. Learning to play in a day: Faster deep reinforcement learning by optimality tightening. In *5th International Conference on Learning Representations, ICLR 2017*, 2019.

[17] Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8):1735–1780, 1997.

[18] Chia-Chun Hung, Timothy Lillicrap, Josh Abramson, Yan Wu, Mehdi Mirza, Federico Carnevale, Arun Ahuja, and Greg Wayne. Optimizing agent behavior over long time scales by transporting value. *Nature communications*, 10(1):1–12, 2019.

[19] Tommi Jaakkola, Michael I Jordan, and Satinder P Singh. On the convergence of stochastic iterative dynamic programming algorithms. *Neural computation*, 6(6):1185–1201, 1994.

[20] Lukasz Kaiser, Mohammad Babaeizadeh, Piotr Milos, Blazej Osinski, Roy H Campbell, Konrad Czechowski, Dumitru Erhan, Chelsea Finn, Piotr Kozakowski, Sergey Levine, et al. Model-based reinforcement learning for atari. *arXiv preprint arXiv:1903.00374*, 2019.

[21] Dharshan Kumaran, Demis Hassabis, and James L McClelland. What learning systems do intelligent agents need? complementary learning systems theory updated. *Trends in cognitive sciences*, 20(7):512–534, 2016.

[22] Hung Le, Truyen Tran, and Svetha Venkatesh. Learning to remember more with less memorization. *arXiv preprint arXiv:1901.01347*, 2019.

[23] Su Young Lee, Choi Sungik, and Sae-Young Chung. Sample-efficient deep reinforcement learning via episodic backward update. In *Advances in Neural Information Processing Systems*, pages 2112–2121, 2019.

[24] Máté Lengyel and Peter Dayan. Hippocampal contributions to control: the third way. In *Advances in neural information processing systems*, pages 889–896, 2008.

[25] Zichuan Lin, Tianqi Zhao, Guangwen Yang, and Lintao Zhang. Episodic memory deep q-networks. *arXiv preprint arXiv:1805.07603*, 2018.

[26] James L McClelland, Bruce L McNaughton, and Randall C O'Reilly. Why there are complementary learning systems in the hippocampus and neocortex: insights from the successes and failures of connectionist models of learning and memory. *Psychological review*, 102(3):419, 1995.

[27] Francisco S Melo. Convergence of q-learning: A simple proof. *Institute Of Systems and Robotics, Tech. Rep*, pages 1–4, 2001.

[28] Volodymyr Mnih, Adria Puigdomenech Badia, Mehdi Mirza, Alex Graves, Timothy Lillicrap, Tim Harley, David Silver, and Koray Kavukcuoglu. Asynchronous methods for deep reinforcement learning. In *International conference on machine learning*, pages 1928–1937, 2016.

[29] Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *nature*, 518(7540):529–533, 2015.

[30] Daichi Nishio and Satoshi Yamane. Faster deep q-learning using neural episodic control. In *2018 IEEE 42nd Annual Computer Software and Applications Conference (COMPSAC)*, volume 1, pages 486–491. IEEE, 2018.

[31] Alexander Pritzel, Benigno Uria, Sriram Srinivasan, Adria Puigdomenech Badia, Oriol Vinyals, Demis Hassabis, Daan Wierstra, and Charles Blundell. Neural episodic control. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pages 2827–2836. JMLR. org, 2017.

[32] Tom Schaul, John Quan, Ioannis Antonoglou, and David Silver. Prioritized experience replay. *arXiv preprint arXiv:1511.05952*, 2015.

[33] John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

[34] Richard S Sutton. Dyna, an integrated architecture for learning, planning, and reacting. *ACM Sigart Bulletin*, 2(4):160–163, 1991.

[35] Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction*. MIT press, 2018.

[36] Endel Tulving. Episodic memory: From mind to brain. *Annual review of psychology*, 53(1):1–25, 2002.

[37] Endel Tulving et al. Episodic and semantic memory. *Organization of memory*, 1:381–403, 1972.

[38] Christopher JCH Watkins and Peter Dayan. Q-learning. *Machine learning*, 8(3-4):279–292, 1992.

[39] Greg Wayne, Chia-Chun Hung, David Amos, Mehdi Mirza, Arun Ahuja, Agnieszka Grabska-Barwinska, Jack Rae, Piotr Mirowski, Joel Z Leibo, Adam Santoro, et al. Unsupervised predictive memory in a goal-directed agent. *arXiv preprint arXiv:1803.10760*, 2018.

[40] Guangxiang Zhu, Zichuan Lin, Guangwen Yang, and Chongjie Zhang. Episodic reinforcement learning with associative memory. In *International Conference on Learning Representations*, 2019.

 Checklist