RelaySum for Decentralized Deep Learning on Heterogeneous Data

Abstract

In decentralized machine learning, workers compute model updates on their local data. Because the workers only communicate with few neighbors without central coordination, these updates propagate progressively over the network. This paradigm enables distributed training on networks without all-to-all connectivity, helping to protect data privacy as well as to reduce the communication cost of distributed training in data centers. A key challenge, primarily in decentralized deep learning, remains the handling of differences between the workers' local data distributions. To tackle this challenge, we introduce the RelaySum mechanism for information propagation in decentralized learning. RelaySum uses spanning trees to distribute information exactly uniformly across all workers with finite delays depending on the distance between nodes. In contrast, the typical gossip averaging mechanism only distributes data uniformly asymptotically while using the same communication volume per step as RelaySum. We prove that RelaySGD, based on this mechanism, is independent of data heterogeneity and scales to many workers, enabling highly accurate decentralized deep learning on heterogeneous data.

1 Introduction

Ever-growing datasets lay at the foundation of the recent breakthroughs in machine learning. Learning algorithms therefore must be able to leverage data distributed over multiple devices, in particular for reasons of efficiency and data privacy. There are various paradigms for distributed learning, and they differ mainly in how the devices collaborate in communicating model updates with each other. In the *all-reduce* paradigm, workers average model updates with all other workers at every training step. In *federated learning* [21], workers perform local updates before sending them to a central server that returns their global average to the workers. Finally, *decentralized learning* significantly generalizes the two previous scenarios. Here, workers communicate their updates with only few directly-connected neighbors in a network, without the help of a server.

Decentralized learning offers strong promise for new applications, allowing any group of agents to collaboratively train a model while respecting the data locality and privacy of each contributor [23]. At the same time, it removes the single point of failure in centralized systems such as in federated learning [11], improving robustness, security, and privacy. Even from a pure efficiency standpoint, decentralized communication patterns can speed up training in data centers [1].

In decentralized learning, workers share their local stochastic gradient updates with the others through *gossip* communication [35]. They send their updates to their neighbors, which iteratively propagate the updates further into the network. The workers typically use iterative *gossip averaging* of their models with their neighbors, using averaging weights chosen to ensure asymptotic uniform distribution of each update across the network. It will take τ rounds of communication for an update from worker i to reach a worker j that is τ hops away, and when it first arrives, the update is

Figure 1: To spread information across a decentralized network, classical gossip averaging diffuses information slowly through the network. The left figure illustrates the spread of information originating from the fourth worker in a chain network. In RelaySum, the messages are *relayed* without reweighting, resulting in uniform delivery of the information to every worker. When multiple workers broadcast simultaneously (not pictured), RelaySum can *sum* their messages and use the same bandwidth as gossip averaging.

exponentially weakened by repeated averaging with weights < 1. In general networks, worker j will never exactly, but only asymptotically receive its uniform share of the update. The slow distribution of updates not only slows down training, but also makes decentralized learning sensitive to heterogeneity in workers' data distributions.

We introduce the RelaySum communication mechanism as an alternative to gossip averaging. RelaySum operates on spanning trees of the network, and distributes information exactly uniformly within a finite number of gossip steps equal to the diameter of the network. Rather than iteratively averaging models, each node acts as a 'router' that *relays* messages through the whole network without decaying their weight at every hop. While naive all-to-all routing requires n^2 messages to be transmitted at each step, we show that on trees, only n messages (one per edge) are sufficient. This is enabled by the key observation that the routers can *merge* messages by *summation* to avoid any extra communication compared to gossip averaging. RelaySum achieves this using additional memory linear in the number of edges, and by tailoring the messages sent to different neighbors. At each time step, RelaySum workers receive a uniform average of exactly one message from each worker. Those messages just originate from different time delays depending on how many hops they travelled. The difference between gossip averaging and RelaySum is illustrated in Figure 1.

We use RelaySum in the RelaySGD learning algorithm. We theoretically show that this algorithm is not affected by differences in workers' data distributions. Compared to other algorithms that have this property [31, 27], RelaySGD does not require the selection of averaging weights, and its convergence does not depend on the spectral gap of the averaging matrix, but instead on the network diameter.

While RelaySum is formulated for trees, it can be used in any decentralized network. We use the Spanning Tree Protocol [26] to construct spanning trees of any network in a decentralized fashion. RelaySGD often performs better on any such spanning tree than gossip-based methods on the original graph. When the communication network can be chosen freely, we use double binary trees [29]. While these trees have logarithmic diameter and scale to many workers, RelaySGD in this setup uses only constant memory equivalent to two extra copies of the model parameters and sends and receives only two models per iteration.

Surprisingly, in deep learning with highly heterogeneous data, prior methods that are theoretically independent of data heterogeneity [31, 27], perform worse than heuristic methods that do not have this property, but use cleverly designed time-varying communication topologies [1]. In extensive tests on image- and text classification, RelaySGD performs better than both kinds of baselines at equal communication budget.

2 Related work

Out of the multitude of decentralized optimization methods, first-order algorithms that interleave local gradient updates with a form of gossip averaging [25, 10] show most promise for deep learning. Theoretical analysis for convex and strongly-convex objectives is provided in [22, 9, 25] and [17, 31, 1, 18] demonstrate that gossip-based methods can perform well in deep learning.

A gossip averaging step updates workers' local models as weighted average of their neighbors. The corresponding mixing matrix can be doubly-stochastic [25, 17, 15], column-stochastic [32, 24, 33, 1],

row-stochastic [34, 38], or a combination [36, 37, 28]. Column-stochastic methods use the *push-sum* consensus mechanism [12] and can be applied to directed graphs.

Another relevant line of work identifies mixing schemes that yield exact consensus in finite steps. For some graphs, this is possible with time-independent averaging weights [14, 4]. One can also achieve finite-time consensus with time-varying mixing matrices. On trees, for instance, exact consensus can be achieved by routing updates to a root node and back, in exactly diameter number of steps [14, 4]. On some graphs, tighter bounds can be established [6]. In general, however, those consensus schemes are not directly applicable to optimization. On fully-connected networks with n workers, Assran et al. [1] design a sparse time-varying communication scheme that yields exact consensus in a cycle of $\log n$ averaging steps and performs well in deep learning.

A fundamental challenge in decentralized learning is dealing with data that is not identically distributed among workers. Because, in this case, workers pursue different optima, workers may drift [25] and this can harm convergence. There is a large family of algorithms that introduce update corrections that provably mitigate such data heterogeneity. Examples applicable to non-convex problems are exact diffusion [39], Gradient Tracking [20, 27, 42], D^2 [31] and PushPull [28]. To tackle the same challenge, Lin et al. [18], Yuan et al. [40] propose modifications to local momentum to empirically improve performance in deep learning, but without provable guarantees.

3 Method

Setup   We consider standard decentralized optimization with data distributed over $n \geq 1$ nodes:

$$f^\star := \min_{\mathbf{x}\in\mathbb{R}^d} \left[f(\mathbf{x}) = \tfrac{1}{n} \sum_{i=1}^n \left[f_i(\mathbf{x}) := \mathbb{E}_{\xi\sim\mathcal{D}_i} F_i(\mathbf{x},\xi_i) \right] \right] .$$

Here $\mathcal{D}_i$ denotes the distribution of the data on node i and $f_i \colon \mathbb{R}^d \to \mathbb{R}$ the local optimization objectives. Workers are connected by a network respecting a graph topology $\mathcal{G} = (\mathcal{V}, \mathcal{E})$, where $\mathcal{V} = \{1, \ldots, n\}$ denotes the set of workers, and $\mathcal{E}$ the set of undirected communication links between them (without self loops). Each worker i can only directly communicate with its neighbors $\mathcal{N}_i \subset \mathcal{V}$.

Decentralized learning with gossip   We consider synchronous first-order algorithms that interleave local gradient-based updates

$$\mathbf{x}_i^{(t+1/2)} = \mathbf{x}_i^{(t)} + \mathbf{u}_i^{(t)}$$

with message exchange between connected workers. For SGD with typical gossip averaging (DP-SGD [17]), the local updates can be written as $\mathbf{u}_i^{(t)} = -\gamma \nabla f_i(\mathbf{x}_i^{(t)}, \xi_i^{(t)})$, and the messages exchanged between pairs of connected workers (i,j) are $\mathbf{m}_{i\to j}^{(t)} = \mathbf{x}_i^{(t+1/2)} \in \mathbb{R}^d$. Each timestep, the workers average their model with received messages,

$$\mathbf{x}_i^{(t+1)} = \mathbf{W}_{ii}\mathbf{x}_i^{(t+1/2)} + \sum_{j\in\mathcal{N}_i} \mathbf{W}_{ij}\mathbf{m}_{j\to i}^{(t)}, \qquad \text{(DP-SGD)}$$

using averaging weights defined by a *gossip matrix* $\mathbf{W} \in \mathbb{R}^{n\times n}$.

In this scheme, an update $\mathbf{u}_i^{(t_1)}$ from any worker i will be linearly incorporated into the model $\mathbf{x}_j^{(t_2)}$ at a later timestep t_2 with weight $(\mathbf{W}^{t_2-t_1})_{ij}$. The gossip matrix must be chosen such that these weights asymptotically converge to $\frac{1}{n}$, distributing all updates uniformly over the workers. This setup appears in, for example, [17, 15].

Uniform model averaging   If the graph topology is fully-connected, any worker can communicate with any other worker, and it is ideal to use 'all-reduce averaging',

$$\mathbf{x}_i^{(t+1)} = \tfrac{1}{n} \sum_{j=1}^n \mathbf{x}_j^{(t+1/2)}.$$

Contrary to the decentralized scheme (DP-SGD), this algorithm does not degrade in performance if data is distributed heterogeneously across workers. In sparsely connected networks, however, all-reduce averaging requires routing messages through the network. On arbitrary networks, such a routing protocol requires at least a number of communication steps equal to the network diameter $\tau_{\max}$—the minimum number of hops some messages have to travel.

Algorithm 1 RelaySGD

Input: $\forall\, i,\, \mathbf{x}_i^{(0)} = \mathbf{x}^{(0)};\ \forall\, i, j,\, \mathbf{m}_{i\to j}^{(-1)} = \mathbf{0}$, counts $c_{i\to j}^{(-1)} = 0$, learning rate γ, tree network

1: **for** $t = 0, 1, \ldots$ **do**
2:     **for** node i **in parallel**
3:         $\mathbf{x}_i^{(t+1/2)} = \mathbf{x}_i^{(t)} - \gamma \mathbf{g}_i(\mathbf{x}_i^{(t)})$ (or Adam/momentum)
4:         **for** each neighbor $j \in \mathcal{N}_i$ **do**
5:             Send $\mathbf{m}_{i\to j}^{(t)} = x_i^{(t+1/2)} + \sum_{k\in\mathcal{N}_i\setminus j} \mathbf{m}_{k\to i}^{(t-1)}$ (relay messages from other neighbors)
6:             Send corresponding counters $c_{i\to j}^{(t)} = 1 + \sum_{k\in\mathcal{N}_i\setminus j} c_{k\to i}^{(t-1)}$
7:             Receive $(\mathbf{m}_{j\to i}^{(t)}, c_{j\to i}^{(t)})$ from node j
8:         **end for**
9:         $\bar{n}_i^{(t+1)} = 1 + \sum_{j\in\mathcal{N}_i} c_{j\to i}^{(t)}$ ($\bar{n}$ converges to the total number of workers)
10:       $\mathbf{x}_i^{t+1} = \frac{1}{\bar{n}_i^{(t+1)}}\left(\mathbf{x}_i^{(t+1/2)} + \sum_{j\in\mathcal{N}_i} \mathbf{m}_{j\to i}^{(t)}\right)$ $\left(= \frac{1}{n}\sum_{j=1}^n \mathbf{x}_j^{(t-\tau_{ij}+1/2)}\right)$
11:     **end for**
12: **end for**

RelaySGD   In this paper, we approximate the all-reduce averaging update as

$$\mathbf{x}_i^{(t+1)} = \frac{1}{n}\sum_{j=1}^n \mathbf{x}_j^{(t-\tau_{ij}+1/2)}, \tag{RelaySGD}$$

where τ_{ij} is minimum number of network hops between workers i and j. Since it takes τ_{ij} steps to route a message from worker i to j, this scheme could be implemented using a peer-to-peer routing protocol like Ethernet. Of course, this naive implementation drastically increases the bandwidth used compared to gossip averaging. The key insight of this paper is that, on tree networks, the RelaySGD update rule can be implemented while using the same communication volume per step as gossip averaging, using additional memory linear in the number of a worker's direct neighbors.

RelaySum   To implement RelaySGD, we require a communication mechanism that delivers sums of delayed 'parcels' $s_w^{(t)} = \sum_{j=1}^n p_j^{(t-\tau_{wj})}$ to each worker w in a tree network, where the parcel $p_j^{(t)}$ is created by worker j at time t. To simplify the exposition, let us first consider the simplest type of tree network: a chain. In a chain, a worker w is connected to workers $w-1$ and $w+1$, if those exist, and the delays are $\tau_{ij} = |i - j|$. We can then decompose

$$s_w^{(t)} = \sum_{j=1}^n p_j^{(t-\tau_{wj})} = p_w^{(t)} + \underbrace{\sum_{j=1}^{w-1} p_j^{(t-\tau_{wj})}}_{\text{parcels from the 'left'}} + \underbrace{\sum_{j=w+1}^n p_j^{(t-\tau_{wj})}}_{\text{parcels from the 'right'}}.$$

The sum of parcels from the 'left' will be sent as one message $m_{(w-1)\to w}$ from worker $w-1$ to w, and the sum of data from the 'right' will be sent as one message $m_{(w+1)\to w}$ from $w+1$ to w. Neighboring workers can compute these messages from the messages they received from their neighbors in the previous timestep. Compared to typical gossip averaging, RelaySum requires additional memory linear in the number of neighbors, but it uses the same volume of communication.

Algorithm 1 shows how this scheme is generalized to general tree networks and incorporated into RelaySGD. Along with the model parameters, we send scalar counters that are used in the first few iterations of the algorithm $t \leq \tau_{\max}$ to correct for messages that have not yet arrived.

Spanning trees   RelaySGD is formulated on tree networks, but it can be used on any communication graph by constructing a spanning tree. In a truly decentralized setting, we can use the Spanning Tree Protocol [26] used in Ethernet to find such trees in a decentralized fashion. The protocol elects a leader as the root of the tree, after which every other node finds the fastest path to this leader.

On the other hand, when the decentralized paradigm is used in a data center to reduce communication, we opt for double binary trees [29] used in MPI and NCCL [8]. The key idea of double binary trees is to use two different communication topologies for different parts of the model. We communicate odd coordinates using a balanced binary tree A, and communicate the even coordinates with a

145 complimentary tree B. The trees A and B are chosen such that internal nodes (with 3 edges) in one
146 tree are leaves (with only 1 edge) in the other. Using the combination of two trees, RelaySGD requires
147 only constant extra memory equivalent to at most 2 model copies (just like the Adam optimizer [13]),
148 and it sends and receives the equivalent of 2 models (just like on a ring).

4 Theoretical analysis

150 Since RelaySGD updates worker's models at time step $t+1$ using models from (at most) the past $\tau_{\max}$
151 steps, we conveniently reformulate RelaySGD in the following way: Let $\mathbf{Y}^{(t)}, \mathbf{G}^{(t)} \in \mathbb{R}^{n(\tau_{\max}+1)\times d}$
152 denote stacked worker models and gradients whose row vectors at index $n\cdot\tau+i$ represent

$$\left[\mathbf{Y}^{(t)}\right]_{n\tau+i}^{\top} = \begin{cases} \mathbf{x}_i^{(t-\tau)} & t \geq \tau \\ \mathbf{x}^{(0)} & \text{otherwise} \end{cases}, \qquad \left[\mathbf{G}^{(t)}\right]_{n\tau+i}^{\top} = \begin{cases} \nabla F_i(\mathbf{x}_i^{(t-\tau)}; \xi_i^{(t-\tau)}) & t \geq \tau \\ \mathbf{x}^{(0)} & \text{otherwise} \end{cases}$$

153 for all times $t \geq 0$, delay $\tau \in [0, \tau_{\max}]$ and worker $i \in [n]$. Then (RelaySGD) can be written as

$$\mathbf{Y}^{(t+1)} = \mathbf{W}\mathbf{Y}^{(t)} - \gamma\tilde{\mathbf{W}}\mathbf{G}^{(t)}$$

154 where $\mathbf{W}, \tilde{\mathbf{W}} \in \mathbb{R}^{n(\tau_{\max}+1)\times n(\tau_{\max}+1)}$ are non-negative matrices whose elements are

$$[\mathbf{W}]_{n\tau+i,n\tau'+j} = \begin{cases} \frac{1}{n} & \tau = 0 \text{ and } \tau' = \tau_{ij} \\ 1 & i = j \text{ and } \tau = \tau'+1 \\ 0 & \text{otherwise} \end{cases}, \qquad \left[\tilde{\mathbf{W}}\right]_{n\tau+i,n\tau'+j} = \begin{cases} \frac{1}{n} & \tau = 0 \text{ and } \tau' = \tau_{ij} \\ 0 & \text{otherwise} \end{cases}$$

155 for all $\tau, \tau' \in [0, \tau_{\max}]$ and $i, j \in [n]$. The matrix $\mathbf{W}$ is row stochastic and its largest eigenvalue is 1.
156 The vector of all ones $\mathbf{1}_{n(\tau_{\max}+1)} \in \mathbb{R}^{n(\tau_{\max}+1)}$ is a right eigenvector of $\mathbf{W}$ and let $\boldsymbol{\pi} \in \mathbb{R}^{n(\tau_{\max}+1)}$
157 be the left eigenvector such that $\boldsymbol{\pi}^{\top}\mathbf{1}_{n(\tau_{\max}+1)} = 1$.

158 We characterize the convergence rate of the consensus distance in the following key lemma:

159 **Lemma 1** (Key lemma). *There exists an integer $m = m(\mathbf{W}) > 0$ such that for any $\mathbf{X} \in$*
160 $\mathbb{R}^{n(\tau_{\max}+1)\times d}$ *we have*
$$\|\mathbf{W}^m\mathbf{X} - \mathbf{1}\boldsymbol{\pi}^{\top}\mathbf{X}\|^2 \leq (1-p)^{2m}\|\mathbf{X} - \mathbf{1}\boldsymbol{\pi}^{\top}\mathbf{X}\|^2,$$

161 *where $p = \frac{1}{2}(1 - |\lambda_2(\mathbf{W})|)$ is a constant.*

162 All the following optimization convergence results will only depend on the *effective spectral gap*
163 $\rho := \frac{p}{m}$ of $\mathbf{W}$. We empirically observe that $\rho = \Theta(1/n)$ for a variety of network topologies (see
164 Figure 5 in Appendix A).

165 **Remark 2.** *The above key lemma is similar to [15, Assumption 4] for gossip-type averaging with*
166 *symmetric matrices. However, in our case $\mathbf{W}$ is just a row stochastic matrix, and its spectral norm*
167 *$\|\mathbf{W}\|_2 > 1$. In general, the consensus distance can increase after just one single communication*
168 *step (multiplication by $\mathbf{W}$). That is why we need $m > 1$. The proof of the Lemma relies on a*
169 *Perron-Frobenius type theorem, and holds over several steps m instead of a single iteration. It means*
170 *RelaySum defines a consensus algorithm with linear convergence rate which pulls models closer.*

171 Our main convergence results hold under the following common assumptions, as e.g. [15].

172 **Assumption A** (L-smoothness). *For each $i \in [n]$, $F_i(\mathbf{x},\xi) : \mathbb{R}^D \times \Omega_i \to \mathbb{R}$ is differentiable for*
173 *each $\xi \in supp(\mathcal{D}_i)$ and there exists a constant $L \geq 0$ such that for each $\mathbf{x}, \mathbf{y} \in \mathbb{R}^d$, $\xi \in supp(\mathcal{D}_i)$:*

$$\|\nabla F_i(\mathbf{x},\xi) - \nabla F_i(\mathbf{y},\xi)\| \leq L\|\mathbf{x} - \mathbf{y}\|.$$

174 **Assumption B** (Bounded noise). *There exists constants M and $\bar{\sigma}$ such that for all $\mathbf{x}_1, \ldots, \mathbf{x}_n \in \mathbb{R}^d$*

$$\frac{1}{n}\sum_{i=1}^{n} \mathbb{E}_{\xi_i} \|\nabla F_i(\mathbf{x}_i,\xi_i) - \nabla f_i(\mathbf{x}_i)\|_2^2 \leq \bar{\sigma}^2 + \frac{M}{n}\sum_{i=1}^{n} \|\nabla f(\mathbf{x}_i)\|_2^2.$$

175 **Assumption C** (μ-convexity). *For $i \in [n]$, each function $f_i : \mathbb{R}^d \to \mathbb{R}$ is μ-(strongly) convex for*
176 *constant $\mu \geq 0$. That is, $\forall \mathbf{x}, \mathbf{y} \in \mathbb{R}^d$*

$$f_i(\mathbf{x}) - f_j(\mathbf{y}) + \frac{\mu}{2}\|\mathbf{x} - \mathbf{y}\|_2^2 \leq \nabla f_i(\mathbf{x})^{\top}(\mathbf{x} - \mathbf{y}).$$

Theorem I (RelaySGD). *For any target accuracy $\varepsilon > 0$ and an optimal solution $\mathbf{x}^\star$,*

*(**Convex:**) under Assumptions A, B and C with $\mu \geq 0$, it holds that $\frac{1}{T+1} \sum_{t=0}^{T} \left(f(\overline{\mathbf{x}}^{(t)}) - f(\mathbf{x}^\star) \right) \leq \varepsilon$ after*

$$\mathcal{O}\left(\frac{\bar{\sigma}^2}{n\varepsilon^2} + \frac{C\sqrt{L}\bar{\sigma}}{\varepsilon^{3/2}} + \frac{CL}{\varepsilon} \right) R_0^2$$

iterations. Here $\overline{\mathbf{x}}^{(t)} := \boldsymbol{\pi}^\top \mathbf{Y}^{(t)}$ averages past models, $R_0^2 = \|\mathbf{x}^0 - \mathbf{x}^\star\|^2$, and $C = \mathcal{O}(\frac{1}{\rho}\tau_{\max}^{3/2})$.

*(**Non-convex:**) under Assumptions A and B, it holds that $\frac{1}{T+1} \sum_{t=0}^{T} \|\nabla f(\overline{\mathbf{x}}^{(t)})\|^2 \leq \varepsilon$ after*

$$\mathcal{O}\left(\frac{\bar{\sigma}^2}{n\varepsilon^2} + \frac{C\bar{\sigma}}{\varepsilon^{3/2}} + \frac{C}{\varepsilon} \right) LF_0$$

iterations, where $F_0 := f(\overline{\mathbf{x}}^{(0)}) - f(\mathbf{x}^\star)$.

The dominant term in our convergence result, $\mathcal{O}\left(\frac{\bar{\sigma}^2}{n\varepsilon^2}\right)$ matches with the dominant term in the convergence rate of centralized ('all-reduce') mini-batch SGD, and thus can not be improved.

In contrast to other methods, the presented convergence result of RelaySGD is independent of the data heterogeneity ζ^2 in [15, Assumption 3b].

Definition D (Data heterogeneity). *There exists a constant ζ^2 such that $\forall\, i \in [n], \mathbf{x} \in \mathbb{R}^d$*

$$\|\nabla f_i(\mathbf{x}) - \nabla f(\mathbf{x})\|_2^2 \leq \zeta^2 \,.$$

Remark 3. *For convex objectives, Assumptions B and D can be relaxed to only hold at the optimum $\mathbf{x}^\star$. A weaker variant of Assumption A only uses L-smoothness of f_i [15, Assumption 1b].*

Comparing to gossip averaging for convex f_i which has complexity $\mathcal{O}(\frac{\bar{\sigma}^2}{n\varepsilon^2} + (\frac{\zeta}{\rho^2} + \frac{\bar{\sigma}}{\sqrt{\rho}})\frac{\sqrt{L}}{\varepsilon^{3/2}} + \frac{L}{\rho\varepsilon})R_0^2$, our rate for RelaySGD does not depend on ζ^2 and has same leading term $\mathcal{O}(\frac{\bar{\sigma}^2}{n\varepsilon})$ as D^2.

5 Experimental analysis and practical properties

5.1 Effect of network topology

Random quadratics To efficiently investigate the scalability of RelaySGD with respect to the number of workers, and to study the benefits of binary tree topologies over chains, we introduce a family of synthetic functions. We study *random quadratics* with local cost functions $f_i(\mathbf{x}) = \|\mathbf{A}_i\mathbf{x} - \mathbf{b}_i^\top\mathbf{x}\|^2$ to precisely control all constants that appear in our theoretical analysis. The Hessians $\mathbf{A}_i$ are initialized randomly, and their spectrum is scaled to achieve a desired smoothness L and strong convexity μ. The offsets $\mathbf{b}_i$ ensure a desired level of heterogeneity ζ^2 and distance between optimum and initialization r_0. Appendix B.4 describes the generation of these quadratics in detail.

Scalability on rings and trees Using these quadratics, Figure 2 studies the number of steps required to reach a suboptimality $f(\bar{\mathbf{x}}) - f(\mathbf{x}^\star) \leq \varepsilon$ with tuned constant learning rates. On *ring* topologies with uniform (1/3) gossip weights (and chains for RelaySum), all compared methods require steps at least linear in the number of workers to reach the target quality. RelaySGD and D^2 empirically scale significantly better than Gradient Tracking, these methods are all independent of data heterogeneity. On a *balanced binary tree network* with Metropolis-Hastings weights [35], both D^2 and Gradient Tracking notably do not scale better than on a ring, while RelaySGD on these trees requires only a number of steps logarithmic in the number of workers. SGP with their time-varying exponential topology scales well, too, but it requires more steps on more heterogeneously distributed data.

5.2 Spanning trees compared to other topologies

RelaySGD cannot utilize all available edges in arbitrary networks to communicate, but is restricted to a spanning tree of the graph. We empirically find that this restriction is not limiting. In Figure 3, we take an organic social network topology based on the Davis Southern Women graph [2] from NetworkX [5], and construct random spanning trees found by the Spanning Tree Protocol [26]. On any such spanning tree, RelaySGD optimizes random heterogeneous quadratics as fast as D^2 on the full graph with Metropolis-Hastings weights [35], significantly faster than DP-SGD.

For decentralized learning used in a fully-connected data center for communication efficiency, the deep learning experiments below show that RelaySGD on double binary trees outperforms the most popular non-tree-based communication scheme used in decentralized deep learning [1].

Figure 2: Time required to optimize random quadratics ($\sigma^2 = 0, r_0 = 10, L = 1, \mu = 0.5$) to suboptimality $\leq 10^{-6}$ with varying numbers of workers with tuned constant learning rates. On a ring (- - -), ■ D^2 and ■ RelaySGD require steps linear in the number of workers, and this number is *independent of the data heterogeneity*. RelaySGD reduces this to $\log n$ on a balanced tree topology (——), but trees do not improve ■ D^2 or ■ Gradient Tracking. For ■ SGP with time-varying exponential topology (⋯⋯), the number of steps does not consistently grow with more workers, but this number becomes higher with more heterogeneity (left v.s. right plot).

Figure 3: Performance of ■ RelaySGD on spanning trees of the Social Network graph (32 nodes) found using Spanning Tree Protocol, compared to ■ DP-SGD and ■ D^2 on the full network. Solid lines (——) indicate spanning trees while dashed lines (- - -) indicate the full graph. The figure on the right shows one spanning tree on top of the original network. Learning rates are tuned to reach suboptimality $\leq 10^{-5}$ on random quadratics ($\zeta^2 = 0.1, \sigma^2 = 0.1, r_0 = 1, L = 1, \mu = 0.5$). ■ RelaySGD on spanning trees converges as fast as ■ D^2 on the full network, while the total communication on spanning trees is smaller than on the full graph.

5.3 Effect of data heterogeneity in decentralized deep learning

We study the performance of RelaySGD in deep-learning based image- and text classification. While the algorithm is theoretically independent of dissimilarities in training data, other methods (D^2, RelaySGD/Grad) that have the same property often lose accuracy in the presence of high data heterogeneity [18]. To study the dependence of RelaySGD in practical deep learning, we partition training data strictly across 16 workers and distribute the classes using a Dirichlet process [41, 18]. The Dirichlet parameter α controls the heterogeneity of the data across workers.

We compare RelaySGD against the methods listed in Table 1. DP-SGD [17] is the most natural combination of SGD with gossip averaging, and we chose D^2 [31] to represent the class of previous work that is theoretically robust to heterogeneity. We extend D^2 to allow varying step sizes and local momentum, according to Appendix D.4, and make it suitable for practical deep learning. Although Stochastic Gradient Push [1] is not theoretically independent of data heterogeneity, it is a popular choice in the data center setting, where they use a time-varying exponential scheme on 2^d workers that mixes exactly uniformly in d rounds (Appendix D.6). We also compare to DP-SGD with quasi-global momentum [18], a practical method recently introduced to increase robustness to heterogeneous data.

Table 2 evaluates RelaySGD in the fully-connected data center setting where we limit the communication budget per iteration to two models. We use 16-workers on Cifar-10, following the experimental details outlined in Appendix B and hyper-parameter tuning procedure from Appendix C. RelaySGD communicates over double binary tree topologies, as described in section 3. We compare against the time-varying exponential scheme of Stochastic Gradient Push (SGP) [1], and for D^2 and DP-SGD,

Table 1: Algorithms compared. We compare to D^2 as a representative gossip-based algorithm that is theoretically independent of data heterogeneity, as it is fast in our synthetic experiments, and uses less communication per iteration than methods like Gradient Tracking. We compare to SGP for their time-varying exponential topology, an efficient communication scheme unsupported by RelaySum. The combination of DP-SGD and time-varying exponential topologies is almost equivalent to SGP.

Algorithm (baseline)		Independent of heterogeneity	Topologies considered (best in bold)
All-reduce		Yes	fully-connected
RelaySGD	(ours)	Yes	chain, **double binary tree**
DP-SGD	Lian et al. [17]	No	**ring**, double binary tree
(+quasi-global-momentum)	Lin et al. [18]	No	**ring**, double binary tree
D^2	Lian et al. [17]	Yes	**ring**, double binary trees
Stochastic Gradient Push (SGP)	Assran et al. [1]	No	**time-varying exponential** [1]

Table 2: Cifar-10 [16] test accuracy with the VGG-11 architecture. We vary the data heterogeneity α [18] between 16 workers. Each method sends/receives 2 models per iteration. We use a ring topology for DP-SGD and D^2 because they perform better on rings than on trees. RelaySum with momentum achieves the best results across all levels of data heterogeneity.

Algorithm	Topology	$\alpha = 1.00$ (most homogeneous)	$\alpha = 0.1$	$\alpha = .01$ (most heterogeneous)
All-reduce (baseline)	fully connected	87.0%	87.0%	87.0%
+momentum		90.2%	90.2%	90.2%
RelaySGD	binary trees	87.4%	86.9%	84.6%
+local momentum		90.2%	89.5%	89.1%
DP-SGD [17]	ring	87.4%	79.9%	53.9%
+quasi-global mom. [18]		89.5%	84.8%	63.3%
D^2 [31]	ring	87.2%	84.0%	38.2%
+local momentum		88.2%	88.5%	61.0%
Stochastic gradient push [1]	time-varying exponential [1]	87.4%	86.7%	86.7%
+local momentum		89.5%	89.2%	87.5%

we use ring topologies, because they perform better on rings than trees (c.f. Appendix E.1). Because SGP normally sends/receives only one model per communication round, we execute two synchronous communication steps per gradient update, increasing its latency. We opt for model architectures without BatchNorm [7]. BatchNorm poses particular challenges to data heterogeneity, and the search for alternatives is an active, and orthogonal, area of research [19].

Even though RelaySGD does not use a time-varying topology, it performs as well as or better than SGP, and RelaySGD with momentum suffers minimal accuracy loss up to heterogeneity $\alpha = 0.01$, a level higher than considered in previous work [18]. While D^2 is theoretically independent of data heterogeneity, and while some of its random repetitions yield good results, it is unstable in the very heterogeneous setting. Moreover, Figure 4 shows that workers with RelaySGD achieve high test accuracies quicker during training than with other algorithms.

These findings are confirmed on ImageNet [3] with the ResNet-20-EvoNorm architecture [19] in Table 3. On the BERT fine-tuning task from [18], Table 4 demonstrates that RelaySGD with the Adam optimizer, customary for such NLP tasks, outperforms all compared algorithms.

Figure 4: Test accuracy during training of 16 workers with heterogeneous data ($\alpha = 0.01$) on Cifar-10. Like, with the ■ all-reduce baseline, all workers in ■ RelaySGD on double binary trees quickly reach good accuracy, while this takes longer for ■ SGP with time-varying exponential topology and ■ D^2 on a ring. ■ DP-SGD does not reach good accuracy with such heterogeneous data.

Table 3: Test accuracies on ImageNet, using 16 workers with heterogeneous data ($\alpha = 0.1$). Even when communicating over a simple chain network, RelaySGD performs similarly to SGP with their time-varying exponential communicating scheme. Methods use default learning rates (Appendix C.2).

Algorithm	Topology	Top-1 Accuracy
Centralized (baseline)	fully-connected	69.7%
RelaySGD w/ momentum	double binary trees	60.0%
DP-SGD [17] w/ quasi-global momentum [18]	ring	55.8%
D^2 [31] w/ momentum	ring	diverged at epoch 65, at 49.5%
SGP [1] w/ momentum	time-varying exponential [1]	58.5%

Algorithm	Topology	Top-1 Accuracy
Centralized Adam	fully-connected	94.2% ± 0.1%
Relay-Adam	chain	93.2% ± 0.1%
DP-SGD Adam	ring	87.3% ± 0.6%
Quasi-global Adam [18]	ring	88.3% ± 0.7%

Table 4: DistilBERT [30] fine-tuning on AG news data [43] using 16 nodes in a ring with heterogeneous data ($\alpha = 0.1$). Transformers are usually trained with Adam, and RelaySGD naturally supports Adam updates. (Appendix B.3).

5.4 Robustness to unreliable communication

Peer-to-peer applications are a central use case for decentralized learning. Decentralized learning algorithms must therefore be robust to workers joining and leaving, and to unreliable communication between workers. Gossip averaging naturally features such robustness, but for methods like D^2, that correct for local data biases, achieving such robustness is non-trivial. As a proxy for these challenges, in Table 5, we verify that RelaySGD can tolerate randomly dropped messages. The algorithm achieves this by reliably counting the number of models summed up in each message. For this experiment, we use an extended version of Algorithm 1, where line 10 is replaced by

$$\mathbf{x}_i^{(t+1)} = \tfrac{1}{n}\Big(\mathbf{x}_i^{(t+1/2)} + \textstyle\sum_{j \in \mathcal{N}_i} \mathbf{m}_{j \to i}^{(t)} + (n - \bar{n}_i^{(t+1)})\mathbf{x}_i^{(t)}\Big). \tag{1}$$

We count the number of models received as $\bar{n}$, and substitute any missing models ($< n$) by the previous state $\mathbf{x}_i^{(t)}$. RelaySGD trains reliably to good test accuracy with up to 10% deleted messages. This behavior is on par with a similarly modified SGP [1] that corrects for missing energy. In contrast, D^2 and DP-SGD with quasi-global momentum are unstable with undelivered messages.

6 Conclusion

Decentralized learning has great promise as a building block in the democratization of deep learning. Deep learning relies on large datasets, and while large companies can afford those, many individuals together can, too. Of course, their data does not follow the exact same distribution, calling for robustness of decentralized learning algorithms to data heterogeneity. Algorithms with this property have been proposed and analyzed theoretically, but they do not always perform well in deep learning.

In this paper, we propose RelaySGD for distributed optimization over decentralized networks with heterogeneous data. Unlike algorithms based on gossip averaging, RelaySGD *relays* models through spanning trees of a network without decaying their magnitude. This yields an algorithm that is both theoretically independent of data heterogeneity, but also high performing in actual deep learning tasks. With its demonstrated robustness to unreliable communication, RelaySGD makes an attractive choice for peer-to-peer deep learning and applications in large-scale data centers.

Table 5: Robustness to unreliable networks. On Cifar-10/VGG-11 with 16 workers and heterogeneous data ($\alpha = 0.01$), we compare momentum versions of the best-performing algorithms from Table 2. RelaySGD with the robust update rule 1 can tolerate up to 10% dropped messages and converge to full test accuracy. Only SGP with the time-varying exponential scheme shares this property.

Algorithm	Topology	Reliable network	1% dropped messages	10% dropped messages
RelaySGD w/ momentum	trees	89.2%	89.3%	89.3%
DP-SGD [17] w/ quasi-global mom. [18]	ring	69.3%	diverges	diverges
D^2 [31] w/ momentum	ring	87.4%	diverges	diverges
SGP [1] w/ momentum	time-varying	88.5%	88.6%	88.1%

References

[1] Mahmoud Assran, Nicolas Loizou, Nicolas Ballas, and Michael G. Rabbat. Stochastic gradient push for distributed deep learning. In Kamalika Chaudhuri and Ruslan Salakhutdinov, editors, *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, volume 97 of *Proceedings of Machine Learning Research*, pages 344–353. PMLR, 2019. URL http://proceedings.mlr.press/v97/assran19a.html.

[2] Allison Davis, Burleigh Bradford Gardner, and Mary R Gardner. *Deep South: A social anthropological study of caste and class*. Univ of South Carolina Press, 1930.

[3] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pages 248–255. Ieee, 2009.

[4] Leonidas Georgopoulos. *Definitive Consensus for Distributed Data Inference*. PhD thesis, EPFL, 2011.

[5] Aric Hagberg, Pieter Swart, and Daniel S Chult. Exploring network structure, dynamics, and function using NetworkX. Technical report, Los Alamos National Lab.(LANL), Los Alamos, NM (United States), 2008.

[6] Julien M. Hendrickx, Raphaël M. Jungers, Alexander Olshevsky, and Guillaume Vankeerberghen. Graph diameter, eigenvalues, and minimum-time consensus. *Automatica*, 50(2):635–640, 2014. doi: https://doi.org/10.1016/j.automatica.2013.11.034. URL https://www.sciencedirect.com/science/article/pii/S0005109813005517.

[7] Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In Francis R. Bach and David M. Blei, editors, *Proceedings of the 32nd International Conference on Machine Learning, ICML 2015, Lille, France, 6-11 July 2015*, volume 37 of *JMLR Workshop and Conference Proceedings*, pages 448–456. JMLR.org, 2015. URL http://proceedings.mlr.press/v37/ioffe15.html.

[8] Sylvain Jeaugey. Massively scale your deep learning training with NCCL 2.4. https://devblogs.nvidia.com/massively-scale-deep-learning-training-nccl-2-4/, 2019. [Online; accessed 21-May-2019].

[9] B. Johansson, M. Rabi, and M. Johansson. A randomized incremental subgradient method for distributed optimization in networked systems. *SIAM Journal on Optimization*, 20(3):1157–1170, 2010. doi: 10.1137/08073038X. URL https://doi.org/10.1137/08073038X.

[10] Björn Johansson, Maben Rabi, and Mikael Johansson. A randomized incremental subgradient method for distributed optimization in networked systems. *SIAM J. Optim.*, 20(3):1157–1170, 2009. doi: 10.1137/08073038X. URL https://doi.org/10.1137/08073038X.

[11] Peter Kairouz, H. Brendan McMahan, Brendan Avent, Aurélien Bellet, Mehdi Bennis, Arjun Nitin Bhagoji, Keith Bonawitz, Zachary Charles, Graham Cormode, Rachel Cummings, Rafael G. L. D'Oliveira, Salim El Rouayheb, David Evans, Josh Gardner, Zachary Garrett, Adrià Gascón, Badih Ghazi, Phillip B. Gibbons, Marco Gruteser, Zaïd Harchaoui, Chaoyang He, Lie He, Zhouyuan Huo, Ben Hutchinson, Justin Hsu, Martin Jaggi, Tara Javidi, Gauri Joshi, Mikhail Khodak, Jakub Konecný, Aleksandra Korolova, Farinaz Koushanfar, Sanmi Koyejo, Tancrède Lepoint, Yang Liu, Prateek Mittal, Mehryar Mohri, Richard Nock, Ayfer Özgür, Rasmus Pagh, Mariana Raykova, Hang Qi, Daniel Ramage, Ramesh Raskar, Dawn Song, Weikang Song, Sebastian U. Stich, Ziteng Sun, Ananda Theertha Suresh, Florian Tramèr, Praneeth Vepakomma, Jianyu Wang, Li Xiong, Zheng Xu, Qiang Yang, Felix X. Yu, Han Yu, and Sen Zhao. Advances and open problems in federated learning. *arXiv*, abs/1912.04977, 2019. URL http://arxiv.org/abs/1912.04977.

[12] David Kempe, Alin Dobra, and Johannes Gehrke. Gossip-based computation of aggregate information. In *44th Symposium on Foundations of Computer Science (FOCS 2003), 11-14 October 2003, Cambridge, MA, USA, Proceedings*, pages 482–491. IEEE Computer Society, 2003. doi: 10.1109/SFCS.2003.1238221. URL https://doi.org/10.1109/SFCS.2003.1238221.

[13] Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In Yoshua Bengio and Yann LeCun, editors, *3rd International Conference on Learning Representations, ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Conference Track Proceedings*, 2015. URL http://arxiv.org/abs/1412.6980.

[14] Chih-Kai Ko. *On Matrix Factorization and Scheduling forFinite-time Average-consensus*. PhD thesis, California Institute of Technology, 2010.

[15] Anastasia Koloskova, Nicolas Loizou, Sadra Boreiri, Martin Jaggi, and Sebastian U. Stich. A unified theory of decentralized SGD with changing topology and local updates. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, volume 119 of *Proceedings of Machine Learning Research*, pages 5381–5393. PMLR, 2020. URL http://proceedings.mlr.press/v119/koloskova20a.html.

[16] Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

[17] Xiangru Lian, Ce Zhang, Huan Zhang, Cho-Jui Hsieh, Wei Zhang, and Ji Liu. Can decentralized algorithms outperform centralized algorithms? A case study for decentralized parallel stochastic gradient descent. In Isabelle Guyon, Ulrike von Luxburg, Samy Bengio, Hanna M. Wallach, Rob Fergus, S. V. N. Vishwanathan, and Roman Garnett, editors, *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, 4-9 December 2017, Long Beach, CA, USA*, pages 5330–5340, 2017. URL http://papers.nips.cc/paper/7117-can-decentralized-algorithms-outperform-centralized-algorithms-a-case-study-for-decentralized-par

[18] Tao Lin, Sai Praneeth Karimireddy, Sebastian U. Stich, and Martin Jaggi. Quasi-global momentum: Accelerating decentralized deep learning on heterogeneous data. *CoRR*, abs/2102.04761, 2021. URL https://arxiv.org/abs/2102.04761.

[19] Hanxiao Liu, Andy Brock, Karen Simonyan, and Quoc Le. Evolving normalization-activation layers. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin, editors, *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. URL https://proceedings.neurips.cc/paper/2020/hash/9d4c03631b8b0c85ae08bf05eda37d0f-Abstract.html.

[20] Paolo Di Lorenzo and Gesualdo Scutari. Next: In-network nonconvex optimization. *IEEE Transactions on Signal and Information Processing over Networks*, 2(2):120–136, 2016. doi: 10.1109/TSIPN.2016.2524588.

[21] Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Agüera y Arcas. Communication-efficient learning of deep networks from decentralized data. In Aarti Singh and Xiaojin (Jerry) Zhu, editors, *Proceedings of the 20th International Conference on Artificial Intelligence and Statistics, AISTATS 2017, 20-22 April 2017, Fort Lauderdale, FL, USA*, volume 54 of *Proceedings of Machine Learning Research*, pages 1273–1282. PMLR, 2017. URL http://proceedings.mlr.press/v54/mcmahan17a.html.

[22] A. Nedić and A. Ozdaglar. Distributed subgradient methods for multi-agent optimization. *IEEE Transactions on Automatic Control*, 54(1):48–61, 2009.

[23] Angelia Nedic. Distributed gradient methods for convex machine learning problems in networks: Distributed optimization. *IEEE Signal Process. Mag.*, 37(3):92–101, 2020. URL https://ieeexplore.ieee.org/abstract/document/9084356.

[24] Angelia Nedic and Alex Olshevsky. Stochastic gradient-push for strongly convex functions on time-varying directed graphs. *IEEE Trans. Autom. Control.*, 61(12):3936–3947, 2016. doi: 10.1109/TAC.2016.2529285. URL https://doi.org/10.1109/TAC.2016.2529285.

[25] Angelia Nedic, Alex Olshevsky, and Wei Shi. Achieving geometric convergence for distributed optimization over time-varying graphs. *SIAM J. Optim.*, 27(4):2597–2633, 2017. doi: 10.1137/16M1084316. URL https://doi.org/10.1137/16M1084316.

[26] Radia J. Perlman. An algorithm for distributed computation of a spanningtree in an extended LAN. In William Lidinsky and Bart W. Stuck, editors, *SIGCOMM '85, Proceedings of the Ninth Symposium on Data Communications, British Columbia, Canada, September 10-12, 1985*, pages 44–53. ACM, 1985. doi: 10.1145/319056.319004. URL https://doi.org/10.1145/319056.319004.

[27] Shi Pu and Angelia Nedic. Distributed stochastic gradient tracking methods. *CoRR*, abs/1805.11454, 2018. URL http://arxiv.org/abs/1805.11454.

[28] Shi Pu, Wei Shi, Jinming Xu, and Angelia Nedic. Push-pull gradient methods for distributed optimization in networks. *IEEE Trans. Autom. Control.*, 66(1):1–16, 2021. doi: 10.1109/TAC.2020.2972824. URL https://doi.org/10.1109/TAC.2020.2972824.

[29] Peter Sanders, Jochen Speck, and Jesper Larsson Träff. Two-tree algorithms for full bandwidth broadcast, reduction and scan. *Parallel Comput.*, 35(12):581–594, 2009. doi: 10.1016/j.parco.2009.09.001. URL https://doi.org/10.1016/j.parco.2009.09.001.

[30] Victor Sanh, Lysandre Debut, Julien Chaumond, and Thomas Wolf. Distilbert, a distilled version of BERT: smaller, faster, cheaper and lighter. *CoRR*, abs/1910.01108, 2019. URL http://arxiv.org/abs/1910.01108.

[31] Hanlin Tang, Xiangru Lian, Ming Yan, Ce Zhang, and Ji Liu. D^2: Decentralized training over decentralized data. In Jennifer G. Dy and Andreas Krause, editors, *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, volume 80 of *Proceedings of Machine Learning Research*, pages 4855–4863. PMLR, 2018. URL http://proceedings.mlr.press/v80/tang18a.html.

[32] Konstantinos I Tsianos, Sean Lawlor, and Michael G Rabbat. Push-sum distributed dual averaging for convex optimization. In *2012 ieee 51st ieee conference on decision and control (cdc)*, pages 5453–5458. IEEE, 2012.

[33] Chenguang Xi and Usman A. Khan. DEXTRA: A fast algorithm for optimization over directed graphs. *IEEE Trans. Automat. Contr.*, 62(10):4980–4993, 2017. doi: 10.1109/TAC.2017.2672698. URL https://doi.org/10.1109/TAC.2017.2672698.

[34] Chenguang Xi, Van Sy Mai, Ran Xin, Eyad H. Abed, and Usman A. Khan. Linear convergence in optimization over directed graphs with row-stochastic matrices. *IEEE Trans. Autom. Control.*, 63(10):3558–3565, 2018. doi: 10.1109/TAC.2018.2797164. URL https://doi.org/10.1109/TAC.2018.2797164.

[35] Lin Xiao and Stephen P. Boyd. Fast linear iterations for distributed averaging. *Syst. Control. Lett.*, 53(1):65–78, 2004. doi: 10.1016/j.sysconle.2004.02.022. URL https://doi.org/10.1016/j.sysconle.2004.02.022.

[36] Ran Xin and Usman A Khan. A linear algorithm for optimization over directed graphs with geometric convergence. *IEEE Control Systems Letters*, 2(3):315–320, 2018.

[37] Ran Xin and Usman A Khan. Distributed heavy-ball: A generalization and acceleration of first-order methods with gradient tracking. *IEEE Transactions on Automatic Control*, 65(6):2627–2633, 2019.

[38] Ran Xin, Chenguang Xi, and Usman A. Khan. FROST - fast row-stochastic optimization with uncoordinated step-sizes. *EURASIP J. Adv. Signal Process.*, 2019:1, 2019. doi: 10.1186/s13634-018-0596-y. URL https://doi.org/10.1186/s13634-018-0596-y.

[39] Kun Yuan, Bicheng Ying, Xiaochuan Zhao, and Ali H. Sayed. Exact diffusion for distributed optimization and learning - part I: algorithm development. *IEEE Trans. Signal Process.*, 67(3):708–723, 2019. doi: 10.1109/TSP.2018.2875898. URL https://doi.org/10.1109/TSP.2018.2875898.

[40] Kun Yuan, Yiming Chen, Xinmeng Huang, Yingya Zhang, Pan Pan, Yinghui Xu, and Wotao Yin. Decentlam: Decentralized momentum SGD for large-batch deep training. *CoRR*, abs/2104.11981, 2021. URL https://arxiv.org/abs/2104.11981.

[41] Mikhail Yurochkin, Mayank Agarwal, Soumya Ghosh, Kristjan H. Greenewald, Trong Nghia Hoang, and Yasaman Khazaeni. Bayesian nonparametric federated learning of neural networks. In Kamalika Chaudhuri and Ruslan Salakhutdinov, editors, *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, volume 97 of *Proceedings of Machine Learning Research*, pages 7252–7261. PMLR, 2019. URL http://proceedings.mlr.press/v97/yurochkin19a.html.

[42] Jiaqi Zhang and Keyou You. Decentralized stochastic gradient tracking for non-convex empirical risk minimization, 2020.

[43] Xiang Zhang, Junbo Jake Zhao, and Yann LeCun. Character-level convolutional networks for text classification. In Corinna Cortes, Neil D. Lawrence, Daniel D. Lee, Masashi Sugiyama, and Roman Garnett, editors, *Advances in Neural Information Processing Systems 28: Annual Conference on Neural Information Processing Systems 2015, December 7-12, 2015, Montreal, Quebec, Canada*, pages 649–657, 2015. URL https://proceedings.neurips.cc/paper/2015/hash/250cf8b51c773f3f8dc8b4be867a9a02-Abstract.html.