FACS: Fast Adaptive Channel Squeezing

Abstract

Channel squeezing is one of the central operations performed in CNN bottlenecks to reduce the number of channels in a feature map. This operation is carried out by using a 1×1 pointwise convolution which constitutes a significant amount of computations and parameters in a given network. ResNet-50 for instance, consists of 16 such layers which form 33% of total layers and 25% (1.05B/4.12B) of total FLOPs or computations. In the light of their predominance, we propose a novel "Fast Adaptive Channel Squeezing" module which carries out the squeezing operation in a computationally efficient manner. The key benefit of FACS is that it neither alters the number of parameters nor affects the accuracy of a given network. When plugged into diverse CNNs architectures, namely ResNet, VGG, and MobileNet-v2, FACS achieves state-of-the-art performance on ImageNet and CIFAR datasets at dramatically reduced FLOPs. FACS also cuts the training time significantly, and lowers the latency which is particularly advantageous for fast inference on edge devices. The source-code will be made publicly available.

1 Introduction

ResNet (5) is the most spectacular accomplishment of the last decade in the field of CNNs (12; 22; 9), spawning a lot of intriguing architectures (18; 16; 23). It employs a tri-convolution layered squeeze-expand unit, in which the first layer (squeeze, 1×1) reduces the channel count by a factor $\mathcal{R}$ while the third layer (expand, 1×1) performs the reverse operation. The middle layer (context extraction, 3×3), on the other hand maintains the channel count, and governs the network's receptive field.

Interestingly, in ResNet like designs, we observe a key structural properties that the squeeze and the expand layers dominate in the number as well as in the computations, and do not contribute to a network's receptive field due to their pointwise nature. For instance, ResNet-50 consists of 32 such layers out of 50 total layers, accounting for $\sim 54\%$ (2.23B/4.12B) of overall FLOPs, whereas ResNet-101 consists of 66 of them out of 101, accounting for $\sim 50\%$ (3.98B/7.85B) of total FLOPs.

As ResNet, VGG style networks are still dominant in both academia and industry (1; 13; 3; 14) due to their architectural simplicity, customizability, and high representation in contrast to newer complex networks (23), the preceding observations compel us to ask a naturally arising question: can computations in 1×1 layers be reduced without sacrificing network accuracy or parameters ? If so, the inference of such networks can be significantly accelerated on state-of-the-art edge devices, benefiting a whole spectrum of applications such as autonomous driving, robotics, and so on.

In this paper, we contribute by showing that indeed it is possible by examining the functioning of squeeze layer through the lens of computational complexity. To this end, we propose a novel "fast adaptive channel squeezing" (FACS) module that transforms a feature map $\mathbf{X} \in \mathbb{R}^{C \times H \times W}$ to another feature map $\mathbf{Y} \in \mathbb{R}^{\frac{C}{\mathcal{R}} \times H \times W}$, mimicking the functionality of a squeeze layer but with fewer computations, while retaining a network's parameters and its accuracy. FACS has been crafted by leveraging many state-of-the-art network design concepts which may individually be found in the literature, however, their aggregation in FACS is entirely novel.

We embed and evaluate FACS module over three different CNN architectures: plain (VGG), residual (ResNet), and mobile-series (MobileNet-v2), and on three datasets: ImageNet, (2), and CIFAR-10, CIFAR-100. We also back FACS with comprehensive ablation study. Since FACS is novel, we also shed light on the intermediate data representations learnt by FACS enhanced network using GradCAM (20), and show that they are better relative to the baselines. FACS brings huge improvements e.g. ResNet-50 becomes $\sim 23\%$ faster along with 0.47% improved accuracy on ImageNet (2), whereas VGG becomes faster by $\sim 6\%$ with 0.23% improved accuracy, without bells and whistles.

Next section deals with the related work. Sec. 3 describes the FACS module, and its integration into different CNNs. Sec. 4 carries solid experiments in support of FACS. Sec. 5, concludes our findings.

2 RELATED WORK

2.1 CONVNETS

The earlier CNN designs (12; 22; 5; 9) are mainly accuracy oriented designs that have grown complex as accuracy has improved. DenseNet (9), for instance, beats ResNet in terms of accuracy and FLOPs but is highly complex due to many branches. Mobile series networks (7; 18; 26; 16) focus on lowering FLOPs for real-time deployment by using depthwise convolutions (21). However these designs suffer from low representation power, and need prolonged training schedule of $200 - 400$ epochs to obtain accuracy comparable to the earlier ones which are typically trained in range of $90 - 120$. In addition, limited representation power hinders their performance on downstream tasks e.g. (7) needs 200 epochs on ImageNet to perform similar to (22) (trained for 75 epochs), but performs poorly on object detection (7). (23) attempts to alleviate this issue by being efficient in parameters and FLOPs, however ends-up being more complex owing to high branching and depth, which makes them memory hungry, sluggish (3). Recent Transformer based methods are still in development and are computationally hungry due to their attention mechanisms (24; 4) which put them out of the reach of edge-devices.

Recent research (19) explores the design space of ResNet to make them more effective. (19) trains several ResNet variants varying in depth, FLOPs, accuracy. Interestingly, (19) models can now compete with (23) like designs while being simpler, which is quite advantageous for edge devices and real-time applications. Similarly, (3) improves the speeds of VGG however its training time design has many branches which is still inferior to ResNet. Furthermore, the approaches such as SENet (8), CBAM (25) propose novel units which when plugged into ResNet, yield improved accuracy at the expense of increased parameters and marginal addition to the computational overhead. The above discussion shows that the older architectures still have a room for improvement, and that real-world applications can benefit from focusing on these areas. Hence, FACS looks for this possibility and indeed proposes further advancements in enhancing the runtime performance of these networks.

2.2 ORTHOGONAL APPROACHES

FACS is entirely orthogonal to the methods such as weight pruning, network compression, network quantization. It is so because these are post training methods which require a priori trained network and are applicable to any network architecture. In contrast, FACS is altogether an architectural enhancement that can also benefit from any of these techniques. However, in this paper, we limit our discussion to the study of FACS in the context to deep networks.

To the best of our knowledge, computationally efficient squeeze operation has not been discussed in the literature, yet the most aligned work we could find is depthwise pooling (10). This method performs pooling in the channel dimension in order to reduce the number of channels. However, it dramatically reduces the number of parameters because the squeeze layers are entirely eliminated from the network, incurring a severe accuracy loss ($\sim 2\%$).

FACS on the other hand preserves the parameters, and outperforms the baselines in terms of FLOPs, throughput, latency. FACS also attains better accuracy however that is not our goal unlike (8; 25). We test FACS on VGG (22), ResNet (5), MobileNet-v2 (18). Although FACS can also be equipped in (19), however, we only study ResNet variants because (19) is essentially the ResNet architecture i.e. squeeze-expand, and many existing works are well evaluated on ResNet (27; 6; 1).

3 FACS

Given an input feature map $\mathbf{X} \in \mathbb{R}^{C \times H \times W}$, FACS progressively infers intermediate 1D descriptors $\mathbf{z} \in \mathbb{R}^{C \times 1 \times 1}$, $\mathbf{p} \in \mathbb{R}^{\frac{C}{R} \times 1 \times 1}$, and an output feature map $\mathbf{Y} \in \mathbb{R}^{\frac{C}{R} \times H \times W}$ of reduced dimensionality. FACS can primarily be sectioned into three stages: First, global context aggregation which provides channel-wise global spatial context in form of a 1D descriptor $\mathbf{z}$. Second, cross channel information blending which transforms $\mathbf{z}$ into another descriptor $\mathbf{p}$, referred as adaptive channel fusion probability. Third, channel fusion which utilizes $\mathbf{p}$ and $\mathbf{X}$ in order to produce $\mathbf{Y}$. The overall structure of FACS module is illustrated in Figure 2.

For reference, we have also shown the baseline channel squeezing method in Figure 1. It can be noticed that FACS is substantially different from the baseline counterpart in term of structure. The only component shared between them is the convolution layer, yet the tensors on which it operates are different. Further, FACS commonly employs global pooling, maximum or averaging operations which maybe found in the existing literature, however their use in FACS configuration is entirely novel. For this reason, we term FACS as a novel module to perform fast channel squeezing.

Figure 1: Baseline squeezing.

Figure 2: FACS block. $\sigma(\cdot)$ denotes sigmoid non-linearity.

3.1 GLOBAL CONTEXT AGGREGATION

The first and foremost step of FACS is to gather global spatial context. For this purpose, we employ global average pooling over the per-channel activations of the input feature map $\mathbf{X}$. We apply the operator on $\mathbf{X}$ which results in channel-wise global contextual information in form of a 1D descriptor $\mathbf{z} \in \mathbb{R}^{C \times 1 \times 1}$. In the computations, each element z_i corresponding to i^{th} channel of $\mathbf{z}$ is given by:

$$z_i = \frac{1}{H \times W} \sum_{h \in H, w \in W} X_i(h, w) \tag{1}$$

The use of global pooling in our case is inspired by the fact that it is most frequently employed at the end of the classification networks (5; 9) etc. to aggregate the knowledge of all spatial locations of the final feature map into a 1D descriptor. It is also utilized by (8; 25) to compute spatial statistics.

3.2 CROSS CHANNEL INFORMATION BLENDING

From the previous step, we obtain global context which is limited to a single channel only, therefore the descriptor $\mathbf{z}$ is devoid of cross-channel information. To mitigate the issue, the per-channel global information in $\mathbf{z}$ is now blended with the other channels by using a 1×1 convolution operator. In addition to the blending, the operator also reduces the input number of channels by a factor of $\mathcal{R}$ i.e. number of input channels are reduced from C to $C/\mathcal{R}$. It is important to note that the convolution operator is same as the squeeze layer in Figure 1, but operates only upon a 1D descriptor instead of a 3D tensor. This is where the majority of computation savings occur in FACS relative to the baseline.

Next, the output of the convolution operator is squeezed into a range $\in [0, 1]$ using sigmoidal activation, resulting in a 1D descriptor $\mathbf{p} \in \mathbb{R}^{C/\mathcal{R}}$. We refer the descriptor $\mathbf{p}$ as adaptive channel fusion probability which accommodates both the spatial, and the channel context. Now both the $\mathbf{p}$ and $\mathbf{X}$ are forwarded to the channel fusion stage which yield the final output $\mathbf{Y}$ of the FACS module.

3.3 CHANNEL FUSION

In this stage, the task of channel squeezing of $\mathbf{X}$ is performed in an adaptive and computationally efficient manner. We define two reduction operations: maximum (Max), and average (Avg). During fusion, the input feature map is first virtually partitioned into chunks of $\mathcal{R}$ channels, and then the channels of each chunk are adaptively fused to produce a single channel. In other words, fusion operation results in $C/\mathcal{R}$ output channels, if the number of input channels were C. We devise two strategies to perform this task, as discussed below.

3.3.1 THRESHOLD BASED FUSION

In this strategy, the channels are fused by applying the reduction operator (Max or Avg) at each of the spatial location $\in H \times W$ across $\mathcal{R}$ channels. For any spatial location $(h, w) \in H \times W$, there exist $\mathcal{R}$ scalar values which are reduced to a single scalar by using one of the reduction operator. The selection of the reduction operator is entirely adaptive because it is determined by the fusion probability $\mathbf{p}$, which in turn is learnt by the network itself during the training. In short, as soon as the reduction operator is selected, the values at any given location are fused via the following equations:

$$Y_i(h, w) = \begin{cases} p_i * \mathrm{Max}(X_j(h, w), ..X_{j+\mathcal{R}}(h, w)), & p_i \leq T_{cf} \\ p_i * \mathrm{Avg}(X_j(h, w), ..X_{j+\mathcal{R}}(h, w)), & p_i > T_{cf} \end{cases} \tag{2}$$

where, p_i is the i^{th} element of $\mathbf{p}$, and T_{cf} is channel fusion threshold. This is a hyperparameter which is set to 0.5 based on our ablation study (See Sec. 4). $Y_i(h, w)$ is the value at the (h, w) spatial location of the i^{th} channel in the output feature map $\mathbf{Y}$, $i \in [0, C/\mathcal{R}]$ and $j = \mathcal{R} * i$. A pictorial represntation of this fusion strategy is provided in Figure 3a.

(a)   (b)

Figure 3: **Channel Fusion strategies.** (a) Threshold based fusion, and (b) weighted fusion.

3.3.2 WEIGHTED FUSION

In contrast to the threshold based fusion, this strategy is free of T_{cf}. In this strategy, for any spatial location $(h, w) \in H \times W$, all the $\mathcal{R}$ scalar values are first reduced by using both of the reduction operators separately, and then the resulting values are combined using a weighted sum as given below.

$$Y_i(h, w) = p_i * \text{Max}(X_j(h, w), ..X_{j+k}(h, w)) + (1 - p_i) * \text{Avg}(X_j(h, w), ..X_{j+k}(h, w)) \quad (3)$$

In this strategy, the network itself learns to determine how much contribution should be given to a reduction operator. Due to this flexibility, each location in a chunk can enjoy different combinations of the reduction operators. This is not the case with threshold based fusion. Infact, threshold based fusion becomes a special case of weighted fusion when p_i approaches the two extremas i.e. $\{0, 1\}$. Figure 3b illustrates the weighted fusion strategy.

In both of the above techniques, the use of $\mathbf{p}$ is inspired by the fact that it helps choosing or weighting different reduction operators adaptively based on the input. Without that, all the squeeze layers shall have to be eliminated which will reduce to the case of (10), leading to a heavy accuracy loss (Table 2).

3.4 EFFECT OF FACS ON COMPUTATIONAL COMPLEXITY

In the baseline method, the squeeze layer operates upon $\mathbf{X} \in \mathbb{R}^{C \times H \times W}$ which requires $C/\mathcal{R} \times C \times H \times W$ FLOPs. Whereas in FACS, the global context aggregation requires $C \times H \times W$ FLOPs, cross-channel information blending requires $C/\mathcal{R} \times C$ FLOPs. and channel fusion requires $C/\mathcal{R} \times (\mathcal{R} - 1) \times H \times W$ FLOPs. As an example, for a tensor $\mathbf{X} \in \mathbb{R}^{12 \times 5 \times 5}$, the baseline squeezing method requires 8100 FLOPs whereas FACS requires only 799 and 1054 FLOPs for threshold based and weight fusion respectively. In the similar manner, we achieve huge gains when FACS is plugged into the existing networks which are discussed in the experiments. For the calculation of FLOPs, kindly refer to the supplementary material.

3.5 EFFECT OF FACS ON MEMORY

Despite the computational benefits, FACS does not introduce any memory overhead. The total memory required by the baseline squeeze operation can be given by: #M $= C/4 \times H \times W$. On the other hand, the memory required for FACS is given by: #M $= C + C/4 + C/4 \times H \times W$. We can see that there is negligible increment in the memory footprint i.e. from $0.75 \times C \times H \times W$ to $0.75 \times C \times H \times W + 1.25C$. For an FP32 precision, the raw memory footprint will be $4 \times M$.

3.6 POTENTIAL SIMILARITY WITH EXISTING ORTHOGONAL WORKS

At a first glance, FACS may appear similar to the spectrum of works SE (8) and CBAM (25), primarily because of the involved terms such as global pooling, maximum or averaging. However, this is not the case. In terms of functionality, both of the above methods focus on improving network accuracy by increasing network's parameters while marginally adding to the computational demands. While in terms of structure, new convolution layers are added in both the SE and CBAM which are the reason for the increased parameters. Also, there is no provision of reduction operators in these approaches.

FACS on the other hand, aims at reducing the computations in the channel squeezing operation without compromising the network's parameters and accuracy. In addition, FACS does not involve new convolution layers, rather reuses the parameters of the original squeeze layer while redefining the information flow. These are by far the most visible differences between FACS and (8; 25).

Interestingly, FACS is fully compatible with SE (8) and CBAM (25), and can be paired with any of the two. In order to demonstrate, we train FACS enhanced ResNet-50 with SE units and observe improved performance (See Sec 4). From the above, it is a crucial observation that FACS does not deteriorate the performance of existing modules.

Figure 4: (a) Squeeze expand residual unit, (b) FACS variant, (c) VGG block, (d) VGG-1×1 block, (e) FACS variant, (f) inverted squeeze-expand unit, and (b) FACS varinat.

3.7 FACS INSTANTIATION

FACS-ResNet. We first integrate FACS into residual squeeze-expand unit. Both the baseline and FACS units are shown in Figure 4a, 4b. To enable ResNet with FACS, we replace all the residual units of ResNet with FACS units. We perform this process with ResNet-50, ResNet-101, and ResNet-152 and name the resulting networks as FACS-ResNet-50, FACS-ResNet-101, and FACS-ResNet-152 respectively. For simplicity, batch-norm (11) and ReLU have been dropped from the figures.

FACS-VGG. We also examine the impact of FACS on plain network VGG (22) because of its popularity in robotics and other real-time applications. However, it doesn't have any provision of squeeze layers as the architecture consists only of 3×3 convolution (Figure 4c). Therefore, to accommodate FACS, we insert a 1×1 convolution before each 3×3 convolution layer except the first (Figure 4d)). The purpose of this layer is to function as a squeeze layer which reduces the input channels by a factor of $\mathcal{R}$. We name the resulting model as VGG-1×1 which is enhanced with FACS as shown in Figure 4e.

FACS-MobileNet-v2. Apart from the above, we also analyze the influence of FACS on a mobile series network MobileNet-v2 (18) which employs inverted residual units with depthwise separable convolutions. The baseline inverted residual unit and its FACS enhanced counterpart is illustrated in Figure 4f, 4g.

4 EXPERIMENTS

In this section, we evaluate FACS on ILSVRC'2012 ImageNet (2) dataset for classification task which consists of 1.28M images for training and 50K for validation over 1000 categories. For illustration of transfer learning, we use CIFAR-10 and CIFAR-100 image classification datasets. In addition, we also evaluate FACS onto a downstream task of semantic segmentation against a popular pipeline (27). We first conduct a comprehensive ablation study over FACS design, and then examine the aforementioned three different network architectures enhanced with FACS. We also shed light on the latency improvements over a number of GPUs including edge devices. All the baselines are retrained in PyTorch (17) framework for fair comparison.

Training Specifications. We keep our training procedure straightforward in order to avoid complexities and to ensure reproducibility. We use a batch size of 256 which is split across 8 GPUs. We use a RandomResized crop of 224×224 along with random horizontal flipping (See supplementary material). We use `SGD Nesterov` momentum of 0.9, `base_lr`=0.1 with CosineAnnealing (15), and a weight decay of 0.0001. All models are trained for 120 epochs as in the original paper of ResNet (5) unless otherwise stated.

4.1 ABLATION STUDY

We empirically validate the efficacy of FACS design practices. ResNet-50 is adopted as the baseline for this purpose. We have performed the most pertinent ablations possible with FACS. To begin with, we first analyze the effect of changing the activation function in the cross-channel information blending stage, and then examine the effect of placing a batch normalization layer prior to the sigmoidal activation. Further, we verify the behavior of two different channel fusion strategies, and also the effect of varying fusion threshold T_{cf}. Below we discuss these ablations in detail.

Table 1: Ablation study of FACS-ResNet-50. Top-1 Accuracy on ImageNet.

Ablation	Parameter	Top-1 Accuracy
Fusion Activation	Sigmoid	76.77%
	TanH	76.39%
Batch-Norm	✗	76.77%
	✓	76.44%
T_{cf}	0.0	76.58%
	0.5	76.77%
	1.0	76.54%
Channel Fusion Strategy	Threshold based Fusion (Eq. 2)	76.77%
	Probabilistic Weighted Fusion (Eq. 3)	76.52%

Fusion Activation. The channel fusion stage utilizes the fusion probability $\mathbf{p}$ produced by the sigmoidal layer. Given that the value of $\mathbf{p}$ lies in the interval $[0, 1]$, we wished to examine the behavior of FACS if this range is achieved via a different activation function. For this purpose, we select `TanH` function which natively squeezes the input into a range $[-1, 1]$. Therefore, we rewrite the mathematical expression to $0.5 * (1 + \text{TanH})$ in order to place the output of TanH into the desired range of $[0, 1]$. We replace the sigmoidal activation with the above expression and retrain the network. The corresponding results are shown in the top section of Table 1. The measures reveal that sigmoidal activation is superior to TanH activation for the case of FACS.

BatchNorm in Global Context Aggregation. Out of curiosity, we also analyze the behavior of FACS module by placing a BatchNorm (11) after the 1×1 convolution, because the squeeze layer in the baseline method is also followed by a BatchNorm layer. We observe that BatchNorm negatively impacts the performance (second section, Table 1).

Effect of Fusion Threshold (T_{cf}). The hyperparameter T_{cf} is evaluated against three values $\in \{0.0, 0.5, 1.0\}$. In accordance with the Eq. 2, $T_{cf} = 0$ corresponds to Avg operator, $T_{cf} = 1.0$ corresponds to Max operator regardless of the value of $\mathbf{p}$. Whereas $T_{cf} = 0.5$ offers equal opportunity to the Max and Avg reduction operators which is adaptively taken care of by the value of $\mathbf{p}$. We present an ablation over the aforementioned three values of T_{cf}. The third section of Table 1 holds the corresponding results. It is observable that $T_{cf} = 0.5$ attains the best performance, which is the case when the network has the flexibility to choose between the two reduction operators adaptively. Hence, in the subsequent experiments, we use $T_{cf} = 0.5$ for threshold based fusion. One may argue that there is marginal accuracy difference for different T_{cf} values, so why not use a prefixed operator? As stated earlier in Sec 3.3, in that case $\mathbf{p}$ becomes of no use, and corresponding conv layer will have to be removed, which translates to (10), resulting in loss of parameters and accuracy (Table-2).

Channel Fusion Strategy. We train the network for both of the fusion strategies. Our findings suggest that threshold based fusion is superior to the weighted fusion, as shown in the bottom section of Table 1. Although, the effect is marginal, in the context of implementation, Eq. (2) is easier and faster as compared to Eq. (3). It is because, Eq. (2) requires atmost one operator to be computed based on the value of T_{cf}, whereas Eq. (3) requires both of the operators to be computed.

4.2 IMAGENET CLASSIFICATION

4.2.1 FACS-RESNET

Table 2 shows evaluation of FACS when plugged into ResNet. FACS indeed achieves computationally efficient squeezing, as indicated by the $\sim 23\%$ reduction in FLOPs of all the FACS variants. Though improving the accuracy is not our goal, FACS also boosts the accuracy significantly i.e. 0.47%, 0.45%, 0.44% for FACS-50, 101, and 152 respectively. To our surprise, FACS-ResNet-101 surpasses the baseline ResNet-152 by 0.18% in accuracy and 47% in FLOPs, indicating a huge improvement.

Throughput & Latency. The $\sim 23\%$ FLOPs reduction directly reflects increased throughput as training time reduces from 4 to 2.5 days for ResNet-50, 4 to 3 days for ResNet-101, and 6 to 4 days for ResNet-152 on an $8 \times$ NVIDIA 1080Ti system. Additionally, huge latency improvements are also seen on edge computing devices. Table 3 shows the latency analysis on a number of GPUs with varying compute capabilities. It is done in order to demonstrate the portability of FACS across devices with varying computational power. The first three are high power GPUs among which the first is compute specialized, second and third are gaming GPUs with former powerful than the latter. On the other hand, the last two are edge computing devices which are far less powerful.

Table 2: FACS vs ResNet. FACS is better for a negative 'ΔAcc%' and a positive 'Δ#FLOPS%'.

Architecture	$\mathcal{R}$	#Params	#FLOPs	Top-1	Top-5	ΔAcc%	Δ#FLOPs%
ResNet-50	8	12.3M	1.85B	73.66%	91.59%	−	−
FACS-ResNet-50	8	12.3M	1.39B	74.47%	92.07%	−0.81%	24.8%
DWP-ResNet-50	4	19.6M	2.82B	74.62%	92.10%	−	−
ResNet-50 (5)	4	25.5M	4.12B	76.30%	92.69%	−	−
FACS-ResNet-50	4	25.5M	3.18B	76.77%	93.34%	−0.47%	22.8%
SE-ResNet-50 (8)	4	28.0M	4.13B	76.71%	93.38%	−	−
SE-FACS-ResNet-50	4	28.0M	3.19B	76.95%	93.40%	−0.24%	22.8%
ResNet-101 (5)	4	44.5M	7.85B	77.21%	93.61%	−	−
FACS-ResNet-101	4	44.5M	6.05B	77.96%	93.91%	−0.45%	22.9%
ResNet-152 (5)	4	60.1M	11.58B	77.78%	93.80%	−	−
FACS-ResNet-152	4	60.1M	8.91B	78.12%	94.02%	−0.44%	23.0%

Table 3: Latency analysis of FACS vs ResNet @224×224, FP32 precision, averaged over 25 runs.

Compute Platform	Cores	Compute power	Res-50	FACS-50	Res-101	FACS-101	Res-152	FACS-152
NVIDIA A40	10752	37.00 TFLOPs	7ms	6ms	11ms	10ms	15ms	14ms
NVIDIA RTX2080Ti	4352	13.45 TFLOPs	8ms	6ms	14ms	12ms	17ms	15ms
NVIDIA GTX1080Ti	3584	11.45 TFLOPs	9ms	7ms	13ms	12ms	17ms	15ms
NVIDIA Jetson NX	384	1.000 TFLOPs	48ms	40ms	75ms	64ms	100ms	85ms
NVIDIA Jetson Nano	128	0.235 TFLOPs	140ms	130ms	230ms	200ms	320ms	280ms

The difference in latency is mostly attributed to the variation in the number of computing elements or cores. Theoretically, more cores should run a network faster, however owing to the sequential linking of layers, a layer must wait until preceding ones finish. This causes similar latency for the first three GPUs. However, for such devices, considerable gains are seen during batched inference and training, which is a measure of throughput and, is reflected via days-long reduction in training time.

In contrast, the impact of FACS is more pronounced on edge devices, where the cores are a scarce resource. On Jetson-NX, FACS-50 is 16% faster then ResNet-50, FACS-101 is 14% faster, and FACS-152 is 15% faster. On Jetson-Nano, FACS-50 is 7% faster then ResNet-50, FACS-101 is 13% faster, and FACS-152 is 12% faster. Notably, these speed-ups are huge which can be further enhanced via half-precision (FP16) inference, roughly doubling the speed. Considering the extensive usage of edge devices in real-time applications, the aforementioned enhancements are quite advantageous.

Reduction Ratio ($\mathcal{R}$). It is important to note that the reduction ratio $\mathcal{R}$ is not a hyperparameter of FACS. It can be a potential source of confusion when discussing (8; 25) which employ two reduction ratios: one for the squeeze layer ($\mathcal{R}$) and one for the SE or CBAM modules (r). The value of $\mathcal{R}$ is independent of the FACS, SE or CBAM since it is the hyperparameter of the baseline ResNet where it is set to 4. Likewise, $\mathcal{R}$ is also set to 4 in the FACS variants. On the other hand, the reduction ratio r is set to 16 in the SE unit of (8) and the shared MLP of the (25), but is irrelevant to FACS.

Although ablation on $\mathcal{R}$ is out of scope of this paper, yet we examine the impact of varying $\mathcal{R}$ on the performance of ResNet and FACS variants. To evaluate, we perform an additional experiment by setting $\mathcal{R} = 8$ whose outcomes are displayed in Table 2. It can be noticed that with $\mathcal{R} = 8$, FACS-ResNet performs better by $\sim 0.81\%$ with almost 25% lesser FLOPs which is huge in itself. In addition, the accuracy gap between ResNet for $\mathcal{R} = 4$ and $\mathcal{R} = 8$ is 2.64%, while this gap reduces to 2.30% for FACS at significant 56% reduction in the computation cost. It shows the robustness of FACS towards parameter reduction and improved generalization over large scale ImageNet dataset by learning richer data representations. It further signifies the vast scope of FACS in edge devices, especially during network customization for a required purpose.

FACS-ResNet vs Depthwise/Channel Pooling. In terms of comparison, a closely matching approach is depthwise pooling (DWP) (10) which is a parameterless method. We endow ResNet-50 with DWP and retrain the network with identical settings of FACS-ResNet-50. Table 2 shows the corresponding comparison. It can be noticed that DWP drastically reduces the number of parameters of the baseline ResNet which results in a huge accuracy drop of 1.68%. Although, there is significant parameter gap between FACS/ResNet and DWP, therefore, at a first glance the comparison might seem unfair. However, our intention to conduct this experiment is to demonstrate that FACS does not incur any reduction in parameter while maintains the accuracy.

FACS in Conjunction With SE(8). When used in conjunction with SE (8) in ResNet-50, FACS reduces the computational demands of baseline SE-ResNet-50 while performing better (Table 2).

Table 4: FACS-VGG vs VGG on ImageNet.

Architecture	$\mathcal{R}$	#Params	#FLOPs	Top-1	Top-5	$\triangle$Acc	$\triangle$#FLOPs
VGG-16-1 $\times$ 1	2	10.3M	10.0B	74.29%	91.86%	—	—
FACS-VGG-16	2	10.3M	9.3B	74.82%	92.16%	-0.53%	7.0%
VGG-16-1 $\times$ 1	4	7.4M	6.7B	72.59%	90.88%	—	—
FACS-VGG-16	4	7.4M	6.3B	72.71%	91.01%	-0.12%	6.0%

Table 5: FACS for MobileNet-v2 vs MobileNet-v2 evaluation on ImageNet.

Architecture	BatchNorm (11)	#Params	#FLOPs	Top-1	Top-5	$\triangle$Acc	$\triangle$#FLOPs
MobileNet-v2(18)	—	3.50M	0.32B	71.80%	90.19%	—	—
FACS-MobileNet-v2	✗	3.50M	0.25B	71.13%	89.85%	0.67%	21.8%
FACS-MobileNet-v2	Pre	3.50M	0.25B	71.00%	89.75%	0.80%	21.8%
FACS-MobileNet-v2	Post	3.50M	0.25B	70.79%	89.59%	1.01%	21.8%
MobileNet-v2(18)	—	25.2M	4.65B	74.48%	92.09%	—	—
FACS-MobileNet-v2	✗	25.2M	4.58B	74.57%	92.07%	-0.09%	1.2%
FACS-MobileNet-v2	Pre	25.2M	4.58B	74.65%	92.11%	-0.17%	1.2%
FACS-MobileNet-v2	Post	25.2M	4.58B	74.52%	92.17%	-0.04%	1.2%

4.2.2 FACS-VGG

We select the popular VGG-16 variant of VGG series and upgrade it to VGG-16-1 $\times$ 1 model with BatchNorm (11) in all the layers. We compare this model with its FACS variant. The experiments are conducted for two values of reduction ratio $\mathcal{R}$ i.e. $\{2, 4\}$, the results for which are shown in Table 4.

It can be observed that the FACS is consistent as computation reduction is $\sim 6\%$ while accuracy is improved significantly for different values of $\mathcal{R}$. Noticeably, relative gain w.r.t. ResNet is smaller (23% vs 6%), it is so because in this architecture most computations are packed into 3×3 convolutions (90%) instead of 1×1 (6%). Nonetheless, potential of FACS is huge in VGG like architecture, especially for low power applications and edge devices because narrower models of VGG are quite popular for real-time applications (14).

4.2.3 FACS-MOBILENET-V2.

Mobile series networks are not our point of consideration because of their limited representation power and complexity, as mentioned in Sec. 2. However, we analyze how FACS behaves with mobilenets which employ inverted-residual bottlenecks consisting of depthwise separable convolution networks. We choose MobileNet-v2 (18) for the evaluation purpose and train for 120 epochs.

The experimental results are reported in Table 5. We observe that for depthwise separable convolution, FACS performs slightly inferior. We hypothesis that the accuracy drop is due to the lack of inter-channel communication in depth-wise separable convolutions. In MobileNet-v2, this communication is performed by the squeeze layer in addition to performing the task of reducing the number of channels. However in FACS, this is performed by global pooling and the convolution layer which operates on a descriptor (less information) instead of the tensor (more information) which according to our hypothesis becomes the reason of slightly reduced accuracy.

To validate our hypothesis, we replace all the depthwise separable convolution by fully connected convolutions in MobileNet-v2. In this case, we observe improvements in the accuracy, as shown in the second section of Table 5. This verifies our previously made hypothesis that devoid of inter-channel communication limits the performance of FACS. However, in this case the FLOPs improvement drops which is expected. It is so because, inverted residual design increases the number of channels which when fed to a fully connected 3×3 convolution, leads to most of the network computations packed into these layers (95%). Hence, effect of FACS diminishes. This experiment is for hypothesis verification only because inverted bottlenecks with fully connected 3×3 are not used in practice due to exponential rise in computations.

In addition to the above, we also performed ablations on MobileNet-v2 by placing BatchNorm (11) at the input and output of FACS. We observe that BatchNorm slightly lowers the performance of depthwise convolutions while for the fully connected case, pre-BatchNorm marginally improves the performance. Conclusively, we say that FACS still performs on a par for depthwise separable convolutions while performs better for fully connected convolutions in inverted-residual units.

Table 6: FACS vs ResNet on classification, and semantic segmentation transfer learning.

Architecture	CIFAR-10	CIFAR-100	CityScapes
ResNet-50 (5)	95.57%	81.60%	–
FACS-ResNet-50	95.67%	82.22%	–
PSPNet (27) + ResNet-101 (5)	–	–	78.4%
PSPNet (27) + FACS-ResNet-101	–	–	79.1%

Figure 5: GradCAM visualizations. More red shows more confidence for a pixel to belong to a class.

4.3 TRANSFER LEARNING

To analyze the generalization of FACS across datasets, we perform transfer learning from ImageNet to CIFAR-10 and CIFAR-100. Each of the dataset consists of 50K training and 10K test images. For training, we finetune FACS-ResNet-50 and ResNet-50 pretrained over ImageNet. The training protocol for both the datasets remain identical to that of ImageNet except 200 epochs. Table 6 shows the classification results. It can be seen that, surprisingly, FACS-ResNet-50 outperforms the baseline by 0.10% on CIFAR-10 and by 0.62% on CIFAR-100 at a lower FLOP requirements.

In addition, we evaluate FACS for a challenging downstream task of semantic segmentation. We use the popular approach (27) and replace the backbone with FACS-ResNet-101. Consistently, FACS variant outperforms the baseline both in terms of FLOPs efficiency and accuracy by 0.7% units mIoU (mean intersection over union), indicating that FACS indeed transfers better across tasks and datasets.

4.4 GRADCAM VISUALIZATION

As FACS employs global context in one of its stages and also choose the reduction operators adaptively, it encouraged us to analyze the behavior of layer activations in the network corresponding to a groundthruth class. To do this, we use GradCAM (20) that utilizes gradients to visualize the importance of spatial activations. GradCAM is given a label for which the attended regions in the feature maps are computed. This feature of GradCAM is utilized to visualize and understand that how FACS attends the spatial regions in comparison to the baseline networks. It gives us the qualitative explanation that despite the reduction in the computations, why FACS is performing better.

Figure 5 shows the GradCAM analysis for ResNet and VGG. It can be seen that FACS significantly improves the attended regions of the target class relative to the baselines. Also, in case of images with multiple instances of an object, FACS focuses on each instance strongly. It indicates that FACS enhances a network's ability to generalize better by learning to emphasize class-specific parts.

5 CONCLUSION

In this work, we introduce a novel module called "Fast Adaptive Channel Squeezing" (FACS) which redefines the manner in which channel squeezing is accomplished in CNNs. It functions by exploiting global spatial context and blending cross-channel information in order to carry out computationally efficient channel squeezing. We plugged the FACS module into three distinct CNN architectures: ResNet, VGG, and MobileNet-v2, and presented a comprehensive ablation study including ImageNet classification results and transfer learning on semantic segmentation task. Our experimental study suggests that FACS-enhanced CNNs are roughly 23% faster (lower FLOPs) while being more accurate in the same number of parameters while generalizing well across datasets and tasks. We show that the reduction in FLOPs cuts a network's training time significantly, and also demonstrate that FACS results in lower latency of a network which speeds-up inference on edge devices.

REFERENCES

[1] Nicolas Carion, Francisco Massa, Gabriel Synnaeve, Nicolas Usunier, Alexander Kirillov, and Sergey Zagoruyko. End-to-end object detection with transformers. In *European Conference on Computer Vision*, pp. 213–229. Springer, 2020.

[2] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pp. 248–255. Ieee, 2009.

[3] Xiaohan Ding, Xiangyu Zhang, Ningning Ma, Jungong Han, Guiguang Ding, and Jian Sun. Repvgg: Making vgg-style convnets great again. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 13733–13742, 2021.

[4] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929*, 2020.

[5] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

[6] Kaiming He, Georgia Gkioxari, Piotr Dollár, and Ross Girshick. Mask r-cnn. In *Proceedings of the IEEE international conference on computer vision*, pp. 2961–2969, 2017.

[7] Andrew G Howard, Menglong Zhu, Bo Chen, Dmitry Kalenichenko, Weijun Wang, Tobias Weyand, Marco Andreetto, and Hartwig Adam. Mobilenets: Efficient convolutional neural networks for mobile vision applications. *arXiv preprint arXiv:1704.04861*, 2017.

[8] Jie Hu, Li Shen, and Gang Sun. Squeeze-and-excitation networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 7132–7141, 2018.

[9] Gao Huang, Zhuang Liu, Kilian Q Weinberger, and Laurens van der Maaten. Densely connected convolutional networks. *CVPR*, 2017.

[10] Abid Hussain and Wang Hesheng. Depth-wise pooling: A parameter-less solution for channel reduction of feature-map in convolutional neural network. In *2019 IEEE International Conference on Real-time Computing and Robotics (RCAR)*, pp. 299–304. IEEE, 2019.

[11] Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *International conference on machine learning*, pp. 448–456. PMLR, 2015.

[12] Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *Advances in neural information processing systems*, pp. 1097–1105, 2012.

[13] Ashish Kumar and Laxmidhar Behera. Semi supervised deep quick instance detection and segmentation. In *2019 International Conference on Robotics and Automation (ICRA)*, pp. 8325–8331. IEEE, 2019.

[14] Ashish Kumar, Mohit Vohra, Ravi Prakash, and Laxmidhar Behera. Towards deep learning assisted autonomous uavs for manipulation tasks in gps-denied environments. In *2020 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 1613–1620. IEEE, 2020.

[15] Ilya Loshchilov and Frank Hutter. Sgdr: Stochastic gradient descent with warm restarts. *arXiv preprint arXiv:1608.03983*, 2016.

[16] Ningning Ma, Xiangyu Zhang, Hai-Tao Zheng, and Jian Sun. Shufflenet v2: Practical guidelines for efficient cnn architecture design. In *Proceedings of the European conference on computer vision (ECCV)*, pp. 116–131, 2018.

[17] Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. *Advances in neural information processing systems*, 32, 2019.

[18] Mark Sandler, Andrew Howard, Menglong Zhu, Andrey Zhmoginov, and Liang-Chieh Chen. Mobilenetv2: Inverted residuals and linear bottlenecks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 4510–4520, 2018.

[19] Nick Schneider, Florian Piewak, Christoph Stiller, and Uwe Franke. Regnet: Multimodal sensor registration using deep neural networks. In *2017 IEEE intelligent vehicles symposium (IV)*, pp. 1803–1810. IEEE, 2017.

[20] Ramprasaath R Selvaraju, Michael Cogswell, Abhishek Das, Ramakrishna Vedantam, Devi Parikh, and Dhruv Batra. Grad-cam: Visual explanations from deep networks via gradient-based localization. In *Proceedings of the IEEE international conference on computer vision*, pp. 618–626, 2017.

[21] L Sifre and S Mallat. Rigid-motion scattering for image classification. arxiv 2014. *arXiv preprint arXiv:1403.1687*.

[22] Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *CoRR*, abs/1409.1556, 2014.

[23] Mingxing Tan and Quoc Le. Efficientnet: Rethinking model scaling for convolutional neural networks. In *International Conference on Machine Learning*, pp. 6105–6114. PMLR, 2019.

[24] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems*, pp. 5998–6008, 2017.

[25] Sanghyun Woo, Jongchan Park, Joon-Young Lee, and In So Kweon. Cbam: Convolutional block attention module. In *Proceedings of the European conference on computer vision (ECCV)*, pp. 3–19, 2018.

[26] Xiangyu Zhang, Xinyu Zhou, Mengxiao Lin, and Jian Sun. Shufflenet: An extremely efficient convolutional neural network for mobile devices. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 6848–6856, 2018.

[27] Hengshuang Zhao, Jianping Shi, Xiaojuan Qi, Xiaogang Wang, and Jiaya Jia. Pyramid scene parsing network. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2881–2890, 2017.