PREFERENCE CONDITIONED NEURAL MULTI-OBJECTIVE COMBINATORIAL OPTIMIZATION

ABSTRACT

Multiobjective combinatorial optimization (MOCO) problems can be found in many real-world applications. However, exactly solving these problems would be very challenging, particularly when they are NP-hard. Many handcrafted heuristic methods have been proposed to tackle different MOCO problems over the past decades. In this work, we generalize the idea of neural combinatorial optimization, and develop a learning-based approach to approximate the whole Pareto set for a given MOCO problem without further search procedure. To be concrete, we propose a single preference-based attention model to directly generate approximate Pareto solutions of all the different trade-offs. We design an efficient multiobjective reinforcement learning algorithm to train the model with different preferences simultaneously. Experimental results show that our proposed method significantly outperforms the other methods on the multiobjective traveling salesman problem (MOTSP), multiobjective vehicle routing problem (MOVRP) and multiobjective knapsack problem (MOKP) in solution quality, speed, and model efficiency.

1   INTRODUCTION

Many real-world applications can be modeled as different multiobjective combinatorial optimization (MOCO) problems (Ehrgott & Gandibleux, 2000). The multiobjective traveling salesman problem (MOTSP) (Lust & Teghem, 2010a), multiobjective vehicle routing problem (MOVRP) (Jozefowiez et al., 2008) and multiobjective knapsack problem (MOKP) (Bazgan et al., 2009) are three widely studied problems in the research community. These problems have multiple conflicting objectives to optimize, and no single solution can optimize all the objectives at the same time. Instead, there is a set of Pareto solutions with different optimal trade-offs among the objectives.

It is very challenging to find all exact Pareto optimal solutions for a MOCO problem. Finding only one Pareto solution would be already NP-hard for many problems (Ehrgott & Gandibleux, 2000), and the number of Pareto solutions could be exponentially large to the problem size (Ehrgott, 2005; Herzel et al., 2021). The decision-maker's preference among different objectives is usually unknown in advance, making it hard to reduce the problem into a single-objective one. Over the past several decades, many methods have been developed to find an approximate Pareto set for different MOCO problems within a reasonable computational time. These methods often need carefully handcrafted and specialized heuristics for each problem, which can be very labor-intensive in practice.

In many real-world applications, the practitioners need to repeatedly solve different problems with similar characteristics, of which the problem instances can be easily obtained or generated (Bengio et al., 2020). It is desirable to learn the patterns behind these problem instances explicitly or implicitly to design efficient algorithms (Cappart et al., 2021). Machine learning techniques can be naturally served for this purpose. Some learning-based methods have been recently proposed for solving single-objective combinatorial optimization problems (Bengio et al., 2020; Vesselinova et al., 2020; Mazyavkina et al., 2021; Cappart et al., 2021). In this work, we extend the learning-based method to solve MOCO problems in a principled way as shown in Figure 1. Our main contributions include:

- We propose a novel preference-conditioned neural combinatorial optimization method to approximate the whole Pareto set with infinite trade-offs via a single model, which allows decision-makers to directly generate any preferred trade-off solution without extra opti-

(a) Problem   (b) Model   (c) Solution Generation

Figure 1: **Preference-Conditioned Neural Multiobjective Combinatorial Optimization:** (a) The model takes a problem instance as input. (b) The decision-makers assign their preferences on different objectives to the model. (c) The model directly generates approximated Pareto solutions with different trade-offs via fast forward inference. In this example, the problem is a general MOTSP with two costs to minimize for a tour. The generated solutions P_1, P_2 and P_3 have different optimal trade-offs among the two costs. The ideal model can generate solutions with all possible optimal trade-offs on the Pareto front and not generate the solution P_4 with a poor trade-off.

    mization. This novel and powerful property is not supported by any other learning-based or heuristics-based methods.

- We develop an efficient end-to-end reinforcement learning algorithm to train the single model for all the different preferences simultaneously, and a simple yet powerful active adaption method to handle out-of-distribution problem instances.

- We conduct comprehensive experiments on MOTSP, MOVR and MOKP problems with different settings. The results show that our proposed method can successfully approximate the Pareto sets for different problems in an efficient way. It also significantly outperforms other methods in solution quality, speed, and/or model efficiency.

2   BACKGROUND AND RELATED WORK

Multiobjective Combinatorial Optimization (MOCO). MOCO has been attracting much research effort from different communities over the past several decades (Sawaragi et al., 1985; Wallenius et al., 2008; Herzel et al., 2021). There are two main approaches to tackle the MOCO problems: the exact method and the approximation method (Ehrgott, 2005). Exact methods could be impractically costly when, as it often happens, the MOCO problem is NP-hard and the number of Pareto optimal solutions is huge (Florios & Mavrotas, 2014). For this reason, many heuristics (Jaszkiewicz, 2002; Ehrgott & Gandibleux, 2008) and approximation methods (Papadimitriou & Yannakakis, 2000; Herzel et al., 2021) have been developed to find a moderately sized set of approximated Pareto solutions with a reasonable amount of computational budget. However, these methods usually depend on carefully handcrafted designs for each specific problem (Ehrgott & Gandibleux, 2000), of which the effort would be nontrivial for a new problem in real-world applications.

Machine Learning for Combinatorial Optimization. According to Bengio et al. (2020), there are three main learning-based approaches for CO: learning to configure algorithms (Kruber et al., 2017; Bonami et al., 2018), learning alongside the algorithms (Lodi & Zarpellon, 2017; Gasse et al., 2019; Chen & Tian, 2019; Kool et al., 2021), and learning to directly predict the solutions (Nowak et al., 2018; Emami & Ranka, 2018; Larsen et al., 2018). Neural combinatorial optimization (NCO) belongs to the last category where the training model directly predicts a good solution for a given problem instance. Vinyals et al. (2015) propose the pointer network to sequentially construct a solution for TSP problem. Bello et al. (2017) make a critical improvement to use reinforcement learning to train the model, eliminating the impractical optimal solutions collection for NP-hard problems. Further improvements on model structure and training procedure have been proposed in the past few years (Nazari et al., 2018; Deudon et al., 2018; Kool et al., 2019; Joshi et al., 2020), especially with graph neural networks (GNNs) (Dai et al., 2017; Li et al., 2018; Joshi et al., 2019; Dwivedi et al., 2020; Drori et al., 2020). Some works have recently been proposed to design more powerful

training strategies, such as optimization with multiple optimum (Kwon et al., 2020), unsupervised learning (Karalias & Loukas, 2020) and curriculum learning schemes (Lisicki et al., 2020).

Neural MOCO. The current learning-based methods are mostly for solving single-objective combinatorial problems. Recently, a few attempts have been made to solve MOCO problems (Li et al., 2020; Wu et al., 2020; Zhang et al., 2021b;a). They first decompose a MOCO problem into multiple single-objective scalarized subproblems, and then build a set of models for each subproblem. However, since the number of Pareto solutions would be exponentially large (Ehrgott, 2005), the required number of models would be huge for finding the whole Pareto set. This work proposes a single preference-based model for solving MOCO problems, where the decision-makers can obtain arbitrary trade-off solutions. The proposed single neural MOCO solver could be much easier to use in a real-world system (Veličković & Blundell, 2021), rather than a large set of separate models. Our method's model efficiency is crucial to truly extend the NCO approach to solve MOCO problems.

3 PROBLEM FORMULATION

3.1 MULTIOBJECTIVE COMBINATORIAL OPTIMIZATION

A multiobjective combinatorial optimization (MOCO) problem can be defined as follows:

$$\min_{x \in \mathcal{X}} F(x) = (f_1(x), f_2(x), \ldots, f_m(x)), \tag{1}$$

where $\mathcal{X}$ is a discrete search space, and $F(x) = (f_1(x), \ldots, f_m(x))$ is an m-objective vector. Since the individual objectives often conflict with each other, no single solution can optimize all of them at the same time. Thus, practitioners are interested in Pareto optimal solutions, defined as follows.

Definition 1 (Pareto Dominance). Let $x_a, x_b \in \mathcal{X}$, x_a is said to dominate x_b ($x_a \prec x_b$) if and only if $f_i(x_a) \leq f_i(x_b), \forall i \in \{1, ..., m\}$ and $f_j(x_a) < f_j(x_b), \exists j \in \{1, ..., m\}$.

Definition 2 (Pareto Optimality). A solution $x^* \in \mathcal{X}$ is a Pareto optimal solution if there does not exist $\hat{x} \in \mathcal{X}$ such that $\hat{x} \prec x^*$. The set of all the Pareto solutions is called the Pareto set, and the image of the Pareto set in the objective space is called the Pareto front.

Each Pareto solution represents an optimal trade-off among the objectives, and it is impossible to further improve one of the objectives without deteriorating any other objectives. For many MOCO problems, the size of Pareto set would be exponentially large with respect to the input size (e.g., nodes in MOTSP), which makes finding the whole Pareto set intractable (Herzel et al., 2021). Therefore, the current heuristic-based and learning-based methods all focus on finding a small subset of approximate Pareto solutions $\{x_1, x_2, \cdots, x_p\}$ (e.g., $p = 101$). The decision-makers can only select solutions from this fixed small set, which is unlikely to contain their preferred solutions precisely.

3.2 PREFERENCE-BASED SCALARIZATION

Preference-based scalarization is a widely-used approach to solve MOCO problems (Ehrgott, 2005). It decomposes a given multiobjective problem into several subproblems with different preferences. By solving all subproblems, we can obtain a set of approximated Pareto solutions. For an m-objective problems, we can define a preference vector $\lambda \in \mathbb{R}^m$ satisfies $\lambda_i \geq 0$ and $\sum_{i=1}^{m} \lambda_i = 1$ such that λ_i is the preference for the i-th objective.

Weight-Sum Scalarization is the most straightforward approach:

$$\min_{x \in \mathcal{X}} g_{\text{ws}}(x|\lambda) = \min_{x \in \mathcal{X}} \sum_{i=1}^{m} \lambda_i f_i(x), \tag{2}$$

where $g_{\text{ws}}(x|\lambda)$ is a single-objective subproblem with preference λ. The decision-makers can assign their preferences among the objectives, and obtain different subproblems. However, the weighted-sum method can only find solutions on the convex hull of the Pareto set (Ehrgott, 2005).

Weighted-Tchebycheff (Weighted-TCH) Scalarization is an alternative:

$$\min_{x \in \mathcal{X}} g_{\text{tch}}(x|\lambda) = \min_{x \in \mathcal{X}} \max_{1 \leq i \leq m} \{\lambda_i | f_i(x) - (z_i^* - \varepsilon)|\}, \tag{3}$$

where z_i^* is the ideal value for objective $f_i(x)$ (e.g., the lower bound), and $u_i^* = z_i^* - \varepsilon$ is a utopia value with small positive component ε. According to Choo & Atkins (1983), any Pareto optimal

| (a) 105 Preferences | (b) 105 Solutions | (c) 1,035 Solutions | (d) 10,011 Solutions |

Figure 2: **Pareto Set Approximation for a New Problem Instance:** Our method with different numbers of preferences on three objective MOTSP with 50 nodes. **a)&b):** With a small number of preferences, our model can generate a uniform approximation to the Pareto set. **c)&d):** With a large number of preferences, it can generate a dense approximation. Our method supports generating arbitrary trade-off solutions with a single model and without extra search, while other methods need to solve or build models for each preference separately.

solution could be an optimal solution of problem (3) with a specific (but unknown) preference λ. To find the whole Pareto set, it still needs to solve a exponentially huge number of subproblems.

Drawbacks and Remarks. Although the scalarization methods are straightforward, some critical drawbacks cannot be ignored. First of all, not all scalarized multiobjective problem is the same as its single-objective version (Ehrgott, 2005). For MOTSP, each weight-sum scalarized subproblem is a single objective TSP so that a powerful TSP solver can solve it. However, it is not the case for MOCVRP. Secondly, although the Tchebycheff scalarization has good properties, it involves min-max optimization, which is typically different from the original problem. For example, the Tchebycheff scalarized MOTSP is not a single-objective TSP and cannot be solved by the state-of-the-art single-objective solver developed in the current years. In our reinforcement learning based framework, we use the Tchebycheff scalarization to combine the rewards of different objectives. It is much more flexible to use, and does not have to consider the problem-specific condition.

3.3 OUR KEY IDEA

In this work, instead of finding a finite set $\{x_1, x_2, \cdots, x_p\}$ as in the current MOCO methods, we propose a novel way to approximate the whole Pareto set $\{x(\boldsymbol{\lambda})| \sum_{i=1}^{m} \lambda_i = 1\}$ with infinite trade-off preferences via a single model. With our method, the decision-makers can easily obtain any solutions on the approximate Pareto set with their preferred trade-offs as shown in Figure 2. That is, our method provides the decision-makers a much more flexible control on the Pareto set. We believe this is a novel and principled way to solve multiobjective combinatorial optimization problems.

4 THE PROPOSED MODEL: PREFERENCE-CONDITIONED NEURAL MOCO

4.1 PREFERENCE-CONDITIONED SOLUTION CONSTRUCTION

The preference-based scalarization approach provides a connection between the preferences and the Pareto solutions. We build a preference-based neural network to solve the MOCO problems. We use the multiobjective traveling salesman problem (MOTSP) to motivate our model design, similar to using TSP in previous single-objective work (Bello et al., 2017; Kool et al., 2019; Joshi et al., 2020). In MOTSP, a problem instance s is a fully connected graph containing n nodes, with multiple costs on each edge. A valid solution (tour) $\boldsymbol{\pi} = (\pi_1, \cdots, \pi_t, \cdots, \pi_n), \pi_t \in \{1, \cdots, n\}$ is a permutation of all the nodes where $\pi_t \neq \pi_{t'}', \forall t \neq t'$. Our model defines a preference-conditioned stochastic policy $p_{\boldsymbol{\theta}(\lambda)}(\boldsymbol{\pi}|s)$ parameterized by $\boldsymbol{\theta}(\lambda)$ to construct a valid solution in sequence:

$$p_{\boldsymbol{\theta}(\lambda)}(\boldsymbol{\pi}|s) = \prod_{t=1}^{n} p_{\boldsymbol{\theta}(\lambda)}(\boldsymbol{\pi}_t|s, \boldsymbol{\pi}_{1:t-1}). \quad (4)$$

The goal is to learn an optimal preference-conditioned policy $p_{\boldsymbol{\theta}(\lambda)}(\pi|s)$ to construct tours with low scalarized costs for each preference λ.

(a) Instance	(b) Encoder	(c) Embedding	(d) Decoder	(e) Solution

Figure 3: **Preference-conditioned Neural MOCO Model:** a) The input is a problem instance s (e.g., a graph). b) A shared attention encoder transfers the instance s into a set of embeddings. c) The embeddings for all nodes would be used by the decoder multiple times with different preferences. d) A MLP takes the preference λ as input, and generates the parameters for the decoder. e) The preference-conditioned attention decoder directly generates different approximated Pareto solutions with different preferences. The trainable parameters are in the **attention encoder** and **MLP model**.

4.2 THE PROPOSED MODEL

In this work, we propose a preference-conditioned encoder-decoder model as shown in Figure 3, with the Attention Model (AM) (Kool et al., 2019) as our basic model. For the MOCO problems and settings considered in this work, a preference-agnostic encoder is capable to transfer the problem instance into embeddings used by the preference-conditioned decoder. In our proposed model, only the decoder's parameters $\boldsymbol{\theta}_{\text{decoder}}(\lambda)$ are conditioned on the preference λ:

$$\boldsymbol{\theta}(\lambda) = [\boldsymbol{\theta}_{\text{encoder}}, \boldsymbol{\theta}_{\text{decoder}}(\lambda)]. \tag{5}$$

Preference-agnostic Encoder. The encoder takes the problem instance s (e.g., a graph with n nodes) as input, and outputs a set of d-dimensional node embeddings $\{\boldsymbol{h}_1, \cdots, \boldsymbol{h}_n\}$, along with an aggregated graph embedding $\bar{\boldsymbol{h}}_{(G)} = \sum_{i=1}^n \boldsymbol{h}_i$. For a given instance, the same embeddings can be used multiple times for different preference λ. We only need a single forward pass for the encoder. We use the shared attention-based encoder as in Kool et al. (2019) for all preferences.

Preference-based Attention Decoder. The decoder takes the nodes and graph embeddings as input, and sequentially selects the next node $\boldsymbol{\pi}_t$ with probability $p_{\boldsymbol{\theta}(\lambda)}(\boldsymbol{\pi}_t|s, \boldsymbol{\pi}_{1:t-1})$. The decoder has the same structure as in the AM model (Kool et al., 2019), but with parameters $\boldsymbol{\theta}_{\text{decoder}}(\lambda) = [W_C(\lambda), W_Q(\lambda), W_K(\lambda), W_{\text{MHA}}(\lambda)]$ conditioned on the preference λ.

One designing choice left is how to generate the preference-conditioned parameters $\boldsymbol{\theta}_{\text{decoder}}(\lambda)$. Multiplicative interactions (Jayakumar et al., 2020) and hypernetwork (Schmidhuber, 1992; Ha et al., 2017) provide a powerful and efficient way for conditional computation, which is widely used for transfer learning (von Oswald et al., 2020; Ehret et al., 2021; Lin et al., 2020; Navon et al., 2021). We use a simple MLP hypernetwork $\boldsymbol{\theta}_{\text{decoder}}(\lambda) = \text{MLP}(\lambda|\boldsymbol{\psi})$ to generate the decoder parameters conditioned on the preference. The details of our proposed model can be found in Appendix B.

Instance Augmentation for MOCO. The model we propose only has a small computational and memory overhead to the original single-objective AM solver. We keep our model as simple as possible, which makes it easily compatible with other models and improvements that are originally developed for single-objective NCO. These properties are crucial to truly generalize the NCO to deal with multiobjective problems. In this work, we extend the instance augmentation method (Kwon et al., 2020) for solving MOCO, of which the details are discussed in the Appendix B.1.

5 PREFERENCE-CONDITIONED MULTIOBJECTIVE POLICY OPTIMIZATION

5.1 COST FUNCTION

The proposed node selection strategy guarantees that the model can always generate feasible solutions. In this section, we develop an efficient multiobjective policy optimization method to train the model for different preferences simultaneously. For an MOTSP problem, the objective functions are a vector of m different costs for a tour $L(\boldsymbol{\pi}) = [L_1(\boldsymbol{\pi}), \cdots, L_m(\boldsymbol{\pi})]$. We can define a weighted-Tchebycheff scalarized cost for each preference λ:

$$L(\boldsymbol{\pi}|\lambda) = \max_{1 \le i \le m} \{\lambda_i | L_i(\boldsymbol{\pi}) - (z_i^* - \varepsilon)|\}, \tag{6}$$

Algorithm 1 Neural MOCO Training

1: **Input:** preference distribution Λ, instances distribution $\mathcal{S}$, number of training steps T, number of preferences per iteration K, batch size B, number of tours N
2: Initialize the model parameters $\boldsymbol{\theta}$
3: **for** $t = 1$ to T **do**
4:     $\lambda_k \sim$ **SamplePreference**(Λ) $\forall k \in \{1, \cdots, K\}$
5:     $s_i \sim$ **SampleInstance**$(\mathcal{S})$ $\forall i \in \{1, \cdots, B\}$
6:     $\boldsymbol{\pi}_{ki}^j \sim$ **SampleTour**$(p_{\boldsymbol{\theta}(\lambda_k)}(\cdot|s_i))$ $\forall k, i$ $\forall j \in \{1, \cdots, N\}$
7:     $b(s_i|\lambda_k) \leftarrow \frac{1}{N}\sum_{j=1}^N L(\boldsymbol{\pi}_{ki}^j|\lambda_k, s_i)$ $\forall k \in \{1, \cdots, K\}$ $\forall i \in \{1, \cdots, B\}$
8:     $\nabla\mathcal{J}(\boldsymbol{\theta}) \leftarrow \frac{1}{KBN}\sum_{k=1}^K\sum_{i=1}^B\sum_{j=1}^N[(L(\boldsymbol{\pi}_{ki}^j|\lambda_k, s_i) - b(s_i|\lambda_k))\nabla_{\boldsymbol{\theta}(\lambda_k)}\log p_{\boldsymbol{\theta}(\lambda_k)}(\boldsymbol{\pi}_{ki}^j|s_i)]$
9:     $\theta \leftarrow$ **ADAM**$(\theta, \nabla\mathcal{J}(\boldsymbol{\theta}))$
10: **end for**
11: **Output:** The model parameter $\boldsymbol{\theta}$

---

where z_i^* is the ideal value for the i-th cost. This method can be easily adapted for the weighted-sum scalarization. For a given instance s, our goal is to minimize the expected cost for all preferences:

$$\mathcal{J}(\boldsymbol{\theta}|s) = \mathbb{E}_{\lambda\sim\Lambda, \boldsymbol{\pi}\sim p_{\boldsymbol{\theta}(\lambda)}(\cdot|s)}L(\boldsymbol{\pi}|\lambda), \tag{7}$$

where Λ is the distribution for the preference λ. To train the model, we repeatedly sample different instances $s \sim \mathcal{S}$ at each iteration, so we can define the training loss as $\mathcal{J}(\boldsymbol{\theta}) = \mathbb{E}_{s\sim\mathcal{S}}\mathcal{J}(\boldsymbol{\theta}|s)$.

5.2 MULTIOBJECTIVE REINFORCE

For a given instance s and a specific preference λ, we use the REINFORCE (Williams, 1992) to estimate the gradient for the preference-conditioned scalar cost:

$$\nabla\mathcal{J}(\boldsymbol{\theta}|\lambda, s) = \mathbb{E}_{\boldsymbol{\pi}\sim p_{\boldsymbol{\theta}(\lambda)}(\cdot|s)}[(L(\boldsymbol{\pi}|\lambda, s) - b(s|\lambda))\nabla_{\boldsymbol{\theta}(\lambda)}\log p_{\boldsymbol{\theta}(\lambda)}(\boldsymbol{\pi}|s)], \tag{8}$$

where $b(s|\lambda)$ is the baseline of expected cost to reduce the gradient variance. This gradient is estimated by Monte Carlo sampling. At each update step, we randomly sample K preference $\{\lambda_1, \cdots, \lambda_K\} \sim \Lambda$, B instances $\{s_1, \cdots, s_B\} \sim \mathcal{S}$, and N different tour $\{\boldsymbol{\pi}_i^1, \cdots, \boldsymbol{\pi}_i^N\} \sim p_{\boldsymbol{\theta}(\lambda_k)}(\cdot|s_i)$ for each λ_k-s_i combination. The approximated gradient is:

$$\nabla\mathcal{J}(\boldsymbol{\theta}) \approx \frac{1}{KBN}\sum_{k=1}^K\sum_{i=1}^B\sum_{j=1}^N[(L(\boldsymbol{\pi}_i^j|\lambda_k, s_i) - b(s_i|\lambda_k))\nabla_{\boldsymbol{\theta}(\lambda_k)}\log p_{\boldsymbol{\theta}(\lambda_k)}(\boldsymbol{\pi}_i^j|s_i)]. \tag{9}$$

In this work, we use the shared baseline $b_{\text{shared}}(s_i|\lambda_k) = \frac{1}{N}\sum_{j=1}^N L(\boldsymbol{\pi}_{ki}^j|\lambda_k, s_i)$ over N sampled tours for each $\lambda_k - s_i$ combination. The starting node for each tour $\boldsymbol{\pi}_{ki}^j$ is chosen in random to force diverse rollouts as proposed in (Kwon et al., 2020). The algorithm is shown in **Algorithm 1**.

5.3 ACTIVE ADAPTION

After end-to-end training, our proposed method can directly generate different trade-off solutions to a given problem without further search procedure. However, similar to single-objective neural combinatorial optimization, this approach could still have a gap to the Pareto front, especially for problems out of the training distribution $\mathcal{S}$ (e.g., with different sizes and patterns) (Lisicki et al., 2020). Iterative search methods, such as sampling and beam search, can further improve the performance for a single solution or single preference (Joshi et al., 2020). However, these approaches can not find a better approximation to the whole Pareto set for a MOCO problem.

We propose a simple yet powerful active adaption approach as shown in **Algorithm 2**. It iteratively adapts the model parameter $\boldsymbol{\theta}(\lambda)$ to a given instance s (or a batch of instances) with all preferences from the distribution Λ rather than searching for a specific solution. This method is similar to the active search in Bello et al. (2017) which actively refines the single-objective model for efficient candidate solutions searching. Our approach focuses on adapting the whole model for a better Pareto front approximation. Since this method is distribution-agnostic (not depend on specific instance distribution $\mathcal{S}$), it is suitable for out-of-distribution adaption.

Algorithm 2 Neural MOCO Active Adaption

1: **Input:** model parameter $\boldsymbol{\theta}$, instance s, preference distribution Λ, number of adaption steps T, number of preferences per iteration K, number of tours N
2: **for** $t = 1$ to T **do**
3: $\quad \lambda_k \sim$ **SamplePreference**$(\Lambda) \quad \forall k \in \{1, \cdots, K\}$
4: $\quad \boldsymbol{\pi}_k^j \sim$ **SampleTour**$(p_{\boldsymbol{\theta}(\lambda_k)}(\cdot|s)) \quad \forall k \in \{1, \cdots, K\} \quad \forall j \in \{1, \cdots, N\}$
5: $\quad b(s|\lambda_k) \leftarrow \frac{1}{N} \sum_{j=1}^{N} L(\boldsymbol{\pi}_k^j|\lambda_k, s) \quad \forall k \in \{1, \cdots, K\}$
6: $\quad \nabla \mathcal{J}(\boldsymbol{\theta}) \leftarrow \frac{1}{KN} \sum_{j=1}^{N} [(L(\boldsymbol{\pi}_k^j|\lambda_k, s) - b(s|\lambda_k)) \nabla_{\boldsymbol{\theta}(\lambda_k)} \log p_{\boldsymbol{\theta}(\lambda_k)}(\boldsymbol{\pi}_k^j|s)]$
7: $\quad \theta \leftarrow$ **ADAM**$(\theta, \nabla \mathcal{J}(\boldsymbol{\theta}))$
8: **end for**
9: **Output:** The model parameter $\boldsymbol{\theta}$

---

6 APPROXIMATION ABILITY

It is hard to give a convergence guarantee for MOCO, where each preference-based subproblem could be already NP-hard, and the number of Pareto solutions is exponentially large with respect to the input size. Similar to the single-objective NCO (Vinyals et al., 2015; Bello et al., 2017; Kool et al., 2019), our method can not guarantee to find the exact Pareto set for a MOCO problem. Instead, inspired from the approximation methods for MOCO (Herzel et al., 2021), we give an ε-Pareto approximation guarantee on the whole Pareto set conditioned on the model's learning ability:

Theorem 1. *Let x_λ^* denote the optimal solution of the problem (3) with preference λ, if our proposed model can generate an approximate solution x_λ ε-dominate x_λ^* for any preference λ, it is able to generate an ε-approximate Pareto set $\mathcal{P}_\varepsilon$ to the MOCO problem (1).*

The detailed definitions, proofs, and further analyses are given in Appendix A.

7 EXPERIMENTS

Problems and Model Setting. We consider MOTSP (Lust & Teghem, 2010a), MOCVRP (Lacomme et al., 2006) and MOKP (Bazgan et al., 2009) in this work, and use the same model settings for all problems with task-specific input size and mask method. The main policy model encoder is the Attention Model (Kool et al., 2019) and the hypernetwork is an MLP. We randomly generate $100,000$ problem instances on the fly for each epoch, and train the model for 200 epochs. The optimizer is ADAM with learning rate $\eta = 10^{-4}$ and weight decay 10^{-6}. We train our models on a single RTX 2080-Ti GPU, and it costs about 10 minutes for an epoch on MOTSP100. We put detailed model settings, problem formulations, and more experimental results in Appendix BCD. Our code will be released open-source upon publication.

Inference. We report the results and time for solving 200 random test instances for each problem, with normally 101 to 105 different trade-offed solutions for each problem, and up to $10,011$ solutions for our proposed method. We also compare the run time for solving each problem. In most cases, we report our model's zero-shot generalization performance without any search and fine-tune.

Baseline. We compare our proposed method with three widely-used algorithm frameworks for solving MOCO problems: 1) **MOGLS** (Jaszkiewicz, 2002) is a multiobjective genetic local search algorithm, 2) **NSGAII** (Deb et al., 2002) is a Pareto dominance-based multiobjective genetic algorithm, and 3) **MOEA/D** (Zhang & Li, 2007) is a decomposition-based multiobjective evolutionary algorithm. These algorithm frameworks all need problem-specific heuristics to solve different problems. We also report the performance for learning-based methods: 4) **DRL-MOA** (Li et al., 2020) decomposes a MOCO with different preferences and builds a Pointer Network (Vinyals et al., 2015; Bello et al., 2017) to solve each subproblem. 5) **AM-MOCO** is a multi-models variant of our proposed model, which builds Attention Model (Kool et al., 2019) for each subproblem. We call our proposed model 6) **P-MOCO** as for preference-conditioned multiobjective combinatorial optimization. 7) **The Weight-Sum** scalarization of MOTSP and MOKP are equal to their single-objective counterpart. Therefore, we also compare with the competitive approach that uses state-of-the-art single-objective solvers to solve each weight-sum subproblem.

Table 1: Model Information for the learning-based methods.

	Model	#Models	#Params	#Pref.
DRL-MOA	Pointer-Network	101	$101 \times 0.2M = 20.2M$ (7%)	Fixed 101
AM-MOCO	Attention Model	101	$101 \times 1.3M = 131.3M$ (1.1%)	Fixed 101
P-MOCO (Ours)	Pref-Conditioned AM	1	1.4M	Flexible

Table 2: Experimental results on two-objective MOTSP, MOCVRP and MOKP with input sizes. The best result and its statistically indifferent results are highlighted in **bold**.

MOTSP									
	MOTSP20			MOTSP50			MOTSP100		
Method	HV	Gap	Time	HV	Gap	Time	HV	Gap	Time
Weight-Sum LKH	0.51	2.44%	(3.9m)	0.59	1.17%	(42m)	**0.68**	**-0.58%**	(3.1h)
Weight-Sum OR Tools	0.48	7.29%	(3.7m)	0.53	8.21%	(38m)	0.63	5.64%	(2.8h)
MOGLS-TSP	0.48	7.96%	(1.7h)	0.52	10.2%	(4.5h)	0.59	14.7%	(12h)
NSGAII-TSP	0.47	9.88%	(45m)	0.47	18.6%	(49m)	0.51	26.5%	(53m)
MOEA/D-TSP	0.48	7.82%	(3.1h)	0.48	17.5%	(3.3h)	0.52	25.0%	(3.7h)
DRL-MOA (101 models)	0.46	11.3%	(2s)	0.49	15.1%	(5s)	0.57	17.0%	(15s)
AM-MOCO (101 models)	**0.52**	**0.22%**	(2s)	0.59	0.86%	(7s)	0.67	0.72%	(18s)
P-MOCO (101 pref.)	**0.52**	**0.19%**	(2s)	0.59	0.91%	(5s)	0.67	0.60%	(16s)
P-MOCO (101 pref., aug)	**0.52**	**0.00%**	(2.1m)	**0.59**	**0.00%**	(5.2m)	0.67	0.00%	(12m)
MOCVRP									
	MOCVRP20			MOCVRP50			MOCVRP100		
Method	HV	Gap	Time	HV	Gap	Time	HV	Gap	Time
MOGLS-MOCVRP	0.33	6.66%	(2.9h)	0.39	10.5%	(4.1h)	0.38	13.0%	(5h)
NSGAII-MOCVRP	0.31	12.3%	(39m)	0.36	18.0%	(39m)	0.35	20.8%	(41m)
MOEAD-MOCVRP	0.29	17.9%	(1.7h)	0.33	24.8%	(1.8h)	0.34	22.3%	(2h)
DRL-MOA (101 models)	0.32	9.19%	(6s)	0.37	16.0%	(15s)	0.37	16.0%	(33s)
AM-MOCO (101 models)	0.35	0.71%	(8s)	0.43	2.84%	(21s)	0.43	3.04%	(39s)
P-MOCO (101 pref.)	0.35	0.58%	(8s)	0.44	0.65%	(18s)	0.44	0.51%	(36s)
P-MOCO (101 pref., aug)	**0.35**	**0.00%**	(1m)	**0.44**	**0.00%**	(2.1m)	**0.45**	**0.00%**	(4.5m)
MOKP									
	MOKP50			MOKP100			MOKP200		
Method	HV	Gap	Time	HV	Gap	Time	HV	Gap	Time
Weight-Sum Exact DP	0.92	1.93%	(16m)	0.94	2.50%	(1.5h)	0.68	3.77%	(4.2h)
Weight-Sum Greedy	0.83	11.6%	(2s)	0.87	9.19%	(4s)	0.64	9.38%	(7s)
MOGLS-KP	0.77	18.4%	(1.8h)	0.83	13.8%	(3.9h)	0.63	11.0%	(9.8h)
NSGAII-KP	0.76	19.0%	(34m)	0.78	18.8%	(33m)	0.58	17.9%	(34m)
MOEAD-KP	0.78	16.8%	(1.5h)	0.87	9.17%	(1.4h)	0.65	8.48%	(1.6h)
DRL-MOA (101 models)	0.82	12.6%	(5s)	0.88	8.64%	(17s)	0.66	7.50%	(35s)
AM-MOCO (101 models)	**0.94**	**0.19%**	(7s)	**0.96**	**0.43%**	(16s)	0.70	0.80%	(42s)
P-MOCO (101 pref.)	**0.94**	**0.00%**	(7s)	**0.96**	**0.00%**	(15s)	**0.71**	**0.00%**	(40s)

Model Information for the learning-based methods is shown in Table 1. Our model supports flexible preference assignment at inference and only has 1.1% total parameters to the multiple-model counterpart. We use the hypervolume indicator (Zitzler et al., 2003) to measure the performance for each method. We report the normalized hypervolume values and also the performance gap to our method. A Wilcoxon rank-sum test with a significance level 1% is conducted to compare the results for each experiment. Details of the hypervolume calculation can be found in Appendix D.1.

7.1 RESULTS AND ANALYSIS

MOTSP. The results on two and three objective MOTSP are shown in Table 2 and Table 3 respectively. MOGLS, NSGAII and MOEA/D all use 2-opt local search heuristic (Jaszkiewicz, 2002) to search for promising solutions. We also include two weight-sum scalarization baselines with the state-of-the-art LKH solver (Helsgaun, 2000; Tinós et al., 2018) and Google OR tools (Perron & Furnon, 2019). For the two-objective problems, our proposed method has similar performance to AM-MOCO in all problems only with a single model. It achieves the best performance with instance

Table 3: Experimental results on three-objective MOTSP with different input sizes. The best result and its statistically indifferent results are highlighted in **bold**.

Method	MOTSP20			MOTSP50			MOTSP100		
	HV	Gap	Time	HV	Gap	Time	HV	Gap	Time
Weight-Sum LKH	0.32	5.83%	(4.5m)	0.36	5.48%	(44m)	0.45	4.03%	(3.5h)
Weight-Sum OR Tools	0.31	8.48%	(4.1m)	0.31	15.5%	(39m)	0.41	11.2%	(3.1h)
MOGLS-MOTSP	0.27	19.6%	(2h)	0.27	27.4%	(5h)	0.33	30.5%	(13h)
NSGAII-MOTSP	0.20	39.9%	(47m)	0.18	49.3%	(56m)	0.25	48.4%	(1h)
MOEA/D-MOTSP	0.21	36.6%	(3.3h)	0.20	46.7%	(3.7h)	0.27	42.7%	(4.1h)
DRL-MOA (105 models)	0.26	21.6%	(2s)	0.28	23.0%	(5s)	0.34	28.8%	(19s)
AM-MOCO (105 models)	0.32	5.52%	(2s)	0.33	6.02%	(7s)	0.42	6.53%	(21s)
P-MOCO (105 pref.)	0.32	5.65%	(2s)	0.36	5.76%	(6s)	0.44	5.52%	(19s)
P-MOCO (105 pref., aug)	0.32	5.46%	(2.1m)	0.36	5.43%	(6.5m)	0.45	4.39%	(20m)
P-MOCO (1,035 pref.)	0.33	2.08%	(19s)	0.36	4.03%	(48s)	0.46	2.12%	(2.9m)
P-MOCO (10,011 pref.)	**0.34**	**0.00%**	(3m)	**0.38**	**0.00%**	(9m)	**0.47**	**0.00%**	(33m)

augmentation, which significantly outperforms other methods but is beaten by the strong LKH solver on the MOTSP100 comparison. For the three objective problems, our method can further improve its performance by generating much more trade-off solutions within a reasonable time, which is not supported by other methods. As shown in Figure 2 and Figure 5, our method has a uniform mapping from the preferences to the corresponding solutions, and can generate a dense prediction to the whole Pareto front. Decision-makers can easily obtain any preferred trade-off solutions as they want. This flexibility could be crucial and desirable for many real-world applications.

MOCVRP. In this problem, each node has a demand, and we need to construct multiple return routes for a vehicle with a fixed capacity from the same depot to handle all demands. The conflicting objectives we consider are to minimize the tour length for all routes and also the tour length for the longest routes (the makespan in scheduling theory) (Lacomme et al., 2006). All the non-learning algorithm frameworks use the problem-specific constructive heuristics and local search method proposed in Lacomme et al. (2006) to search valid non-dominated solutions. The results in Table 2 show that our method significantly outperforms the non-learning heuristics both in solution quality and running time. It also outperforms AM-MOCO with 100 individual models, which might occur due to the asymmetric objective scales. We provide further analysis in Appendix D.4.

MOKP. The multiobjective 0-1 knapsack problem can be found in many real-world applications (Bazgan et al., 2009). We consider the uni-dimension problem, where each item has multiple values and one weight. The goal is to select a subset of items to maximize all obtained values with a weight constraint. The non-learning methods use binary coding with a greedy transformation heuristic to maintain feasibility (Ishibuchi et al., 2014). We also include weight-sum scalarization baselines with exact dynamic programming (DP) and the strong greedy search based on the value-weight ratio. According to the results in Table 2, our method has the best performance for all problems. The DP method is also outperformed since the weight-sum scalarization can only find the convex hull of the Pareto front. The Tchebycheff scalarization of MOKP is not a KP problem, while our method is more flexible to use Tchebycheff scalarization on the reward function. We also report the zero-shot generalization results to problems with up to 10 objectives and 500 items in Appendix D.5.

Out-of-Distribution Problems and Active Adaption. We also validate our method's generalization performance on 6 out-of-distribution (OOD) MOTSP problem from Fonseca et al. (2006), which have exact Pareto fronts by costly exhaustive search. The results are shown in Appendix D.2 due to page limit. With active adaption, our method can achieve good performance (1% - 1.5% HV gap to exact Pareto fronts) on these OOD problems.

8 CONCLUSION

In this paper, we propose a novel preference-conditioned method to approximate the whole Pareto front for MOCO problems with a single model. It provides extra flexibility for decision-makers to directly obtain arbitrary trade-off solutions without any extra search, which is a more principled way to deal with MOCO. Experiments on different problems confirm that our proposed method can significantly outperform other methods in performance, speed and model efficiency.

REFERENCES

Cristina Bazgan, Hadrien Hugot, and Daniel Vanderpooten. Solving efficiently the 0-1 multi-objective knapsack problem. *Computers & Operations Research*, 36(1):260–279, 2009.

Cristina Bazgan, Florian Jamain, and Daniel Vanderpooten. Discrete representation of the non-dominated set for multi-objective optimization problems using kernels. *European Journal of Operational Research*, 260(3):814–827, 2017.

Irwan Bello, Hieu Pham, Quoc V Le, Mohammad Norouzi, and Samy Bengio. Neural combinatorial optimization with reinforcement learning. In *International Conference on Learning Representations (ICLR) Workshops*, 2017.

Yoshua Bengio, Andrea Lodi, and Antoine Prouvost. Machine learning for combinatorial optimization: a methodological tour d'horizon. *European Journal of Operational Research*, 2020.

Pierre Bonami, Andrea Lodi, and Giulia Zarpellon. Learning a classification of mixed-integer quadratic programming problems. In *International Conference on the Integration of Constraint Programming, Artificial Intelligence, and Operations Research (CPAIOR)*, 2018.

Quentin Cappart, Didier Chételat, Elias Khalil, Andrea Lodi, Christopher Morris, and Petar Veličković. Combinatorial optimization and reasoning with graph neural networks. In *International Joint Conferences on Artificial Intelligence (IJCAI)*, 2021.

Xinyun Chen and Yuandong Tian. Learning to perform local rewriting for combinatorial optimization. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2019.

Eng Ung Choo and DR Atkins. Proper efficiency in nonconvex multicriteria programming. *Mathematics of Operations Research*, 8(3):467–470, 1983.

Hanjun Dai, Elias B Khalil, Yuyu Zhang, Bistra Dilkina, and Le Song. Learning combinatorial optimization algorithms over graphs. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2017.

Indraneel Das and John E Dennis. Normal-boundary intersection: A new method for generating the pareto surface in nonlinear multicriteria optimization problems. *SIAM journal on optimization*, 8(3):631–657, 1998.

Kalyanmoy Deb, Amrit Pratap, Sameer Agarwal, and TAMT Meyarivan. A fast and elitist multiobjective genetic algorithm: Nsga-ii. *IEEE Transactions on Evolutionary Computation*, 6(2):182–197, 2002.

Michel Deudon, Pierre Cournut, Alexandre Lacoste, Yossiri Adulyasak, and Louis-Martin Rousseau. Learning heuristics for the tsp by policy gradient. In *International Conference on the Integration of Constraint Programming, Artificial Intelligence, and Operations Research (CPAIOR)*, 2018.

Iddo Drori, Anant Kharkar, William R Sickinger, Brandon Kates, Qiang Ma, Suwen Ge, Eden Dolev, Brenda Dietrich, David P Williamson, and Madeleine Udell. Learning to solve combinatorial optimization problems on real-world graphs in linear time. In *IEEE International Conference on Machine Learning and Applications (ICMLA)*, 2020.

Vijay Prakash Dwivedi, Chaitanya K Joshi, Thomas Laurent, Yoshua Bengio, and Xavier Bresson. Benchmarking graph neural networks. *arXiv preprint arXiv:2003.00982*, 2020.

Benjamin Ehret, Christian Henning, Maria R. Cervera, Alexander Meulemans, Johannes von Oswald, and Benjamin F. Grewe. Continual learning in recurrent neural networks. In *International Conference on Learning Representations (ICLR)*, 2021.

Matthias Ehrgott. *Multicriteria optimization*, volume 491. Springer Science & Business Media, 2005.

Matthias Ehrgott and Xavier Gandibleux. A survey and annotated bibliography of multiobjective combinatorial optimization. *OR-Spektrum*, 22(4):425–460, 2000.

Matthias Ehrgott and Xavier Gandibleux. *Multiobjective combinatorial optimization—theory, methodology, and applications*, pp. 369–444. Springer, 2003.

Matthias Ehrgott and Xavier Gandibleux. Hybrid metaheuristics for multi-objective combinatorial optimization. In *Hybrid metaheuristics*, pp. 221–259. Springer, 2008.

Patrick Emami and Sanjay Ranka. Learning permutations with sinkhorn policy gradient. *arXiv preprint arXiv:1805.07010*, 2018.

Kostas Florios and George Mavrotas. Generation of the exact pareto set in multi-objective traveling salesman and set covering problems. *Applied Mathematics and Computation*, 237:1–19, 2014.

Carlos M Fonseca, Luís Paquete, and Manuel López-Ibánez. An improved dimension-sweep algorithm for the hypervolume indicator. In *IEEE Congress on Evolutionary Computation (CEC)*, 2006.

Maxime Gasse, Didier Chételat, Nicola Ferroni, Laurent Charlin, and Andrea Lodi. Exact combinatorial optimization with graph convolutional neural networks. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2019.

David Ha, Andrew M. Dai, and Quoc V. Le. Hypernetworks. In *International Conference on Learning Representations (ICLR)*, 2017.

Pierre Hansen. Bicriterion path problems. In *Multiple criteria decision making theory and application*, 1980.

Keld Helsgaun. An effective implementation of the lin–kernighan traveling salesman heuristic. *European Journal of Operational Research*, 126(1):106–130, 2000.

Arne Herzel, Stefan Ruzika, and Clemens Thielen. Approximation methods for multiobjective optimization problems: A survey. *INFORMS Journal on Computing*, 2021.

Hisao Ishibuchi, Naoya Akedo, and Yusuke Nojima. Behavior of multiobjective evolutionary algorithms on many-objective knapsack problems. *IEEE Transactions on Evolutionary Computation*, 19(2):264–283, 2014.

Andrzej Jaszkiewicz. Genetic local search for multi-objective combinatorial optimization. *European Journal of Operational Research*, 137(1):50–71, 2002.

Siddhant M. Jayakumar, Jacob Menick, Wojciech M. Czarnecki, Jonathan Schwarz, Jack Rae, Simon Osindero, Yee Whye Teh, Tim Harley, and Razvan Pascanu. Multiplicative interactions and where to find them. In *International Conference on Learning Representations (ICLR)*, 2020.

Chaitanya K Joshi, Thomas Laurent, and Xavier Bresson. An efficient graph convolutional network technique for the travelling salesman problem. *arXiv preprint arXiv:1906.01227*, 2019.

Chaitanya K Joshi, Quentin Cappart, Louis-Martin Rousseau, Thomas Laurent, and Xavier Bresson. Learning tsp requires rethinking generalization. *arXiv preprint arXiv:2006.07054*, 2020.

Nicolas Jozefowiez, Frédéric Semet, and El-Ghazali Talbi. Multi-objective vehicle routing problems. *European Journal of Operational Research*, 189(2):293–309, 2008.

Nikolaos Karalias and Andreas Loukas. Erdos goes neural: an unsupervised learning framework for combinatorial optimization on graphs. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

Vladlen Koltun and Christos H Papadimitriou. Approximately dominating representatives. In *International Conference on Database Theory*, pp. 204–214. Springer, 2005.

Wouter Kool, Herke van Hoof, and Max Welling. Attention, learn to solve routing problems! In *International Conference on Learning Representations (ICLR)*, 2019.

Wouter Kool, Herke van Hoof, Joaquim Gromicho, and Max Welling. Deep policy dynamic programming for vehicle routing problems. *arXiv preprint arXiv:2102.11756*, 2021.

Markus Kruber, Marco E Lübbecke, and Axel Parmentier. Learning when to use a decomposition. In *International Conference on the Integration of Constraint Programming, Artificial Intelligence, and Operations Research (CPAIOR)*, 2017.

Yeong-Dae Kwon, Jinho Choo, Byoungjip Kim, Iljoo Yoon, Youngjune Gwon, and Seungjai Min. Pomo: Policy optimization with multiple optima for reinforcement learning. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

Philippe Lacomme, Christian Prins, and Marc Sevaux. A genetic algorithm for a bi-objective capacitated arc routing problem. *Computers & Operations Research*, 33(12):3473–3493, 2006.

Eric Larsen, Sébastien Lachapelle, Yoshua Bengio, Emma Frejinger, Simon Lacoste-Julien, and Andrea Lodi. Predicting tactical solutions to operational planning problems under imperfect information. *arXiv preprint arXiv:1807.11876*, 2018.

Kaiwen Li, Tao Zhang, and Rui Wang. Deep reinforcement learning for multiobjective optimization. *IEEE Transactions on Cybernetics*, 2020.

Zhuwen Li, Qifeng Chen, and Vladlen Koltun. Combinatorial optimization with graph convolutional networks and guided tree search. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2018.

Xi Lin, Zhiyuan Yang, Qingfu Zhang, and Sam Kwong. Controllable pareto multi-task learning. *arXiv preprint arXiv:2010.06313*, 2020.

Michal Lisicki, Arash Afkanpour, and Graham W Taylor. Evaluating curriculum learning strategies in neural combinatorial optimization. *arXiv preprint arXiv:2011.06188*, 2020.

Andrea Lodi and Giulia Zarpellon. On learning and branching: a survey. *TOP*, 25(2):207–236, 2017.

Thibaut Lust and Jacques Teghem. The multiobjective traveling salesman problem: A survey and a new approach. In *Advances in Multi-Objective Nature Inspired Computing*, pp. 119–141. Springer, 2010a.

Thibaut Lust and Jacques Teghem. Two-phase pareto local search for the biobjective traveling salesman problem. *Journal of Heuristics*, 16(3):475–510, 2010b.

Nina Mazyavkina, Sergey Sviridov, Sergei Ivanov, and Evgeny Burnaev. Reinforcement learning for combinatorial optimization: A survey. *Comput. Oper. Res.*, 2021.

Aviv Navon, Aviv Shamsian, Ethan Fetaya, and Gal Chechik. Learning the pareto front with hypernetworks. In *International Conference on Learning Representations (ICLR)*, 2021.

Mohammadreza Nazari, Afshin Oroojlooy, Martin Takáč, and Lawrence V Snyder. Reinforcement learning for solving the vehicle routing problem. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2018.

Alex Nowak, Soledad Villar, Afonso S Bandeira, and Joan Bruna. Revised note on learning algorithms for quadratic assignment with graph neural networks. In *IEEE Data Science Workshop (DSW)*, 2018.

Christos H Papadimitriou and Mihalis Yannakakis. On the approximability of trade-offs and optimal access of web sources. In *IEEE Symposium on Foundations of Computer Science (FOCS)*, 2000.

Laurent Perron and Vincent Furnon. Or-tools, 2019. URL https://developers.google.com/optimization/.

Yoshikazu Sawaragi, HIROTAKA NAKAYAMA, and TETSUZO TANINO. *Theory of multiobjective optimization*. Elsevier, 1985.

Jürgen Schmidhuber. Learning to control fast-weight memories: an alternative to dynamic recurrent networks. *Neural Computation*, 4(1):131–139, 1992.

Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jon Shlens, and Zbigniew Wojna. Rethinking the inception architecture for computer vision. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2016.

Renato Tinós, Keld Helsgaun, and Darrell Whitley. Efficient recombination in the lin-kernighan-helsgaun traveling salesman heuristic. In *International Conference on Parallel Problem Solving from Nature (PPSN)*, 2018.

Sergei Vassilvitskii and Mihalis Yannakakis. Efficiently computing succinct trade-off curves. *Theoretical Computer Science*, 348(2-3):334–356, 2005.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2017.

Petar Veličković and Charles Blundell. Neural algorithmic reasoning. *arXiv preprint arXiv:2105.02761*, 2021.

Natalia Vesselinova, Rebecca Steinert, Daniel F Perez-Ramirez, and Magnus Boman. Learning combinatorial optimization on graphs: A survey with applications to networking. *IEEE Access*, 8:120388–120416, 2020.

Oriol Vinyals, Meire Fortunato, and Navdeep Jaitly. Pointer networks. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2015.

Johannes von Oswald, Christian Henning, João Sacramento, and Benjamin F. Grewe. Continual learning with hypernetworks. In *International Conference on Learning Representations (ICLR)*, 2020.

Jyrki Wallenius, James S Dyer, Peter C Fishburn, Ralph E Steuer, Stanley Zionts, and Kalyanmoy Deb. Multiple criteria decision making, multiattribute utility theory: Recent accomplishments and what lies ahead. *Management Science*, 54(7):1336–1349, 2008.

Ronald J Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine learning*, 8(3-4):229–256, 1992.

Hong Wu, Jiahai Wang, and Zizhen Zhang. Modrl/d-am: Multiobjective deep reinforcement learning algorithm using decomposition and attention model for multiobjective optimization. In *International Symposium on Intelligence Computation and Applications (ISICA)*, 2020.

Qingfu Zhang and Hui Li. MOEA/D: A multiobjective evolutionary algorithm based on decomposition. *IEEE Transactions on Evolutionary Computation*, 11(6):712–731, 2007.

Yongxin Zhang, Jiahai Wang, Zizhen Zhang, and Yalan Zhou. Modrl/d-el: Multiobjective deep reinforcement learning with evolutionary learning for multiobjective optimization. In *International Joint Conference on Neural Networks (IJCNN)*, 2021a.

Zizhen Zhang, Zhiyuan Wu, and Jiahai Wang. Meta-learning-based deep reinforcement learning for multiobjective optimization problems. *arXiv preprint arXiv:2105.02741*, 2021b.

Eckart Zitzler, Lothar Thiele, Marco Laumanns, Carlos M Fonseca, and Viviane Grunert Da Fonseca. Performance assessment of multiobjective optimizers: An analysis and review. *IEEE Transactions on Evolutionary Computation*, 7(2):117–132, 2003.

Eckart Zitzler, Dimo Brockhoff, and Lothar Thiele. The hypervolume indicator revisited: On the design of pareto-compliant indicators via weighted integration. In *International Conference on Evolutionary Multi-Criterion Optimization*, pp. 862–876. Springer, 2007.

We provide more discussion, details on the method and MOCO problems, experimental results and analysis in this appendix. Specifically:

- **Learning Ability and Approximation Analysis:** We discuss the learning ability of our proposed method, and give a thorough analysis on its approximation ability in Section A.
- **Method and Problem Detail:** We provide the details on our proposed model and the MOCO problems in Section B and Section C, respectively.
- **More Experimental Results:** We give a detailed introduction to the hypervolume indicator, and present more experimental results with analysis in Section D.

A   PARETO SET LEARNING AND APPROXIMATION ANALYSIS

A.1   PARETO SET LEARNING AND CONVERGENCE GUARANTEE

In this work, we propose a novel neural combinatorial optimization (NCO) method to approximate the whole Pareto set for MOCO problems with a single model. The proposed learning-based MOCO solver can directly generate arbitrary trade-off solutions without extra optimization. We believe it is a principled way to solve MOCO problems.

As briefly discussed in the main paper, however, the lack of an exact optimality guarantee is a limitation of the proposed method, which is also the case for previous work on single-objective neural combinatorial optimization (Vinyals et al., 2015; Bello et al., 2017; Kool et al., 2019). This limitation is mainly due to the fact that many single-objective combinatorial optimization (CO) problems are NP-hard, and the size of Pareto sets for a MOCO problem would be exponentially huge, which makes it very difficult to exactly solving the problems (Ehrgott, 2005; Herzel et al., 2021). In addition, the training for the parameterized policy (neural network model) cannot guarantee to fit all training problems perfectly. The generalization ability to problem instances with different patterns (out-of-distribution generalization) is another critical issue that makes it difficult to give an exact optimality guarantee to the proposed learning-based algorithm.

On the other hand, our proposed model is an efficient mapping from the preferences to the corresponding approximate set of the Pareto optimal solutions. It provides a flexible way for decision-makers to obtain an approximate solution with their preferred trade-off directly. The experimental results also show that our proposed method can generate good approximate Pareto sets for three different MOCO problems. In the next subsection, we provide a thorough discussion on the approximation ability of our proposed method.

A.2   APPROXIMATION ANALYSIS

For a MOCO problem, the number of Pareto solutions could be exponentially large with respect to its input size, which makes the problem intractable (Ehrgott, 2005; Herzel et al., 2021). The preference-based scalarization method (Choo & Atkins, 1983; Zhang & Li, 2007) we used provides a principled way to link the Pareto solutions with preference, allowing us to tackle the problem in a systematic manner. In this work, we propose to approximately solve the scalarized subproblem with all preferences via a single model.

We first briefly review the weighted scalarization method and its Pareto optimality guarantee as discussed in the main paper. Then we provide further discussion on the approximation analysis.

Our proposed method decomposes a MOCO problem into preference-based subproblems with the weighted-Tchebycheff scalarization (Weighted-TCH):

$$\min_{x \in \mathcal{X}} g_{\text{tch}}(x|\lambda) = \min_{x \in \mathcal{X}} \max_{1 \leq i \leq m} \{\lambda_i |f_i(x) - (z_i^* - \varepsilon)|\}, \tag{10}$$

where z_i^* is the ideal value for objective $f_i(x)$ (e.g., the lower bound), and $u_i^* = z_i^* - \varepsilon$ is a utopia value with small positive component ε. The preference vector $\lambda \in \mathbb{R}^m$ satisfies $\lambda_i \geq 0$ and $\sum_{i=1}^m \lambda_i = 1$, where λ_i is the preference for the i-th objective. This approach has a desirable property:

Lemma 1 (Choo & Atkins (1983)). *A feasible solution $x \in \mathcal{X}$ is Pareto optimal if and only if there is a weight vector $\lambda > 0$ such that x is an optimal solution to the problem (10).*

According to **Lemma 1**, we can obtain any Pareto solution by solving the Weighted-TCH subproblem with a specific weight. However, the weight for each Pareto solution depends on its objective values, which are not known in advance (Sawaragi et al., 1985; Ehrgott, 2005). The decision-maker still needs to solve multiple subproblems with different preferences to find a desirable solution. To find the whole Pareto set, it needs to solve an exponentially huge number of subproblems.

Given a problem instance s, our proposed model provides a single mapping function $x_\lambda = h(\lambda)$ from any preference λ to its corresponding solution x_λ, which is constructed by the preference-based policy $p_{\boldsymbol{\theta}(\lambda)}(x|s)$. In the ideal case, if all generated solutions x_λ are the optimal solutions x_λ^* of problem (10) with preference λ, according to **Lemma 1**, our proposed model can generate the whole Pareto set (all Pareto optimal solutions) for the original MOCO problem.

In practice, we are interested in the proposed method's approximation ability. We find that its performance strongly depends on the approximation ability of the parameterized policy (neural network model) on the single-objective scalarized subproblem. We first give an informal claim on our method's approximation ability, then provide detailed explanations and discussions.

(Informal) Claim 1. If the proposed method can approximately solve the subproblem (10) with any preference λ, it can generate a good approximation to the whole Pareto set for the MOCO problem.

To support this claim, we follow the traditional ε-Pareto approximate method for MOCO problems (Papadimitriou & Yannakakis, 2000; Herzel et al., 2021). First, an ε-Pareto domination relation between two individual solutions can be defined as:

Definition 3 (ε-Pareto Domination). For a MOCO problem and an $\varepsilon > 0$, let $x_a, x_b \in \mathcal{X}$, x_a is said to ε-dominate x_b ($x_a \prec_\varepsilon x_b$) if $f_i(x_a) \leq (1+\varepsilon)f_i(x_b), \forall i \in \{1, \cdots, m\}$.

This definition is a natural generalization from the $(1 + \varepsilon)$-approximation for single-objective optimization. With this concept, an ε-approximate Pareto set (Papadimitriou & Yannakakis, 2000) can be defined as:

Definition 4 (ε-Approximate Pareto Set). For an $\varepsilon > 0$, a set $\mathcal{P}_\varepsilon \subset \mathcal{X}$ is an ε-approximate Pareto set, if for any feasible solution $x \in \mathcal{X}$, there exists a solution $x' \in \mathcal{P}_\varepsilon$ such that $x' \prec_\varepsilon x$.

In other words, all feasible solutions of the MOCO problem can be almost dominated by some solutions in $\mathcal{P}_\varepsilon$ (Papadimitriou & Yannakakis, 2000). When the Pareto set is intractable and hard to find, the ε-approximate Pareto set would be a reasonable choice to achieve in practice. Each MOCO problem has a unique Pareto set, but can have different ε-approximate Pareto sets. The ability of our proposed method to find an ε-approximate Pareto set strongly depends on its performance on each single-objective preference-based subproblem.

Theorem 1. *Let x_λ^* denotes the optimal solution of the problem (10) with preference λ, if the proposed method can generate an approximate solution $x_\lambda \prec_\varepsilon x_\lambda^*$ for any preference λ, it is able to generate an ε-approximate Pareto set $\mathcal{P}_\varepsilon$ to the MOCO problem.*

Proof. Let $\mathcal{P}$ be the Pareto set for a MOCO problem, for any $x_{\text{Pareto}} \in \mathcal{P}$, according to **Lemma 1**, there is a weight vector $\lambda > 0$ such that $x = x_\lambda^*$ is the optimal solution for subproblem (10) with a specific preference λ. Therefore, our proposed method can generate an approximated solution $x_\lambda \prec_\varepsilon x_\lambda^* = x_{\text{Pareto}}$. By generating approximate solutions for all $x_{\text{Pareto}} \in \mathcal{P}$, our proposed method is able to generate an ε-approximate Pareto set $\mathcal{P}_\varepsilon$ to the MOCO problem. $\square$

A crucial concern would be the required number of solutions in the ε-approximate Pareto set $\mathcal{P}_\varepsilon$. If the required number is exponential to the input size, the approximation itself is also intractable. In their seminal work, Papadimitriou & Yannakakis (2000) establish a promising result:

Theorem 2 (Papadimitriou & Yannakakis (2000)). *For any multiobjective optimization problem and any ε, there is an ε-approximate Pareto set $\mathcal{P}_\varepsilon$ of which the size is polynomial in the number of solutions and $\frac{1}{\varepsilon}$ (but exponential in the number of objectives).*

However, the existence of such a set still does not mean that it can be easily found (Papadimitriou & Yannakakis, 2000; Herzel et al., 2021). The computability (whether $\mathcal{P}_\varepsilon$ can be constructed in polynomial time) would be hard to justify for a real-world problem. For a new unseen problem instance in practice, our proposed method might still need to generate an exponentially large number

of solutions to construct an ε-approximate Pareto set $\mathcal{P}_\varepsilon$. It is also unclear how to properly select a set of preferences in advance. Many research efforts have been made on developing approximation methods for solving MOCO problems in the past decades (Herzel et al., 2021; Hansen, 1980; Papadimitriou & Yannakakis, 2000; Vassilvitskii & Yannakakis, 2005; Koltun & Papadimitriou, 2005; Bazgan et al., 2017). In future work, it is important to better leverage the current advanced approximation strategies to design more efficient preference-based methods. In the learning-based optimization scenario we consider, it is also possible to learn the suitable approximation method and/or preference distribution directly from the data (problem instances).

B   DETAILS ON THE PROPOSED MODEL

B.1   MODEL SETTING

Table 4: Model Information.

	#Models	#Total Params	#Encoder Params	#Decoder Params	#Preference
Attention Model	1	1.3M	1.2M	0.1M	Fixed 1
P-MOCO (Ours)	1	1.4M	1.2M	0.2M	Flexible

We use the same model for all MOCO problems while tuning the input size and mask method for each problem. Table 4 shows the number of parameters of a standard single-objective attention model (Kool et al., 2019) and our proposed preference-based multiobjective attention model. Our model supports flexible preference assignment at the inference time with a small overhead, while the other neural MOCO methods all require training multiple AM models for different preferences. We build the single-preference attention models as well as our model following the implementation in Kwon et al. (2020).

Attention Encoder. The encoder we use is the standard attention encoder as in Kool et al. (2019), and it is shared by all preferences. The encoder has 6 attention layers, and 128-dimensional node embedding for the input nodes. Each attention layer has a multi-head attention (MHA) with eight 16-dimensional heads, and a fully connected layer (FC) with one 512-dimension hidden sublayer. The encoder also includes skip-connection and batch normalization for each attention layer. We use the same model for all MOCO problems (MOTSP, MOCVRP, MOKP) but with different input dimensions for each problem, which will be introduced in the next section.

Preference-Conditioned Decoder. The decoder's main model structure is the same as the AM decoder (Kool et al., 2019). It has one multi-head attention layer with eight 16-dimensional heads similar to the encoder, but without skip-connection and batch normalization. The decoder uses a single 128-dimensional attention head to calculate the probabilities of selecting different nodes at each step. Different problems have different masking methods for probability calculation.

We use a simple MLP model to generate the preference-conditioned parameters for the decoder. For all MOCO problems, the MLP model has two 128-dimensional hidden layers with ReLu activation. The input is an m-dimensional preference vector λ which satisfies $\lambda_i \geq 0$ and $\sum_{i=1}^m \lambda_i = 1$, where m is the number of objectives and λ_i is the preference for the i-th objective. We adopt the parameter compression approach in Ha et al. (2017) to control the model size. The MLP model first generates a hidden embedding $e(\lambda) = \mathbf{MLP}(\lambda|\psi)$, then maps the hidden embedding to the decoder parameters via linear projection $\theta_{\mathbf{decoder}} = We(\lambda) + b$. The learnable parameters are ψ for the MLP model $\mathbf{MLP}(\lambda|\psi)$ and the parameter matrices W and b for the decoder.

At time step t, with the learned parameters $\boldsymbol{\theta}_{\text{decoder}}(\lambda) = [W_C(\lambda), W_Q(\lambda), W_K(\lambda), W_{\text{MHA}}(\lambda)]$ conditioned on the preference λ, the decoder first constructs a context embedding $\hat{\boldsymbol{h}}_{(C)} = W_C(\lambda)[\bar{\boldsymbol{h}}_{(G)}, \boldsymbol{h}_{\boldsymbol{\pi}_1}, \boldsymbol{h}_{\boldsymbol{\pi}_{t-1}}]$ from the embeddings for graph $\bar{\boldsymbol{h}}_{(G)}$, the first selected node $\boldsymbol{h}_{\boldsymbol{\pi}_1}$, and the last selected node $\boldsymbol{h}_{\boldsymbol{\pi}_{t-1}}$. The matrix $W_C(\lambda) \in \mathbb{R}^{d \times 3d}$ projects the concatenated $3d$-dimensional vector to a d-dimensional vector. Then we update the context embedding via an m-head Multi-Head Attention (MHA) (Vaswani et al., 2017) with all node embeddings $\{\boldsymbol{h}_1, \cdots, \boldsymbol{h}_n\}$:

$$\boldsymbol{h}_{(C)} = \mathbf{MHA}(Q = \hat{\boldsymbol{h}}_{(C)}, K = \{\boldsymbol{h}_1, \cdots, \boldsymbol{h}_n\}, V = \{\boldsymbol{h}_1, \cdots, \boldsymbol{h}_n\}|W_{\mathbf{MHA}}(\lambda)), \qquad (11)$$

where Q, K, V are the query, key and value for MHA, and $W_{\mathbf{MHA}}(\lambda)$ represents the parameters in the MHA. We set the number of heads $h = 8$ as in the AM paper (Kool et al., 2019).

We can calculate the logit for selecting the j-th node with single-head attention:

$$\text{logit}_j = \begin{cases} C \cdot \tanh(\frac{(W_Q(\lambda)\boldsymbol{h}_{(C)})^T(W_Q(\lambda)\boldsymbol{h}_j)}{\sqrt{d}}) & \text{if } j \neq \boldsymbol{\pi}_{t'} \quad \forall t' < t \\ -\infty & \text{otherwise.} \end{cases} \tag{12}$$

All already visited nodes are masked with $-\infty$ and will not be selected as the next node. The logits of the rest nodes are clipped into $[-C, C](C = 10)$ as in the AM model (Kool et al., 2019). The probability for choosing the j-th node at time step t can be calculated as $p_{\boldsymbol{\theta}(\lambda)}(\boldsymbol{\pi}_t = j | s, \boldsymbol{\pi}_{1:t-1}) = e^{\text{logit}_j} / \sum_k e^{\text{logit}_k}$. With this probability, the decoder can construct a valid tour in sequence.

Training Procedure. For all problems, we train our proposed model for 200 epochs, with $100,000$ problem instances randomly generated on the fly at each epoch. At each iteration step, we need to sample K preferences, B problem instances, and N tours to calculate the policy gradient. We set $K \times B = 64$ to make the batch of 64 instances for training a single AM model, and let N equal to the problem size (e.g., the number of nodes) as in Kwon et al. (2020). We find the model performance is equally good for setting $K = 1, 2$ and 4, and keep using $K = 1$ for all problems.

For the AM-MOCO baseline, we adapt the transfer training approach in Li et al. (2020) to train multiple AM models for different preferences. We first train a single AM model with a single preference on one objective from scratch with 200 epochs, then transfer its parameter to the model for neighbor subproblem with similar preference, and fine-tune the new model with 5 epochs. With sequentially transfer and fine-tune, we can obtain a set of trained models for different preferences. In most experiments, we set the number of preferences as 101. Therefore, we need to build 101 AM models with total 700 training epochs.

Instance Augmentation for MOCO: Due to the design choice of minimal essential change (e.g., the preference-conditioned decoder), our method can also enjoy the current improvements that were originally proposed for the single objective NCO. Here, we generalize the instance augmentation method proposed in Kwon et al. (2020) to the MOCO version.

The key idea of instance augmentation for NCO is to find multiple efficient transformations for the original problem such that they share the same optimal solution. Then, we can use an NCO method to solve all problems and select the best solution among all obtained (potentially different) solutions. In this way, we have a more robust result similar to the test-time augmentation for computer vision (Szegedy et al., 2016). For the single-objective euclidean TSP and CVRP, there is a set of straightforward transformations, which simply flips or rotates the coordinate for all the 2D locations in a problem instance (Kwon et al., 2020). For a location (x, y), there is eight different transformation, namely, $\{(x, y), (y, x), (x, 1-y), (y, 1-x), (1-x, y), (1-y, x), (1-x, 1-y), (1-y, 1-x)\}$.

For an m-objective euclidean MOTSP problem, the concrete location representations are independent for each objective. Therefore, we can independently apply different transformations for each objective. Consider the above eight different transformations for each objective, we can have 8^m different problem transformations for an MOTSP instance. We have fixed 8 transformations for MOCVRP since it only has one 2D coordinate, and no transformation for MOKP. The details for each problem can be found in the next section.

B.2 TRAINING EFFICIENCY

We use the same amount of samples to train our proposed preference-based model as the other single-objective solvers need (Kool et al., 2019; Kwon et al., 2020). Indeed, our proposed model requires significantly fewer samples and training epochs, compared to the other MOCO methods that need to build multiple models for different preferences.

We compare our model's performance on one of the objective (e.g., with preference $(1, 0)$) with the other SOTA single-objective solver and learning-based solver, the results are shown in Table 5. The results of Concorde/LKH/OR Tools are from Kwon et al. (2020), and we run the learning-based solver by ourselves. We report the average performance over $10,000$ test instances. AM is the single-objective solver (one model in AM-MOCO), P-MOCO (single preference) is our proposed model but only training on a single fixed preference $(1, 0)$, and P-MOCO (all preferences) is our

Table 5: The Performance on a Single Preference.

	Concorde	LKH	OR Tools	AM (Single Obj.)	P-MOCO (Single Pref.)	P-MOCO (all pref.)
TSP20	3.83 (5m)	3.83 (42s)	3.86 (1m)	3.83 (1s)	3.83 (1s)	3.83 (1s)
TSP50	5.69 (13m)	5.69 (6m)	5.85 (5m)	5.76 (3s)	5.77 (3s)	5.77 (3s)
TSP100	7.76 (1h)	7.76 (25m)	8.06 (23m)	7.98 (10s)	7.97 (10s)	7.98 (10s)

proposed model with the reported result on the preference $(1, 0)$. With the same amount of training samples, our model has similar single-objective performance with learning-based single-objective solver, while it can additionally approximate the whole Pareto front. The learning-based solver's performance can be further improved by sampling or active search.

These results indicate that we can use a single encoder to efficiently learn a shared representation for all trade-offs among different objectives, and there is a positive knowledge transfer among preferences during the learning procedure. In addition, it also confirms the assumption that similar preferences should have similar corresponding (approximate) Pareto solutions for the multiobjective problems we consider in this paper. These findings could be useful to design more powerful learning-based models for MOCO in the future.

C   DETAILS OF THE MOCO PROBLEMS

This section introduces the detailed problem formulation for the MOTSP, MOCVRP and MOKP we used in this work. We also provide the model configuration (e.g., input size, masks) for each problem.

C.1   MOTSP

We consider the Euclidean multiobjective traveling salesman problem (Euclidean MOTSP), which is widely used in the MOCO community (Lust & Teghem, 2010b; Florios & Mavrotas, 2014). Its single objective counterpart, 2D Euclidean TSP, has also been studied in single-objective neural combinatorial optimization (NCO) (Vinyals et al., 2015; Bello et al., 2017; Kool et al., 2019). A general m-objective MOTSP instance s with n nodes has m $n \times n$ cost matrices $\{C^i = (c^i_{jk}), i = 1, \cdots, m\}$ for m different costs. The problem is to find a tour (cyclic permutation $\boldsymbol{\pi}$) to minimize all the costs:

$$\min L(\boldsymbol{\pi}|s) = \min(L_1(\boldsymbol{\pi}|s), L_2(\boldsymbol{\pi}|s), \cdots, L_m(\boldsymbol{\pi}|s)),$$

$$\text{where } L_i(\boldsymbol{\pi}|s) = c^i_{\boldsymbol{\pi}(n)\boldsymbol{\pi}(1)} + \sum_{j=1}^{n-1} c^i_{\boldsymbol{\pi}(j)\boldsymbol{\pi}(j+1)}. \tag{13}$$

In a Euclidean MOTSP, the cost information is stored in the nodes rather than the edges. The j-th node has a $2m$-dimensional vector $[\boldsymbol{x}^1_j, \boldsymbol{x}^2_j, \cdots, \boldsymbol{x}^m_j]$ where $\boldsymbol{x}^i_j \in \mathbb{R}^2$ is a 2D coordinate for the i-th objective. The i-th cost $c^i_{jk} = ||\boldsymbol{x}^i_j - \boldsymbol{x}^i_k||_2$ is the Euclidean distance for moving from node j to k.

If we only have one objective $m = 1$, it reduces to the single-objective 2D Euclidean TSP:

$$\min_{\boldsymbol{\pi}} L_1(\boldsymbol{\pi}|s) = ||\boldsymbol{x}_{\boldsymbol{\pi}(n)} - \boldsymbol{x}_{\boldsymbol{\pi}(1)}||_2 + \sum_{j=1}^{n-1} ||\boldsymbol{x}_{\boldsymbol{\pi}(i)} - \boldsymbol{x}_{\boldsymbol{\pi}(i+1)}||_2. \tag{14}$$

The single-objective TSP is already NP-hard, so does the MOTSP. In addition, the Pareto set of MOTSP has a exponential cardinality with respect to its input size (e.g., number of nodes), so it is intractable even for the 2-objective case (Ehrgott & Gandibleux, 2003).

Problem Instance. Similar to the previous work on single-objective NCO (Lust & Teghem, 2010b; Florios & Mavrotas, 2014), we randomly sample all n nodes with uniform distribution on the $2m$-dimensional unit hyper-square (e.g., $[0, 1]^{2m}$) for all problem instances.

Model Details. In m-objective MOTSP, each node has a $2m$-dimensional vector to store all cost information, so the input size is $2m$ for the encoder. To calculate the probability for selecting the

next node, the decoder needs to mask all already visited nodes as unavailable. We have a valid tour when all node is selected (we assume the end node will connect to the start node).

C.2 MOCVRP

The vehicle routing problem (VRP) is a classical generalization of TSP, which has been studied for several decades. This work studies the capacitated vehicle routing problem (CVRP). In this problem, in addition to the location, each node (city) has a demand δ_i needed to be satisfied. There is an extra depot node and a vehicle with a fixed capacity $D > \delta_i, \forall i$ to handle all the demands. The vehicle will always start from the depot node, then goes to different cities to satisfy multiple demands $\sum \delta_i \leq D$, and turns back to the depot node. A solution to this problem is a set of routes that satisfies the demands for all cities.

In the multiobjective problem, we consider two objectives to optimize. The first one is the total tour length as in the single-objective CVRP, and the other one is the tour length for the longest route (which is also called makespan in scheduling theory). This problem has been studied in the MOCO community (Lacomme et al., 2006).

Problem Instance. Similar to the TSP problem, the location of n nodes are uniformly sampled from the unit square. For the demand, similar to the previous work on the single-objective counterpart (Kool et al., 2019; Kwon et al., 2020), we randomly sample discrete δ_i from the set $\{1, \cdots, 9\}$. For problem with size $n = 20, 50, 100$, we set the capacity as $D_{20} = 30$, $D_{50} = 40$ and $D_{100} = 50$, respectively. Without loss of generality, we normalize the demands $\hat{\delta}_i = \frac{\delta_i}{D}$ and capacity $\hat{D} = \frac{D}{D} = 1$ as in the previous work (Kool et al., 2019; Kwon et al., 2020). Split delivery is not allowed in this problem.

Model Details. In the MOCVRP, the depot node has a 2-dimensional location vector, and the other nodes all have 3-dimensional vectors to store their locations and demands. We use different parameter matrices to project the nodes into the input embedding with the same dimension $d_h = 128$. For node selection, the model records the current capacity of the vehicle and the rest demands for all nodes. If a node has been already visited or has demand larger than the vehicle's current capacity, it will be masked as unavailable for the vehicle to visit. If no node is available to visit, the vehicle will go back to the depot. Once all nodes have 0 demands, the node selection is finished and we have a valid solution to the problem.

C.3 MOKP

Knapsack problem (KP) is also a widely studied combinatorial optimization problem. In this work, we consider the 0-1 multiobjective knapsack problem (MOKP) with m objectives and n items:

$$
\begin{aligned}
&\max f(x) = \max(f_1(x), f_2(x), \cdots, f_m(x)), \\
&\text{where } f_i(x) = \sum_{j=1}^{n} v_j^i x_j, \\
&\text{subject to } \sum_{j=1}^{n} w_j x_j \leq W, \quad x_j \in \{0, 1\},
\end{aligned}
\tag{15}
$$

where each item has a weight w_j and m different values $\{v_j^i, i = 1, \cdots, m\}$. The problem (e.g., knapsack) has a maximum weight capacity W, and the goal is to select a set of items within the weight capacity to maximize the sum values for each objective. To make this problem nontrivial, we further assume all values $v_j^i, \forall i, j$, weights $w_j \forall j$ and the total capacity are non-negative real value. The total weight of all items is larger than the capacity $\sum w_i > W$, while each single weight is smaller than the capacity $w_i < W, \forall i = 1, \cdots, n$. The single-objective knapsack problem is NP-hard, so does the MOKP problem (Ehrgott & Gandibleux, 2003).

Problem Instance. We randomly generate the values and weight for each item both uniformly in $[0, 1]$. We consider problems with $n = 50, 100, 200$ nodes, and the weight capacities are $W_{50} = 12.5, W_{100} = W_{200} = 25$ as in the previous work (Bello et al., 2017; Kwon et al., 2020).

Model Details. In an m-objective MOKP, each item has m values and 1 weight, so the input dimension is 3 for the encoder. For node selection at each step, we mask all already selected nodes and nodes with weights larger than the remained capacity as unavailable. We terminate the selection when all nodes are labeled as unavailable.

D   ADDITIONAL EXPERIMENTAL RESULTS

D.1   HYPERVOLUME INDICATOR

Figure 4: Hypervolume illustration.

To solve a MOCO problem, the result for each method is a set of approximate Pareto solutions. Since the ground truth Pareto set is usually unknown, we use the hypervolume (HV) indicator (Zitzler et al., 2007) to numerically compare the performance for each method. The hypervolume indicator is widely used in the MOCO community for algorithm comparison.

The hypervolume of a set is the volume in the objective space it dominates. For a set $P \subset \mathbb{R}^m$ in the objective space, we can find a reference point r^* that dominated by all solutions in P, and define the hypervolume $H(P)$ as the volume of the set:

$$S = \{r \in \mathbb{R}^m \mid \exists y \in P \text{ such that } y \prec r \prec r^*\}, \tag{16}$$

where $H(P) = \textbf{Vol}(S)$. An illustration example is shown in Figure 4. The grey area is the set S dominated by the solutions in set $P = \{p_1, p_2, p_3, p_4\}$ with the reference point r^*. In this 2-dimensional case, the hypervolume $H(P)$ is the size of the grey area.

The hypervolume indicator has two important advantages for measuring the approximate set quality with respect to Pareto optimality (Zitzler et al., 2007). First, if an approximate set A dominates another approximate set B, it will have a strictly better hypervolume $H(A) > H(B)$. In addition, if an approximate set C contains all Pareto optimal solutions, it is guaranteed to have the maximum hypervolume value. In comparison, an approximate set has better performance if it has a larger hypervolume.

With different objective scales, the hypervolume value will vary significantly among different problems. We report the normalized hypervolume values $\hat{H}(P) = H(P)/\prod_i^m r_i^*$ for all methods and also their performance gaps to our method. For each experiment, all methods share the same reference point r^*, which contains the largest value achieved for each objective. Since all problems we consider have positive objective values, we have $0 \leq H(P) \leq 1$ for all solution sets. The ground truth Pareto set P^* usually has $H(P^*) < 1$, unless the zero vector $\mathbf{0} \in \mathbb{R}^m$ is feasible and in the Pareto set.

D.2 OUT-OF-DISTRIBUTION PROBLEM WITH EXACT PARETO FRONT

Table 6: The Results on Problems with Exact Pareto Front.

	L1			L2		
Method	HV	HV Gap	IGD	HV	HV Gap	IGD
Exact Pareto front	0.733	-	0	0.735	-	0
Weight-Sum LKH	0.728	0.71%	0.008	0.730	0.75%	0.007
Weight-Sum OR Tools	0.721	1.68%	0.012	0.722	1.76%	0.009
P-MOCO (101 pref.)	0.718	2.01%	0.014	0.717	2.43%	0.013
P-MOCO (101 pref., aug.)	0.722	1.52%	0.012	0.721	1.88%	0.010
P-MOCO (101 pref., aug., active)	0.724	1.21%	0.010	0.724	1.48%	0.008
	L3			L4		
Method	HV	HV Gap	IGD	HV	HV Gap	IGD
Exact Pareto front	0.737	-	0	0.737	-	0
Weight-Sum LKH	0.733	0.53%	0.007	0.731	0.83%	0.006
Weight-Sum OR Tools	0.723	1.89%	0.012	0.718	2.56%	0.014
P-MOCO (101 pref.)	0.722	2.04%	0.013	0.720	2.27%	0.012
P-MOCO (101 pref., aug.)	0.724	1.72%	0.012	0.723	1.93%	0.011
P-MOCO (101 pref., aug., active)	0.726	1.43%	0.010	0.727	1.33%	0.008
	L5			L6		
Method	HV	HV Gap	IGD	HV	HV Gap	IGD
Exact Pareto front	0.734	-	0	0.746	-	0
Weight-Sum LKH	0.727	0.92%	0.007	0.742	0.48%	0.006
Weight-Sum OR Tools	0.721	1.79%	0.012	0.728	2.43%	0.015
P-MOCO (101 pref.)	0.719	2.05%	0.014	0.729	2.19%	0.014
P-MOCO (101 pref., aug.)	0.723	1.48%	0.011	0.732	1.82%	0.012
P-MOCO (101 pref., aug., active)	0.725	1.29%	0.009	0.737	1.19%	0.009

We conduct experiments on 6 two-objective MOTSP100 instance (L1-L6) in Florios & Mavrotas (2014) of which the exact Pareto fronts are available. In these problems, the objective functions have different ranges, and the cities are not uniformly located, so they are out of our method's training distribution. The results can be found in the Table 6.

In addition to hypervolume, we also report the Inverted Generational Distance (IGD) (Fonseca et al., 2006) to measure the average Euclidean distance between the set of approximated Pareto solutions to the exact Pareto front. A smaller IGD value means the approximated set is closer to the exact Pareto front. According to the results, our method, with the instance augmentation and/or active search (10 min budget), can have a good performance on these out-of-distribution (OOD) instances with a $1\% - 1.5\%$ hypervolume gap. The proposed method also significantly outperforms the weight-sum OR tools baseline. There is still a gap to the strong weight-sum LKH baseline. As discussed in the paper, robust OOD generalization is an important research direction for the learning-based solver.

(a) 105 Preferences (b) 1035 Preferences (c) 10011 Preferences

(d) MOTSP20: 105 Solutions (e) MOTSP20: 1035 Solutions (f) MOTSP20: 10011 Solutions

(g) MOTSP50: 105 Solutions (h) MOTSP50: 1035 Solutions (i) MOTSP50: 10011 Solutions

(j) MOTSP100: 105 Solutions (k) MOTSP100: 1035 Solutions (l) MOTSP100: 10011 Solutions

Figure 5: Different number of uniform distributed preferences and the corresponding solutions generated by our method on MOTSP20, MOTSP50 and MOTSP100. Our model can generate well-distributed solutions with a small number of preferences, and generate a dense approximation with a large number of preferences.

D.3 FLEXIBLE PREFERENCE-BASED APPROXIMATION

With our model, it is flexible to generate different number of solutions to approximate the Pareto front. We present an example on the three-objective MOTSP in Figure 5. We follow the sampling approach proposed by Das & Dennis (1998) to uniformly generate 105, 1035 and 10011 3-dimensional preferences $\lambda \in \mathbb{R}^3$ which satisfies $\lambda_i \geq 0$ and $\sum_{i=1}^{3} \lambda_i = 1$ as shown in Figure 5(a)(b)(c).

We also show the corresponding generated solutions for MOTSP with 20, 50 and 100 nodes. According to the results in Figure 5, our model can generate well-distributed solutions with a small number of preferences, and generate a dense approximation with more preferences. The ability to generate a dense approximation to the whole Pareto set also allows the decision-maker to generate arbitrary preferred solutions on the approximate front.

D.4 PREFERENCE-SOLUTION CONNECTION

(a) 11 Preferences (HV = 0.649) (b) 101 Preferences (HV = 0.664) (c) 1,001 Preferences (HV = 0.669)

Figure 6: Different number of uniformly distributed preferences and their connections to the corresponding solutions on MOTSP100.

(a) MA-MOCO
(101 Models, HV = 0.417)

(b) P-MOCO
(101 Preferences, HV = 0.435)

(c) P-MOCO
(1,001 Preferences, HV = 0.441)

Figure 7: Different number of uniformly distributed preferences and their connections to the corresponding solutions on MOCVRP100. We report the approximate Pareto front for MA-MOCO with 101 models, and our model with 101 and 1,001 preferences.

We further analyze the connection between the preference and its corresponding solution on the uniform and non-uniform Pareto front. Figure 6 shows the connections in our model with different numbers of preferences for the MOTSP100 instance. Since the two objectives (costs) in MOTSP have the same scale, this problem has a uniform connection between the preferences and the (approximate) Pareto front. By increasing the number of preferences, we have three sparse to dense generated Pareto front approximations.

We are more interested in MOCVRP, which has a non-uniform Pareto front. In this problem, we consider two different objectives to optimize, namely, the total tour length (objective 1) and the tour length for the longest route (objective 2). These two objectives are in quite different scales, where the first objective is significantly larger than the second one. In Figure 7, we show different connections for the MOCVRP100 instance. For MA-MOCO, we report the connections for all 101 models. For our proposed model, we report the connections with different numbers of uniform preferences.

In this problem, 101 models or our model with 101 uniform preferences are not enough to generate a dense approximate Pareto front. The obtained solutions are biased to the area that objective 1 has a much better relative performance. By increasing the number of preferences, our proposed method can generate more solutions that have relatively better performance for objective 2, which leads to a better Pareto front approximation with higher hypervolume. In this work, we always use a straightforward uniform sampling method to select the preferences. It is interesting to design a learning-based approach to select the preferences for a given problem instance. Preference adjustment and model adaption with awareness on the shape of Pareto front are also worthy to investigate. We left them to the future work.

In the MOCVRP instance, we also find the 101-model MA-MOCO has a worse performance compared to our method with 101 preferences. The reason would be the mismatch between the uniform transfer training and the non-uniform Pareto front. Increasing the training steps for fine-tuning each model might fix this issue, but will lead to an even larger computational overhead, given the current training already require 700 epochs. The fixed preferences assignment is another issue for MA-MOCO. It requires a fixed set of preferences for each model at the start of the training procedure when the decision-makers might have no knowledge on the problem. When the training procedure is done, it dose not allow any preference adjustment without retraining the models.

D.5 PROBLEM WITH MORE OBJECTIVES

(a) MOEA/D (5×10^5 evals.)   (b) NSGA-II (5×10^5 evals.)   (c) P-MOCO (zero-shot)

Figure 8: The value path plots for the 10-objective MOKP100 obtained by MOEA/D, NSGA-II and our proposed P-MOCO. In the plot, each line (value path) represents a solution's 10 objective values with its specific preference. In MOKP, we want to maximize the values for all objectives. Our proposed method has significantly better overall performance.

(a) MOEA/D (10×10^5 evals.)   (b) NSGA-II (10×10^5 eval.)   (c) P-MOCO (zero-shot)

Figure 9: The value path plots for the 10-objective MOKP with 500 items obtained by MOEA/D, NSGA-II and our proposed P-MOCO. Our model is trained on 10-objective MOKP100.

Finally, we test the performance of our proposed method on the 10-objective knapsack problems. The obtained value path plots on the 10-objective MOKP100 are shown in Figure 8. For problems with more objectives, we need a large number of solutions to approximate the Pareto set. Training a large number of neural network models would have a huge computational and storage overhead, which is also not desirable in practice. Therefore, we do not compare with the AM-MOCO and MOA-DRL methods on this problem.

To approximate the Pareto set, each method generates 715 solutions with different trade-offs, so there are 715 different value paths (lines) on each plot. In MOKP, we want to maximize the values for all objectives under the capacity limitation. A set of good approximate solutions should have relatively high overall values. According to the results, our proposed method has the best performance. We also test the performance of our method on a larger problem with 500 items. The results shown in Figure 9 confirm that our trained model generalizes well to problems with a larger size.