CEIP: Combining Explicit and Implicit Priors for Reinforcement Learning with Demonstrations

Abstract

Although reinforcement learning has found widespread use in dense reward settings, training autonomous agents with sparse rewards remains challenging. To address this difficulty, prior work has shown promising results when using not only task-specific demonstrations but also task-agnostic albeit somewhat related demonstrations. In most cases, the available demonstrations are distilled into an implicit prior, commonly represented via a single deep net. Explicit priors in the form of a database that can be queried have also been shown to lead to encouraging results. To better benefit from available demonstrations, we develop a method to Combine Explicit and Implicit Priors (CEIP). CEIP exploits multiple implicit priors in the form of normalizing flows in parallel to form a single complex prior. Moreover, CEIP uses an effective explicit retrieval and push-forward mechanism to condition the implicit priors. In three challenging environments, we find the proposed CEIP method to improve upon sophisticated state-of-the-art techniques.

1 Introduction

Reinforcement learning (RL) has found widespread use across domains from robotics [55] and game AI [43] to recommender systems [6]. Despite its success, reinforcement learning is also known to be sample inefficient. For instance, training a robot arm with sparse rewards to sort objects from scratch still requires many training steps if it is at all feasible [45].

To increase the sample efficiency of reinforcement learning, prior work aims to leverage demonstrations [4, 34, 39]. These demonstrations can be *task-specific* [4, 17], i.e., they directly correspond to and address the task of interest. More recently, the use of *task-agnostic* demonstrations has also been studied [14, 16, 34, 45], showing that demonstrations for loosely related tasks can enhance sample efficiency of reinforcement learning agents.

To benefit from either of these two types of demonstrations, most work distills the information within the demonstrations into an *implicit prior*, by encoding available demonstrations in a deep net. For example, SKiLD [34] and FIST [16] use a variational auto-encoder (VAE) to encode the "skills," i.e., action sequences, in a latent space, and train a prior conditioned on states based on demonstrations to use the skills. Differently, PARROT [45] adopts a state-conditional normalizing flow to encode a transformation from a latent space to the actual action space. However, the idea of using the available demonstrations as an *explicit prior* has not received a lot of attention. Explicit priors enable the agent to maintain a database of demonstrations, which can be used to retrieve state-action sequences given an agent's current state. This technique has been utilized in robotics [32, 46] and early attempts of reinforcement learning with demonstrations [4]. It was also implemented as a baseline in [14]. One notable recent exception is FIST [16], which queries a database of demonstrations using the current state to retrieve a likely next state. The use of an explicit prior was shown to greatly enhance the

performance. However, FIST uses pure imitation learning without any RL, removing the chance for trial and remedy if the imitation is not good enough.

Our key insight is to leverage demonstrations both explicitly *and* implicitly, thus benefiting from both worlds. To achieve this, we develop **CEIP**, a method which **c**ombines **e**xplicit and **i**mplicit **p**riors. **CEIP** leverages implicit demonstrations by learning a transformation from a latent space to the real action space via normalizing flows. More importantly, different from prior work, such as PARROT and FIST, which combine all the information within a single deep net, **CEIP** selects the most useful prior by combining multiple flows *in parallel* to form a single large flow. To benefit from demonstrations explicitly, **CEIP** augments the input of the normalizing flow with a likely future state, which is retrieved via a lookup from a database of transitions. For an effective retrieval, we propose a push-forward technique which ensures the database to return future states that have not been referred to yet, encouraging the agent to complete the whole trajectory even if it fails on a single task.

We evaluate the proposed approach on three challenging environments: fetchreach [36], kitchen [11], and office [44]. In each environment, we study the use of both task-specific and task-agnostic demonstrations. We observe that integrating an explicit prior, especially with our proposed push-forward technique, greatly improves results. Notably, the proposed approach works well on sophisticated long-horizon robotics tasks with a few, sometimes even one task-specific demonstration.

2 Preliminaries

Reinforcement Learning. Reinforcement learning (RL) aims to train an *agent* to make the 'best' decision towards completing a particular task in a given environment. The environment and the task are often described as a Markov Decision Process (MDP), which is defined by a tuple $(\mathcal{S}, \mathcal{A}, T, r, \gamma)$. In timestep t of the Markov process, the agent observes the current *state* $s_t \in \mathcal{S}$, and executes an *action* $a_t \in \mathcal{A}$ following some probability distribution, i.e., *policy* $\pi(a_t|s_t) \in \Delta(\mathcal{A})$, where $\Delta(\mathcal{A})$ denotes the probability simplex over elements in space $\mathcal{A}$. Upon executing action a_t, the state of the agent changes to s_{t+1} following the dynamics of the environment, which are governed by the *transition function* $T(s_t, a_t) : \mathcal{S} \times \mathcal{A} \to \Delta(\mathcal{S})$. Meanwhile, the agent receives a *reward* $r(s_t, a_t) \in \mathbb{R}$. The agent aims to maximize the cumulative reward $\sum_t \gamma^t r(s_t, a_t)$, where $\gamma \in [0, 1]$ is the discount factor. One complete run in an environment is called an *episode*, and the corresponding state-action pairs $\tau = \{(s_1, a_1), (s_2, a_2), \dots\}$ form a *trajectory* τ.

Normalizing Flows. A normalizing flow [24] is a generative model that transforms elements z_0 drawn from a simple distribution, e.g., a Gaussian, to elements a_0 drawn from a more complex distribution. For this transformation, a bijective function f is used, i.e., $a_0 = f(z_0)$. The use of a bijective function ensures that the log-likelihood of the more complex distribution at any point is tractable and that samples of such a distribution can be easily generated by taking samples from the simple distribution and pushing them through the flow. Formally, the core idea of a normalizing flow can be summarized via $p_a(a_0) = p_z(f^{-1}(a_0)) \log \left| \frac{\partial f^{-1}(a)}{\partial a}|_{a=a_0} \right|$, where $|\cdot|$ is the determinant (guaranteed positive by flow designs), a is a random variable with the desired more complex distribution, and z is a random variable governed by a simple distribution. To efficiently compute the determinant of the Jacobian matrix of f^{-1}, special constraints are imposed on the form of f. For example, coupling flows like RealNVP [8] and autoregressive flows [31] impose the Jacobian of f^{-1} to be triangular.

3 CEIP: Combining Explicit and Implicit Priors

3.1 Overview

As illustrated in Fig. 1, our goal is to train an autonomous agent to solve challenging tasks despite sparse rewards, such as controlling a robot arm to complete item manipulation tasks (like turning on a switch or opening a cabinet). For this we aim to benefit from available demonstrations. Formally, we consider a task-specific dataset $D_{\text{TS}} = \{\tau_1^{\text{TS}}, \tau_2^{\text{TS}}, \dots, \tau_m^{\text{TS}}\}$, where τ_i^{TS} is the i-th trajectory of the task-specific dataset, and a task-agnostic dataset $D_{\text{TA}} = \{\bigcup D_i | i \in \{1, 2, 3, \dots, n\}\}$, where $D_i = \{\tau_1^i, \tau_2^i, \dots, \tau_{m_i}^i\}$ subsumes the demonstration trajectories for the i-th task in the task-agnostic dataset. Each trajectory $\tau = \{(s_1, a_1), (s_2, a_2), \dots\}$ in the dataset is a state-action pair sequence of a complete episode, where s is the state, and a is the action. We assume that the number of

Figure 1: Overview of our proposed approach, CEIP. Our approach can be divided into three steps: a) cluster the task-agnostic dataset into different tasks, and then train one flow on each of the n tasks of the task-agnostic dataset; b) train a flow on the task-specific dataset, and then train the coefficients to combine the $n + 1$ flows into one large flow f_{TS}, which is the implicit prior; c) conduct reinforcement learning on the target task; for each timestep, we perform a dataset lookup in the task-specific dataset to find the state most similar to current state s, and return the likely *next state* $\hat{s}_{\text{next}}$ in the trajectory, which is the explicit prior.

available task-specific trajectories is very small, i.e., $\sum_{i=1}^{n} m_i \gg m$, which is common in practice. For readability, we will also refer to D_{TS} using D_{n+1}.

Our approach leverages demonstrations implicitly by training a normalizing flow f_{TS}, which transforms the probability distribution represented by a policy $\pi(z|s)$ over a simple latent probability space $\mathcal{Z}$, i.e., $z \in \mathcal{Z}$, into a reasonable expert policy over the space of real-world actions $\mathcal{A}$. As before, s is the current environment state. Thus, the downstream RL agent only needs to learn a policy $\pi(z|s)$ that results in a probability distribution over latent space $\mathcal{Z}$, which is subsequently mapped via the flow f_{TS} to a real-world action $a \in \mathcal{A}$. Intuitively, the MDP in the latent space is governed by a less complex probability distribution, making it easier to train because the flow increases the exposure of more likely actions, while reducing the chance that a less-likely action is chosen. This is because the flow reduces the probability mass for less likely actions given the current state.

Task-agnostic demonstrations contain useful patterns that may be related to the task at hand. However, not all the task-agnostic data are always equally useful, as different task-agnostic data may require to expose different parts of the action space. Therefore, different from prior work where all data are fed into the same deep net model, we first partition the task-agnostic dataset into different groups according to task similarity so as to increase flexibility. For this we use a classical k-means algorithm. We then train different flows f_i on each of the groups, and finally combine the flows via learned coefficients into a single flow f_{TS}. Beneficially, this process permits to expose different parts of the action space as needed and according to perceived task similarity.

Lastly, our approach further leverages demonstrations explicitly, by conditioning the flow not only on the current state but also on a likely next state, to better inform the agent of the state it should try to achieve with its current action. In the following, we first discuss the implicit prior of **CEIP** in Sec. 3.2; afterward we discuss our explicit prior in Sec. 3.3, and the downstream reinforcement learning with both priors in Sec. 3.4.

3.2 Implicit Prior

To better benefit from demonstrations implicitly, we use a 1-layer normalizing flow as the backbone of our implicit prior. It essentially corresponds to a conditioned affine transformation of a Gaussian distribution. We choose a flow-based model instead of a VAE-based one for two reasons: 1) as the dimensionality before and after the transformation via a normalizing flow remains identical and since the flow is invertible, the agent is guaranteed to have control over the whole action space. This ensures that all parts of the action space are accessible, which is not guaranteed by VAE-based methods like SKiLD or FIST; 2) normalizing flows, especially coupling flows such as RealNVP [8], can be easily stacked *horizontally*, so that the combination of parallel flows is also a flow. Among feasible flow models, we found the simplest 1-layer flow suffices to achieve good results, and is even more robust in training than a more complex RealNVP. Next, in Sec. 3.2.1 we first introduce details regarding the normalizing flow f_i, before we discuss in Sec. 3.2.2 how to combine the flows into one flow f_{TS} applicable to the task for which the task-specific dataset contains demonstrations.

Figure 2: An illustration of how we combine different flows into one large flow for the task-specific dataset. Each red block of "NN" stands for a neural network. Note that $c_i(u)$ and $d_i(u)$ are vectors, while μ_i and λ_i are the i-th dimension of $\mu(u)$ and $\lambda(u)$.

3.2.1 Normalizing Flow Prior. For each task i in the task-agnostic dataset, i.e., for each D_i, we train a conditional 1-layer normalizing flow $f_i(z; u) = a$ which maps a latent space variable $z \in \mathbb{R}^p$ to an action $a \in \mathbb{R}^p$, where p is the number of dimensions of the real-valued action vector. We let u refer to a conditioning variable. In our case u is either the current environment state s (if no explicit prior is used) or a concatenation of the current and a likely next state $[s, s_{\text{next}}]$ (if an explicit prior is used). Concretely, the formulation of our 1-layer flow is

$$f_i(z; u) = a = \exp\{c_i(u)\} \odot z + d_i(u), \tag{1}$$

where $c_i(u) \in \mathbb{R}^p$, $d_i(u) \in \mathbb{R}^p$ are trainable deep nets, and $\odot$ refers to the Hadamard product. The $\exp$ function is applied elementwise. When training the flow, we sample state-action pairs (without explicit prior) or transitions (with explicit prior) (u, a) from the dataset D_i, and maximize the log-likelihood $\mathbb{E}_{(u,a)\sim D_i} \log p(a|u)$; refer to [24] for how to maximize such objective.

In the discussion above, we assume the decomposition of the task-agnostic dataset into tasks to be given. If such a decomposition is not provided (e.g., for the kitchen and office environments in our experiments), we perform a k-means clustering to divide the task-agnostic dataset into different parts. The clustering algorithm operates on the last state of a trajectory, which is used to represent the whole trajectory. The intuition is two-fold. First, for many real-world MDPs, achieving a particular terminal state is more important than the actions taken [12]. For example, when we control a robot to pick and place items, we want all target items to reach the right place eventually; however, we do not care too much about the actions taken to achieve this state. Second, among all the states, the final state is often the most informative about the task that the agent has completed. The number of clusters k in the k-means algorithm is a hyperparameter, which empirically should be larger than the number of dimensions of the action space. Though we assume the task-agnostic dataset is partitioned into labeled clusters, our experiments show that our approach is robust and good results are achieved even without a precise ground-truth decomposition.

In addition to the clusters in the task-agnostic dataset, we train a flow $f_{n+1}(z; u) = a$ on the task-specific dataset $D_{n+1} = D_{\text{TS}}$, using the same maximum log-likelihood loss, which is optional but always available. This is not necessary when the task is relatively simple and the episodes are short (e.g., the fetchreach environment in the experiment section), but becomes particularly helpful in scenarios where some subtasks of a task sequence only appear in the task-specific dataset (e.g., the kitchen environment).

3.2.2 Few-shot Adaptation. The flow models discussed in Sec. 3.2.1 learn which parts of the action space to more strongly expose from the latent space. However, not all the flows expose useful parts of the action space for the current state. For example, the target task needs the agent to move its gripper upwards at a particular location, but in the task-agnostic dataset, the robot more often moves the gripper downwards to finish another task. In order to select the most useful prior, we need to tune our set of flows learned on the task-agnostic datasets to the small number of trajectories available in the task-specific dataset. To ensure that this does not lead to overfitting as only a very small number of task-specific trajectories are available, we train a set of coefficients that select the flow that works the best for the current task. Concretely, given all the trained flows, we train a set of coefficients to combine the flows f_1 to f_n trained on the task-agnostic data, and also the flow f_{n+1} trained on the task-specific data. The coefficients select from the set of available flows the most useful one. To

achieve this, we use the combination flow illustrated in Fig. 2 which is formally specified as follows:

$$f_{\text{TS}}(z; u) = \left(\sum_{i=1}^{n+1} \mu_i(u) \exp\{c_i(u)\} \right) \odot z + \left(\sum_{i=1}^{n+1} \lambda_i(u) d_i(u) \right). \tag{2}$$

Here, $\mu_i(u) \in \mathbb{R}$, $\lambda_i(u) \in \mathbb{R}$ are the i-th entry of the deep nets $\mu(u) \in \mathbb{R}^{n+1}$, $\lambda(u) \in \mathbb{R}^{n+1}$, respectively, which yield the coefficients while the deep nets c_i and d_i are frozen. As before, the exp function is applied elementwise. We use a softplus activation and an offset at the output of μ to force $\mu_i(u) \geq 10^{-4}$ for any i for numerical stability. Note that the combined flow f_{TS} consisting of multiple 1-layer flows is also a 1-layer normalizing flow. Hence, all the compelling properties over VAE-based architectures described at the beginning of Sec. 3.2 remain valid. To train the combined flow, we use the same log likelihood loss $\mathbb{E}_{(u,a) \sim D_i} \log p(a|u)$ used for training of single flows. Here, maximization w.r.t. f_{TS} denotes maximization w.r.t. the parameters of the deep nets μ and λ. Obviously, the employed combination of flows can be straightforwardly expanded to a more complicated flow, e.g., a RealNVP or Glow. However, we found the discussed simple formulation to work remarkably well and to be robust.

3.3 Explicit Prior

Beyond distilling information from demonstrations into deep nets which are then used as implicit priors, we find explicit use of demonstrations to also be remarkably useful. To benefit, we encode future state information into the input of the flow. More specifically, instead of sampling (s, a)-pairs from a dataset D for training the flows, we consider sampling a *transition* (s, a, s_{next}) from D. During training, we concatenate s and s_{next} before feeding it into a flow, i.e., $u = [s, s_{\text{next}}]$ instead of $u = s$.

However, we do not know the future state s_{next} when deploying the policy. To obtain an estimate, we use task-specific demonstrations as explicit priors. More formally, we use the trajectories within the task-specific dataset D_{TS} as a database. This is manageable as we assume the task-specific dataset to be small. For each environment step of reinforcement learning with current state s, we perform a lookup, where s is the query, states s_{key} in the trajectories are the keys, and their corresponding next state s_{next} is the value. More specifically, we define $\hat{s}_{\text{next}}$ as the result of the database retrieval:

$$\hat{s}_{\text{next}} = \text{argmin}_{s_{\text{next}} | (s_{\text{key}}, a, s_{\text{next}}) \in D_{\text{TS}}} [(s_{\text{key}} - s)^2 + C \cdot \delta(s_{\text{next}})], \text{where}$$

$$\delta(s_{\text{next}}) = \begin{cases} 1 \text{ if } \exists \tau \in D_{n+1}, \text{ s.t. } s_{\text{next}} \in \tau, s'_{\text{next}} \text{ is no earlier than } s_{\text{next}} \text{ and has been retrieved,} \\ 0 \text{ otherwise.} \end{cases}$$

(3)

In Eq. (3), C is a constant and δ is the indicator function. We set $u = [s, \hat{s}_{\text{next}}]$ as the condition, feed it into the trained flow f_{TS}, and map the latent space element z obtained from the RL policy to the real-world action a. The penalty term δ is a push-forward technique, which aims to push the agent to move forward instead of staying put, imposing monotonicity on the retrieved $\hat{s}_{\text{next}}$. Consider an agent at a particular state s and a flow f_{TS}, conditioned on $u = [s, \hat{s}_{\text{next}}]$ which maps the chosen action z to a real-world action a that does not modify the environment. Without the penalty term, the agent will remain at the same state, retrieve the same likely next state, which again maps onto the action that does not change the environment. Intuitively, this term discourages 1) retrieving the same state twice, and 2) returning to earlier states in a given trajectory. In our experiments, we set $C = 1$.

3.4 Reinforcement Learning with Priors

Given the implicit and explicit priors, we use RL to train a policy $\pi(z|s)$ to accomplish the target task demonstrated in the task-specific dataset. As shown in Fig. 1, the RL agent receives a state s and provides a latent space element z. The conditioning variable of the flow is retrieved via the dataset lookup described in Sec. 3.3 and the real-world action a is then computed using the flow. Note, our approach is suitable for any RL method, i.e., the policy $\pi(z|s)$ can be trained using any RL algorithm.

4 Experiments

In this section, we evaluate our CEIP approach on three challenging environments: fetchreach (Sec. 4.1), kitchen (Sec. 4.2), and office (Sec. 4.3), which are all tasks that manipulate a robot arm.

In each experiment, we study the following questions: 1) Can the algorithm make good use of the demonstrations compared to baselines; 2) Are our core design decisions (e.g., state augmentation with explicit prior and the push-forward technique) indeed helpful.

Baselines. We compare the proposed method to three baselines: PARROT [45], SKiLD [34], and FIST [16]. In all environments, we use reward as our criteria (higher is better), and the results are averaged over 3 runs for SKiLD (which is much slower to train than other baselines) and 9 runs for all other methods unless otherwise mentioned. To differentiate variants of the PARROT baseline and our method, we use suffixes. We use "EX" to refer to variants that use an explicit prior, and "forward" to denote variants with the push-forward technique. For our method, if we train a task-specific flow on $D_{\text{TS}} = D_{n+1}$, we append the abbreviation "TS". For PARROT, the use of the task-specific data is indicated with "TS" and the use of task-agnostic data is indicated with "TA."[1] See Tab. 3 and Tab. 4 for precise correspondence.

4.1 FetchReach Environment

Environment Setup. The agent needs to control a robot arm to move its gripper to a goal location in 3D space, and remain there. During an episode of 40 steps, the agent receives a 10-dimensional state about its location and outputs a 4-dimensional action, which indicates the change of coordinates of the agent and the openness of the gripper. It will receive a reward of 0 if it arrives and stays in the vicinity of its target. Otherwise, it will receive a reward of -1. This environment is a harder version of the FetchReach-v1 robotics environment in gym [36], where we increase the average distance of the starting point to the goal, effectively increasing the training difficulty. Moreover, to test the robustness of the algorithm, we sample a random action from a normal distribution at the beginning of each episode, which the agent executes for x steps before the episode begins. We use $x \sim U[5, 20]$. For simplicity, we denote the goal generated with azimuth $\frac{\pi d}{4}$ as "direction d" (e.g., direction 4.5).

Dataset Setup. We use trajectories from directions $0, 1, 2, \ldots, 7$ as the task-agnostic data. Each task includes 40 trajectories, and each of the trajectories has 40 steps, i.e., 1600 environment steps in total. The task-specific dataset contains directions $4.5, 5.5, 6.5$, and 7.5. The robot cannot reach the other four .5 directions due to physical limits. For each task-specific dataset, we use 4 trajectories, for a total of 160 environment steps.

Experimental Setup. For fetchreach, we use a fully-connected deep net with one hidden layer of width 32 and ReLU [1] activation as a standard "block" of our algorithm (each block corresponds to a red "NN" rectangle in Fig. 2). We have a pair of blocks for $c_i(s)$ and $d_i(s)$ for each flow f_i. For flow training, we train 8 flows for 8 directions in the task-agnostic dataset. We use a batch size of 40 and train for 1000 epochs for both each flow and the combination of flows, with gradient clipping at norm 10^{-4}, learning rate 0.001, and Adam optimizer [21]. We use the model that has the best performance on the validation dataset at the end of every epoch. For each dataset, we randomly draw 80% state-action pairs or transitions as the training set and 20% state-action pairs as the validation set. The combination of flow is also a block, which outputs both $\mu(s)$ and $\lambda(s)$. See the appendix for the implementation details of SKiLD, FIST, and PARROT. For each method with RL training, we use a soft-actor-critic (SAC) [15] with 30K environment steps, a batch size of 256, and 1000 steps of initial random exploration. Unless otherwise noted, all other RL hyperparameters in all experiments use the default values of Stable-baselines3 [38].

Analysis. Fig. 3 shows the results for different methods without explicit priors or task-specific single flow f_{n+1}. In all four tasks, our method significantly outperforms the other baselines. This indicates that the flow training indeed helps boost the exploration process. Naive reinforcement learning from scratch fails in most cases, which underscores the necessity of utilizing demonstrations to aid RL exploration. As this is a simple task with only a few wildly varied trajectories, adding a flow for the task-specific dataset does not improve our method. Noteworthy, neither SKiLD nor FIST works on fetchreach. Their VAE-based architecture with each action sequence as the agent's output ("skill") can not be trained with the little amount and wildly varied data and the short horizon. Flow-based models like ours and PARROT, which only consider the action of the current step instead of the action sequence, work better. To better understand the effect of each component of our method, we conduct ablation studies on our method and PARROT. See Appendix D for details.

---

[1]The original PARROT in [45] is essentially PARROT+TA. It is straightforward to use PARROT directly on the task-specific dataset. Hence, we tried PARROT+TS and PARROT+(TS+TA) as well.

| (a) Direction 4.5 | (b) Direction 5.5 | (c) Direction 6.5 | (d) Direction 7.5 |

Figure 3: Main performance results on the fetchreach environment for different directions, where the lines are the mean reward (higher is better) and shades are the standard deviation. FIST is represented by a dashed line as it does not require RL.

4.2 Kitchen Environment

Environment Setup. We use the kitchen environment adopted from D4RL [11], which serves as a testbed for many reinforcement learning and imitation learning approaches, like SPiRL [33], SKiLD [34], relay policy learning [14], and FIST [16]. The agent needs to control a 7-DOF robot arm to complete a sequence of four tasks (e.g., move the kettle, or slide the cabinet) in the correct order. The agent will receive a $+1$ reward only upon finishing a task, and 0 otherwise. The action space is 9-dimensional and the state space is 60-dimensional. This environment is very challenging as high-precision control of the robot arm is needed, and as a long horizon of 280 timesteps is needed. Moreover, there is a small noise applied to each agent action, which requires the agent to be robust.

Dataset Setup. We use two dataset settings, which are adopted from SKiLD and FIST (denoted as *Kitchen-SKiLD* and *Kitchen-FIST* below). In Kitchen-SKiLD, we use 601 teleoperated sequences that perform a variety of task sequences as the task-agnostic dataset, and use *only one* trajectory for the task-specific dataset. In Kitchen-FIST, we use part of the task-agnostic dataset (about $200 - 300$ trajectories) that *does not* contain a particular task in the task-specific dataset, and use *only one* trajectory for the task-specific dataset. There are two different task-specific datasets in Kitchen-SKiLD, and four different task-specific datasets in Kitchen-FIST. The latter is significantly harder, as the agent must learn a new task from very little data. For simplicity, we will denote them as "SKiLD-A/B" and "FIST-A/B/C/D" respectively. See Appendix C for details on each task.

Experimental Setup. We use k-means to partition the task-agnostic datasets into 24 different clusters, and train 24 flows accordingly. For each flow, we use a fully-connected network with 2 hidden layers of width 256 with ReLU activation as a "block" for our algorithm. For the combination of flows, we use a fully-connected network with 1 hidden layer of width 64 with ReLU activation. Each layer of the deep net (except the output layer) described above has a 1D batchnorm function. The blocks are used analogously to the fetchreach environment. We use a batch size of 256 for the task-agnostic dataset and a batch size of 128 for the task-specific dataset. Other training hyperparameters are identical to the fetchreach environment. For each RL training, we use proximal policy optimization (PPO) [42] for 200K environment steps, with update interval being 2048 (Kitchen-SKiLD) / 4096 (Kitchen-FIST), 60 epochs per update, and a batch size of 64.

Analysis. Fig. 4 shows the main results on Kitchen-SKiLD and Kitchen-FIST. Our method outperforms all other baselines in all of the 6 settings of the task-agnostic and the task-specific dataset. For our method, we use the task-specific single flow f_{n+1}, explicit prior, and the push-forward technique. We compare to the original PARROT formulation. See Appendix D for ablation studies of PARROT with explicit prior and our method without f_{n+1} or explicit prior.

4.3 Office Environment

Environment and Dataset Setup. We follow SKiLD, where a robot with 8-dimensional action space and 97-dimensional state space needs to put three randomly selected items on a table into three containers in the correct, randomly generated order. The agent will receive a $+1$ reward when it completes a subtask (e.g., picking up an item, or dropping the item at the right place), and 0 otherwise. This environment is even harder than the kitchen environment, as the agent must manipulate freely movable objects and the number of possible subtasks in the task-agnostic dataset is much larger than that in the kitchen environment. We use the same task-agnostic dataset as SKiLD, which contains

Figure 4: Comparison on Kitchen-SKiLD and Kitchen-FIST environments.

298 2400 trajectories with randomized subtasks sampled from a script policy. For the task-specific dataset,
299 we use 5 trajectories for a particular combination of tasks.

300 **Experimental Setup.** Similar to the kitchen environment, we use k-means over the last state of
301 each trajectory and partition the task-agnostic dataset into 24 clusters. The architecture and training
302 paradigm of the flow model are identical to those used in the kitchen environment. For RL training,
303 we use PPO for 2M environment steps, with update interval being 4096 environment steps, 60 epochs
304 per update, and a batch size of 64. All other hyperparameters follow the kitchen environment setting.
305 We run each method with 3 different seeds.

306 **Analysis and Ablation**
307 **Study.** Fig. 5a shows
308 the main performance
309 result across different
310 methods. Our method
311 with explicit prior, push-
312 forward technique, and
313 task-specific flow out-
314 performs all baselines.
315 FIST works well in this
316 environment, probably
317 because of two reasons:
318 1) there are a sufficient

(a) Main result   (b) Ours ablation   (c) PARROT ablation

Figure 5: Main result and ablation of our method and PARROT on the office
environment.

319 number of task-specific trajectories for the VAE-architecture, and 2) the office environment is less
320 noisy than the kitchen environment. However, as FIST does not contain a reinforcement learning
321 stage, it has no chance to improve on a decent policy which could have been a good start for an RL
322 agent. Fig. 5b shows the ablation of our method. While the task-specific single flow f_{n+1} does not
323 help in this environment, the explicit prior greatly improves results. Also, as illustrated, the reward
324 curve of the variants with explicit prior but without push-forward skill does not grow, which is due
325 to the agent getting stuck as described at the end of Sec. 3.3. Fig. 5c shows the ablation result of
326 PARROT, which also emphasizes that explicit prior and push-forward skill greatly improve results.

327 ## 5 Related Work

328 **Reinforcement Learning with Demonstrations.** Using demonstrations to improve the sample
329 efficiency of RL is an established direction [13, 26, 40, 53]. Recently, the use of task-agnostic

demonstrations gained popularity as task-specific data needs to be sampled from a particular expert and can be expensive to acquire [33, 34, 45]. To utilize the prior, skill-based works such as SPiRL [33], SKiLD [34], and SIMPL [30] extract action sequences from the dataset with a VAE-based model, while TRAIL [56] recovers transitions from a task-agnostic dataset with uniformly randomly sampled action. Our method considers the situation where both task-agnostic *and* task-specific data exist and significantly improves results over works with similar settings like SKiLD [34].

Action Priors. An action prior is a common way to utilize demonstrations for reinforcement learning [34] and imitation learning [16]. Most works use an implicit prior, where a probability distribution of actions conditioned on a state is learned by a deep net and then used to rule out unlikely attempts [3], to form a hierarchical structure [34, 45] or to serve as a regularizer for RL training [34, 39], preventing the agent to stray too far from expert demonstrations. Explicit priors are less explored. They come in the form of nearest neighbors [2] (as in our work) or in the form of locally weighted regression [32]. They are utilized in robotics [2, 32, 41, 46] and early works of RL with demonstrations [4]. Another way to explicitly use demonstrations includes filling the buffer of offline RL algorithms with transitions sampled from an expert dataset to help exploration [17, 29, 52]. Different from all these works, we propose a novel way of using both implicit and explicit priors.

Normalizing Flow. Normalizing flows are a generative model that can be used for variational inference [23, 51] and density estimation [18, 31] and comes in different forms: RealNVP [8], Glow [22], or autoregressive flow [31]. Many works use normalizing flows in reinforcement learning [20, 27, 28, 47, 48, 54] and imitation learning [5]. However, most prior works use normalizing flows as a strong density estimator to exploit a richer class of policies. Most closely related to our work is PARROT [45], which trains a single normalizing flow as an implicit prior. Different from our work, PARROT does not differentiate tasks among the task-agnostic dataset and does not use an explicit prior. More importantly, different from prior works, we develop a simple yet effective way to combine flows using learned coefficients. While there are some works that combine flows via variational mixtures [7, 35], they have not been shown to succeed on challenging RL tasks.

Few-shot Generalization. Few-shot generalization [49] is broadly related, as a model is first trained across different datasets, and then adapted to a new dataset with small sample size. For example, similar to our work, FLUTE [50], SUR [9], and URT [25] use models for multiple datasets, which are then combined via weights for few-shot adaptation. Other works have shared parameters across different tasks and only used parts within the model for adaptation [10, 37, 50, 57]. While most works focus on classification tasks, we address more complex RL tasks. Also, different from these works, we found training of independent 1-layer flows without shared layers to be more flexible, and free from negative transfer as also reported by [19].

6 Discussion and Conclusion

We developed **CEIP**, a method for reinforcement learning which combines explicit and implicit priors obtained from task-agnostic and task-specific demonstrations. For implicit priors we use normalizing flows. For explicit priors we use a database lookup with a push-forward retrieval. In three challenging environments, we show that **CEIP** improves upon baselines.

Limitations. Limitations of CEIP are as follows: 1) *Training time.* The use of demonstrations requires training a decent number of flows which can be time-consuming, albeit mitigated to some extent by parallel training; 2) *Reliance on optimality of expert demonstrations.* Similar to prior work like SKiLD [34] and FIST [16], our method assumes availability of optimal state-action trajectories for the target task. Accuracy of those demonstrations impacts results. Future work should improve robustness and generality; 3) *Balance between the degree of freedom and generalization in fitting the flow mixture.* Fig. 10 reveals that more degrees of freedom in the flow mixture improve results of CEIP. Our current design uses a linear combination which offers $O(n)$ degrees of freedom (μ and λ), where n is the number of flows. In contrast, too many degrees of freedom will result in overfitting. It is interesting future work to study this tradeoff.

Societal impact. Our work helps to train RL agents more efficiently from demonstrations for the same and closely related tasks, particularly if the environment only provides sparse rewards. If successful, this expands the applicability of automation. However, increased automation may also cause job loss which negatively impacts society.

References

[1] A. F. Agarap. Deep learning using rectified linear units (relu). *ArXiv preprint: arXiv1803.08375*, 2018.

[2] S. P. Arunachalam, S. Silwal, B. Evans, and L. Pinto. Dexterous imitation made easy: A learning-based framework for efficient dexterous manipulation. *ArXiv preprint: arXiv2203.13251*, 2022.

[3] O. Biza, D. Wang, R. Platt, J.-W. van de Meent, and L. L. Wong. Action priors for large action spaces in robotics. In *AAMAS*, 2021.

[4] T. Brys, A. Harutyunyan, H. B. Suay, S. Chernova, M. E. Taylor, and A. Nowé. Reinforcement learning from demonstration through shaping. In *IJCAI*, 2015.

[5] W.-D. Chang, J. C. G. Higuera, S. Fujimoto, D. Meger, and G. Dudek. Il-flow: Imitation learning from observation using normalizing flows. In *NeurIPS 2021 Workshop on Robot Learning*, 2021.

[6] X. Chen, S. Li, H. Li, S. Jiang, Y. Qi, and L. Song. Generative adversarial user model for reinforcement learning based recommendation system. In *ICML*, 2019.

[7] S. Ciobanu. Mixtures of normalizing flows. In *CAINE*, 2021.

[8] L. Dinh, J. Sohl-Dickstein, and S. Bengio. Density estimation using real NVP. In *ICLR*, 2017.

[9] N. Dvornik, C. Schmid, and J. Mairal. Selecting relevant features from a multi-domain representation for few-shot classification. In *ECCV*, 2020.

[10] S. Flennerhag, A. A. Rusu, R. Pascanu, H. Yin, and R. Hadsell. Meta-learning with warped gradient descent. In *ICLR*, 2020.

[11] J. Fu, A. Kumar, O. Nachum, G. Tucker, and S. Levine. D4rl: Datasets for deep data-driven reinforcement learning. *ArXiv preprint: arXiv2004.07219*, 2020.

[12] S. Ghasemipour, R. Zemel, and S. Gu. A divergence minimization perspective on imitation learning methods. In *CoRL*, 2019.

[13] A. Giusti, J. Guzzi, D. C. Cireşan, F.-L. He, J. P. Rodríguez, F. Fontana, M. Faessler, C. Forster, J. Schmidhuber, G. D. Caro, D. Scaramuzza, and L. M. Gambardella. A machine learning approach to visual perception of forest trails for mobile robots. *IEEE Robotics and Automation Letters*, 2016.

[14] A. Gupta, V. Kumar, C. Lynch, S. Levine, and K. Hausman. Relay policy learning: Solving long-horizon tasks via imitation and reinforcement learning. In *CoRL*, 2019.

[15] T. Haarnoja, A. Zhou, P. Abbeel, and S. Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *ICML*, 2018.

[16] K. Hakhamaneshi, R. Zhao, A. Zhan, P. Abbeel, and M. Laskin. Hierarchical few-shot imitation with skill transition models. In *ICLR*, 2022.

[17] T. Hester, M. Vecerik, O. Pietquin, M. Lanctot, T. Schaul, B. Piot, D. Horgan, J. Quan, A. Sendonaris, I. Osband, G. Dulac-Arnold, J. Agapiou, J. Z. Leibo, and A. Gruslys. Deep q-learning from demonstrations. In *AAAI*, 2018.

[18] C.-W. Huang, D. Krueger, A. Lacoste, and A. Courville. Neural autoregressive flows. In *ICML*, 2018.

[19] A. Javaloy and I. Valera. Rotograd: Gradient homogenization in multitask learning. In *ICLR*, 2021.

[20] S. A. Khader, H. Yin, P. Falco, and D. Kragic. Learning stable normalizing-flow control for robotic manipulation. In *ICRA*, 2021.

[21] D. P. Kingma and J. Ba. Adam: A method for stochastic optimization. In *ICLR*, 2015.

[22] D. P. Kingma and P. Dhariwal. Glow: Generative flow with invertible 1x1 convolutions. In *NeurIPS*, 2018.

[23] D. P. Kingma, T. Salimans, R. Jozefowicz, X. Chen, I. Sutskever, and M. Welling. Improved variational inference with inverse autoregressive flow. In *NIPS*, 2016.

[24] I. Kobyzev, S. J. Prince, and M. A. Brubaker. Normalizing flows: An introduction and review of current methods. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2021.

[25] L. Liu, W. Hamilton, G. Long, J. Jiang, and H. Larochelle. A universal representation transformer layer for few-shot image classification. In *ICLR*, 2021.

[26] C. Lynch, M. Khansari, T. Xiao, V. Kumar, J. Tompson, S. Levine, and P. Sermanet. Learning latent plans from play. In *CoRL*, 2019.

[27] X. Ma, J. K. Gupta, and M. J. Kochenderfer. Normalizing flow policies for multi-agent systems. In *GameSec*, 2020.

[28] B. Mazoure, T. Doan, A. Durand, R. D. Hjelm, and J. Pineau. Leveraging exploration in off-policy algorithms via normalizing flows. In *CoRL*, 2019.

[29] A. Nair, A. Gupta, M. Dalal, and S. Levine. Awac: Accelerating online reinforcement learning with offline datasets. *ArXiv preprint: arXiv2006.09359*, 2020.

[30] T. Nam, S.-H. Sun, K. Pertsch, S. J. Hwang, and J. J. Lim. Skill-based meta-reinforcement learning. In *ICLR*, 2022.

[31] G. Papamakarios, T. Pavlakou, and I. Murray. Masked autoregressive flow for density estimation. In *NIPS*, 2017.

[32] J. Pari, N. M. Shafiullah, S. P. Arunachalam, and L. Pinto. The surprising effectiveness of representation learning for visual imitation. *ArXiv preprint: arXiv2112.01511*, 2021.

[33] K. Pertsch, Y. Lee, and J. J. Lim. Accelerating reinforcement learning with learned skill priors. In *CoRL*, 2020.

[34] K. Pertsch, Y. Lee, Y. Wu, and J. J. Lim. Demonstration-guided reinforcement learning with learned skills. In *CoRL*, 2021.

[35] G. G. P. F. Pires and M. A. T. Figueiredo. Variational mixture of normalizing flows. In *ESANN*, 2020.

[36] M. Plappert, M. Andrychowicz, A. Ray, B. McGrew, B. Baker, G. Powell, J. Schneider, J. Tobin, M. Chociej, P. Welinder, V. Kumar, and W. Zaremba. Multi-goal reinforcement learning: Challenging robotics environments and request for research. *ArXiv preprint: arXiv1802.09464*, 2018.

[37] J. Puigcerver, C. Riquelme, B. Mustafa, C. Renggli, A. S. Pinto, S. Gelly, D. Keysers, and N. Houlsby. Scalable transfer learning with expert models. In *ICLR*, 2021.

[38] A. Raffin, A. Hill, A. Gleave, A. Kanervisto, M. Ernestus, and N. Dormann. Stable-baselines3: Reliable reinforcement learning implementations. *Journal of Machine Learning Research*, 2021.

[39] D. Rengarajan, G. Vaidya, A. Sarvesh, D. Kalathil, and S. Shakkottai. Reinforcement learning with sparse rewards using guidance from offline demonstration. In *ICLR*, 2022.

[40] S. Schaal. Learning from demonstration. In *NIPS*, 1996.

[41] S. Schaal and C. Atkeson. Robot juggling: implementation of memory-based learning. *IEEE Control Systems Magazine*, 1994.

[42] J. Schulman, F. Wolski, P. Dhariwal, A. Radford, and O. Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

[43] D. Silver, T. Hubert, J. Schrittwieser, I. Antonoglou, M. Lai, A. Guez, M. Lanctot, L. Sifre, D. Kumaran, T. Graepel, T. P. Lillicrap, K. Simonyan, and D. Hassabis. Mastering chess and shogi by self-play with a general reinforcement learning algorithm. *Science*, 2018.

[44] A. Singh, A. Yu, J. Yang, J. Zhang, A. Kumar, and S. Levine. Cog: Connecting new skills to past experience with offline reinforcement learning. In *CoRL*, 2020.

[45] A. Singh, H. Liu, G. Zhou, A. Yu, N. Rhinehart, and S. Levine. Parrot: Data-driven behavioral priors for reinforcement learning. In *ICLR*, 2021.

[46] D. Singh Chaplot, R. Salakhutdinov, A. Gupta, and S. Gupta. Neural topological slam for visual navigation. In *CVPR*, 2020.

[47] Y. Tang and S. Agrawal. Boosting trust region policy optimization by normalizing flows policy. *ArXiv preprint: arXiv1809.10326*, 2018.

[48] A. Touati, H. Satija, J. Romoff, J. Pineau, and P. Vincent. Randomized value functions via multiplicative normalizing flows. In *UAI*, 2019.

[49] E. Triantafillou, T. Zhu, V. Dumoulin, P. Lamblin, U. Evci, K. Xu, R. Goroshin, C. Gelada, K. Swersky, P. Manzagol, and H. Larochelle. Meta-dataset: A dataset of datasets for learning to learn from few examples. In *ICLR*, 2020.

[50] E. Triantafillou, H. Larochelle, R. Zemel, and V. Dumoulin. Learning a universal template for few-shot dataset generalization. In *ICML*, 2021.

[51] R. van den Berg, L. Hasenclever, J. Tomczak, and M. Welling. Sylvester normalizing flows for variational inference. In *UAI*, 2018.

[52] M. Vecerík, T. Hester, J. Scholz, F. Wang, O. Pietquin, B. Piot, N. M. O. Heess, T. Rothörl, T. Lampe, and M. A. Riedmiller. Leveraging demonstrations for deep reinforcement learning on robotics problems with sparse rewards. *ArXiv preprint: arXiv1707.08817*, 2017.

[53] Y. Wang, C. Xu, B. Du, and H. Lee. Learning to weight imperfect demonstrations. In *ICML*, 2021.

[54] P. N. Ward, A. Smofsky, and A. Bose. Improving exploration in soft-actor-critic with normalizing flows policies. In *Workshop on Invertible Neural Networks and Normalizing Flows in ICML*, 2019.

[55] F. Xia, C. Li, R. Martín-Martín, O. Litany, A. Toshev, and S. Savarese. Relmogen: Leveraging motion generation in reinforcement learning for mobile manipulation. *arXiv preprint arXiv:2008.07792*, 2020.

[56] M. Yang, S. Levine, and O. Nachum. Trail: Near-optimal imitation learning with suboptimal data. In *NeurIPS*, 2021.

[57] L. M. Zintgraf, K. Shiarlis, V. Kurin, K. Hofmann, and S. Whiteson. Fast context adaptation via meta-learning. In *ICML*, 2019.