CAREER PATH MODELING AND RECOMMENDATIONS WITH LINKEDIN CAREER DATA AND PREDICTED SALARY ESTIMATIONS

Micaela T. Cerilla, Aaron A. Santillan, & Carl John R. Viñas *
Department of Computer Science
Polytechnic University of The Philippines
1016 Anonas, Santa Mesa, Maynila, Kalakhang Maynila
{mtcerilla,aasantillan,cjrvinas}@iskolarngbayan.pup.edu.ph

Michael B. Dela Fuente
Department of Computer Science
Polytechnic University of The Philippines
mbdelafuente@pup.edu.ph

ABSTRACT

Career planning involves devising a sequence of steps that build up an ideal career path for a person. However, career planning has become more complex in recent years, demanding the need for better models and systems for recommending Career Paths. With that in mind, we explored new variables and techniques that could help in predicting better career paths. We built a Long-Short Term Memory Network with Self Attention Layers called LSTM-ATT, that predicts a person's possible career path using Linkedin Career History and new variables such as salary estimations and social networks. We measured the model's performance in terms of Mean Percentile Rank and Precision at 50 and 100. We found that LSTM and self-attention layers were able to show good predictive performance for multi-class classification even with over 6000 classes for companies and skills, effectively beating a multi-channel CNN for all metrics. However, by checking the versions of either model with added features, they did not yield any major increase in predictive accuracy against the models without it. This leads us to conclude that the added variables did not help in predicting better career paths.

1 INTRODUCTION

We define a career path as a series of steps that allow individuals to achieve a specific goal or objective. There have been a few studies exploring predicting and recommending career paths (Wan & Ye, 2022; Natividad et al., 2019; Li et al., 2017b;a; Ghosh et al., 2020; Zhang et al., 2020).

However, choosing a career path has become more complex in recent years because of the following causes: (1) inaccessibility to career counseling, (2) the diversity of roles that an individual may partake in, and (3) career planning can lead to information overload (Wan & Ye, 2022). Given the limitations of existing models, we explored new variables and techniques that could help in predicting better career paths. We look into unexplored variables from previous studies (Ghosh et al., 2020), namely social networks (better known as LinkedIn recommendations) and predicted salary estimations while utilizing Long-Short Term Memory Networks and Self-Attention Layers for improved accuracy.

---

*All three authors listed here provided equal contribution to the creation of this research. The ordering was decided through the probability of a D20 dice roll.

2 PROBLEM CONTEXT AND EXPERIMENTAL SETUP

Predicting a career path through machine learning can be defined as two recommendation problems:

1. The first problem is defined as recommending the user's **latest** job and company as a relevant item.

2. The second problem is defined as recommending all the skills that an individual possesses in the given user or Linkedin Profile as all relevant items.

To understand if LSTM-ATT and the added features help in predicting career paths for both of these problems, we create different versions of LSTM-ATT models and M-CNN (another algorithm used for career path recommendations) with or without the added variables to test their effectiveness in recommendations. We then used the usual metrics in the domain of recommendation systems, namely the Mean Percentile Rank (MPR)and Precision @ K (at 10 and 100) to evaluate all of the models.

3 MODEL ARCHITECTURE

We developed a model called LSTM-ATT and used scraped data obtained from LinkedIn and Payscale to predict career paths (See Section 5.1). For Linkedin, we extracted users' career histories (which consist of all the jobs and companies they transitioned in their professional journey), set of skills, education history, and Linkedin recommendations posted by the user. On the other hand, predicted salaries per job are derived by matching jobs from each job history of all users to the predicted salaries of each job taken from Payscale. We then converted all features into embeddings, concatenated them, and fed them to the LSTM-ATT model to predict the latest career path.

4 RESULTS, DISCUSSIONS, AND RECOMMENDATIONS

Based on the predictive results of the LSTM-ATT models below (See Table 1), LSTM and self-attention layers were able to show good predictive performance for multi-class classification even with over 6000 classes for companies and skills, effectively beating a multi-channel CNN for all metrics. This leads us to conclude that LSTM and Attention Layers significantly helped in performance. Using the same table, by checking the versions of either model with added features, it can be seen that they did not yield in any major increase in predictive accuracy against the models without it. This leads us to conclude that the added variables did not help in predicting better career paths.

For future work, further investigation is needed in checking if there is a change in results with bigger datasets since the size of our dataset used in our experiment pales in comparison to previous works (Ghosh et al., 2020).

Table 1: Results on Model Predictions for Jobs, Companies, and Skills for LSTM-ATT and M-CNN

Methods	Jobs			Companies			Skills		
	MPR	P@10	P@100	MPR	P@10	P@100	MPR	P@10	P@100
LSTM-ATT	0.011	0.107	0.134	0.118	0.747	0.952	0.059	0.293	0.402
LSTM-ATT + SAL	0.017	0.088	0.113	0.111	0.760	0.940	0.062	0.299	0.407
LSTM-ATT + SN	0.017	0.128	0.173	0.063	0.854	0.913	0.061	0.286	0.395
LSTM-ATT + SAL + SN	0.021	0.105	0.163	0.063	0.086	0.921	0.060	0.285	0.379
M-CNN	0.012	0.074	0.090	0.339	0.446	0.592	0.059	0.212	0.274
M-CNN + SAL	0.011	0.049	0.069	0.030	0.371	0.542	0.062	0.229	0.293
M-CNN + SN	0.004	0.037	0.038	0.048	0.120	0.197	0.056	0.198	0.251
M-CNN + SAL + SN	0.047	0.047	0.060	0.014	0.165	0.498	0.058	0.221	0.267

Definitions: *LSTM-ATT = LSTM with Self Attention Layers, M-CNN = Multi-Channel CNN, SAL = Salary Feature, SN = Social Networks*

5 APPENDICES

5.1 VISUALIZATION OF THE MODEL ARCHITECTURE AND OVERALL PROCESS

5.2 EXPERIMENT PARAMETERS

For generating the experimental results for both models (Table 1), Here are the defined parameters for the entire experiment. All the embedding dimensions and epoch parameters for LSTM-ATT were selected through hyperparameter tuning.

1. **For LSTM-ATT**

   (a) Skills Embedding Output Dim - 480
   (b) Jobs Embedding Output Dim - 128
   (c) Establishments Embedding Output Dim - 384
   (d) Education Embedding Output Dim - 128
   (e) Salaries Embedding Output Dim - 128
   (f) Duration Embedding Output Dim - 128
   (g) Given Recommendations Embedding Output Dim - 128
   (h) Received Recommendations Embedding Output Dim - 128
   (i) Epochs - 30
   (j) Learning Rate - 0.001
   (k) Optimizer - Adam
   (l) Verbose - 2
   (m) Loss Function - modified Sparse Categorical CrossEntropy

2. **For M-CNN**

   (a) Skills Embedding Output Dim - 480
   (b) Jobs Embedding Output Dim - 128
   (c) Establishments Embedding Output Dim - 384
   (d) Education Embedding Output Dim - 128
   (e) Salaries Embedding Output Dim - 128
   (f) Duration Embedding Output Dim - 128
   (g) Given Recommendations Embedding Output Dim - 128
   (h) Received Recommendations Embedding Output Dim - 128
   (i) Epochs - 30

       (j) Learning Rate - 0.001

      (k) Optimizer - Adam

       (l) Verbose - 2

     (m) Loss Function - modified Sparse Categorical CrossEntropy

5.3 USED MATERIALS

Listed here are all resources we used for this research.

1. Code Repository - contains both the actual code and datasets.

2. Notebooks - the actual code to run the model and generate the experiments.

3. Datasets - contains the pre-processed dataset for training, evaluating, and hyper-tuning the model. Also includes the required item dictionaries for forming the tokenizers and embeddings needed for the model.

6 URM STATEMENT

The authors acknowledge that at least one key author of this work meets the URM criteria of ICLR 2023 Tiny Papers Track.

REFERENCES

Aritra Ghosh, Beverly Woolf, Shlomo Zilberstein, and Andrew Lan. Skill-based career path modeling and recommendation. In *2020 IEEE International Conference on Big Data (Big Data)*, pp. 1156–1165, 2020. doi: 10.1109/BigData50022.2020.9377992.

Huayu Li, Yong Ge, Hengshu Zhu, Hui Xiong, and Hongke Zhao. Prospecting the career development of talents: A survival analysis perspective. In *Proceedings of the 23rd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, KDD '17, pp. 917–925, New York, NY, USA, 2017a. Association for Computing Machinery. ISBN 9781450348874. doi: 10.1145/3097983.3098107. URL https://doi.org/10.1145/3097983.3098107.

Liangyue Li, How Jing, Hanghang Tong, Jaewon Yang, Qi He, and Bee-Chung Chen. Nemo: Next career move prediction with contextual embedding. In *Proceedings of the 26th International Conference on World Wide Web Companion*, WWW '17 Companion, pp. 505–513, Republic and Canton of Geneva, CHE, 2017b. International World Wide Web Conferences Steering Committee. ISBN 9781450349147. doi: 10.1145/3041021.3054200. URL https://doi.org/10.1145/3041021.3054200.

M C B Natividad, B D Gerardo, and R P Medina. A fuzzy-based career recommender system for senior high school students in k to 12 education. *IOP Conference Series: Materials Science and Engineering*, 482(1):012025, feb 2019. doi: 10.1088/1757-899X/482/1/012025. URL https://dx.doi.org/10.1088/1757-899X/482/1/012025.

Qing Wan and Lin Ye. Career recommendation for college students based on deep learning and machine learning. *Scientific Programming*, 2022:3437139, Feb 2022. ISSN 1058-9244. doi: 10.1155/2022/3437139. URL https://doi.org/10.1155/2022/3437139.

Denghui Zhang, Junming Liu, Hengshu Zhu, Yanchi Liu, Lichen Wang, Pengyang Wang, and Hui Xiong. Job2vec: Job title benchmarking with collective multi-view representation learning, 2020. URL https://arxiv.org/abs/2009.07429.