ADVERSARIAL PROBLEMS FOR GENERATIVE NETWORKS

ABSTRACT

We are interested in the design of generative networks. The training of these mathematical structures is mostly performed with the help of adversarial (min-max) optimization problems. We propose a simple methodology for constructing such problems assuring, at the same time, consistency of the corresponding solution. We give characteristic examples developed by our method, some of which can be recognized from other applications and some are introduced here for the first time. We compare various possibilities by applying them to well known datasets using neural networks of different configurations and sizes.

1 INTRODUCTION

The problem we are interested in, can be summarized as follows: We are given two collections of training data $\{\mathbf{z}_j\}$ and $\{\mathbf{x}_i\}$. In the first set the samples follow the *origin* probability density $h(\mathbf{z})$ and in the second the *target* density $f(\mathbf{x})$. The target density $f(\mathbf{x})$ is considered unknown while $h(\mathbf{z})$ can either be known with the possibility to produce samples $\mathbf{z}_j$ every time it is necessary or unknown in which case we have a second fixed training set $\{\mathbf{z}_j\}$. Our goal is to design a deterministic transformation $G(\mathbf{z})$ so that the data $\{\mathbf{y}_j\}$ produced by applying the transformation $\mathbf{y} = G(Z)$ onto $\{\mathbf{z}_j\}$ follow the target density $f(\mathbf{y})$.

Of course one may wonder whether the proposed problem enjoys any solution, namely, whether there indeed exists a transformation $G(\mathbf{z})$ capable of transforming $\mathbf{z}$ into $\mathbf{y}$ with the former following the origin density $h(\mathbf{z})$ and the latter the target density $f(\mathbf{y})$. The problem of transforming random vectors has been analyzed in Box & Cox (1964) where *existence* is shown under general conditions. Computing, however, the actual transformation is a completely different challenge with one of the possible solutions relying on adversarial approaches applied to neural networks.

The most well known usage of this result is the possibility to generate synthetic data that follow the unknown target density $f(\mathbf{x})$. In this case $h(\mathbf{z})$ is selected to be simple (e.g. i.i.d. standard Gaussian or i.i.d. uniform) so that generating realizations from $h(\mathbf{z})$ is straightforward. As mentioned, the adversarial approach can be applied even if the origin density $h(\mathbf{z})$ is unknown provided that we have a dataset $\{\mathbf{z}_j\}$ with data following the origin density.

It was Goodfellow et al. (2014) that first introduced the idea of *adversarial* (min-max) optimization and demonstrated that it results in the determination of the desired transformation $G(\mathbf{z})$ (consistency). Alternative adversarial approaches were subsequently suggested by Martin Arjovsky & Bottou (2017); Bińkowski et al. (2018) and shown to also deliver the correct transformation $G(\mathbf{z})$. Finally, we must mention the work by Nowozin et al. (2016) which is closely related to our results and for which, at the end of Section 2, we give details, emphasizing differences and similarities with our method. As in Nowozin et al. (2016), we will show that our methods provides an *abundance* of adversarial problems that are capable of identifying the appropriate transformation $G(\mathbf{z})$. Furthermore, we will also provide a simple recipe as to how we can successfully construct such problems.

Arguing along the same lines of the existing min-max formulations: We would like to optimally specify a vector transformation $G(\mathbf{z})$, the *generator*, and a scalar function $D(\mathbf{x})$, the *discriminator*. To achieve this, for each combination $\{G(\mathbf{z}), D(\mathbf{x})\}$ we define the cost function

$$J(G, D) = \mathbb{E}_{\mathbf{x} \sim f}\big[\phi\big(D(\mathbf{x})\big)\big] + \mathbb{E}_{\mathbf{z} \sim h}\big[\psi\big(D(G(\mathbf{z}))\big)\big] \tag{1}$$

where $\phi(z), \psi(z)$ are two scalar functions of the scalar z and $\mathbb{E}_{\mathbf{x} \sim f}[\cdot], \mathbb{E}_{\mathbf{z} \sim h}[\cdot]$ denote expectation with respect to the density $f(\mathbf{x}), h(\mathbf{z})$ respectively. The optimum combination genera-

tor/discriminator is then identified by solving the following min-max problem

$$\min_{G(\mathbf{z})} \max_{D(\mathbf{x})} J(G, D) = \min_{G(\mathbf{z})} \max_{D(\mathbf{x})} \left\{ \mathbb{E}_{\mathbf{x} \sim f}\left[\phi\big(D(\mathbf{x})\big)\right] + \mathbb{E}_{\mathbf{z} \sim h}\left[\psi\big(D(G(\mathbf{z}))\big)\right] \right\}. \tag{2}$$

We must point out that our goal is not to solve equation 2, but rather *find a class of functions* $\phi(z), \psi(z)$ *so that the transformation* $G(\mathbf{z})$ *that will come out of the solution of equation 2 is such that* $\mathbf{y} = G(\mathbf{z})$ *follows the target density* $f(\mathbf{y})$ *when* $\mathbf{z}$ *follows the origin density* $h(\mathbf{z})$.

If $\mathbf{z}$ is random following $h(\mathbf{z})$ then $\mathbf{y} = G(\mathbf{z})$ is also random and we denote with $g(\mathbf{y})$ its corresponding probability density. Clearly, there exists a correspondence between transformations $G(\mathbf{z})$ and densities $g(\mathbf{y})$ when the density $h(\mathbf{z})$ of $\mathbf{z}$ is fixed. Since we can write

$$\mathbb{E}_{\mathbf{z} \sim h}\left[\psi\big(D(G(\mathbf{z}))\big)\right] = \mathbb{E}_{\mathbf{y} \sim g}\left[\psi\big(D(\mathbf{y})\big)\right],$$

this allows us to argue that the min-max problem in equation 2 is equivalent to

$$\min_{g(\mathbf{y})} \max_{D(\mathbf{x})} \left\{ \mathbb{E}_{\mathbf{x} \sim f}\left[\phi\big(D(\mathbf{x})\big)\right] + \mathbb{E}_{\mathbf{y} \sim g}\left[\psi\big(D(\mathbf{y})\big)\right] \right\}. \tag{3}$$

It is now possible to combine the two expectations by applying a change of measure and a change of variables and equivalently write equation 3 as follows

$$\min_{g(\mathbf{x})} \max_{D(\mathbf{x})} \mathbb{E}_{\mathbf{x} \sim f}\left[\phi\big(D(\mathbf{x})\big) + r(\mathbf{x})\psi\big(D(\mathbf{x})\big)\right], \tag{4}$$

where $r(\mathbf{x}) = g(\mathbf{x})/f(\mathbf{x})$ denotes the corresponding likelihood ratio. Since $f(\mathbf{x})$ is also fixed, there is again a correspondence between $r(\mathbf{x})$ and $g(\mathbf{x})$, hence the previous min-max problem becomes equivalent to

$$\min_{r(\mathbf{x}) \in \mathbb{L}_f} \max_{D(\mathbf{x})} \mathbb{E}_{\mathbf{x} \sim f}\left[\phi\big(D(\mathbf{x})\big) + r(\mathbf{x})\psi\big(D(\mathbf{x})\big)\right]. \tag{5}$$

Here $\mathbb{L}_f$ denotes the class of all likelihood ratios $r(\mathbf{x})$ with respect to the density $f(\mathbf{x})$, namely, all the functions $r(\mathbf{x})$ that satisfy

$$\mathbb{L}_f = \left\{ r(\mathbf{x}) : \ r(\mathbf{x}) \geq 0, \ \int r(\mathbf{x})f(\mathbf{x}) \, d\mathbf{x} = 1 \right\}. \tag{6}$$

Using these definitions, let us define the cost

$$J(r, D) = \mathbb{E}_{\mathbf{x} \sim f}\left[\phi\big(D(\mathbf{x})\big) + r(\mathbf{x})\psi\big(D(\mathbf{x})\big)\right] \tag{7}$$

and, according to equation 5, we are interested in the following min-max problem

$$\min_{r(\mathbf{x}) \in \mathbb{L}_f} \max_{D(\mathbf{x})} J(r, D). \tag{8}$$

As mentioned, our actual goal is not to solve the adversarial problem. Instead, we would like to properly *identify* pairs of functions $\{\phi(z), \psi(z)\}$ so that equation 8 *accepts as solution the function* $r(X) = 1$. Indeed, if $r(X) = 1$ is the solution to equation 8, this means that $g(\mathbf{x}) = f(\mathbf{x})$ is the solution to equation 3 and, finally, that the optimum $G(\mathbf{x})$ obtained from equation 1 is such that $\mathbf{y} = G(\mathbf{x})$ follows $g(\mathbf{y}) = f(\mathbf{y})$ which, of course, is our original objective. Even though the min-max problem in equation 1 is what we attempt to solve, it is through equation 8 that we understand what its solution entails. In the next section we focus on equation 7, equation 8 and propose a simple design method (recipe) for the two functions $\phi(z), \psi(z)$ that assures that the solution of equation 8 is indeed $r(\mathbf{x}) = 1$. Before we discuss the details of our work, we would like to summarize this paper's contribution.

- We design a family of GANs problems using a likelihood ratio approach. In this class all optimization problems have the desired property that the generator output follows the target distribution of the random vector of interest, $\mathbf{x}$, in other words that the likelihood ratio of the two distributions is equal to one.

- We propose a straightforward *recipe* to explore the GANs family. With this methodology, we were able to identify subgroups characterised by specific transformations of the likelihood ratio. In these subgroups, we discovered novel objective functions and classified to them previously introduced GANs (such as Wasserstein, Cross-Entropy GANs).

- Our experiments provide insights for the behavior of the different GANs objective functions, with some of the novel objective functions performing better than the already known GANs.

2 A CLASS OF FUNCTIONS $\phi(z), \psi(z)$

Suppose that $\omega(r)$ is a *strictly increasing and (left and right) differentiable* scalar function of the nonnegative scalar r, i.e. $r \in [0, \infty)$. Denote with $\mathbb{J}_\omega = \omega\big([0, \infty)\big)$ the range of values of $\omega(r)$ and let $\omega^{-1}(z)$ be the inverse function of $\omega(r)$ which exists and is defined for $z \in \mathbb{J}_\omega$. Let $\rho(z) > 0$ be a positive scalar function also defined for $z \in \mathbb{J}_\omega$ then, using $\omega(r)$ and $\rho(z)$, we propose the following pair $\phi(z), \psi(z)$

$$\phi'(z) = -\omega^{-1}(z)\rho(z), \ \ \psi'(z) = \rho(z), \tag{9}$$

where "′" denotes derivative. Since $\omega(r)$ and $\rho(z)$ are arbitrary (provided they satisfy the strict increase and positivity constraint respectively), the class of pairs defined by equation 9 is very rich allowing for a multitude of choices. We show next that *any* such pair $\{\phi(z), \psi(z)\}$ gives rise to a min-max problem, as in equation 8, that accepts $r(\mathbf{x}) = 1$ as its unique solution. We prove this claim in two steps. The first, involves a theorem where we consider a simplified version of the min-max problem.

Theorem 1 *Let $\omega(r), \phi(z), \psi(z)$ and $\mathbb{J}_\omega$ be defined as above with the additional constraint $\psi\big(\omega(1)\big) = 0$. Fix $r \geq 0$ and consider $\phi(D) + r\psi(D)$ as a function of the scalar D. Then, for any $D \in \mathbb{J}_\omega$, we have that*

$$\phi(D) + r\psi(D) \leq \phi\big(\omega(r)\big) + r\psi\big(\omega(r)\big), \tag{10}$$

with equality if and only if $D = \omega(r)$.

Consider next the minimization with respect to r of the maximal value in equation 10. It is then true that

$$\min_{r \geq 0} \big\{\phi\big(\omega(r)\big) + r\psi\big(\omega(r)\big)\big\} = \phi\big(\omega(1)\big), \tag{11}$$

with equality if and only if $r = 1$.

A consequence of Theorem 1 is the next corollary, which constitutes the second and final step in proving that the adversarial problem defined in equation 8 has as unique solution the function $r(X) = 1$.

Corollary 1 *If the functions $\phi(z), \psi(z)$ satisfy equation 9 and $\omega(r)$ is strictly increasing and left and right differentiable, then in the adversarial problem defined in equation 8 the maximizer is $D(X) = \omega\big(r(X)\big)$ and the minimizer is $r(X) = 1$, while the resulting min-max value is equal to*

$$\min_{r(X) \in \mathbb{L}_f} \max_{D(\mathbf{x})} \mathbb{E}_{\mathbf{x} \sim f} \big[\phi\big(D(\mathbf{x})\big) + r(X)\psi\big(D(\mathbf{x})\big)\big] = \phi\big(\omega(1)\big) + \psi\big(\omega(1)\big). \tag{12}$$

We must emphasize that there already exists the significant work by Nowozin et al. (2016) that addresses a similar problem as our current work, namely the definition of a class of min-max optimizations that can be used to design generator/discriminator pairs. The class in Nowozin et al. (2016) is defined in terms of a convex function $f(r)$ which can be shown to correspond to the outcome of our maximization, namely the function $\phi\big(\omega(r)\big) + r\psi\big(\omega(r)\big)$. This establishes a one-to-one correspondence between the two methods under the ideal (non data-driven) setup. However, we believe that, our approach enjoys certain significant advantages: First, the definition of the two functions $\phi(z), \psi(z)$ in Equ. equation 9 is straightforward while in Nowozin et al. (2016) requires the solution of an optimization problem. Second, in our case we have complete control over the result of the maximization problem that defines the discriminator. In other words we can decide what transformation $\omega(r)$ of the likelihood ratio r, the discriminator must estimate. In Nowozin et al. (2016) such flexibility does not exist.

Controlling the function we estimate with the discriminator plays a significant role in the implementation of the corresponding method. Indeed, we can select $\omega(r)$ properly so that we avoid the need to impose difficult constraints on the discriminator output (e.g. positivity), since such constraints tend to seriously affect the approximation quality of the corresponding neural network. We should also note that there are important applications in Statistics where one is interested in estimating only the transformation of the likelihood ratio $\omega(r)$, with the most common cases being the likelihood ratio itself, its logarithm (log-likelihood ratio), or the ratio $\frac{r}{1+r}$ which plays the role of the posterior probability between two densities. In other words, there are applications where one is interested only in the "max" part of the min-max problem. In fact, in the next section we mention problems where the discriminator function becomes the actual target and not the generator.

3   THE SUBCLASSES OF THE GANS FAMILY

Let us now present some of the subclasses of the GANs family, where each subclass is character-ized by the type of transformation of the likelihood ratio, $\omega(r)$. Once we fix $\omega(r)$ and give pairs $\{\phi(z), \psi(z)\}$ that satisfy equation 9, we are able to "pick" objective functions laying in the $\omega(r)$ subregion.

Subclass A $- \omega(r) = r^\alpha$: The first examined subclass is the simplest one, consisting of just powers of the likelihood ratio. To the best of our knowledge this is the first work proposing objective functions from this class. To find the pairs $\{\phi(z), \psi(z)\}$ we proceed as follows.

We have that $\omega^{-1}(z) = z^{\frac{1}{\alpha}}$ and $\mathbb{J}_\omega = [0, \infty)$. According to equation 9, for $z \in [0, \infty)$ we must define $\phi'(z) = -z^{\frac{1}{\alpha}}\rho(z)$, $\psi'(z) = \rho(z)$. The following examples can be shown to satisfy these equations.

A1) If we select $\rho(z) = z^\beta$, with $\beta \neq -1, -1 - \frac{1}{\alpha}$, this yields $\phi(z) = -\frac{z^{1+\frac{1}{\alpha}+\beta}}{1+\frac{1}{\alpha}+\beta}$ and $\psi(z) = \frac{z^{1+\beta}}{1+\beta}$. For $\beta = -1$, $\rho(z) = z^{-1}$, $\phi(z) = -\alpha z^{\frac{1}{\alpha}}$, $\psi(z) = \log z$. For $\beta = -1 - \frac{1}{\alpha}$, $\rho(z) = z^{-1-\frac{1}{\alpha}}$, $\phi(z) = -\log z$, $\psi(z) = -\alpha z^{-\frac{1}{\alpha}}$.

A2) If we select $\alpha = 1$, $\rho(z) = \frac{1}{(1+z)}$ then, $\phi(z) = -(1+z)$ and $\psi(z) = -(1+z^{-1})$.

A3) If we select $\alpha = 1$, $\rho(z) = \frac{1}{(1+z)z}$ then, $\phi(z) = -\log(1+z)$ and $\psi(z) = -\log(1+z^{-1})$.

For the particular selection $\omega(r) = r$ (corresponding to $\alpha = 1$) we can show that the resulting cost is equivalent to the Bregman cost (Bregman, 1967). In fact there is a one-to-one correspondence between our $\rho(z)$ function and the function that defines the Bregman cost. This correspondence however is lost once we switch to a different α or a different $\omega(r)$ function, suggesting that the proposed class of pairs $\{\phi(z), \psi(z)\}$, is far richer than the class induced by the Bregman cost.

We should mention that in A1) the selection $\alpha = 1, \beta = 0$ is known as the mean square error criterion and if we apply only the maximization problem then this corresponds to a likelihood ratio estimation technique proposed in the literature by Sugiyama et al. (2010; 2012). We will refer to this case as the *MSE* GAN.

Subclass B $- \omega(r) = \alpha^{-1} \log r$: This subclass considers one of the most popular transformations of the likelihood ratio, the log-likelihood ratio. As in the first subclass the next examples are pre-sented for the first time and can be used either under a min-max setting for the determination of the generator/discriminator pair or under a purely maximization setting for the direct estimation of the log-likelihood ratio function $\log r(\mathbf{x})$.

We have $\omega^{-1}(z) = e^{\alpha z}$ and $\mathbb{J}_\omega = \mathbb{R}$. As before $\rho(z)$ must be strictly positive and, according to equation 9, for all real z we must define $\phi'(z) = -e^{\alpha z}\rho(z)$, $\psi'(z) = \rho(z)$. The following examples satisfy these equations.

B1) If $\rho(z) = e^{-\beta z}$ with $\beta \neq 0, \alpha$, this produces $\phi(z) = -\frac{e^{(\alpha-\beta)z}}{\alpha-\beta}$, $\psi(z) = -\frac{e^{-\beta z}}{\beta}$. If $\beta = 0$ then $\rho(z) = 1$, $\phi(z) = -\frac{e^{\alpha z}}{\alpha}$, $\psi(z) = z$. If $\beta = \alpha$ then $\rho(z) = e^{-\alpha z}$, $\phi(z) = -z$ and $\psi(z) = -\frac{e^{-\alpha z}}{\alpha}$. We call the $\alpha = 1, \beta = 0.5$ case the *Exponential* GAN.

B2) If $\alpha = 1$, $\rho(z) = \frac{1}{1+e^z}$ then, $\phi(z) = -\log(1+e^z)$ and $\psi(z) = -\log(1+e^{-z})$.

Subclass C $- \omega(r) = \frac{r}{r+1}$: As we already mentioned this is another important transform of the like-lihood ratio. Interestingly, in this subclass belongs the first introduced GAN (Goodfellow et al., 2014) the *Cross Entropy* GAN.

When $\omega(r) = \frac{r}{r+1}$ we have $\omega^{-1}(z) = \frac{z}{1-z}$ and $\mathbb{J}_\omega = [0, 1]$. For $\rho(z) > 0, z \in [0, 1]$ we must define the functions $\phi(z), \psi(z)$ according to equation 9 $\phi'(z) = -\frac{z}{1-z}\rho(z)$, $\psi'(z) = \rho(z)$. The next set of examples can be seen to satisfy these equations.

C1) If we select $\rho(z) = \frac{1}{z}$, this yields $\phi(z) = \log(1-z)$ and $\psi(z) = \log z$.

C2) Selecting $\rho(z) = (1-z)^{\alpha}$, with $\alpha \neq 0, -1$, yields $\phi(z) = -\frac{1}{1+\alpha}(1-z)^{\alpha+1} + \frac{1}{\alpha}(1-z)^{\alpha}$ and $\psi(z) = -\frac{1}{1+\alpha}(1-z)^{1+\alpha}$. For $\alpha = 0$, we have $\rho(z) = 1$ and $\phi(z) = z + \log(1-z)$, $\psi(z) = z$, while for $\alpha = -1$ we have $\rho(z) = \frac{1}{1-z}$ and $\phi(z) = -\log(1-z) - \frac{1}{1-z}$, $\psi(z) = -\log(1-z)$.

In C1) we recognize the functions used in the original article by Goodfellow et al. (2014). C2) appears for the first time.

Subclass D $- \omega(r) = \text{sign}(\log r)$: This is a special case of $\omega(r)$ with the corresponding function not being strictly increasing. It turns out that we can still come up with optimization problems, two of which are known and used in practice, by considering $\omega(r)$ as a *limit* of a sequence of strictly increasing functions.

Monotone Loss: As a first approximation we propose $\text{sign}(z) \approx \tanh(\frac{c}{2}z)$ where $c > 0$ a parameter. We note that $\lim_{c \to \infty} \tanh(\frac{c}{2}z) = \text{sign}(z)$. Using this approximation we can write

$$\text{sign}(\log r) \approx \tanh\left(\frac{c}{2}\log r\right) = \frac{r^c - 1}{r^c + 1} = \omega(r). \tag{13}$$

As we mentioned, we have exact equality for $c \to \infty$. Let us perform our analysis by assuming that c is finite. We note that $\omega^{-1}(z) = (\frac{1+z}{1-z})^{\frac{1}{c}}$ and $\mathbb{J}_{\omega} = [-1, 1]$. Consequently, if $\rho(z) > 0$ for $z \in [-1, 1]$, we must define $\phi'(z) = -\left(\frac{1+z}{1-z}\right)^{\frac{1}{c}}\rho(z)$, $\psi'(z) = \rho(z)$.

D1) If we let $c \to \infty$ in order to converge to the desired sign function, this yields $\phi'(z) = -\rho(z)$ and $\psi'(z) = \rho(z)$. This suggests that $\phi(z) = -\int^z \rho(x)dx$ is decreasing and $\psi(z) = \int^z \rho(x)dx = -\phi(z)$ is increasing. In fact any strictly increasing function $\psi(z)$ can be adopted provided we select $\phi(z) = -\psi(z)$.

There is a popular combination that falls under Case D1). In particular, the selection $\psi(z) = z = -\phi(z)$ reminds us of Wasserstein GAN Martin Arjovsky & Bottou (2017), with two differences, in our case z should lie in $[-1, 1]$ and the discriminator is not constrained to be a Lipschitz function.

Hinge Loss: As a second approximation we use the expression $\text{sign}(z) \approx \text{sign}(z)|z|^{\frac{1}{c}}$, $c > 0$, which is strictly increasing, continuous and converges to $\text{sgn}(z)$ as $c \to \infty$. This suggests that

$$\text{sign}(\log r) \approx \text{sign}(\log r)|\log r|^{\frac{1}{c}} = \omega(r), \tag{14}$$

and $\omega^{-1}(z) = e^{z^c}$. Since $\omega(r)$ can assume any real value we conclude that $\mathbb{J}_{\omega} = \mathbb{R}$ which, clearly, differs from the previous approximation where we had $\mathbb{J}_{\omega} = [-1, 1]$. If $\rho(z) > 0, z \in \mathbb{R}$ then, according to equation 9 we must define $\phi'(z) = -e^{z^c}\rho(z)$, $\psi'(z) = \rho(z)$. We present the following case that leads to a very well known pair from a completely different application.

D2) If we select $\psi'(z) = \rho(z) = \{e^{-|z|^{\frac{1}{c}}} + \mathbf{1}_{z < -1}\} > 0$ then $\phi'(z) = -e^{z^{\frac{1}{c}}}\{e^{-|z|^{\frac{1}{c}}} + \mathbf{1}_{z < -1}\}$. If we now let $c \to \infty$, we obtain the limiting form for the derivatives which become $\psi'(z) = -\mathbf{1}_{z < 1}$ and $\phi'(z) = \mathbf{1}_{z > -1}$. By integrating we arrive at $\phi(z) = -\max\{1+z, 0\}$ and $\psi(z) = -\max\{1-z, 0\}$. The cost based on this particular pair is called the *hinge loss* Tang (2013) and it is very popular in binary classification where one is interested only in the maximization problem. The corresponding method is known to exhibit an overall performance which in practice is considered among the best Rosasco et al. (2004); Janocha & Czarnecki (2017). Here, as in Zhao et al. (2016), we propose the hinge loss as a means to perform adversarial optimization for the design of the generator $G(\mathbf{x})$.

This completes our presentation of examples. However, we must emphasize, that these are only a few illustrations of possible pairs $\{\phi(z), \psi(z)\}$ one can construct. Indeed combining, as dictated by equation 9, any strictly increasing function $\omega(r)$ with any positive function $\rho(z)$ generates a legitimate pair $\{\phi(z), \psi(z)\}$ and a corresponding min-max problem equation 8 that enjoys the desired solution $r(\mathbf{x}) = 1$.

In Table 1 we summarize some of the aforementioned GAN objectives that were used in our simulations.

Remark 1 *Given the numerous choices we have in defining adversarial optimizations for solving the same problem, one may wonder whether there exists a means to rank these methods and identify the most efficient, at least for classes of data. This is an extremely challenging question which,*

Table 1: Optimization problems for GANs

GAN	$\phi(z)$	$\psi(z)$	$\mathbb{J}_\omega$
A1a	$-z$	$\log(z)$	$[0, \infty)$
A1b	$-\log(z)$	$-z^{-1}$	$[0, \infty)$
A2	$-(1+z)$	$-(1+z^{-1})$	$[0, \infty)$
A3	$-\log(1+z)$	$-\log(1+z^{-1})$	$[0, \infty)$
MSE	$-0.5z^2$	z	$[0, \infty)$
B1a	$-e^z$	e^z	$\mathbb{R}$
B1b	$-z$	$-e^{-z}$	$\mathbb{R}$
Exponential	$-e^{0.5z}$	$-e^{-0.5z}$	$\mathbb{R}$
B2	$-\log(1+e^z)$	$-\log(1+e^{-z})$	$\mathbb{R}$
Cross Entropy	$\log(1-z)$	$\log(z)$	$[0, 1]$
C2	$z + \log(1-z)$	z	$[0, 1]$
Hinge	$-(1+z)_+$	$-(1-z)_+$	$\mathbb{R}$
Wasserstein	z	$-z$	$\mathbb{R}$

unfortunately, finds no answer even in simpler problems. For example, in binary classification there are also classes of optimization problems that are used to train neural networks Bartlett et al. (2006); Masnadi-Shirazi & Vasconcelos (2009). However, until now, no theoretical analysis exists that can order them and designate the most efficient one. This is possible only through experience with countless simulations.

4 DATA-DRIVEN SETUP AND NEURAL NETWORKS

Let us now consider the data-driven version of the problem. As mentioned, the target density $f(\mathbf{x})$ is unknown. Instead we are given a collection of realizations $\{\mathbf{x}_i\}$ that follow $f(\mathbf{x})$ and a second collection $\{\mathbf{z}_j\}$ that follows the origin density $h(\mathbf{z})$. These data constitute our *training set*. Since we are now considering the data-driven version of the problem, we are going to limit $G(\mathbf{z}), D(\mathbf{x})$ to be the outputs of corresponding neural networks. Therefore the generator is replaced by $G(\mathbf{z}, \theta)$ while the discriminator by $D(\mathbf{x}, \vartheta)$ where θ, ϑ summarize the parameters of the two neural networks.

Once we have selected our favorite $\omega(r)$ and $\rho(z)$ functions we can compute from equation 9 the functions $\phi(z), \psi(z)$ that enter into the min-max problem defined in equation 2. This problem, after limiting the generator and discriminator to neural networks, can be rewritten as follows

$$\min_\theta \max_\vartheta \mathcal{J}(\theta, \vartheta) = \min_\theta \max_\vartheta \left\{ \mathbb{E}_{\mathbf{x} \sim f}\left[\phi\big(D(\mathbf{x}, \vartheta)\big)\right] + \mathbb{E}_{\mathbf{z} \sim h}\left[\psi\big(D(G(\mathbf{z}, \theta), \vartheta)\big)\right] \right\}. \quad (15)$$

If θ_o, ϑ_o are the corresponding optimum parameter values, and the structure of the two networks is sufficiently rich, we expect that $G(\mathbf{z}, \theta_o), D(\mathbf{x}, \vartheta_o)$ will approximate the optimum functions $D(\mathbf{x}), G(\mathbf{z})$ of the ideal problem in equation 2 respectively. In particular for θ_o, the generator $G(\mathbf{z}, \theta_o)$, whenever applied onto any $\mathbf{z}_j$ that follows $h(\mathbf{z})$, it will result in a $\mathbf{y}_j = G(\mathbf{z}_j, \theta_o)$ that follows a density which is expected to be close to the target density $f(\mathbf{y})$.

5 EXPERIMENTS

In this section we want to examine the performance of the GANs objectives presented in Table 1 for different datasets. For that reason we tested their performance on four different datasets, namely MNIST (LeCun et al., 1998), CelebA (Liu et al., 2015), CIFAR-10 datasets (Krizhevsky et al., 2009), and Stanford Cars (Krause et al., 2013). We recall that GANs are notorious for their nonrobust behavior Bengio (2012); Creswell et al. (2018); Mescheder et al. (2017). For the stabilization of the training process, we used the maximum gradient-penalty methodology described in Gulrajani et al. (2017) which was generalized to a class of Lipschitz GANs in Zhou et al. (2019) (implementation details in the Appendix A.2).

In Tables 2, 3 we present the final attained Frechet Inception Distances (FID) Heusel et al. (2017) and Kernel Inception Distances (KID) Bińkowski et al. (2018) scores after training while in Figure 1 we show the evolution of FID (second row) and KID (third row) during training. In the first row we

see the value of the distance $d(\mathbf{x}, \mathbf{y}) = \mathbb{E}_{\mathbf{x} \sim f}[D(\mathbf{x})] - \mathbb{E}_{\mathbf{y} \sim g}[D(\mathbf{y})]$. For the expectations estimation we used 64 examples for MNIST and 128 for Stanford Cars, CelebA, and CIFAR-10. We believe that this is a insightful quantity since its value is an indicator of how accurate the discriminator can distinguish samples from the target distribution and the generator output. Finally, in the Appendix A.2 we include some generated samples of our trained generative models.

For the MNIST dataset the different GANs have very similar performance, something that is reasonable since this is a simple dataset. The $d(\mathbf{x}, \mathbf{y})$ curves are quickly converging showing that the discriminator has stabilized. Interestingly, the FID, KID curves GANs with similar $d(\mathbf{x}, \mathbf{y})$ have also close FID, KID scores. In particular, Subclass C GANs (Cross-Entropy with C2); Subclass D (Hinge) with Wasserstein; B2, B1a and A3; B1b with Exponential, A1b with A2; and A1a with MSE. For CIFAR-10 dataset again in terms of FID, KID the different objective functions tend to have similar behavior but we can spot some differences. The objectives A1a, A1b, A2, MSE, B1a, B1b in the first iterations create a steep valley where in the FID score in this period these objectives attain smaller FID scores faster than the other GANs. Also the further improvement of the scores during training seems to be related with the behavior of $d(\mathbf{x}, \mathbf{y})$. For instance the $d(\mathbf{x}, \mathbf{y})$ of A1b, A2 is still increasing in the last iterations and additionally the generated image quality (FID score) is improving as well. Lastly, similarly with MNIST, GANs that have very close $d(\mathbf{x}, \mathbf{y})$ tend to have close FID, KID curves.

For the Stanford Cars and CelebA we observe some performance gaps between different subclasses. Specifically for CelebA the Subclass D and Subclass B objective functions start to diverge after some training steps, something that is evident from the FID, KID curves where the scores increase dramatically after approximately the first half of iterations. Also, this is noticeable in the $d(x, y)$ curves where a sudden drop is recorded around the same period. For Stanford Cars the Subclass C has the worst performance, with the recorded MMD score being an order larger than the other objectives (expect Subclass B –B2, Exponential objectives–). Furthermore, for this dataset the distances $d(\mathbf{x}, \mathbf{y})$ are "noisy" (strong fluctuations) and with approximately 10 times bigger magnitude value when compared the to the corresponding curves in the other datasets. This is reasonable since this dataset is a complex one, where we have natural scenes with cars and importantly a significantly smaller dataset ($\sim$ 8000 training samples, when MNIST, CIFAR10 has 60000 and CelebA 200000).

In summary, our simulations indicate that the Subclass A objectives A1a, A1b, A2, MSE have the best performance both in terms of the computed metrics (hence image generation quality) and stability during training. They might not give the exact best score in all datasets but they are very close the best recorded and most importantly they have an overall more stable behavior when compared to objectives from the other subclasses. Furthermore, the distance $d(\mathbf{x}, \mathbf{y})$ can be an ad-hoc measure of the behavior/stability of our generative models than can be used during training to provide online useful insights of the current training condition.

Table 2: FID Scores

GAN	CARS	CELEBA	CIFAR10	MNIST
A1a	23.30 ± 0.10	7.53 ± 0.02	9.67 ± 0.01	2.18 ± 0.01
A1b	24.22 ± 0.22	7.68 ± 0.04	9.69 ± 0.04	2.13 ± 0.01
A2	24.40 ± 0.04	7.62 ± 0.04	9.53 ± 0.04	2.17 ± 0.01
A3	23.64 ± 0.23	8.50 ± 0.06	9.72 ± 0.04	2.15 ± 0.01
MSE	23.99 ± 0.04	7.66 ± 0.07	9.61 ± 0.03	2.15 ± 0.01
B1a	23.60 ± 0.12	8.06 ± 0.02	9.67 ± 0.05	2.13 ± 0.01
B1b	23.91 ± 0.07	8.07 ± 0.06	9.67 ± 0.04	2.18 ± 0.01
Exponential	23.52 ± 0.06	9.15 ± 0.03	9.79 ± 0.03	2.13 ± 0.01
B2	23.46 ± 0.12	9.39 ± 0.06	9.79 ± 0.07	2.09 ± 0.01
Cross Entropy	25.39 ± 0.16	$7.53 + 0.03$	9.72 ± 0.09	2.08 ± 0.01
C2	24.36 ± 0.12	7.47 ± 0.01	9.75 ± 0.03	2.10 ± 0.01
Hinge	22.88 ± 0.14	10.91 ± 0.05	9.99 ± 0.03	2.16 ± 0.01
Wasserstein	23.99 ± 0.04	10.08 ± 0.04	$9.74 \pm 0.02.$	2.16 ± 0.01

6 CONCLUSION

In this paper, we provided and demonstrated a straightforward methodology to determine loss functions that solve the generative adversarial problem. Our results suggest that there is not a single

Figure 1: Evolution of the corresponding FID and KID scores during training for the datasets LSUN-Cars, CelebA, Cifar10, and Mnist.

Table 3: KID Scores

GAN	CARS $\times 10^{-6} \pm \times 10^{-12}$	CELEBA $\times 10^{-6} \pm \times 10^{-12}$	CIFAR10 $\times 10^{-6} \pm \times 10^{-12}$	MNIST $\times 10^{-4} \pm \times 10^{-8}$
A1a	4.03 ± 2.45	2.57 ± 5.05	2.75 ± 8.47	7.80 ± 5.86
A1b	3.33 ± 1.89	2.67 ± 8.35	2.36 ± 5.86	6.30 ± 4.32
A2	4.36 ± 3.18	3.38 ± 9.68	3.09 ± 8.35	8.79 ± 4.65
A3	4.42 ± 2.49	7.29 ± 5.48	2.40 ± 4.95	8.53 ± 7.35
Mean Square	3.79 ± 1.71	2.55 ± 9.34	2.09 ± 5.63	8.64 ± 7.51
B1a	6.17 ± 3.62	5.56 ± 9.78	2.35 ± 5.52	8.05 ± 3.30
B1b	5.24 ± 2.27	7.32 ± 1.18	2.63 ± 8.42	6.85 ± 3.71
Exponential	5.49 ± 2.86	10.05 ± 6.10	2.81 ± 8.34	6.88 ± 3.41
B2	7.06 ± 3.40	12.48 ± 7.38	2.47 ± 5.42	8.82 ± 3.69
Cross Entropy	13.09 ± 8.95	3.53 ± 12.65	2.53 ± 5.58	6.16 ± 5.37
C2	8.45 ± 2.92	3.11 ± 9.72	4.17 ± 11.03	7.72 ± 3.36
Hinge	4.97 ± 3.50	26.65 ± 16.81	3.97 ± 9.42	8.33 ± 4.16
Wasserstein	4.92 ± 2.70	20.45 ± 28.38	1.74 ± 5.22	7.33 ± 3.33

loss function that achieves the best performance in terms of the examined metrics for all different datasets. This performance variation among loss functions becomes evident as the increasing complexity of the datasets that convolutes the generation task is better addressed by some loss functions that clearly outperform others. Specifically, in simpler datasets, such as MNIST, the evaluated loss functions yield very similar performance, whereas, in more intricate datasets like CelebA, CIFAR-10, and Stanford Cars, performance "gaps" between the different loss functions, and different sub-classes, emerges. Our findings also propose that in every generation task unexplored loss functions outperformed the previously proposed ones. Consequently, this function class is worth-exploring to identify new loss functions that can be used and evaluated in different applications. Our method provides a versatile tool that can be exploited in that direction.

REFERENCES

Peter L Bartlett, Michael I Jordan, and Jon D McAuliffe. Convexity, classification, and risk bounds. *Journal of the American Statistical Association*, 101(473):138–156, 2006.

Yoshua Bengio. Practical recommendations for gradient-based training of deep architectures. In *Neural networks: Tricks of the trade*, pp. 437–478. Springer, 2012.

Mikołaj Bińkowski, Dougal J Sutherland, Michael Arbel, and Arthur Gretton. Demystifying mmd gans. *arXiv preprint arXiv:1801.01401*, 2018.

George EP Box and David R Cox. An analysis of transformations. *Journal of the Royal Statistical Society: Series B (Methodological)*, 26(2):211–243, 1964.

Lev M Bregman. The relaxation method of finding the common point of convex sets and its application to the solution of problems in convex programming. *USSR computational mathematics and mathematical physics*, 7(3):200–217, 1967.

Antonia Creswell, Tom White, Vincent Dumoulin, Kai Arulkumaran, Biswa Sengupta, and Anil A Bharath. Generative adversarial networks: An overview. *IEEE Signal Processing Magazine*, 35 (1):53–65, 2018.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *Advances in neural information processing systems*, pp. 2672–2680, 2014.

Ishaan Gulrajani, Faruk Ahmed, Martin Arjovsky, Vincent Dumoulin, and Aaron C Courville. Improved training of wasserstein gans. In *Advances in neural information processing systems*, pp. 5767–5777, 2017.

Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. In *Advances in neural information processing systems*, pp. 6626–6637, 2017.

Katarzyna Janocha and Wojciech Marian Czarnecki. On loss functions for deep neural networks in classification. *arXiv preprint arXiv:1702.05659*, 2017.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Jonathan Krause, Michael Stark, Jia Deng, and Li Fei-Fei. 3d object representations for fine-grained categorization. In *4th International IEEE Workshop on 3D Representation and Recognition (3dRR-13)*, Sydney, Australia, 2013.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Ziwei Liu, Ping Luo, Xiaogang Wang, and Xiaoou Tang. Deep learning face attributes in the wild. In *Proceedings of the IEEE international conference on computer vision*, pp. 3730–3738, 2015.

SC Martin Arjovsky and Leon Bottou. Wasserstein generative adversarial networks. In *Proceedings of the 34 th International Conference on Machine Learning, Sydney, Australia*, 2017.

Hamed Masnadi-Shirazi and Nuno Vasconcelos. On the design of loss functions for classification: theory, robustness to outliers, and savageboost. In *Advances in neural information processing systems*, pp. 1049–1056, 2009.

Lars Mescheder, Sebastian Nowozin, and Andreas Geiger. The numerics of gans. In *Advances in Neural Information Processing Systems*, pp. 1825–1835, 2017.

Sebastian Nowozin, Botond Cseke, and Ryota Tomioka. f-gan: Training generative neural samplers using variational divergence minimization. In *Advances in neural information processing systems*, pp. 271–279, 2016.

Lorenzo Rosasco, Ernesto De Vito, Andrea Caponnetto, Michele Piana, and Alessandro Verri. Are loss functions all the same? *Neural Computation*, 16(5):1063–1076, 2004.

Masashi Sugiyama, Taiji Suzuki, and Takafumi Kanamori. Density ratio estimation: A comprehensive review (statistical experiment and its related topics). 2010.

Masashi Sugiyama, Taiji Suzuki, and Takafumi Kanamori. *Density ratio estimation in machine learning*. Cambridge University Press, 2012.

Yichuan Tang. Deep learning using linear support vector machines. *arXiv preprint arXiv:1306.0239*, 2013.

Junbo Zhao, Michael Mathieu, and Yann LeCun. Energy-based generative adversarial network. *arXiv preprint arXiv:1609.03126*, 2016.

Zhiming Zhou, Jiadong Liang, Yuxuan Song, Lantao Yu, Hongwei Wang, Weinan Zhang, Yong Yu, and Zhihua Zhang. Lipschitz generative adversarial nets. *arXiv preprint arXiv:1902.05687*, 2019.

A APPENDIX

A.1 PROOFS

Theorem 1 Proof. We note that the constraint $\psi\big(\omega(1)\big) = 0$ does not affect the generality of our class of functions since from equation 9 we have that $\psi(z)$, after integration, is defined up to an arbitrary additive constant. We can always select this constant so that the constraint is satisfied. We would also like to emphasize that this constraint is needed only for the proof of this theorem and it is not necessary for the corresponding min-max problem defined in equation 8.

For fixed r, to find the maximum of $\phi(D) + r\psi(D)$ we consider the derivative with respect to D which, using equation 9, takes the form

$$\phi'(D) + r\psi'(D) = \big(r - \omega^{-1}(D)\big)\rho(D).$$

The strict increase of $\omega(r)$ is inherited by its inverse function $\omega^{-1}(z)$ which, combined with the positivity of $\rho(z)$, implies that the previous expression has the same sign as $r - \omega^{-1}(D)$ or $\omega(r) - D$. Consequently $D = \omega(r)$ is the *only critical point* of $\phi(D) + r\psi(D)$ which is a global maximum. Of course there are possibilities for extrema at the two end points of $\mathbb{J}_\omega$ but they can only be (local) minima.

Let us now focus on the resulting function $\phi\big(\omega(r)\big) + r\psi\big(\omega(r)\big)$. Taking its derivative with respect to r yields

$$\big\{\phi\big(\omega(r)\big) + r\psi\big(\omega(r)\big)\big\}' = \big\{\phi'\big(\omega(r)\big) + r\psi'\big(\omega(r)\big)\big\}\omega'(r) + \psi\big(\omega(r)\big) = \psi\big(\omega(r)\big),$$

where the last equality is due to the specific definition of the two functions $\phi(z), \psi(z)$ in equation 9. Since $\psi'(z) = \rho(z) > 0$, this implies that $\psi(z)$ is strictly increasing, being also the integral of $\rho(z)$ it is continuous in z. If we combine this property with the strict increase and continuity (as a result of left and right differentiability) of $\omega(r)$ we conclude that $\psi\big(\omega(r)\big)$ is also strictly increasing and continuous in r. We recall that $\psi(z)$ is selected to satisfy $\psi\big(\omega(1)\big) = 0$, consequently for $r = 1$ the function $\phi\big(\omega(r)\big) + r\psi\big(\omega(r)\big)$ has a unique minimum which is global and no other critical points. Of course it can still exhibit extrema at $r = 0$ and/or $r \to \infty$ but they can only be (local) maxima. ∎

Corollary 1 Proof. First, we observe that

$$\mathbb{E}_{\mathbf{x}\sim f}\big[\phi\big(D(\mathbf{x})\big) + r(\mathbf{x})\psi\big(D(\mathbf{x})\big)\big] = \mathbb{E}_{\mathbf{x}\sim f}\big[\phi\big(D(\mathbf{x})\big) + r(\mathbf{x})\tilde{\psi}\big(D(\mathbf{x})\big)\big] + \psi\big(\omega(1)\big) \quad (16)$$

with the last equality being true since $\mathbb{E}_{\mathbf{x}\sim f}[r(\mathbf{x})] = 1$ and where $\tilde{\psi}(z) = \psi(z) - \psi\big(\omega(1)\big)$. We start with the maximization problem. Since $D(\mathbf{x})$ is a function of $\mathbf{x}$ we have

$$\max_{D(\mathbf{x})} \mathbb{E}_{\mathbf{x}\sim f}\big[\phi\big(D(\mathbf{x})\big) + r(\mathbf{x})\tilde{\psi}\big(D(\mathbf{x})\big)\big] = \mathbb{E}_{\mathbf{x}\sim f}\Big[\max_{D(\mathbf{x})}\big\{\phi\big(D(\mathbf{x})\big) + r(\mathbf{x})\tilde{\psi}\big(D(\mathbf{x})\big)\big\}\Big]. \quad (17)$$

The maximization under the expectation can be performed for each fixed $\mathbf{x}$. However, when we fix $\mathbf{x}$ then $r(\mathbf{x})$ becomes a constant and the result of the maximization depends only on the actual value of $r(\mathbf{x})$. This suggests that we can limit ourselves to functions of the form $D(\mathbf{x}) = D\big(r(\mathbf{x})\big)$. After this observation we can drop the dependence on $\mathbf{x}$ and perform, equivalently, the maximization $\max_D\big\{\phi\big(D(r)\big) + r\tilde{\psi}\big(D(r)\big)\big\}$ for each fixed r. The pair $\{\phi(z), \tilde{\psi}(z)\}$ satisfies the assumptions of Theorem 1, therefore maximization is achieved for $D(r) = \omega(r)$. This implies that

$$\max_{D(\mathbf{x})} \mathbb{E}_{\mathbf{x}\sim f}\big[\phi\big(D(\mathbf{x})\big) + r(\mathbf{x})\psi\big(D(\mathbf{x})\big)\big] = \mathbb{E}_{\mathbf{x}\sim f}\big[\phi\big(\omega\big(r(\mathbf{x})\big)\big) + r(\mathbf{x})\tilde{\psi}\big(\omega\big(r(\mathbf{x})\big)\big)\big] + \psi\big(\omega(1)\big).$$

We can now continue in a similar way for the minimization problem. Specifically

$$\min_{r(\mathbf{x}) \in \mathbb{L}_f} \max_{D(\mathbf{x})} \mathbb{E}_{\mathbf{x} \sim f} \left[\phi(D(\mathbf{x})) + r(\mathbf{x})\tilde{\psi}(D(\mathbf{x})) \right] =$$

$$\min_{r(\mathbf{x}) \in \mathbb{L}_f} \mathbb{E}_{\mathbf{x} \sim f} \left[\phi(\omega(r(\mathbf{x}))) + r(\mathbf{x})\tilde{\psi}(\omega(r(\mathbf{x}))) \right] \geq$$

$$\mathbb{E}_{\mathbf{x} \sim f} \left[\min_{r(\mathbf{x}) \in \mathbb{L}_f} \left\{ \phi(\omega(r(\mathbf{x}))) + r(\mathbf{x})\tilde{\psi}(\omega(r(\mathbf{x}))) \right\} \right] \geq$$

$$\mathbb{E}_{\mathbf{x} \sim f} \left[\min_{r} \left\{ \phi(\omega(r)) + r\tilde{\psi}(\omega(r)) \right\} \right] =$$

$$\phi(\omega(1))$$

with the last inequality being true since the minimization that follows is unconstrained and the last equality being a consequence of Theorem 1. The final lower bound is clearly attained by $r(X) = 1$, which is also a legitimate solution of the constrained minimization, since $r(X) = 1$ belongs to the class $\mathbb{L}_f$ of likelihood ratios. Consequently $r(X) = 1$ is the solution to the min-max problem. Returning to the original min-max setup with $\psi(z)$ replacing $\tilde{\psi}(z)$, we can clearly see that it satisfies equation 12. This completes the proof. ∎

A.2 EXPERIMENTS

In our experiments we employed the two neural networks the generator and the discriminator. For the generator, we used a four-layer neural network where the first layer is linear and the remaining deconvolutional; with ReLU activation functions between the layers except the final layer where we used a sigmoid function since the output is an image with pixel values in the range $[0, 1]$. The generator input is a standard i.i.d. normal vector with dimension 64 for MNIST and 128 for Stanford Cars, CelebA and CIFAR-10. The output of the generator is a 784×1 vector for the MNIST dataset, whereas for the other datasets it is a 3072×1 vector.

For the discriminator, we used a four-layer neural network with three convolutional layers followed by a linear layer. We applied Leaky ReLUs between the layers except for the final layer where we adopted proper functions based on the range $\mathbb{J}_\omega$. For the training of the two neural networks we applied the Adam algorithm Kingma & Ba (2014) with $\beta_1 = 0.5, \beta_2 = 0.9$, learning rate 10^{-4} and batch size 50 for MNIST and 128 for Stanford Cars, CelebA and CIFAR-10. For all datasets, the training lasted 180000 iterations.

In the Figures 2, 3 and 4 we present some random samples of the trained generators for the datasets Stanford cars, CelebA, and CIFAR-10.

Figure 2: Random samples for different GANs objective function on Stanford cars dataset.

Figure 3: Random samples for different GANs objective function on CelebA dataset.

Figure 4: Random samples for different GANs objective function on CIFAR-10 dataset.