A FRAMEWORK FOR LEARNED SPARSE SKETCHES

ABSTRACT

Sketching is a compression technique that can be applied to many problems to solve them quickly and approximately. The matrices used to project data to smaller dimensions are called "sketches". In this work, we consider the problem of optimizing sketches to obtain low approximation error over a data distribution.

We introduce a general framework for "learning" and applying input-independent sparse sketches. The sketch optimization procedure has two stages: one for optimizing the placement of the sketch's non-zero entries and another for optimizing their values. Next, we provide a way to apply learned sketches that has worst-case guarantees for approximation error.

We instantiate this framework with three sketching applications: least-squares regression, low-rank approximation (LRA), and k-means clustering. Our experiments demonstrate that our approach substantially decreases approximation error compared to classical and naïvely learned sketches.

Finally, we investigate the theoretical aspects of our approach. For regression and LRA, we show that our method obtains state-of-the art accuracy for fixed time complexity. For LRA, we prove that it is strictly better to include the first optimization stage. For k-means, we derive a more straightforward means of retaining approximation guarantees.

1 INTRODUCTION

In recent years, we have seen the influence of machine learning extend far beyond the field of artificial intelligence. Specifically, the underlying paradigm, which assumes an algorithm input distribution and optimizes algorithm parameters accordingly, has even been applied with success to "classical" algorithms (Kraska et al., 2018; Lykouris & Vassilvitskii, 2018; Purohit et al., 2018; Hsu et al., 2019). This input distribution assumption is often accurate in practice. For example, data is often streamed. E-commerce platforms record users' purchases and browsing history, ride-sharing applications continuously track traffic conditions in their users' vicinities, etc. Here, algorithms are applied to consecutive data points which are closely related.

In particular, we are interested in how this ML paradigm can be applied to sketching. Sketching is a well-studied data compression technique that has been applied to problems such as low-rank approximation, robust regression, and clustering, among many others (Sarlos, 2006; Clarkson & Woodruff, 2009; 2014; 2017; Cohen et al., 2015; Makarychev et al., 2019). With the dramatic increase in the dimensions of collected data in the past decade, compression methods are more important than ever. Thus, it is of practical interest to improve the accuracy and efficiency of sketching algorithms.

In the basic sketching scheme, we compress our input by applying a linear projection (via matrix multiplication with a "sketch" matrix) and compute an approximate solution using this smaller, compressed input. Together, the methods for constructing the sketch and for computing a solution using the sketched input are the "sketching algorithm". Sketching algorithms are application-specific and have theoretical guarantees about worst-case approximation error in terms of sketch size (or, equivalently, algorithm runtime).

Classically, sketches are constructed so that they satisfy worst-case bounds on arbitrary inputs. A natural question is whether better sketches can be constructed if we assume inputs are not arbitrary, but are sampled from a distribution. Further, we consider if it still has worst-case guarantees for distribution-dependent sketches. Our aim is to address these problems in our work.

Our results. Our main contribution is providing a framework for creating and using "learned" input-independent sparse sketches that can be extended to various applications. We have focused on input-independent sparse sketches because they enable the fastest sketching algorithms. Input-independent sketches[1] are the quickest to construct because they do not require computations on a possibly high-dimensional input. Sparse sketches are the quickest to apply because matrix multiplication is fast for a matrix with mostly zero entries. Specifically, we focus on sketches with the same sparsity pattern as *CountSketch* which has one non-zero entry per column (Charikar et al., 2002). While our learned sketch will maintain this sparsity for its speed advantage, the values of its non-zero entries will differ from those of classic CountSketch because we will be optimizing them.

When learning a sparse sketch, we must optimize both the placement of the non-zero entries and their values. Our framework proposes a greedy entry-by-entry strategy for the first problem and a gradient descent-based method for the second. We instantiate this framework on three applications: least-squares regression, low-rank approximation (LRA), and k-means clustering. We demonstrate for all three that this two-stage optimization gives state-of-the-art approximation error on holdout data. For regression and LRA, we prove that this is the case.

It is important to have absolute confidence in worst-case sketching performance, so we consider how to retain the guarantees offered by classical sketches. Learned sparse sketches can be arbitrary, so such guarantees do not translate to them. Our solution is to sketch with learned and classical sketches, quickly evaluating both and taking the better of the two. We also prove a simpler approach for k-means clustering, which is analogous to a prior result for LRA (Indyk et al., 2019) where guarantees were retained by sketching with a classical sketch appended to the learned one.

Finally, we conduct an ablation study of the components of our algorithm. We show empirically that including the time-consuming first optimization stage is either comparable to or much better than not including it at all. Further, we prove that it is *strictly* better to include it for LRA.

Related work In the last few years, there has been much work on leveraging ML to improve classical algorithms; we only mention a few examples here. One related body of work is data-dependent dimensionality reduction, such as an approach for pair-wise/multi-wise similarity preservation for indexing big data (Wang et al., 2017) and a method for learning linear projections for general applications (Hegde et al., 2015). Projection with a sparse sketch is equivalent to hashing the rows of an input matrix to a small number of bins. Thus, we also find connections with the body of work on learned hashes, most of which addresses the nearest neighbor search problem (see Wang et al. for a survey). However, in order to obtain approximation guarantees, our "hash function" (sparse sketch) must satisfy properties which these learned hashes do not, such as affine ϵ-embeddings (Def. A.1).

In particular, we build off of the work of Indyk et al. (2019). This work introduced a gradient-based optimization method specifically for an LRA application. We add an additional optimization step which is important for sparse sketches. We show empirically that our two-stage optimization is better than a one-stage gradient-based optimization and prove this for LRA. Additionally, we extend this concept to different and more complex applications. We examine regression, clustering, and a more intricate sketching algorithm for LRA. Finally, whereas Indyk et al. gives an LRA-specific method for worst-case guarantees, we give a method which is extensible to different applications.

2 PRELIMINARIES

Our learned sketches have the sparsity pattern of the classical CountSketch. The construction of this sketch is described below. We also define affine ϵ-embeddings, which is a class of sketches that includes CountSketch. This ϵ-embedding property is desirable because it allows us to prove that certain sketching algorithms give $(1 + \epsilon)$-approximations.

Definition 2.1 (Classical CountSketch). *The* CountSketch *(abbreviated as CS) matrix S has one non-zero entry in each column with a random location and random value in $\{\pm 1\}$.*

Definition 2.2 (Affine Embedding). *Given a pair of matrices A and B, a matrix S is an* affine *ϵ-embedding if for all X of the appropriate shape, $\|S(AX - B)\|_F^2 = (1 \pm \epsilon) \|AX - B\|_F^2$.*

---

[1] An input-independent sketch has a construction that is not a function of the input.

Notation. We denote the singular value decomposition (SVD) of A by $A = U\Sigma V^\top$ with orthogonal U, V and diagonal Σ. Relatedly, the Moore-Penrose pseudo-inverse of A is $A^\dagger = V\Sigma^{-1}U^\top$, where Σ^{-1} is constructed by inverting the non-zero diagonal entries.

3 FRAMEWORK

We describe our framework for learning input-independent, sparse sketches. This framework can be applied to many different sketching applications. It consists of two parts: a sketch optimization algorithm (Part 1 below) and a learned sketch algorithm (Part 2) that is used for applying the sketch with guarantees.

PART 1: OPTIMIZING THE SKETCH

Every sketching application is defined by an objective function, which we denote by $\mathcal{L}(\cdot)$ to stand for loss function. For these applications, the goal is to find a solution which minimizes the objective. As an example, for least-squares regression, $\mathcal{L}(X) = \|AX - B\|_F^2$.

Our overarching goal is to minimize the objective value of the *sketched solution* with respect to the *sketch parameters* (i.e., nonzero entry placement and value). The application-specific sketching algorithm defines the sketched solution as a function of the sketch (parameters). Returning to our least-squares regression example: the sketching algorithm computes the sketched solution $\hat{X} = (SA)^\dagger(SB)$. We want to minimize the regression error of this solution with respect to the sketch (parameters):

$$S^* = \arg\min_S \mathcal{L}(S, \mathcal{I}) = \arg\min_S \left\| A(SA)^\dagger(SB) - B \right\|_F^2$$

where $\mathcal{I}$ is the input data ((A, B) in this case).

Stage 1: Placing the nonzero entries We want to maintain the sparsity pattern of CS (one nonzero entry per column), but we are free to place that nonzero entry wherever we like for each column. A naïve method would be to evaluate the objective for the exponential number of placement combinations. As this is intractable, we consider a greedy alternative. Our method is to build the sketch incrementally, placing one nonzero entry at a time. For each nonzero entry, we evaluate the objective for all $m \times 2$ possible (placement, value) additions[2] to the sketch constructed thus far (Algorithm 1).

We note that for some applications it can be inefficient to evaluate the objective. This is especially true for applications where the sketched solution does not have a closed form (i.e., k-means) and is instead computed iteratively. In these cases, we recommend finding a surrogate objective which is faster to compute, as we illustrate in later sections. This myopic greedy algorithm is empirically very effective (Section 5) and also provably so for LRA (Theorem 4.3)).

Algorithm 1 GREEDY STAGE

Require: $\mathcal{A}_{\text{train}} = \{A_1, ..., A_N\}$ with $A_i \in \mathbb{R}^{n \times d}$; sketch dimension m
 1: initialize $S = \mathbf{0}^{m \times n}$
 2: **for** i in range(n) **do**
 3: $\quad w^*, j^* = \arg\min_{w \in \{\pm 1\}, j \in [m]} \sum_{A_i \in A_{\text{train}}} \mathcal{L}(S_{w,j}, A_i)$ where $S_{w,j} = S + w(\vec{e_j}\vec{e_i}^\top)$
 4: $\quad S[j^*, i] = w^*$
 5: **end for**

Stage 2: Optimizing the nonzero values. For many applications, $\mathcal{L}(S, \mathcal{I})$ is differentiable with respect to S. Thus, we can minimize the objective with respect to the sketch's nonzero entries via gradient descent. For implementation, we will rely on automatic differentiation packages. However, we also need to enforce the "sparsity pattern" that we computed at the previous stage. To do that, we express S as two vectors: $\vec{p} \in \mathbb{Z}_m^n$, specifying the row index of each column's nonzero entry, and $\vec{v} \in \mathbb{R}^n$, specifying the value of each nonzero entry. We construct S as $S = \mathbf{0}^{m \times n}$ and then

---

[2]Restricting the hash weights to ± 1

$S[\vec{p}, \text{range}(n)] = \vec{v}$. Now we can differentiate the objective with respect to $\vec{v}$ and only update $\vec{v}$, keeping the locations of the nonzero entries ($\vec{p}$) fixed (Algorithm 2).

Algorithm 2 GRADIENT STAGE

Require: $\mathcal{A}_{\text{train}} = \{A_1, ..., A_N\}$ with $A_i \in \mathbb{R}^{n \times d}$; $\vec{v}, \vec{p}$ from Alg. 1; learning rate α
1: **for** i in $\text{range}(n_{\text{iter}})$ **do**
2:   $S = \mathbf{0}^{m \times n}$
3:   $S[\vec{p}, \text{range}(n)] = \vec{v}$
4:   sample A_{batch} from A_{train}
5:   $\vec{v} \leftarrow \vec{v} - \alpha \frac{\partial \mathcal{L}(\vec{v}, A_{\text{batch}})}{\partial \vec{v}}$
6: **end for**

PART 2: APPLYING THE SKETCH WITH GUARANTEES

To apply the sketch, we run the original sketching algorithm using our learned sketch and add an extra step to preserve worst-case guarantees.

Classical algorithms always have worst-case guarantees on the approximation error. However, since the output of sketch optimization can be arbitrary, the guarantees for highly-structured classical sketches do not carry over to learned sketches. In the worst case, learned sketches can either encounter out-of-distribution inputs or in-distribution inputs which were not well-represented in the training data. To address both cases, we suggest a method where a classical sketch is used as a fallback. This is useful because the worst-case guarantees for classical sketches hold for arbitrary inputs and also (consequently) arbitrary input distributions.

Our method involves computing the objective values for both our learned sketch and a classical sketch and using them to select the better sketch. However, calculating the objectives requires computation on potentially large inputs, so we only approximately compute them, using sketching, for the sake of speed (Alg. 3). This speed of this comparison allows us to append this step without changing the time complexity of the classical sketching algorithm. Other advantages are that this step is simple enough to be practically useful and that it is extensible to various applications.

Indyk et al. provides an even simpler alternative for retaining worst-case guarantees for LRA, which is to sketch using the learned sketch appended to a classical sketch. We prove that this is also possible for k-means clustering (Theorem 4.4).

Algorithm 3 LEARNED-SKETCH-ALGORITHM. For many applications, the objective is the Frobenius norm of a matrix M. We let $M = \mathcal{M}(S, \mathcal{I})$ be a function related to the loss via $\mathcal{L}(S, \mathcal{I}) = \|\mathcal{M}(S, \mathcal{I})\|_F^2$.

Require: learned β-approximate sketch S_L; classical sketch S_C; input data $\mathcal{I}$
1: $M_L \in \mathbb{R}^{n \times d} \leftarrow \mathcal{M}(S_L, \mathcal{I})$, $M_C \in \mathbb{R}^{n \times d} \leftarrow \mathcal{M}(S_C, \mathcal{I})$
2: $S \leftarrow \text{CountSketch} \in \mathbb{R}^{\frac{1}{\beta^2} \times n}$, $R \leftarrow \text{CountSketch} \in \mathbb{R}^{\frac{1}{\beta^2} \times d}$
3: $\Delta_L \leftarrow \|SM_L R^\top\|_F^2$, $\Delta_C \leftarrow \|SM_C R^\top\|_F^2$
4: **if** $\Delta_L \leq \Delta_C$ **then**
5:   **return** solution computed with S_L
6: **end if**
7: **return** solution computed with S_C

---

4 INSTANTIATIONS

We chose the following sketching applications for their ubiquity in the ML literature. For each, we define the objective function and a sketching algorithm, which allows us to express the objective in terms of just the sketch and the inputs $(S, \mathcal{I})$. We also compare the worst-case guarantees of the classical sketching algorithm and our learned sketch algorithm. All missing proofs in this section are deferred to the appendix.

4.1 LEAST-SQUARES REGRESSION

We consider a generalized version of ℓ_2 regression called "multiple-response regression" (MRR). Given a matrix of observations ($A \in \mathbb{R}^{n \times d}$) and a matrix of corresponding values ($B \in \mathbb{R}^{n \times d'}$), the goal of MRR is to solve $\min_X \mathcal{L}(X) = \min_X \|AX - B\|_F^2$.

Sketching algorithm. The algorithm is simply to sketch A, B with a sparse sketching matrix S (e.g., CS) and compute the closed-form solution on SA, SB, which are small (Algorithm 4).

Algorithm 4 SKETCH-REGRESSION (Sarlos, 2006; Clarkson & Woodruff, 2017)

Require: $A \in \mathbb{R}^{n \times d}, B \in \mathbb{R}^{n \times d'}, S \in \mathbb{R}^{m \times n}$
  1: **return:** $\hat{X} = (SA)^+(SB)$

Sketch optimization. For both the greedy and gradient stages, we use the objective $\mathcal{L}(S, A, B) = \|A(SA)^+(SB) - B\|_F^2$.

Learned sketch algorithm. For fixed accuracy, our learned sketch algorithm achieves state-of-the-art time complexity, besting the classical algorithm. We prove an equivalent statement: the learned sketch algorithm yields better approximation error for fixed time complexity. (See Lemma A.4 for the classical algorithm's worst-case guarantee). In the following theorem, we assume Alg. 3 uses a learned sketch which is an affine β-embedding and also a classical sketch of the same size which is an affine ϵ-embedding. If $\beta < \epsilon$, the above statement is true.

Theorem 4.1 (Learned sketching with guarantees for MRR). *Given a learned sparse sketching matrix $S_L \in \mathbb{R}^{\frac{d}{\epsilon^2} \times n}$ which attains a $(1 + \beta)$-approximation for MRR on $A \in \mathbb{R}^{n \times d}, B \in \mathbb{R}^{n \times d'}$, Alg. 3 gives a $(1 + \min(\beta, \epsilon))$-approximation in $O(\text{nnz}(A) + \text{nnz}(B) + \text{poly}(dd'\epsilon) + d\beta^{-4})$ time.*

4.2 LOW-RANK APPROXIMATION

Given an input matrix $A \in \mathbb{R}^{n \times d}$ and a desired rank k, the goal of LRA is to solve

$$\min_{X, \text{rank } k} \mathcal{L}(X) = \min_{X, \text{rank } k} \|X - A\|_F^2$$

Sketching algorithm. We consider the time-optimal (up to low order terms) sketching algorithm by Sarlos; Clarkson & Woodruff; Avron et al. (Algorithm 5) with worst-case guarantees described in Lemma A.8.

Algorithm 5 SKETCH-LOWRANK (Sarlos, 2006; Clarkson & Woodruff, 2017; Avron et al., 2016).

Require: $A \in \mathbb{R}^{n \times d}, S \in \mathbb{R}^{m_S \times n}, R \in \mathbb{R}^{m_R \times d}, S_2 \in \mathbb{R}^{m_{S2} \times n}, R_2 \in \mathbb{R}^{m_{R2} \times d}$
  1: $U_C \begin{bmatrix} T_C & T'_C \end{bmatrix} \leftarrow S_2 A R^\top, \begin{bmatrix} T_D^\top \\ T_D'^\top \end{bmatrix} U_D^\top \leftarrow SAR_2^\top$ with U_C, U_D orthogonal
  2: $G \leftarrow S_2 A R_2^\top$
  3: $Z'_L Z'_R \leftarrow [U_C^\top G U_D]_k$
  4: $Z_L = \begin{bmatrix} Z'_L T_D^{-\top} & 0 \end{bmatrix}, Z_R = \begin{bmatrix} T_C^{-1} Z'_R \\ 0 \end{bmatrix}$
  5: $Z = Z_L Z_R$
  6: **return:** $AR^\top Z SA$ in form $P_{n \times k}, Q_{k \times d}$

Sketch optimization. For the greedy stage, we optimize sketches S and R individually. However, we do not use $\mathcal{L}(S, R, S_2, R_2, A) = \|X - A\|_F^2$ with X from Alg. 5 as the objective. This is because the optimization for one sketch would then depend on the other sketches. Instead, we use a proxy objective. We observe that the proof that Alg. 5 is an ϵ-approximation uses the fact that the row space of SA and the column space of AR both contain a good rank-k approximation to A. Thus, the proxy objectives for S and R are for k-rank approximation in the row/column space of SA/AR,

respectively. For example, the proxy objective for S is $\mathcal{L}(S, A) = \left\| [AV]_k V^\top - A \right\|_F^2$ where V is from the SVD $SA = U\Sigma V^\top$ and $[\cdot]_k$ takes the optimal k-rank approximation using truncated SVD. The proxy objective for R is defined analogously.

For the gradient stage, we optimize all four sketches (S, R, S_2, R_2) simultaneously using $\mathcal{L}(S, R, S_2, R_2, A) = \|X - A\|_F^2$ with X from Algorithm 5, since it can easily be implemented with differentiable functions.

Learned sketch algorithm. Just like for regression (Section 4.1), we can prove that our learned sketch algorithm achieves a better accuracy than the classical one given the same runtime.

Theorem 4.2 (Low-Rank Approximation). *Given a learned sparse sketching matrix $S_L \in \mathbb{R}^{\mathrm{poly}(\frac{k}{\epsilon}) \times n}$ which is a $(1 + \beta)$-approximation for LRA on $A \in \mathbb{R}^{n \times d}$, Algorithm 3 gives a $(1 + \min(\beta, \epsilon))$-approximation in $O(\mathrm{nnz}(A) + (n + d)\,\mathrm{poly}(\frac{k}{\epsilon}) + \frac{k^4}{\beta^4} \cdot \mathrm{poly}(\frac{k}{\epsilon}))$ time.*

Greedy stage offers strict improvement. Finally, we prove for LRA that including the greedy stage is strictly better than not including it. We can show this for two different natural distributions (spiked covariance and Zipfian). The intuition is that the greedy algorithm separates heavy-norm rows (which are important "directions" in the row space) into different bins.

Theorem 4.3. *Consider a matrix A from either the spiked covariance or Zipfian distribution. Let S_L denote a sparse sketch that Algorithm 1 has computed by iterating through indices in order of non-increasing row norms of A. Let S_C denote a CountSketch matrix. Then, there is a fixed $\eta > 0$ such that $\min_{\text{rank-}k\, X \in \mathrm{rowsp}(S_L A)} \|X - A\|_F^2 \leq (1 - \eta) \min_{\text{rank-}k\, X \in \mathrm{rowsp}(S_C A)} \|X - A\|_F^2$.*

4.3 k-MEANS CLUSTERING

Let $A \in \mathbb{R}^{n \times d}$ represent a set of n points, $A_1, \ldots, A_n \in \mathbb{R}^d$. In k-means clustering, the goal is to find a partition of $A_1, ..., A_n$ into k clusters $C = \{\mathcal{C}_1, \ldots, \mathcal{C}_k\}$ to

$$\min_C \mathcal{L}(C, A) = \min_C \sum_{i=1}^k \min_{\mu_i \in \mathbb{R}^d} \sum_{j \in C_i} \|A_j - \mu_i\|_F^2$$

where μ_i^* denotes the center of cluster $\mathcal{C}_i$.

Sketching algorithm. First, compress A into AV, where V is from SVD $SA = U\Sigma V^\top$ and $S \in \mathbb{R}^{O(k^2/\epsilon^2) \times n}$ is a CountSketch. Then, we use an approximation algorithm for k-means, such as Lloyd's algorithm with a k-means++ initialization (Lloyd, 1982; Arthur & Vassilvitskii, 2007). Solving with AV gives a $(1 + \epsilon)$-approximation (Cohen et al., 2015) and Lloyd's gives an $O(\log(k))$ approximation, so we have a $(1 + \epsilon)O(\log(k))$ approximation overall.

Sketch optimization. k-means is an interesting case study because it presents a challenge for both stages of optimization. For the greedy stage, we observe that k-means does not have a closed form solution, which means that evaluating the objective requires a (relatively) time-consuming iterative process. In the gradient stage, it is possible to differentiate through this iterative computation, but propagating the gradient through such a nested expression is time-consuming. Thus, a proxy objective which is simple and quick to evaluate would be useful for both stages.

Cohen et al. showed that we get a good k-means solution if A is projected to an *approximate top singular vector space*. This suggests that a suitable proxy objective would be low-rank approximation: $\mathcal{L}(S, A) = \left\| [AV]_k V^\top - A \right\|_F^2$, like in Section 4.2. We use this objective for both the greedy and gradient stages.

Learned sketch algorithm. For k-means, we can use a different method to obtain worst-case guarantees. We prove that by concatenating a classical sketch to our learned sketch, our sketched solution will be a $(1 + O(\epsilon))$-approximation.

Theorem 4.4 (Sketch monotonicity property for k-means). *For a given classical CountSketch $S_C \in \mathbb{R}^{O(\mathrm{poly}(k/\epsilon)) \times n}$, sketching with any extension of S_C (i.e., by a learned sparse sketch S_L) yields a better approximate solution for k-means than sketching with S_C itself.*

5 EVALUATION

We implemented and compared the following sketches:

- **Random**: classical random CountSketch
- **GD only**: a sparse sketch with optimized values and random positions for non-zero entries
- **Ours**: a sparse sketch for which both the values and the positions of the non-zero entries have been optimized.

We also consider two "naïvely" learned sketches for LRA, which are computed on only one data point from the training set.

- **Exact SVD**: Randomly sample $A_i \in A_{\text{train}}$, compute $A_i = U\Sigma V^T$ and sketch as AV_m, where V_m is formed from the top m singular vectors.
- **Column sampling**: sketch as AR, where R is computed from a randomly sampled $A_i \in A_{\text{train}}$. R selects columns of A_i with probability proportional to the squared column norm and scales by its inverse.

Data sets. We used a variety of high-dimensional data sets to test the performance of our method.

- **Friends**: frames from a YouTube video of a scene from the TV show *Friends*. Each A was formed by flattening a $1920 \times 1080 \times 3$ RGB array. $A \in \mathbb{R}^{5760 \times 1080}, |A_{\text{train}}| = 400, |A_{\text{test}}| = 100.$[3]
- **Hyper:** hyperspectral images depicting outdoor scenes. $A \in \mathbb{R}^{1024 \times 768}, |A_{\text{train}}| = 400, |A_{\text{test}}| = 100.$[4]
- **Logo**: frames from a YouTube video of a logo being painted. Each A was formed by flattening a $1920 \times 1080 \times 3$ RGB array. $A \in \mathbb{R}^{5760 \times 1080}, |A_{\text{train}}| = 400, |A_{\text{test}}| = 100.$[5]

Evaluation metric. To evaluate the quality of a sketch S, we compute the difference between the objective value of the sketched solution and the optimal solution (with no sketching). That is, the values in this section's tables denote

$$\Delta_S = \mathcal{L}(S, \mathcal{A}_{\text{test}}) - \mathcal{L}^*(\mathcal{A}_{\text{test}})$$

averaged over 10 trials.

Analysis of results. For least-squares regression and LRA, our method is significantly better than random. For least-squares and LRA, our method attains improvements of around 100% and around 70% respectively over a classical sparse sketch. For k-means, "Column Sampling" dominated on two data sets. However, we note that our method was always a close second and also, more importantly, the values for k-means were only trivially different ($< 1\%$) between methods.

Ablation of greedy component In our empirical results, including the greedy optimization stage is always better than not including it (compare the "Ours" vs. "GD only" methods). For regression, LRA, and k-means, including this step offers around 30%, 40%, and $< 1\%$ improvement respectively. We should note that for k-means in general, the values don't differ much between methods.

---

[3]http://youtu.be/xmLZsEfXEgE
[4]https://github.com/gistairc/HS-SOD
[5]http://youtu.be/L5HQoFIaT4I

Table 5.1: Average errors for least-squares regression

Algorithm	Parameter	Datasets		
	m	**Friends**	**Hyper**	**Logo**
Ours	20	**0.435998**	**0.624235**	**0.194232**
	40	**0.248538**	**0.538046**	**0.160682**
SGD only	20	0.544233	0.678957	0.254736
	40	0.368762	0.571753	0.185835
Random	20	0.779231	0.822629	0.377272
	40	0.521325	0.641426	0.238863

Table 5.2: Average errors for k-means clustering

Algorithm	Parameters	Data sets		
	# clusters, m, rank k	**Friends**	**Hyper**	**Logo**
Ours	(30, 60, 30)	0.260410	0.544765	0.106176
	(20, 40, 20)	0.293407	**0.611040**	0.125092
GD only	(30, 60, 30)	0.260472	0.545206	0.106260
	(20, 40, 20)	0.293484	0.611665	0.125273
Random	(30, 60, 30)	0.260439	0.545297	0.106207
	(20, 40, 20)	0.293303	0.612209	0.125447
Exact SVD	(30, 60, 30)	0.260531	**0.544627**	0.106263
	(20, 40, 20)	0.293417	0.611300	0.125262
Column sampling	(30, 60, 30)	**0.260217**	0.545884	**0.105936**
	(20, 40, 20)	**0.293212**	0.612865	**0.124980**

Table 5.3: Average error for LRA

Algorithm	Parameters	Datasets		
	rank k, m	**Friends**	**Hyper**	**Logo**
Ours	(20, 40)	**0.899775**	**2.497674**	**0.500948**
	(30, 60)	**0.794488**	**2.492039**	**0.492886**
GD only	(20, 40)	1.048410	3.764833	0.687883
	(30, 60)	1.077225	3.748752	0.734824
Random	(20, 40)	4.072981	6.344514	2.372124
	(30, 60)	2.683610	5.390449	1.642822

REFERENCES

David Arthur and Sergei Vassilvitskii. k-means++: The advantages of careful seeding. In *Proceedings of the 18th Annual ACM SIAM Symposium on Discrete Algorithms*, pp. 1027–1035, 2007.

Haim Avron, Kenneth L Clarkson, and David P Woodruff. Sharper bounds for regularized data fitting. *arXiv preprint arXiv:1611.03225*, 2016.

Matthew Brand. Fast low-rank modifications of the thin singular value decomposition. *Linear Algebra and its Applications*, 415.1, 2006.

Moses Charikar, Kevin Chen, and Martin Farach-Colton. Finding frequent items in data streams. In *International Colloquium on Automata, Languages, and Programming*, pp. 693–703. Springer, 2002.

Kenneth L Clarkson and David P Woodruff. Numerical linear algebra in the streaming model. In *Proceedings of the forty-first annual symposium on Theory of computing (STOC)*, pp. 205–214, 2009.

Kenneth L. Clarkson and David P. Woodruff. Sketching for m-estimators: A unified approach to robust regression. In *Proceedings of the 26th Annual ACM SIAM Symposium on Discrete Algorithms*, pp. 921–939, 2014.

Kenneth L Clarkson and David P Woodruff. Low-rank approximation and regression in input sparsity time. *Journal of the ACM (JACM)*, 63(6):54, 2017.

Michael B Cohen, Sam Elder, Cameron Musco, Christopher Musco, and Madalina Persu. Dimensionality reduction for k-means clustering and low rank approximation. In *Proceedings of the forty-seventh annual ACM symposium on Theory of computing*, pp. 163–172, 2015.

Dan Feldman, Melanie Schmidt, and Christian Sohler. Turning big data into tiny data: Constant-size coresets for k-means, pca and projective clustering. In *Proceedings of the 24th annual ACM-SIAM symposium on Discrete Algorithms*, pp. 1434–1453, 2013.

Chinmay Hegde, Aswin C. Sankaranarayanan, Wotao Yin, and Richard G. Baraniuk. Numax: A convex approach for learning near-isometric linear embeddings. In *IEEE Transactions on Signal Processing*, pp. 6109–6121, 2015.

Chen-Yu Hsu, Piotr Indyk, Dina Katabi, and Ali Vakilian. Learning-based frequency estimation algorithms. *International Conference on Learning Representations*, 2019.

Piotr Indyk, Ali Vakilian, and Yang Yuan. Learning-based low-rank approximations. In *Advances in Neural Information Processing Systems*, pp. 7400–7410, 2019.

Tim Kraska, Alex Beutel, Ed H Chi, Jeffrey Dean, and Neoklis Polyzotis. The case for learned index structures. In *Proceedings of the 2018 International Conference on Management of Data*, pp. 489–504, 2018.

Stuart Lloyd. Least squares quantization in pcm. *IEEE transactions on information theory*, 28(2): 129–137, 1982.

Thodoris Lykouris and Sergei Vassilvitskii. Competitive caching with machine learned advice. In *International Conference on Machine Learning*, pp. 3302–3311, 2018.

Konstantin Makarychev, Yury Makarychev, and Ilya P. Razenshteyn. Performance of johnson-lindenstrauss transform for k-means and k-medians clustering. In *Proceedings of the 51st Annual ACM SIGACT Symposium on Theory of Computing, STOC*, pp. 1027–1038, 2019.

Xiangrui Meng and Michael W Mahoney. Low-distortion subspace embeddings in input-sparsity time and applications to robust linear regression. In *Proceedings of the forty-fifth annual ACM symposium on Theory of computing*, pp. 91–100, 2013.

Jelani Nelson and Huy L Nguyên. Osnap: Faster numerical linear algebra algorithms via sparser subspace embeddings. In *Foundations of Computer Science (FOCS), 2013 IEEE 54th Annual Symposium on*, pp. 117–126, 2013.

Manish Purohit, Zoya Svitkina, and Ravi Kumar. Improving online algorithms via ml predictions. In *Advances in Neural Information Processing Systems*, pp. 9661–9670, 2018.

Tamas Sarlos. Improved approximation algorithms for large matrices via random projections. In *47th Annual IEEE Symposium on Foundations of Computer Science (FOCS)*, pp. 143–152, 2006.

Jingdong Wang, Ting Zhang, Nicu Sebe, and Heng Tao ShenWang. A survey on learning to hash. In *IEEE Transactions on Pattern Analysis and Machine Intelligence*, pp. 769–790, 2017.

David P Woodruff. Sketching as a tool for numerical linear algebra. *Foundations and Trends® in Theoretical Computer Science*, 10(1–2):1–157, 2014.

A   APPENDIX

CORRESPONDING TO SECTION 4.1: LEAST-SQUARES REGRESSION

Definition A.1 (Subspace Embedding). *Given an $n \times d$ matrix A, a matrix S is an* affine ϵ-embedding *for (the column space of) A if for $x \in \mathbb{R}^d$, $\|SAx\|_2^2 = (1 \pm \epsilon) \|Ax\|_2^2$.*

The following result is shown in Clarkson & Woodruff (2017) and sharpened with Nelson & Nguyên (2013); Meng & Mahoney (2013).

Lemma A.2. *Given matrices A, B with n rows, a sparse embedding matrix (i.e., random CS) with $O(\mathrm{rank}(A)^2/\epsilon^2)$ rows is an affine ϵ-embedding matrix with constant probability. Moreover, the matrix product SA can be computed in $O(\mathrm{nnz}(A))$ time, where $\mathrm{nnz}(A)$ denotes the number of non-zero entries of matrix A.*

Lemma A.3 (Clarkson & Woodruff (2017); Lemma 40). *Let A be an $n \times d$ matrix and let $S \in \mathbb{R}^{O(\frac{1}{\epsilon^2}) \times n}$ be a randomly chosen sparse embedding matrix (i.e., random CS). Then with constant probability, $\|SA\|_F^2 = (1 \pm \epsilon) \|A\|_F^2$.*

Lemma A.4 (Sarlos (2006); Clarkson & Woodruff (2017)). *Given classical CountSketch $S \in \mathbb{R}^{m \times n}$,* SKETCH-REGRESSION$(A, B, S)$ *returns a $(1 + \epsilon)$-approximation in time $O(\mathrm{nnz}(A) + \mathrm{nnz}(B) + dd'm^2)$.*

Proof of **Lemma A.4.** Since S is an affine ϵ-embedding matrix of A, B, then

$$\|SAX - SB\|_F^2 = (1 \pm \epsilon) \|AX - B\|_F^2$$

Next, by the normal equations, $(SA)^+(SB)$ is a minimizer of $\min_X \|SAX - SB\|_F^2$.

To bound the runtime, note that since S is a sparse sketching matrix (i.e., random CS) we can compute SA and SB in time $O(\mathrm{nnz}(A) + \mathrm{nnz}(B))$ and reduce the problem to an instance of multiple-response regression with m rows. Then, we can solve the reduced size problem in time $O(d \cdot d' \cdot m^2)$: $O(d \cdot m^2)$ to compute $(SA)^+$ and $O(d \cdot d' \cdot m^2)$ to compute $(SA)^+(SB)$. $\qquad\square$

Proof of **Theorem 4.1.** By Lemma A.2, a random CS S_O with $O(\frac{d}{\epsilon^2})$ rows is an affine ϵ-embedding matrix of A, B with constant probability.

Next, let X_L and X_O be respectively the solutions returned by SKETCH-REGRESSION(A, B, S_L) and SKETCH-REGRESSION(A, B, S_O). By Lemma A.4, with constant probability,

$$\|AX_O - B\|_F^2 \le (1 + \epsilon) \min_X \|AX - B\|_F^2 .$$

Together with the assumption that S_L is a β-affine embedding sketching matrix over $\mathcal{A}_{\text{train}}$,

$$\min(\|AX_L - B\|_F^2, \|AX_O - B\|_F^2) \le (1 + \min(\epsilon, \beta)) \|AX - B\|_F^2 \qquad (A.1)$$

Hence, it only remains to compute the minimum of $\|AX_L - B\|_F^2$ and $\|AX_O - B\|_F^2$ efficiently. Note that it takes $\Omega(n \cdot d \cdot d')$ to compute these values. However, for our purpose it suffices to compare $(1 + \beta)$-estimates of these values and return the minimum of the estimates. To achieve this, we use two applications of Lemma A.3 with $R^\top \in \mathbb{R}^{O(\frac{1}{\beta^2}) \times d'}, S \in \mathbb{R}^{O(\frac{1}{\beta^2}) \times n}$. For any X' (in particular, both X_O and X_L), with constant probability,

$$\|S(AX' - B)R\|_F^2 = \left\|R^\top (AX' - B)^\top S^\top\right\|_F^2 = (1 \pm \beta) \|(AX' - B)\|_F^2 \qquad (A.2)$$

Let Δ_L and Δ_O respectively denote $\|S(AX_L - B)R\|_F^2$ and $\|S(AX_O - B)R\|_F^2$. By Eq. (A.2) and union bound over of X_O and X_L, with constant probability,

$$\min(\Delta_L, \Delta_O) \leq (1 + O(\beta)) \cdot \min(\|AX_L - B\|_F^2, \|AX_O - B\|_F^2)$$
$$\leq (1 + O(\min(\epsilon, \beta))) \|AX - B\|_F^2 \qquad \triangleright \text{ by Eq. (A.1)}$$

Runtime Analysis. By Lemma A.4, X_O an X_L can be computed in $O(\text{nnz}(A) + \text{nnz}(B) + d^3 d' \epsilon^{-4})$ time. Next, the time to compute Δ_L and Δ_O is

$$O(\text{nnz}(A) + \text{nnz}(XR) + \text{nnz}(B) + \frac{d}{\beta^4}) = O(\text{nnz}(A) + \text{nnz}(B) + dd' + \frac{d}{\beta^4}),$$

where X is either X_O or X_L and we use that fact that $\text{nnz}(X) \leq d \cdot d'$ (i.e., the total number of cells in X).

Thus, the total runtime of Algorithm 3 is $O(\text{nnz}(A) + \text{nnz}(B) + d^3 d' \epsilon^{-4} + d\beta^{-4})$. $\qquad\square$

Theorem A.5 (Least Squares Regression). *Suppose there exists a learned, sparse, subspace embedding matrix S_L computed over $\mathcal{A}_{\text{train}}$ with $\text{poly}(\frac{d}{\epsilon})$ rows that attains a β-approximation over $\mathcal{A}_{\text{test}}$. Then, there exists an algorithm that runs in time $O(\text{nnz}(A) + \text{poly}(d/\epsilon))$ that outputs a $(1 + \min(\beta, \epsilon))$-approximation to the least squares regression problem.*

Proof: Note that to solve $\min_{x \in \mathbb{R}^d} \|Ax - b\|_2$, given a sparse embedding matrix $S \in \mathbb{R}^{m \times n}$ for the columns of A together with the vector b, the problem can be solved within $(1 + \epsilon)$-approximation in time $\text{nnz}(A) + \text{poly}(d/\epsilon)$ (e.g., see Theorem 2.14 Woodruff (2014)).

The proof outline is similar to the proof of Theorem 4.1. First, we compute solutions $x_L, x_O \in \mathbb{R}^d$ to the given instance using respectively a learned sketching matrix S_L and a learning-free sketching algorithm. Then, we compare $\|Ax_L - b\|_2$ and $\|Ax_O - b\|_2$ and report the better. Note that since x_L, x_O are vectors, unlike the case of MRR, the naive comparison (i.e., without applying any sketching matrices) takes $\text{nnz}(A)$. Hence, the algorithm runs in time $\text{nnz}(A) + \text{poly}(d/\epsilon)$ and returns a $(1 + \min(\epsilon, \beta))$-approximate solution of the least squares regression problem.

Moreover, we can employ the best known sketching techniques for the least squares regression problem and achieve the dependence d/ϵ^2 in the running time (e.g., see Section 2.5 of Woodruff (2014)). $\qquad\square$

A.1 Corresponding to Section 4.2: Low-rank approximation

Lemma A.6. *Suppose that $S \in \mathbb{R}^{m_S \times n}$ and $R \in \mathbb{R}^{m_R \times d}$ are sparse affine ϵ-embedding matrices for $(A^\top, A)$ and $((SA)^\top, A^\top)$. Then,*

$$\min_{\text{rank-}k\ X} \left\| AR^\top X SA - A \right\|_F^2 \leq (1 + \epsilon) \|A_k - A\|_F^2$$

Proof: Consider the following multiple-response regression problem:

$$\min_{\text{rank-}k\ X} \|A_k X - A\|_F^2 . \tag{A.3}$$

Note that since $X = I_k$ is a feasible solution to Eq. (A.3), $\min_{\text{rank-}k\ X} \|A_k X - A\|_F^2 = \|A_k - A\|_F^2$. Let $S \in \mathbb{R}^{m_S \times n}$ be a sketching matrix that satisfies the condition of Lemma A.9 for $A := A_k$ and $B := A$. By the normal equations, the rank-k minimizer of $\|SA_k X - SA\|_F^2$ is $(SA_k)^+ SA$. Hence,

$$\left\| A_k (SA_k)^+ SA - A \right\|_F^2 \leq (1 + \epsilon) \|A_k - A\|_F^2 , \tag{A.4}$$

which in particular shows that a $(1 + \epsilon)$ rank-k approximation of A exists in the row space of SA. In other words,

$$\min_{\text{rank-}k\ X} \|X SA - A\|_F^2 \leq (1 + \epsilon) \|A_k - A\|_F^2 . \tag{A.5}$$

Next, let $R \in \mathbb{R}^{m_R \times d}$ be a sketching matrix that satisfies the condition of Lemma A.9 for $A := (SA)^\top$ and $B := A^\top$. Let Y denote the rank-k minimizer of $\left\| R(SA)^\top X^\top - RA^\top \right\|_F^2$. Hence,

$$\left\| (SA)^\top Y^\top - A^\top \right\|_F^2 \leq (1 + \epsilon) \min_{\text{rank-}k\ X} \|X SA - A\|_F^2 \qquad \triangleright \text{Lemma A.9}$$

$$\leq (1 + O(\epsilon)) \|A_k - A\|_F^2 \qquad \triangleright \text{Eq. (A.5)} \qquad \text{(A.6)}$$

Note that by the normal equations, again $\text{rowsp}(Y^\top) \subseteq \text{rowsp}(RA^\top)$ and we can write $Y = AR^\top Z$ where $\text{rank}(Z) = k$. Thus,

$$\min_{\text{rank-}k\ X} \left\|AR^\top X SA - A\right\|_F^2 \leq \left\|AR^\top Z SA - A\right\|_F^2$$

$$= \left\|(SA)^\top Y^\top - A^\top\right\|_F^2 \qquad \triangleright Y = AR^\top Z$$

$$\leq (1 + O(\epsilon)) \|A_k - A\|_F^2 \qquad \triangleright \text{Eq. (A.6)} \qquad \square$$

Lemma A.7 (Avron et al. (2016); Lemma 27). *For $C \in \mathbb{R}^{p \times m'}, D \in \mathbb{R}^{m \times p'}, G \in \mathbb{R}^{p \times p'}$, the following problem*

$$\min_{\text{rank-}k\ Z} \|CZD - G\|_F^2 \qquad (A.7)$$

can be solved in $O(pm'r_C + p'mr_D + pp'(r_D + r_C))$ time, where $r_C = \text{rank}(C) \leq \min\{m', p\}$ and $r_D = \text{rank}(D) \leq \min\{m, p'\}$.

Proof: Let U_C and $U_D^\top$ be orthogonal bases for $\text{colsp}(C)$ and $\text{rowsp}(D)$, respectively, so that for each Z, $CZD = U_C Z' U_D^\top$ for some Z'. Let P_C and P_D be the projection matrices onto the subspaces spanned by the rows of $C^\top$ and $D^\top$, respectively: $P_C = U_C U_C^\top$ and $P_D = U_D U_D^\top$. Then by the Pythagorean theorem,

$$\|CZD - G\|_F^2 = \left\|P_C U_C Z' U_D^\top P_D - G\right\|_F^2$$

$$= \left\|P_C U_C Z' U_D^\top P_D - P_C G P_D\right\|_F^2 + \left\|P_C G (I - P_D)\right\|_F^2 + \left\|(I - P_C)G\right\|_F^2,$$

where the first equality holds since $P_C U_C = U_C$ and $U_D^\top P_D = U_D^\top$ and the second equality follows from the Pythagorean theorem. Hence,

$$\arg\min_{\text{rank-}k\ Z} \|CZD - G\|_F^2 = \arg\min_{\text{rank-}k\ Z} \left\|P_C U_C Z U_D^\top P_D - P_C G P_D\right\|_F^2.$$

Moreover,

$$\left\|P_C U_C Z U_D^\top P_D - P_C G P_D\right\|_F^2 = \left\|U_C Z U_D^\top - U_C U_C^\top G U_D U_D^\top\right\|_F^2 = \left\|Z - U_C^\top G U_D\right\|_F^2,$$

where the first equality holds since $U_C^\top U_C = I$ and $U_D^\top U_D = I$, and the second equality holds since U_C and $U_D^\top$ are orthonormal. Hence,

$$\arg\min_{\text{rank-}k\ Z} \|CZD - G\|_F^2 = \arg\min_{\text{rank-}k\ Z} \left\|Z - U_C^\top G U_D\right\|_F^2.$$

Next, we can find $Z = [U_C^\top G U_D]_k$ by computing the SVD of $U_C^\top G U_D$.

Runtime analysis. We can compute U_C and U_D by the Gram-Schmidt process in time $O(pm'r_C + p'mr_D)$, and $U_C^\top G U_D$ in time $O(\min\{r_C p'(p + r_D), r_D p(p' + r_C)\})$. Finally, the time to compute Z (i.e., an SVD computation of $U_C^\top G U_D$) is $O(r_C r_D \cdot \min\{r_C, r_D\})$. Since $r_C \leq \min\{p, m'\}$ and $r_D \leq \min\{p', m\}$, the total runtime to minimize Z in Eq. (A.7) is $O(pm'r_C + p'mr_D + pp'(r_C + r_D))$. $\square$

Lemma A.8. *Given CS matrices $S \in \mathbb{R}^{\text{poly}(k/\epsilon) \times d}$, $R \in \mathbb{R}^{\text{poly}(k/\epsilon) \times d}$, $S_2 \in \mathbb{R}^{\frac{k^2}{\epsilon^2} \times n}$, and $R_2 \in \mathbb{R}^{\frac{k^2}{\epsilon^2} \times d}$, Algorithm 5 runs in $O(\text{nnz}(A) + (n + d)\,\text{poly}(k/\epsilon))$ time and with constant probability gives a $(1 + \epsilon)$-approximate rank-k approximation of A.*

Proof of **Lemma A.8.** It first computes $C = S_2 A R^\top, D = SAR_2^\top, G = S_2 A R_2^\top$ which can be done in time $O(\text{nnz}(A))$. As an example, we bound the time to compute $C = S_2 AR$. Note that since S_2 is a sparse sketching matrix (i.e., CountSketch), $S_2 A$ can be computed in $O(\text{nnz}(A))$ time and the number of non-zero entries in the resulting matrix is at most $\text{nnz}(A)$. Hence, since R is a sparse sketching matrix as well, C can be computed in time $O(\text{nnz}(A) + \text{nnz}(S_2 A)) = O(\text{nnz}(A))$. Then, it takes an extra $\text{poly}(k/\epsilon) \cdot \frac{k^2}{\beta^2}$ time to store C, D and G in matrix form. Next, as we showed in Lemma A.7, the time to compute Z in Algorithm 5 is $O(\frac{k^4}{\beta^4} \cdot \text{poly}(k/\epsilon))$. Finally, it takes $(n + d)\,\text{poly}(k/\epsilon)$ time to return the solution in the form of $P_{n \times k} Q_{k \times d}$. Hence, the total runtime is $O(\text{nnz}(A) + (n + d)\,\text{poly}(k/\epsilon) + \frac{k^4}{\beta^4} \cdot \text{poly}(k/\epsilon))$. The exact analysis goes through for the approximation guarantee and we omit it here. $\square$

Lemma A.9 (Avron et al. (2016); Lemma 25). *Suppose that $A \in \mathbb{R}^{n \times d}$ and $B \in \mathbb{R}^{n \times d'}$. Moreover, let S be an oblivious sparse affine ϵ-embedding matrix (i.e., a random CS) with $(\operatorname{rank}(A)^2/\epsilon^2)$ rows. Then with constant probability, $\tilde{X} = \arg\min_{\text{rank-}k\, X} \|SAX - SB\|_F^2$, satisfies*

$$\left\| A\tilde{X} - B \right\|_F^2 \leq (1+\epsilon) \min_{\text{rank-}k\, X} \|AX - B\|_F^2.$$

In other words, in $O(\operatorname{nnz}(A) + \operatorname{nnz}(B)) + (d + d')(\operatorname{rank}(A)^2/\epsilon^2)$ time, we can reduce the problem to a smaller (multi-response regression) problem with $(\operatorname{rank}(A)^2/\epsilon^2)$ rows whose optimal solution is a $(1+\epsilon)$-approximate solution to the original problem.

Proof of **Theorem 4.2.** Let S_O and R_O be CountSketch matrices of size $\operatorname{poly}(k/\epsilon) \times n$ and $\operatorname{poly}(k/\epsilon) \times d$. Note that since $\operatorname{rank}(A_k) = k$ and $\operatorname{rank}((S_O A)^\top) \leq \operatorname{poly}(k/\epsilon)$, S_O and R_O are respectively affine ϵ-embedding matrices of (A_k, A) and $((S_O A)^\top, A^\top)$. Then, by an application of Lemma A.6

$$\min_{\text{rank-}k\, X} \left\| A R_O^\top X S_O A - A \right\|_F^2 \leq (1 + O(\epsilon)) \|A_k - A\|_F^2 \tag{A.8}$$

Similarly, by the properties mentioned for S_L and R_L and an application of Lemma A.6 if $(A_k, A) \in \mathcal{D}$ and $((S_L A)^\top, A^\top) \in \mathcal{D}'$, then

$$\min_{\text{rank-}k\, X} \left\| A R_L^\top X S_L A - A \right\|_F^2 \leq (1 + O(\beta)) \|A_k - A\|_F^2 \tag{A.9}$$

Next, by applications of Lemma A.2, we multiply Eq. (A.9) from both sides by oblivious *sparse* affine β-embedding matrices (i.e., CountSketch) S_2, R_2 with $O(k^2/\beta^2)$ rows,

$$\min_{\text{rank-}k\, X} \left\| S_2 (A R_L^\top X S_L A) R_2^\top - S_2 A R_2^\top \right\|_F^2 = (1 + O(\beta)) \min_{\text{rank-}k\, X} \left\| S_2 A R_L^\top X S_L A - S_2 A \right\|_F^2 \tag{A.10}$$

where the first inequality follows since R_2 is an affine β-embedding for $(SA)^\top$ which is of rank $\operatorname{poly}(k/\epsilon)$ and the second inequality follows since S_2 is an affine β-embedding for $AR^\top$ which is of rank $\operatorname{poly}(k/\epsilon)$. By a similar argument,

$$\min_{\text{rank-}k\, X} \left\| S_2 (A R_O^\top X S_O A) R_2^\top - S_2 A R_2^\top \right\|_F^2 = (1 + O(\epsilon)) \min_{\text{rank-}k\, X} \|A_k - A\|_F^2, \tag{A.11}$$

Next, let (P_L, Q_L) and (P_O, Q_O) be respectively the rank-k approximations of A in factored form using (S_L, R_L) and (S_O, R_O) (see Algorithm 5). Then, Eq. (A.10) together with Eq. (A.11) implies that

$$\min(\|P_L Q_L - A\|_F^2, \|P_O Q_O - A\|_F^2) = (1 + O(\min(\epsilon, \beta))) \|A_k - A\|_F^2 \tag{A.12}$$

Hence, it only remains to compute the minimum of $\|P_L Q_L - A\|_F^2$ and $\|P_O Q_O - A\|_F^2$ efficiently and we proceed similarly to the proof of Theorem 4.1. We use two applications of Lemma A.3 with $R^\top \in \mathbb{R}^{O(\frac{1}{\beta^2}) \times d}, S \in \mathbb{R}^{O(\frac{1}{\beta^2}) \times n}$: $\Delta_L := \|S(P_L Q_L - A)R\|_F^2$ and $\Delta_O := \|S(P_O Q_O - A)R\|_F^2$. Hence,

$$\min(\Delta_L, \Delta_O) \leq (1 + O(\beta)) \cdot \min(\|P_L Q_L - A\|_F^2, \|P_O Q_O - A\|_F^2)$$
$$\leq (1 + O(\min(\epsilon, \beta))) \|A_k - A\|_F^2 \qquad \rhd \text{ by Eq. (A.12)}$$

Runtime analysis. By Lemma A.8, Algorithm 5 computes P_L, Q_L and P_O, Q_O in $O(\operatorname{nnz}(A) + (n + d) \operatorname{poly}(\frac{k}{\epsilon}) + (\frac{k^4}{\beta^4}) \cdot \operatorname{poly}(\frac{k}{\epsilon}))$.

Next, it takes $O(\operatorname{nnz}(A) + (n + d) \cdot k + \frac{k}{\beta^4})$ to compute Δ_L and Δ_O. As an example, we bound the amount of time required to compute $SP_L Q_L R - SAR$ corresponding to Δ_L. Since S and R are sparse sketching matrices, $SP_L, Q_L R$ and SAR can be computed in $\operatorname{nnz}(SP_L) + \operatorname{nnz}(Q_L R) + \operatorname{nnz}(A)$. Since SP_L and $Q_L R$ are respectively of size $\frac{1}{\beta^2} \times k$ and $k \times \frac{1}{\beta^2}$, in total it takes $O(\operatorname{nnz}(A) + \frac{k}{\beta^2})$ to compute these three matrices. Then, we can compute $SP_L Q_L R$ and $\|SP_L Q_L R S A R\|_F$ in time $O(\frac{k}{\beta^4})$.

Hence, the total runtime of Algorithm 5 is $O(\operatorname{nnz}(A) + (n + d) \cdot \operatorname{poly}(\frac{k}{\epsilon}) + (\frac{k^4}{\beta^4}) \cdot \operatorname{poly}(\frac{k}{\epsilon}))$. $\qquad \square$

A.2 Corresponding to Section 4.3: k-means

We restate notation and the main result below for ease of reference.

Notation. We define A_m as the optimal m-rank approximation of A formed by truncated SVD: $A_m = U_m \Sigma_m V_m^\top$.

Given a matrix U with orthogonal columns, let $\pi_U(A) = AUU^\top$, which is the projection of the rows of A onto $col(U)$. Let C_U be the optimal k-means partition of $\pi_U(A)$. Further, we let $\mu_{C_{U,i}}$ denote the i-th cluster's center in the optimal k-means clustering on $\pi_U(A)$.

We denote $\text{dist}^2(A, \mu)$ as the k-means loss given cluster centers (and their corresponding partition):

$$\text{dist}^2(A, \mu) = \sum_{i \in [k]} \sum_{j \in C_i} \|A_j - \mu_i\|_2^2$$

Likewise, $\text{cost}(C)$ is the k-means loss given a partition:

$$\text{cost}(C) = \sum_{i \in [k]} \min_{\mu_i} \sum_{j \in C_i} \|A_j - \mu_i\|_2^2$$

Definition A.10 (Projection-cost preserving sketch). *$\tilde{A}$ is a projection-cost preserving sketch of A if for any low rank projection matrix P and c not dependent on P:*

$$(1 - \epsilon)\|A - PA\|_F^2 \leq \left\|\tilde{A} - P\tilde{A}\right\|_F^2 + c \leq (1 + \epsilon)\|A - PA\|_F^2$$

Theorem (4.4: Sketch monotonicity property for k-means). *Assume we have $A \in \mathbb{R}^{n \times d}$. We also have random CountSketch $S \in \mathbb{R}^{O(\text{poly}(k/\epsilon)) \times n}$ and define $U \in \mathbb{R}^{d \times O(\text{poly}(k/\epsilon))}$ with orthogonal columns such that $\text{colsp}(U) = \text{rowsp}(SA)$. Then, any extension of S to S' (for example, concatenation with a learned CountSketch S_L) yields a better approximate k-means approximation. Specifically, define W with orthogonal columns such that $col(W) = row(S'A)$. Let C^* denote the optimal partition of A, C_U denote the optimal partition of $\pi_U(A)$, and C_W denote the optimal partition of $\pi_W(A)$. Then*

$$\text{cost}(C_W) \leq (1 + O(\epsilon))\text{cost}(C_U) \leq (1 + O(\epsilon))\text{cost}(C^*)$$

Proof:

$$\text{cost}(C_W) = \sum_{i \in [k]} \min_{\mu_i} \sum_{j \in C_{W,i}} \|A_j - \mu_i\|^2$$

$$\leq \sum_{i \in [k]} \sum_{j \in C_{W,i}} \left\|A_j - \mu_{C_{W,i}}\right\|^2$$

$$= \sum_{i \in [k]} \sum_{j \in C_{W,i}} \left\|A_j - \pi_W(A_j)\right\|^2 + \left\|\pi_W(A_j) - \mu_{C_{W,i}}\right\|^2 \quad \text{(A.13)}$$

$$\leq \sum_{i \in [k]} \sum_{j \in C_{U,i}} \left\|A_j - \pi_W(A_j)\right\|^2 + \left\|\pi_W(A_j) - \mu_{C_{U,i}}\right\|^2 \quad \text{(A.14)}$$

$$= \sum_{i \in [k]} \sum_{j \in C_{U,i}} \left\|A_j - \mu_{C_{U,i}}\right\|^2 \quad \text{(A.15)}$$

$$\leq (1 + \epsilon) \sum_{i \in k} \min_{\mu_i} \sum_{j \in C_{U,i}} \|A_j - \mu_i\|^2 \quad \text{(A.16)}$$

$$= (1 + \epsilon)\text{cost}(C_U)$$

$$\leq (1 + O(\epsilon))\text{cost}(C^*) \qquad \qquad \square$$

(A.13): $\mu_{C_W} \in \text{colsp}(W)$ so we can apply the Pythagorean Theorem.

(A.14): (μ_{C_W}, C_W) is an optimal k-means clustering of the projected points $\pi_W(A)$.

(A.15): $\mu_{C_U} \in \text{colsp}(U) \subset \text{colsp}(W)$, so we can apply the Pythagorean Theorem.

(A.16): We apply Corollary A.14.

Remark A.11. Our result shows that the "sketch monotonicity" property holds for sketching matrices that provide strong coresets for k-means clustering. Besides strong coresets, an alternate approach to showing that the clustering objective is approximately preserved on sketched inputs is to show a weaker property: the clustering cost is preserved for *all possible partitions* of the points into k groups Makarychev et al. (2019). While the dimension reduction mappings satisfying strong coresets require $\text{poly}(k/\epsilon)$ dimensions, Makarychev et al. (2019) shows that $O(\log k/\epsilon^2)$ dimensions suffice to satisfy this "partition" guarantee. An interesting question for further research is if the sketch monotonicity guarantee also applies to the construction of Makarychev et al. (2019).

Corollary A.12. *Assume we have* $A \in \mathbb{R}^{n \times d}$, $j \in \mathbb{Z}^+$, $\epsilon > 0$. *Define* $m = \min(O(\text{poly}(j/\epsilon)), d)$. *Let* $\tilde{A}_m$ *be a* $(1 + \epsilon)$-*approximation to* A_m *of the form* $\tilde{A}_m = AVV^\top$ *where* $SA = U\Sigma V^\top$ *for CountSketch* $S \in \mathbb{R}^{m \times n}$. *Let* $X \in \mathbb{R}^{d \times j}$ *be a matrix whose columns are orthonormal, and let* $Y \in \mathbb{R}^{d \times (d-j)}$ *be a matrix with orthonormal columns that spans the orthogonal complement of* $colsp(X)$. *Then*

$$\left\| AXX^\top - \tilde{A}_m XX^\top \right\|_F^2 \le \epsilon \cdot \|AY\|_F^2.$$

Proof:

$$\left\| AXX^\top - \tilde{A}_m XX^\top \right\|_F^2 = \left\| A(I - VV^\top)XX^\top \right\|_F^2$$

$$\le j \left\| A(I - VV^\top)XX^\top \right\|_2^2 \tag{A.17}$$

$$\le j \left\| A(I - VV^\top) \right\|_2^2 \tag{A.18}$$

$$\le j \cdot O(\frac{\epsilon}{j}) \|A - A_j\|_F^2 \tag{A.19}$$

$$= O(\epsilon) \sum_{i=j}^{\min(n,d)} \sigma_i^2 \tag{A.20}$$

$$\le O(\epsilon) \|AY\|_F^2 \tag{A.21}$$

$$\square$$

(A.17) Note that $\text{rank}(X) = j$, so $\text{rank}(A(I - VV^\top)XX^\top) = j$. We use this fact to bound the Frobenius norm by the operator norm.
(A.18) Using the fact that $XX^\top$ is a projection.
(A.19) Using Lemma 18 from Cohen et al. (2015), where A_j is the optimal rank-j approximation to A. We can apply this lemma because CountSketch is one of the eligible types of random projection matrices.
(A.20) Letting σ_i be the singular values of A.
(A.21) $\sum_{i=j}^{\min(n,d)} \sigma_i^2 = \min_Y \|AY\|_F^2$ for $Y \in \mathbb{R}^{d \times (d-j)}$ with orthonormal columns.

Theorem A.13. *Assume we have* $A \in \mathbb{R}^{n \times d}$, $j \in \mathbb{Z}^+$, $\epsilon \in (0, 1]$. *Define* $m = \min(O(\text{poly}(j/\epsilon)), d)$. *Let* $\tilde{A}_m$ *be a* $(1 + \epsilon)$-*approximation to* A_m *of the form* $\tilde{A}_m = AVV^\top$ *where* $SA = U\Sigma V^\top$ *for CountSketch* $S \in \mathbb{R}^{m \times n}$. *Then, for any non-empty set* μ *contained in a* j-*dimensional subspace, we have:*

$$\left| \text{dist}^2(\tilde{A}_m, \mu) + \left\| \tilde{A}_m - A \right\|_F^2 - \text{dist}^2(A, \mu) \right| \le \epsilon \, \text{dist}^2(A, \mu)$$

Proof: We follow the proof of Theorem 22 in Feldman et al. (2013), but substitute different analyses in place of Corollaries 16 and 20. The result of Feldman et al. (2013) involves the *best* rank-m approximation of A, A_m; we will show it for the *approximate* rank-m approximation, $\tilde{A}_m$.

Define $X \in \mathbb{R}^{d \times j}$ with orthonormal columns such that $colsp(X) = \text{span}(\mu)$. Likewise, define $Y \in \mathbb{R}^{d \times (d-j)}$ with orthonormal columns such that $colsp(Y) = \text{span}(\mu)^\perp$. By the Pythagorean theorem:

$$\text{dist}^2(\tilde{A}_m, \mu) = \|\tilde{A}_m Y\|_F^2 + \text{dist}^2(\tilde{A}_m XX^T, \mu)$$

and

$$\text{dist}^2(A, \mu) = \|AY\|_F^2 + \text{dist}^2(AXX^T, \mu). \tag{A.22}$$

Hence,

$$\left| \left(\operatorname{dist}^2(\tilde{A}_m, \mu) + \left\| A - \tilde{A}_m \right\|_F^2 \right) - \operatorname{dist}^2(A, \mu) \right|$$

$$= \left| \| \tilde{A}_m Y \|_F^2 + \operatorname{dist}^2(\tilde{A}_m X X^T, \mu) + \left\| A - \tilde{A}_m \right\|_F^2 - \left(\| A Y \|_F^2 + \operatorname{dist}^2(A X X^T, \mu) \right) \right|$$

$$\leq \left| \| \tilde{A}_m Y \|_F^2 + \| A - \tilde{A}_m \|_F^2 - \| A Y \|_F^2 \right| + \left| \operatorname{dist}^2(\tilde{A}_m X X^T, \mu) - \operatorname{dist}^2(A X X^T, \mu) \right| \quad \text{(A.23)}$$

$$\leq \frac{\varepsilon^2}{8} \cdot \| A Y \|_F^2 + \left| \operatorname{dist}^2(\tilde{A}_m X X^T, \mu) - \operatorname{dist}^2(A X X^T, \mu) \right| \quad \text{(A.24)}$$

$$\leq \frac{\varepsilon^2}{8} \cdot \operatorname{dist}^2(A, \mu) + \left| \operatorname{dist}^2(\tilde{A}_m X X^T, \mu) - \operatorname{dist}^2(A X X^T, \mu) \right| \quad \triangleright \text{ Used (A.22)} \quad \text{(A.25)}$$

(A.23) Triangle inequality.
(A.24) Take ϵ in Theorem 16 from Cohen et al. (2015) as $\epsilon^2/8$. This theorem implies that $\tilde{A}_m$ is a projection-cost preserving sketch with the c term as $\left\| A - \tilde{A}_m \right\|_F^2$. Specifically, it says AV is a project-cost preserving sketch, which means $\tilde{A}_m = AVV^\top$ is too: V has orthonormal columns so $\|(I - P)AV\|_F^2 = \left\| (I - P)AVV^\top \right\|_F^2$.

By Corollary A.12,

$$\left\| \tilde{A}_m X X^T - A X X^T \right\|_F^2 \leq \frac{\epsilon^2}{8} \cdot \| A Y \|_F^2.$$

Since $\mu \in \operatorname{rowsp}(X)$, we have $\| A Y \|_F^2 \leq \operatorname{dist}^2(A, \mu)$. Using Corollary 21 from Feldman et al. (2013) while taking ϵ as $\epsilon/4$, A as $\tilde{A}_m X X^T$, and B as $A X X^T$ yields

$$| \operatorname{dist}^2(\tilde{A}_m X X^T, \mu) - \operatorname{dist}^2(A X X^T, \mu) | \leq \frac{\epsilon}{4} \cdot \operatorname{dist}^2(A X X^T, \mu) + (1 + \frac{4}{\epsilon}) \cdot \left\| \tilde{A}_m X X^T - A X X^T \right\|_F^2$$

By A.22, $\operatorname{dist}^2(A X X^T, \mu) \leq \operatorname{dist}^2(A, \mu)$. Finally, we combining the last two inequalities with (A.25):

$$\left| \left(\operatorname{dist}^2(\tilde{A}_m, \mu) + \left\| A - \tilde{A}_m \right\|_F^2 \right) - \operatorname{dist}^2(A, \mu) \right|$$

$$\leq \frac{\varepsilon^2}{8} \cdot \operatorname{dist}^2(A, \mu) + \frac{\epsilon}{4} \cdot \operatorname{dist}^2(A, \mu) + \frac{\epsilon^2}{8} \cdot (1 + \frac{4}{\epsilon}) \cdot \operatorname{dist}^2(A, \mu)$$

$$\leq \epsilon \cdot \operatorname{dist}^2(A, \mu),$$

where in the last inequality we used the assumption $\epsilon \leq 1$. $\qquad \square$

Corollary A.14. *Assume we have $A \in \mathbb{R}^{n \times d}$ and CountSketch $S \in \mathbb{R}^{O(\operatorname{poly}(k/\epsilon)) \times n}$. Then, define $U \in \mathbb{R}^{d \times O(\operatorname{poly}(k/\epsilon))}$ with orthogonal columns spanning $\operatorname{row}(SA)$. Also define $A^U = \pi_U(A)$ and μ_U as the set of optimal cluster centers found on A^U. Now, assume $\epsilon \in (0, 1/3]$. Then, μ_U is a $(1 + \epsilon)$-approximation to the optimal k-means clustering of A. That is, defining μ_U^* as the cluster centers which minimize the cost of partition C_U on A, we have:*

$$\operatorname{dist}^2(A, \mu_U) \leq (1 + \epsilon) \operatorname{dist}^2(A, \mu_U^*)$$

Proof: By using $\frac{\epsilon}{3}$ in Theorem A.13 with j as k,

$$\left| \operatorname{dist}^2(A^U, \mu_U) + \left\| A - A^U \right\|_F^2 - \operatorname{dist}^2(A, \mu_U) \right| \leq \frac{\epsilon}{3} \operatorname{dist}^2(A, \mu_U)$$

which implies that

$$(1 - \frac{\epsilon}{3}) \operatorname{dist}^2(A, \mu_U) \leq \operatorname{dist}^2(A^U, \mu_U) + \left\| A - A^U \right\|_F^2 \quad \text{(A.26)}$$

Likewise, by Theorem A.13 on A^U and μ_U^* (and taking j as k),

$$\left| \mathrm{dist}^2(A^U, \mu_U^*) + \left\| A - A^U \right\|_F^2 - \mathrm{dist}^2(A, \mu_U^*) \right| \leq \frac{\epsilon}{3} \mathrm{dist}^2(A, \mu_U^*)$$

which implies that

$$\mathrm{dist}^2(A^U, \mu_U^*) + \left\| A - A^U \right\|_F^2 \leq (1 + \frac{\epsilon}{3}) \mathrm{dist}^2(A, \mu_U^*) \tag{A.27}$$

By (A.26) and (A.27) together, we have:

$$(1 - \frac{\epsilon}{3}) \mathrm{dist}^2(A, \mu_U) \leq \mathrm{dist}^2(A^U, \mu_U) + \left\| A - A^U \right\|_F^2$$
$$\leq \mathrm{dist}^2(A^U, \mu_U^*) + \left\| A - A^U \right\|_F^2$$
$$\leq (1 + \frac{\epsilon}{3}) \mathrm{dist}^2(A, \mu_U^*)$$

Now, $\frac{1+\epsilon/3}{1-\epsilon/3} \leq 1 + \epsilon$, so we have $\mathrm{dist}^2(A, \mu_U) \leq (1 + \epsilon) \mathrm{dist}^2(A, \mu_U^*)$. □

B SPECTRAL NORM GUARANTEE FOR ZIPFIAN MATRICES

In this section, we show that if the singular values of the input matrix A follow a Zipfian distribution (i.e., $\sigma_i \propto i^{-\alpha}$ for a constant α), we can find a $(1 + \epsilon)$ rank-k approximation of A with respect to the *spectral* norm. A key theorem in this section is the following.

Theorem B.1 (Cohen et al. (2015), Theorem 27). *Given an input matrix $A \in \mathbb{R}^{n \times d}$, there exists an algorithm that runs in $O(\mathrm{nnz}(A) + (n+d) \mathrm{poly}(k/\epsilon))$ and returns a projection matrix $P = QQ^\top$ such that with constant probability the following holds:*

$$\|AP - A\|_2^2 \leq (1 + \epsilon) \|A - A_k\|_2^2 + O(\frac{\epsilon}{k}) \|A - A_k\|_F^2 \tag{B.1}$$

Next, we prove the main claim in this section. There are various ways to prove this, using, for example, a bound on the *stable rank* of A; we give the following short proof for completeness.

Theorem B.2. *Given a matrix $A \in \mathbb{R}^{n \times d}$ whose singular values follow a Zipfian distribution (i.e., $\sigma_i \propto i^{-\alpha}$) with a constant $\alpha \geq 1/2$, there exists an algorithm that computes a* rank-k *matrix B (in factored form) such that $\|A - B\|_2^2 \leq (1 + \epsilon) \|A - A_k\|_2^2$.*

Proof: Note that since the singular values of A follow a Zipfian distribution with parameter α, for any value of k,

$$\|A - A_k\|_F^2 = \sum_{i=k+1}^{\mathrm{rank}(A)} \sigma_i^2 = C \cdot \sum_{i=k+1}^{\mathrm{rank}(A)} i^{-2\alpha} \qquad \triangleright \sigma_i = \sqrt{C}/i^\alpha$$
$$\leq C \cdot \int_k^{\mathrm{rank}(A)} x^{-2\alpha} \, dx$$
$$\leq k \cdot \frac{1}{2\alpha - 1} \cdot (1 + \frac{1}{k})^{2\alpha} \cdot C/(k+1)^{2\alpha}$$
$$= O(k \cdot \sigma_{k+1}^2)$$
$$= O(k \cdot \|A - A_k\|_2^2) \tag{B.2}$$

By an application of Theorem B.1, we can compute a matrix B in a factored form in time $O(\mathrm{nnz}(A) + (n+d) \mathrm{poly}(k/\epsilon))$ such that with constant probability,

$$\|B - A\|_2^2 \leq (1 + \epsilon) \|A - A_k\|_2^2 + O(\frac{\epsilon}{k}) \|A - A_k\|_F^2 \qquad \triangleright \text{By Eq. (B.1)}$$
$$\leq (1 + O(\epsilon)) \|A - A_k\|_2^2 \qquad \triangleright \text{Eq. (B.2)} \qquad □$$

C GREEDY INITIALIZATION

In this section, we analyze the performance of the greedy algorithm on the two distributions mentioned in Theorem 4.3.

Preliminaries and Notation. Left-multiplying A by CountSketch $S \in \mathbb{R}^{m \times n}$ is equivalent to hashing the rows of A to m bins with coefficients in $\{-1, 1\}$. The greedy algorithm proceeds through the rows of A (in some order) and decides which bin to hash to, denoting this by adding an entry to S. We will denote the bins as b_i and their summed contents as w_i.

C.1 SPIKED COVARIANCE MODEL WITH SPARSE LEFT SINGULAR VECTORS.

To recap, every matrix $A \in \mathbb{R}^{n \times d}$ from the distribution $\mathcal{A}_{sp}(s, \ell)$ has $s < k$ "heavy" rows $(A_{r_1}, \cdots, A_{r_s})$ of norm $\ell > 1$. The indices of the heavy rows can be arbitrary, but must be the same for all members of the distribution and are unknown to the algorithm. The remaining rows (called "light" rows) have unit norm.

In other words: let $\mathcal{R} = \{r_1, \ldots, r_s\}$. For all rows $A_i, i \in [n]$:

$$A_i = \begin{cases} \ell \cdot v_i & \text{if } i \in \mathcal{R} \\ v_i & \text{o.w.} \end{cases}$$

where v_i is a uniformly random unit vector.

We also assume that $S_r, S_g \in \mathbb{R}^{k \times n}$ and non-increasing row norm ordering for the greedy algorithm.

Proof sketch. First, we show that the greedy algorithm using a non-increasing row norm ordering will isolate heavy rows (i.e., each is alone in a bin). Then, we conclude by showing that this yields a better k-rank approximation error when d is sufficiently large compared to n. We begin with some preliminary observations that will be of use later.

It is well known that a set of uniformly random vectors are ϵ-*almost orthogonal* (i.e., the magnitudes of their pairwise inner products are at most ϵ).

Observation C.1. *Let $v_1, \cdots, v_n \in \mathbb{R}^d$ be a set of random unit vectors. Then with high probability $|\langle v_i, v_j \rangle| \leq 2\sqrt{\frac{\log n}{d}}, \forall\, i < j \leq n$.*

We define $\bar{\epsilon} = 2\sqrt{\frac{\log n}{d}}$.

Observation C.2. *Let $u_1, \cdots, u_t$ be a set of vectors such that for each pair of $i < j \leq t$, $|\langle \frac{u_i}{\|u_i\|}, \frac{u_j}{\|u_j\|} \rangle| \leq \epsilon$, and $g_i, \cdots, g_j \in \{-1, 1\}$. Then,*

$$\sum_{i=1}^{t} \|u_i\|_2^2 - 2\epsilon \sum_{i<j\leq t} \|u_i\|_2 \|u_j\|_2 \leq \left\| \sum_{i=1}^{t} g_i u_i \right\|_2^2 \leq \sum_{i=1}^{t} \|u_i\|_2^2 + 2\epsilon \sum_{i<j\leq t} \|u_i\|_2 \|u_j\|_2 \quad \text{(C.1)}$$

Next, a straightforward consequence of ϵ-almost orthogonality is that we can find a QR-factorization of the matrix of such vectors where R (an upper diagonal matrix) has diagonal entries close to 1 and entries above the diagonal are close to 0.

Lemma C.3. *Let $u_1, \cdots, u_t \in \mathbb{R}^d$ be a set of unit vectors such that for any pair of $i < j \leq t$, $|\langle u_i, u_j \rangle| \leq \epsilon$ where $\epsilon = O(t^{-2})$. There exists an orthonormal basis $e_1, \cdots, e_t$ for the subspace spanned by $u_1, \cdots, u_t$ such that for each $i \leq t$, $u_i = \sum_{j=1}^{i} a_{i,j} e_j$ where $a_{i,i}^2 \geq 1 - \sum_{j=1}^{i-1} j^2 \cdot \epsilon^2$ and for each $j < i$, $a_{i,j}^2 \leq j^2 \epsilon^2$.*

Proof: We follow the Gram-Schmidt process to construct the orthonormal basis $e_1, \cdots, e_t$ of the space spanned by $u_1, \cdots, u_t$. by first setting $e_1 = u_1$ and then processing $u_2, \cdots, u_t$, one by one.

The proof is by induction. We show that once the first j vectors $u_1, \cdots, u_j$ are processed the statement of the lemma holds for these vectors. Note that the base case of the induction trivially holds as $u_1 = e_1$. Next, suppose that the induction hypothesis holds for the first ℓ vectors $u_1, \cdots, u_\ell$.

Claim C.4. *For each $j \le \ell$, $a_{\ell+1,j}^2 \le j^2\epsilon^2$.*

Proof: The proof of the claim is itself by induction. Note that, for $j = 1$ and using the fact that $|\langle u_1, u_{\ell+1}\rangle| \le \epsilon$, the statement holds and $a_{\ell+1,1}^2 \le \epsilon^2$. Next, suppose that the statement holds for all $j \le i < \ell$, then by $|\langle u_{i+1}, u_{\ell+1}\rangle| \le \epsilon$,

$$|a_{\ell+1,i+1}| \le (|\langle u_{\ell+1}, u_{i+1}| + \sum_{j=1}^{i} |a_{\ell+1,j}| \cdot |a_{i+1,j}|)/|a_{i+1,i+1}|$$

$$\le (\epsilon + \sum_{j=1}^{i} j^2\epsilon^2)/|a_{i+1,i+1}| \quad \triangleright \text{ by induction hypothesis on } a_{\ell+1,j} \text{ for } j \le i$$

$$\le (\epsilon + \sum_{j=1}^{i} j^2\epsilon^2)/(1 - \sum_{j=1}^{i} j^2 \cdot \epsilon^2)^{1/2} \quad \triangleright \text{ by induction hypothesis on } a_{i+1,i+1}$$

$$\le (\epsilon + \sum_{j=1}^{i} j^2\epsilon^2) \cdot (1 - \sum_{j=1}^{i} j^2 \cdot \epsilon^2)^{1/2} \cdot (1 + 2 \cdot \sum_{j=1}^{i} j^2\epsilon^2)$$

$$\le (\epsilon + \sum_{j=1}^{i} j^2\epsilon^2) \cdot (1 + 2 \cdot \sum_{j=1}^{i} j^2\epsilon^2)$$

$$\le \epsilon((\sum_{j=1}^{i} j^2\epsilon) \cdot (1 + 4\epsilon \cdot \sum_{j=1}^{i} j^2\epsilon) + 1)$$

$$\le \epsilon(i + 1) \quad \triangleright \text{ by } \epsilon = O(t^{-2}) \qquad \qquad \square$$

Finally, since $\|u_{\ell+1}\|_2^2 = 1$, $a_{\ell+1,\ell+1}^2 \ge 1 - \sum_{j=1}^{\ell} j^2\epsilon^2$. $\qquad \square$

Corollary C.5. *Suppose that $\bar{\epsilon} = O(t^{-2})$. There exists an orthonormal basis $e_1, \cdots, e_t$ for the space spanned by the randomly picked vectors $v_1, \cdots, v_t$, of unit norm, so that for each i, $v_i = \sum_{j=1}^{i} a_{i,j}e_j$ where $a_{i,i}^2 \ge 1 - \sum_{j=1}^{i-1} j^2 \cdot \bar{\epsilon}^2$ and for each $j < i$, $a_{i,j}^2 \le j^2 \cdot \bar{\epsilon}^2$.*

Proof: The proof follows from Lemma C.3 and the fact that the set of vectors $v_1, \cdots, v_t$ are $\bar{\epsilon}$-almost orthogonal (by Observation C.1). $\qquad \square$

The first main step is to show that the greedy algorithm (with non-increasing row norm ordering) will isolate rows into their own bins until all bins are filled. In particular, this means that the heavy rows (the first to be processed) will all be isolated.

We note that because we set $\text{rank}(SA) = k$, the k-rank approximation cost is the simplified expression $\|AVV^\top - A\|_F^2$, where $U\Sigma V^\top = SA$, rather than $\|[AV]_k V^\top - A\|_F^2$. This is just the projection cost onto $row(SA)$. Also, we observe that minimizing this projection cost is the same as maximizing the sum of squared projection coefficients:

$$\min_S \|A - AVV^\top\|_F^2 \sim \min_S \sum_{i \in [n]} \|A_i - (\langle A_i, v_1\rangle v_1 + \ldots + \langle A_i, v_k\rangle v_k)\|_2^2$$

$$\sim \min_S \sum_{i \in [n]} (\|A_i\|_2^2 - \sum_{j \in [k]} \langle A_i, v_j\rangle^2)$$

$$\sim \max_S \sum_{i \in [n]} \sum_{j \in [k]} \langle A_i, v_j\rangle^2$$

In the following sections, we will prove that our greedy algorithm makes certain choices by showing that these choices maximize the sum of squared projection coefficients.

Lemma C.6. *For any matrix A or batch of matrices $\mathcal{A}$, at the end of iteration k, the learned CountSketch matrix S maps each row to an isolated bin. In particular, heavy rows are mapped to isolated bins.*

Proof: For any iteration $i \leq k$, we consider the choice of assigning A_i to an empty bin versus an occupied bin. Without loss of generality, let this occupied bin be b_{i-1}, which already contains A_{i-1}.

We consider the difference in cost for empty versus occupied. We will do this cost comparison for A_j with $j \leq i-2$, $j \geq i+1$, and finally, $j \in \{i-1, i\}$.

First, we let $\{e_1, \ldots, e_i\}$ be an orthonormal basis for $\{A_1, \ldots, A_i\}$ such that for each $r \leq i$, $A_r = \sum_{j=1}^{r} a_{r,j} e_j$ where $a_{r,r} > 0$. This exists by Lemma C.3. Let $\{e_1, \ldots, e_{i-2}, \bar{e}\}$ be an orthonormal basis for $\{A_1, \ldots, A_{i+2}, A_{i-1} \pm A_i\}$. Now, $\bar{e} = c_0 e_{i-1} + c_1 e_i$ for some c_0, c_1 because $(A_{i-1} \pm A_i) - \text{proj}_{\{e_1, \ldots, e_{i-2}\}}(A_{i-1} \pm A_i) \in \text{span}(e_{i-1}, e_i)$. We note that $c_0^2 + c_1^2 = 1$ because we let $\bar{e}$ be a unit vector. We can find c_0, c_1 to be:

$$c_0 = \frac{a_{i-1,i-1} + a_{i,i-1}}{\sqrt{(a_{i-1,i-1} + a_{i,i-1})^2 + a_{i,i}^2}}, \quad c_1 = \frac{a_{i,i}}{\sqrt{(a_{i-1,i-1} + a_{i,i-1})^2 + a_{i,i}^2}}$$

1. $j \leq i-2$: The cost is zero for both cases because $A_j \in \text{span}(\{e_1, \ldots, e_{i-2}\})$.

2. $j \geq i+1$: We compare the rewards (sum of squared projection coefficients) and find that $\{e_1, \ldots, e_{i-2}, \bar{e}\}$ is no better than $\{e_1, \ldots, e_i\}$.

$$\begin{aligned}
\langle A_j, \bar{e} \rangle^2 &= (c_0 \langle A_j, e_{i-1} \rangle + c_1 \langle A_j, e_i \rangle)^2 \\
&\leq (c_1^2 + c_0^2)(\langle A_j, e_{i-1} \rangle^2 + \langle A_j, e_i \rangle^2) \qquad \triangleright \text{ Cauchy-Schwarz inequality} \\
&= \langle A_j, e_{i-1} \rangle^2 + \langle A_j, e_i \rangle^2
\end{aligned}$$

3. $j \in \{i-1, i\}$: We compute the sum of squared projection coefficients of A_{i-1} and A_i onto $\bar{e}$:

$$\begin{aligned}
&(\frac{1}{(a_{i-1,i-1} + a_{i,i-1})^2 + a_{i,i}^2}) \cdot (a_{i-1,i-1}^2 (a_{i-1,i-1} + a_{i,i-1})^2 \\
&+ (a_{i,i-1}(a_{i-1,i-1} + a_{i,i-1}) + a_{i,i} a_{i,i})^2) \\
=&(\frac{1}{(a_{i-1,i-1} + a_{i,i-1})^2 + a_{i,i}^2}) \cdot ((a_{i-1,i-1} + a_{i,i-1})^2 (a_{i-1,i-1}^2 && \text{(C.2)} \\
&+ a_{i,i-1}^2) + a_{i,i}^4 + 2 a_{i,i-1} a_{i,i}^2 (a_{i-1,i-1} + a_{i,i-1})) && \text{(C.3)}
\end{aligned}$$

On the other hand, the sum of squared projection coefficients of A_{i-1} and A_i onto $e_{i-1} \cup e_i$ is:

$$(\frac{(a_{i-1,i-1} + a_{i,i-1})^2 + a_{i,i}^2}{(a_{i-1,i-1} + a_{i,i-1})^2 + a_{i,i}^2}) \cdot (a_{i-1,i-1}^2 + a_{i,i-1}^2 + a_{i,i}^2) \qquad \text{(C.4)}$$

Hence, the difference between the sum of squared projections of A_{i-1} and A_i onto $\bar{e}$ and $e_{i-1} \cup e_i$ is ((C.4) - (C.3))

$$\begin{aligned}
&\frac{a_{i,i}^2((a_{i-1,i-1} + a_{i,i-1})^2 + a_{i-1,i-1}^2 + a_{i,i-1}^2 - 2a_{i,i-1}(a_{i-1,i-1} + a_{i,i-1}))}{((a_{i-1,i-1} + a_{i,i-1})^2 + a_{i,i}^2)} \\
=&\frac{2a_{i,i}^2 a_{i-1,i-1}^2}{((a_{i-1,i-1} + a_{i,i-1})^2 + a_{i,i}^2)} > 0
\end{aligned}$$

Thus, we find that $\{e_1, \ldots, e_i\}$ is a strictly better basis than $\{e_1, \ldots, e_{i-2}, \bar{e}\}$. This means the greedy algorithm will choose to place A_i in an empty bin. $\qquad \square$

Next, we show that none of the rows left to be processed (all light rows) will be assigned to the same bin as a heavy row. The main proof idea is to compare the cost of "colliding" with a heavy row to the cost of "avoiding" the heavy rows. Specifically, we compare the *decrease* (before and after bin assignment of a light row) in the sum of squared projection coefficients, lower-bounding it in the former case and upper-bounding it in the latter.

We introduce some results that will be used in Lemma C.10.

Claim C.7. *Let $A_{k+r}, r \in [1, \ldots, n-k]$ be a light row not yet processed by the greedy algorithm. Let $\{e_1, \ldots, e_k\}$ be the Gram-Schmidt basis for the current $\{w_1, \ldots, w_k\}$. Let $\beta = O(n^{-1}k^{-3})$ upper bound the inner products of normalized $A_{k+r}, w_1, \ldots, w_k$. Then, for any bin i, $\langle e_i, A_{k+r} \rangle^2 \leq \beta^2 \cdot k^2$.*

Proof: This is a straightforward application of Lemma C.3. From that, we have $\langle A_{k+r}, e_i \rangle^2 \leq i^2 \beta^2$, for $i \in [1, \ldots, k]$, which means $\langle A_{k+r}, e_i \rangle^2 \leq k^2 \beta^2$. □

Claim C.8. *Let A_{k+r} be a light row that has been processed by the greedy algorithm. Let $\{e_1, \ldots, e_k\}$ be the Gram-Schmidt basis for the current $\{w_1, \ldots, w_k\}$. If A_{k+r} is assigned to bin b_{k-1} (w.l.o.g.), the squared projection coefficient of A_{k+r} onto $e_i, i \neq k-1$ is at most $4\beta^2 \cdot k^2$, where $\beta = O(n^{-1}k^{-3})$ upper bounds the inner products of normalized $A_{k+r}, w_1, \cdots, w_k$.*

Proof: Without loss of generality, it suffices to bound the squared projection of A_{k+r} onto the direction of w_k that is orthogonal to the subspace spanned by $w_1, \cdots, w_{k-1}$. Let $e_1, \cdots, e_k$ be an orthonormal basis of $w_1, \cdots, w_k$ guaranteed by Lemma C.3. Next, we expand the orthonormal basis to include e_{k+1} so that we can write the normalized vector of A_{k+r} as $v_{k+r} = \sum_{j=1}^{k+1} b_j e_j$. By a similar approach to the proof of Lemma C.3, for each $j \leq k-2$, $b_j \leq \beta^2 j^2$. Next, since $|\langle w_k, v_{k+r} \rangle| \leq \beta$,

$$|b_k| \leq \frac{1}{|\langle w_k, e_k \rangle|} \cdot \left(|\langle w_k, v_{k+r} \rangle| + \sum_{j=1}^{k-1} |b_j \cdot \langle w_k, e_j \rangle| \right)$$

$$\leq \frac{1}{\sqrt{1 - \sum_{j=1}^{k-1} \beta^2 \cdot j^2}} \cdot \left(\beta + \sum_{j=1}^{k-2} \beta^2 \cdot j^2 + (k-1) \cdot \beta \right) \quad \triangleright |b_{k-1}| \leq 1$$

$$= \frac{\beta + \sum_{j=1}^{k-2} \beta^2 \cdot j^2}{\sqrt{1 - \sum_{j=1}^{k-1} \beta^2 \cdot j^2}} + (k-1)\beta$$

$$\leq 2(k-1)\beta - \frac{\beta^2 (k-1)^2}{\sqrt{1 - \sum_{j=1}^{k-1} \beta^2 \cdot j^2}} \quad\quad \triangleright \text{ similar to the proof of Lemma C.3}$$

$$< 2\beta \cdot k$$

Hence, the squared projection of A_{k+r} onto e_k is at most $4\beta^2 \cdot k^2 \cdot \|A_{k+r}\|_2^2$. We assumed $\|A_{k+r}\|$. □

Claim C.9. *We assume that the absolute values of the inner products of vectors in $v_1, \cdots, v_n$ are at most $\bar{\epsilon} < 1/(n^2 \sum_{A_i \in b} \|A_i\|_2)$ and the absolute values of the inner products of the normalized vectors of $w_1, \cdots, w_k$ are at most $\beta = O(n^{-3}k^{-\frac{3}{2}})$. Suppose that bin b contains the row A_{k+r}. Then, the squared projection of A_{k+r} onto the direction of w orthogonal to $\text{span}(\{w_1, \cdots, w_k\} \setminus \{w\})$ is at most $\frac{\|A_{k+r}\|_2^4}{\|w\|_2^2} + O(n^{-2})$ and is at least $\frac{\|A_{k+r}\|_2^4}{\|w\|_2^2} - O(n^{-2})$.*

Proof: Without loss of generality, we assume that A_{k+r} is mapped to b_k; $w = w_k$. First, we provide an upper and a lower bound for $|\langle v_{k+r}, \overline{w}_k \rangle|$ where for each $i \leq k$, we let $\overline{w}_i = \frac{w_i}{\|w_i\|_2}$ denote the normalized vector of w_i. Recall that by definition $v_{k+r} = \frac{A_{k+r}}{\|A_{k+r}\|_2}$.

$$|\langle \overline{w}_k, v_{k+r} \rangle| \leq \frac{\|A_{k+r}\|_2 + \sum_{A_i \in b_k} \bar{\epsilon} \|A_i\|_2}{\|w_k\|_2}$$

$$\leq \frac{\|A_{k+r}\|_2 + n^{-2}}{\|w_k\|_2} \quad\quad \triangleright \text{ by } \bar{\epsilon} < \frac{n^{-2}}{\sum_{A_i \in b_k} \|A_i\|_2}$$

$$\leq \frac{\|A_{k+r}\|_2}{\|w_k\|_2} + n^{-2} \quad\quad \triangleright \|w_k\|_2 \geq 1 \quad\quad\quad (C.5)$$

$$|\langle \overline{w}_k, v_{k+r} \rangle| \geq \frac{\|A_{k+r}\|_2 - \sum_{A_i \in b_k} \|A_i\|_2 \cdot \bar{\epsilon}}{\|w_k\|_2}$$

$$\geq \frac{\|A_{k+r}\|_2}{\|w_k\|_2} - n^{-2} \quad\quad\quad\quad\quad\quad\quad\quad\quad (C.6)$$

Now, let $\{e_1, \cdots, e_k\}$ be an orthonormal basis for the subspace spanned by $\{w_1, \cdots, w_k\}$ guaranteed by Lemma C.3. Next, we expand the orthonormal basis to include e_{k+1} so that we can write $v_{k+r} = \sum_{j=1}^{k+1} b_j e_j$. By a similar approach to the proof of Lemma C.3, we can show that for each $j \le k-1$, $b_j^2 \le \beta^2 j^2$. Moreover,

$$|b_k| \le \frac{1}{|\langle \overline{w}_k, e_k \rangle|} \cdot (|\langle \overline{w}_k, v_{k+r} \rangle| + \sum_{j=1}^{k-1} |b_j \cdot \langle \overline{w}_k, e_j \rangle|)$$

$$\le \frac{1}{\sqrt{1 - \sum_{j=1}^{k-1} \beta^2 \cdot j^2}} \cdot (|\langle \overline{w}_k, v_{k+r} \rangle| + \sum_{j=1}^{k-1} \beta^2 \cdot j^2) \qquad \triangleright \text{ by Lemma C.3}$$

$$\le \frac{1}{\sqrt{1 - \sum_{j=1}^{k-1} \beta^2 \cdot j^2}} \cdot (n^{-2} + \frac{\|A_{k+r}\|_2}{\|w_k\|_2} + \sum_{j=1}^{k-1} \beta^2 \cdot j^2) \qquad \triangleright \text{ by (C.5)}$$

$$< \beta \cdot k + \frac{1}{\sqrt{1 - \beta^2 k^3}} \cdot (n^{-2} + \frac{\|A_{k+r}\|_2}{\|w_k\|_2}) \qquad \triangleright \text{ similar to the proof of Lemma C.3}$$

$$\le O(n^{-2}) + (1 + O(n^{-2})) \frac{\|A_{k+r}\|_2}{\|w_k\|_2} \qquad \triangleright \text{ by } \beta = O(n^{-3} k^{-\frac{3}{2}})$$

$$\le \frac{\|A_{k+r}\|_2}{\|w_k\|_2} + O(n^{-2}) \qquad \triangleright \frac{\|A_{k+r}\|_2}{\|w_k\|_2} \le 1$$

and,

$$|b_k| \ge \frac{1}{|\langle \overline{w}_k, e_k \rangle|} \cdot (|\langle \overline{w}_k, v_{k+r} \rangle| - \sum_{j=1}^{k-1} |b_j \cdot \langle \overline{w}_k, e_j \rangle|)$$

$$\ge |\langle \overline{w}_k, v_{k+r} \rangle| - \sum_{j=1}^{k-1} \beta^2 \cdot j^2 \qquad \triangleright \text{ since } |\langle \overline{w}_k, e_k \rangle| \le 1$$

$$\ge \frac{\|A_{k+r}\|_2}{\|w_k\|_2} - n^{-2} - \sum_{j=1}^{k-1} \beta^2 \cdot j^2 \qquad \triangleright \text{ by (C.6)}$$

$$\ge \frac{\|A_{k+r}\|_2}{\|w_k\|_2} - O(n^{-2}) \qquad \triangleright \text{ by } \beta = O(n^{-3} k^{-\frac{3}{2}})$$

Hence, the squared projection of A_{k+r} onto e_k is at most $\frac{\|A_{k+r}\|_2^4}{\|w_k\|_2^2} + O(n^{-2})$ and is at least $\frac{\|A_{k+r}\|_2^4}{\|w_k\|_2^2} - O(n^{-2})$. $\qquad\square$

Now, we show that at the end of the algorithm no light row will be assigned to the bins that contain heavy rows.

Lemma C.10. *We assume that the absolute values of the inner products of vectors in $v_1, \cdots, v_n$ are at most $\overline{\epsilon} < \min\{n^{-2} k^{-\frac{5}{3}}, (n \sum_{A_i \in w} \|A_i\|_2)^{-1}\}$. At each iteration $k + r$, the greedy algorithm will assign the light row A_{k+r} to a bin that does not contain a heavy row.*

Proof: The proof is by induction. Lemma C.6 implies that no light row has been mapped to a bin that contains a heavy row for the first k iterations. Next, we assume that this holds for the first $k + r - 1$ iterations and show that is also must hold for the $k + r^{\text{th}}$ iteration.

To this end, we compare the sum of squared projection coefficients when A_{k+r} avoids and collides with a heavy row.

First, we upper bound $\beta = \max_{i \ne j \le k} |\langle w_i, w_j \rangle| / (\|w_i\|_2 \|w_j\|_2)$. Let c_i and c_j respectively denote the number of rows assigned to b_i and b_j.

$$\beta = \max_{i \ne j \le k} \frac{|\langle w_i, w_j \rangle|}{\|w_i\|_2 \|w_j\|_2} \le \frac{c_i \cdot c_j \cdot \overline{\epsilon}}{\sqrt{c_i - 2\overline{\epsilon} c_i^2} \cdot \sqrt{c_j - 2\overline{\epsilon} c_j^2}} \qquad \triangleright \text{ Observation C.2}$$

$$\leq 16\overline{\epsilon}\sqrt{c_i c_j} \qquad\qquad\qquad \triangleright \overline{\epsilon} \leq n^{-2}k^{-5/3}$$
$$\leq n^{-1}k^{-\frac{5}{3}} \qquad\qquad\qquad \triangleright \overline{\epsilon} \leq n^{-2}k^{-5/3}$$

1. If A_{k+r} is assigned to a bin that contains c light rows and no heavy rows. In this case, the projection loss of the heavy rows $A_1, \cdots, A_s$ onto $row(SA)$ remains zero. Thus, we only need to bound the change in the sum of squared projection coefficients of the light rows before and after iteration $k + r$.

Without loss of generality, let w_k denote the bin that contains A_{k+r}. Since $\mathbb{S}_{k-1} = \mathrm{span}(\{w_1, \cdots, w_{k-1}\})$ has not changed, we only need to bound the difference in cost between projecting onto the component of $w_k - A_{k+r}$ orthogonal to $\mathbb{S}_{k-1}$ and the component of w_k orthogonal to $\mathbb{S}_{k-1}$, respectively denoted as e_k and $\overline{e}_k$.

   I. By Claim C.7, for the light rows that are not yet processed (i.e., A_j for $j > k+r$), the squared projection of each onto e_k is at most $\beta^2 k^2$. Hence, the total decrease in the squared projection is at most $(n - k - r) \cdot \beta^2 k^2$.

   II. By Claim C.8, for the processed light rows that are not mapped to the last bin, the squared projection of each onto e_k is at most $4\beta^2 k^2$. Hence, the total decrease in the squared projection cost is at most $(r - 1) \cdot 4\beta^2 k^2$.

   III. For each row $A_i \neq A_{k+r}$ that is mapped to the last bin, by Claim C.9 and the fact $\|A_i\|_2^4 = \|A_i\|_2^2 = 1$, the squared projection of A_i onto e_k is at most $\frac{\|A_i\|_2^2}{\|w_k - A_{k+r}\|_2^2} + O(n^{-2})$ and the squared projection of A_i onto $\overline{e}_k$ is at least $\frac{\|A_i\|_2^2}{\|w_k\|_2^2} - O(n^{-2})$.

      Moreover, the squared projection of A_{k+r} onto e_k compared to $\overline{e}_k$ increases by at least $(\frac{\|A_{k+r}\|_2^2}{\|w_k\|_2^2} - O(n^{-2})) - O(n^{-2}) = \frac{\|A_{k+r}\|_2^2}{\|w_k\|_2^2} - O(n^{-2})$.

      Hence, the total squared projection of the rows in the bin b_k decreases by at least:

$$\Big(\sum_{A_i \in w_k / \{A_{r+k}\}} \frac{\|A_i\|_2^2}{\|w_k - A_{r+k}\|_2^2} + O(n^{-2})\Big) - \Big(\sum_{A_i \in w_k} \frac{\|A_i\|_2^2}{\|w_k\|_2^2} - O(n^{-2})\Big)$$
$$\leq \frac{\|w_k - A_{r+k}\|_2^2 + O(n^{-1})}{\|w_k - A_{r+k}\|_2^2} - \frac{\|w_k\|_2^2 - O(n^{-1})}{\|w_k\|_2^2} + O(n^{-1}) \qquad \triangleright \text{ by Observation C.2}$$
$$\leq O(n^{-1})$$

Hence, summing up the bounds in items I to III above, the total decrease in the sum of squared projection coefficients is at most $O(n^{-1})$.

2. If A_{k+r} is assigned to a bin that contains a heavy row. Without loss of generality, we can assume that A_{k+r} is mapped to b_k that contains the heavy row A_s. In this case, the distance of heavy rows $A_1, \cdots, A_{s-1}$ onto the space spanned by the rows of SA is zero. Next, we bound the amount of change in the squared distance of A_s and light rows onto the space spanned by the rows of SA.

Note that the $(k-1)$-dimensional space corresponding to $w_1, \cdots, w_{k-1}$ has not changed. Hence, we only need to bound the decrease in the projection distance of A_{k+r} onto $\overline{e}_k$ compared to e_k (where $\overline{e}_k, e_k$ are defined similarly as in the last part).

   1. For the light rows other than A_{k+r}, the squared projection of each onto e_k is at most $\beta^2 k^2$. Hence, the total increase in the squared projection of light rows onto e_k is at most $(n - k) \cdot \beta^2 k^2 = O(n^{-1})$.

   2. By Claim C.9, the sum of squared projections of A_s and A_{k+r} onto e_k decreases by at least

$$\|A_s\|_2^2 - \Big(\frac{\|A_s\|_2^4 + \|A_{k+r}\|_2^4}{\|A_s + A_{r+k}\|_2^2} + O(n^{-1})\Big)$$

$$\geq \|A_s\|_2^2 - (\frac{\|A_s\|_2^4 + \|A_{k+r}\|_2^4}{\|A_s\|_2^2 + \|A_{r+k}\|_2^2 - n^{-O(1)}} + O(n^{-1})) \qquad \triangleright \text{ by Observation C.2}$$

$$\geq \frac{\|A_{r+k}\|_2^2 (\|A_s\|_2^2 - \|A_{k+r}\|_2^2) - \|A_s\|_2^2 \cdot O(n^{-1})}{\|A_s\|_2^2 + \|A_{r+k}\|_2^2 - O(n^{-1})} - O(n^{-1})$$

$$\geq \frac{\|A_{r+k}\|_2^2 (\|A_s\|_2^2 - \|A_{k+r}\|_2^2) - \|A_s\|_2^2 \cdot O(n^{-1})}{\|A_s\|_2^2 + \|A_{r+k}\|_2^2} - O(n^{-1})$$

$$\geq \frac{\|A_{r+k}\|_2^2 (\|A_s\|_2^2 - \|A_{k+r}\|_2^2)}{\|A_s\|_2^2 + \|A_{r+k}\|_2^2} - O(n^{-1})$$

$$\geq \frac{\|A_{r+k}\|_2^2 (1 - (\|A_{k+r}\|_2^2 / \|A_s\|_2^2))}{1 + (\|A_{r+k}\|_2^2 / \|A_s\|_2^2)} - O(n^{-1})$$

$$\geq \|A_{r+k}\|_2^2 (1 - \frac{\|A_{k+r}\|_2}{\|A_s\|_2}) - O(n^{-1}) \qquad \triangleright \frac{1 - \epsilon^2}{1 + \epsilon^2} \geq 1 - \epsilon$$

Hence, in this case, the total decrease in the squared projection is at least

$$\|A_{r+k}\|_2^2 (1 - \frac{\|A_{k+r}\|_2}{\|A_s\|_2}) - O(n^{-1}) = 1 - \frac{\|A_{k+r}\|_2}{\|A_s\|_2}) - O(n^{-1}) \qquad \triangleright \|A_{r+k}\|_2 = 1$$

$$= 1 - (1/\sqrt{\ell}) - O(n^{-1}) \qquad \triangleright \|A_s\|_2 = \sqrt{\ell}$$

Thus, for a sufficiently large value of ℓ, the greedy algorithm will assign A_{k+r} to a bin that only contains light rows. This completes the inductive proof and in particular implies that at the end of the algorithm, heavy rows are assigned to isolated bins. $\qquad \square$

Corollary C.11. *The approximation loss of the best* rank-k *approximate solution in the rowspace* $S_g A$ *for* $A \sim \mathcal{A}_{sp}(s, \ell)$ *where* $A \in \mathbb{R}^{n \times d}$ *for* $d = \Omega(n^4 k^4 \log n)$ *and* S_g *is the CountSketch constructed by the greedy algorithm with non-increasing order is at most* $n - s$.

Proof: First, we need to show that absolute values of the inner products of vectors in $v_1, \cdots, v_n$ is at most $\bar{\epsilon} < \min\{n^{-2} k^{-2}, (n \sum_{A_i \in w} \|A_i\|_2)^{-1}\}$ so that we can apply Lemma C.10. To show this, note that by Observation C.1, $\bar{\epsilon} \leq 2\sqrt{\frac{\log n}{d}} \leq n^{-2} k^{-2}$ since $d = \Omega(n^4 k^4 \log n)$. The proof follows from Lemma C.6 and Lemma C.10. Since all heavy rows are mapped to isolated bins, the projection loss of the light rows is at most $n - s$. $\qquad \square$

Next, we bound the Frobenius norm error of the best rank-k-approximation solution constructed by the standard CountSketch with a randomly chosen sparsity pattern.

Lemma C.12. *Let* $s = \alpha k$ *where* $0.7 < \alpha < 1$. *The expected squared loss of the best* rank-k *approximate solution in the rowspace* $S_r A$ *for* $A \in \mathbb{R}^{n \times d} \sim \mathcal{A}_{sp}(s, \ell)$ *where* $d = \Omega(n^6 \ell^2)$ *and* S_r *is the sparsity pattern of CountSketch is chosen uniformly at random is at least* $n + \frac{\ell k}{4e} - (1 + \alpha)k - n^{-O(1)}$.

Proof: We can interpret the randomized construction of the CountSketch as a "balls and bins" experiment. In particular, considering the heavy rows, we compute the expected number of bins (i.e., rows in $S_r A$) that contain a heavy row. Note that the expected number of rows in $S_r A$ that do not contain any heavy row is $k \cdot (1 - \frac{1}{k})^s \geq k \cdot e^{-\frac{s}{k-1}}$. Hence, the number of rows in $S_r A$ that contain a heavy row of A is at most $k(1 - e^{-\frac{s}{k-1}})$. Thus, at least $s - k(1 - e^{-\frac{s}{k-1}})$ heavy rows are not mapped to an isolated bin (i.e., they collide with some other heavy rows). Then, it is straightforward to show that the squared loss of each such row is at least $\ell - n^{-O(1)}$.

Claim C.13. *Suppose that heavy rows* $A_{r_1}, \cdots, A_{r_c}$ *are mapped to the same bin via a CountSketch* S. *Then, the total squared distances of these rows from the subspace spanned by* SA *is at least* $(c - 1)\ell - O(n^{-1})$.

Proof: Let b denote the bin that contains the rows $A_{r_1}, \cdots, A_{r_c}$ and suppose that it has c' light rows as well. Note that by Claim C.8 and Claim C.9, the squared projection of each row A_{r_i} onto the subspace spanned by the k bins is at most

$$\frac{\|A_{h_i}\|_2^4}{\|w\|_2^2} + O(n^{-1})$$

$$\leq \frac{\ell^2}{c\ell + c' - 2\overline{\epsilon}(c^2\ell + cc'\sqrt{\ell} + c'^2)} + O(n^{-1})$$

$$\leq \frac{\ell^2}{c\ell - n^{-O(1)}} + n^{-O(1)} \qquad\qquad \triangleright \text{ by } \overline{\epsilon} \leq n^{-3}\ell^{-1}$$

$$\leq \frac{\ell^2}{c^2\ell^2} \cdot (c\ell + O(n^{-1}) + O(n^{-1})$$

$$\leq \frac{\ell}{c} + O(n^{-1})$$

Hence, the total squared loss of these c heavy rows is at least $c\ell - c \cdot (\frac{\ell}{c} + O(n^{-1})) \geq (c-1)\ell - O(n^{-1})$. $\qquad\square$

Hence, the expected total squared loss of heavy rows is at least:

$$\ell \cdot (s - k(1 - e^{-\frac{s}{k-1}})) - s \cdot n^{-O(1)}$$

$$\geq \ell \cdot k(\alpha - 1 + e^{-\alpha}) - \ell\alpha - n^{-O(1)} \qquad \triangleright s = \alpha \cdot (k-1) \text{ where } 0.7 < \alpha < 1$$

$$\geq \frac{\ell k}{2e} - \ell - n^{-O(1)} \qquad\qquad\qquad \triangleright \alpha \geq 0.7$$

$$\geq \frac{\ell k}{4e} - O(n^{-1}) \qquad\qquad\qquad \triangleright \text{ assuming } k > 4e$$

Next, we compute a lower bound on the expected squared loss of the light rows. Note that Claim C.8 and Claim C.9 imply that when a light row collides with other rows, its contribution to the total squared loss (which the loss accounts for the amount it decreases from the squared projection of the other rows in the bin as well) is at least $1 - O(n^{-1})$. Hence, the expected total squared loss of the light rows is at least:

$$(n - s - k)(1 - O(n^{-1})) \geq (n - (1 + \alpha) \cdot k) - O(n^{-1})$$

Hence, the expected squared loss of a CountSketch whose sparsity is picked at random is at least

$$\frac{\ell k}{4e} - O(n^{-1}) + n - (1 + \alpha)k - O(n^{-1}) \geq n + \frac{\ell k}{4e} - (1 + \alpha)k - O(n^{-1}) \qquad\square$$

Corollary C.14. *Let $s = \alpha(k - 1)$ where $0.7 < \alpha < 1$ and let $\ell \geq \frac{(4e+1)n}{\alpha k}$. Let S_g be the CountSketch whose sparsity pattern is learned over a training set drawn from $\mathcal{A}_{sp}$ via the greedy approach. Let S_r be a CountSketch whose sparsity pattern is picked uniformly at random. Then, for an $n \times d$ matrix $A \sim \mathcal{A}_{sp}$ where $d = \Omega(n^6\ell^2)$, the expected loss of the best rank-k approximation of A returned by S_r is worse than the approximation loss of the best rank-k approximation of A returned by S_g by at least a constant factor.*

Proof:

$$\mathbf{E}_{S_r}\left[\min_{\text{rank-}k\ X\in\text{rowsp}(S_r A)} \|X - A\|_F^2\right] \geq n + \frac{\ell k}{4e} - (1 + \alpha)k - n^{-O(1)} \qquad \triangleright \text{ Lemma C.12}$$

$$\geq (1 + 1/\alpha)(n - s) \qquad\qquad \triangleright \ell \geq \frac{(4e + 1)n}{\alpha k}$$

$$= (1 + 1/\alpha)\min_{\text{rank-}k\ X\in\text{rowsp}(S_g A)} \|X - A\|_F^2 \qquad \triangleright \text{ Corollary C.11}$$

$$\square$$

C.2 ZIPFIAN ON SQUARED ROW NORMS.

Each matrix $A \in \mathbb{R}^{n \times d} \sim \mathcal{A}_{zipf}$ has rows which are uniformly random and orthogonal. Each A has 2^{i+1} rows of squared norm $n^2/2^{2i}$ for $i \in [1, \ldots, \mathcal{O}(\log(n))]$. We also assume that each row has the same squared norm for all members of $\mathcal{A}_{zipf}$.

In this section, the s rows with largest norm are called the *heavy* rows and the remaining are the *light* rows. For convenience, we number the heavy rows $1 - s$; however, the heavy rows can appear at any indices, as long as any row of a given index has the same norm for all members of $\mathcal{A}_{zipf}$. Also, we assume that $s \leq k/2$ and, for simplicity, $s = \sum_{i=1}^{h_s} 2^{i+1}$ for some $h_s \in \mathbb{Z}^+$. That means the minimum squared norm of a heavy row is $n^2/2^{2h_s}$ and the maximum squared norm of a light row is $n^2/2^{2h_s+2}$.

The analysis of the greedy algorithm ordered by non-increasing row norms on this family of matrices is similar to our analysis for the spiked covariance model. Here we analyze the case in which rows are orthogonal. By continuity, if the rows are close enough to being orthogonal, all decisions made by the greedy algorithm will be the same.

As a first step, by Lemma C.6, at the end of iteration k the first k rows are assigned to different bins. Then, via a similar inductive proof, we show that none of the light rows are mapped to a bin that contains one of the top s heavy rows.

Lemma C.15. *At each iteration $k + r$, the greedy algorithm picks the position of the non-zero value in the $(k + r)$-th column of the CountSketch matrix S so that the light row A_{k+r} is mapped to a bin that does not contain any of top s heavy rows.*

Proof: We prove the statement by induction. The base case $r = 0$ trivially holds as the first k rows are assigned to distinct bins. Next we assume that in none of the first $k + r - 1$ iterations a light row is assigned to a bin that contains a heavy row. Now, we consider the following cases:

1. If A_{k+r} is assigned to a bin that only contains light rows. Without loss of generality we can assume that A_{k+r} is assigned to b_k. Since the vectors are orthogonal, we only need to bound the difference in the projection of A_{k+r} and the light rows that are assigned to b_k onto the direction of w_k before and after adding A_{k+r} to b_k. In this case, the total squared loss corresponding to rows in b_k and A_{k+r} before and after adding A_{k+1} are respectively

$$\textit{before adding } A_{k+r} \textit{ to } b_k\text{: } \|A_{k+r}\|_2^2 + \sum_{A_j \in b_k} \|A_j\|_2^2 - \left(\frac{\sum_{A_j \in b_k} \|A_j\|_2^4}{\sum_{A_j \in b_k} \|A_j\|_2^2}\right)$$

$$\textit{after adding } A_{k+r} \textit{ to } b_k\text{: } \|A_{k+r}\|_2^2 + \sum_{A_j \in b_k} \|A_j\|_2^2 - \left(\frac{\|A_{k+r}\|_2^4 + \sum_{A_j \in b_k} \|A_j\|_2^4}{\|A_{k+r}\|_2^2 + \sum_{A_j \in b_k} \|A_j\|_2^2}\right)$$

Thus, the amount of increase in the squared loss is

$$\left(\frac{\sum_{A_j \in b_k} \|A_j\|_2^4}{\sum_{A_j \in b_k} \|A_j\|_2^2}\right) - \left(\frac{\|A_{k+r}\|_2^4 + \sum_{A_j \in b_k} \|A_j\|_2^4}{\|A_{k+r}\|_2^2 + \sum_{A_j \in b_k} \|A_j\|_2^2}\right) = \frac{\|A_{k+r}\|_2^2 \cdot \sum_{A_j \in b_k} \|A_j\|_2^4 - \|A_{k+r}\|_2^4 \cdot \sum_{A_j \in b_k} \|A_j\|_2^2}{(\sum_{A_j \in b_k} \|A_j\|_2^2)(\|A_{k+r}\|_2^2 + \sum_{A_j \in b_k} \|A_j\|_2^2)}$$

$$= \|A_{k+r}\|_2^2 \cdot \frac{\frac{\sum_{A_j \in b_k} \|A_j\|_2^4}{\sum_{A_j \in b_k} \|A_j\|_2^2} - \|A_{k+r}\|_2^2}{\sum_{A_j \in b_k} \|A_j\|_2^2 + \|A_{k+r}\|_2^2}$$

$$\leq \|A_{k+r}\|_2^2 \cdot \frac{\sum_{A_j \in b_k} \|A_j\|_2^2 - \|A_{k+r}\|_2^2}{\sum_{A_j \in b_k} \|A_j\|_2^2 + \|A_{k+r}\|_2^2} \tag{C.7}$$

2. If A_{k+r} is assigned to a bin that contains a heavy row. Without loss of generality and by the induction hypothesis, we assume that A_{k+r} is assigned to a bin b that only contains a heavy row A_j. Since the rows are orthogonal, we only need to bound the difference in the projection of A_{k+r} and A_j In this case, the total squared loss corresponding to A_j and A_{k+r} before and after adding A_{k+1} to b are respectively

$$\textit{before adding } A_{k+r} \textit{ to } b_k\text{: } \|A_{k+r}\|_2^2$$

$$\textit{after adding } A_{k+r} \textit{ to } b_k\text{: } \|A_{k+r}\|_2^2 + \|A_j\|_2^2 - \left(\frac{\|A_{k+r}\|_2^4 + \|A_j\|_2^4}{\|A_{k+r}\|_2^2 + \|A_j\|_2^2}\right)$$

Thus, the amount of increase in the squared loss is

$$\|A_j\|_2^2 - (\frac{\|A_{k+r}\|_2^4 + \|A_j\|_2^4}{\|A_{k+r}\|_2^2 + \|A_j\|_2^2}) = \|A_{k+r}\|_2^2 \cdot \frac{\|A_j\|_2^2 - \|A_{k+r}\|_2^2}{\|A_j\|_2^2 + \|A_{k+r}\|_2^2} \tag{C.8}$$

Then (C.8) is larger than (C.7) if $\|A_j\|_2^2 \geq \sum_{A_i \in b_k} \|A_i\|_2^2$. Next, we show that at every inductive iteration, there exists a bin b which only contains light rows and whose squared norm is smaller than the squared norm of any heavy row. For each value m, define h_m so that $m = \sum_{i=1}^{h_m} 2^{i+1} = 2^{h_m+2} - 2$.

Recall that all heavy rows have squared norm at least $\frac{n^2}{2^{2h_s}}$. There must be a bin b that only contains light rows and has squared norm at most

$$\begin{aligned}
\|w\|_2^2 = \sum_{A_i \in b} \|A_i\|_2^2 &\leq \frac{n^2}{2^{2(h_s+1)}} + \frac{\sum_{i=h_k+1}^{h_n} \frac{2^{i+1}n^2}{2^{2i}}}{k-s} \\
&\leq \frac{n^2}{2^{2(h_s+1)}} + \frac{2n^2}{2^{h_k}(k-s)} \\
&\leq \frac{n^2}{2^{2(h_s+1)}} + \frac{n^2}{2^{2h_k}} \qquad \triangleright s \leq k/2 \text{ and } k > 2^{h_k+1} \\
&\leq \frac{n^2}{2^{2h_s+1}} \qquad\qquad\qquad \triangleright h_k \geq h_s + 1 \\
&< \|A_s\|_2^2
\end{aligned}$$

Hence, the greedy algorithm will map A_{k+r} to a bin that only contains light rows. $\qquad\square$

Corollary C.16. *The squared loss of the best* rank-k *approximate solution in the rowspace of $S_g A$ for $A \in \mathbb{R}^{n \times d} \sim \mathcal{A}_{zipf}$ where $A \in \mathbb{R}^{n \times d}$ and S_g is the CountSketch constructed by the greedy algorithm with non-increasing order, is $< \frac{n^2}{2^{h_k-2}}$.*

Proof: At the end of iteration k, the total squared loss is $\sum_{i=h_k+1}^{h_n} 2^{i+1} \cdot \frac{n^2}{2^{2i}}$. After that, in each iteration $k + r$, by (C.7), the squared loss increases by at most $\|A_{k+r}\|_2^2$. Hence, the total squared loss in the solution returned by S_g is at most

$$2(\sum_{i=h_k+1}^{h_n} \frac{2^{i+1}n^2}{2^{2i}}) = 4n^2 \cdot \sum_{i=h_k+1}^{h_n} \frac{1}{2^i}$$
$$< \frac{4n^2}{2^{h_k}} = \frac{n^2}{2^{h_k-2}} \qquad\qquad\qquad\square$$

Next, we bound the squared loss of the best rank-k-approximate solution constructed by the standard CountSketch with a randomly chosen sparsity pattern.

Observation C.17. *Let us assume that the orthogonal rows $A_{r_1}, \cdots, A_{r_c}$ are mapped to same bin and for each $i \leq c$, $\|A_{r_1}\|_2^2 \geq \|A_{r_i}\|_2^2$. Then, the total squared loss of $A_{r_1}, \cdots, A_{r_c}$ after projecting onto $A_{r_1} \pm \cdots \pm A_{r_c}$ is at least $\|A_{r_2}\|_2^2 + \cdots + \|A_{r_c}\|_2^2$.*

Proof: Note that since $A_{r_1}, \cdots, A_{r_c}$ are orthogonal, for each $i \leq c$, the squared projection of A_{r_i} onto $A_{r_1} \pm \cdots \pm A_{r_c}$ is $\|A_{r_i}\|_2^4 / \sum_{j=1}^c \|A_{r_j}\|_2^2$. Hence, the sum of squared projection coefficients of $A_{r_1}, \cdots, A_{r_c}$ onto $A_{r_1} \pm \cdots \pm A_{r_c}$ is

$$\frac{\sum_{j=1}^c \|A_{r_j}\|_2^4}{\sum_{j=1}^c \|A_{r_j}\|_2^2} \leq \|A_{r_1}\|_2^2$$

Hence, the total projection loss of $A_{r_1}, \cdots, A_{r_c}$ onto $A_{r_1} \pm \cdots \pm A_{r_c}$ is at least

$$\sum_{j=1}^c \|A_{r_j}\|_2^2 - \|A_{r_1}\|_2^2 = \|A_{r_2}\|_2^2 + \cdots + \|A_{r_c}\|_2^2. \qquad\qquad\square$$

In particular, Observation C.17 implies that whenever two rows are mapped into a same bin, the squared norm of the row with smaller norm *fully* contributes to the total squared loss of the solution.

Lemma C.18. *For $k > 2^{10} - 2$, the expected squared loss of the best rank-k approximate solution in the rowspace of $S_r A$ for $A_{n \times d} \sim \mathcal{A}_{zipf}$, where S_r is the sparsity pattern of a CountSketch chosen uniformly at random, is at least $\frac{1.095 n^2}{2^{h_k-2}}$.*

Proof: In light of Observation C.17, we need to compute the expected number of collision between rows with "large" norm. We can interpret the randomized construction of the CountSketch as a "balls and bins" experiment.

For each $0 \le j \le h_k$, let $\mathcal{A}_j$ denote the set of rows with squared norm $\frac{n^2}{2^{2(h_k-j)}}$ and let $\mathcal{A}_{>j} = \bigcup_{j < i \le h_k} \mathcal{A}_i$. Note that for each j, $|\mathcal{A}_j| = 2^{h_k-j+1}$ and $|\mathcal{A}_{>j}| = \sum_{i=j+1}^{h_k} 2^{h_k-i+1} = \sum_{i=1}^{h_k-j} 2^i = 2(2^{h_k-j} - 1)$. Moreover, note that $k = 2(2^{h_k+1} - 1)$. Next, for a row A_r in $\mathcal{A}_j$ ($0 \le j < h_k$), we compute the probability that at least one row in $\mathcal{A}_{>j}$ collide with A_r.

$$\mathbf{Pr}[\text{at least one row in } \mathcal{A}_{>j} \text{ collide with } A_r] = (1 - (1 - \frac{1}{k})^{|\mathcal{A}_{>j}|})$$

$$\ge (1 - e^{-\frac{|\mathcal{A}_{>j}|}{k}})$$

$$= (1 - e^{-\frac{2^{h_k-j}-1}{2^{h_k+1}-1}})$$

$$\ge (1 - e^{-2^{-j-2}}) \qquad \triangleright \text{since } \frac{2^{h_k-j}-1}{2^{h_k+1}-1} > 2^{-j-2}$$

Hence, by Observation C.17, the contribution of rows in $\mathcal{A}_j$ to the total squared loss is at least

$$(1 - e^{-2^{-j-2}}) \cdot |\mathcal{A}_j| \cdot \frac{n^2}{2^{2(h_k-j)}} = (1 - e^{-2^{-j-2}}) \cdot \frac{n^2}{2^{h_k-j-1}}$$

$$= (1 - e^{-2^{-j-2}}) \cdot \frac{n^2}{2^{h_k-2}} \cdot 2^{j-1}$$

Thus, the contribution of rows with "large" squared norm, i.e., $\mathcal{A}_{>0}$, to the total squared loss is at least[6]

$$\frac{n^2}{2^{h_k-2}} \cdot \sum_{j=0}^{h_k} 2^{j-1} \cdot (1 - e^{-2^{-j-2}}) \ge 1.095 \cdot \frac{n^2}{2^{h_k-2}} \qquad \triangleright \text{for } h_k > 8 \qquad \square$$

Corollary C.19. *Let S_g be a CountSketch whose sparsity pattern is learned over a training set drawn from $\mathcal{A}_{sp}$ via the greedy approach. Let S_r be a CountSketch whose sparsity pattern is picked uniformly at random. Then, for an $n \times d$ matrix $A \sim \mathcal{A}_{zipf}$, for a sufficiently large value of k, the expected loss of the best rank-k approximation of A returned by S_r is worse than the approximation loss of the best rank-k approximation of A returned by S_g by at least a constant factor.*

Proof: The proof follows from Lemma C.18 and Corollary C.16. $\square$

Remark C.20. We have provided evidence that the greedy algorithm that examines the rows of A according to a non-increasing order of their norms (i.e., *greedy with non-increasing order*) results in a better rank-k solution compared to the CountSketch whose sparsity pattern is chosen at random. However, still other implementations of the greedy algorithm may result in a better solution compared to the greedy with non-increasing order. To give an example, in the following simple instance the greedy algorithm that check the rows of A in a random order (i.e., *greedy with random order*) achieves a rank-k solution whose cost is a constant factor better than the solution returned by the greedy with non-increasing order.

Let A be a matrix with four orthogonal rows u, u, v, w where $\|u\|_2 = 1$ and $\|v\|_2 = \|w\|_2 = 1 + \epsilon$ and suppose that the goal is to compute a rank-2 approximation of A. Note that in the greedy with non-decreasing order, v and w will be assigned to different bins and by a simple calculation we can show that the copies of u also will be assigned to different bins. Hence, the squared loss in the computed rank-2 solution is $1 + \frac{(1+\epsilon)^2}{2+(1+\epsilon)^2}$. However, the optimal solution will assign v and w to

---

[6]The numerical calculation is computed by WolframAlpha.

one bin and the two copies of u to the other bin which results in the squared loss of $(1 + \epsilon)^2$ which is a constant factor smaller than the solution returned by the greedy with non-increasing order for sufficiently small values of ϵ.

On the other hand, in the greedy algorithm with random order, with a constant probability $(\frac{1}{3} + \frac{1}{8})$, the computed solution is the same as the optimal solution. Otherwise, the greedy algorithm a with random order returns the same solution as the greedy algorithm with a non-increasing order. Hence, in expectation, the solution returned by the greedy with random order is better than the solution returned by the greedy algorithm with non-increasing order by a constant factor.

D   EXPERIMENTS - APPENDIX

D.1   BASELINES

We comment on two of our baselines:

- **Exact SVD**: In the canonical, learning-free sketching setting (i.e., any matrix is equally probable), sketching using the top m singular vectors yields a $(1 + \epsilon)$-approximation for both LRA and k-means Cohen et al. (2015).

- **Column sampling**: In the canonical, learning-free sketching setting, sketching via column sampling yields a $(1 + \epsilon)$-approximation for k-means Cohen et al. (2015).

D.2   EXPERIMENTAL PARAMETERS

For the tables in Section 5, we describe experimental parameters. First, we provide some general implementation details.

We implemented both the greedy (Algorithm 1) and stochastic gradient descent (Algorithm 2) algorithms in PyTorch. In the first case, PyTorch allowed us to harness GPUs to speed up computation on large matrices. We used several Nvidia GeForce GTX 1080 Ti machines. In the second case, PyTorch allowed us to effortlessly compute numerical gradients for each task's objective function. Specifically, PyTorch provides automatic differentiation, which is implemented by backpropagation through chained differentiable operators.

There are also two points of note in the greedy algorithm implementation. First, we noticed that for MRR and LRA, each iteration required computing the SVD for many rank-1 updates of the current S. Instead of computing the SVD from scratch for each of these variants, we first computed the SVD of S and then used fast rank-1 SVD updates Brand (2006). This greatly improved the runtime of Algorithm 1. Second, we decided to set $\mathcal{D}_w$ (the set of candidate row weights) to 10 samples in $[-2, 2]$ because we noticed most weights were in this range after running Algorithm 2.

D.3   RUNNING TIME

We examine the runtimes of our various sketching algorithms. In Table D.1, the times are obtained for the LRA task with $k = 30, m = 60$ on the logo data set. However, similar trends should be expected for other combinations of task, task parameters, and data sets.

We define the *inference* runtime as the time to apply the sketching algorithm. The *training* runtime is the time to train a sketch on $\mathcal{A}_{\text{train}}$ and only applies to learned sketches. Generally, the long *training* times are not problematic because training is only done once and can be completed offline. On the other hand, the *inference* runtime should be as fast as possible.

Note that *inference* was timed using 1 matrix from $\mathcal{A}_{\text{test}}$ on an Nvidia Geforce GTX 1080 Ti GPU. The values were averaged over 10 trials.

We observe that sparse sketches (such as the ones used in *GD only* and *Ours*) have much lower *inference* runtimes than the dense sketches of *exact SVD*.

Table D.1: Timing comparison of sketching algorithms for LRA (using Algorithm 1 from Indyk et al. (2019))

	Time (sec)
random: inference	0.0114
exact SVD: inference	0.185
learned (random pattern): training	193 (3 min)
learned (random pattern): inference	0.0114
learned (greedy pattern): training	6300 (1 h 45 min)
learned (greedy pattern): inference	0.0114