Learning from Distributed Users in Contextual Linear Bandits Without Sharing the Context

Abstract

Contextual linear bandits is a rich and theoretically important model that has many practical applications. Recently, this setup gained a lot of interest in applications over wireless where communication constraints can be a performance bottleneck, especially when the contexts come from a large d-dimensional space. In this paper, we consider a distributed memoryless contextual linear bandit learning problem, where the agents who observe the contexts and take actions are geographically separated from the learner who performs the learning while not seeing the contexts. We assume that contexts are generated from a distribution and propose a method that uses $\approx 5d$ bits per context for the case of unknown context distribution and 0 bits per context if the context distribution is known, while achieving nearly the same regret bound as if the contexts were directly observable. The former bound improves upon existing bounds by a $\log(T)$ factor, where T is the length of the horizon, while the latter achieves information theoretical tightness.

1 Introduction

Contextual linear bandits offer a sequential decision-making framework that combines fundamental theoretical importance with significant practical popularity [8], as it offers a tractable way to capture side information (context), as well as a potentially infinite set of decisions (actions). The most prominent application is in recommendation systems [30], but it has also been used in applications such as virtual support agents [39], clinical trials [12], transportation systems [9], wireless optimization [26, 25], health [10], robotics [31] and online education [34].

In this paper, we develop algorithms that support the deployment of contextual linear bandits in distributed settings. In particular, we consider the case where a central learner wishes to solve a contextual linear bandit problem with the help of transient agents. That is, we assume that the agents do not keep memory of past actions and may not be present for the whole duration of learning; learning in our setup can happen thanks to the persistent presence of the central learner. We view the central learner as a "knowledge repository", that accumulates knowledge from the experience of the transient agents and makes it available to next agents. The central learner, through the information it keeps, could help passing by devices decide how to perform an action, for example: passing by drones decide how to perform a manoeuver; agricultural robots decide what amounts of substances such as pesticids to release; and passing by mobile devices decide which local restaurants to recommend.

The main challenge we try to address in this paper is the efficient communication of the context the agents experience. More specifically, in our setup, each time an agent joins, she receives from the central learner information on the system, such as current estimates of the system parameters; she observes her current context, selects and plays an action and collects the corresponding reward. Note that although the distributed agent knows her context, the action she plays and the observed reward, the central learner does not - and needs this information to update its estimate of the system parameters.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

The context in particular can be communication heavy - in the examples we mentioned before, for drones the context could be their navigation capabilities, physical attributes, and enviromental factors such as wind speed; for agricultural robots, it could be images that indicate state of plants and sensor measurements such as of soil consistency; for restaurant recommendations, it could be the personal dietary preferences and restrictions, budget, and emotional state. Moreover, because of geographical separation, the central learner may not have any other way to learn the context beyond communication. Unlike the reward, that is usually a single scalar value, the context can be a vector of a large dimension d from an infinite alphabet, and thus, communicating the context efficiently is heavily nontrivial.

The technical question we ask is, *how many bits do we need to convey per context to solve the linear bandit problem without downgrading the performance as compared to the non-distributed setting?*

In this paper, we design algorithms that support this goal. We note that our algorithms optimize the uplink communication (from the agents to the central learner), and assume unlimited (cost-free) downlink communication. This is a standard assumption in wireless [7, 33, 21] for several reasons: uplink wireless links tend to be much more bandwidth restricted, since several users may be sharing the same channel; uplink communication may also be battery-powered and thus more expensive to sustain; in our particular case, the agents may have less incentive to communicate (provide their feedback) than the central learner (who needs to learn). Having said that, we note that our algorithms (in Sections 3 and 4) make frugal use of the downlink channels, only using them to transmit system parameters.

Below we summarize our main contributions:
1. We show the surprising result that, if the central learner knows the distribution of the contexts, we do not need to communicate the context at all - the agent does not need to send any information on the actual context she observes and the action she plays. It is sufficient for the agent to just send 1 bit to convey quantized information on her observed reward and nothing else. But for this very limited communication, the central learner can learn a policy that achieves the same order of regret as if full information about the context and reward is received. This result holds for nearly all context distributions and it is the best we can hope for - *zero bits* of communication for the context.
2. If the central learner has no knowledge of the context distribution, we show that $\approx 5d$ bits per context (where d is the context dimension) is sufficient to achieve the same order regret as knowing the context in full precision. Note that previous algorithms, that rely on constructing $1/T$-net for the set of feature vectors, use $O(d \log T)$ bits per context to achieve the same order regret, where T is the length of the horizon [24], and require time complexity of $O(T^d)$ which is exponential in d.

Related Work and Distinction. Contextual linear bandits is a rich and important model that has attracted significant interest both in theory and applications [8, 24]. Within this space, our work focuses on operation under communications constraints in a distributed setting.

There is large body of work focusing on distributed linear contextual bandits settings, but mainly within the framework of federated learning, where batched algorithms have been proposed for communication efficiency [43, 41, 6, 5, 23] that aggregate together observations and parameter learning across a large number of iterations. This is possible because in federated learning, the agents themselves wish to learn the system parameters, remain active playing multiple actions throughout the learning process, and exchange information with the goal of speeding up their learning [43, 41]. In contrast, in our setup batched algorithms cannot reduce the communication cost because each agent only plays a single action; this may be because agents are transient, but also because they may not be interested in learning - this may not be a task that the agents wish to consistently perform - and thus do not wish to devote resources to it. For example, an agent may wish to try a restaurant in a special occasion, but would not be interested in sampling multiple restaurants/learning recommendation system parameters. In other words, we consider a scenario where the user benefits from receiving an action (or policy) from the central learner, e.g., a recommendation. In response, the user gives feedback to the central learner in terms of (compressed) context/reward. The compression operations benefit the user by helping reduce her communication cost. In principle, the user is not required to respond. But the central learner will be able to learn whenever there is a feedback; creating an incentive for the user to respond could be an interesting future topic. Our setup supports a different (and complementary) set of applications than the federated learning framework, and requires a new set of algorithms that operate without requiring agents to keep memory of past actions.[1]

---

[1]Our techniques could be adapted to additionally improve the communication efficiency of batched algorithms, but this is not the focus of our work.

To the best of our knowledge, our framework has not been examined before for linear contextual bandits. Work in the literature has examined compression for distributed memoryless MABs [21], but only for rewards (scalar values) and not the contexts (large vectors), and thus these techniques also do not extend to our case. Additional less-closely related work is reviewed in App. A.

Paper organization. Section 2 reviews our notation and problem formulation; Section 3 provides and analyzes our algorithm for known and Section 4 for unknown context distributions.

2 Notation and Problem Formulation

Notation. We use the following notation throughout the paper. For a vector X we use X_i or $(X)_i$ to denote the i-th element of the vector X; similarly for a matrix V, we use V_{ij} or $(V)_{ij}$ to denote the element at row i, and column j. We use $\|V\|_2$ to denote the matrix spectral norm. For a function f, we denote its domain and range by $\mathrm{dom}(f)$, $\mathrm{ran}(f)$ respectively. When $\mathrm{dom}(f) \subseteq \mathbb{R}$, we use $f(X)$ for a vector $X \in \mathbb{R}^d$ to denote $f(X) := [f(X_1), ..., f(X_d)]$, i.e., the function f is applied element-wise; for example we use X^2 to denote the element-wise square of X. We denote the inverse of a function f by f^{-1}; if f is not one-to-one, with abuse of notation we use f^{-1} to denote a function that satisfies $f(f^{-1}(x)) = x \forall x \in \mathrm{ran}(f)$ (this is justified due to the axiom of choice [22]). For a matrix V, we use V^{-1} to denote its inverse; if V is singular, we use V^{-1} to denote its pseudo-inverse. We use $[N]$ for $N \in \mathbb{N}$ to denote $\{1, ..., N\}$, and $\{X_a\}_{a \in \mathcal{A}}$ to denote the set $\{(a, X_a) | a \in \mathcal{A}\}$. We say that $y = O(f(x))$ if there is x_0 and a constant C such that $y \leq Cf(x) \ \forall x > x_0$; we also use $\tilde{O}(f(x))$ to omit log factors.

Contextual Linear Bandits. We consider a contextual linear bandits problem over a horizon of length T [8], where at each iteration $t = 1, ..., T$, an agent, taking into account the context, chooses an action $a_t \in \mathcal{A}$ and receives a reward r_t. For each action $a \in \mathcal{A}$, the agent has access to a corresponding feature vector $X_{t,a} \in \mathbb{R}^d$. The set of all such vectors $\{X_{t,a}\}_{a \in \mathcal{A}}$ is the context at time t, and the agent can use it to decide which action a_t to play. We assume that the context is generated from a distribution, i.e., given a, $X_{t,a}$ is generated from a distribution $\mathcal{P}_a$. As a specific example, we could have that $a \in \mathbb{R}^d$ and $X_{t,a}$ is generated from a Gaussian distribution with zero mean and covariance matrix $\|a\|_2 I$, where I is the identity matrix, i.e., $\mathcal{P}_a = \mathcal{N}(0, \|a\|_2 I)$. The selection of a_t may depend not only on the current context $\{X_{t,a}\}_{a \in \mathcal{A}}$ but also on the history $H_t \triangleq \{\{X_{1,a}\}_{a \in \mathcal{A}}, a_1, r_1, ..., \{X_{t-1,a}\}_{a \in \mathcal{A}}, a_{t-1}, r_{t-1}\}$, namely, all previously selected actions, observed contexts and rewards. Once an action is selected, the reward is generated according to

$$r_t = \langle X_{t,a_t}, \theta_\star \rangle + \eta_t, \tag{1}$$

where $\langle ., . \rangle$ denotes the dot product, $\theta_\star$ is an unknown (but fixed) parameter vector in $\mathbb{R}^d$, and η_t is noise. We assume that the noise follows an unknown distribution with $\mathbb{E}[\eta_t | \mathcal{F}_t] = 0$ and $\mathbb{E}[\exp(\lambda \eta_t) | \mathcal{F}_t] \leq \exp(\lambda^2/2) \forall \lambda \in \mathbb{R}$, where $\mathcal{F}_t = \sigma(\{X_{1,a}\}_{a \in \mathcal{A}}, a_1, r_1, ..., \{X_{t,a}\}_{a \in \mathcal{A}}, a_t)$ is the filtration [13] of historic information up to time t, and $\sigma(X)$ is the σ-algebra generated by X [13].

The objective is to minimize the regret R_T over a horizon of length T, where

$$R_T = \sum_{t=1}^{T} \max_{a \in \mathcal{A}} \langle X_{t,a}, \theta_\star \rangle - \langle X_{t,a_t}, \theta_\star \rangle. \tag{2}$$

The best performing algorithms for this problem, such as LinUCB and contextual Thompson sampling, achieve a worst case regret of $\tilde{O}(d\sqrt{T})$ [29, 28, 1, 2]. The best known lower bound is $\Omega(d\sqrt{T})$ [37].

In the rest of this paper, we make the following assumptions that are standard in the literature [24].

Assumption 1. *We consider contextual linear bandits that satisfy:*
(1.) $\|X_{t,a}\|_2 \leq 1$, $\forall t \in [T]$, $a \in \mathcal{A}$.   **(2.)** $\|\theta_\star\|_2 \leq 1$.   **(3.)** $r_t \in [0, 1]$, $\forall t \in [T]$.

The boundedness assumption on r_t can be relaxed using [21], which only requires approximately 3.5 bits on average to send r_t, even if it is unbounded.

Memoryless Distributed Contextual Linear Bandits. We consider a distributed setting that consists of a central learner communicating with geographically separated agents. For example, the agents are drones that interact with a traffic policeman (central learner) as they fly by. We assume that the agents do not keep memory of past actions and may not be present for the whole duration of learning; learning in our setup can happen thanks to the persistent presence of the central learner.

At each time t, $t = 1 \ldots T$, a distributed agent joins the system; she receives from the central learner information on the system, such as the current estimate of the parameter vector $\theta_\star$ or the history H_t; she observes the current context $\{X_{t,a}\}_{a \in \mathcal{A}}$, selects and plays an action a_t and collects the corresponding reward r_t. Note that although the distributed agent knows the context $\{X_{t,a}\}_{a \in \mathcal{A}}$, the action a_t and the observed reward r_t, the central learner does not. The central learner may need this information to update its estimate of the system parameters, such as the unknown parameter vector θ_*, and the history H_{t+1}. However, we assume that the agent is restricted to utilize a communication-constrained channel and thus may not be able to send the full information to the central learner.

The main question we ask in this paper is: can we design a compression scheme, where the agent sends to the central learner only one message using B_t bits (for as small as possible a value of B_t) that enables the central learner to learn equally well (experience the same order of regret) as if there were no communication constraints? With no communication constraints the agent could send unquantized the full information $\{\{X_{t,a}\}_{a \in \mathcal{A}}, a_t, r_t\}$. Instead, the agent transmits a message that could be a function of all locally available information at the agent. For example, it could be a function of $(H_t, \{X_{t,a_t}\}_{a \in \mathcal{A}}, a_t, r_t)$, if the agent had received H_t from the central learner. It could also be a function of just (X_{t,a_t}, r_t), which could be sufficient if the central learner employs an algorithm such as LinUCB [1, 37]. In summary, we set the following goal.

Goal. Design contextual linear bandit schemes for the memoryless distributed setting that achieve the best known regret of $O(d\sqrt{T \log(T)})$, while communicating a small number of bits B_t.

We only impose communication constraints on the uplink communication (from the agents to the central learner) and assume no cost downlink communication (see discussion in Secttion 1).

Stochastic Quantizer (SQ) [16]. Our proposed algorithms use stochastic quantization, that we next review. We define $SQ_\ell, \ell \in \mathbb{N}$ to be a quantizer, that uses $\log(\ell + 1)$ bits, consisting of an encoder and decoder described as following. The encoder ξ_ℓ takes a value $x \in [0, \ell]$ and outputs an integer value

$$\xi_\ell = \begin{cases} \lfloor x \rfloor & \text{with probability } \lceil x \rceil - x \\ \lceil x \rceil & \text{with probability } x - \lfloor x \rfloor. \end{cases} \tag{3}$$

The output ξ_ℓ is represented with $\log(\ell + 1)$ bits. The decoder D_ℓ takes as input the binary representation of $\xi_\ell(x)$ and outputs the real value $\xi_\ell(x)$. The composition of the encoder ξ_ℓ, the binary mapping, and decoder D_ℓ is denoted by SQ_ℓ. We notice that since the decoder only inverts the binary mapping operation, we have that $SQ_\ell = \xi_\ell$. When SQ_ℓ is applied at the agents side, the agent encodes its data, x, as $\xi_\ell(x)$, then sends the corresponding binary mapping to the central learner that applies D_ℓ to get $SQ_\ell(x)$. With slightly abuse of notation, this operation is described in the paper, by saying that the agent sends SQ_ℓ to the central learner.

The quantizer SQ_ℓ is a form of dithering [16] and it has the following properties

$$\mathbb{E}[SQ_\ell(x)|x] = \lfloor x \rfloor(\lceil x \rceil - x) + \lceil x \rceil(x - \lfloor x \rfloor) = x(\lceil x \rceil - \lfloor x \rfloor) = x, \quad \text{and} \quad |SQ_\ell(x) - x| \le 1.$$

In particular, it conveys an unbiased estimate of the input with a difference that is bounded by 1 almost surely. We also define a generalization of SQ_ℓ denoted by $SQ_\ell^{[a,b]}$ where the input x of the encoder is in $[a, b]$ instead of $[0, \ell]$. The encoder first shifts and scales x using $\tilde{x} = \frac{\ell}{b-a}(x - a)$ to make it lie in $[0, \ell]$, then feeds $\tilde{x}$ to the encoder in (3). This operation is inverted at the decoder. It is easy to see that $SQ_\ell^{[a,b]}$ satisfies

$$\mathbb{E}[SQ_\ell^{[a,b]}(x)|x] = x, |SQ_\ell^{[a,b]}(x) - x| \le \frac{b-a}{\ell}.$$

3 Contextual Linear Bandits with Known Context Distribution

In this section, we show that if the central learner knows the distributions for the vectors $X_{t,a}$, then the agent does not need to convey the specific realization of the vector $X_{t,a}$ she observes at all - it is sufficient to just send 1 bit to convey some information on the observed reward and nothing else. But for this very limited communication, the central learner can experience the same order regret, as when receiving in full precision all the information that the agents have, namely, $R_T = O(d\sqrt{T \log T})$. Algorithm 1, that we describe in this section, provides a method to achieve this. Algorithm 1 is clearly optimal, as we cannot hope to use less than zero bits for the vector $X_{t,a}$.

Remark 1. Knowledge of the distribution of $X_{t,a}$ is possible in practice, since many times the context may be capturing well studied statistics (e.g., male or female, age, weight, income, race, dietary restrictions, emotional state, etc) - the advent of large data has made and will continue to make such distributions available. Similarly, actions may be finite (eg., restaurants to visit) or well described (e.g., released amounts of substances), and thus the distribution of $X_{t,a}$ could be derived. When the distribution is approximately known, we provide later in this section a bound on the misspefication performance penalty in terms of regret.

Main Idea. The intuition behind Algorithm 1 is that it reduces the multi-context linear bandit problem to a single context problem. In particular, it calls as a subroutine an algorithm we term Λ, that serves as a placeholder for any current (or future) bandit algorithm that achieves regret $O(d\sqrt{T \log T})$ for the case of a single context (for example, LinUCB [1, 37]). The central learner uses Λ to convey to the agents the information they need to select a good action. Our aim is to parametrize the single context problem appropriately, so that, by solving it we also solve our original problem.

Recall that in a single context problem, at each iteration t, any standard linear bandit algorithm Λ selects a feature vector (an action) x_t from a set of allowable actions $\mathcal{X}$, and observes a reward

$$r_t = \langle x_t, \theta'_\star \rangle + \eta_t, \tag{4}$$

where $\theta'_\star$ is an uknown parameter and η_t is noise that satisfies the same assumptions as in (1). The objective of Λ is to minimize the standard linear regret $R_T(\Lambda)$ over a horizon of length T, namely

$$R_T(\Lambda) = \sum_{t=1}^{T} \max_{x \in \mathcal{X}} \langle x, \theta'_\star \rangle - \langle x_t, \theta'_\star \rangle. \tag{5}$$

Our reduction proceeds as follows. We assume that Λ operates over the same horizon of length T and is parametrized by an unknown parameter $\theta'_\star$. We will design the action set $\mathcal{X}$ that we provide to Λ using our knowledge of the distributions $\mathcal{P}_a$[2] as we will describe later in (7). During each iteration, the central learner asks Λ to select an action $x_t \in \mathcal{X}$ and then provides to Λ a reward for this action (our design ensures that this reward satisfies (4) with $\theta'_\star = \theta_\star$). Λ operates with this information, oblivious to what else the central learner does. Yet, the action x_t is never actually played: the central learner uses the selected action x_t to create an updated estimate of the parameter vector $\hat{\theta}_t$, as we will describe later, and only sends this parameter vector estimate to the distributed agent. The agent observes her context, selects what action to play, and sends back her observed quantized reward to the central learner. This is the reward that the central learner provides to Λ. We design the set $\mathcal{X}$ and the agent operation to satisfy that: (4) holds; and $R_T - R_T(\Lambda)$ is small, where R_T is the regret for our original multi-context problem and $R_T(\Lambda)$ the regret of Λ. We next try to provide some intuition on how we achieve this.

We first describe how we construct the set $\mathcal{X}$. Let Θ be the set of all values that $\theta_\star$ could possibly take. For each possible parameter vector value $\theta \in \Theta$ the central learner considers the quantity

$$X^\star(\theta) = \mathbb{E}_{\{x_a : x_a \sim P_a\}} [\arg \max_{x \in \{x_a : a \in A\}} \langle x, \theta \rangle] \tag{6}$$

where x_a is the random variable that follows the distribution $\mathcal{P}_a$. Ties in (6) can be broken uniformly at random. In fact any pre-selected choice function would work as long as the same function is also used in step 12 of Algorithm 1. Note that the function $X^\star : \mathbb{R}^d \to \mathbb{R}^d$ can be computed offline before the learning starts, see Example 1. We then use

$$\mathcal{X} = \{X^\star(\theta) | \theta \in \Theta\}. \tag{7}$$

Intuitively, for each value of θ, we optimistically assume that the distributed agent may select the best possible realization $X_{t,a}$ for this θ (that has the expectation in (6)), and receive the associated reward; accordingly, we restrict the action space $\mathcal{X}$ of Λ to only contain the expectation of these "best" $X_{t,a}$. The vector $x_t \in \mathcal{X}$ may not actually be the vector corresponding to the action the agent selects; it is only used to convey to the agent an estimate of the unknown parameter $\hat{\theta}_t$ that satisfies $x_t = X^\star(\hat{\theta}_t)$. Although the central learner does not control which action the agent plays, this is influenced by $\hat{\theta}_t$; we show in App. B that X_{t,a_t} is an unbiased estimate of x_t, and the generated reward follows the linear model in (4) with $\theta'_\star = \theta_\star$. In Theorem 1, we prove that

$$\arg \max_{x \in \mathcal{X}} \langle x, \theta_\star \rangle = X^\star(\theta_\star). \tag{8}$$

---

[2]Recall that given a, $X_{t,a}$ is generated from distribution $\mathcal{P}_a$, see Section 2.

Hence, if Λ converges to selecting the best action for the single context problem, we will have that $\hat{\theta}_t$ converges to $\theta_\star$ if the maximizer in (8) is unique. If there are multiple values for θ with $X^\star(\theta) = X^\star(\theta_\star)$, we show in the proof of Theorem 1 that they all lead to the same expected reward for the original multi-context problem.

Example 1. Consider the case where $d = 1$, $\mathcal{A} = \{1, 2\}$, $X_{t,a} \in \{-1, 1\} \; \forall a \in \mathcal{A}$, $\Theta = \{-1, 1\}$, $\theta_\star = 1$ and $X_{t,1}$ takes the value -1 with probability p and 1 otherwise, while $X_{t,2}$ takes the values -1 with probability q and 1 otherwise. Then, we have that

$$\arg\max_{X_{t,a}}\langle X_{t,a}, 1\rangle = \left\{ \begin{array}{ll} 1 & \text{with probability } 1 - pq \\ -1 & \text{with probability } pq, \end{array} \right. \tag{9}$$

where we use the fact that if $\arg\max_{X_{t,a}}\langle X_{t,a}, 1\rangle \neq 1$, it must be the case that both $X_{t,1}$ and $X_{t,2}$ are -1. Thus, $X^\star(1) = \mathbb{E}[\arg\max_{X_{t,a}}\langle X_{t,a}, 1\rangle] = 1 - 2pq$, and similarly $X^\star(-1) = -1 + 2(1-p)(1-q)$, and hence, $\mathcal{X} = \{1 - 2pq, -1 + 2(1-p)(1-q)\}$. If Λ decides to pick $x_t = 1 - 2pq$, we have that $\hat{\theta}_t = 1$, otherwise $\hat{\theta}_t = -1$. This estimate $\hat{\theta}_t$ is then conveyed to the agent to help her pick the action.

Algorithm Operation. The pseudo-code is provided in Algorithm 1.
- First, the central learner calculates the function

$$X^\star(\theta) = \mathbb{E}_{\{x_a : x_a \sim P_a\}}[\arg\max_{x \in \{x_a : a \in A\}}\langle x, \theta\rangle], \tag{10}$$

and creates the action set $\mathcal{X} = \{X^\star(\theta)|\theta \in \Theta\}$ that algorithm Λ is going to use.
- At each time t, based on past history, Λ decides on a next action $x_t \in \mathcal{X}$. The central learner uses x_t to calculate the new update $\hat{\theta}_t = X^{-1}(x_t)$, where X^{-1} is the inverse of $X^\star$ (see Section 2).
- The agent receives $\hat{\theta}_t$ from the central learner, observes her context, plays an action $a_t = \arg\max_{a \in \mathcal{A}}\langle X_{t,a}, \hat{\theta}_t\rangle$, and observes the reward r_t. She then quantizes the reward using a stochastic quantizer SQ_1 (see Section 2), and communicates the outcome using one bit to the central learner.
- The central learner provides the quantized reward as input to Λ. Note that Λ is oblivious to what actions are actually played; it treats the received reward as corresponding to the action x_t it had decided.

Algorithm 1 Communication efficient for contextual linear bandits with known distribution

---
1: Input: an algorithm Λ for one context case, underlying set of actions $\mathcal{X}$, and time horizon T.
2: Initialize: $X^\star(\theta) = \mathbb{E}_{\{x_a : x_a \sim P_a\}}[\arg\max_{x \in \{x_a : a \in A\}}\langle x, \theta\rangle], \mathcal{X} = \{X^\star(\theta)|\theta \in \Theta\}, \hat{r}_0 = 0$.
3: Let X^{-1} be an inverse of $X^\star$.
4: **for** $t = 1 : T$ **do**
5:     **Central learner**:
6:         Receive $\hat{r}_{t-1}$ and provide it to Λ.
7:         Λ, using the history $(x_1, \hat{r}_1, ..., x_{t-1}, \hat{r}_{t-1})$, selects x_t.
8:         Send $\hat{\theta}_t = X^{-1}(x_t)$ to agent.
9:     **Agent**:
10:        Receive $\hat{\theta}_t$ from the central learner.
11:        Observe context realization $\{X_{t,a}\}_{a \in \mathcal{A}}$.
12:        Pull arm $a_t = \arg\max_{a \in \mathcal{A}}\langle X_{t,a}, \hat{\theta}_t\rangle$ and receive reward r_t.
13:        Send $\hat{r}_t = SQ_1(r_t)$ to the central learner using 1-bit.

The following theorem proves that Algorithm 1 achieves a regret $R_T(\Lambda) + O(\sqrt{T \log T})$, where $R_T(\Lambda)$ is the regret of Λ in (5). Hence, if Λ satisfies the best known regret bound of $O(d\sqrt{T \log T})$, e.g., LinUCB, Algorithm 1 achieves a regret of $O(d\sqrt{T \log T})$. The theorem holds under the mild set of assumptions that we stated in Section 2.

Theorem 1. *Algorithm 1 uses 1 bit per reward and 0 bits per context. Under Assumption 1, it achieves a regret $R_T = R_T(\Lambda) + O(\sqrt{T \log T})$ with probability at least $1 - \frac{1}{T}$.*

Proof outline. The complete proof is available in App. B. We next provide a short outline. From the definition of $X^\star$ in (10), we notice the following. Recall that the distributed agent receives $\hat{\theta}_t$ from the central learner, and pulls the best action for this $\hat{\theta}_t$, i.e., $a_t = \arg\max_{a \in \mathcal{A}}\langle X_{t,a}, \hat{\theta}_t\rangle$. We

show that conditioned on x_t, the associated vector X_{t,a_t} is an unbiased estimate of x_t with a small variance. Given this, we prove that $\hat{r}_t$ satisfies (6), and thus the rewards observed by Λ are generated according to a linear bandit model with unknown parameter that is the same as $\theta_\star$.

We next decompose the difference $R_T - R_T(\Lambda)$ to two terms: $\Sigma_T = \sum_{t=1}^{T}\langle \arg\max_{X_{t,a}}\langle X_{t,a}, \theta_\star\rangle, \theta_\star\rangle - \langle x_t, \theta_\star\rangle$ and $\Sigma'_T = \sum_{t=1}^{T}\langle \arg\max_{X_{t,a}}\langle X_{t,a}, \hat{\theta}_t\rangle, \theta_\star\rangle - \max_{x\in\mathcal{X}}\langle x, \theta_\star\rangle$. To bound the first term, we show that the unbiasdness property together with Assumption 1 implies that Σ_T is a martingale with bounded difference. This implies that $|\Sigma_T| = O(\sqrt{T\log T})$ with high probability. To bound Σ'_T, we first show that $\arg\max_{x\in\mathcal{X}}\langle x, \theta_\star\rangle = X^\star(\theta_\star)$ (we note that this is why the algorithm converges to $\hat{\theta}_t$ that is equal to, or results in the same expected reward as, $\theta_\star$). Then, following a similar approach, we can show that Σ'_T is a martingale with bounded difference which implies that $|\Sigma'_T| = O(\sqrt{T\log T})$ with high probability. $\qquad\square$

Downlink Communication. The downlink cost of our scheme is $O(d)$ (see App. B for discussion).

Operation Complexity. The main complexity that our algorithm adds beyond the complexity of Λ, is the computation of the function $X^\star$. For many practical distributions $\mathcal{P}_a$, this can be calculated efficiently. We discuss this in more details in App. B.

Imperfect Knowledge of Distributions. Since we only use the distributions to calculate $X^\star$, imperfect knowledge of distribution only affects us in the degree that it affects the calculation of $X^\star$. Suppose that we have an estimate $\tilde{X}^\star$ of $X^\star$ that satisfies

$$\sup_{\theta\in\Theta}\|X^\star(\theta) - \tilde{X}^\star(\theta)\|_2 \le \epsilon. \tag{11}$$

Using Theorem 1 we prove in App. B the following corollary.

Corollary 1. Suppose we are given $\tilde{X}^\star$ that satisfies (11). Then, there exists an algorithm Λ for which Algorithm 1 achieves $R_T = \tilde{O}(d\sqrt{T} + \epsilon T\sqrt{d})$ with probability at least $1 - \frac{1}{T}$.

Privacy. Our result may be useful for applications beyond communication efficiency; indeed, the context may contain private information (e.g., personal preferences, financial information, etc); use of our algorithm enables to not share this private information at all with the central learner, without impeding the learning process. Surprisingly, work in [48], motivated from privacy considerations, has shown that if an agent adds a small amount of zero mean noise to the true context before sending it to the central learner, this can severely affect the regret in some cases - and yet our algorithm essentially enables to "guess" the context with no regret penalty if the distributions are known. Although adding a zero mean noise to the observed feature vector conveys an unbiased estimate of the observation, the difference between this and our case is technical and mainly due to the fact that the unbiasdness is required to hold conditioned on the central learner observation (noisy context); see App. B for more details. We also discuss potential uses of our algorithm in preserving the context privacy in App B.

4 Contextual Linear Bandits with Unknown Context Distribution

We now consider the case where the learner does not know the context distributions, and thus Algorithm 1 that uses zero bits for the context cannot be applied. In this case, related literature conjectures a lower bound of $\Omega(d)$ [46, 47] – which is discouraging since it is probably impossible to establish an algorithm with communication logarithmically depending on d. Additionally, in practice we use $32d$ bits to convey full precision values - thus this conjecture indicates that in practice we may not be able to achieve order improvements in terms of bits communicated, without performance loss.

In this section, we provide Algorithm 2 that uses $\approx 5d$ bits per context and achieves (optimal) regret $R_T = O(d\sqrt{T\log T})$. We believe Algorithm 2 is interesting for two reasons:
1. In theory, we need an infinite number of bits to convey full precision values- we prove that a constant number of bits per dimension per context is sufficient. Previously best-known algorithms, which rely on constructing $1/T$-net for the set of feature vectors, use $O(d\log T)$ bits per context, which goes to infinity as T goes to infinity. Moreover, these algorithms require exponential complexity [24] while ours is computationally efficient.
2. In practice, especially for large values of d, reducing the number of bits conveyed from $32d$ to $\approx 5d$ is quite significant - this is a reduction by a factor of six, which implies six times less communication.

Main Idea. The intuition behind Algorithm 2 is the following. The central learner is going to use an estimate of the $d \times d$ least-squares matrix $V_t = \sum_{i=1}^{t} X_{i,a_i} X_{i,a_i}^T$ to update her estimates for the parameter vector $\theta_\star$. Thus, when quantizing the vector $X_{t,a}$, we want to make sure that not only this vector is conveyed with sufficient accuracy, but also that the central learner can calculate the matrix V_t accurately. In particular, we would like the central learner to be able to calculate an unbiased estimator for each entry of $X_{t,a}$ and each entry of the matrix V_t. Our algorithm achieves this by quantizing the feature vectors X_{t,a_t}, and also the diagonal (only the diagonal) entries of the least squares matrix V_t. We prove that by doing so, with only $\approx 5d$ bits we can provide an unbiased estimate and guarantee an $O(\frac{1}{\sqrt{d}})$ quantization error for each entry in the matrix almost surely.

Quantization Scheme. We here describe the proposed quantization scheme.

• *To quantize X_{t,a_t}:* Let $m \triangleq \lceil\sqrt{d}\rceil$. We first send the sign of each coordinate of X_{t,a_t} using d bits, namely, we send the vector $s_t = X_{t,a_t}/|X_{t,a_t}|$. To quantize the magnitude $|X_{t,a_t}|$, we scale each coordinate of $|X_{t,a_t}|$ by m and quantize it using a Stochastic Quantizer (SQ)[3] with $m+1$ levels in the interval $[0, m]$. Let $X_t \triangleq \mathrm{SQ}_m(m|X_{t,a_t}|)$ denote the resulting SQ outputs, we note that X_t takes non-negative integer values and lies in a norm-1 ball of radius $2d$ (this holds since the original vector lies in a norm-2 ball of radius 1 and the error in each coordinate is at most $1/m$). That is, it holds that $X_t \in \mathcal{Q} = \{x \in \mathbb{N}^d | \|x\|_1 \leq 2d\}$. We then use any enumeration $h : \mathcal{Q} \to [|\mathcal{Q}|]$ of this set to encode X_t using $\log(|\mathcal{Q}|)$ bits.

• *To quantize $X_{t,a_t} X_{t,a_t}^T$:* Let X_{t,a_t}^2 denote a vector that collects the diagonal entries of $X_{t,a_t} X_{t,a_t}^T$. Let $\hat{X}_t \triangleq s_t X_t / m$ be the estimate of X_{t,a_t} that the central learner retrieves. Note that $\hat{X}_t^2$ is not an unbiased estimate of X_{t,a_t}^2; however, $(X_{t,a_t}^2 - \hat{X}_t^2)_i \leq 3/m$ for all coordinates i (proved in App. C). Our scheme simply conveys the difference $X_{t,a_t}^2 - \hat{X}_t^2$ with 1 bit per coordinate using a $\mathrm{SQ}_1^{[-3/m,3/m]}$ quantizer.

The central learner and distributed agent operations are presented in Algorithm 2.

Example 2. Consider the case where $d = 5$. Then each coordinate of $|X_{t,a_t}|$ is scaled by 3 and quantized using SQ_3 to one of the values $0, 1, 2, 3$ to get X_t. The function h then maps the values for X_t that satisfy the $\|X_t\|_1 \leq 10$ to a unique value (a code) in the set $[|\mathcal{Q}|]$. For instance the value $3.\mathbf{1}$ is not given a code, where $\mathbf{1}$ is the vector of all ones. However, note that for $|X_{t,a_t}|$ to be mapped to $3.\mathbf{1}$, we must have $3|(X_{t,a_t})_i| \geq 2$ for all coordinates i, which cannot happen since it implies that $\|X_{t,a_t}\|_2 \geq 2\sqrt{5/6} > 1$ which contradicts Assumption 1.

Algorithm Performance. Theorem 2, stated next, holds under Assumption 1 in Section 2 and some additional regulatory assumptions on the distributions $\mathcal{P}_a$ provided in Assumption 2.

Assumption 2. *There exist constants c, c' such that for any sequence $\theta_1, ..., \theta_T$, where θ_t depends only on H_t, with probability at least $1 - \frac{c'}{T}$, it holds that*

$$\sum_{i=1}^{t} X_{i,a_i} X_{i,a_i}^T \geq \frac{ct}{d} I \quad \forall t \in [T], \tag{12}$$

where $a_t = \arg\max_{a \in \mathcal{A}} \langle X_{t,a}, \theta_t \rangle$, and I is the identity matrix.

We note that several common assumptions in the literature imply (12), for example, bounded eigenvalues for the covariance matrix of X_{t,a_t} [11, 27, 17]. Such assumptions hold for a wide range of distributions, including subgaussian distribitions with bounded density [36]. We discuss the challenge in relaxing this assumption in App. C.

Theorem 2. *Algorithm 2 satisfies that for all t: $X_t \in \mathcal{Q}$; and $B_t \leq 1 + \log_2(2d + 1) + 5.03d$ bits. Under assumptions 1, 2, it achieves a regret $R_T = O(d\sqrt{T \log T})$ with probability at least $1 - \frac{1}{T}$.*

Proof Outline. To bound the number of bits B_t, we first bound the size of $\mathcal{Q}$ by formulating a standard counting problem: we find the number of non-negative integer solutions for a linear equation. To bound the regret R_T, we start by proving that our quantization scheme guarantees some desirable properties, namely, unbiasedness and $O(\frac{1}{\sqrt{d}})$ quantization error for each vector coordinate. We then upper bound the regret in terms of $\|\hat{\theta}_t - \theta_\star\|_2$ and show that this difference can be decomposed as

$$\|\hat{\theta}_t - \theta_\star\|_2 = \|V_t^{-1}\|_2 (\| \sum_{i=1}^{t} E_i\|_2 + (1 + |\eta_i|)\| \sum_{i=1}^{t} e_i\|_2 + \| \sum_{i=1}^{t} \hat{\eta}_i X_{i,a_i}\|_2, \tag{13}$$

---

[3]As described in (3) in Section 2, SQ maps value x to an integer value, namely $\lfloor x \rfloor$ with probability $\lceil x \rceil - x$ and $\lceil x \rceil$ with probability $x - \lfloor x \rfloor$.

Algorithm 2 Communication efficient for contextual linear bandits with unknown distribution

---

1: Input: underlying set of actions $\mathcal{A}$, and time horizon T.
2: $\hat{\theta}_0 = 0, \tilde{V}_0 = 0, u_0 = 0, m = \lceil \sqrt{d} \rceil$.
3: Let h be an enumeration of the set $\mathcal{Q} = \{x \in \mathbb{N}^d | \|x\|_1 \le 2d\}$.
4: **for** $t = 1 : T$ **do**
5:     **Agent**:
6:         Receive $\hat{\theta}_{t-1}$ from the central learner.
7:         Observe context realization $\{X_{t,a}\}_{a \in \mathcal{A}}$.
8:         Pull arm $a_t = \arg\max_{a \in \mathcal{A}} \langle X_{t,a}, \hat{\theta}_{t-1} \rangle$ and receive reward r_t.
9:         Compute the signs $s_t = X_{t,a_t}/|X_{t,a_t}|$ of X_{t,a_t}.
10:         Let $X_t = \mathrm{SQ}_m(m|X_{t,a_t}|)$.
11:         $e_t^2 = \mathrm{SQ}_1^{[-3/m,3/m]}(X_{t,a_t}^2 - \hat{X}_t^2)$, where $\hat{X}_t = s_t X_t / m$.
12:         Send to the central learner $h(X_t)$, s_t, and e_t^2 using $\log_2(|\mathcal{Q}|)$, d, and d bits, respectively.
13:         Send $\hat{r}_t = \mathrm{SQ}_1(r_t)$ using 1-bit.
14:     **Central learner**:
15:         Receive X_t, s_t, e_t^2, and $\hat{r}_t$ from the distributed agent.
16:         $\hat{X}_t = s_t X_t / m$, $\hat{X}_t^{(D)} = \hat{X}_t^2 + e_t^2$.
17:         $u_t \leftarrow u_{t-1} + \hat{r}_t \hat{X}_t$.
18:         $\tilde{V}_t \leftarrow \tilde{V}_{t-1} + \hat{X}_t \hat{X}_t^T - \mathrm{diag}(\hat{X}_t \hat{X}_t^T) + \mathrm{diag}(\hat{X}_t^{(D)})$.
19:         $\hat{\theta}_t \leftarrow \tilde{V}_t^{-1} u_t$.
20:         Send $\hat{\theta}_t$ to the next agent.

---

where E_t captures the error in estimating the matrix $X_{t,a_t} X_{t,a_t}^T$, e_t is the error in estimating X_{t,a_t}, and η_t' is a noise that satisfies the same properties as η_t. Using Assumption 2, we prove that V_t^{-1} grows as $O(\frac{d}{t})$ with high probability, and from the unbiasdness and boundedness of all error quantities we show that they grow as $O(\sqrt{t \log t})$ with high probability. This implies that $\|\hat{\theta}_t - \theta_\star\|_2 = O(d\sqrt{\frac{\log t}{t}})$, and hence, $R_T = O(d\sqrt{T \log T})$. The complete proof is provided in App. C. $\qquad\square$

Algorithm Complexity. If we do not count the quantization operations, it is easy to see that the complexity of the rest of the algorithm is dominated by the complexity of computing V_t^{-1} which can be done in $O(d^{2.373})$ [4]. For the quantization, we note that each coordinate of X_t can be computed in $\tilde{O}(1)$ time[4]. Moreover, the computation of $h(x)$ for $x \in \mathcal{Q}$ can be done in constant time with high probability using hash tables, where h is the enumeration function in Step 3. Hence, the added computational complexity is almost linear in d. Although a hash table for h can consume $\Omega(2^{5d})$ memory, by sacrificing a constant factor in the number of bits, we can find enumeration functions that can be stored efficiently. As an example, consider the scheme in [14] that can find an one-to-one function $h : \mathcal{Q} \to \mathbb{N}^+$ which can be stored and computed efficiently, but only gives guarantees in expectation that $\mathbb{E}[\log(h(x))] = O(d)$ for all $x \in \mathcal{Q}$.

Downlink Communication Cost. Although we assume no-cost downlink communication, as was also the case for Algorithm 1, the downlink in Algorithm 2 is only used to send the updated parameter vector $\hat{\theta}_t$ to the agents. If desired, these estimates can be quantized using the same method as for X_{t,a_t}, which (following a similar proof to that of Theorem 2) can be shown to not affect the order of the regret while reducing the downlink communication to $\approx 5d$ bits per iteration.

Offloading To Agents. For applications where the agents wish to computationally help the central learner, the central learner may simply aggregate information to keep track of $u_t, \tilde{V}_t$ and broadcast these values to the agents; the estimate $\hat{\theta}_t$ can be calculated at each agent. Moving the computational load to the agents does not affect the regret order or the number of bits communicated on the uplink.

Remark 2. Under the regulatory assumptions in [17], the regret bound can be improved by a factor of $\sqrt{\log(K)/d}$, where $K = |\mathcal{A}|$ is the number of actions. However, this does not improve the regret in the worst case as the worst case number of actions is $O(C^d), C > 1$ [24].

---

[4]Multiplication by $\sqrt{d}$ can take $O(\log d)$ time.

References

[1] Y. Abbasi-Yadkori, D. Pál, and C. Szepesvári. Improved algorithms for linear stochastic bandits. *Advances in neural information processing systems*, 24, 2011.

[2] S. Agrawal and N. Goyal. Thompson sampling for contextual bandits with linear payoffs. In *International conference on machine learning*, pages 127–135. PMLR, 2013.

[3] D. Alistarh, D. Grubic, J. Li, R. Tomioka, and M. Vojnovic. Qsgd: Communication-efficient sgd via gradient quantization and encoding. *Advances in Neural Information Processing Systems*, 30, 2017.

[4] J. Alman and V. V. Williams. A refined laser method and faster matrix multiplication. In *Proceedings of the 2021 ACM-SIAM Symposium on Discrete Algorithms (SODA)*, pages 522–539. SIAM, 2021.

[5] A. Anandkumar, N. Michael, A. K. Tang, and A. Swami. Distributed algorithms for learning and cognitive medium access with logarithmic regret. *IEEE Journal on Selected Areas in Communications*, 29(4):731–745, 2011.

[6] V. Anantharam, P. Varaiya, and J. Walrand. Asymptotically efficient allocation rules for the multiarmed bandit problem with multiple plays-part i: Iid rewards. *IEEE Transactions on Automatic Control*, 32(11):968–976, 1987.

[7] M. H. Anisi, G. Abdul-Salaam, and A. H. Abdullah. A survey of wireless sensor network approaches and their energy consumption for monitoring farm fields in precision agriculture. *Precision Agriculture*, 16(2):216–238, 2015.

[8] P. Auer. Using confidence bounds for exploitation-exploration trade-offs. *Journal of Machine Learning Research*, 3(Nov):397–422, 2002.

[9] B. Awerbuch and R. D. Kleinberg. Adaptive routing with end-to-end feedback: Distributed learning and geometric approaches. In *Proceedings of the thirty-sixth annual ACM symposium on Theory of computing*, pages 45–53, 2004.

[10] D. Bouneffouf, I. Rish, and G. A. Cecchi. Bandit models of human behavior: Reward processing in mental disorders. In *International Conference on Artificial General Intelligence*, pages 237–248. Springer, 2017.

[11] Q. Ding, C.-J. Hsieh, and J. Sharpnack. An efficient algorithm for generalized linear bandit: Online stochastic gradient descent and thompson sampling. In *International Conference on Artificial Intelligence and Statistics*, pages 1585–1593. PMLR, 2021.

[12] A. Durand, C. Achilleos, D. Iacovides, K. Strati, G. D. Mitsis, and J. Pineau. Contextual bandits for adapting treatment in a mouse model of de novo carcinogenesis. In *Machine learning for healthcare conference*, pages 67–82. PMLR, 2018.

[13] R. Durrett. *Probability: theory and examples*, volume 49. Cambridge university press, 2019.

[14] P. Elias. Universal codeword sets and representations of the integers. *IEEE transactions on information theory*, 21(2):194–203, 1975.

[15] A. Gersho and R. M. Gray. *Vector quantization and signal compression*, volume 159. Springer Science & Business Media, 2012.

[16] R. M. Gray and T. G. Stockham. Dithered quantizers. *IEEE Transactions on Information Theory*, 39(3):805–812, 1993.

[17] Y. Han, Z. Zhou, Z. Zhou, J. Blanchet, P. W. Glynn, and Y. Ye. Sequential batch learning in finite-action linear contextual bandits. *arXiv preprint arXiv:2004.06321*, 2020.

[18] O. A. Hanna, Y. H. Ezzeldin, C. Fragouli, and S. Diggavi. Quantization of distributed data for learning. *IEEE Journal on Selected Areas in Information Theory*, 2(3):987–1001, 2021.

[19] O. A. Hanna, Y. H. Ezzeldin, T. Sadjadpour, C. Fragouli, and S. Diggavi. On distributed quantization for classification. *IEEE Journal on Selected Areas in Information Theory*, 1(1):237–249, 2020.

[20] O. A. Hanna, A. M. Girgis, C. Fragouli, and S. Diggavi. Differentially private stochastic linear bandits:(almost) for free. *arXiv preprint arXiv:2207.03445*, 2022.

[21] O. A. Hanna, L. Yang, and C. Fragouli. Solving multi-arm bandit using a few bits of communication. In *International Conference on Artificial Intelligence and Statistics*, pages 11215–11236. PMLR, 2022.

[22] T. J. Jech. *The axiom of choice*. Courier Corporation, 2008.

[23] P. C. Landgren. *Distributed multi-agent multi-armed bandits*. PhD thesis, Princeton University, 2019.

[24] T. Lattimore and C. Szepesvári. *Bandit algorithms*. Cambridge University Press, 2020.

[25] T. Le, C. Szepesvari, and R. Zheng. Sequential learning for multi-channel wireless network monitoring with channel switching costs. *IEEE Transactions on Signal Processing*, 62(22):5919–5929, 2014.

[26] F. Li, D. Yu, H. Yang, J. Yu, H. Karl, and X. Cheng. Multi-armed-bandit-based spectrum scheduling algorithms in wireless networks: A survey. *IEEE Wireless Communications*, 27(1):24–30, 2020.

[27] L. Li, Y. Lu, and D. Zhou. Provably optimal algorithms for generalized linear contextual bandits. In *International Conference on Machine Learning*, pages 2071–2080. PMLR, 2017.

[28] Y. Li, Y. Wang, X. Chen, and Y. Zhou. Tight regret bounds for infinite-armed linear contextual bandits. In *International Conference on Artificial Intelligence and Statistics*, pages 370–378. PMLR, 2021.

[29] Y. Li, Y. Wang, and Y. Zhou. Nearly minimax-optimal regret for linearly parameterized bandits. In *Conference on Learning Theory*, pages 2173–2174. PMLR, 2019.

[30] J. Mary, R. Gaudel, and P. Preux. Bandits and recommender systems. In *International Workshop on Machine Learning, Optimization and Big Data*, pages 325–336. Springer, 2015.

[31] P. Matikainen, P. M. Furlong, R. Sukthankar, and M. Hebert. Multi-armed recommendation bandits for selecting state machine policies for robotic systems. In *2013 IEEE International Conference on Robotics and Automation*, pages 4545–4551. IEEE, 2013.

[32] P. Mayekar and H. Tyagi. Ratq: A universal fixed-length quantizer for stochastic optimization. In *International Conference on Artificial Intelligence and Statistics*, pages 1399–1409. PMLR, 2020.

[33] T. D. Novlan, H. S. Dhillon, and J. G. Andrews. Analytical modeling of uplink cellular networks. *IEEE Transactions on Wireless Communications*, 12(6):2669–2679, 2013.

[34] A. N. Rafferty, H. Ying, and J. J. Williams. Bandit assignment for educational experiments: Benefits to students versus statistical power. In *International Conference on Artificial Intelligence in Education*, pages 286–290. Springer, 2018.

[35] W. Ren, X. Zhou, J. Liu, and N. B. Shroff. Multi-armed bandits with local differential privacy. *arXiv preprint arXiv:2007.03121*, 2020.

[36] Z. Ren and Z. Zhou. Dynamic batch learning in high-dimensional sparse linear contextual bandits. *arXiv preprint arXiv:2008.11918*, 2020.

[37] P. Rusmevichientong and J. N. Tsitsiklis. Linearly parameterized bandits. *Mathematics of Operations Research*, 35(2):395–411, 2010.

[38] T. Sajed and O. Sheffet. An optimal private stochastic-mab algorithm based on optimal private stopping rule. In *International Conference on Machine Learning*, pages 5579–5588. PMLR, 2019.

[39] S. Sajeev, J. Huang, N. Karampatziakis, M. Hall, S. Kochman, and W. Chen. Contextual bandit applications in a customer support bot. In *Proceedings of the 27th ACM SIGKDD Conference on Knowledge Discovery & Data Mining*, pages 3522–3530, 2021.

[40] F. Seide, H. Fu, J. Droppo, G. Li, and D. Yu. 1-bit stochastic gradient descent and its application to data-parallel distributed training of speech dnns. In *Fifteenth Annual Conference of the International Speech Communication Association*. Citeseer, 2014.

[41] S. Shahrampour, A. Rakhlin, and A. Jadbabaie. Multi-armed bandits in multi-agent networks. In *2017 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 2786–2790. IEEE, 2017.

[42] R. Shariff and O. Sheffet. Differentially private contextual linear bandits. *Advances in Neural Information Processing Systems*, 31, 2018.

[43] C. Shi and C. Shen. Federated multi-armed bandits. In *Proceedings of the 35th AAAI Conference on Artificial Intelligence (AAAI)*, 2021.

[44] J. Tenenbaum, H. Kaplan, Y. Mansour, and U. Stemmer. Differentially private multi-armed bandits in the shuffle model. *Advances in Neural Information Processing Systems*, 34:24956–24967, 2021.

[45] M. J. Wainwright. *High-dimensional statistics: A non-asymptotic viewpoint*, volume 48. Cambridge University Press, 2019.

[46] Y. Wang, J. Hu, X. Chen, and L. Wang. Distributed bandit learning: Near-optimal regret with efficient communication. In *International Conference on Learning Representations*, 2019.

[47] Y. Zhang, J. Duchi, M. I. Jordan, and M. J. Wainwright. Information-theoretic lower bounds for distributed statistical estimation with communication constraints. *Advances in Neural Information Processing Systems*, 26, 2013.

[48] K. Zheng, T. Cai, W. Huang, Z. Li, and L. Wang. Locally differentially private (contextual) bandits learning. *Advances in Neural Information Processing Systems*, 33:12300–12310, 2020.