Oracle-RLAIF: An Improved Fine-Tuning Framework for Multi-modal Video Models using Reinforcement Learning from Ranked Feedback

Abstract

Recent advances in large video-language models (VLMs) rely on extensive fine-tuning techniques that strengthen alignment between textual and visual comprehension. Many implementations typically begin with supervised fine-tuning (SFT) followed by reinforcement learning from preference data to enhance video comprehension. However, as VLMs scale in parameter size, so does the cost of gathering enough human feedback. To make fine-tuning more cost-effective, recent frameworks have explored reinforcement learning with AI feedback (RLAIF), which replace human preference with AI as a judge. Current RLAIF frameworks rely on a specialized reward model trained with video narratives to create calibrated scalar rewards– an expensive and restrictive pipeline. We propose Oracle-RLAIF, a novel framework that replaces the trained reward model with a more general Oracle ranker which acts as a drop-in model ranking candidate model responses rather than scoring them. Alongside Oracle-RLAIF, we introduce $GRPO_{rank}$, a novel rank-based loss function based on Group Relative Policy Optimization (GRPO) that directly optimizes ordinal feedback with rank-aware advantages. Empirically, we demonstrate that Oracle-RLAIF consistently outperforms leading VLM fine-tuning methods when evaluated across various video comprehension benchmarks. Oracle-RLAIF paves the path to creating flexible and data-efficient frameworks for aligning large multi-modal video models with reinforcement learning from rank rather than score.

1 Introduction

Current multi-modal foundation models are capable of providing fluent image captioning, accurate video question answering, and video reasoning capabilities (Ahn et al., 2024; Liu et al., 2023; Li et al., 2023b). Typically, the state-of-the-art (SOTA) models are additionally trained following a two-step process. First, supervised fine-tuning (SFT) through human-annotated videos allows video language models (VLMs) to produce syntactically correct and relevant answers (Luo et al., 2023). Next, following SFT, a reinforcement-learning-from-human-feedback (RLHF) (Ouyang et al., 2022) phase uses human preference over possible model outputs to further video comprehension in the VLM. Although human labeled responses provide quality ground-truth data, this method introduces substantial bottlenecks of labeling inefficiency and cost. As a result, a few works in the literature started to rely on AI judge models to replace human feedback– resulting in reinforcement-learning-from-AI-feedback (RLAIF) (Ahn et al., 2024). RLAIF consists of using a model capable of outputting a "reward" signal for an arbitrary prompt answer such that it can be used for fine-tuning. However, for many tasks, building a model capable of generating consistent and grounded rewards for any arbitrary combination of prompts and outputs has proven challenging (Shen et al., 2024; Chen et al., 2024).

We address these limitations by proposing a more flexible RLAIF framework called Oracle-RLAIF. Instead of relying on a fully functioning reward model capable of scoring any combination of prompts and responses, we only require an *Oracle model* capable of ranking responses in order of quality. This makes our framework broadly applicable to a variety of scenarios, including fine-tuning with feedback from a general-purpose

closed-source model (e.g. through a model API) or distilling knowledge from a larger legacy model into a smaller, more efficient model. Moreover, we introduce a novel GRPO extension we call $GRPO_{rank}$, which directly processes ranks from Oracle to effectively fine-tune the initial multi-modal model. Across multiple video evaluation datasets, our Oracle-RLAIF model directly outperforms previous state-of-the-art fine-tuned VLMs. Our contribution is three-fold and can be summarized as follows:

1. We introduce Oracle-RLAIF, a novel rank-based RLAIF framework, utilizing a drop-in Oracle ranker, relaxing the need of a fully-functional reward model for RLAIF fine-tuning.

2. We propose $GRPO_{rank}$, a robust GRPO modification, in which we directly process rank signals in the loss function

3. We extensively validate our proposed rank-based framework by training and evaluating our Oracle-RLAIF VLM. When directly compared to current fine-tuning techniques, Oracle-RLAIF improves video comprehension performance across benchmark datasets.

2 Background

We begin by providing all necessary background information for multi-modal learning as well as fine-tuning techniques for video language models. Additionally, we include in-depth description of the framework we build off and the specific limitations we address.

2.1 Multi-Modal Learning

Multi-modal learning trains models that can comprehend inputs from various modalities such as vision, audio and language (Radford et al., 2021; Alayrac et al., 2022; Li et al., 2023a). In video language models (VLMs), this means generating textual responses conditioned on visual information. These models typically comprise a vision encoder, which converts raw images into feature representations aligned with text (Radford et al., 2021; Li et al., 2023a), and a large language model (e.g., LLaMA, GPT (OpenAI, 2023; Touvron et al., 2023)) that generates responses based on those features.

To enhance video understanding, models are further trained via supervised fine-tuning (SFT) on video–question–answer triplets, grounding generation in visual reasoning tasks such as action detection or temporal comprehension. In recent work, to further align models, reinforcement learning after SFT has become necessary to achieve SOTA video question answering performance (Liu et al., 2023; Ahn et al., 2024).

2.2 Reinforcement Learning techniques for Fine-Tuning Video Language Models

After extensive training with supervised learning on labeled datasets, the model is capable of outputting contextually relevant answers. However, extensive spatial and temporal understanding is still limited. Two main frameworks have previously been implemented in reinforcement learning. Reinforcement Learning from Human Feedback (RLHF) is the process of using human feedback to choose a preferred response from two distinct model outputs for a given query (Figure 1-top). This preference dataset is then used to train the reward model (RM) which is finally used in reinforcement learning to fine-tune the initial policy VLM (Ouyang et al., 2022). Due to the high cost of human labeling, researchers have begun using RLAIF (Bai et al., 2022; Lee et al., 2023; Su et al., 2023) where a *context aware AI* replaces the human as the judge (Figure 1). Recently, VLM-RLAIF applied this to multi-modal models by scoring two candidate responses from an initial supervised fine-tuned VLM (VLM-SFT) using a context aware AI judge. VLM-RLAIF significantly improved video question-answering abilities when compared to VLM-SFT, and currently acheives state-of-the-art performance across various video datasets (Ahn et al., 2024).

For both human and AI feedback, the purpose of the preference data is to train a reward model to score answers; and then use those rewards to guide an initial VLM towards preferred answers [1] (Hong et al., 2025).

---

[1]Some RLHF techniques do not require an explicit reward model in memory, however they follow assumptions regarding the preference distribution, thus the same general problem stands (Rafailov et al., 2023)

Figure 1: Dataset creation pipelines for RLHF and RLAIF, illustrating how preferences are used to train reward models which are then used in the reinforcement learning loop to align the initial VLM.

When in possession of this reward model, any canonical RL algorithm can be used to fine-tune the model responses. In the LLM fine-tuning space, a few specific algorithms are widely used since they have been demonstrated to be effective.

Proximal Policy Optimization (PPO) (Schulman et al., 2017) is arguably the most prominent algorithm for LLM fine-tuning, and is also the algorithm employed by the original VLM-RLAIF framework. PPO maximizes expected reward using a clipped surrogate objective that discourages large deviations from the previous policy, approximating a trust-region constraint while promoting stable policy gradient updates. The loss function for PPO is:

$$\mathcal{L}_{\text{PPO}}(\theta) = \mathbb{E}_t\Big[\min\big(r_t(\theta)\,\hat{A}_t,\ \text{clip}\big(r_t(\theta), 1 - \varepsilon, 1 + \varepsilon\big)\hat{A}_t\big)\ - \beta\,D_{\text{KL}}\big[\,\pi_{\theta_{\text{old}}}\,\|\,\pi_\theta\big]\Big] \tag{1}$$

For a trajectory $\big(s_t, a_t\big)$ with return $\hat{R}_t$ and baseline value $V_\theta(s_t)$,

$$\hat{A}_t \ = \ \hat{R}_t - V_\phi(s_t), \qquad r_t(\theta) \ = \ \frac{\pi_\theta(a_t \mid s_t)}{\pi_{\theta_{\text{old}}}(a_t \mid s_t)} \tag{2}$$

The expected reward is represented through the advantage function $\hat{A}_t$, encoding how much better than the "average" action that particular action is expected to be. This policy optimization algorithm is used in the VLM-RLAIF framework to guide the initial SFT model based on rewards from the trained RM.

Group Relative Policy Optimization (GRPO) (Shao et al., 2024) addresses some limitations of PPO including unstable updates from reward magnitudes and the requirement of a trained value function to compute advantage. As introduced by DeepSeekMath, GRPO extends PPO to token probabilities $\boldsymbol{o_t}$ over $\boldsymbol{G_i}$ candidate responses for one query $\boldsymbol{q}$.

$$\mathcal{L}_{\text{GRPO}}(\theta) = \frac{1}{G}\sum_{i=1}^{G}\left[\frac{1}{|o_i|}\sum_{t=1}^{|o_i|}\Big\{\min\big(r_t(\theta)\hat{\boldsymbol{A}}_{\boldsymbol{i,t}},\ \text{clip}\,(r_t(\theta), 1 - \epsilon,\ 1 + \epsilon)\,\hat{\boldsymbol{A}}_{\boldsymbol{i,t}}\big)\Big\}\right.$$

$$\left. - \beta \cdot D_{\text{KL}}\left[\pi_{\theta_{\text{old}}}(\cdot \mid \boldsymbol{q})\,\|\,\pi_\theta(\cdot \mid \boldsymbol{q})\right] + c_{\text{entropy}} \cdot \mathcal{H}[\pi_\theta(\cdot \mid \boldsymbol{q})]\right] \tag{3}$$

where the policy importance ratio is defined as:

$$r_t(\theta) = \frac{\pi_\theta(o_{i,t} \mid \boldsymbol{q}, o_{i,<t})}{\pi_{\theta_{\text{old}}}(o_{i,t} \mid \boldsymbol{q}, o_{i,<t})} \tag{4}$$

and the advantage uses **normalized reward**

$$\hat{\boldsymbol{A}}_{\boldsymbol{i,t}} = \frac{R(\boldsymbol{q}, o_i) - \mu_R(\boldsymbol{q})}{\sigma_R(\boldsymbol{q})} \tag{5}$$

where:

Since rewards are rescaled per-query, GRPO is robust to varying reward magnitudes and eliminates the need for a separate value function (Eq 5). Used by DeepSeek to finetune their R1 reasoning models, GRPO has already been proven effective for LLM post-training alignment (DeepSeek-AI, 2025).

Direct Preference Optimization (DPO) (Rafailov et al., 2023) is another popular algorithm used in LLM fine-tuning, built explicitly to eliminate the need for a trained reward model. DPO replaces the reward function with a preference loss, creating a binary cross entropy objective which optimizes based directly on preference pairs (y_w, y_l).

$$\mathcal{L}_{\text{DPO}}(\theta) = -\mathbb{E}(x, y_w, y_l) \sim \mathcal{D}! \left[\log \sigma \left(\beta \log \frac{\pi_\theta(y_w \mid x)}{\pi_{\text{ref}}(y_w \mid x)}; -; \beta \log \frac{\pi_\theta(y_l \mid x)}{\pi_{\text{ref}}(y_l \mid x)} \right) \right] \tag{6}$$

3 RLAIF through Oracle Preferences

Figure 2: The general pipeline of fine tuning the initial policy VLM using Oracle-RLAIF. The light blue shading on the left indicates SFT training already applied to the initial policy VLM. The cyan shading on the right represents fine-tuning using our RLAIF Oracle ranker pipeline.

We propose the Oracle-RLAIF fine-tuning framework that replaces the traditional trained Reward Model (RM) with a drop-in Oracle ranker. We assume the Oracle ranker- whether a larger closed source model or a legacy system- can accurately rank the response quality conditioned on the prompt and visual context. Crucially, unlike frameworks such as VLM-RLAIF (Ahn et al., 2024), Oracle-RLAIF eliminates the need for auxiliary reward or value functions. Instead, it operates purely on the interaction between the initial

Supervised Fine-Tuned (SFT) policy and the external ranker. By modifying the standard RLAIF loop to leverage direct rank-based supervision, the iterative fine-tuning process proceeds as follows:

1. Response Generation (Exploration) For a given visual and textual prompt, the current policy (the SFT model) generates N candidate responses. This allows the model to explore its own generation space.

2. Oracle Ranking (Ground Truth) A stronger multi-modal Oracle model (e.g., GPT-4o) evaluates the N responses. It ranks them based on quality and relevance to the visual input. These rankings are treated as the ground truth rankings.

3. Policy ranking (Prediction) The policy model calculates the internal log-probabilities for each of its own generated responses. These probabilities are sorted to produce the predicted rankings, representing the model's perceived confidence in its outputs.

4. Rank-based Optimization Our proposed loss function (Eq 7) compares the predicted rankings against the ground truth rankings. This signal updates the policy to align its internal confidence (log-probs) with the Oracle's external quality assessment.

Algorithm 1 Oracle-RLAIF

Require: Pretrained SFT Video Language Model π_{SFT} (Policy Initialization)
Require: Oracle Model $\mathcal{O}_\phi$ (e.g., ChatGPT-4o)
Require: Multimodal Dataset $\mathcal{D} = \{(v, q)\}$ (Video, Question)
1: Initialize policy model: $\pi_\theta \leftarrow \pi_{\text{SFT}}$
2: **for** each prompt $(v, q) \in \mathcal{D}_b$ **do**
3:     **Step 1: Generation**
4:     Generate G responses $\{o_i\}_{i=1}^G$ from $\pi_\theta(\cdot \mid v, q)$
5:     **Step 2: Ground Truth Ranking (Oracle)**
6:     Query $\mathcal{O}_\phi$ to rank $\{o_i\}$ based on quality and relevance to visual input v.
7:     Define ground truth ranking vector: $\mathbf{r}^* = [rank_{\text{oracle}}(o_1), \ldots, rank_{\text{oracle}}(o_G)]$
8:     **Step 3: Predicted Ranking (Policy)**
9:     Compute log-probabilities for each response under current policy:

$$\ell_i = \sum_{t=1}^{|o_i|} \log \pi_\theta(o_{i,t} \mid o_{i,<t}, v, q) \quad \forall i \in \{1, \ldots, G\}$$

10:     Derive predicted rankings $\hat{\mathbf{r}}$ by sorting $\boldsymbol{\ell}$ descending:

$$\hat{\mathbf{r}} = \text{argsort}_{\text{desc}}(\boldsymbol{\ell})$$

11:     **Step 4: Policy Optimization**
12:     Update policy parameters θ using a generic rank-alignment algorithm (e.g., DPO, PRO) that minimizes the divergence between the predicted rank $\hat{\mathbf{r}}$ and oracle rank $\mathbf{r}^*$:

$$\theta \leftarrow \text{PolicyOptimizer}\left(\pi_\theta, \underbrace{\mathbf{r}^*}_{\text{Ground Truth}}, \underbrace{\hat{\mathbf{r}}}_{\text{Predicted}}\right)$$

13: **end for**
14: **return** final policy π_θ

---

4 Fine-tuning Policy Models using Oracle Ranking

Since our Oracle provides ranked feedback rather than absolute scores, traditional methods like PPO are incompatible. To address this, we look to Group Relative Policy Optimization (GRPO), which already relies on comparing candidate responses within a group. We extend this relational paradigm to create $GRPO_{rank}$,

where we build off rank intuitions to modify the calculation of the advantage function. We expand on these intuitions in the next subsection.

4.1 Rank Adapted GRPO Objective

We introduce $GRPO_{rank}$ to optimize the policy within our Oracle-RLAIF framework. It applies non-linear penalization of rank errors, assigning larger penalties and smaller advantages when the predicted rank deviates more from the Oracle ground truth. It also penalizes false promotion of low-quality responses, encouraging the model to both prioritize high-quality outputs and suppress poor ones. To capture these intuitions, we use a normalized Discounted Cumulative Gain (nDCG) penalty that compares the *predicted rank* (based on the model's internal log probabilities) to the *ground-truth rank* assessed by the more powerful Oracle ranker. This penalty captures both position sensitivity and error severity, and is used to construct the advantage function for our policy gradient updates.

For stability, $GRPO_{rank}$ generates on-policy responses while using a frozen reference policy for importance sampling. Our loss function modifies the original GRPO loss(Eq 3) by replacing the advantage term with $\hat{A}_{\text{rank}}$:

$$\mathcal{L}_{GRPO_{rank}}(\theta) = \frac{1}{G} \sum_{i=1}^{G} \left[\frac{1}{|o_i|} \sum_{t=1}^{|o_i|} \left\{ \min\left(r_t(\theta)\hat{A}_{rank},\ \text{clip}\left(r_t(\theta), 1-\epsilon,\ 1+\epsilon\right)\hat{A}_{rank}\right) \right\} \right.$$
$$\left. - \beta \cdot D_{\text{KL}}\left[\pi_{\theta_{\text{old}}}(\cdot \mid \boldsymbol{q}) \,\|\, \pi_\theta(\cdot \mid \boldsymbol{q})\right] + c_{\text{entropy}} \cdot \mathcal{H}[\pi_\theta(\cdot \mid \boldsymbol{q})] \right] \tag{7}$$

The advantage function $\hat{A}_{\text{rank}}$ in $GRPO_{rank}$ measures how much better each response i is when compared to the model's "average response" and is defined as:

$$\hat{A}_{\text{rank}} = \mathbb{E}_{j \in G_i}[\delta_j] - \delta_i \tag{8}$$

with the expected group penalty for K responses within group G_i:

$$\mathbb{E}_{j \in G_i}[\delta_j] = \frac{1}{K} \sum_{j \in G_i} \delta_j \tag{9}$$

and the penalty term δ_i represents the deviation of the model's predicted rankings from the Oracle's ranking. This penalty is calculated using normalized Discounted Cumulative Gain (nDCG):

$$\delta_i = 1 - \text{nDCG}_i = 1 - \frac{\text{DCG}(\hat{\text{rank}}_i)}{\text{DCG}(\text{rank}_i)} \tag{10}$$

where $\hat{\text{rank}}_i \in \{0, \ldots, K-1\}$ is the model's predicted ranking computed from ordering the policy model's internal log probabilities and $\text{rank}_i \in \{0, \ldots, K-1\}$ is from the Oracle ranker. Finally, DCG is computed as:

$$\text{DCG}(\text{rank}) = \frac{\frac{1}{1+\text{rank}}}{\log_2(2 + \text{rank})} \tag{11}$$

Algorithm 2 Rank-GRPO Optimization Step

Require: Policy π_θ, Reference π_{ref}, Responses $\{o_i\}_{i=1}^{G}$
Require: Ground Truth Ranks $\mathbf{r}^*$ (Oracle) and Predicted Ranks $\hat{\mathbf{r}}$ (Policy)
 1: **1. Compute Rank Penalties (nDCG Deviation)**
 2: **for** each response $i \in \{1, \ldots, G\}$ **do**
 3:     Calculate penalty δ_i based on deviation between $\hat{\text{rank}}_i$ and rank_i:

$$\delta_i = 1 - \frac{\text{DCG}(\hat{\text{rank}}_i)}{\text{DCG}(\text{rank}_i)} \quad \text{(Eq. 10)}$$

 4: **end for**
 5: **2. Compute Group Advantages**
 6: Calculate average group penalty $\bar{\delta} = \frac{1}{G}\sum_{j=1}^{G}\delta_j$
 7: **for** each response $i \in \{1, \ldots, G\}$ **do**
 8:     Compute advantage by subtracting individual penalty from group average:

$$\hat{A}_{\text{rank}}^{(i)} = \bar{\delta} - \delta_i \quad \text{(Eq. 8)}$$

 9: **end for**
10: **3. Update Policy**
11: Update π_θ by minimizing the Rank-GRPO loss defined in Eq. 7

We detail the iterative $GRPO_{rank}$ fine-tuning algorithm in Algorithm 2 In each epoch, batches of prompts are sampled, and candidate responses are generated using the current policy model. The *Oracle model* provides relative rankings over responses in each group, from which nDCG-based penalties are computed. These penalties are then used to define an advantage function $\hat{A}_{\text{rank}}$, which captures how much better or worse each response is compared to the average performance in its group. The policy is then updated by maximizing a clipped surrogate objective (Eq. 7), incorporating KL and entropy regularization to ensure stability. This allows the model to iteratively prefer responses ranked higher by the oracle while preventing large policy deviations.

4.2 Mathematical Properties

To further understand the motivation behind the elements in our $GRPO_{rank}$ objective, we highlight key mathematical properties that guided our formulation. This section explains the desired properties and how our formulation satisfies them. Additional examples from Appendix A.2 illustrate advantages via hypothetical rank configurations.

1. Zero-Sum Property Within Groups. Our advantage formulation:
$$\hat{A}_{\text{rank}} = \mathbb{E}_{j \in G_i}[\delta_j] - \delta_i$$
ensures that total advantage across group members sums to zero, enforcing relative comparison within each group:

$$\sum_{i \in G}\hat{A}_{i,t} = \sum_{i \in G}\left(\mathbb{E}_{j \in G}[\delta_j] - \delta_i\right) = K \cdot \mathbb{E}_{j \in G}[\delta_j] - \sum_{i \in G}\delta_i = K \cdot \left(\frac{1}{K}\sum_{j \in G}\delta_j\right) - \sum_{i \in G}\delta_i = 0$$

2. Boundedness of Penalty. Since $\text{rank}_i, \hat{\text{rank}}_i \in \{0, \ldots, K-1\}$, DCG values fall in:

$$\text{DCG}_i \in \left[\frac{1}{(1+K-1)\cdot \log_2(K+1)}, 1\right]$$

Thus the normalized DCG, $\text{nDCG}_i = \frac{\text{DCG}_i(\hat{\text{rank}}_i)}{\text{DCG}_i(\text{rank}_i)} \in (0, 1]$, leading to bounded penalties:

$$\delta_i = 1 - \text{nDCG}_i \in [0, 1)$$

ensuring numerically stable and interpretable advantage values.

3. Position-Sensitive Discounting.   The use of logarithmic discounting in:

$$\text{DCG}(\text{rank}) = \frac{\frac{1}{1+\text{rank}}}{\log_2(2 + \text{rank})} \tag{12}$$

ensures that rank errors at the top are penalized exponentially more than those at the bottom. This encodes our preference to rank correctly the top answers, which are the ones that will be displayed to the user, while the relative rankings of worse answers are not as important; for example:

$$\text{True Rank 0, Predicted Rank 1:} \quad \text{nDCG} = 0.7925 \Rightarrow \delta = 0.2075$$
$$\text{True Rank 4, Predicted Rank 3:} \quad \text{nDCG} = 0.9757 \Rightarrow \delta = 0.0243$$

Finally, the highest penalty originates from a low-ranked high-quality response; for example:

$$\text{True Rank 0, Predicted Rank 4:} \quad \text{nDCG} = 0.5170 \Rightarrow \delta = 0.4830$$

5   Empirical Evaluation

The primary goal in our experimentation is to assess the effectiveness of Oracle-RLAIF compared to leading fine-tuning frameworks for VLMs– specifically VLM-RLAIF. We benchmark using datasets which test a model's capacity to interpret and describe visual events. To compare Oracle-RLAIF against VLM-RLAIF, we apply both frameworks to the same initial SFT policy model in (Figure 2), taken from the VLM-SFT 7B checkpoint as published in Ahn et al. (2024). Additionally, we compare against reported results of other strong baselines, assessing the contribution of our rank-based policy optimization approach.

Evaluation Protocol   Since our main purpose is to evaluate the fine-tuning performance of our proposal compared to VLM-RLAIF, we start both approaches with the same SFT model (the VLM-SFT 7B checkpoint as published in Ahn et al. (2024)). From there, VLM-RLAIF is trained as described in their paper (Appendix A.1) with the released public implementation– with only a few training configurations modified below. Thus we use their publicly released and pre-trained reward model to train VLM-RLAIF for 4 epochs and a rollout batch size of 64 for more frequent gradient updates (modified from 1 epoch and 256 batch size in the original publication to allow for more policy updates)

In reinforcement learning for Oracle-RLAIF, our initial SFT model outputs 5 candidate responses which are ranked by our drop in Oracle ranker. In our implementation, the Oracle ranker is ChatGPT-4o. We provide the Oracle ranker with the images and candidate responses related to the query. The Oracle model contains a comprehensive system message to strictly rank the candidate responses. These ranks are then fed into Rank-GRPO as the ground truth ranks which are compared to the internal model predicted ranks.

A primary motivation of the Oracle-RLAIF framework is to enable fine-tuning of large video language models through reinforcement learning without the added complexity of a trained reward model. In this context, Direct Preference Optimization (DPO) stands out as the prevalent standard for reward-model-free alignment, however we hypothesized the implementation of DPO was insufficient due to distribution shifts. Therefore, we include a DPO baseline to directly compare to the effectiveness of Oracle-RLAIF using our proposed $GRPO_{rank}$ (Eq 7). To maintain consistency with Oracle-RLAIF, the preference is provided by the same oracle API ChatGPT-4o with identical system messages, and we call this baseline *Oracle-DPO*.

All models are trained using 4×NVIDIA H100 80GB GPUs with *Quantized Low-Rank Adapter (QLoRA)* (Dettmers et al., 2023), which enables efficient fine-tuning by combining 4-bit quantization with low-rank adapters. The fully trained models are then evaluated as described in the next subsections.

Evaluation Datasets and Benchmarks   We compared the models across two distinct evaluation regimes. In the first, we follow the evaluation pipeline used in VLM-RLAIF by benchmarking across MSVD, MSRVTT, and ActivityNet (Wu et al., 2017; Xu et al., 2016; Yu et al., 2019) video question answering datasets which

target action recognition, temporal reasoning, and overall multi-modal understanding. Since the benchmark uses open-ended questions, the model's responses must be evaluated by an LLM (in this case GPT-4o) in comparison to human-annotated ground-truth labels. This follows the methodology described in Li et al. (2023c). The LLM as a judge considers five key dimensions (response relevance to video content, detail capture, contextual understanding, temporal reasoning, and consistency) to create a numeric score from 0 to 5 as well as a binary "yes" or "no" indicating correct response.

In the second evaluation regime, we instead benchmark against the better performing "final" checkpoint of the VLM-RLAIF 7B model as trained and evaluated by the authors.[2] In this comparison, we take advantage of a more contemporary dataset Video-MME (Fu et al., 2025) which was not available at the time of VLM-RLAIF's publication. By design, Video-MME does not originate from existing video evaluation datasets, allowing no possibility of data leakage into training. Additionally, unlike prior benchmarks which rely on GPT-judged open-ended answers, Video-MME establishes objective and reproducible evaluation through multiple choice question answering. Thus, we are able to directly compare accuracy across categories without relying on language model judgements. Video-MME is currently widely used for benchmarking, and we consider this our most meaningful experiment.

Table 1: Performance of Oracle-RLAIF versus baseline VLMs in zero-shot question answering across MSVD, MSRVTT, and ActivityNet.

Model	Fine-tuning method	MSVD-QA		MSRVTT-QA		ActivityNet-QA	
		Acc.	Score	Acc.	Score	Acc.	Score
VideoLLaMA ((Zhang et al., 2024))	SFT	51.6	2.5	29.6	1.8	12.4	1.1
Video-ChatGPT ((Maaz et al., 2023))	SFT	64.9	3.3	49.3	2.9	35.2	2.7
BT-Adapter ((Liu et al., 2024b))	SFT	67.5	3.7	57.0	3.2	45.7	3.2
Video-LLaVA ((Lin et al., 2024))	SFT	70.7	3.9	59.2	3.5	45.3	3.3
LLaMA-VID ((Li et al., 2024))	SFT	69.7	3.7	57.7	3.2	47.4	3.23
VideoChat2 ((Li et al., 2023b))	SFT	70.0	3.9	54.1	3.3	49.1	3.3
VLM-SFT (baseline)	SFT	67.2	3.6	52.4	3.0	44.1	3.2
VLM-RLAIF	RLAIF (PPO)	68.5	3.6	54.2	3.1	46.1	3.4
Oracle-DPO	RLAIF (DPO)	64.7	3.4	53.2	3.1	40.1	2.9
Oracle-RLAIF	RLAIF ($GRPO_{rank}$)	**73.5**	**4.0**	**60.8**	**3.8**	**48.0**	**3.5**
Δ (Oracle $-$ VLM-RLAIF)		**+5.0%**	**+0.4**	**+5.6%**	**+0.7**	**+1.9%**	**+0.1**

Detailed Analysis Table 1 shows the results for our first experiment.[3] Oracle-RLAIF outperforms all baselines we evaluated in video-question answering performance. Specifically, we observe consistent gains across all three benchmarks when compared to our reproduced VLM-RLAIF model following the author's framework. This demonstrates that our rank-based optimization approach yields more effective policy updates compared to VLM-RLAIF, which employs scalar reward modeling and PPO updates. The original VLM-RLAIF publication reports significantly better results than we could achieve on ActivityNet— which we attribute to the use of ActivityNet caption data in their reward model training which we omitted, thus creating unfair evaluation within this dataset.

Therefore, in our second experiment reported in Table 2, we use Video-MME ensuring no data leakage from training to evaluation. Here, Oracle-RLAIF significantly outperforms the original VLM-RLAIF checkpoint, demonstrating superior generalization and robustness. Overall, Oracle-RLAIF achieves a +6.2% percent improvement in average accuracy, with significant improvements in *Temporal Perception* (+21.2%), *Action Recognition* (+11.7%), and *Object Reasoning* (+11.2%)– tasks which involve physical actions and causal

---

[2]Despite our best attempt to replicate the results in the original paper using the public implementation, a few key scripts were missing causing slightly lower performances than the final published checkpoint. In the second evaluation, however, we use the best performing model, even though we could not replicate its training.

[3]We do not replicate experiments for all models that are not bolded, and instead report their published results from prior works.

Table 2: Video-MME: performance comparison across short and medium videos

Category	Oracle-DPO	VLM-RLAIF	Oracle-RLAIF	Δ(Oracle-VLM-RLAIF)
Temporal Perception	**71.0%**	49.8%	70.0%	+20.2
Action Recognition	39.0%	27.3%	**42.3%**	+15.0
Object Reasoning	46.5%	38.3%	**49.2%**	+11.0
Object Recognition	46.0%	35.2%	**48.8%**	+13.6
Counting Problem	27.1%	19.4%	**29.5%**	+10.1
OCR Problems	**38.1%**	34.6%	37.8%	+3.2
Attribute Perception	40.2%	39.4%	**42.3%**	+2.9
Temporal Reasoning	27.9%	27.7%	**30.1%**	+2.4
Action Reasoning	30.5%	31.8%	**33.8%**	+2.0
Information Synopsis	48.5%	**49.4%**	48.0%	-1.4
Spatial Perception	32.5%	**35.1%**	33.0%	-2.1
Spatial Reasoning	50.2%	**55.0%**	53.7%	-1.3
Overall Accuracy	41.4%	36.9%	**43.2%**	+6.3

events. For instance, Oracle-RLAIF accurately answers questions such as "*Which action is not included in the third magic trick?*" from *Action Recognition*, and successfully understands time-based cues in questions like "*In which part of the video is the woman in the blue top interviewed?*" from *Temporal Perception*. These improvements results point to the core strength of our rank-based optimization to, which improves model alignment with temporally and causally grounded responses. These results point to the core strength of our rank-based optimization to improve model alignment with temporally and causally grounded responses.

In contrast, Oracle-RLAIF shows performance declines in *Spatial Perception*, *Spatial Reasoning*, and *Information Synopsis*. We hypothesize that these categories contain higher ambiguity or abstraction, causing rank-based optimization to be less effective. For example, *Spatial Reasoning* questions such as "*What holiday was the video most likely recorded during?*" or "*What can be inferred about the setting from the lighting and background?*" rely on implicit cues that are not effectively optimized through relative ranking. Furthermore, we hypothesize the slight divergence in improvement may stem from a scarcity of high-quality training samples in those specific domains. Similarly, tasks requiring spatial awareness across frames may benefit from further investigation into architectural adjustments. All together, further investigation is necessary to mitigate this drop in performance, however, the general performance gains strongly validate our framework's efficacy in multi-modal video understanding.

6 Ablation Studies

After running the previous experiments, we conducted further ablations within the reinforcement learning process. Specifically, we investigate replacing the oracle api ranker with a trained reward model, comparing policy optimization algorithms, and specifics within $GRPO_{rank}$.

6.1 Replacing the Oracle ranker with Trained RM

By comparing against VLM-RLAIF, we already assessed the effectiveness of our Oracle ranker and $GRPO_{rank}$ relative to a learned reward model (RM) and PPO-based optimization. In this ablation, we replace the Oracle API with a trained reward model, in order to answer the important question: does Oracle-RLAIF benefit from using a calibrated reward model, or is a legacy API sufficient as the ranking signal?

We adopt the reward model released in the open-source implementation of Ahn et al. (2024), which is trained to assign a scalar reward to candidate responses. To integrate this RM into our ranking-based RLAIF setup with $GRPO_{rank}$ (Eq. 7), we convert the scalar reward scores into rankings by sorting candidates according to their predicted reward. During evaluation, we report accuracy across the same VQA benchmarks used in Table 1.

Figure 3: Comparison of Oracle-based alignment methods across video benchmarks.

As shown in Figure 3, the direct API-based Oracle consistently matches or exceeds the performance of the trained Reward Model across all benchmarks. This confirms our hypothesis that the intrinsic reasoning capabilities of a strong general-purpose API are sufficient to provide high-quality ranking signals. Consequently, we can achieve effective preference optimization without the additional computational overhead and complexity of training and calibrating a dedicated reward model to use as our Oracle.

6.2 Number of Return Sequences in $GRPO_{rank}$

In Oracle-RLAIF, a large computational overhead comes from the N candidate responses produced in the fine-tuning process. Thus, we hope to optimize the amount of responses to capture variances in output, while minimizing the cost as well. We vary the number of return sequences (RS) using 3, 4, 5, and 10 and report the corresponding performances on various VQA datasets.

Figure 4: Performance comparison of Oracle-RS variants across benchmarks.

Figure 4 demonstrates that performance generally improves with an increased number return sequences from 3 to 5, but drops off when increased to 10. Therefore, we employ Oracle-5RS in our experiments to maximize absolute VQA accuracy; however, Oracle-4RS serves as a viable alternative where computational efficiency is prioritized, delivering comparable results with lower generation costs.

7 Related Works

Our work builds on a growing body of literature exploring alignment through preferences, rankings, and human feedback. Most prior approaches to learning from preference signals rely on scalar reward modeling or supervised objectives, limiting their ability to use key rank intuitions during optimization. The core innovation of Oracle-RLAIF lies in directly leveraging rank signal and hierarchical ordering in our proposed loss function, without pre-processing or transformation. While prior work has utilized rating-based feedback (Luu et al., 2025; Xu & Zhu, 2025; Yuan et al., 2023; Choi et al., 2024), none formulate a loss function as we do. Existing approaches differ fundamentally in how they treat ranking information and structure their optimization objectives. For instance, ERL-VLM (Luu et al., 2025) uses rankings to *generate training data for a reward model* rather than to optimize the policy directly. Meta-RL (Xu & Zhu, 2025) maintains ranking across tasks within a meta-learning framework, instead of using group-wise ranks for per-update feedback. RRHF and RAFT (Yuan et al., 2023; Yao et al., 2024) apply ranking in supervised fine-tuning to align with human preferences but do not incorporate it into policy gradient methods. Similarly, LiPO (Zheng et al., 2025) uses listwise preference optimization, but its formulation remains within supervised learning and lacks reinforcement learning updates. In contrast, our method introduces the first policy optimization algorithm that directly integrates ranking feedback, allowing $GRPO_{rank}$ to explicitly model ordinal feedback and better exploit rank-based intuitions.

More recently, PREF-GRPO (Wang et al., 2025) introduces a preference-based extension of GRPO for text-to-image models, replacing pointwise rewards with pairwise win rates to stabilize training. However, PREF-GRPO still converts preferences into scalar rewards and does not operate on full listwise orderings. In parallel, AI-feedback approaches in robotics (Liu et al., 2024a) use multimodal LLM judges to derive preferences that are distilled into reward models and subsequently optimized via reinforcement learning. In contrast, our method introduces the first policy optimization algorithm that directly integrates ranking feedback, allowing $GRPO_{rank}$ to explicitly model ordinal feedback and better exploit rank-based intuitions without reward-model learning.

8 Conclusion

In this work, we introduce a novel reinforcement learning from AI rankings framework to fine-tune large video multi-modal models. We use a drop-in Oracle ranking model in place of the trained and calibrated reward model used in past RLAIF frameworks. To handle ranked feedback, we develop a rank adapted Group Relative Policy Optimization algorithm $GRPO_{rank}$. We train and empirically evaluate Oracle-RLAIF across multiple video-text understanding benchmarks and directly outperform leading fine-tuning methods. Future work includes considering additional types of "Oracle" models and evaluating them (such as closed general-purpose commercial models), and evaluating $GRPO_{rank}$ across a wider range of multi-modal tasks such as audio. We will also explore the use of multi-modal oracles in the context of accelerating general RL tasks (Silva et al., 2017; 2020).

References

Daechul Ahn, Yujin Hu, Oleksandr Ostapenko, Malika Prabhudesai, Cindy Wang, Katerina Fragkiadaki, and Svetlana Lazebnik. Tuning large multimodal models for videos using reinforcement learning from ai feedback. In *ACL*, 2024.

Jean-Baptiste Alayrac, Jeff Donahue, Pauline Luc, Antoine Miech, Iain Barr, Yana Hasson, Karel Lenc, Arthur Mensch, Katherine Millican, Malcolm Reynolds, Roman Ring, Eliza Rutherford, Serkan Cabi, Tengda Han, Zhitao Gong, Sina Samangooei, Marianne Monteiro, Jacob Menick, Sebastian Borgeaud, Andy Brock, Aida Nematzadeh, Sahand Sharifzadeh, Mikolaj Binkowski, Ricardo Barreira, Oriol Vinyals, Andrew Zisserman, and Karen Simonyan. Flamingo: a visual language model for few-shot learning. In *Advances in Neural Information Processing Systems*, volume 35, 2022.

Yuntao Bai, Andy Jones, Kamal Ndousse, Amanda Askell, Anna Chen, Nova DasSarma, Dawn Drain, Stanislav Fort, Deep Ganguli, Tom Henighan, Nicholas Joseph, Saurav Kadavath, Jackson Kernion, Tom Conerly, Sheer El-Showk, Nelson Elhage, Zac Hatfield-Dodds, Danny Hernandez, Tristan Hume, Scott Johnston, Shauna Kravec, Liane Lovitt, Neel Nanda, Catherine Olsson, Dario Amodei, Tom Brown, Jack Clark, Sam McCandlish, Chris Olah, Ben Mann,

and Jared Kaplan. Training a helpful and harmless assistant with reinforcement learning from human feedback. *arXiv preprint arXiv:2204.05862*, 2022.

Alex Fang Chang, Berk Ustun, Hal Ehrenberg, Chuang Gan, and Ser-Nam Lim. Data determines distributional robustness in contrastive language image pre-training (clip). In *Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics: Main Volume*, pp. 648–661. Association for Computational Linguistics, 2021.

Yanjun Chen, Dawei Zhu, Yirong Sun, Xinghao Chen, Wei Zhang, and Xiaoyu Shen. The accuracy paradox in rlhf: When better reward models don't yield better language models. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 2980–2989, Miami, Florida, USA, 2024. Association for Computational Linguistics.

Heewoong Choi, Sangwon Jung, Hongjoon Ahn, and Taesup Moon. Listwise reward estimation for offline preference-based reinforcement learning. In *Proceedings of the 41st International Conference on Machine Learning*, volume 235, pp. 8651–8671, 2024.

DeepSeek-AI. Deepseek-r1 incentivizes reasoning in llms through reinforcement learning. *Nature*, 645:633–638, 2025. doi: 10.1038/s41586-025-09422-z.

Tim Dettmers, Artidoro Pagnoni, Ari Holtzman, and Luke Zettlemoyer. Qlora: Efficient finetuning of quantized llms. In *Advances in Neural Information Processing Systems*, volume 36, pp. 10088–10115, 2023.

Chaoyou Fu, Yuhan Dai, Yongdong Luo, Lei Li, Shuhuai Ren, Renrui Zhang, Zihan Wang, Chenyu Zhou, Yunhang Shen, Mengdan Zhang, Peixian Chen, Yanwei Li, Shaohui Lin, Sirui Zhao, Ke Li, Tong Xu, Xiawu Zheng, Enhong Chen, Caifeng Shan, Ran He, and Xing Sun. Video-mme: The first-ever comprehensive evaluation benchmark of multi-modal llms in video analysis. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2025.

Jiwoo Hong, Noah Lee, Eunki Kim, Guijin Son, Woojin Chung, Aman Gupta, Shao Tang, and James Thorne. On the robustness of reward models for language model alignment. In *Proceedings of the 42nd International Conference on Machine Learning*, 2025.

Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. Lora: Low-rank adaptation of large language models. In *International Conference on Learning Representations*, 2022.

Harrison Lee, Samrat Phatale, Hassan Mansoor, Kellie Lu, Thomas Mesnard, Colton Bishop, Victor Carbune, and Abhinav Rastogi. Rlaif: Scaling reinforcement learning from human feedback with ai feedback. *arXiv preprint arXiv:2309.00267*, 2023.

Junnan Li, Dongxu Li, Caiming Xiong, and Steven Hoi. Blip-2: Bootstrapping language-image pre-training with frozen image encoders and large language models. In *Proceedings of the 40th International Conference on Machine Learning*, 2023a.

Kunchang Li, Yinan He, Yi Wang, Yizhuo Li, Wenhai Wang, Ping Luo, Yali Wang, Limin Wang, and Yu Qiao. Videochat: Chat-centric video understanding. *arXiv preprint arXiv:2305.06355*, 2023b.

Shuailin Li, Yuang Zhang, Yucheng Zhao, Qiuyue Wang, Fan Jia, Yingfei Liu, and Tiancai Wang. Vlm-eval: A general evaluation on video large language models. *arXiv preprint arXiv:2311.11865*, 2023c.

Yanwei Li, Chengyao Wang, and Jiaya Jia. Llama-vid: An image is worth 2 tokens in large language models. In *European Conference on Computer Vision*, pp. 323–340. Springer, 2024.

Bin Lin, Yang Ye, Bin Zhu, Jiaxi Cui, Munan Ning, Peng Jin, and Li Yuan. Video-llava: Learning united visual representation by alignment before projection. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 5971–5984, Miami, Florida, USA, November 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.emnlp-main.342.

Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning. In *Advances in Neural Information Processing Systems*, 2023.

J. Liu, Y. Yuan, J. Hao, F. Ni, L. Fu, Y. Chen, and Y. Zheng. Enhancing robotic manipulation with ai feedback from multimodal large language models. *arXiv preprint arXiv:2402.14245*, 2024a.

Ruyang Liu, Chen Li, Yixiao Ge, Thomas H. Li, Ying Shan, and Ge Li. Bt-adapter: Video conversation is feasible without video instruction tuning. In *Proceedings of the European Conference on Computer Vision (ECCV)*, 2024b.

Ruipu Luo, Ziwang Zhao, Min Yang, Junwei Dong, Minghui Qiu, Pengcheng Lu, Tao Wang, and Zhongyu Wei. Valley: Video assistant with large language model enhanced ability. *arXiv preprint arXiv:2306.07207*, 2023.

Tung M Luu, Younghwan Lee, Donghood Lee, Sunho Kim, Min Jun Kim, and Chang D. Yoo. Enhancing rating-based reinforcement learning to effectively leverage feedback from large vision-language models. In *Proceedings of the 42nd International Conference on Machine Learning*, 2025.

Muhammad Maaz, Hanoona Rasheed, Salman Khan, and Fahad Shahbaz Khan. Video-chatgpt: Towards detailed video understanding via large vision and language models. *arXiv preprint arXiv:2306.05424*, 2023.

OpenAI. Gpt-4 technical report. `https://openai.com/research/gpt-4`, 2023.

Long Ouyang, Jeff Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, John Schulman, Jacob Hilton, Fraser Kelton, Luke Miller, Maddie Simens, Amanda Askell, Peter Welinder, Paul F Christiano, Jan Leike, and Ryan Lowe. Training language models to follow instructions with human feedback. In *Advances in Neural Information Processing Systems*, volume 35, 2022.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. Learning transferable visual models from natural language supervision. In *Proceedings of the 38th International Conference on Machine Learning*, 2021.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Stefano Ermon, Christopher Manning, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. In *Advances in Neural Information Processing Systems 36 (NeurIPS 2023)*, 2023.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, Y.K. Li, Y. Wu, and Daya Guo. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*, 2024.

Wei Shen, Xiaoying Zhang, Yuanshun Yao, Rui Zheng, Hongyi Guo, and Yang Liu. Improving reinforcement learning from human feedback using contrastive rewards. In *Proceedings of the 41st International Conference on Machine Learning*, 2024.

Felipe Leno Da Silva, Ruben Glatt, and Anna Helena Reali Costa. Simultaneously learning and advising in multiagent reinforcement learning. In *Proceedings of the 16th conference on Autonomous Agents and Multiagent Systems (AAMAS)*, pp. 1100–1108, 2017.

Felipe Leno Da Silva, Pablo Hernandez-Leal, Bilal Kartal, and Matthew E Taylor. Uncertainty-aware action advising for deep reinforcement learning agents. In *Proceedings of the AAAI conference on artificial intelligence*, volume 34, pp. 5792–5799, 2020.

Yixuan Su, Tian Lan, Huayang Li, Jialu Xu, Yan Wang, and Deng Cai. Pandagpt: One model to instruction-follow them all. *arXiv preprint arXiv:2305.16355*, 2023.

Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*, 2023.

Yibin Wang, Zhimin Li, Yuhang Zang, Yujie Zhou, Jiazi Bu, Chunyu Wang, Qinglin Lu, Cheng Jin, and Jiaqi Wang. Pref-grpo: Pairwise preference reward-based grpo for stable text-to-image reinforcement learning. *arXiv preprint arXiv:2508.20751*, 2025.

Zuxuan Wu, Ting Yao, Yanwei Fu, and Yu-Gang Jiang. Deep learning for video classification and captioning. In *Frontiers of Multimedia Research*, pp. 3–29. ACM, 2017.

Junbin Xiao, Xindi Shang, Angela Yao, and Tat-Seng Chua. Next-qa: Next phase of question-answering to explaining temporal actions. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 9777–9786, 2021.

Jun Xu, Tao Mei, Ting Yao, and Yong Rui. Msr-vtt: A large video description dataset for bridging video and language. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 5288–5296, 2016.

Siyuan Xu and Minghui Zhu. Meta-reinforcement learning with adaptation from human feedback via preference-order-preserving task embedding. In *Proceedings of the 42nd International Conference on Machine Learning*, 2025.

Chujie Yao, Runzhe Deng, Yujia Wu, Yichi Zhang, Hu Xu, Yuwei Zhang, Xiang Zhan, Meisam Shah, Ashish Kapoor, Weinan Shi, et al. Raft: Reward-ranked fine-tuning for generative foundation model alignment. In *ICLR 2024 Workshop on Mathematical and Empirical Understanding of Foundation Models*, 2024. Oral Presentation.

Zhou Yu, Dejing Xu, Jun Yu, Ting Yu, Zhou Zhao, Yueting Zhuang, and Dacheng Tao. Activitynet-qa: A dataset for understanding complex web videos via question answering. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pp. 9127–9134, 2019.

Zheng Yuan, Hongyi Yuan, Chuanqi Tan, Wei Wang, Songfang Huang, and Fei Huang. Rrhf: Rank responses to align language models with human feedback without tears. In *Advances in Neural Information Processing Systems*, volume 36, pp. 10935–10950, 2023.

Renrui Zhang, Jiaming Han, Aojun Zhou, Xiangfei Hu, Shilin Yan, Pan Lu, Hongsheng Li, Peng Gao, and Yu Qiao. Llama-adapter: Efficient fine-tuning of language models with zero-init attention. In *The Twelfth International Conference on Learning Representations (ICLR)*, 2024.

Haiyang Zheng, Yuxuan Shao, Baolin Wang, Xiang Ren, Chen Sun, Junnan Liu, Xinyang Liu, and Percy Liang. Listwise preference optimization for language model fine-tuning. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (ACL)*, Bangkok, Thailand, 2025. Association for Computational Linguistics.

A Appendix

A.1 VLM-RLAIF Specific Training Configurations

We build directly on the RLAIF framework by (Ahn et al., 2024) which has proven successful in fine tuning *video–language* models. Below we discuss their specific framework framework.

Policy architecture Their policy starts from LLaMA-2-7B and inserts a frozen openai–clip-vit-large-patch14-336 followed by a 32-token Q-Former adapter, yielding ≈ 7.1 B parameters. The vision encoder contains two linear layers and additional learnable parameters using LoRA (Hu et al., 2022) This creates a LLaVA framework as the pretrained model (Liu et al., 2023).

Supervised warm-start Before RL, the model is SFT-pretrained on synthetically generated video-text instruction-tuning data (80k) (Maaz et al., 2023; Su et al., 2023), video question answering datasets (67k) (Xiao et al., 2021; Liu et al., 2023), and further generated object-centric datasets (180k). In SFT, the tuning dataset is split into easy (214k) and hard (113k) to create a curriculum learning strategy (Chang et al., 2021) which begins with basic video question answering before progressing to advanced comprehension question answering; where difficulty is measured as the correct answer length.

Reward Model Trained with Context In order to ground their reward model used to score responses for PPO, the authors trained using video, question, video narrative, and preference. This video narrative was gathered by prompting VLM-SFT over the ActivityNet dataset (more than 99,000 videos). The final 13B RM is trained to score responses, and used to drive reinforcement learning with PPO.

Reinforcement Learning with PPO fine-tuning In the VLM-RLAIF fine tuning pipeline, the initial policy outputs two responses per query and computes advantage $\hat{A}_t$ with a learned value head $V_\phi(s_t)$, and updates the policy using the clipped PPO objective and a frozen reference policy (Eq 1).

Training Details For input, videos are uniformly sampled to 50 frames, where the CLIP visual encoder extracts spatial and temporal features similar to (Maaz et al., 2023). In SFT, LoRA rank and α are set to 32 and training is for one epoch at each stage. For RL, QLoRA (Dettmers et al., 2023) rank is 65 and α to 16 and train the policy model for one epoch . All using 8xNVIDIA A100 GPUS (80G)

A.2 Illustrative Examples

Below is a hypothetical table showing computed values for different predicted ranks when $K = 5$, ground-truth rank $= 0$:

Table 3: $\text{GRPO}_{\text{rank}}$ advantage calculation with ground truth rank $= 0$ and predicted ranks from 0 to 4

Pred. Rank	DCG	nDCG	$\delta_i = 1 - \text{nDCG}_i$	$\mathbb{E}[\delta_j]$	$\hat{A}_{\text{rank}}$
0	1.0000	1.0000	0.0000	0.2887	+0.2887
1	0.7925	0.7925	0.2075	0.2887	+0.0812
2	0.6667	0.6667	0.3333	0.2887	−0.0446
3	0.5805	0.5805	0.4195	0.2887	−0.1308
4	0.5170	0.5170	0.4830	0.2887	−0.1943