Optimal Pattern Detection Tree for Symbolic Rule-Based Classification

Abstract

Pattern discovery in data plays a crucial role across diverse domains, including healthcare, risk assessment, and machinery maintenance. In contrast to black-box deep learning models, symbolic rule discovery emerges as a key data mining task, generating human-interpretable rules that offer both transparency and intuitive explainability. This paper introduces the optimal pattern detection tree (OPDT) for binary classification, a rule-based machine learning model based on novel mixed integer programming to extract an optimal pattern in data. This optimization-based approach discovers a hidden underlying pattern in datasets, when it exists, by identifying an optimal rule that maximizes coverage while minimizing the false positive rate due to misclassification. Our computational experiments show that OPDT discovers a pattern with optimality guarantees on moderately sized datasets within reasonable runtime.

1 Introduction

Data mining is the process of discovering and extracting hidden patterns from datasets to gain valuable insights and support decision-making. Especially, symbolic rule discovery is an important data mining task that generates human-interpretable rules in a natural and intuitive manner. However, recent developments in artificial intelligence (AI) and machine learning (ML) have driven attention toward black-box models, particularly deep learning approaches. This trend has led, in turn, to a growing demand for developing algorithms that inherently learn interpretable white-box models, especially in high-stakes domains such as healthcare, personalized medicine, criminal justice, and financial risk assessment, where decisions can significantly impact human lives (Rudin, 2019; Rudin et al., 2022). The exponential growth in healthcare data collection, driven by advanced monitoring technologies and digital health systems, have resulted in a growing volume of biological and medical data at unprecedented speed and scale (Luo et al., 2016). While the tremendous amounts of data—collected from electronic health records or monitoring devices can be utilized for a more effective and enhanced clinical decison making (Rea et al., 2012), it is significant challenges in efficiently analyzing and extracting useful information and actionable insights from such overwhelming volumes of data (Najarian et al., 2013).

Over the last decade, various pattern recognition techniques have been developed for medical decision support systems to help clinicians effectively utilize the overwhelming amount of healthcare data. These techniques are applied to biomedical data for automated clinical diagnosis or therapeutic support, integrating data-driven knowledge and patient-specific information to enhance cost-effective healthcare delivery (Moja et al., 2014). The development of novel pattern recognition methods and algorithms with high performances, in terms of accuracy and time complexity, improves healthcare delivery by allowing clinicians to make a better informed and timely decisions (Asgari et al., 2019). To take reliable actions in high-stakes domains, the patterns extracted from data must be understood by human domain experts, unlike the opaque solutions provided by black-box ML approaches (Rudin, 2019). If domain experts do not fully comprehend the reasoning behind these patterns, there is a risk of making misinformed or potentially harmful decisions in life-threatening situations. Therefore, developing human-readable rules is crucial for addressing emerging challenges in critical decision-making processes and ensuring accountability, transparency, and trust in automated systems.

Rule-based machine learning (RBML) models offer a promising solution by combining the interpretability of traditional rule-based systems with the automated learning capabilities of ML approaches. Unlike conventional black-box ML models, RBML generates explicit decision rules that can be readily understood and validated by domain experts. Furthermore, for high-risk tasks requiring accountability, not only is interpretability crucial, but models must also comply with domain expert-specified constraints to be trustworthy (Nanfack et al., 2022). For example, learned patterns may not make sense from a medical or clinical perspective, as algorithms typically consider only information extracted from medical datasets without incorporating domain knowledge (López-Vallverdú et al., 2007). Therefore, ML models can become more trustworthy and reliable if they incorporate additional domain knowledge in the form of constraints.

This paper proposes a novel rule extraction algorithm for binary classification that adheres to user-defined structural constraints, ensuring high interpretability while incorporating prior domain knowledge. We develop optimal pattern detection tree (OPDT) based on optimal decision tree with *branching structure constraints* that control: 1) the tree's topology through split decisions, and 2) the feature group assignments for each branch node. This optimization-based rule extracting approach discovers a hidden underlying pattern in datasets, when it exists, by identifying an optimal rule that maximizes coverage while minimizing the false positive rate due to misclassification. The remainder of the paper is structured as follows. In Section 2, we discuss the related work regarding the interpretable RBML and optimal decision tree (ODT). In Section 3, we present our proposed approach, OPDT to extract an optimal pattern from dataset. In Section 4, we demonstrate the performance of the OPDT over different real-world dataset from the UCI repository and compares it with other RBML methods.

2 Related Literature

2.1 Rule-Based Machine Learning

Among advanced AI and ML technologies, the ability to extract valuable insights from complex datasets has become crucial for various fields, including healthcare, criminal justice, and financial risk assessment. However, the lack of interpretability in ML models can potentially lead to adverse or even life-threatening consequences (Ahmad et al., 2018). There is a growing demand for interpretable ML that allows end-users to understand the logic and reasoning behind predictions, especially in domains such as healthcare and criminal justice systems. This demand for improved interpretability has also increased to mitigate the risk of making unjustifiable decisions. Especially, studies in domains like healthcare and criminal justice have revealed that ML systems can systematically exhibit unfair biases (Burrell, 2016). Thus, interpretability is needed to ensure such systems are free from bias (Hajian et al., 2016). Recent research has focused on developing explainable or interpretable AI models (Murdoch et al., 2019; Vilone & Longo, 2021) because model interpretability and explainability are crucial for clinical and healthcare practices (Ahmad et al., 2018; Kolyshkina & Simoff, 2021), where misclassification costs can be potentially high. To address this, data mining techniques have emerged to discover interpretable rules by generating symbolic rules that humans can readily understand. By providing understandable patterns or rules from training data, we can involve human experts such as doctors or nurses, allowing them to review AI model results and provide feedback or corrections. Consequently, this approach can improve the reliability of life-critical decision-making in healthcare.

Unlike deep learning-based models that often operate as black boxes, RBML is an algorithm that induces a set of symbolic rules from training data. RBML automatically identifies regularities or patterns that can be expressed in the form of "IF-THEN" statements. Here, the left hand side ("IF" part) is called the rule antecedent or condition, which can be expressed in logical operators like disjunction, conjunction, and negation. The right hand side ("THEN" part) of a rule is called the rule consequent or conclusion. In particular, rule conditions represented in disjunctive normal form (DNF: OR-of-ANDs) or conjunctive normal form (CNF: AND-of-ORs) are intuitively understandable to humans as they mirror natural reasoning processes. For example, a medical diagnosis rule might state: "IF (patient age > 65 AND white blood cell count > 11,000) OR (body temperature > 100 AND patient has chest pain) THEN (further diagnostic tests for potential infection)". One of a natural choice for interpretability is to represent ML output as logical operators like disjunction, conjunction, and negation with the IF-THEN structure, and these can be expressed through rule sets, decision trees, and decision lists. RBML's full transparency and intuitive

explainability make it particularly valuable in applications where decision-making processes must be clear and explainable. The principles of RBML are most commonly implemented through the form of rule-based classifiers in modern ML applications. Rule-based classifiers can be seen as a generalization of decision tree classifier since the obtained rules do not require to be represented in the form of a tree, thus being more flexible (Palliser-Sans, 2021). Unlike trees, DNF rules need not be mutually exclusive. These rules are potentially more compact and predictive than trees. Regarding the induced rules, it uses conjunctive antecedents: "IF condition_01 AND condition_02 AND ... THEN conclusion". Each individual condition, also called a selector, is formed by an attribute-value pair, where the pair refers to a specific feature of the data and its corresponding value. Rule-based classifiers have already been successfully implemented in various domains such as medical diagnosis, financial fraud detection, intrusion detection, and machine failure diagnosis in manufacturing systems, with each application domain delivering promising results (Palliser-Sans, 2021).

Research on RBML has introduced various approaches to extract rules from data. Frist, Rules Extraction System (RULES) (Pham & Aksoy, 1995) is a simple algorithm for extracting a set of classification rules from a set of training instances given set of classes. It follows a general-to-specific approach and enforces perfect precision (100%) in the generated rules unless there are inconsistencies in the data. RRULES (Palliser-Sans, 2021) was proposed as an optimization of RULES by focusing on two key points: the mechanism to detect irrelevant rules and the stopping condition. PRISM (Cendrowska, 1988) introduced a unique approach of generating rules by selecting examples of a specific class and iteratively adding conditions until the obtained rule has prefect precision. As a non-ordered and non-incremental algorithm, PRISM builds rules from general to specific patterns, with rule order being irrelevant for predictions. Interpretable Decision Sets (IDS) (Lakkaraju et al., 2016) presented a method for generating decision sets which are sets of independent if-then rules. Since each rule can be applied independently, decision sets are simple, concise, and easily interpretable compared to a decision list. Bayesian Rule Sets (BRS) (Wang et al., 2017) introduced a novel Bayesian framework for learning rule sets that uses a generative model to incorporate prior knowledge about interpretable rules while maintaining strong predictive performance. Incremental Reduced Error Pruning (IREP) (Fürnkranz & Widmer, 1994) addressed the computational inefficiencies of standard reduced error pruning in rule learning by integrating the pruning process directly into rule learning rather than as a post-processing step. This innovation laid the foundation for RIPPER (Cohen et al., 1995), which demonstrated that incremental pruning could achieve comparable or better results than standard pruning while being substantially more efficient. RuleFit (Friedman & Popescu, 2008) extracts rules from an ensemble of trees by automatically detecting interaction effects in the form of decision rules and builds a weighted combination of these rules using L1-regularized optimization over the weights (Friedman & Popescu, 2004). SkopeRules (Goix et al., 2020) is based on RuleFit's approach, utilizing a Random Forest model to fit class labels. The two methods differ only in their rule pruning strategy: RuleFit uses a linear model whereas SkopeRules heuristically deduplicates overlapping rules.

2.2 Optimal Classification

In recent years, researchers have increasingly applied discrete optimization techniques to learn optimal decision trees in ML problems. The problem of learning an optimal decision tree is NP-hard (Laurent & Rivest, 1976), which has led to the widespread adoption of greedy heuristics such as Classification And Regression Trees (CART) (Breiman et al., 1984), which constructs univariate classification trees. However, over the last decades, there have seen overall 800 billion speedup increase in the computational power of optimization solvers (Bertsimas & Dunn, 2017). This astonishing increase in optimization solver performance has enabled to applying modern mixed-integer optimization (MIO) methods to solve optimal decision trees. An overview of recent developments in optimization techniques for ML is presented in Bottou et al. (Bottou et al., 2018) and Gambella et al. (Gambella et al., 2021).

Recently, Bertsimas & Dunn (2017) introduced optimal classification tree (OCT), which is a mixed-integer programming (MIP) formulation to learn optimal decision trees given a fixed depth. The constraints and variables of the formulation can be decomposed into three sets: those defining the structure of the tree through split decisions at each node, those routing data samples from root to leaf nodes, and those counting misclassifications. The objective function balances minimizing training set misclassifications against tree

complexity to preserve interpretability (Ales et al., 2024). The MIP model supports both axis-aligned and oblique splits with exponential complexity in tree depth, and can handle both continuous and categorical features. Günlük et al. (2021) proposed an alternative formulation for optimal decision trees that specializes in categorical features. Their formulation exploits the combinatorial structure of categorical variables, enabling branching on subsets of categorical feature values. However, both models can easily become intractable as the size of training dataset grows. To address this issue, Verwer & Zhang (2019) proposed BinOCT, which represents decision thresholds through binary encoding, drastically reducing the number of decision variables. The number of decision variables is largely independent of the training set size. It only depends logarithmically on the number of unique feature values. To further improve scalability, Firat et al. (2020) introduced a new formulation based on root-to-leaf paths for fixed-depth trees, which is solved using a column generation-based heuristic. Finally, Aghaei et al. (2024) introduced a flow-based MIP formulation that represents optimal classification trees as a maximum flow problem. The flowOCT formulation avoids big-M constraints, resulting in stronger linear programming (LP) relaxations compared to previous OCT models. However, it only works with binary features.

In addition to classification decision trees, recent work has explored discrete optimization techniques to learn boolean rules and rule sets. Su et al. (2016) developed an integer programming (IP) formulation for interpretable two-level boolean rules, expressed in either CNF or DNF, with a predefined maximum number of clauses, enabling controlled model complexity and enhanced transparency in classification tasks for high-stakes domains such as healthcare and law. Lawless et al. (2023) proposed an IP framework using column generation to learn sparse and interpretable boolean rule sets in DNF form, while incorporating fairness constraints.

3 Methods

This section presents a structure-constrained decision tree approach to identify patterns in datasets while adhering to prior domain knowledge and structural constraints defined by domain experts. In rule-based classification, any pattern or rule can be expressed through a nested if-then statement since their logical structure inherently consists of conditions (IF clause) and consequences (THEN clause). On the other hand, decision trees effectively extract meaningful patterns from data and transform them into interpretable rules by linearizing conditions along paths from root to leaf nodes. Therefore, we utilize a decision tree approach that discovers classification patterns through nested if-then-else structures, ensuring all possible combinations of conditions, including negation scenarios.

Most business domains have domain-specific prior knowledge about their data. For example, in medical diagnosis, physicians know that elevated blood pressure and high cholesterol levels are key risk factors for cardiovascular disease. Similarly, in diabetes prediction, medical experts rely on crucial diagnostic indicators such as body mass index (BMI), fasting blood glucose levels, and age. Also, domain experts recognize that features can be naturally grouped based on their relevance. In cardiovascular disease assessment, for instance, blood test results (cholesterol levels, triglycerides, and blood glucose) form one group, while vital signs (blood pressure, heart rate, and body temperature) form another. Even when domain knowledge is unavailable, various ML methods can extract prior information about features. For example, SHAP (SHapley Additive exPlanations) is a model-agnostic method that explains the contribution of each feature to model outputs (Lundberg & Lee, 2017). Similarly, Boruta is a feature selection algorithm that identifies which features are statistically significant or relevant to the outcome variable (Kursa & Rudnicki, 2010). Also, feature importance in decision trees quantifies the relative contribution of each input feature to the model's predictions. Therefore, we can reasonably assume two types of prior knowledge: 1) feature groupings based on feature correlation and 2) feature impact on the target variable based on feature importance. Given the prior knowledge, we propose a structure-constrained decision tree to identify optimal patterns in data. This paper develops an optimization-based model that utilizes prior information from either domain experts or ML algorithms.

3.1 Structure Constrained Decision Tree

A structure constrained decision tree (SCDT) refers to a decision tree where the learning process is guided and restricted by specific constraints imposed on its structure. These constraints aim to improve the interpretability, fairness, compliance, or other desired properties of the resulting tree. In pattern discovery, we incorporate prior domain knowledge into the decision tree through structural constraints, following three steps to detect patterns in data, as illustrated in Figure 1. First, given the prior knowledge from domain experts or feature relevance determined by ML algorithms, we define feature groups by splitting features into small subsets that have mutually exclusive impacts on classification. For instance, in diabetes diagnosis, laboratory measurements (fasting blood glucose, HbA1c levels) and patient characteristics (age, BMI, family history) can be formed into separate groups, reflecting their distinct roles in diagnosis. Second, we define the topology of the binary tree using the feature groups, which restricts feature availability at each branching node and the depth of the tree. For example, in medical diagnosis, blood test results might be restricted to upper-level nodes while patient symptoms are considered at lower levels, following clinical diagnostic procedures. Finally, we run the SCDT where feature selection at each branching node is guided by predefined feature groups. This approach ensures the learning process follows the branching constraints imposed on the decision tree.

Figure 1: Structure Constrained Decision Tree (SCDT)

3.2 Optimal Pattern Detection Tree

In this section, we first introduce the volume-impurity index that measures coverage volume and misclassification by a rule and then present the basic concepts of OPDT. Subsequently, we present the IP formulation of OPDT. Finally, we describe branching structure constraints on OPDT and their enhancements to improve computational efficiency.

Metrics We propose a volume-impurity (VI) index that balances classification volume and classification impurity, defined as:

$$\text{volume-impurity (VI) index} = \text{"volume gain"}$$
$$- w \times \text{"misclassification loss"}$$

where w is the weight controlling precision.

In rule discovery, volume gain refers to the size of samples covered by the rule, while misclassification loss represents the size of incorrectly classified samples among the covered samples.

Approach The primary focus in rule discovery is identifying patterns and regularities within a dataset. In this paper, we aim to find an optimal pattern that maximizes coverage volume while controlling misclassification through a given weight. We utilize a decision tree approach to discover an optimal pattern through nested if-then-else structures handling negation scenarios, incorporating prior knowledge via structural constraints. Given feature groups (e.g., $G_1, G_2, \cdots, G_D$ in Figure 2) from prior domain

knowledge or heuristic algorithms, we initially assume a fixed length of rule conditions, allowing us to assign feature groups to specific depths in the chain of rule conditions (e.g., $\{G_1\} - \{G_2\} - \{\cdots\} - \{G_D\}$ in Figure 2). This determines the topology of the nested if-then-else tree. Using discrete optimization, we formulate our rule learning framework as a decision tree where leaf nodes are measured by the VI index and find rule conditions that maximize this value, yielding the optimal pattern among all possible combinations of rule conditions. We call this approach the optimal pattern detection tree.

Figure 2: Optimal Pattern Detection Tree (OPDT)

Mathematical Formulation We use discrete optimization to solve the OPDT problem. Since OPDT aims to discover rule conditions rather than making predictions based on majority class of training samples in leaf nodes, the approach discards most nodes except for the node with maximal VI value. It extracts splitting conditions along the path from root to the leaf node with maximal VI value to form the IF part of the decision rule. The learned rule is represented as a chain of conditions and a label prediction. When a sample meets all conditions in the IF part, we say the rule fires, and we define such a sample as covered by the rule. The rule is then evaluated by two metrics: coverage (measured by fired volume) and precision (measured by misclassification loss).

Table 1: Sets for OPDT

Symbol	Definition
P	set of features in a dataset with one-hot encoded categorical variables
N	set of samples in a dataset
G_A	feature group containing all features, P
G_N	set of numerical feature groups
G_C	set of categorical feature groups
$P_N(g)$	set of index for numerical feature group g, $g \in G_N$
$P_C(g)$	set of index for one-hot encoded categorical feature group g, $g \in G_C$
x_i	ith sample in a dataset, $i \in 1, \ldots, N$
y_i	ith sample's label in a dataset, $i \in 1, \ldots, N$
Y_{ik}	one-hot encoded matrix on y, $\mathbf{1}\{y_i = k\}$, $\forall k = 1, \ldots, K, i = 1, \ldots, N$
K	set of class label
k	class label, $k \in K$
D	maximum depth of the optimal decision tree
T	maximum possible nodes by tree with a depth of D, $T = 2^{(D+1)} - 1$

Continued on next page

Table 1: Table 1 continued from previous page

Symbol	Definition
T_B	branch nodes with split $a^T x < b$, $T_B = 1, \ldots, \lfloor T/2 \rfloor$
T_L	leaf nodes with class prediction for samples in the leaf node, $T_L = \lfloor T/2 \rfloor + 1, \ldots, T$
T_{obj}	target leaf nodes in objective function, $T_{obj} \subseteq T_L$
t	index of each node, $t = 1, \ldots, T$
w	weight on misclassified samples in a node, $w \geq 1$
$p(t)$	parent node of node t
$A(t)$	set of ancestors of node t, $A(t) = A_L(t) \cup A_R(t)$
$A_L(t)$	set of left-branch ancestors of node t whose left branch has been followed on the path from the root node to node t
$A_R(t)$	set of right-branch ancestors of node t whose right branch has been followed on the path from the root node to node t
$E_L(t)$	set of all leaf nodes from a left child of node t
$E_R(t)$	two rightmost leaf nodes for both children (left and right) of node t
$B(\text{split})_t$	binary value indicating a split of branching node t in T_B, $|B(\text{split})| = |T_B|$
$B(\text{group})_t$	feature group assigned to branching node t in T_B, $|B(\text{group})| = |T_B|$

Table 2: Variables for OPDT

Symbol	Definition
$\vec{a}_t$	slope of split applied at node t, $\forall t \in T_B$
a_{pt}	slope element of split applied at node t, $\forall p \in P, \forall t \in T_B$
b_t	intercept of split applied at node t, $\forall t \in T_B$
d_t	$\mathbf{1}\{\text{node } t \text{ applies a split}\}$, $\forall t \in T_B$
z_{it}	$\mathbf{1}\{x_i \text{ is in node } t\}$, $\forall i \in N, \forall t \in T_L$
l_t	$\mathbf{1}\{\text{leaf } t \text{ contains any sample}\}$, $\forall t \in T_L$
N_t	total number of samples in node t, $\forall t \in T_L$
N_{kt}	number of samples of label k in node t, $\forall k \in K, \forall t \in T_L$
c_{kt}	$\mathbf{1}\{\text{the most common labels in node } t \text{ is } k\}$, $c_{kt} = \mathbf{1}\{\arg\max_{k=1,\ldots,K}\{N_{kt}\} = k\}$, $\forall k \in K, \forall t \in T_L$
L_t	the number of misclassified samples ($L_t = N_t - M_t$) in the leaf node t, where M_t is total number of the most common labels in node t, $M_t = \max_{k=1,\ldots,K} N_{kt}$, $\forall t \in T_L$
I_t	volume-impurity (VI) value calculated as the total number of samples minus the misclassified samples in a leaf node, $I_t = \{N_t - wL_t\}, \forall t \in T_L$
I_{max}	maximum number of I_t over all leaf nodes, $I_{max} = \max\{N_t - wL_t\}, \forall t \in T_L$
q_t	binary variable to indicate that a leaf node t has the maxium number of volume-impurity (VI) or not, $\forall t \in T_L$

$$\max I_{max} \tag{1}$$

subject to:

$$\sum_{p=1}^{P} a_{pt} = d_t, \quad \forall t \in T_B \tag{2}$$

$$d_t \leq d_{p(t)}, \quad \forall t \in T_B \setminus \{1\} \tag{3}$$

$$l_s \leq d_t, \quad \forall t \in T_B, \forall s \in E_L(t) \tag{4}$$

$$l_s \geq d_t, \quad \forall t \in T_B, \forall s \in E_R(t) \tag{5}$$

$$z_{it} \leq l_t, \quad \forall i \in N, \forall t \in T_L \tag{6}$$

$$N_t = \sum_{i=1}^{n} z_{it}, \quad \forall t \in T_L \tag{7}$$

$$\sum_{t \in T_L} z_{it} = 1, \quad \forall i \in N \tag{8}$$

$$\vec{a}_s^T(x_i + \vec{\epsilon}) \leq b_s + (1 + \epsilon_{max})(1 - z_{it}),$$
$$\forall i \in N, \forall t \in T_L, \forall s \in A_L(t) \tag{9}$$

$$\vec{a}_s^T x_i \geq b_s - (1 - z_{it}),$$
$$\forall i \in N, \forall t \in T_L, \forall s \in A_R(t) \tag{10}$$

$$\sum_{k=1}^{K} c_{kt} = l_t, \quad \forall t \in T_L \tag{11}$$

$$N_{kt} = \sum_{i=1}^{n} Y_{ik} z_{it}, \quad \forall k \in K, t \in T_L \tag{12}$$

$$L_t \geq N_t - N_{kt} - M(1 - c_{kt}),$$
$$\forall k \in K, \forall t \in T_L \tag{13}$$

$$L_t \leq N_t - N_{kt} + M c_{kt},$$
$$\forall k \in K, \forall t \in T_L \tag{14}$$

$$L_t \geq 0, \quad \forall t \in T_L \tag{15}$$

$$I_{max} \geq N_t - wL_t, \qquad \forall t \in T_L \tag{16}$$

$$I_{max} \leq N_t - wL_t + M(1 - q_t), \qquad \forall t \in T_L \tag{17}$$

$$\sum_{t \in T_L} q_t = 1 \tag{18}$$

$$a_{pt} \in \{0, 1\}, \quad \forall p \in P, \forall t \in T_B \tag{19}$$

$$0 \leq b_t \leq d_t, \quad \forall t \in T_B \tag{20}$$

We formulate OPDT as a mixed-integer program as follows. The objective (1) maximizes volume on one of the leaf nodes while minimizing misclassification loss through the VI index, which combines volume and misclassification loss with weight w. Constraints (16, 17, and 18) represent the maximum value of the VI index over all leaf nodes, where the largest valid value of M is $w|N|$. Constraint (2) ensures that a slope variable a_{pt} for a branching node can be activated if the node applies a split. Constraint (3) allows a branch node to split only if its parent node splits. Constraint (4) ensures that all leaf nodes from a left child of a branching node have zero samples if the node doesn't split, forcing samples to be assigned to the rightmost leaf nodes. Constraint (5) ensures that the two rightmost leaf nodes from both left and right children of a branching node must be active if the branching node splits. Constraint (6) guarantees that samples can be assigned to a leaf node if the node is active. Constraint (7) counts the total number of samples at leaves. Constraint (8) forces each sample to be assigned to exactly one leaf. Constraints (9 and 10) formulate the branching rules at each node. Constraint (11) enforces a single class prediction at each leaf node if the node is active. Constraint (12) counts the number of samples of class k in each leaf node. Constraints (13, 14, and 15) represent misclassification loss in each leaf node. Finally, decision variables (19 and 20) specify the slope and threshold for split $a^T x < b$ at each branch node.

Branching Structure Constraints We incorporate branching structure constraints (BSC) into OPDT to integrate prior knowledge from domain experts. These constraints aim to improve the interpretability and compliance of the resulting rule while enhancing computational efficiency. We design a decision tree that complies with BSC to control: 1) the tree topology through splitting decisions and 2) feature allocation at each branching node through predefined feature groups. Specifically, we define two arrays for branching nodes: $B(split)$, which indicates whether each branching node i needs to be split or not, and $B(group)$, which specifies feature group G_j for branching node i, where G_j is a subset of features used for branching. These arrays enable us to construct the desired tree structure and feature allocations over branching nodes to solve the OPDT problem. We assume that feature subgroups for $B(group)$ can be determined by domain expert knowledge. However, this grouping is optional. For cases without predefined groups, we define a

universal feature group G_A containing all features. By assigning G_A to all branching nodes, OPDT can enumerate all feature combinations without any subgrouping constraints (e.g., not even requiring separation into numerical and categorical features). We demonstrate the computational gains from feature subgrouping in Section 4.

Algorithm 1: Branching Structure Constraints (BSC)

---

1 **Input:** $|B(\text{split})|, |B(\text{group})|$
    // $B(\text{split})$: binary array to indicate branching splits
    // $B(\text{group})$: subset of features allocated to each branching node
2 **foreach** $t \in T_B$ **do**
3 $d_t = B(\text{split})_t$
4 $g \leftarrow B(\text{group})_t$
5   **if** $g = G_A$ **then**
6 $a_{pt} \geq 0, \qquad \forall p \in P$
7   **else if** $g \in G_N$ **then**
8 $a_{pt} \leq 0, \qquad \forall p \in P \setminus P_N(g)$
9   **else if** $g \in G_C$ **then**
10 $a_{pt} \leq 0, \qquad \forall p \in P \setminus P_C(g); \; b_t = 0.5$

---

4 Computational Results

In this section, we evaluate the performance of OPDT on datasets from the UCI Machine Learning Repository (Kelly et al., 2017). Since the purpose of this paper is to identify a single pattern in data that maximizes coverage while minimizing the false positive rate due to misclassification, for algorithms that generate multiple rules, we analyze the best candidate rule among the set of rules generated by ruleset extracting models such as BRS (Wang et al., 2017), IDS (Lakkaraju et al., 2016), IREP (Fürnkranz & Widmer, 1994), PRISM (Cendrowska, 1988), and Ripper (Cohen et al., 1995). All experiments were conducted on an Apple M2 system with an 8-core CPU and 8GB of RAM.

4.1 Datasets

For our experiments, we use all 15 publicly available datasets from the UCI Machine Learning Repository (Kelly et al., 2017) as detailed in Table 3. For domains that require high interpretability and reliability, we focus on healthcare and finance datasets. We apply an 80/20 train-test split for our experiments.

Table 3: UCI Dataset

Dataset	n_instances (n_missing)	n_features (num, cat)	weights (neg, pos)	description
Australian	653 (37)	15 (6, 9)	(357, 296)	credit approval
German	1000 (0)	20 (7, 13)	(300, 700)	credit approval
Blood Transfusion	748 (0)	4 (4, 0)	(570, 178)	healthcare
Breast Cancer	569 (0)	30 (30, 0)	(212, 357)	healthcare
Chronic Kidney	215 (185)	24 (11, 13)	(128, 87)	healthcare
Early Stage Diabetes	520 (0)	16 (1, 15)	(320, 200)	healthcare
Echocardiogram	62 (69)	7 (4, 3)	(44, 18)	healthcare
Fertility	100 (0)	9 (2, 7)	(88, 12)	healthcare
Heart Disease	297 (6)	13 (6, 7)	(160, 137)	healthcare
Heart Failure	299 (0)	12 (7, 5)	(203, 96)	healthcare
Hepatitis	80 (75)	19 (6, 13)	(67, 13)	healthcare
Indian Liver Patient	579 (4)	10 (9, 1)	(414, 165)	healthcare
Parkinsons	195 (0)	23 (22, 1)	(147, 48)	healthcare
Pima Indians Diabetes	768 (0)	8 (8, 0)	(500, 268)	healthcare
Thoracic Surgery	470 (0)	16 (3, 13)	(400, 70)	healthcare

4.2 Performance Enhancements

Generally, solving an ODT is known to be an NP-hard problem (Laurent & Rivest, 1976). To address this computational challenge, we propose three complementary techniques to enhance performance: 1) Branching Structure Constraints (BSC), which leverages prior knowledge about feature relationships to reduce the search space, 2) warmstart initialization, which provides a quality initial solution to accelerate convergence, and 3) branching priority orders, which guides the search process by prioritizing promising decision variables. These techniques work synergistically - BSC narrows the feasible region, warmstart provides a good starting point within this reduced space, and priority ordering helps efficiently navigate toward optimal solutions. Our empirical results demonstrate that this combination significantly reduces computational time while maintaining or improving solution quality across diverse datasets.

First, BSC enhances both interpretability and computational efficiency by imposing meaningful constraints on the branching structure of decision trees. Table 4, with a 10-minute time limit, demonstrates significant computational savings when prior knowledge about rule structure is incorporated. The impact is particularly dramatic for certain rule structures - for instance, employing "{categorical} - {numerical}" constraints reduces runtime from 1232 seconds to 23 seconds for Heart Disease and from 924 seconds to 21 seconds for Thoracic Surgery. Furthermore, decomposing features into numerical and categorical subgroups proves highly effective. In the case of Chronic Kidney Disease, this systematic decomposition strategy reduces the total runtime from 978 seconds (by all features) to approximately 45 seconds (by decomposing features). Beyond runtime improvements, the systematic feature decomposition assists in feature pruning by identifying essential structural patterns for optimality. For example, in Thoracic Surgery, while optimality of the solution with $VI = 42$ remains uncertain due to the time limit being hit on one of feature decomposition, any potential better solution must exist under the "{numerical}-{numerical}" rule structure, as all other feature combinations involving categorical features were solved to optimality within the time limit. This effectively eliminates categorical features from the search space for an optimal solution. Such insights significantly reduce the search space by allowing us to focus computational resources on the most promising feature combinations. In real-world applications, prior domain knowledge could enable even finer feature groupings beyond the basic numerical-categorical group separation. Therefore, BSC not only enhances computational efficiency but also provides valuable guidance toward optimal solutions through strategic feature decomposition.

Table 4: OPDT Runtime (in seconds) and VI by Branching Structure Constraints (BSC)

| | Structure Constraints (solver time limit = 600 sec) | | | | | | | | | |
| | all-all | | num-num | | num-cat | | cat-num | | cat-cat | |
Dataset	Runtime	VI	Runtime	VI	Runtime	VI	Runtime	VI	Runtime	VI
Australian	600.04	143	982.97	49	975.71	143	45.66	143	7.29	124
German	1475.81	31	631.47	35	1065.43	45	1006.65	45	968.56	44
Chronic Kidney	977.94	99	23.35	93	16.66	99	4.64	99	0.57	88
Early Stage Diabetes	23.07	151	3.53	25	6.88	130	1.32	130	8.27	151
Echocardiogram	12.08	13	2.03	13	0.85	13	0.19	13	0.05	6
Fertility	5.33	31	0.36	31	0.74	30	0.23	30	0.11	24
Heart Disease	1232.83	31	1061.62	26	947.29	31	22.67	31	1.93	17
Heart Failure	1017.01	61	1410.82	61	4.01	21	79.37	21	-	-
Hepatitis	10.70	40	1.82	40	0.50	38	0.15	38	0.11	35
Indian Liver Patient	1421.23	75	600.02	75	0.41	45	6.18	45	-	-
Parkinsons	600.02	86	954.41	86	4.08	64	0.96	64	-	-
Thoracic Surgery	924.10	39	964.28	34	77.15	42	20.54	42	2.34	42

For warmstart initialization, we develop a novel heuristic algorithm adapted from CART (Breiman et al., 1984) for structure constraints, called Branching Structure Constrained Classification and Regression Tree (BSCCART), as no existing heuristics for structure constrained decision trees are available. BSCCART modifies CART's branching criteria by restricting feature selection at each node to comply with the branching structure constraints. By applying the same structure constraints used in OPDT, the BSCCART solution can serve as a warmstart for OPDT. The performance comparison between BSCCART and OPDT is presented

in Tables 6 and 7. For branching priority orders, we assign higher priorities to topology variables (e.g., a_{pt} and d_t), guiding the MIP solver to decide the tree structure variables before others.

Table 5 presents the computational runtime and VI values across different configurations of warmstart and branching priority orders, where "on/on" denotes the use of both strategies. Generally, the "on/on" configuration demonstrates superior or equivalent performance compared to other configurations, showing trends toward higher VI values or faster runtimes. This is particularly evident in datasets solved to optimality within the time limit, such as Early Stage Diabetes, Echocardiogram, Fertility, and Hepatitis, which show identical VI values across all configurations. For these datasets, the runtime analysis clearly demonstrates that both warmstart and branching priority orders contribute to faster computation times compared to their "off" counterparts. Furthermore, the "on/on" configuration exhibits more stable performance with moderate standard deviations, while the "off/off" configuration often shows larger variability. However, the optimal configuration appears to be dataset-dependent, with some exceptions: Blood Transfusion achieves slightly better VI with "on/off", Indian Liver Patient performs best with "on/off", and Breast Cancer shows optimal results with "off/on". Overall, despite some dataset-specific variations, the combined use of warmstart and branching priority orders ("on/on") enhances both solution quality and computational efficiency across diverse datasets.

Table 5: OPDT Runtime (in seconds) and VI by Warmstart and Branching Priority Orders. **Bold** represents the highest VI value

Dataset	Warmstart from BSCCART / Branching Priority Orders (solver time limit = 120 sec)							
	on / on		on / off		off / on		off / off	
	Runtime	VI	Runtime	VI	Runtime	VI	Runtime	VI
Australian	18.715	**134.300**	26.616	**134.300**	23.496	132.400	54.946	**134.300**
	(±16.804)	(±12.996)	(±33.923)	(±12.996)	(±21.194)	(±12.963)	(±49.832)	(±12.781)
German	29.296	**53.800**	11.331	51.300	42.333	33.800	108.277	24.600
	(±39.142)	(±17.568)	(±20.068)	(±17.468)	(±40.723)	(±12.109)	(±297.212)	(±19.856)
Blood Transfusion	7.574	51.000	18.458	**51.200**	9.565	50.100	6.575	50.800
	(±9.662)	(±10.509)	(±26.890)	(±10.443)	(±12.220)	(±12.387)	(±6.100)	(±10.696)
Breast Cancer	37.938	230.100	29.135	230.000	42.666	**231.000**	68.280	223.300
	(±30.127)	(±5.782)	(±19.873)	(±5.774)	(±32.837)	(±7.630)	(±26.746)	(±16.958)
Chronic Kidney	1.230	98.700	3.675	**99.200**	3.201	**99.200**	4.746	98.500
	(±1.101)	(±3.234)	(±3.503)	(±3.327)	(±2.730)	(±3.327)	(±7.048)	(±3.408)
Early Stage Diabetes	1.302	**153.400**	1.811	**153.400**	3.230	**153.400**	4.536	**153.400**
	(±1.032)	(±3.565)	(±1.275)	(±3.565)	(±1.231)	(±3.565)	(±1.904)	(±3.565)
Echocardiogram	0.162	**18.667**	0.233	**18.667**	0.664	**18.667**	0.654	**18.667**
	(±0.180)	(±4.743)	(±0.263)	(±4.743)	(±0.552)	(±4.743)	(±0.563)	(±4.743)
Fertility	0.073	**34.300**	0.101	**34.300**	0.252	**34.300**	0.342	**34.300**
	(±0.089)	(±1.947)	(±0.141)	(±1.947)	(±0.118)	(±1.947)	(±0.164)	(±1.947)
Heart Disease	14.438	**28.200**	18.029	26.700	9.782	26.100	15.690	27.700
	(±19.564)	(±4.709)	(±29.863)	(±4.423)	(±12.683)	(±3.178)	(±16.870)	(±4.832)
Heart Failure	10.971	**62.100**	11.723	61.800	11.219	60.200	16.533	61.500
	(±17.315)	(±5.859)	(±19.361)	(±5.996)	(±11.942)	(±4.467)	(±14.937)	(±6.329)
Hepatitis	0.667	**42.200**	0.869	**42.200**	0.653	**42.200**	0.703	**42.200**
	(±1.357)	(±3.393)	(±1.834)	(±3.393)	(±0.551)	(±3.393)	(±0.428)	(±3.393)
Indian Liver Patient	14.701	82.300	21.831	**84.000**	27.622	83.800	23.099	76.200
	(±15.843)	(±8.220)	(±21.734)	(±7.454)	(±31.831)	(±7.361)	(±28.159)	(±15.817)
Parkinsons	25.639	**82.700**	15.436	82.500	30.355	**82.700**	15.611	**82.700**
	(±34.000)	(±3.268)	(±23.398)	(±3.308)	(±32.283)	(±3.268)	(±15.215)	(±3.268)
Pima Indians Diabetes	22.204	**91.200**	26.598	90.900	21.091	91.100	54.652	89.500
	(±33.173)	(±5.329)	(±20.140)	(±6.173)	(±23.323)	(±5.322)	(±30.207)	(±6.704)
Thoracic Surgery	29.033	**46.200**	21.901	45.600	26.106	45.444	32.679	**46.200**
	(±28.946)	(±5.095)	(±14.735)	(±4.812)	(±27.370)	(±5.223)	(±20.418)	(±5.095)

4.3 Computational Experiments

In this paper, we preprocess features differently according to each algorithm's requirements. For RSCRULES, IREP, PRISM, IDS, and RIPPER, we discretize numerical features into ten equal bins. For BRS, we binarize features into a binary format. For OPDT and BSCRULES, while continuous numerical features can be used

without transformation, categorical features must be one-hot encoded. Regarding rule complexity, we limit the length of rule conditions to two for RIPPER, BRS in ruleset extracting models, and all structure-constrained models as shown in Tables 6 and 7. Other algorithms, having no such rule length parameter, can generate rules with conditions longer than two as they have more flexibility in rule generation. To provide another structure-constrained method alongside BSCCART, we develop a simple rule structure-constrained (RSC) algorithm based on Rules Extraction System (RULES) (Pham & Aksoy, 1995), which we call RSCRULES. Finally, we impose a 10-minute time limit on OPDT runtime.

For experiments, we create 10 random data splits through shuffling. For each split, we compute performance metrics and report their averages across the splits. Additionally, since RIPPER and BRS are non-deterministic algorithms, we run them with multiple random seeds on each split: 50 different seeds for BRS and 10 different seeds for RIPPER. The computational details are provided in Table 8 in the Appendix. We compare the induced rules based on their precision, coverage, and volume-impurity. Precision is calculated as the ratio between the number of samples correctly classified by a rule and the total number of samples covered by the rule. Coverage is computed as the ratio between the number of samples covered by the rule and the total number of samples in the dataset. VI is computed based on volume and misclassified samples with respect to weight w. We use test data to evaluate how well the induced rule captures a common pattern in unseen data.

Table 6: OPDT Performance at Various Methods on Training Datasets (80%). **Bold** indicates ranking in top 4 methods, and underlined represents the best performance across all methods.

| | | Training Data (80%) | | | | | | | |
| | | Structure-constrained Models | | | Ruleset Extracting Models | | | | |
Dataset		OPDT	BSCCART	RSCRULES	BRS	IDS	IREP	PRISM	Ripper
Australian	VI	**135.60**	**130.50**	103.40	**116.72**	36.30	103.40	44.20	**114.38**
	Time	602.00	0.25	0.04	0.36	0.22	0.08	3.03	2.01
German	VI	**60.00**	**49.80**	**57.80**	16.27	19.20	-32.20	20.10	**47.62**
	Time	749.82	0.20	0.10	0.53	0.25	0.09	7.20	0.17
Blood Transfusion	VI	**51.20**	**45.50**	**24.00**	-583.40	12.20	10.72	15.10	**18.17**
	Time	90.70	0.13	0.02	0.23	0.23	0.04	0.53	0.07
Breast Cancer	VI	**230.00**	**183.50**	**124.60**	114.00	111.70	50.51	**114.30**	50.50
	Time	790.97	7.25	0.06	0.59	0.22	0.39	2.95	0.49
Chronic Kidney	VI	**99.20**	**98.10**	52.90	46.31	49.60	**79.10**	52.90	**84.00**
	Time	6.60	0.24	0.02	0.33	0.19	0.13	0.29	0.15
Early Stage Diabetes	VI	**153.40**	**153.40**	121.20	**151.83**	119.30	118.16	90.60	**151.75**
	Time	3.71	0.03	0.02	0.54	0.21	0.04	0.63	0.08
Echocardiogram	VI	**18.10**	**14.50**	**9.90**	-8.13	**7.50**	4.31	7.10	5.74
	Time	0.80	0.07	0.01	0.24	0.18	0.05	0.18	0.07
Fertility	VI	**34.30**	**34.30**	17.40	**18.71**	**20.30**	16.19	15.00	17.18
	Time	0.25	0.02	0.01	0.27	0.19	0.03	0.13	0.04
Heart Disease	VI	**29.20**	**16.80**	**20.50**	15.01	**15.10**	-5.89	13.30	13.59
	Time	524.81	0.14	0.03	0.36	0.20	0.06	1.01	0.10
Heart Failure	VI	**62.10**	**29.60**	16.30	-41.97	19.40	17.58	**20.70**	**21.41**
	Time	729.32	0.36	0.03	0.30	0.19	0.07	0.82	0.11
Hepatitis	VI	**42.20**	**40.10**	17.50	**29.31**	25.00	26.33	21.80	**28.00**
	Time	0.82	0.10	0.01	0.27	0.19	0.06	0.15	0.07
Indian Liver Patient	VI	**82.50**	**54.50**	19.60	-790.93	17.40	**42.62**	18.10	**46.09**
	Time	999.70	0.61	0.04	0.27	0.21	0.09	2.98	0.14
Parkinsons	VI	**82.00**	**70.20**	**28.50**	**52.25**	25.40	17.56	26.70	18.16
	Time	863.11	1.77	0.03	0.37	0.19	0.35	1.56	0.41
Pima Indians Diabetes	VI	**89.10**	**36.20**	**37.40**	-920.73	21.50	22.69	22.80	**26.88**
	Time	1047.67	0.76	0.07	0.35	0.22	0.08	3.35	0.13
Thoracic Surgery	VI	**46.20**	**20.20**	**31.70**	-21.07	14.40	-2.14	16.90	**26.36**
	Time	133.21	0.10	0.02	2.13	0.21	0.05	1.70	2.16

First, Table 6 shows that OPDT can find better common patterns in data compared to other models, including ruleset extracting models that have more flexibility in rule length. Regarding runtime in Table 8 in the Appendix, we measure total runtime including warmstart generation, model initialization, and 10 minutes of solver time, which can exceed 600 seconds. In other words, a runtime less than 600 seconds

indicates the problem was solved to optimality. Table 8 demonstrates that several datasets were solved within the time limit, showing that OPDT is applicable for finding an optimal rule in moderate-sized datasets. Furthermore, as shown in Table 9 in the Appendix, even for datasets that do not reach optimality within the 10-minute limit, the best solutions are typically found within the first 2 minutes. Second, among the structure-constrained heuristic methods we developed, Table 6 shows that BSCCART performs better than RSCRULES. Moreover, BSCCART achieves the second-best performance in finding high-quality rules among all methods while complying with structure constraints given by domain experts. Among the ruleset extracting models, RIPPER shows comparably good performance to other methods.

As seen in Table 8, OPDT requires more than 10 minutes to prove optimality for some datasets. This could raise concerns about the scalability of OPDT to real-world applications. However, in this paper, we use only the basic numerical-categorical group separation without considering domain-specific knowledge for feature grouping. As shown in Table 4, if feature grouping is actively utilized, computational efficiency can be enhanced significantly. Finally, we evaluate the induced rules from each model on test datasets. Table 7 shows that OPDT achieves the best VI scores in 6 datasets, which is double that of BSCCART or RIPPER that have the best VI in 3 datasets. Furthermore, OPDT performs within the top 4 in most datasets, with exceptions in 5 datasets. BSCCART and RIPPER maintain their strong performance on test datasets, consistent with their performance in training datasets, showing the second-best results after OPDT.

Table 7: OPDT Performance at Various Methods on Testing Datasets (20%). **Bold** indicates ranking in top 4 methods, and underlined represents the best performance across all methods.

| | Test Data (20%) | | | | | | | |
| | Structure-constrained Models | | | Ruleset Extracting Models | | | | |
Dataset	OPDT	BSCCART	RSCRULES	BRS	IDS	IREP	PRISM	Ripper
Australian	**-6.50**	**-6.60**	**-6.30**	-299.24	-13.30	-28.31	**-10.10**	-31.68
German	**48.20**	**38.60**	**25.60**	21.22	21.30	10.04	**25.30**	10.62
Blood Transfusion	**16.80**	**17.60**	13.10	9.33	10.10	**19.83**	13.10	**21.80**
Breast Cancer	**22.80**	**21.70**	**20.60**	**20.93**	5.00	-41.30	8.20	-8.26
Chronic Kidney	-7.90	**1.80**	-4.20	**-0.71**	1.80	-37.32	**0.80**	**10.52**
Early Stage Diabetes	**38.10**	**39.60**	31.80	**38.31**	27.20	26.44	24.00	**38.74**
Echocardiogram	**-2.20**	**-1.60**	-2.80	-8.98	**-2.20**	**-0.10**	-2.30	**-1.33**
Fertility	**6.60**	**6.60**	0.10	1.03	3.10	**3.58**	3.80	-1.94
Heart Disease	-9.20	**5.00**	**-0.90**	**0.64**	**2.10**	-19.49	0.20	-4.52
Heart Failure	**5.10**	**-1.20**	-5.20	-19.25	**3.80**	-8.55	**1.00**	-6.73
Hepatitis	0.50	-2.20	-5.40	**3.43**	1.10	**4.55**	**2.70**	**5.66**
Indian Liver Patient	**12.70**	2.30	**4.20**	-198.45	3.50	**7.05**	**4.40**	-7.92
Parkinsons	2.80	-5.80	**8.60**	**9.06**	0.00	**4.06**	3.20	**4.60**
Pima Indians Diabetes	**4.90**	-8.40	**4.90**	-237.90	**3.70**	-9.60	**1.60**	-8.96
Thoracic Surgery	-9.80	**-3.80**	**-4.90**	-27.67	**-0.10**	-12.72	**4.50**	-8.17

5   Conclusion and Future Work

In this paper, we introduce a RBML model that demonstrates high interpretability and compliance for rule discovery. Our proposed model, OPDT, is based on an optimal decision tree, incorporating customizable rule structures based on decision-maker's needs. OPDT effectively identifies and describes significant patterns within a reasonable time while adhering to desired rule structures and precision requirements. To enhance computational efficiency, we develop three key techniques: branching structure constraints (BSC), warmstart initialization with BSCCART, and branching priority orders. Our experimental results across 15 UCI datasets demonstrate that OPDT consistently finds high-quality rules that comply with given structure constraints. Moreover, the systematic feature decomposition approach not only improves computational efficiency but also provides valuable guidance toward optimal solutions through strategic feature grouping. This work contributes to rule-based machine learning by providing a flexible framework for discovering interpretable rules that balance solution quality, structure compliance, and computational time.

References

Sina Aghaei, Andrés Gómez, and Phebe Vayanos. Strong optimal classification trees. *Operations Research*, 2024.

Muhammad Aurangzeb Ahmad, Carly Eckert, and Ankur Teredesai. Interpretable machine learning in healthcare. In *Proceedings of the 2018 ACM international conference on bioinformatics, computational biology, and health informatics*, pp. 559–560, 2018.

Zacharie Ales, Valentine Huré, and Amélie Lambert. New optimization models for optimal classification trees. *Computers & Operations Research*, 164:106515, 2024.

Shadnaz Asgari, Fabien Scalzo, and Magdalena Kasprowicz. Pattern recognition in medical decision support. *BioMed research international*, 2019, 2019.

Dimitris Bertsimas and Jack Dunn. Optimal classification trees. *Machine Learning*, 106:1039–1082, 2017.

Léon Bottou, Frank E Curtis, and Jorge Nocedal. Optimization methods for large-scale machine learning. *SIAM review*, 60(2):223–311, 2018.

Leo Breiman, Jerome H Friedman, Richard A Olshen, and Charles J Stone. *Classification and regression trees*. Wadsworth, 1984.

Jenna Burrell. How the machine 'thinks': Understanding opacity in machine learning algorithms. *Big data & society*, 3(1):2053951715622512, 2016.

Jadzia Cendrowska. Prism: An algorithm for inducing modular rules. *Knowledge-Based Systems*, 1:255–276, 1988.

William W Cohen et al. Fast effective rule induction. In *Proceedings of the twelfth international conference on machine learning*, pp. 115–123, 1995.

Murat Firat, Guillaume Crognier, Adriana F Gabor, Cor AJ Hurkens, and Yingqian Zhang. Column generation based heuristic for learning classification trees. *Computers & Operations Research*, 116:104866, 2020.

Jerome Friedman and Bogdan E Popescu. Gradient directed regularization. *Unpublished manuscript, http://www-stat. stanford. edu/jhf/ftp/pathlite. pdf*, 2004.

Jerome H Friedman and Bogdan E Popescu. Predictive learning via rule ensembles. *The Annals of Applied Statistics*, 2(3):916–954, 2008.

Johannes Fürnkranz and Gerhard Widmer. Incremental reduced error pruning. In *Machine learning proceedings 1994*, pp. 70–77. Elsevier, 1994.

Claudio Gambella, Bissan Ghaddar, and Joe Naoum-Sawaya. Optimization problems for machine learning: A survey. *European Journal of Operational Research*, 290(3):807–828, 2021.

Nicolas Goix, Vighnesh Birodkar, Florian Gardin, Jean-Matthieu Schertzer, HOEBIN JEONG, manoj kumar, Alexandre Gramfort, Tim Staley, Tom Dupré la Tour, Boyuan Deng, C, Fabian Pedregosa, Lawrence Wu, Ariel Rokem, Kyle Jackson, and mrahim. scikit-learn-contrib/skope-rules v1.0.1, 12 2020. URL https://doi.org/10.5281/zenodo.4316671.

Oktay Günlük, Jayant Kalagnanam, Minhan Li, Matt Menickelly, and Katya Scheinberg. Optimal decision trees for categorical data via integer programming. *Journal of global optimization*, 81:233–260, 2021.

Sara Hajian, Francesco Bonchi, and Carlos Castillo. Algorithmic bias: From discrimination discovery to fairness-aware data mining. In *Proceedings of the 22nd ACM SIGKDD international conference on knowledge discovery and data mining*, pp. 2125–2126, 2016.

Markelle Kelly, Rachel Longjohn, and Kolby Nottingham. Uci machine learning repository, 2017. URL https://archive.ics.uci.edu.

Inna Kolyshkina and Simeon Simoff. Interpretability of machine learning solutions in public healthcare: The crisp-ml approach. *Frontiers in big data*, 4:660206, 2021.

Miron B Kursa and Witold R Rudnicki. Feature selection with the boruta package. *Journal of statistical software*, 36:1–13, 2010.

Himabindu Lakkaraju, Stephen H Bach, and Jure Leskovec. Interpretable decision sets: A joint framework for description and prediction. In *Proceedings of the 22nd ACM SIGKDD international conference on knowledge discovery and data mining*, pp. 1675–1684, 2016.

Hyafil Laurent and Ronald L Rivest. Constructing optimal binary decision trees is np-complete. *Information processing letters*, 5(1):15–17, 1976.

Connor Lawless, Sanjeeb Dash, Oktay Gunluk, and Dennis Wei. Interpretable and fair boolean rule sets via column generation. *Journal of Machine Learning Research*, 24(229):1–50, 2023.

Joan Albert López-Vallverdú, David Riano, and Antoni Collado. Increasing acceptability of decision trees with domain attributes partial orders. In *Twentieth IEEE International Symposium on Computer-Based Medical Systems (CBMS'07)*, pp. 569–574. IEEE, 2007.

Scott M Lundberg and Su-In Lee. A unified approach to interpreting model predictions. *Advances in neural information processing systems*, 30, 2017.

Jake Luo, Min Wu, Deepika Gopukumar, and Yiqing Zhao. Big data application in biomedical research and health care: a literature review. *Biomedical informatics insights*, 8:BII–S31559, 2016.

Lorenzo Moja, Koren H Kwag, Theodore Lytras, Lorenzo Bertizzolo, Linn Brandt, Valentina Pecoraro, Giulio Rigon, Alberto Vaona, Francesca Ruggiero, Massimo Mangia, et al. Effectiveness of computerized decision support systems linked to electronic health records: a systematic review and meta-analysis. *American journal of public health*, 104(12):e12–e22, 2014.

W James Murdoch, Chandan Singh, Karl Kumbier, Reza Abbasi-Asl, and Bin Yu. Definitions, methods, and applications in interpretable machine learning. *Proceedings of the National Academy of Sciences*, 116 (44):22071–22080, 2019.

Kayvan Najarian, Kevin R Ward, Shahram Shirani, et al. Biomedical signal and image processing for clinical decision support systems. *Comput. Math. Methods Medicine*, 2013:578320–1, 2013.

Géraldin Nanfack, Paul Temple, and Benoît Frénay. Constraint enforcement on decision trees: A survey. *ACM Computing Surveys (CSUR)*, 54(10s):1–36, 2022.

Rafel Palliser-Sans. Rrules: An improvement of the rules rule-based classifier. *arXiv preprint arXiv:2106.07296*, 2021.

DT Pham and MS Aksoy. Rules: A simple rule extraction system. *Expert Systems with Applications*, 8(1): 59–65, 1995.

Susan Rea, Jyotishman Pathak, Guergana Savova, Thomas A Oniki, Les Westberg, Calvin E Beebe, Cui Tao, Craig G Parker, Peter J Haug, Stanley M Huff, et al. Building a robust, scalable and standards-driven infrastructure for secondary use of ehr data: the sharpn project. *Journal of biomedical informatics*, 45(4): 763–771, 2012.

Cynthia Rudin. Stop explaining black box machine learning models for high stakes decisions and use interpretable models instead. *Nature machine intelligence*, 1(5):206–215, 2019.

Cynthia Rudin, Chaofan Chen, Zhi Chen, Haiyang Huang, Lesia Semenova, and Chudi Zhong. Interpretable machine learning: Fundamental principles and 10 grand challenges. *Statistic Surveys*, 16:1–85, 2022.

Guolong Su, Dennis Wei, Kush R Varshney, and Dmitry M Malioutov. Learning sparse two-level boolean rules. In *2016 IEEE 26th International Workshop on Machine Learning for Signal Processing (MLSP)*, pp. 1–6. IEEE, 2016.

Sicco Verwer and Yingqian Zhang. Learning optimal classification trees using a binary linear program formulation. In *Proceedings of the AAAI conference on artificial intelligence*, volume 33, pp. 1625–1632, 2019.

Giulia Vilone and Luca Longo. Notions of explainability and evaluation approaches for explainable artificial intelligence. *Information Fusion*, 76:89–106, 2021.

Tong Wang, Cynthia Rudin, Finale Doshi-Velez, Yimin Liu, Erica Klampfl, and Perry MacNeille. A bayesian framework for learning rule sets for interpretable classification. *Journal of Machine Learning Research*, 18 (70):1–37, 2017.

A   Appendix

Table 8: OPDT and Benchmark Methods Performance on Training Data (80%) and Test Data (20%): mean ($\pm$ standard deviation) across 10 random data splits

| Dataset | Runtime | Training Data (80%) | | | Test Data (20%) | | |
		Precision	Coverage	VI	Precision	Coverage	VI
Blood Transfusion							
- OPDT	90.70	0.948	0.220	51.200	0.892	0.220	-6.500
	($\pm$11.522)	($\pm$0.014)	($\pm$0.055)	($\pm$10.443)	($\pm$0.017)	($\pm$0.072)	($\pm$14.222)
- BSCCART	0.13	0.955	0.195	45.500	0.889	0.195	-6.600
	($\pm$0.004)	($\pm$0.023)	($\pm$0.085)	($\pm$10.886)	($\pm$0.025)	($\pm$0.095)	($\pm$15.079)
- RSCRULES	0.02	0.963	0.088	24.000	0.841	0.087	-6.300
	($\pm$0.006)	($\pm$0.021)	($\pm$0.044)	($\pm$5.416)	($\pm$0.125)	($\pm$0.053)	($\pm$11.046)
- BRS	0.23	0.775	0.922	-583.396	0.771	0.921	-299.236
	($\pm$0.042)	($\pm$0.043)	($\pm$0.142)	($\pm$185.327)	($\pm$0.044)	($\pm$0.151)	($\pm$94.622)
- IDS	0.23	1.000	0.024	12.200	0.552	0.023	-13.300
	($\pm$0.006)	($\pm$0.000)	($\pm$0.007)	($\pm$3.676)	($\pm$0.337)	($\pm$0.012)	($\pm$11.605)
- IREP	0.04	0.931	0.085	10.720	0.785	0.124	-28.306
	($\pm$0.001)	($\pm$0.025)	($\pm$0.012)	($\pm$11.740)	($\pm$0.040)	($\pm$0.018)	($\pm$10.268)
- PRISM	0.53	0.993	0.034	15.100	0.707	0.036	-10.100
	($\pm$0.032)	($\pm$0.015)	($\pm$0.013)	($\pm$3.900)	($\pm$0.263)	($\pm$0.019)	($\pm$4.977)
- Ripper	0.07	0.959	0.071	18.166	0.687	0.112	-31.678
	($\pm$0.002)	($\pm$0.022)	($\pm$0.023)	($\pm$8.388)	($\pm$0.039)	($\pm$0.054)	($\pm$14.771)
Breast Cancer							
- OPDT	790.97	0.992	0.549	230.000	0.979	0.537	48.200
	($\pm$255.965)	($\pm$0.004)	($\pm$0.013)	($\pm$8.055)	($\pm$0.018)	($\pm$0.021)	($\pm$10.185)
- BSCCART	7.25	0.966	0.617	183.500	0.958	0.602	38.600
	($\pm$0.105)	($\pm$0.014)	($\pm$0.028)	($\pm$29.289)	($\pm$0.026)	($\pm$0.041)	($\pm$16.460)
- RSCRULES	0.06	0.971	0.386	124.600	0.962	0.365	25.600
	($\pm$0.003)	($\pm$0.007)	($\pm$0.029)	($\pm$20.359)	($\pm$0.024)	($\pm$0.043)	($\pm$9.698)
- BRS	0.59	1.000	0.251	113.998	0.982	0.235	21.216
	($\pm$0.092)	($\pm$0.000)	($\pm$0.025)	($\pm$11.555)	($\pm$0.022)	($\pm$0.045)	($\pm$5.170)
- IDS	0.22	1.000	0.245	111.700	0.982	0.231	21.300
	($\pm$0.027)	($\pm$0.000)	($\pm$0.037)	($\pm$16.747)	($\pm$0.031)	($\pm$0.048)	($\pm$7.973)
- IREP	0.39	1.000	0.111	50.514	0.975	0.110	10.041
	($\pm$0.001)	($\pm$0.000)	($\pm$0.007)	($\pm$3.355)	($\pm$0.030)	($\pm$0.014)	($\pm$4.096)
- PRISM	2.95	1.000	0.251	114.300	0.995	0.239	25.300
	($\pm$0.169)	($\pm$0.000)	($\pm$0.024)	($\pm$10.740)	($\pm$0.017)	($\pm$0.045)	($\pm$4.762)
- Ripper	0.49	1.000	0.111	50.502	0.993	0.100	10.618
	($\pm$0.003)	($\pm$0.000)	($\pm$0.007)	($\pm$3.309)	($\pm$0.008)	($\pm$0.023)	($\pm$3.265)
Chronic Kidney							
- OPDT	6.60	1.000	0.577	99.200	0.966	0.600	16.800
	($\pm$10.083)	($\pm$0.000)	($\pm$0.019)	($\pm$3.327)	($\pm$0.021)	($\pm$0.041)	($\pm$4.237)
- BSCCART	0.24	0.996	0.594	98.100	0.967	0.619	17.600
	($\pm$0.023)	($\pm$0.005)	($\pm$0.006)	($\pm$4.433)	($\pm$0.030)	($\pm$0.025)	($\pm$7.947)

Table 8 continued from previous page

Dataset	Training Data (80%)				Test Data (20%)		
	Runtime	Precision	Coverage	VI	Precision	Coverage	VI
- RSCRULES	0.02	1.000	0.308	52.900	1.000	0.305	13.100
	(±0.000)	(±0.000)	(±0.009)	(±1.524)	(±0.000)	(±0.035)	(±1.524)
- BRS	0.33	0.999	0.276	46.305	0.982	0.276	9.332
	(±0.066)	(±0.002)	(±0.014)	(±0.964)	(±0.008)	(±0.009)	(±0.879)
- IDS	0.19	1.000	0.288	49.600	0.983	0.281	10.100
	(±0.003)	(±0.000)	(±0.017)	(±2.914)	(±0.053)	(±0.040)	(±6.590)
- IREP	0.13	0.984	0.551	79.096	0.996	0.488	19.834
	(±0.001)	(±0.003)	(±0.012)	(±3.668)	(±0.004)	(±0.046)	(±1.621)
- PRISM	0.29	1.000	0.308	52.900	1.000	0.305	13.100
	(±0.135)	(±0.000)	(±0.009)	(±1.524)	(±0.000)	(±0.035)	(±1.524)
- Ripper	0.15	0.987	0.563	84.004	0.998	0.520	21.796
	(±0.001)	(±0.002)	(±0.006)	(±2.406)	(±0.002)	(±0.044)	(±1.456)
Australian							
- OPDT	602.00	0.963	0.411	135.600	0.940	0.426	22.800
	(±482.907)	(±0.007)	(±0.018)	(±12.492)	(±0.028)	(±0.039)	(±15.091)
- BSCCART	0.25	0.957	0.442	130.500	0.937	0.456	21.700
	(±0.175)	(±0.007)	(±0.015)	(±14.254)	(±0.023)	(±0.040)	(±13.598)
- RSCRULES	0.04	0.943	0.462	103.400	0.933	0.478	20.600
	(±0.011)	(±0.006)	(±0.006)	(±14.010)	(±0.023)	(±0.026)	(±14.010)
- BRS	0.36	0.950	0.453	116.720	0.934	0.470	20.930
	(±0.009)	(±0.006)	(±0.020)	(±13.667)	(±0.022)	(±0.029)	(±13.623)
- IDS	0.22	1.000	0.070	36.300	0.955	0.069	5.000
	(±0.005)	(±0.000)	(±0.028)	(±14.863)	(±0.065)	(±0.032)	(±5.598)
- IREP	0.08	0.943	0.462	103.400	0.811	0.315	-41.303
	(±0.001)	(±0.006)	(±0.006)	(±14.010)	(±0.043)	(±0.089)	(±27.431)
- PRISM	3.03	1.000	0.085	44.200	0.963	0.085	8.200
	(±0.133)	(±0.000)	(±0.007)	(±3.584)	(±0.078)	(±0.025)	(±8.135)
- Ripper	2.01	0.952	0.428	114.384	0.826	0.106	-8.260
	(±5.924)	(±0.006)	(±0.014)	(±13.649)	(±0.063)	(±0.051)	(±3.715)
German							
- OPDT	749.82	0.936	0.225	60.000	0.883	0.231	-7.900
	(±370.714)	(±0.011)	(±0.085)	(±12.481)	(±0.020)	(±0.098)	(±10.609)
- BSCCART	0.20	0.920	0.315	49.800	0.896	0.326	-1.800
	(±0.126)	(±0.008)	(±0.023)	(±18.920)	(±0.027)	(±0.043)	(±16.498)
- RSCRULES	0.10	0.938	0.205	57.800	0.895	0.199	-4.200
	(±0.006)	(±0.012)	(±0.087)	(±13.815)	(±0.032)	(±0.094)	(±10.696)
- BRS	0.53	0.908	0.349	16.266	0.901	0.361	-0.712
	(±0.064)	(±0.010)	(±0.017)	(±33.298)	(±0.029)	(±0.030)	(±20.104)
- IDS	0.25	1.000	0.024	19.200	0.950	0.019	1.800
	(±0.009)	(±0.000)	(±0.004)	(±3.360)	(±0.112)	(±0.007)	(±4.077)
- IREP	0.09	0.867	0.209	-32.202	0.801	0.266	-37.322
	(±0.002)	(±0.014)	(±0.043)	(±13.316)	(±0.023)	(±0.051)	(±13.754)
- PRISM	7.20	1.000	0.025	20.100	0.949	0.024	0.800
	(±0.112)	(±0.000)	(±0.003)	(±2.079)	(±0.086)	(±0.013)	(±4.803)
- Ripper	0.17	0.925	0.256	47.618	0.917	0.207	10.524
	(±0.001)	(±0.010)	(±0.045)	(±17.287)	(±0.017)	(±0.095)	(±8.096)
Early Stage Diabetes							
- OPDT	3.71	0.999	0.374	153.400	0.996	0.386	38.100
	(±3.314)	(±0.004)	(±0.012)	(±3.565)	(±0.012)	(±0.045)	(±3.725)
- BSCCART	0.03	1.000	0.369	153.400	1.000	0.381	39.600
	(±0.000)	(±0.000)	(±0.009)	(±3.565)	(±0.000)	(±0.034)	(±3.565)
- RSCRULES	0.02	0.965	0.448	121.200	0.968	0.450	31.800
	(±0.009)	(±0.006)	(±0.008)	(±10.163)	(±0.023)	(±0.032)	(±10.163)
- BRS	0.54	1.000	0.365	151.830	1.000	0.369	38.314
	(±0.086)	(±0.000)	(±0.009)	(±3.751)	(±0.001)	(±0.033)	(±3.537)
- IDS	0.21	1.000	0.287	119.300	0.995	0.271	27.200
	(±0.003)	(±0.000)	(±0.067)	(±27.745)	(±0.015)	(±0.082)	(±9.953)
- IREP	0.04	0.966	0.437	118.158	0.970	0.381	26.444
	(±0.001)	(±0.006)	(±0.019)	(±12.140)	(±0.017)	(±0.063)	(±7.322)
- PRISM	0.63	1.000	0.218	90.600	1.000	0.231	24.000
	(±0.059)	(±0.000)	(±0.056)	(±23.201)	(±0.000)	(±0.062)	(±6.446)
- Ripper	0.08	0.999	0.371	151.746	0.999	0.375	38.740
	(±0.002)	(±0.001)	(±0.010)	(±3.258)	(±0.001)	(±0.033)	(±3.551)
Echocardiogram							

Table 8 continued from previous page

Dataset	Training Data (80%)				Test Data (20%)		
	Runtime	Precision	Coverage	VI	Precision	Coverage	VI
- OPDT	0.80	0.988	0.430	18.100	0.762	0.369	-2.200
	(±0.618)	(±0.020)	(±0.094)	(±4.818)	(±0.317)	(±0.191)	(±6.477)
- BSCCART	0.07	0.961	0.500	14.500	0.886	0.492	-1.600
	(±0.013)	(±0.036)	(±0.040)	(±7.990)	(±0.136)	(±0.126)	(±9.477)
- RSCRULES	0.01	0.986	0.263	9.900	0.598	0.246	-2.800
	(±0.001)	(±0.022)	(±0.163)	(±4.886)	(±0.439)	(±0.248)	(±5.138)
- BRS	0.24	0.937	0.429	-8.132	0.782	0.428	-8.982
	(±0.035)	(±0.041)	(±0.118)	(±15.676)	(±0.110)	(±0.174)	(±3.871)
- IDS	0.18	1.000	0.153	7.500	0.831	0.215	-2.200
	(±0.003)	(±0.000)	(±0.036)	(±1.780)	(±0.171)	(±0.149)	(±3.994)
- IREP	0.05	0.949	0.267	4.307	0.935	0.229	-0.102
	(±0.001)	(±0.032)	(±0.093)	(±5.100)	(±0.087)	(±0.095)	(±3.682)
- PRISM	0.18	1.000	0.145	7.100	0.500	0.131	-2.300
	(±0.016)	(±0.000)	(±0.095)	(±4.654)	(±0.456)	(±0.195)	(±4.644)
- Ripper	0.07	0.966	0.223	5.740	0.894	0.166	-1.325
	(±0.001)	(±0.027)	(±0.102)	(±4.041)	(±0.065)	(±0.089)	(±2.444)
Fertility							
- OPDT	0.25	1.000	0.429	34.300	0.971	0.480	6.600
	(±0.132)	(±0.000)	(±0.024)	(±1.947)	(±0.049)	(±0.098)	(±4.477)
- BSCCART	0.02	1.000	0.429	34.300	0.971	0.480	6.600
	(±0.003)	(±0.000)	(±0.024)	(±1.947)	(±0.049)	(±0.098)	(±4.477)
- RSCRULES	0.01	0.969	0.342	17.400	0.912	0.405	0.100
	(±0.001)	(±0.024)	(±0.095)	(±3.950)	(±0.072)	(±0.119)	(±5.021)
- BRS	0.27	0.997	0.259	18.713	0.910	0.293	1.025
	(±0.025)	(±0.006)	(±0.047)	(±4.000)	(±0.075)	(±0.074)	(±3.001)
- IDS	0.19	1.000	0.254	20.300	0.965	0.255	3.100
	(±0.003)	(±0.000)	(±0.034)	(±2.710)	(±0.082)	(±0.096)	(±3.604)
- IREP	0.03	0.958	0.375	16.192	0.954	0.371	3.577
	(±0.001)	(±0.019)	(±0.053)	(±4.380)	(±0.024)	(±0.046)	(±1.860)
- PRISM	0.13	1.000	0.188	15.000	0.976	0.290	3.800
	(±0.029)	(±0.000)	(±0.037)	(±2.981)	(±0.052)	(±0.115)	(±3.327)
- Ripper	0.04	0.969	0.333	17.182	0.876	0.206	-1.939
	(±0.001)	(±0.009)	(±0.044)	(±3.462)	(±0.052)	(±0.100)	(±2.228)
Heart Disease							
- OPDT	524.81	0.979	0.165	29.200	0.800	0.180	-9.200
	(±534.168)	(±0.021)	(±0.047)	(±3.155)	(±0.063)	(±0.079)	(±5.160)
- BSCCART	0.14	0.926	0.269	16.800	0.944	0.250	5.000
	(±0.019)	(±0.011)	(±0.021)	(±6.339)	(±0.074)	(±0.058)	(±13.199)
- RSCRULES	0.03	0.969	0.137	20.500	0.929	0.118	-0.900
	(±0.005)	(±0.020)	(±0.052)	(±3.171)	(±0.097)	(±0.064)	(±7.937)
- BRS	0.36	0.949	0.210	15.010	0.928	0.200	0.636
	(±0.049)	(±0.037)	(±0.079)	(±17.335)	(±0.089)	(±0.081)	(±11.493)
- IDS	0.20	1.000	0.064	15.100	0.955	0.068	2.100
	(±0.002)	(±0.000)	(±0.015)	(±3.510)	(±0.096)	(±0.020)	(±4.175)
- IREP	0.06	0.903	0.224	-5.888	0.827	0.342	-19.485
	(±0.001)	(±0.020)	(±0.039)	(±11.122)	(±0.043)	(±0.025)	(±10.521)
- PRISM	1.01	1.000	0.056	13.300	0.922	0.053	0.200
	(±0.040)	(±0.000)	(±0.008)	(±1.889)	(±0.130)	(±0.022)	(±4.442)
- Ripper	0.10	0.944	0.163	13.592	0.852	0.208	-4.524
	(±0.001)	(±0.010)	(±0.046)	(±5.094)	(±0.042)	(±0.037)	(±5.392)
Heart Failure							
- OPDT	729.32	0.982	0.331	62.100	0.935	0.335	5.100
	(±581.965)	(±0.017)	(±0.088)	(±5.859)	(±0.045)	(±0.124)	(±9.036)
- BSCCART	0.36	0.927	0.513	29.600	0.884	0.530	-1.200
	(±0.008)	(±0.012)	(±0.178)	(±11.937)	(±0.053)	(±0.178)	(±12.136)
- RSCRULES	0.03	0.975	0.097	16.300	0.817	0.097	-5.200
	(±0.004)	(±0.023)	(±0.028)	(±4.296)	(±0.114)	(±0.064)	(±4.211)
- BRS	0.30	0.953	0.238	-41.974	0.782	0.239	-19.254
	(±0.062)	(±0.096)	(±0.318)	(±126.072)	(±0.106)	(±0.333)	(±30.173)
- IDS	0.19	1.000	0.081	19.400	0.975	0.080	3.800
	(±0.003)	(±0.000)	(±0.008)	(±2.011)	(±0.079)	(±0.029)	(±3.853)
- IREP	0.07	0.975	0.103	17.578	0.823	0.123	-8.545
	(±0.002)	(±0.018)	(±0.012)	(±5.046)	(±0.064)	(±0.037)	(±8.333)
- PRISM	0.82	1.000	0.087	20.700	0.955	0.067	1.000
	(±0.078)	(±0.000)	(±0.012)	(±2.908)	(±0.096)	(±0.039)	(±4.944)

Table 8 continued from previous page

Dataset	Training Data (80%)				Test Data (20%)		
	Runtime	Precision	Coverage	VI	Precision	Coverage	VI
- Ripper	0.11	0.994	0.096	21.412	0.792	0.088	-6.730
	(±0.002)	(±0.012)	(±0.006)	(±3.611)	(±0.063)	(±0.025)	(±3.177)
Hepatitis							
- OPDT	0.82	0.998	0.675	42.200	0.907	0.656	0.500
	(±0.727)	(±0.006)	(±0.059)	(±3.393)	(±0.082)	(±0.107)	(±7.792)
- BSCCART	0.10	0.986	0.736	40.100	0.885	0.737	-2.200
	(±0.028)	(±0.013)	(±0.053)	(±3.755)	(±0.069)	(±0.121)	(±8.804)
- RSCRULES	0.01	0.947	0.664	17.500	0.873	0.662	-5.400
	(±0.002)	(±0.024)	(±0.198)	(±4.223)	(±0.091)	(±0.238)	(±8.449)
- BRS	0.27	1.000	0.458	29.314	0.962	0.446	3.429
	(±0.022)	(±0.000)	(±0.187)	(±11.940)	(±0.049)	(±0.186)	(±3.645)
- IDS	0.19	1.000	0.391	25.000	0.915	0.381	1.100
	(±0.027)	(±0.000)	(±0.085)	(±5.416)	(±0.133)	(±0.133)	(±7.310)
- IREP	0.06	0.967	0.646	26.330	0.970	0.475	4.554
	(±0.001)	(±0.014)	(±0.054)	(±4.966)	(±0.020)	(±0.143)	(±2.280)
- PRISM	0.15	1.000	0.341	21.800	0.881	0.294	2.700
	(±0.017)	(±0.000)	(±0.133)	(±8.496)	(±0.312)	(±0.213)	(±1.889)
- Ripper	0.07	0.973	0.615	28.004	0.988	0.430	5.664
	(±0.001)	(±0.012)	(±0.045)	(±4.501)	(±0.024)	(±0.174)	(±2.723)
Indian Liver Patient							
- OPDT	999.70	0.981	0.221	82.500	0.948	0.239	12.700
	(±224.994)	(±0.008)	(±0.024)	(±10.069)	(±0.043)	(±0.028)	(±10.843)
- BSCCART	0.61	0.942	0.297	54.500	0.907	0.313	2.300
	(±0.015)	(±0.022)	(±0.040)	(±24.968)	(±0.036)	(±0.056)	(±13.679)
- RSCRULES	0.04	0.996	0.044	19.600	0.986	0.045	4.200
	(±0.015)	(±0.013)	(±0.006)	(±2.716)	(±0.045)	(±0.013)	(±2.860)
- BRS	0.27	0.731	0.902	-790.932	0.730	0.896	-198.454
	(±0.043)	(±0.031)	(±0.088)	(±96.273)	(±0.032)	(±0.087)	(±24.312)
- IDS	0.21	1.000	0.038	17.400	0.975	0.039	3.500
	(±0.003)	(±0.000)	(±0.005)	(±2.366)	(±0.079)	(±0.017)	(±3.866)
- IREP	0.09	0.995	0.104	42.624	0.959	0.113	7.045
	(±0.002)	(±0.005)	(±0.008)	(±7.690)	(±0.021)	(±0.021)	(±5.418)
- PRISM	2.98	1.000	0.039	18.100	1.000	0.038	4.400
	(±0.054)	(±0.000)	(±0.006)	(±2.923)	(±0.000)	(±0.022)	(±2.591)
- Ripper	0.14	0.999	0.101	46.088	0.775	0.064	-7.918
	(±0.001)	(±0.001)	(±0.001)	(±0.820)	(±0.060)	(±0.014)	(±3.601)
Parkinsons							
- OPDT	863.11	0.999	0.532	82.000	0.919	0.508	2.800
	(±340.952)	(±0.003)	(±0.032)	(±4.447)	(±0.052)	(±0.077)	(±9.682)
- BSCCART	1.77	0.977	0.597	70.200	0.884	0.621	-5.800
	(±0.116)	(±0.018)	(±0.077)	(±10.633)	(±0.070)	(±0.109)	(±18.207)
- RSCRULES	0.03	0.976	0.240	28.500	0.990	0.246	8.600
	(±0.007)	(±0.009)	(±0.014)	(±3.689)	(±0.032)	(±0.058)	(±3.777)
- BRS	0.37	1.000	0.335	52.247	0.978	0.315	9.064
	(±0.061)	(±0.000)	(±0.058)	(±9.034)	(±0.027)	(±0.073)	(±4.337)
- IDS	0.19	1.000	0.163	25.400	0.876	0.154	0.000
	(±0.004)	(±0.000)	(±0.033)	(±5.103)	(±0.166)	(±0.091)	(±4.397)
- IREP	0.35	0.998	0.116	17.560	0.983	0.120	4.056
	(±0.002)	(±0.003)	(±0.009)	(±1.554)	(±0.012)	(±0.018)	(±0.831)
- PRISM	1.56	1.000	0.171	26.700	0.954	0.185	3.200
	(±0.140)	(±0.000)	(±0.030)	(±4.668)	(±0.062)	(±0.067)	(±3.910)
- Ripper	0.41	1.000	0.117	18.164	1.000	0.116	4.599
	(±0.003)	(±0.000)	(±0.010)	(±1.515)	(±0.001)	(±0.018)	(±0.687)
Pima Indians Diabetes							
- OPDT	1047.67	0.979	0.187	89.100	0.925	0.201	4.900
	(±76.896)	(±0.012)	(±0.032)	(±6.590)	(±0.049)	(±0.047)	(±12.758)
- BSCCART	0.76	0.922	0.297	36.200	0.889	0.309	-8.400
	(±0.010)	(±0.039)	(±0.105)	(±46.492)	(±0.038)	(±0.117)	(±21.287)
- RSCRULES	0.07	0.962	0.105	37.400	0.953	0.097	4.900
	(±0.003)	(±0.016)	(±0.041)	(±8.897)	(±0.047)	(±0.055)	(±7.340)
- BRS	0.35	0.727	0.859	-920.728	0.722	0.863	-237.896
	(±0.025)	(±0.006)	(±0.022)	(±36.483)	(±0.022)	(±0.037)	(±36.960)
- IDS	0.22	1.000	0.035	21.500	0.963	0.037	3.700
	(±0.008)	(±0.000)	(±0.010)	(±6.042)	(±0.078)	(±0.019)	(±5.250)

Table 8 continued from previous page

Dataset	Training Data (80%)				Test Data (20%)		
	Runtime	Precision	Coverage	VI	Precision	Coverage	VI
- IREP	0.08	0.938	0.100	22.686	0.837	0.093	-9.601
	($\pm$0.001)	($\pm$0.013)	($\pm$0.005)	($\pm$6.723)	($\pm$0.026)	($\pm$0.016)	($\pm$3.598)
- PRISM	3.35	1.000	0.037	22.800	0.924	0.049	1.600
	($\pm$0.137)	($\pm$0.000)	($\pm$0.015)	($\pm$8.942)	($\pm$0.107)	($\pm$0.021)	($\pm$8.859)
- Ripper	0.13	0.980	0.064	26.876	0.802	0.056	-8.958
	($\pm$0.003)	($\pm$0.015)	($\pm$0.019)	($\pm$5.161)	($\pm$0.057)	($\pm$0.020)	($\pm$4.647)
Thoracic Surgery							
- OPDT	133.21	0.949	0.264	46.200	0.855	0.247	-9.800
	($\pm$327.588)	($\pm$0.012)	($\pm$0.058)	($\pm$5.095)	($\pm$0.079)	($\pm$0.037)	($\pm$16.430)
- BSCCART	0.10	0.991	0.064	20.200	0.521	0.066	-3.800
	($\pm$0.047)	($\pm$0.015)	($\pm$0.052)	($\pm$15.483)	($\pm$0.449)	($\pm$0.054)	($\pm$4.392)
- RSCRULES	0.02	0.937	0.244	31.700	0.867	0.214	-4.900
	($\pm$0.006)	($\pm$0.010)	($\pm$0.084)	($\pm$7.009)	($\pm$0.059)	($\pm$0.091)	($\pm$13.304)
- BRS	2.13	0.898	0.706	-21.068	0.863	0.717	-27.672
	($\pm$5.802)	($\pm$0.015)	($\pm$0.127)	($\pm$45.358)	($\pm$0.023)	($\pm$0.143)	($\pm$12.292)
- IDS	0.21	1.000	0.038	14.400	0.933	0.031	-0.100
	($\pm$0.003)	($\pm$0.000)	($\pm$0.011)	($\pm$4.169)	($\pm$0.200)	($\pm$0.022)	($\pm$8.950)
- IREP	0.05	0.902	0.322	-2.136	0.862	0.445	-12.724
	($\pm$0.002)	($\pm$0.014)	($\pm$0.049)	($\pm$18.640)	($\pm$0.016)	($\pm$0.072)	($\pm$4.690)
- PRISM	1.70	1.000	0.045	16.900	1.000	0.048	4.500
	($\pm$0.090)	($\pm$0.000)	($\pm$0.005)	($\pm$1.912)	($\pm$0.000)	($\pm$0.020)	($\pm$1.841)
- Ripper	2.16	0.914	0.250	26.356	0.835	0.130	-8.167
	($\pm$6.556)	($\pm$0.023)	($\pm$0.044)	($\pm$10.267)	($\pm$0.069)	($\pm$0.050)	($\pm$5.930)

Table 9: OPDT Runtime and Time to Solution (in seconds) without BSC

dataset	Runtime	Time to Solution
Australian	139.363 ($\pm$45.693)	11.625 ($\pm$14.371)
German	930.113 ($\pm$382.954)	104.823 ($\pm$141.195)
Blood Transfusion	776.287 ($\pm$534.019)	2.771 ($\pm$2.539)
Breast Cancer	1096.570 ($\pm$234.938)	125.454 ($\pm$300.844)
Chronic Kidney	916.377 ($\pm$292.314)	119.097 ($\pm$169.979)
Early Stage Diabetes	112.018 ($\pm$311.394)	2.764 ($\pm$2.390)
Echocardiogram	109.457 ($\pm$321.932)	0.176 ($\pm$0.487)
Fertility	4.687 ($\pm$1.996)	0.213 ($\pm$0.448)
Heart Disease	904.345 ($\pm$380.713)	41.906 ($\pm$85.544)
Heart Failure	187.302 ($\pm$42.433)	17.734 ($\pm$27.696)
Hepatitis	8.601 ($\pm$3.545)	0.560 ($\pm$1.071)
Indian Liver Patient	1161.727 ($\pm$196.850)	10.659 ($\pm$12.828)
Parkinsons	899.464 ($\pm$338.915)	14.228 ($\pm$29.471)
Pima Indians Diabetes	600.030 ($\pm$0.007)	140.321 ($\pm$182.179)
Thoracic Surgery	585.058 ($\pm$47.319)	28.280 ($\pm$32.392)