PRISM: Post-Training LLM Pruning via Residual Importance Signal Merging and Intra-Block Sparsity Allocation

Abstract

Post-training pruning compresses Large Language Models (LLMs) without retraining, but performance degrades sharply at high sparsity. We identify two limitations in existing methods: local importance estimates miss global spectral structure, and uniform within-block sparsity ignores heterogeneous sensitivity across transformer projections. We propose **PRISM**, a post-training pruning framework that augments activation-based scoring with two adaptive-rank SVD-derived signals for principal-subspace and residual-aware importance, combines the factors through parameter-free CV-based fusion, and allocates sparsity non-uniformly across attention and MLP projections using a gradient-weighted matrix-level sensitivity proxy. Across six Qwen3 and LLaMA models, PRISM consistently outperforms existing pruning baselines, yielding up to 16.8% relative improvement in WikiText-2 perplexity under the evaluated sparsity settings.

1 Introduction

The proliferation of Large Language Models (LLMs) has revolutionized natural language processing, with models like GPT-4 (OpenAI, 2023), LLaMA-3.1 (Dubey et al., 2024), and Qwen3 (Team, 2025) demonstrating unprecedented capabilities across diverse tasks. However, this performance comes at the cost of massive parameter counts—ranging from billions to trillions of parameters—creating substantial barriers to deployment in resource-constrained environments (Frantar and Alistarh, 2023; Sun et al., 2024).

Model compression techniques, including quantization (Lin et al., 2024; Frantar et al., 2022), pruning (Frantar and Alistarh, 2023; Sun et al., 2024), and low-rank decomposition (Hsu et al., 2022; Yuan et al., 2023), have emerged as essential strategies for reducing computational and memory requirements. Among these, **post-training pruning** is particularly attractive as it eliminates the need for expensive retraining while achieving significant compression ratios (Sun et al., 2024; Frantar and Alistarh, 2023). At high sparsity, however, current post-training pruning methods still suffer from two core bottlenecks:

(a) Local Scoring Without Global Structural Awareness. Methods like Wanda (Sun et al., 2024) score weights solely by activation magnitude ($|W_{ij}| \cdot \|X_j\|_2$), implicitly assuming a *diagonal* input covariance and therefore minimizing only the element-wise reconstruction error while ignoring *cross-column* correlations. SparseGPT (Frantar and Alistarh, 2023) partially addresses this via approximate Hessian information, but its row-by-row greedy weight update still solves a *local* regression for each row independently—it does not model the *global spectral structure* shared across all rows of the weight matrix. In transformer layers, where input features are strongly correlated after LayerNorm and attention, this lack of a global structural prior causes both methods to systematically under-estimate the pruning cost for weights that lie within the weight matrix's principal singular subspace—structurally important weights that are individually unremarkable yet jointly critical. This bottleneck becomes even harder once multiple complementary signals are available: recent adaptive fusion methods such as HyWIA (Liu et al., 2025) introduce learned weighting mechanisms to combine different importance assessments, while hand-tuned fixed mixtures increase adaptation cost and can generalize poorly across matrices. A training-free adaptive fusion mechanism that can combine local and spectral cues is therefore still missing.

(b) Uniform Per-Matrix Pruning. Recent non-uniform allocation methods such as OWL (Yin et al., 2024), BESA (Xu et al., 2024), and AlphaPruning (Lu et al., 2024) have shown that sparsity should not be assigned uniformly *across layers*. However, they distribute budgets only at the layer level and treat all projection matrices within a trans-

Figure 1: Illustration of the mechanism targeted by PRISM: preserving structurally important weights missed by local pruning, which can reduce the cross-column term $\mathcal{L}_{\text{cross}}$ under the analysis in Section 3.6.

former block identically. As a result, both inter-layer methods and uniform pruning baselines such as Wanda (Sun et al., 2024) and SparseGPT (Frantar and Alistarh, 2023) apply the same sparsity ratio to every projection matrix ($\mathbf{W}_q, \mathbf{W}_k, \mathbf{W}_v, \mathbf{W}_o$ in attention and $\mathbf{W}_{\text{up}}, \mathbf{W}_{\text{gate}}, \mathbf{W}_{\text{down}}$ in MLP) within each block. This overlooks the heterogeneous sensitivity across matrices—attention projections and MLP projections contribute unevenly to the output—and can therefore over-prune high-impact matrices (Ilin and Richtarik, 2025). This gap suggests that intra-block allocation should complement, rather than replace, existing inter-layer budget schemes.

Figure 1 contrasts the first bottleneck with PRISM's remedy: weights that look individually unremarkable can still be structurally important, and PRISM preserves them by adding SVD-derived importance signals. To address these two bottlenecks, we propose **PRISM** (**P**ost-training p**R**uning via res**I**dual importance **S**ignal **M**erging). The method is organized around two core ideas plus one enabling mechanism:

1. **Spectral-Aware Multi-Factor Scoring.** We introduce two complementary importance signals derived from adaptive-rank SVD that expose the global spectral structure of weight matrices—information invisible to both activation-based scoring (Wanda) and row-local Hessian regression (SparseGPT). By decomposing $\mathbf{W} = \mathbf{W}_{\text{low}} + \mathbf{R}$, we derive: (a) *residual-gated magnitude*, a matrix-normalized measure that highlights weights well reconstructed by the low-rank component, and (b) *low-rank component importance*, which highlights weights lying in the principal singular subspace. These two sig-

nals capture complementary aspects of spectral structure. Unlike SVD-based compression methods that replace weight matrices with low-rank factorizations, PRISM uses SVD only for one-shot importance estimation and retains the original weight structure.

2. **CV-Based Parameter-Free Fusion.** To combine activation and spectral cues without auxiliary training, we derive matrix-level fusion weights from the coefficient of variation (CV) of the candidate factors. This simple training-free rule adaptively reweights the three signals for each matrix and requires neither learnable parameters nor grid search (Section 3.3).

3. **Gradient-Weighted Intra-Block Allocation.** We complement existing inter-layer allocation methods by allocating heterogeneous sparsity *within* each transformer block, across its 7 projection matrices ($\mathbf{W}_q, \mathbf{W}_k, \mathbf{W}_v, \mathbf{W}_o, \mathbf{W}_{\text{up}}, \mathbf{W}_{\text{gate}}, \mathbf{W}_{\text{down}}$). This gradient-weighted block-local allocator prevents over-pruning of high-impact matrices and is designed to work on top of an external layer-wise budget. It is therefore complementary to existing inter-layer sparsity allocation methods.

Extensive evaluations across six Qwen3 and LLaMA models show consistent gains for PRISM under unstructured and N:M sparsity.

2 Related Work

Post-training pruning removes weights from pre-trained models without retraining, making it attractive for billion-scale LLMs. Wanda (Sun et al., 2024) scores weights by $|W_{ij}| \cdot \|X_j\|_2$, and Wanda++ (Yang et al., 2025) adds regional updates while retaining the same activation-centric scoring. SparseGPT (Frantar and Alistarh, 2023), Thanos (Ilin and Richtarik, 2025), and FISTAPruner (Zhao et al., 2025) incorporate richer second-order or structured approximations, but they still operate locally rather than modeling the global spectral structure shared across rows of a weight matrix. SVD-based compression methods such as ASVD (Yuan et al., 2023), SVD-LLM (Wang et al., 2025b), and Dobi-SVD (Wang et al., 2025a), as well as sparse–low-rank hybrids such as HASSLE-free (Makni et al., 2025) and SALR (Zhang et al., 2026), exploit spectral structure by changing the deployed representation. PRISM instead uses SVD only as a

one-shot diagnostic for importance estimation and keeps the original sparse architecture unchanged.

Combining multiple pruning signals is itself non-trivial. HyWIA (Liu et al., 2025) adaptively blends fine- and coarse-grained importance assessments for structured LLM pruning, UNComp (Xiong et al., 2025) uses entropy-style uncertainty measures for KV-cache compression, and MaskLLM (Fang et al., 2024) learns adaptive semi-structured masks end-to-end. In contrast, our CV-based fusion is training-free and parameter-free: it derives matrix-level adaptive weights from the relative dispersion of the candidate factors.

For non-uniform sparsity allocation, OWL (Yin et al., 2024), BESA (Xu et al., 2024), and AlphaPruning (Lu et al., 2024) assign different budgets across layers, but still use uniform sparsity across the projection matrices inside each transformer block. PRISM targets this finer within-block granularity, allocating retention across $\mathbf{W}_q, \mathbf{W}_k, \mathbf{W}_v, \mathbf{W}_o, \mathbf{W}_{\text{up}}, \mathbf{W}_{\text{gate}}, \mathbf{W}_{\text{down}}$, and is therefore complementary to representative inter-layer allocators such as AlphaPruning.

3 Methodology

3.1 Preliminaries and Problem Formulation

Figure 2 illustrates the complete PRISM pipeline. Consider an LLM with L transformer layers. For layer l, let $\mathbf{W}^{(l)} \in \mathbb{R}^{m_l \times n_l}$ denote a weight matrix (e.g., query projection in attention or up-projection in FFN). Given a calibration dataset $\mathcal{D}_{cal} = \{(\mathbf{X}_i, \mathbf{y}_i)\}_{i=1}^N$, our goal is to find a sparse mask $\mathbf{M}^{(l)} \in \{0, 1\}^{m_l \times n_l}$ for each layer such that:

$$\min_{\{\mathbf{M}^{(l)}\}} \quad \mathcal{L}\Big(f_{\text{pruned}}(\mathbf{X}; \{\mathbf{M}^{(l)} \odot \mathbf{W}^{(l)}\}), \mathbf{y}\Big)$$
$$\text{s.t.} \quad \frac{\|\mathbf{M}^{(l)}\|_0}{m_l \cdot n_l} = 1 - s^{(l)} \tag{1}$$

where $s^{(l)}$ is the sparsity ratio for layer l and $\mathcal{L}$ is the language modeling loss.

3.2 Adaptive-Rank SVD for Multi-Signal Construction

Weight matrices in LLMs exhibit low-rank structure combined with sparse residual information (Hsu et al., 2022). This structure has a direct consequence for pruning: the layer reconstruction error $\mathcal{L} = \text{tr}(\boldsymbol{\Delta}\boldsymbol{\Sigma}_X\boldsymbol{\Delta}^T)$ decomposes into an element-wise term and a *cross-column correlation term* that depends on how pruned weights interact through

the input covariance; Section 3.6 summarizes this mechanism and Appendix D gives the full derivation.

Wanda minimises only the element-wise term ($\mathcal{L}_{\text{diag}}$). SparseGPT improves on this by incorporating the full input covariance $\boldsymbol{\Sigma}_X$ via Hessian-based regression, but it processes each *row* of $\mathbf{W}$ independently in a greedy column-by-column update—the resulting mask for row i does not account for the spectral structure *shared across all rows* of $\mathbf{W}$. The SVD of $\mathbf{W}$ captures exactly this shared structure: the right singular vectors $\mathbf{V}_k$ span the principal directions along which all rows concentrate their energy. By extracting per-element importance from $\mathbf{V}_k$, PRISM provides a *global structural prior* that complements both Wanda's diagonal scoring and SparseGPT's row-local Hessian through a one-shot offline scoring step. The end-to-end offline pruning cost, including the optional RO stage in Section 3.5, is reported separately in Appendix E.

Unlike prior work that uses a fixed rank for all layers (Yuan et al., 2023), we propose an *adaptive rank selection* mechanism that dynamically assigns a layer-specific rank based on sensitivity.

3.2.1 Layer Sensitivity Analysis

We first compute the sensitivity of each layer to rank reduction at a fixed probe rank $\bar{k} = k_{\min}$:

$$\mathcal{S}^{(l)} = \frac{\|\mathbf{W}^{(l)}\|_F^2 - \|\mathbf{W}_{\text{low}}^{(l)}(\bar{k})\|_F^2}{\|\mathbf{W}^{(l)}\|_F^2} \cdot \left\|\frac{\partial \mathcal{L}}{\partial \mathbf{W}^{(l)}}\right\|_F \tag{2}$$

where the first term measures the relative reconstruction error and the second term (gradient norm) captures the layer's importance for the task. Higher $\mathcal{S}^{(l)}$ indicates the layer is more sensitive to compression and should retain more parameters. Using a fixed probe rank makes sensitivities comparable across matrices, keeping the procedure one-shot.

3.2.2 Sensitivity-Guided Rank Selection

Based on sensitivity, we determine the adaptive rank $k^{(l)}$ for layer l:

$$k^{(l)} = k_{\min} + (k_{\max} - k_{\min}) \cdot \frac{\mathcal{S}^{(l)} - \mathcal{S}_{\min}}{\mathcal{S}_{\max} - \mathcal{S}_{\min}} \tag{3}$$

where $k_{\max} = 0.5 \times \min(m, n)$ and $k_{\min} = 0.1 \times \min(m, n)$. In implementation, the mapped value is converted to an integer by truncation and clipped to the feasible interval $[k_{\min}, k_{\max}]$.

Rank-selection intuition. Higher sensitivities should receive larger ranks: under a smoothness

Figure 2: PRISM pipeline: adaptive-rank SVD, CV-based fusion, intra-block allocation, and optional RO.

bound, the loss increase from SVD truncation grows with both the residual norm and the layer gradient, and both are reflected in $\mathcal{S}^{(l)}$. Therefore, we use the monotone mapping in Eq. (3); Appendix C gives the full directional argument.

Definition 1 (SVD-Derived Importance Signals). *Given the selected rank $k^{(l)}$ and the corresponding rank-$k^{(l)}$ truncation $\mathbf{W}_{low}^{(l)}$, the adaptive SVD yields two complementary per-element importance signals (used as $\mathbf{I}_{mag}$ and $\mathbf{I}_{low}$ in Section 3.3):*

$$\mathbf{I}_{mag,ij}^{(l)} = |\mathbf{W}_{ij}^{(l)}| \cdot \max\left(1 - \frac{|\mathbf{W}_{ij}^{(l)} - \mathbf{W}_{low,ij}^{(l)}|}{\sigma_W^{(l)} + \epsilon_0}, \, 0\right) \tag{4}$$

$$\mathbf{I}_{low,ij}^{(l)} = \frac{|\mathbf{W}_{low,ij}^{(l)}|}{\|\mathbf{W}_{low}^{(l)}\|_F + \epsilon_0} \tag{5}$$

where $\sigma_W^{(l)} = \text{std}(\mathbf{W}^{(l)})$ is the weight standard deviation, and $\|\cdot\|_F$ denotes the Frobenius norm. $\mathbf{I}_{mag}$ is a residual-gated magnitude score built from a matrix-normalized reconstruction gap. Dividing $|W_{ij} - W_{low,ij}|$ by $\sigma_W^{(l)} + \epsilon_0$ makes the gating term dimensionless and less sensitive to matrix-wise weight rescaling, while the outer factor $|W_{ij}|$ preserves absolute salience. $\mathbf{I}_{low}$ measures principal subspace membership: weights with large Frobenius-normalized low-rank magnitude lie within the dominant singular directions and should be preserved during pruning.

Complementarity of the two signals. *A weight can have large $\mathbf{I}_{low}$ but moderate $\mathbf{I}_{mag}$: this occurs when the low-rank component is large at that position (the weight lies in the principal subspace)*

yet the high-rank residual is also non-negligible, so the normalized reconstruction gap remains sizeable. Conversely, a weight can have large $\mathbf{I}_{mag}$ but small $\mathbf{I}_{low}$: this occurs when the weight is small in absolute value yet almost entirely captured by the low-rank part, making the normalized reconstruction gap small and the gate close to 1 while $|W_{low,ij}|$ itself remains small. Thus $\mathbf{I}_{mag}$ and $\mathbf{I}_{low}$ identify overlapping but distinct subsets of structurally important weights. Both signals are designed to reduce the principal-subspace pruning energy defined in Eq. (23), which, under the alignment condition summarized in Section 3.6 and detailed in Appendix D, is associated with lower cross-column reconstruction error.

3.3 CV-Based Parameter-Free Fusion

We fuse three per-element importance factors: activation importance following Wanda,

$$\mathbf{I}_{act,ij}^{(l)} = |\mathbf{W}_{ij}^{(l)}| \cdot \sqrt{\bar{s}_j^{(l)}} \tag{6}$$

where $\bar{s}_j^{(l)} = \frac{1}{N}\sum_{i=1}^{N}\|\mathbf{X}_{i,j}^{(l)}\|_2^2$ is the average squared activation norm of input channel j over the N calibration samples; and the two SVD-derived factors $\mathbf{I}_{mag}$ and $\mathbf{I}_{low}$ defined in Eqs. (4) and (5). The matrix-normalized construction in Eq. (4) reduces within-matrix scale sensitivity. We do not further standardize the three raw factors before summation; instead, we use the coefficient of variation (CV) to derive matrix-level adaptive weights from

each factor's relative dispersion:

$$\mathrm{CV}_f^{(l)} = \frac{\mathrm{std}(\mathbf{I}_f^{(l)})}{\mathrm{mean}(\mathbf{I}_f^{(l)}) + \epsilon_0}, \tag{7}$$

$$f \in \mathcal{F} = \{\mathrm{act}, \mathrm{mag}, \mathrm{low}\}$$

CV is scale-invariant, so it remains comparable as a measure of relative spread across factors. We therefore assign matrix-level fusion weights directly proportional to CV:

$$w_f^{(l)} = \frac{\mathrm{CV}_f^{(l)}}{\sum_{f' \in \mathcal{F}} \mathrm{CV}_{f'}^{(l)}}, \quad \epsilon_0 = 10^{-6} \tag{8}$$

Higher-CV factors receive larger weight, while nearly uniform factors are down-weighted automatically. Since the raw factor values are still summed directly, CV fusion should be viewed as a training-free adaptive reweighting heuristic. The final unified score is

$$\mathcal{S}_{ij}^{(l)} = \sum_{f \in \mathcal{F}} w_f^{(l)} \cdot \mathbf{I}_{f,ij}^{(l)} \tag{9}$$

which is computed independently for each weight matrix and used directly to generate the sparse mask $\mathbf{M}^{(l)}$. Section 4.4 shows this CV-based reweighting outperforms uniform, standard-deviation-proportional, and global hand-tuned fusion.

3.4 Gradient-Weighted Intra-Block Allocation

Each transformer block b contains $T=7$ projection matrices $\{\mathbf{W}_t^{(b)}\}_{t \in \mathcal{T}}$ with $\mathcal{T} = \{q, k, v, o, \mathrm{up}, \mathrm{gate}, \mathrm{down}\}$. Instead of assigning them a uniform sparsity ratio, we allocate retention within each block, a granularity that shares a block budget while remaining compatible with external inter-layer allocation.

For each matrix t in block b, we define local importance as the block-normalized RMS unified score from Eq. (9):

$$\mathcal{I}_{\mathrm{local}}^{(b,t)} = \frac{\|\mathcal{S}^{(b,t)}\|_F / \sqrt{|\mathbf{W}^{(b,t)}|}}{\sum_{t' \in \mathcal{T}} \|\mathcal{S}^{(b,t')}\|_F / \sqrt{|\mathbf{W}^{(b,t')}|}} \tag{10}$$

We define a matrix-level gradient-weight sensitivity proxy as

$$\mathcal{I}_{\mathrm{sens}}^{(b,t)} = \left\| \mathbf{W}^{(b,t)} \odot \nabla_{\mathbf{W}^{(b,t)}} \mathcal{L} \right\|_F, \tag{11}$$

which is inspired by Fisher-style saliency measures but does not estimate the Fisher matrix or its diagonal. We then combine the two signals by a block-wise normalized geometric mean:

$$\mathcal{I}^{(b,t)} = \left(\tilde{\mathcal{I}}_{\mathrm{local}}^{(b,t)} \right)^{\lambda} \cdot \left(\tilde{\mathcal{I}}_{\mathrm{sens}}^{(b,t)} \right)^{1-\lambda} \tag{12}$$

where $\tilde{\cdot}$ denotes normalization within block b and $\lambda = 0.8$. We use $\lambda > 0.5$ because local importance already aggregates all three fused element-wise signals, while the gradient-weight sensitivity proxy provides a complementary matrix-level correction.

We convert $\mathcal{I}^{(b,t)}$ into matrix budgets by ranking the seven matrices within each block. Higher-ranked matrices receive larger initial retention through a bounded linear schedule over $[r_{\min}, r_{\max}]$; a block-wise scaling factor then enforces the target retention, and each matrix is pruned using the unified score $\mathcal{S}^{(b,t)}$. This rank-based schedule avoids relying on uncalibrated absolute scales across projection types while preserving the sensitivity ordering. In the default setting, the target is the global uniform budget; with an external inter-layer allocator such as AlphaPruning, PRISM instead redistributes its layer-wise target within each block, as evaluated in Section 4.4. Algorithm 1 in Appendix A.1 gives the full procedure.

3.5 Regional Optimization

We adopt Wanda++'s Regional Optimization (RO) (Yang et al., 2025) as an optional post-pruning reconstruction step, but use a fixed-mask variant tailored to PRISM. Unlike Wanda++, we do not alternate re-pruning and weight updates: once the mask is produced by the SVD-derived scoring, CV fusion, and intra-block allocation stages, RO updates only the surviving weights. To stabilize this fixed-mask setting, we add an L2 anchor that keeps the updated weights close to their pre-pruning values. The resulting per-block objective is

$$\begin{aligned} \min_{\{\mathbf{W}_{\mathrm{surv}}^{(b)}\}} \frac{1}{B} \sum_{j=1}^{B} & \left\| f_b(\mathbf{x}_j; \mathbf{M}^{(b)} \odot \mathbf{W}^{(b)}) \right. \\ & \left. - f_b(\mathbf{x}_j; \mathbf{W}_{\mathrm{orig}}^{(b)}) \right\|^2 \\ & + \mu \left\| \mathbf{W}_{\mathrm{surv}}^{(b)} - \mathbf{W}_{\mathrm{orig,surv}}^{(b)} \right\|^2, \end{aligned} \tag{13}$$

where gradients and updates are applied to non-zero weights. This step is optional and orthogonal to the scoring stage; implementation and cost are deferred to Appendix A and Appendix E.

Table 1: WikiText-2 (Merity et al., 2016) perplexity on Qwen3 (Team, 2025) and LLaMA-family models (Dubey et al., 2024) under unstructured and N:M sparsity. Lower is better. Wanda++ and PRISM use RO by default; the corresponding "w/o RO" rows disable the reconstruction stage to isolate the underlying pruning quality. Percentages denote relative improvement over the strongest external baseline.

| Sparsity | Method | Qwen3 | | | LLaMA-3.1 | LLaMA-3.2 | |
		0.6B	4B	8B	8B	1B	3B
	Dense	23.89	11.18	10.93	6.96	11.00	8.74
50%	SparseGPT	38.77	14.17	13.05	10.54	21.86	13.76
	Wanda	39.90	14.17	12.92	10.72	26.36	14.74
	AlphaPruning (Wanda)	41.73	14.51	13.12	10.62	26.16	14.64
	Thanos	40.58	14.21	13.29	10.40	22.41	13.84
	Wanda++ w/o RO	38.88	14.09	13.01	10.24	21.68	13.74
	Wanda++	34.43	13.93	12.71	9.98	18.92	12.93
	PRISM w/o RO	37.64	13.99	12.81	10.12	21.04	13.56
	PRISM	**32.36** (-6.0%)	**13.65** (-2.0%)	**12.52** (-1.5%)	**9.65** (-3.3%)	**17.70** (-6.4%)	**12.61** (-2.5%)
2:4	SparseGPT	81.63	24.95	18.31	18.45	39.52	25.38
	Wanda	215.29	25.16	18.28	26.30	101.76	39.88
	Thanos	91.11	22.78	16.58	18.78	38.74	25.42
	Wanda++ w/o RO	82.32	24.45	17.56	17.68	39.13	24.95
	Wanda++	55.24	22.53	16.22	16.89	30.13	21.83
	PRISM w/o RO	77.64	22.12	16.53	17.42	35.23	23.67
	PRISM	**48.13** (-12.9%)	**18.75** (-16.8%)	**15.95** (-1.7%)	**15.10** (-10.6%)	**27.96** (-7.2%)	**21.77** (-0.3%)
4:8	SparseGPT	58.34	17.87	14.93	13.76	28.45	18.60
	Wanda	90.15	18.01	14.89	15.50	50.91	24.00
	Thanos	59.35	17.41	14.40	13.85	28.00	18.50
	Wanda++ w/o RO	57.64	17.68	14.82	13.69	27.23	17.88
	Wanda++	45.12	16.93	14.39	12.95	25.33	16.99
	PRISM w/o RO	54.22	17.33	14.54	13.12	25.12	17.01
	PRISM	**39.00** (-13.6%)	**16.37** (-3.3%)	**14.17** (-1.5%)	**11.93** (-7.9%)	**22.21** (-12.3%)	**16.18** (-4.8%)

3.6 Analysis of SVD-Guided Pruning

We summarize the mechanism and defer proofs to Appendix D. The analysis is *conditional*: it does not claim global optimality, but identifies when SVD-derived signals can reduce reconstruction error beyond activation-only scoring.

Pruning error decomposes into a diagonal term and a cross-column term from input-feature correlations. Activation-only scoring mainly targets the diagonal term, whereas the SVD-derived signals discourage pruning weights in the dominant right-singular subspace. This motivates the *principal-subspace pruning energy* $E_{\mathrm{prin}}(M) = \|\Delta V_k\|_F^2$.

When off-diagonal input covariance aligns with this subspace, lower $E_{\mathrm{prin}}(M)$ can imply lower cross-column error. Thus I_{act} targets diagonal reconstruction cost, while I_{mag} and I_{low} provide complementary spectral terms. Because the cross-column term is not directly observable in the full nonlinear model, Section 4.4 evaluates the closest diagnostic: whether PRISM lowers layer-wise principal-subspace pruning energy relative to activation-only pruning.

4 Results and Analysis

4.1 Experimental Setup

We evaluate PRISM on Qwen3 (0.6B, 4B, 8B), LLaMA-3.1 8B, and LLaMA-3.2 (1B, 3B) (Team, 2025; Dubey et al., 2024). Calibration follows prior work with 128 C4 sequences of length 1024 (Raffel et al., 2020; Sun et al., 2024; Frantar and Alistarh, 2023). We report WikiText-2 perplexity (Merity et al., 2016) and zero-shot accuracy on HellaSwag (Zellers et al., 2019), ARC-easy/challenge (Clark et al., 2018), Winogrande (Sakaguchi et al., 2021), PIQA (Bisk et al., 2020), and BoolQ (Clark et al., 2019). We compare against SparseGPT (Frantar and Alistarh, 2023), Wanda (Sun et al., 2024), Thanos (Ilin and Richtarik, 2025), AlphaPruning (Lu et al., 2024), and Wanda++ (Yang et al., 2025); unless stated, all baseline results are reproduced from released implementations under the same protocol. Because inter-layer allocation requires adjustable layer-wise budgets, AlphaPruning is reported only at 50% unstructured sparsity and omitted for fixed N:M sparsity. In Table 1, Wanda++ and PRISM use RO by default, while "w/o RO" dis-

ables reconstruction to isolate pruning quality. Table 3(e) contrasts PRISM and PRISM + AlphaPruning on LLaMA-3.1 8B. Detailed settings are in Appendix A.

4.2 Main Results

Table 1 presents WikiText-2 perplexity across three sparsity patterns (50% unstructured, 2:4, and 4:8) on Qwen3, LLaMA-3.1, and LLaMA-3.2 models. PRISM achieves the lowest final perplexity in every setting. At 50% unstructured sparsity, PRISM w/o RO is the strongest no-RO method on all six models; on LLaMA-3.1 8B, it reaches 10.12, ahead of Wanda++ w/o RO (10.24), Thanos (10.40), SparseGPT (10.54), AlphaPruning (10.62), and Wanda (10.72). With RO, PRISM improves to 9.65 and surpasses Wanda++ (9.98), with the largest gains on smaller models. PRISM targets settings where extra one-time pruning cost is acceptable; Appendix E shows PRISM + RO is costlier than Wanda and SparseGPT, but still 2.28× faster than Wanda++ with RO on LLaMA-3.1 8B. Table 3(e) further shows that AlphaPruning improves PRISM from 9.65 to 9.62, demonstrating complementarity with inter-layer allocation. Under N:M sparsity, both allocation stages are inapplicable, so gains come from the spectral-aware scoring stack: SVD-derived signals and CV fusion. PRISM outperforms the applicable baselines, for example 48.13 vs. 55.24 on Qwen3-0.6B at 2:4 and 15.10 vs. 16.89 on LLaMA-3.1 8B; PRISM w/o RO also remains better than Wanda++ w/o RO across all six models under both 2:4 and 4:8.

4.3 Zero-Shot Results

Table 2 reports zero-shot accuracy for LLaMA-3.1 8B at 50% unstructured sparsity on the six benchmarks introduced in Section 4.1. PRISM achieves the best results on ARC-e, Winogrande, PIQA, and BoolQ, while remaining competitive on HellaSwag and ARC-c, where Wanda++ is slightly stronger. This shows that the perplexity gains in Table 1 transfer to downstream reasoning performance rather than reflecting only language-model calibration. Appendix B further reports a text-branch pruning evaluation on Qwen3-VL.

4.4 Ablation Studies

4.4.1 Component Analysis

Table 3 summarizes the incremental contribution of each PRISM component. Panels (a)–(d) use **Wanda + RO** as the baseline to isolate PRISM's

Table 2: Zero-shot accuracy (%) for LLaMA-3.1 8B at 50% unstructured sparsity. Higher is better.

Method	HellaSwag	ARC-e	ARC-c	Winogrande	PIQA	BoolQ
Dense	79.31	82.53	54.95	74.59	81.18	83.06
SparseGPT	71.88	69.74	43.52	71.03	77.74	80.95
Wanda	69.70	69.61	45.05	69.53	77.26	79.17
Wanda++	**71.95**	70.75	**45.90**	69.14	77.69	79.72
PRISM	71.81	**73.06**	45.56	71.32	77.75	81.18

Figure 3: Layer-wise normalized principal-subspace pruning energy for Wanda + RO and PRISM, normalized by the Wanda + RO baseline (1.00). Lower is better.

scoring, fusion, and intra-block allocation stages; panel (e) separately tests compatibility with AlphaPruning. Starting from 10.23 PPL, the full PRISM pipeline reaches 9.65, a 5.7% relative reduction; the largest single gain comes from adding the SVD-derived signals, with smaller but consistent gains from adaptive rank selection, CV fusion, and intra-block allocation.

4.4.2 SVD-Derived Signal Analysis

Table 3(b) isolates the SVD-derived scoring terms before CV fusion and intra-block allocation. Adding $\mathcal{I}_{\mathrm{mag}}$ to activation-only scoring reduces PPL from 10.23 to 10.13, while $\mathcal{I}_{\mathrm{low}}$ alone gives a smaller improvement to 10.22. Combining both signals is more effective, reaching 9.89 with a fixed rank and 9.83 with adaptive rank selection, which supports their complementarity.

Figure 3 further shows that PRISM reduces layer-wise normalized principal-subspace pruning energy relative to the activation-only baseline, supporting the mechanism in Section 3.6 and Appendix D. This diagnostic suggests that the fused spectral signals preferentially rescue weights aligned with dominant singular directions, though it does not establish causality.

(a) Components

Configuration	PPL	Δ	Role
Wanda (no RO)	10.72	–	–
Wanda + RO (base.)	10.23	–	–
+ SVD-derived signals	9.89	−3.3%	Core 1
+ Adaptive rank	9.83	−3.9%	Core 1
+ CV fusion	9.74	−4.8%	Enabler
+ Intra-block alloc. (**PRISM**)	**9.65**	**−5.7%**	Core 2

(b) SVD Signals

Scoring Variant	PPL
Act.-only scoring (Wanda + RO)	10.23
$\mathcal{I}_{act} + \mathcal{I}_{mag}$	10.13
$\mathcal{I}_{act} + \mathcal{I}_{low}$	10.22
$\mathcal{I}_{act} + \mathcal{I}_{mag} + \mathcal{I}_{low}$ (fix. rank)	9.89
$\mathcal{I}_{act} + \mathcal{I}_{mag} + \mathcal{I}_{low}$ (adapt. rank)	**9.83**

(c) Fusion

Fusion Strategy	PPL
Uniform $\left(\frac{1}{3}, \frac{1}{3}, \frac{1}{3}\right)$	9.83
Global tuned ratio	9.79
Std.-prop. weighting	9.81
CV-prop. (ours)	**9.74**

(d) Intra-Block Allocation

Allocation Strategy	PPL
Uniform within block	9.74
Local-score-only allocation	9.69
Gradient-weight-only allocation	9.72
Score-proportional allocation	9.68
Arithmetic-mean fusion	9.67
Geom.-mean allocation (ours)	**9.65**

(e) Inter-Layer Compatibility

Setting	PPL
Wanda	10.72
Wanda + AlphaPruning	10.62
PRISM	9.65
PRISM + AlphaPruning	**9.62**

Table 3: Ablations on LLaMA-3.1 8B at 50% unstructured sparsity. Panels (a)–(d) use PRISM without inter-layer allocation; panel (e) compares PRISM and PRISM + AlphaPruning. Lower is better.

Figure 4: Layer-wise mean CV-based fusion weights for $\mathcal{I}_{act}$, $\mathcal{I}_{mag}$, and $\mathcal{I}_{low}$.

4.4.3 Fusion Strategy Ablation

Table 3(c) compares fusion rules with the scoring pipeline fixed. Uniform weighting gives 9.83 PPL, standard-deviation-proportional weighting gives 9.81, and a global hand-tuned ratio gives 9.79. CV-proportional fusion performs best at 9.74, indicating that matrix-specific relative dispersion is a useful training-free weighting signal.

Figure 4 shows that activation importance usually receives the largest share, while both SVD-derived factors remain substantial and vary with depth. We therefore interpret CV fusion as a training-free adaptive reweighting heuristic rather than a complete normalization scheme.

4.4.4 Intra-Block Allocation Analysis

Table 3(d) evaluates intra-block allocation with the element-wise scorer fixed. Uniform within-block retention gives 9.74 PPL; local-score-only, gradient-weight-only, and score-proportional variants improve to 9.69, 9.72, and 9.68, respectively. The proposed geometric-mean allocator performs best at 9.65, showing that combining local score strength with gradient-weight sensitivity is useful.

Table 3(e) shows that PRISM remains complementary to inter-layer allocation. Adding AlphaPruning improves PRISM from 9.65 to 9.62, giving the best overall PPL under the same external layer-wise budget.

Appendix Figure 5 visualizes the learned retention shift relative to uniform 50% within-block allocation. The allocator consistently protects $\mathbf{W}_k$, $\mathbf{W}_q$, and $\mathbf{W}_{gate}$, while pruning $\mathbf{W}_o$ and $\mathbf{W}_{down}$ more aggressively; this structured pattern explains why allocation based on matrix sensitivity improves over uniform and single-signal alternatives.

5 Conclusion

We present PRISM, a post-training pruning framework organized around two core ideas and one enabling mechanism: spectral-aware multi-factor scoring from SVD-derived signals, parameter-free CV-based fusion, and gradient-weighted intra-block allocation. Across six Qwen3 and LLaMA models under unstructured and N:M sparsity, PRISM shows consistent improvements over representative baselines, with up to 16.8% relative perplexity improvement. The intra-block allocator is further shown to be complementary to existing inter-layer methods such as AlphaPruning.

Limitations

PRISM still has a limitation in multimodal settings. The current formulation is designed primarily for the language decoder, so in our multimodal experiment we prune only the text branch while keeping the visual encoder and fusion modules unchanged. Extending PRISM to jointly prune all multimodal components remains future work.

Potential risks are mainly related to deployment. By reducing LLM deployment cost, PRISM may also lower the barrier for harmful uses of existing models. In addition, pruning can change robustness, factuality, or safety behavior in ways not fully captured by standard benchmarks, so pruned models should be evaluated carefully before deployment.

References

Shuai Bai, Yuxuan Cai, Ruizhe Chen, Keqin Chen, Xionghui Chen, Zesen Cheng, Lianghao Deng, Wei Ding, Chang Gao, Chunjiang Ge, and 1 others. 2025. Qwen3-vl technical report. *arXiv preprint arXiv:2511.21631*.

Yonatan Bisk, Rowan Zellers, Ronan Le Bras, Jianfeng Gao, and Yejin Choi. 2020. PIQA: Reasoning about physical commonsense in natural language. *Proceedings of the AAAI Conference on Artificial Intelligence*, 34(05):7432–7439.

Christopher Clark, Kenton Lee, Ming-Wei Chang, Tom Kwiatkowski, Michael Collins, and Kristina Toutanova. 2019. Boolq: Exploring the surprising difficulty of natural yes/no questions. In *Proceedings of the 2019 conference of the north American chapter of the association for computational linguistics: Human language technologies, volume 1 (long and short papers)*, pages 2924–2936.

Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. 2018. Think you have solved question answering? try ARC, the AI2 reasoning challenge. *arXiv preprint arXiv:1803.05457*.

Abhimanyu Dubey, Abhinav Jauhri, Abhishek Pandey, Amit Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, and 1 others. 2024. The Llama 3 herd of models. *arXiv preprint arXiv:2407.21783*.

Gongfan Fang, Hongxu Yin, Saurav Muralidharan, Greg Heinrich, Jeff Pool, Jan Kautz, Pavlo Molchanov, and Xinchao Wang. 2024. Maskllm: Learnable semi-structured sparsity for large language models. *Advances in Neural Information Processing Systems*, 37:7736–7758.

Elias Frantar and Dan Alistarh. 2023. Sparsegpt: Massive language models can be accurately pruned in one-shot. In *International Conference on Machine Learning, ICML 2023, 23-29 July 2023, Honolulu, Hawaii, USA*, volume 202 of *Proceedings of Machine Learning Research*, pages 10323–10337. PMLR.

Elias Frantar, Saleh Ashkboos, Torsten Hoefler, and Dan Alistarh. 2022. Gptq: Accurate post-training quantization for generative pre-trained transformers. *arXiv preprint arXiv:2210.17323*.

Tianrui Guan, Fuxiao Liu, Xiyang Wu, Ruiqi Xian, Zongxia Li, Xiaoyu Liu, Xijun Wang, Lichang Chen, Furong Huang, Yaser Yacoob, and 1 others. 2024. Hallusionbench: an advanced diagnostic suite for entangled language hallucination and visual illusion in large vision-language models. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 14375–14385.

Yen-Chang Hsu, Ting Hua, Sungen Chang, Qian Lou, Yilin Shen, and Hongxia Jin. 2022. Language model compression with weighted low-rank factorization. In *The Tenth International Conference on Learning Representations, ICLR 2022, Virtual Event, April 25-29, 2022*. OpenReview.net.

Ivan Ilin and Peter Richtarik. 2025. Thanos: A block-wise pruning algorithm for efficient large language model compression. *arXiv preprint arXiv:2504.05346*.

Ji Lin, Jiaming Tang, Haotian Tang, Shang Yang, Wei-Ming Chen, Wei-Chen Wang, Guangxuan Xiao, Xingyu Dang, Chuang Gan, and Song Han. 2024. Awq: Activation-aware weight quantization for on-device llm compression and acceleration. *Proceedings of machine learning and systems*, 6:87–100.

Jun Liu, Zhenglun Kong, Pu Zhao, Changdi Yang, Xuan Shen, Hao Tang, Geng Yuan, Wei Niu, Wenbin Zhang, Xue Lin, Dong Huang, and Yanzhi Wang. 2025. Toward adaptive large language models structured pruning via hybrid-grained weight importance assessment. In *Thirty-Ninth AAAI Conference on Artificial Intelligence, Thirty-Seventh Conference on Innovative Applications of Artificial Intelligence, Fifteenth Symposium on Educational Advances in Artificial Intelligence, AAAI 2025, Philadelphia, PA, USA, February 25 - March 4, 2025*, pages 18879–18887. AAAI Press.

Yuan Liu, Haodong Duan, Yuanhan Zhang, Bo Li, Songyang Zhang, Wangbo Zhao, Yike Yuan, Jiaqi Wang, Conghui He, Ziwei Liu, and 1 others. 2024. Mmbench: Is your multi-modal model an all-around player? In *European conference on computer vision*, pages 216–233. Springer.

Haiquan Lu, Yefan Zhou, Shiwei Liu, Zhangyang Wang, Michael W Mahoney, and Yaoqing Yang. 2024. Alphapruning: Using heavy-tailed self regularization theory for improved layer-wise pruning of large language models. *Advances in neural information processing systems*, 37:9117–9152.

Mehdi Makni, Kayhan Behdin, Zheng Xu, Natalia Pono-mareva, and Rahul Mazumder. 2025. A unified framework for sparse plus low-rank matrix decomposition for llms. In *The Second Conference on Parsimony and Learning (Proceedings Track)*.

Minesh Mathew, Dimosthenis Karatzas, and C. V. Jawahar. 2021. Docvqa: A dataset for vqa on document images. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision (WACV)*, pages 2200–2209.

Stephen Merity, Caiming Xiong, James Bradbury, and Richard Socher. 2016. Pointer sentinel mixture models. *arXiv preprint arXiv:1609.07843*.

OpenAI. 2023. GPT-4 technical report. *CoRR*, abs/2303.08774.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, and 1 others. 2019. Pytorch: An imperative style, high-performance deep learning library. *Advances in Neural Information Processing Systems*, 32.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. 2020. Exploring the limits of transfer learning with a unified text-to-text transformer. *Journal of Machine Learning Research*, 21(140):1–67.

Keisuke Sakaguchi, Ronan Le Bras, Chandra Bhagavatula, and Yejin Choi. 2021. Winogrande: An adversarial winograd schema challenge at scale. *Communications of the ACM*, 64(9):99–106.

Mingjie Sun, Zhuang Liu, Anna Bair, and J. Zico Kolter. 2024. A simple and effective pruning approach for large language models. In *The Twelfth International Conference on Learning Representations, ICLR 2024, Vienna, Austria, May 7-11, 2024*. OpenReview.net.

Qwen Team. 2025. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*.

Qinsi Wang, Jinghan Ke, Masayoshi Tomizuka, Kurt Keutzer, and Chenfeng Xu. 2025a. Dobi-SVD: Differentiable SVD for LLM compression and some new perspectives. In *International Conference on Learning Representations (ICLR)*.

Xin Wang, Yu Zheng, Zhongwei Wan, and Mi Zhang. 2025b. SVD-LLM: Truncation-aware singular value decomposition for large language model compression. In *International Conference on Learning Representations (ICLR)*.

Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, and 1 others. 2020. Transformers: State-of-the-art natural language processing. *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 38–45.

Jing Xiong, Jianghan Shen, Fanghua Ye, Chaofan Tao, Zhongwei Wan, Jianqiao Lu, Xun Wu, Chuanyang Zheng, Zhijiang Guo, Lingpeng Kong, and Ngai Wong. 2025. UNComp: Can matrix entropy uncover sparsity? A compressor design from an uncertainty-aware perspective. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*.

Peng Xu, Wenqi Shao, Mengzhao Chen, Shitao Tang, Kaipeng Zhang, Peng Gao, Fengwei An, Yu Qiao, and Ping Luo. 2024. BESA: Pruning large language models with blockwise parameter-efficient sparsity allocation. In *International Conference on Learning Representations (ICLR)*.

Yifan Yang, Kai Zhen, Bhavana Ganesh, Aram Galstyan, Goeric Huybrechts, Markus Müller, Jonas M. Kübler, Rupak Vignesh Swaminathan, Athanasios Mouchtaris, Sravan Babu Bodapati, Nathan Susanj, Zheng Zhang, Jack FitzGerald, and Abhishek Kumar. 2025. Wanda++: Pruning large language models via regional gradients. In *Findings of the Association for Computational Linguistics, ACL 2025, Vienna, Austria, July 27 - August 1, 2025*, volume ACL 2025 of *Findings of ACL*, pages 4321–4333. Association for Computational Linguistics.

Lu Yin, You Wu, Zhenyu Zhang, Cheng-Yu Hsieh, Yaqing Wang, Yiling Jia, Mykola Pechenizkiy, Yi Liang, Zhangyang Wang, and Shiwei Liu. 2024. Outlier weighed layerwise sparsity (OWL): A missing secret sauce for pruning llms to high sparsity. In *International Conference on Machine Learning (ICML)*.

Zhihang Yuan, Yuzhang Shang, Yue Song, Qiang Wu, Yan Yan, and Guangyu Sun. 2023. ASVD: activation-aware singular value decomposition for compressing large language models. *CoRR*, abs/2312.05821.

Rowan Zellers, Ari Holtzman, Yonatan Bisk, Ali Farhadi, and Yejin Choi. 2019. Hellaswag: Can a machine really finish your sentence? In *Proceedings of the 57th annual meeting of the association for computational linguistics*, pages 4791–4800.

Longteng Zhang, Sen Wu, Shuai Hou, Zhengyu Qing, Zhuo Zheng, Danning Ke, Qihong Lin, Qiang Wang, Shaohuai Shi, and Xiaowen Chu. 2026. Salr: Sparsity-aware low-rank representation for efficient fine-tuning of large language models. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 40, pages 28337–28345.

Pengxiang Zhao, Hanyu Hu, Ping Li, Yi Zheng, Zhefeng Wang, and Xiaoming Yuan. 2025. FISTApruner: Layer-wise post-training pruning for large language models. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 29457–29475.

A Implementation Details

We implement PRISM in PyTorch (Paszke et al., 2019) with HuggingFace Transformers (Wolf et al., 2020). All experiments are conducted on a single NVIDIA H800 GPU. For fairness, all baselines are run with their released official implementations under the same data protocol as PRISM: identical C4 calibration samples (128 sequences of length 1024), the same sparsity targets, and the same WikiText-2 / zero-shot evaluation sets. For clarity, our Wanda++ w/o RO implementation is exactly the original Wanda++ pruning pipeline, corresponding to the "Wanda++ RGS" variant reported in the Wanda++ paper. Adaptive SVD uses $k_{\min} = 0.1 \min(m, n)$ and $k_{\max} = 0.5 \min(m, n)$; sensitivity is evaluated once at the probe rank $\bar{k} = k_{\min}$ and then mapped to an integer rank via Eq. (3). CV-based fusion uses $w_f^{(l)} = \mathrm{CV}_f^{(l)} / \sum_{f'} \mathrm{CV}_{f'}^{(l)}$ with $\epsilon_0 = 10^{-6}$, and the activation-factor CV is averaged over $B = 5$ mini-batches. Intra-block allocation uses the gradient-weight sensitivity proxy $\|\mathbf{W} \odot \nabla_{\mathbf{W}} \mathcal{L}\|_F$ and geometric-mean fusion with $\lambda = 0.8$; this proxy is inspired by Fisher-style saliency measures but does not estimate the Fisher matrix or its diagonal. We use an initial retention spread $[r_{\min}, r_{\max}] = [0.46, 0.54]$. Regional Optimization uses RMSprop with learning rate 1×10^{-5}, gradient clipping $\|\nabla\|_{\max} = 1.0$, L2 anchor $\mu = 1.0$, 10 iterations, and 64 random calibration samples per iteration. For the cost results in Section E, all methods are timed under the same calibration setup, and the reported wall-clock includes the full offline pruning pipeline: activation collection, gradient collection, scoring/mask generation, and optional RO.

A.1 Intra-Block Allocation Procedure

Algorithm 1 Intra-block cross-matrix allocation

Require: Target sparsity S_{target}, initial retention bounds $[r_{\min}, r_{\max}]$, balancing λ

Require: Unified scores $\{\mathcal{S}^{(b,t)}\}$, pre-computed gradients $\{\nabla_{\mathbf{W}^{(b,t)}} \mathcal{L}\}$

1: **for** each block $b = 1, \ldots, B$ **do**

2:   Compute local importance $\mathcal{I}_{\text{local}}^{(b,t)}$ and gradient-weight sensitivity $\mathcal{I}_{\text{sens}}^{(b,t)}$ for each $t \in \mathcal{T}$

3:   Normalise both within the block; compute $\mathcal{I}^{(b,t)}$ via geometric mean

4:   Rank the T matrices by $\mathcal{I}^{(b,t)}$; assign initial retention ratios linearly from $[r_{\min}, r_{\max}]$:

$$r^{(b,t)} = r_{\min} + (r_{\max} - r_{\min}) \cdot \frac{\text{rank}(t)}{T - 1} \quad (14)$$

5:   Apply a global scaling factor κ so the block satisfies the target:

$$\kappa = \frac{(1 - S_{\text{target}}) \sum_t |\mathbf{W}^{(b,t)}|}{\sum_t r^{(b,t)} \cdot |\mathbf{W}^{(b,t)}|},\quad (15)$$
$$r^{(b,t)} \leftarrow \text{clip}(\kappa \cdot r^{(b,t)}, 0, 1)$$

6:   Prune each matrix t to sparsity $1 - r^{(b,t)}$ using unified scores $\mathcal{S}^{(b,t)}$

7: **end for**

We use $\mathcal{I}^{(b,t)}$ to rank the seven matrices rather than allocating retention proportionally, as its absolute scale is not calibrated across projection types. The linearly spaced initialization in $[r_{\min}, r_{\max}]$ yields a bounded redistribution less sensitive to score outliers while preserving the within-block ordering. After global scaling, actual retention may shift outside this window (clipped to $[0, 1]$); $[r_{\min}, r_{\max}]$ controls the spread of the initial allocation, not a hard constraint.

B Additional Multimodal Evaluation

We further examine whether PRISM transfers to multimodal large language models using Qwen3-VL-4B-Instruct (Bai et al., 2025). Since our current importance estimation and sparsity allocation are designed for the language decoder, we prune only the text branch and keep the visual encoder and multimodal fusion modules unchanged.

Table B.1 reports results on MMBench-en and MMBench-cn (Liu et al., 2024), Hallu-

Figure 5: Layer-wise retention shift from uniform 50% within-block allocation under the final geometric-mean allocator. Positive means protection; negative means more pruning.

Table B.1: Multimodal results on Qwen3-VL-4B-Instruct with only the text branch pruned. Higher is better.

Method	MMBench-en	MMBench-cn	HallusionBench	DocVQA test
Dense	83.1	82.5	56.9	94.3
SparseGPT	77.4	77.2	52.5	90.1
Wanda	76.5	76.1	50.1	89.6
Wanda++	78.3	78.2	53.9	90.9
PRISM	**78.8**	**78.4**	**54.1**	**91.3**

sionBench (Guan et al., 2024), and DocVQA test (Mathew et al., 2021). PRISM consistently achieves the best performance among all pruned variants, reaching 78.8, 78.4, 54.1, and 91.3, respectively. Compared with the strongest pruning baseline Wanda++, PRISM improves by 0.5 points on MMBench-en, 0.2 on MMBench-cn, 0.2 on HallusionBench, and 0.4 on DocVQA test. These results suggest that the proposed text-side importance signals remain effective in multimodal decoders. Pruning the visual and fusion modules is left for future work.

C Justification of Sensitivity-Guided Rank Selection

We give a short directional argument linking sensitivity and rank allocation. Let $\phi_l(U)$ denote the loss function with layer l replaced by U, assume ϕ_l is β_l-smooth, let $R_l(k) = W^{(l)} - W^{(l)}_{\text{low}}(k)$ be the residual from rank-k SVD truncation, and let $g_l = \|\nabla_{W^{(l)}}\mathcal{L}\|_F$. A standard smoothness bound gives

$$
\begin{aligned}
\Delta_l(k) &= \phi_l(W^{(l)}_{\text{low}}(k)) - \phi_l(W^{(l)}) \\
&\leq g_l\|R_l(k)\|_F + \frac{\beta_l}{2}\|R_l(k)\|_F^2.
\end{aligned} \tag{16}
$$

Since $\|R_l(k)\|_F^2 = \sum_{i>k}(\sigma_i^{(l)})^2$ decreases monotonically with k, the upper bound also decreases with k. Since $\mathcal{S}^{(l)} = r_l(\bar{k}) \cdot g_l$ for a fixed probe

rank $\bar{k}$, higher sensitivity implies either larger gradient norm or larger residual ratio at the probe rank; both favor assigning a larger rank to keep the loss increment under control. Eq. (3) instantiates this intuition through an increasing affine mapping,

$$
\frac{\partial k^{(l)}}{\partial \mathcal{S}^{(l)}} = \frac{k_{\max} - k_{\min}}{\mathcal{S}_{\max} - \mathcal{S}_{\min}} > 0. \tag{17}
$$

Thus higher sensitivities map monotonically to larger ranks, while robust layers use lower ranks. Here β_l appears only in the smoothness upper bound above; it is not estimated or used as an algorithmic hyperparameter. We therefore keep the final rule as the simple monotone mapping in Eq. (3) rather than introducing a separate per-layer optimization objective over candidate ranks.

D Detailed Analysis of SVD-Guided Pruning

This appendix provides the full conditional analysis summarized in Section 3.6. Our goal is not to claim global optimality of the final mask, but to identify a mechanism through which the SVD-derived signals can reduce pruning-induced reconstruction error beyond activation-only scoring.

D.1 Reconstruction Error Decomposition

Consider a linear layer with input $X \in \mathbb{R}^n$ and output $y = WX$, where $W \in \mathbb{R}^{m \times n}$. Let $M \in \{0, 1\}^{m \times n}$ denote the binary pruning mask, and define the pruned error matrix

$$
\Delta = (1 - M) \odot W. \tag{18}
$$

Then the output reconstruction error of pruning is

$$
\begin{aligned}
L(M) &= \mathbb{E}\|\Delta X\|_2^2 = \text{tr}\left(\Delta \Sigma_X \Delta^\top\right), \\
\Sigma_X &= \mathbb{E}[XX^\top].
\end{aligned} \tag{19}
$$

Proposition 1 (Reconstruction error decomposition). *Let $s_j = [\Sigma_X]_{jj}$ and let $\Sigma_X^{\text{off}} = \Sigma_X - \text{diag}(s_1, \ldots, s_n)$. For row i, define $\delta_i^\top$ as the i-th row of Δ and $P_i = \{j : M_{ij} = 0\}$ as the pruned set in that row. Then*

$$
L(M) = \underbrace{\sum_{i=1}^{m}\sum_{j=1}^{n}(1 - M_{ij})^2 W_{ij}^2 s_j}_{L_{\text{diag}}(M)} \\
+ \underbrace{\sum_{i=1}^{m}\sum_{\substack{j \neq j' \\ j,j' \in P_i}} W_{ij}W_{ij'}[\Sigma_X]_{jj'}}_{L_{\text{cross}}(M)}. \tag{20}
$$

Equivalently,

$$L_{\text{cross}}(M) = \sum_{i=1}^{m} \delta_i^\top \Sigma_X^{\text{off}} \delta_i. \qquad (21)$$

Proof. From (19), $L(M) = \sum_{i=1}^{m} \delta_i^\top \Sigma_X \delta_i$. Expanding each quadratic form into diagonal and off-diagonal parts yields (20). Equation (21) is the same expression written using Σ_X^{off}. $\qquad \square$

Implication. Activation-only scoring mainly aligns with $L_{\text{diag}}(M)$ because it ranks entries by a magnitude–activation proxy. However, when transformer features are correlated across channels, $L_{\text{cross}}(M)$ can be substantial, and controlling only the diagonal term is insufficient.

D.2 Principal-Subspace Pruning Energy

Let the adaptive-rank SVD of the weight matrix be

$$W = W_{\text{low}} + R = U_k \Sigma_k V_k^\top + R, \qquad (22)$$

where $V_k \in \mathbb{R}^{n \times k}$ contains the top-k right singular vectors and R is the residual. We define the *principal-subspace pruning energy* as

$$E_{\text{prin}}(M) := \|\Delta V_k\|_F^2 = \sum_{i=1}^{m} \|V_k^\top \delta_i\|_2^2. \qquad (23)$$

This quantity measures how much of the *pruned* weight mass falls inside the dominant right-singular subspace of W.

Proposition 2 (Upper bound induced by the SVD decomposition). *For any pruning mask M,*

$$\begin{aligned} E_{\text{prin}}(M) \leq{}& 2\|((1-M) \odot W_{\text{low}})\|_F^2 \\ & + 2\|((1-M) \odot R)\|_F^2. \end{aligned} \qquad (24)$$

Proof. Using (18) and (22),

$$\begin{aligned} \Delta V_k &= ((1-M) \odot W) V_k \\ &= ((1-M) \odot W_{\text{low}}) V_k \\ &\quad + ((1-M) \odot R) V_k. \end{aligned}$$

Applying $\|A + B\|_F^2 \leq 2\|A\|_F^2 + 2\|B\|_F^2$ gives

$$\begin{aligned} E_{\text{prin}}(M) \leq{}& 2\|((1-M) \odot W_{\text{low}}) V_k\|_F^2 \\ & + 2\|((1-M) \odot R) V_k\|_F^2. \end{aligned}$$

Since V_k has orthonormal columns, right multiplication by V_k cannot increase the Frobenius norm, i.e., $\|A V_k\|_F \leq \|A\|_F$ for any conformable matrix A. Substituting this inequality yields (24). $\qquad \square$

Proposition 2 gives a direct interpretation of the two SVD-derived importance factors. The low-rank score I_{low} explicitly protects entries with large $|W_{\text{low},ij}|$, thereby reducing the first term in (24). The residual-gated magnitude score I_{mag} complements this by favoring entries whose observed weight magnitude is large while the low-rank reconstruction gap is small. In particular, for each entry,

$$|W_{\text{low},ij}| = |W_{ij} - R_{ij}| \geq \max(|W_{ij}| - |R_{ij}|, 0), \qquad (25)$$

so entries with large $|W_{ij}|$ and small residual $|R_{ij}|$ necessarily carry substantial low-rank mass. This makes I_{mag} a residual-aware proxy for low-rank salience, complementary to the explicit low-rank score I_{low}.

D.3 Conditional Relation to Cross-Column Error

To connect (23) to the cross-column term $L_{\text{cross}}(M)$, decompose each row residual in the singular basis:

$$\begin{aligned} \delta_i &= V_k \pi_i + V_\perp \rho_i, \\ \pi_i &= V_k^\top \delta_i, \\ \rho_i &= V_\perp^\top \delta_i, \end{aligned} \qquad (26)$$

where $[V_k, V_\perp]$ is an orthonormal basis of $\mathbb{R}^n$. Define

$$\begin{aligned} A_k &= V_k^\top \Sigma_X^{\text{off}} V_k, \\ B_k &= V_k^\top \Sigma_X^{\text{off}} V_\perp, \\ C_k &= V_\perp^\top \Sigma_X^{\text{off}} V_\perp, \end{aligned} \qquad (27)$$

and the tail energy

$$E_{\text{tail}}(M) := \|\Delta V_\perp\|_F^2 = \sum_{i=1}^{m} \|\rho_i\|_2^2. \qquad (28)$$

Proposition 3 (Cross-column error in the singular basis). *With the definitions above,*

$$\begin{aligned} L_{\text{cross}}(M) = \sum_{i=1}^{m} \Big(& \pi_i^\top A_k \pi_i + 2\, \pi_i^\top B_k \rho_i \\ & + \rho_i^\top C_k \rho_i \Big). \end{aligned} \qquad (29)$$

Consequently,

$$\begin{aligned} |L_{\text{cross}}(M)| \leq{}& \|A_k\|_2 E_{\text{prin}}(M) \\ & + 2\|B_k\|_2 \sqrt{E_{\text{prin}}(M)\, E_{\text{tail}}(M)} \\ & + \|C_k\|_2 E_{\text{tail}}(M). \end{aligned} \qquad (30)$$

Moreover, if $A_k \succeq \mu I$ for some $\mu > 0$, then

$$L_{\mathrm{cross}}(M) \geq \mu\, E_{\mathrm{prin}}(M)$$
$$- 2\|B_k\|_2 \sqrt{E_{\mathrm{prin}}(M)\, E_{\mathrm{tail}}(M)}$$
$$- \|C_k\|_2 E_{\mathrm{tail}}(M). \tag{31}$$

Proof. Substituting (26) into $L_{\mathrm{cross}}(M) = \sum_i \delta_i^\top \Sigma_X^{\mathrm{off}} \delta_i$ gives (29). Then

$$\sum_i \pi_i^\top A_k \pi_i \leq \|A_k\|_2 \sum_i \|\pi_i\|_2^2$$
$$= \|A_k\|_2 E_{\mathrm{prin}}(M),$$

$$2\sum_i |\pi_i^\top B_k \rho_i| \leq 2\|B_k\|_2 \sum_i \|\pi_i\|_2 \|\rho_i\|_2$$
$$\leq 2\|B_k\|_2 \sqrt{E_{\mathrm{prin}}(M)\, E_{\mathrm{tail}}(M)},$$

and

$$\sum_i \rho_i^\top C_k \rho_i \leq \|C_k\|_2 E_{\mathrm{tail}}(M),$$

which yields (30). If $A_k \succeq \mu I$, then $\pi_i^\top A_k \pi_i \geq \mu\|\pi_i\|_2^2$, and (31) follows by lower-bounding the leading term and upper-bounding the remaining two terms in absolute value. $\square$

Proposition 3 clarifies the condition under which the SVD-derived scores are most beneficial. When the off-diagonal input covariance is well aligned with the dominant right-singular subspace—that is, when $\|A_k\|_2$ is non-negligible while the coupling and tail terms $\|B_k\|_2$, $\|C_k\|_2$, and $E_{\mathrm{tail}}(M)$ remain moderate—the cross-column error is largely governed by $E_{\mathrm{prin}}(M)$. In this regime, preserving entries that carry substantial low-rank mass can reduce the dominant component of $L_{\mathrm{cross}}(M)$ beyond what activation-only scoring achieves.

D.4 Interpretation of the Unified Score

Our final element-wise score for layer l is

$$S_{ij}^{(l)} = w_{\mathrm{act}}^{(l)} I_{\mathrm{act},ij}^{(l)} + w_{\mathrm{mag}}^{(l)} I_{\mathrm{mag},ij}^{(l)}$$
$$+ w_{\mathrm{low}}^{(l)} I_{\mathrm{low},ij}^{(l)}, \tag{32}$$
$$w_f^{(l)} \geq 0, \quad \sum_{f \in \{\mathrm{act,mag,low}\}} w_f^{(l)} = 1,$$

where the matrix-level weights $w_f^{(l)}$ are obtained by the CV-based rule in Section 3.3. The three terms play complementary roles:

Table E.1: Offline pruning wall-clock and peak GPU memory on LLaMA-3.1 8B at 50% unstructured sparsity under the same calibration setup. For Wanda++ and PRISM, the corresponding "w/o RO" rows disable the reconstruction stage and isolate the base pruning pipeline. Lower is better.

Method	Time (s)	Peak GPU Mem. (GB)
Wanda	34.65	19.23
SparseGPT	260.02	19.51
Wanda++ w/o RO	144.35	32.57
Wanda++	1929.28	34.75
PRISM w/o RO	836.54	43.22
PRISM + RO	844.77	45.91

- I_{act} is aligned with the diagonal term $L_{\mathrm{diag}}(M)$ in Proposition 1, as it favors entries with large weight magnitude on channels with strong activation energy.

- I_{low} explicitly protects entries with large low-rank magnitude and therefore tightens the upper bound in Proposition 2.

- I_{mag} acts as a residual-aware proxy for low-rank salience via (25), preferentially preserving entries that are both large in magnitude and well explained by the low-rank component.

Therefore, the activation term mainly targets the diagonal reconstruction cost, while the two SVD-derived terms bias the mask toward lower principal-subspace pruning energy and, under the alignment condition described above, lower cross-column error. The role of the CV-based fusion is to heuristically balance these complementary objectives on a per-matrix basis.

Empirical validation. The analysis above motivates several empirical diagnostics. In Section 4.4, we partially validate the mechanism by focusing on the most direct observable prediction: the reduction of layer-wise principal-subspace pruning energy $E_{\mathrm{prin}}(M)$ by PRISM relative to activation-only pruning. This observation does not constitute a global proof of optimality, but it supports the central mechanism identified by the analysis.

E Offline Pruning Cost

Table E.1 reports end-to-end offline pruning cost under the same calibration setup for all methods; the timing includes activation collection, gradient collection, scoring/mask generation, and optional

RO. Post-training pruning is an offline, one-time procedure for a given model and sparsity target, so our objective is not to minimize pruning time at all costs, but to improve the final sparse model within a practical offline budget when such a budget is acceptable. Under this view, PRISM occupies a middle operating regime: it is materially more expensive than lightweight one-shot baselines such as Wanda and SparseGPT, and its SVD-based scoring stage is also heavier than Wanda++ w/o RO (836.54 vs. 144.35 seconds), but it remains much cheaper than the stronger iterative Wanda++ pipeline with RO. Under this protocol, RO adds only 8.23 seconds over PRISM without RO (844.77 vs. 836.54 seconds), i.e., 0.98% extra wall-clock in the full offline pipeline. By contrast, the RO stage increases Wanda++ from 144.35 to 1929.28 seconds, an additional 1784.93 seconds. As a result, the final PRISM + RO pipeline remains $2.28\times$ faster than Wanda++ with RO in wall-clock (844.77 vs. 1929.28 seconds). The main reason is algorithmic: PRISM keeps the sparse mask fixed during RO, so each iteration performs only reconstruction updates on the surviving weights. Wanda++, in contrast, repeatedly re-prunes during RO and re-collects sublayer-specific inputs before each iteration, which substantially increases offline cost. PRISM's peak GPU memory is higher because the SVD-based scoring stage and the fused matrix-level statistics are computed in addition to activation-driven pruning.