VERY DEEP VAES GENERALIZE AUTOREGRESSIVE MODELS AND CAN OUTPERFORM THEM ON IMAGES

ABSTRACT

We present a hierarchical VAE that, for the first time, outperforms the PixelCNN in log-likelihood on all natural image benchmarks. Our work is motivated by the observation that VAEs can actually implement autoregressive models, and other, more efficient generative models, if made sufficiently deep. Despite this, autoregressive models have traditionally outperformed VAEs. To test if depth explains why, we develop an architecture with more stochastic layers than previous work and train it on CIFAR-10, ImageNet, and FFHQ. We find that, in comparison to the PixelCNN, very deep VAEs achieve higher likelihoods, use fewer parameters, generate samples thousands of times faster, and are more easily applied to high-resolution images. We attribute this to the VAEs learning efficient hierarchical representations, which we verify with visualizations of the generative process.

Figure 1: **Selected samples from our very deep VAE on FFHQ-256, and a demonstration of the learned generative process.** VAEs can learn to first generate global features at low resolution, then fill in local details in parallel at higher resolutions. When made sufficiently deep, this learned, parallel, multiscale generative procedure attains a higher log-likelihood than the PixelCNN.

1 INTRODUCTION

One potential path to increased data-efficiency, generalization, and robustness of machine learning methods is to train generative models. These models can learn useful representations without hu-

man supervision by learning to create examples of the data itself. Many types of generative models have flourished in recent years, including likelihood-based generative models, which include autoregressive models (Uria et al., 2013), variational autoencoders (VAEs) (Kingma & Welling, 2014; Rezende et al., 2014), and invertible flows (Dinh et al., 2014; 2016). Their objective, the negative log-likelihood, is equivalent to the KL divergence between the data distribution and the model distribution. A wide variety of models can be compared and assessed along this criteria, which corresponds to how well they fit the data in an information-theoretic sense.

Starting with the PixelCNN (Van den Oord et al., 2016), autoregressive models have long achieved the highest log-likelihoods across many modalities, despite counterintuitive modeling assumptions. For example, although natural images are observations of latent scenes, autoregressive models learn dependencies solely between observed variables. That process can require complex function approximators that integrate long-range dependencies (Oord et al., 2016; Child et al., 2019). In contrast, VAEs and invertible flows incorporate latent variables and can thus, in principle, learn a simpler model that mirrors how images are actually generated. Despite this theoretical advantage, on the landmark ImageNet density estimation benchmark, the Gated PixelCNN still achieves higher likelihoods than all flows and VAEs, corresponding to a better fit with the data.

Is the autoregressive modeling assumption actually a better inductive bias for images, or can VAEs, sufficiently improved, outperform autoregressive models? The answer has significant practical stakes, because large, compute-intensive autoregressive models (Strubell et al., 2019) are increasingly used for a variety of applications (Oord et al., 2016; Brown et al., 2020; Dhariwal et al., 2020; Chen et al., 2020). Unlike autoregressive models, latent variable models only need to learn dependencies between latent and observed variables; such models can not only support faster synthesis and higher-dimensional data, but may also do so using smaller, less powerful architectures.

We start this work with a simple but (to the best of our knowledge) unstated observation: hierarchical VAEs *should* be able to at least match autoregressive models, because autoregressive models are equivalent to VAEs with a powerful prior and restricted approximate posterior (which merely outputs observed variables). In the worst case, VAEs should be able to replicate the functionality of autoregressive models; in the best case, they should be able to learn better latent representations, possibly with much fewer layers, if such representations exist.

We formalize this observation in Section 3, showing it is only true for VAEs with more stochastic layers than previous work has explored. Then we experimentally test it on competitive natural image benchmarks. Our contributions are the following:

- We provide theoretical justification for why greater depth (up to the data dimension D, but also as low as some value $K \ll D$) could improve VAE performance (Section 3)

- We introduce an architecture capable of scaling past 70 layers, when previous work explored at most 30 (Section 4)

- We verify that depth, independent of model capacity, improves log-likelihood, and allows VAEs to outperform the PixelCNN on all benchmarks (Section 5.1)

- Compared to the PixelCNN, we show the model also uses fewer parameters, generates samples thousands of times more quickly, and can be scaled to larger images. We show evidence these qualities may emerge from the model learning an efficient hierarchical representation of images (Section 5.2)

- We release our source code to support research on VAE architectures and techniques

2 PRELIMINARIES

We review prior work and introduce some of the basic terminology used in the field.

2.1 VARIATIONAL AUTOENCODERS

Variational autoencoders (Kingma & Welling, 2014; Rezende et al., 2014) consist of a *generator* $p_\theta(\boldsymbol{x}|\boldsymbol{z})$, a *prior* $p_\theta(\boldsymbol{z})$, and an *approximate posterior* $q_\phi(\mathbf{z}|\mathbf{x})$. Neural networks ϕ and θ are trained

Figure 2: **Different possible learned generative models in a VAE. Left:** A VAE can learn an autoregressive model by using observed variables as latent variables and learning the autoregression in the prior. **Right:** VAEs can also potentially learn more efficient hierarchies of latent variables (black). If the bottom group of three latent variables is conditionally independent given the first, they can be generated in parallel. This could be a faster, but equally correct, generative process.

end-to-end with backpropagation and the reparameterization trick in order to maximize the evidence lower bound (ELBO):

$$\log p_\theta(\mathbf{x}) \geq E_{\mathbf{z} \sim q_\phi(\mathbf{z}|\mathbf{x})} \log p_\theta(\mathbf{x}|\mathbf{z}) - D_{KL}[q_\phi(\mathbf{z}|\mathbf{x})||p_\theta(\mathbf{z})] \tag{1}$$

See Kingma & Welling (2019) for an in-depth introduction. There are many choices for what networks are used for $p_\theta(\boldsymbol{x}|\boldsymbol{z})$, $q_\phi(\boldsymbol{z}|\boldsymbol{x})$, and whether $p_\theta(\boldsymbol{z})$ is also learned or set to a simple distribution.

We study VAEs with independent $p_\theta(\boldsymbol{x}|\boldsymbol{z})$ – that is, where each observed x_i is output without conditioning on any other x_j. This ensures generation time does not increase linearly with the dimensionality of the data, and requires that these VAEs learn to incorporate the complexity of the data into a rich distribution over latent variables $\boldsymbol{z}$. It is possible to have autoregressive $p_\theta(\boldsymbol{x}|\boldsymbol{z})$ (Gulrajani et al., 2016), but generation time is slow for these models. They also sometimes ignore latent variables entirely, becoming equivalent to normal autoregressive models (Chen et al. (2016)).

2.2 HIERARCHICAL VARIATIONAL AUTOENCODERS

Much of the early work on VAEs incorporate fully-factorized Gaussian $q_\phi(\boldsymbol{z}|\boldsymbol{x})$ and $p_\theta(\boldsymbol{z})$. This can lead to poor outcomes if the latent variables required for good generation take on a more complex distribution, as is common with independent $p_\theta(\boldsymbol{x}|\boldsymbol{z})$. One of the simplest methods of gaining greater expressivity in both distributions is to use a hierarchical VAE, which has several *stochastic layers* of latent variables. These variables are emitted in groups $\boldsymbol{z}_0, \boldsymbol{z}_1, ..., \boldsymbol{z}_N$, which are conditionally dependent upon each other in some way. For images, latent variables are typically output in feature maps of varying resolutions, with $\boldsymbol{z}_0$ corresponding to a small number of latent variables at low resolution at the "top" of the network, and $\boldsymbol{z}_N$ corresponding to a larger number of latent variables at high resolution at the "bottom".

One particularly elegant conditioning structure is the *top-down VAE*, introduced in Sønderby et al. (2016). In this model, both the prior and the approximate posterior generate latent variables in the same order:

$$p_\theta(\boldsymbol{z}) = p_\theta(\boldsymbol{z}_0)p_\theta(\boldsymbol{z}_1|\boldsymbol{z}_0)...p_\theta(\boldsymbol{z}_N|\boldsymbol{z}_{<N}) \tag{2}$$

$$q_\phi(\boldsymbol{z}|\boldsymbol{x}) = q_\phi(\boldsymbol{z}_0|\boldsymbol{x})q_\phi(\boldsymbol{z}_1|\boldsymbol{z}_0, \boldsymbol{x})...q_\phi(\boldsymbol{z}_N|\boldsymbol{z}_{<N}, \boldsymbol{x}) \tag{3}$$

A diagram of this process appears in Figure 3. A typical implementation of this model has ϕ first perform a deterministic "bottom-up" pass on the data to generate features, then processes the groups of latent variables from top to bottom, using feedforward networks to generate features which are shared between the approximate posterior, prior, and reconstruction network $p_\theta(\boldsymbol{x}|\boldsymbol{z})$. We adopt this base architecture as it is simple, empirically effective, and has been postulated to resemble biological processes of perception (Dayan et al., 1995).

Figure 3: **A diagram of our top-down VAE architecture.** Residual blocks are similar to bottleneck ResNet blocks (He et al., 2016). Each convolution is preceded by the GELU nonlinearity (Hendrycks & Gimpel, 2016). $q_\phi(.)$ and $p_\theta(.)$ are diagonal Gaussian distributions. $\mathbf{z}$ is sampled from $q_\phi(.)$ during training, and $p_\theta(.)$ when sampling.

3 WHY DEPTH MATTERS FOR HIERARCHICAL VAEs

We find that hierarchical VAEs with sufficient depth can not only learn arbitrary orderings over observed variables, but also learn more effective latent variable distributions, if such distributions exist. We present these results below.

Definition (N-layer VAE). A deep hierarchical VAE with N stochastic layers, independent $p(\boldsymbol{x}|\boldsymbol{z})$, and the top-down factorization of the prior and approximate posterior in Equations 2-3.

Proposition 1. *N-layer VAEs generalize autoregressive models when N is the data dimension*

Proposition 2. *N-layer VAEs are universal approximators of N-dimensional latent densities*

Proposition 1 (proof in Appendix, also visualized in Figure 2, left) leads to a possible explanation of why autoregressive models to date have outperformed VAEs: *they are deeper*, in the sense of statistical dependence. A VAE must be as deep as the data dimension D (3072 layers in the case of 32x32 images) if the images truly require D steps to generate.

Luckily, however, Proposition 2 (proof and further technical requirements in Appendix) suggests that shorter procedures, if they exist, are also learnable. $N = D$ is an extreme case, where the most effective latent variables $\boldsymbol{z} \in \mathbb{R}^D$ are the observed variables themselves. But if for some $K < D$ there exist latent variables $\boldsymbol{z} \in \mathbb{R}^K$ that the generator can use to more efficiently compress the data, Proposition 2 states a K-layer VAE can learn the posterior and prior distribution over those variables.

Such shorter generative paths could emerge in two ways. First, as depicted in Figure 2 (right), if the model discovers that certain variables are conditionally independent given others, the model can generate multiple variables in each $\boldsymbol{z}$ independently and in parallel. We hypothesize these efficient hierarchies should emerge in images, as they contain many spatially independent textures, and study this in Section 5.2. Second, the model could learn a low-dimensional representation of the data. Dai & Wipf (2019) recently showed that when a VAE is trained on data distributed on a K-dimensional

manifold embedded in $\mathbb{R}^D$, a VAE will only activate K dimensions in its latent space, meaning that the VAE will require fewer layers unless the manifold dimension is D, which is unlikely to be the case for images.

It is difficult to ascertain the lowest possible value of K for a given dataset, but it may be deeper than most hierarchical VAEs to date. Images have many thousands of observed variables, but early hierarchical VAEs did not exceed 3 layers, until Maaløe et al. (2019) investigated a Gaussian VAE with 15 layers and found it displayed impressive performance along a variety of measures. Kingma et al. (2016) and Vahdat & Kautz (2020) additionally explored networks up to 12 and 30 layers. (These additionally incorporated additional statistical dependencies in the approximate posterior through the usage of inverse autoregressive flow (Kingma et al., 2016), an alternative approach which we contrast with our approach in Section A.3). Nevertheless, given these results we hypothesize that greater depth may improve the performance of VAEs. In the next section, we introduce an architecture capable of scaling to a greater number of stochastic layers. In Section 5.1 we show depth indeed improves performance.

4   AN ARCHITECTURE FOR VERY DEEP VAEs

We consider a "very deep" VAE to simply be one with greater depth than has previously been explored (and do not define it to be a specific number of layers). We found existing implementations of VAEs could not support many more stochastic layers than they were trained on, and so reimplemented a minimal VAE with the sole aim of supporting large numbers of stochastic layers. This network consists only of convolutions, nonlinearities, and Gaussian stochastic layers, and does not exhibit posterior collapse even for large numbers of stochastic layers. We detail key implementation notes here, and refer readers to our source code for further detail.

4.1   ARCHITECTURAL COMPONENTS AND INITIALIZATION

We present a diagram of our network in Figure 3. It is similar to the ResNet VAE in Kingma et al. (2016), but with bottleneck residual blocks. As an alternative to weight normalization and data-dependent initialization (Salimans & Kingma, 2016), we find that we can simply adopt the default PyTorch weight intialization for most layers in the network. The one exception is the the final convolutional layer in each residual bottleneck block, which we scale by $\frac{1}{\sqrt{N}}$, where N is the depth of the network (similar to Radford et al. (2019); Child et al. (2019); Zhang et al. (2019)). Additionally, our upsampling layers simply perform nearest-neighbor interpolation, instead of being learned convolutional layers.

We found no posterior collapse occured when using nearest-neighbor interpolation, even with many layers. This may be because the topmost stochastic layers receive gradients directly from the bottommost reconstruction loss without being scaled by intermediate convolutional layers. This allows us to remove the "free bits" or KL "warming up" terms from the objective that appear in related work.

4.2   STABILIZING TRAINING WITH GRADIENT SKIPPING AND PRIOR WARMUP

VAEs have notorious "optimization difficulties," which are not frequently discussed in the literature but nevertheless well-known by practitioners. These manifest as extremely high reconstruction or KL losses and corresponding large gradient magnitudes, which may be due to the variance involved in sampling latent variables. We found the vast majority of gradients would have norms within a predictable range, and relatively few (one in a thousand updates) would have unusually high or NaN gradient norms. Vahdat & Kautz (2020) adopted a spectral regularization term in order to address this, but we chose to adopt the heuristic strategy of skipping updates with grad norm above a certain value (set as a hyperparameter). We found this led to reliable convergence without significantly affecting training dynamics.

We also found that directly training $p_\theta(z)$ against $q_\phi(z|x)$ initially led to instability during training, as both distributions can take on arbitrarily large or small values. We adopted a heuristic method of training $q_\phi(z|x)$ against the initial, fixed value of the prior for around the first half of training, then directly training them against each other for the second half. This results in stable training, but is

Table 1: **Loss by network with different configurations of stochastic layers on ImageNet-32** (similar trends appear on CIFAR-10). **Left**: Networks with equal number of layers, but with masking introduced such that the effective stochastic depth is lower. Increasing depth up to 48 layers still shows gains, which is farther than previous work has explored. **Right**: Networks with 48 layers, but distributed at different resolutions. We find higher resolutions benefit more from layers.

Depth	Params	Test Loss		Distribution of 48 layers					Test Loss
				32x32	16x16	8x8	4x4	1x1	
3	41M	4.30							
6	41M	4.18		10	10	10	10	8	3.98
12	41M	4.06		12	12	10	8	6	3.97
24	41M	3.98		14	14	10	6	4	3.96
48	41M	3.95		16	16	10	4	2	3.95

admittedly a heuristic approach that could benefit from deeper investigation into training dynamics in VAEs, which we defer to future work.

5 EXPERIMENTS

We trained very deep VAEs on challenging natural image datasets. All hyperparameters for experiments are available in our source code.

5.1 STATISTICAL DEPTH, INDEPENDENT OF CAPACITY, IMPROVES PERFORMANCE

We first tested whether greater statistical depth, independent of other factors, can result in improved performance. We trained a network with 48 layers for 600k steps on ImageNet-32, grouping layers to output variables independently, instead of conditioning on each other, in order to reduce the effective depth (Table 1, left). Stochastic depth shows a clear correlation with performance, even up to 48 layers, which is past what previous work has explored.

We then tested our hypothesis at scale. We trained networks on CIFAR-10, ImageNet-32, and ImageNet-64 with greater numbers of stochastic layers, but with *fewer* parameters than related work (see Table 2). On CIFAR-10, we trained a model with 45 stochastic layers and only 39M parameters, and found it achieved a test log-likelihood of 2.86 bits per dim (average of 4 seeds). On ImageNet-32 and ImageNet-64, we trained networks with 78 and 75 stochastic layers and only approximately 115M parameters, and achieved likelihoods of 3.82 and 3.55.

On all tasks, these results outperform all GatedPixelCNN/PixelCNN++ models, and all non-autoregressive models, while using similar or fewer parameters. These results support our hypothesis that *stochastic depth*, as opposed to other factors, explains the gap between VAEs and autoregressive models.

5.2 VERY DEEP VAEs LEARN AN EFFICIENT HIERARCHICAL ORDERING

One question that emerges from the analysis in Section 3 is whether VAEs need to be as deep as autoregressive models, or whether they can learn a latent hierarchy of conditionally independent variables which are able to be synthesized in parallel. We qualitatively show this is true in Figure 4. For FFHQ-256 images, the first several layers at low resolution almost wholly determine the global features of the image, even though they only account for less than 1% of the latent variables. The rest of the high-resolution variables can be output in parallel, largely independent of each other, in a number of steps much lower than the dimensionality of the image. This efficient hierarchical representation may underlie the VAE's ability to achieve better log-likelihoods than the PixelCNN while simultaneously sampling thousands of times faster. This can be viewed as an *learned* parallel multiscale generation method, unlike the handcrafted approaches of Kolesnikov & Lampert (2017); Menick & Kalchbrenner (2018); Reed et al. (2017).

Additionally, we found that on all datasets we tested, very deep VAEs used roughly 30% fewer parameters than the PixelCNN (Table 2). One possible explanation is that the learned hierarchical generation procedure involves fewer long-range dependencies, or may otherwise be simpler to learn.

| 1x1 | 4x4 | 8x8 | 16x16 | 32x32 | 64x64 | 128x128 |

| <0.001% | 0.03% | 0.15% | 1.1% | 9.5% | 30.1% | 74% |

Figure 4: **Cumulative percentage of latent variables at a given resolution, and reconstructions of samples on FFHQ-256.** Low-resolution variables account for a small fraction of variables, but encode most of the global structure. This suggests deep VAEs learn efficient hierarchical orderings of variables, which requires less depth than autoregressive models and enables fast, parallel synthesis.

We found that networks in general benefited from more layers at higher resolutions (Table 1, right). This suggests that global features may account for a smaller fraction of information than local details and textures, and that it is important to have many latent variables at high resolution. Regardless, as the visualization in Figure 4 shows, these local details can be rendered in parallel in a VAE, as opposed to requiring sequential synthesis as in an autoregressive model.

5.2.1 VERY DEEP VAES ARE EASILY SCALED TO HIGH DIMENSIONAL DATA

Scaling autoregressive models to higher resolutions presents several challenges. First, the sampling time and memory requirements of autoregressive models increase *linearly* with resolution. This scaling makes datasets like FFHQ-256 and FFHQ-1024 intractable for naive approaches. Although clever factorization techniques have been adopted for 256x256 images (Menick & Kalchbrenner, 2018), such factorizations may not be as effective for alternate datasets or higher-resolution images.

Our VAE, in contrast, scales easily across multiple resolutions. It uses essentially the same network for 32x32, 64x64, 256x256, and 1024x1024 images. For each higher resolution, we simply add successive higher-resolution convolutional layers. Unlike with autoregressive models, this scaling does not require greater training resources in kind. Although FFHQ-1024 is approximately a thousand times higher in dimensionality than ImageNet-32, we were able to train a similar amount of steps on an equally-sized model (about 100M parameters) using identical training resources (32 GPUs for 2 weeks). Samples are generated similarly as fast on both resolutions (although the samples on FFHQ-1024 are not as high quality due to the increased complexity of the dataset; see Appendix). These computational benefits of VAEs are a clear advantage over autoregressive models.

6 RELATED WORK AND DISCUSSION

Our work is inspired by previous and concurrent work in hierarchical VAEs (Sønderby et al., 2016; Maaløe et al., 2019; Vahdat & Kautz, 2020). Relative to these works, we provide some justification for why deeper networks may perform better, introduce a new architecture, and empirically demonstrate gains in log-likelihood. Many aspects of prior work are complementary with ours and could be combined. Maaløe et al. (2019), for instance, incorporates a "bottom-up" stochastic path that doubles the depth of the approximate posterior, and Vahdat & Kautz (2020) introduces a number of powerful architecture components and improved training techniques. We seek here not to introduce a significantly better method than these alternatives, but to demonstrate that depth is a key overlooked factor in most prior approaches to VAEs.

Diffusion models can be seen as deep VAEs that, like autoregressive models, have a specific analytical posterior. Ho et al. (2020) showed that such models achieve impressive sample quality with great

Table 2: **Our main results on standard benchmark datasets.** Very deep VAEs outperform PixelCNN-based autoregressive models with fewer parameters while maintaining fast sampling. "Depth" refers to the number of stochastic layers for hierarchical VAEs (although BIVA and IAF-based networks have additional statistical dependencies). Sampling refers to the number of network evaluations per sample, and D designates the dimensionality of the data. An asterisk (*) denotes our estimate of parameters. Samples for ImageNet and CIFAR-10 are in the Appendix.

	Model type	Params	Depth	Sampling	NLL
CIFAR-10					
PixelCNN++ (Salimans et al., 2017)	AR	53M*		D	2.92
PixelSNAIL (Chen et al., 2017)	AR			D	2.85
Sparse Transformer (Child et al., 2019)	AR	59M		D	**2.80**
VLAE (Chen et al., 2016)	VAE			D	≤ 2.95
IAF-VAE (Kingma et al., 2016)	VAE		12	1	≤ 3.11
Flow++ (Ho et al., 2019)	Flow	31M		1	≤ 3.08
BIVA (Maaløe et al., 2019)	VAE	103M	15	1	≤ 3.08
NVAE (Vahdat & Kautz, 2020)	VAE	131M	30	1	≤ 2.91
Very Deep VAE (**ours**)	VAE	39M	45	1	$\leq$ **2.86**
ImageNet-32					
Gated PixelCNN	AR	177M*	10	D	3.83
Image Transformer (Parmar et al., 2018)	AR			D	**3.77**
BIVA	VAE	103M*	15	1	≤ 3.96
NVAE	VAE	268M	28	1	≤ 3.92
Flow++	Flow	169M		1	≤ 3.86
Very Deep VAE (**ours**)	VAE	114M	78	1	$\leq$ **3.82**
ImageNet-64					
Gated PixelCNN	AR	177M*		D	3.57
SPN (Menick & Kalchbrenner, 2018)	AR	150M		D	3.52
Sparse Transformer	AR	152M		D	**3.44**
Glow (Kingma & Dhariwal, 2018)	Flow			1	3.81
Flow++	Flow	73M		1	≤ 3.69
Very Deep VAE (**ours**)	VAE	117M	75	1	$\leq$ **3.55**
FFHQ-256 (5 bit)					
NVAE	VAE		36	1	≤ 0.68
Very Deep VAE (**ours**)	VAE	100M	62	1	$\leq$ **0.66**
FFHQ-1024 (8 bit)					
Very Deep VAE (**ours**)	VAE	106M	72	1	$\leq$ **2.50**

depth, which is in line with our observations that greater depth is helpful for VAEs. One benefit of the VAEs we outline in this work over diffusion models is that our VAEs generate samples with a single network evaluation, whereas diffusion models currently require a large number of network evaluations per sample.

Inverse autoregressive flows (IAF) are also closely related, and we discuss the differences with hierarchical models in Section A.3. The work of Zhao et al. (2017) may also appear to contradict our findings, and we discuss that work in Section A.4.

7 CONCLUSION

We argue deeper VAEs should perform better, introduce a deeper architecture, and show it outperforms all PixelCNN-based autoregressive models in likelihood while being more efficient. We hope this encourages work in further improving VAEs and latent variable models.

REFERENCES

Tom B Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *arXiv preprint arXiv:2005.14165*, 2020.

Mark Chen, Alec Radford, Rewon Child, Jeff Wu, Heewoo Jun, Prafulla Dhariwal, David Luan, and Ilya Sutskever. Generative pretraining from pixels. In *Proceedings of the 37th International Conference on Machine Learning*, 2020.

Xi Chen, Diederik P Kingma, Tim Salimans, Yan Duan, Prafulla Dhariwal, John Schulman, Ilya Sutskever, and Pieter Abbeel. Variational lossy autoencoder. *arXiv preprint arXiv:1611.02731*, 2016.

Xi Chen, Nikhil Mishra, Mostafa Rohaninejad, and Pieter Abbeel. Pixelsnail: An improved autoregressive generative model. *arXiv preprint arXiv:1712.09763*, 2017.

Rewon Child, Scott Gray, Alec Radford, and Ilya Sutskever. Generating long sequences with sparse transformers. *arXiv preprint arXiv:1904.10509*, 2019.

Bin Dai and David Wipf. Diagnosing and enhancing vae models. *arXiv preprint arXiv:1903.05789*, 2019.

Peter Dayan, Geoffrey E Hinton, Radford M Neal, and Richard S Zemel. The helmholtz machine. *Neural computation*, 7(5):889–904, 1995.

Prafulla Dhariwal, Heewoo Jun, Christine Payne, Jong Wook Kim, Alec Radford, and Ilya Sutskever. Jukebox: A generative model for music. *arXiv preprint arXiv:2005.00341*, 2020.

Laurent Dinh, David Krueger, and Yoshua Bengio. Nice: Non-linear independent components estimation. *arXiv preprint arXiv:1410.8516*, 2014.

Laurent Dinh, Jascha Sohl-Dickstein, and Samy Bengio. Density estimation using real nvp. *arXiv preprint arXiv:1605.08803*, 2016.

Ishaan Gulrajani, Kundan Kumar, Faruk Ahmed, Adrien Ali Taiga, Francesco Visin, David Vazquez, and Aaron Courville. Pixelvae: A latent variable model for natural images. *arXiv preprint arXiv:1611.05013*, 2016.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Dan Hendrycks and Kevin Gimpel. Gaussian error linear units (gelus). *arXiv preprint arXiv:1606.08415*, 2016.

Jonathan Ho, Xi Chen, Aravind Srinivas, Yan Duan, and Pieter Abbeel. Flow++: Improving flow-based generative models with variational dequantization and architecture design. *arXiv preprint arXiv:1902.00275*, 2019.

Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. *arXiv preprint arxiv:2006.11239*, 2020.

Chin-Wei Huang, Ahmed Touati, Laurent Dinh, Michal Drozdzal, Mohammad Havaei, Laurent Charlin, and Aaron Courville. Learnable explicit density for continuous latent space and variational inference. *arXiv preprint arXiv:1710.02248*, 2017.

Chin-Wei Huang, David Krueger, Alexandre Lacoste, and Aaron Courville. Neural autoregressive flows. *arXiv preprint arXiv:1804.00779*, 2018.

Diederik P Kingma and Max Welling. Stochastic gradient vb and the variational auto-encoder. In *Second International Conference on Learning Representations, ICLR*, volume 19, 2014.

Diederik P Kingma and Max Welling. An introduction to variational autoencoders. *arXiv preprint arXiv:1906.02691*, 2019.

Durk P Kingma and Prafulla Dhariwal. Glow: Generative flow with invertible 1x1 convolutions. In *Advances in Neural Information Processing Systems*, pp. 10215–10224, 2018.

Durk P Kingma, Tim Salimans, Rafal Jozefowicz, Xi Chen, Ilya Sutskever, and Max Welling. Improved variational inference with inverse autoregressive flow. In *Advances in neural information processing systems*, pp. 4743–4751, 2016.

Alexander Kolesnikov and Christoph H Lampert. Pixelcnn models with auxiliary variables for natural image modeling. In *International Conference on Machine Learning*, pp. 1905–1914. PMLR, 2017.

Lars Maaløe, Marco Fraccaro, Valentin Liévin, and Ole Winther. Biva: A very deep hierarchy of latent variables for generative modeling. In *Advances in neural information processing systems*, pp. 6548–6558, 2019.

Jacob Menick and Nal Kalchbrenner. Generating high fidelity images with subscale pixel networks and multidimensional upscaling. *arXiv preprint arXiv:1812.01608*, 2018.

Aaron van den Oord, Sander Dieleman, Heiga Zen, Karen Simonyan, Oriol Vinyals, Alex Graves, Nal Kalchbrenner, Andrew Senior, and Koray Kavukcuoglu. Wavenet: A generative model for raw audio. *arXiv preprint arXiv:1609.03499*, 2016.

George Papamakarios, Eric Nalisnick, Danilo Jimenez Rezende, Shakir Mohamed, and Balaji Lakshminarayanan. Normalizing flows for probabilistic modeling and inference. *arXiv preprint arXiv:1912.02762*, 2019.

Niki Parmar, Ashish Vaswani, Jakob Uszkoreit, Łukasz Kaiser, Noam Shazeer, Alexander Ku, and Dustin Tran. Image transformer. *arXiv preprint arXiv:1802.05751*, 2018.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. Language models are unsupervised multitask learners. *OpenAI Blog*, 1(8):9, 2019.

Scott Reed, Aäron van den Oord, Nal Kalchbrenner, Sergio Gómez Colmenarejo, Ziyu Wang, Dan Belov, and Nando De Freitas. Parallel multiscale autoregressive density estimation. *arXiv preprint arXiv:1703.03664*, 2017.

Danilo Jimenez Rezende, Shakir Mohamed, and Daan Wierstra. Stochastic backpropagation and approximate inference in deep generative models. *arXiv preprint arXiv:1401.4082*, 2014.

Tim Salimans and Durk P Kingma. Weight normalization: A simple reparameterization to accelerate training of deep neural networks. In *Advances in neural information processing systems*, pp. 901–909, 2016.

Tim Salimans, Andrej Karpathy, Xi Chen, and Diederik P Kingma. Pixelcnn++: Improving the pixelcnn with discretized logistic mixture likelihood and other modifications. *arXiv preprint arXiv:1701.05517*, 2017.

Casper Kaae Sønderby, Tapani Raiko, Lars Maaløe, Søren Kaae Sønderby, and Ole Winther. Ladder variational autoencoders. In *Advances in neural information processing systems*, pp. 3738–3746, 2016.

Emma Strubell, Ananya Ganesh, and Andrew McCallum. Energy and policy considerations for deep learning in nlp. *arXiv preprint arXiv:1906.02243*, 2019.

Benigno Uria, Iain Murray, and Hugo Larochelle. Rnade: The real-valued neural autoregressive density-estimator. In *Advances in Neural Information Processing Systems*, pp. 2175–2183, 2013.

Arash Vahdat and Jan Kautz. Nvae: A deep hierarchical variational autoencoder. *arXiv preprint arXiv:2007.03898*, 2020.

Aaron Van den Oord, Nal Kalchbrenner, Lasse Espeholt, Oriol Vinyals, Alex Graves, et al. Conditional image generation with pixelcnn decoders. In *Advances in neural information processing systems*, pp. 4790–4798, 2016.

Hongyi Zhang, Yann N Dauphin, and Tengyu Ma. Fixup initialization: Residual learning without normalization. *arXiv preprint arXiv:1901.09321*, 2019.

Shengjia Zhao, Jiaming Song, and Stefano Ermon. Learning hierarchical features from generative models. *arXiv preprint arXiv:1702.08396*, 2017.

A   Appendix

Figure 5: **Non-cherrypicked, temperature 1.0 samples on FFHQ-256.** Cover images were each cherrypicked from a batch of 16 (unadjusted temperature) samples. Here we show a random batch of 16 images for comparison.

A.1   Proposition 1: N-layer VAEs generalize autoregressive models when N is the data dimension

Proposition 1 shows that an autoregressive model with an arbitrary ordering over observed variables in $\boldsymbol{x} \in \mathbb{R}^N$ is equivalent to an N-layer VAE with an approximate posterior that simply outputs the observed variables in the given order, and a generator that performs the identity function (see Figure 2).

Without loss of generality, we simplify notation by assuming each vector-valued latent variable $\boldsymbol{z}_i$ only has one element, which we write as z_i.

Proof. Let $q(z_i = x_i | z_{<i}, \boldsymbol{x}) = 1$, and $p(x_i = z_i | \boldsymbol{z}) = 1$. Then $p(\boldsymbol{z}|\boldsymbol{x}) = q(\boldsymbol{z}|\boldsymbol{x})$, which is well-known to imply equality in the evidence lower bound (ELBO) of Eq. 1. Since $\log q(\boldsymbol{z}|\boldsymbol{x}) = \log p(\boldsymbol{x}|\boldsymbol{z}) = 0$, the ELBO becomes $\log p_\theta(\boldsymbol{x}) = \log p_\theta(\boldsymbol{z}) = \sum_{i=1}^N \log p_\theta(z_i|z_{<i}) = \sum_{i=1}^N \log p_\theta(x_i|x_{<i})$, which is equivalent to an autoregressive model over the observed variables. $\square$

Figure 6: **Non-cherrypicked, temperature 0.85 samples on FFHQ-256.** Lower temperature samples result in greater regularity in images.

A.2 Proposition 2: N-layer VAEs are universal approximators of N-dimensional latent densities

Proposition 2 shows that hierarchical VAEs learn depthwise autoregressive flows, and under certain conditions (described in Huang et al. (2017)) can express *any* density over latent variables of N dimensions, given enough capacity.

Without loss of generality, we simplify notation by assuming each vector-valued latent variable $\boldsymbol{z}_i$ only has one element, which we write as z_i.

Proof. We omit full proof, and refer readers to Huang et al. (2017); Papamakarios et al. (2019), where universality is established for autoregressive flows. Here we only note that the prior and approximate posterior in an N-layer VAE are autoregressive flows: Let $p_\theta(\boldsymbol{z})$ be the prior distribution. $p_\theta(\boldsymbol{z})$ can be written using the reparameterization trick as a deterministic function of noise ϵ drawn from a known base density p_N: $p_\theta(\boldsymbol{z}) = p_N(\epsilon) \left| \det \frac{\partial f(\epsilon, \theta)}{\partial \epsilon} \right|$, where f is a neural network that implements the factorization in Eq. 2. Since f is autoregressive and its Jacobian is lower triangular, $p_\theta(\boldsymbol{z})$ can approximate any $p(\boldsymbol{z})$ that fits the criteria in Huang et al. (2017). The same logic applies to $q_\phi(\boldsymbol{z}|\boldsymbol{x})$ and $p(\boldsymbol{z}|\boldsymbol{x})$. It should be noted that this result depends on f being able to implement the inverse CDF of an arbitrary probability density, and so using Gaussian distributions will restrict the densities the VAE can express in practice. This is a limitation of our architecture that we nevertheless adopt since we hypothesize depth, not the elementwise density, is the more important factor. More discussion on this subject, and options for removing this restriction, are described in Huang et al. (2017) and Huang et al. (2018), and we defer studying more expressive elementwise densities to future work. $\qquad\square$

Figure 7: **Non-cherrypicked, temperature 0.60 samples on FFHQ-256.** We visualize temperature 0.60 samples for comparison with Vahdat & Kautz (2020)

A.3   A NOTE ON INVERSE AUTOREGRESSIVE FLOW

Inverse autoregressive flows (IAF, Kingma et al. (2016)) and are similar to very deep VAEs in that they are universal approximators of posterior distributions in VAEs, even with just a *single* layer and sufficiently expressive univariate density (Huang et al., 2018).

There are several practical differences between IAFs and deep hierarchical VAEs, however, which can result in qualitatively very different behavior. First, the masked autoregressive components in IAF build statistical dependencies *spatially*, whereas a very deep hierarchical VAE builds dependencies *depthwise*, and these inductive biases may better suit different domains. Additionally, IAFs spend an equal amount of computation and parameters on each variable. In contrast, a deep VAE can specify a structure, like a hierarchy of global-to-local variables, which have different computational and modeling capacities for each stage. For images, these differences may result in qualitatively different behavior, and it is not clear whether a single layer IAF can readily learn the sort of rich hierarchical decomposition of images that appear with very deep VAEs.

Nevertheless, the two techniques are complementary – IAF was introduced in a deep hierarchical VAE (Kingma et al., 2016), in fact, and it is likely that introducing IAF into our architecture (as in Vahdat & Kautz (2020)) would improve performance.

A.4   A NOTE ON LEARNING HIERARCHICAL FEATURES

The work of Zhao et al. (2017) may appear to contradict our work, by suggesting that additional layers in hierarchical VAEs *do not* lead to additional expressivity, based off their finding that Gibbs sampling from the last stochastic layer is sufficient to recover the data. For high dimensional data like images, however, the last stochastic layer may have many thousands of variables, and Gibbs

Figure 8: **ImageNet-32 (left) and ImageNet-64 (right) reconstructions and samples.** Reconstructions of validation images from various stages in the latent hierarchy (top), and unconditional samples from the model at temperature 1.0 (bottom).

Figure 9: **FFHQ-1024 samples.** These are generated with reduced temperature (top) and temperature 1.0 (bottom). The model we train has similar capacity to smaller ones we use on 32x32, 64x64, and 256x256 images, and so fails to capture the intricacies of this more complex distribution well. A larger model, trained for longer, may achieve better sample quality.

sampling may take unacceptably long to converge. A hierarchy of latent variables as in our model allows efficient and tractable sampling from this distribution. Additionally, assumptions regarding

global maximization of the ELBO may not apply in practice. Nevertheless, we think further clarifying these contradictory statements would be useful future work.

A.5 BROADER IMPACT

Broadly speaking, any generative model will reflect the biases of the datasets they are trained on. If deployed without careful consideration, generative models (including but not limited to VAEs) trained on research datasets like ImageNet, CIFAR-10, and FFHQ may inadvertently cause harm by propagating or otherwise reinforcing harmful biases in the dataset. Further work is required to improve and debias research benchmark datasets to mitigate this source of negative impact.

Some VAEs are distinguished from other generative models by their fast synthesis of new data examples. Generative models with fast synthesis can allow for realtime synthesis of high dimensional data, such as music, speech, and video. These models could be used to augment human creativity and lead to a number of helpful applications in real-time media applications. Such models could also be used for compression, which could assist in delivering content to bandwidth-constrained regions of the world. They can also be used for spreading disinformation, generally making it less possible to distinguish real from generated data. An additional potential harm is that fast, high quality synthesis of data could end up economically displacing individuals who rely upon creative work, such as musicians, visual artists, and more.

VAEs also are distinguished by their usage of latent variables. Generative models with useful latent variables could have positive impacts in scientific domains, where density estimation could lead to novel insights about chemical, physical, or biological data. Latent variable representations of data could also be helpful in efforts to debias, interpret, or otherwise increase understandibility of models and their representations.