Deep Ensembling with No Overhead for either Training or Testing: The All-Round Blessings of Dynamic Sparsity

Abstract

Recent works on sparse neural networks have demonstrated the possibility to train a sparse subnetwork independently from scratch, to match the performance of its corresponding dense network. However, identifying such sparse subnetworks ("winning tickets") either involves a costly iterative train-prune-retrain process (e.g., Lottery Ticket Hypothesis) or an over-extended training time (e.g., Dynamic Sparse Training). In this work, we draw a unique connection between sparse neural network training and the deep ensembling technique, yielding a novel ensemble learning framework called $FreeTickets$. Instead of starting from a dense network, $FreeTickets$ randomly initializes a sparse subnetwork, and then trains the subnetwork while dynamically adjusting its sparse mask, resulting in many diverse sparse subnetworks throughout the training process. $FreeTickets$ is defined as the ensemble of these sparse subnetworks freely obtained during this one-pass, sparse-to-sparse training, which uses only a fraction of the computational resources required by the vanilla dense training. Moreover, despite being an ensemble of models, $FreeTickets$ has even fewer parameters and training FLOPs compared to a single dense model: this seemingly counter-intuitive outcome is due to the high sparsity of each subnetwork. $FreeTickets$ is observed to demonstrate a significant all-round improvement compared to standard dense baselines, in prediction accuracy, uncertainty estimation, robustness, and efficiency. $FreeTickets$ easily outperforms the naive deep ensemble with ResNet50 on ImageNet using only a quarter of the training FLOPs required by the latter. Our results provide insights into the strength of sparse neural networks and suggest that the benefits of sparsity go way beyond the usually expected inference efficiency.

1 Introduction

Recently proposed large-scale models (Touvron et al., 2020; Dosovitskiy et al., 2021; Brown et al., 2020; Touvron et al., 2021) have shown strong results on different tasks, with prohibitive training time and financial costs. These enormous training costs are potentially beyond the reach of most of researchers and startups, leading to financial and environmental concerns (García-Martín et al., 2019; Schwartz et al., 2019; Strubell et al., 2019).

To accelerate the training process, researchers have investigated efforts to train sparse neural networks from scratch (sparse training), and meanwhile maintain comparable performance. While being promising on training efficiency, sparse training in general is a tough nut to crack, as directly training a sparse network from scratch typically results in worse performance than their dense counterparts (Kalchbrenner et al., 2018; Evci et al., 2019). Currently, two emerging techniques have stood out with matching performance while keeping the network sparse throughout the training time: Lottery Ticket Hypothesis (Frankle & Carbin, 2018; Frankle et al., 2020; Renda et al., 2020; Chen et al., 2020b) and Dynamic Sparse Training (Mocanu et al., 2018; Bellec et al., 2018; Evci et al., 2020a; Liu et al., 2021b).

Works on the Lottery Ticket Hypothesis (LTH) point out the existence of highly trainable sparse subnetworks (winning tickets) at initialization or the early stage of training, which can be trained in isolation to match the performance of the dense networks. Despite the insightful findings, these winning tickets are found by iterative post-training pruning, hindering the usage of LTH in practice.

For instance, the overall floating-point operations (FLOPs) required to find and train a winning ticket at a sparsity of 80% is 4 times more than training a dense model. On the other hand, Dynamic Sparse Training (DST) seeks to train sparse neural networks from scratch with strict training budget. It starts from a randomly-initialized sparse network and optimizes the model weights together with the sparse connectivity during training. Currently, the current only way for DST to match the performance of its dense counterpart on the popular benchmark, e.g., ResNet-50 on ImageNet, is to perform In-Time Over-Parameterization (Evci et al., 2020a; Liu et al., 2021b), which might require thousands of training epochs for extremely sparse models.

In this paper, we attempt to address this problem from a different perspective. The insight we build on comes from the work of Liu et al. (2020) which empirically demonstrates that a full network contains a plenitude of performant subnetworks that are very different in the topological space. We further ask the following question: *Instead of allocating all resources to find a strong learner (winning ticket), can we find many weak learners with very low extra costs (free tickets), where the combination of these free tickets can significantly outperform the dense equivalents?*

Note that it is not trivial to obtain the free tickets. To guarantee superior ensemble performance, three key desiderata the free tickets are expected to satisfy (1) *high diversity*: according to the ensemble theory (LeCun et al., 2015; Hansen & Salamon, 1990; Ovadia et al., 2019), higher diversity among ensemble members leads to higher predictive performance; (2) *high accessibility*: free tickets should be cheap to obtain so that the overall training cost does not compromise too much; and (3) *high expressibility*: the performance of each free ticket should be comparable with the dense model.

Figure 1: Illustration of $FreeTickets$. Sparse neural network training efficiently produces in one shot many diverse subnetworks with very low extra cost (free tickets). By combining all these free tickets, $FreeTickets$ outperforms the corresponding dense ensemble with only half of FLOPs required to train a single dense model.

In this paper, we instantiate the concept of $FreeTickets$ by proposing two DST-based efficient ensemble methods, which consummately satisfies the above-mentioned criteria. We make the following contributions:

- We introduce and conduct the concept of $FreeTickets$, by proposing two efficient ensemble methods with can produce in one shot many diverse yet accurate subnetworks – Dynamic Sparse Training Ensemble (DST Ensemble) and Efficient Dynamic Sparse Training Ensemble (EDST Ensemble).

- Our lightest method (EDST Ensemble) yields many free tickets in **one single run**, which is more efficient to train and inference than a **single dense model**, while approaching the performance of the naive **dense ensemble**.

- We analyze the diversity of the individual subnetworks generated by our methods and confirm the effectiveness of our methods on inducing model diversity.

- Our results suggest that besides the training/inference efficiency, sparse neural networks enjoy also other favourable properties which are absent in dense networks (robustness, out-of-distribution generalization, etc), opening the path for new research directions.

2 RELATED WORKS

2.1 ENSEMBLES

A large body of work have broadly studied ensembles for better performance (Breiman, 1996; Hansen & Salamon, 1990; Perrone & Cooper, 1992; Dietterich, 2000; Fort et al., 2019; Levin et al., 1990)

and uncertainty estimation (Lakshminarayanan et al., 2017; Ovadia et al., 2019; Gustafsson et al., 2019; Havasi et al., 2021) in deep learning. One major drawback of ensembles is the expensive computational and memory costs for both training and testing. To address this problem, various approaches have been proposed, including but not limited to Horizontal and vertical ensemble (Xie et al., 2013), TreeNet (Lee et al., 2015), Monte Carlo Dropout (Gal & Ghahramani, 2016), Snapshot (Huang et al., 2017), BatchEnsemble (Wen et al., 2020), hyper-batch ensembles (Wenzel et al., 2020), MIMO (Havasi et al., 2021), and Late Phase (Oswald et al., 2021). However, the training resources required by these methods are still at least the same as training a single dense model. In contrast to the existing efficient ensemble methods, our methods (EDST Ensemble) can match the performance of naive ensemble with only a fraction of the resources required by training a single dense network.

2.2 DYNAMIC SPARSE TRAINING

Dynamic Sparse Training (DST) is a class of methods that enables training sparse neural networks from scratch by optimizing the sparse connectivity together with the weight values during training. DST stems from Sparse Evolutionary Training (SET) (Mocanu et al., 2018), a sparse training algorithm that outperforms training a static sparse model from scratch (Mocanu et al., 2016; Evci et al., 2019). Weight reallocation was further proposed in Mostafa & Wang (2019); Dettmers & Zettlemoyer (2019); Liu et al. (2021a) to reallocate new weights across layers for better layer-wise sparsity. Further, Dettmers & Zettlemoyer (2019); Evci et al. (2020a) leverage the gradient information in the backward pass to guide the optimization of sparse connectivity and demonstrate substantial performance improvement. Some recent works (Jayakumar et al., 2020; Raihan & Aamodt, 2020; Liu et al., 2021b) demonstrate that a large range of exploration in the parameter space is important for dynamic sparse training. DST has also demonstrated its strength in feature detection (Atashgahi et al., 2020), lifelong learning (Sokar et al., 2021), federated learning (Zhu & Jin, 2019), and adversarial training (Özdenizci & Legenstein, 2021).

3 FREETICKETS

3.1 PRELIMINARY AND SETUPS

Dynamic Sparse Training. Let's consider an i.i.d. classification setting with data $\{(x_i, y_i)\}_{i=1}^N$, where x usually denotes input samples and y is the corresponding labels. For a network $f(\boldsymbol{x}; \boldsymbol{\theta})$ parameterized by $\boldsymbol{\theta}^l \in \mathbb{R}^{d_l}$ in each layer of $l \in \{1, \ldots, L\}$, we train $f(\boldsymbol{x}; \boldsymbol{\theta})$ to solve the following optimization problem: $\hat{\boldsymbol{\theta}} = \arg\min_{\boldsymbol{\theta}} \sum_{i=1}^N \mathcal{L}(f(x_i; \boldsymbol{\theta}), y_i)$.

Dynamic sparse training (DST) starts with a randomly-initialized sparse neural network $f(\boldsymbol{x}; \boldsymbol{\theta}_s)$, parameterized by a fraction of parameters $\boldsymbol{\theta}_s$. The sparsity level of the sparse model is pre-defined as $S = 1 - \frac{\|\boldsymbol{\theta}_s\|_0}{\|\boldsymbol{\theta}\|_0}$, where $\|\cdot\|_0$ is the ℓ_0-norm. The goal of DST is to yield a sparse network with the target sparsity S after training, while maintaining the overall computational and memory overheads close to training a static sparse model (fixed sparse connectivity).

During training, DST continuously minimizes the loss $\sum_{i=1}^N \mathcal{L}(f(x_i; \boldsymbol{\theta}_s), y_i)$, while periodically exploring the parameter space for better sparse connectivity with non-differentiable heuristics. A simple yet effective exploration heuristics is prune-and-grow, that is, pruning p percentage of the unimportant weights from $\boldsymbol{\theta}_s$, followed by regrowing the same number of new weights. By repeating this prune-and-grow cycle, DST continuously searches for better sparse connectivities while stick to a fixed parameter budget. Denote ΔT as the update interval, referring to the number of training iterations between two parameter exploration. Denote p as the exploration rate, referring to the ratio of the changed parameters to the total nonzero parameters. See Appendix A for a general pseudocode and full details of DST, where a literature review of DST is provided.

FreeTickets Ensemble. We propose the concept of $FreeTickets$ here. Let $\epsilon(f(\boldsymbol{x}; \boldsymbol{\theta}_s))$ be the evaluation metric of model $f(\boldsymbol{x}; \boldsymbol{\theta}_s)$ on the corresponding task. A free ticket is one of the sparse neural networks (subnetworks) generated during the dynamic sparse training procedure. These free tickets $\{\theta_s^1, \theta_s^2, \ldots \theta_s^M\}$, observed and collected, are further used to construct the $FreeTickets$ Ensemble.

The evaluation of $\epsilon(f(\boldsymbol{x}; \boldsymbol{\theta}_s^j))$ lead us to a weighted probability vector over all the neurons $a_k^{(L)}$, $\forall k \in [1, n^{(L)}]$ for each subnetwork in the last layer L, such that $\sum_k p(a_k^{(L)}) = 1$. Even if there are many ways how one can control the importance of each output probabilities, we simply average it. Thus each neuron in the ensemble output is $\frac{1}{M} \sum_{j=1}^M p(a_k^{j(L)})$.

To produce qualified free tickets, we introduce two DST-based ensemble methods, **DST Ensemble** and **EDST Ensemble**, which consummately satisfy the above-mentioned three key desiderata of ensembles: *(1) high diversity*, *(2) high accessibility*, and *(3) high expressibility*.

Compared with the existing efficient ensemble techniques (Huang et al., 2017; Wen et al., 2020), $FreeTickets$ induces diversity from the perspective that there exists many performant subnetworks with very different topologies within the full network (Liu et al., 2020). The efficiency of $FreeTickets$ comes from the fact that each subnetwork is *sparse from the beginning*, so that the memory and floating-point operations (FLOPs) required by $FreeTickets$ can be even fewer than training a single dense network. One closely related work is MIMO (Havasi et al., 2021) which also builds efficient ensemble based on subnetworks. However, MIMO uses a multi-input multi-output configuration to concurrently discover subnetworks that co-habit the dense network without explicit separation. The potential ensemble size and diversity of MIMO are limited by the capacity of the dense network. Instead, $FreeTickets$ directly trains subnetworks from scratch and thus benefits more from the increased ensemble size.

3.2 DST ENSEMBLE

Dynamic Sparse Training Ensemble (DST Ensemble) is presented in Algorithm 3, Appendix B. DST Ensemble takes advantage of the training efficiency from DST and independently trains M sparse networks with DST from scratch. By averaging the predictions of each sparse neural network, DST Ensemble can improve the predictive accuracy and uncertainty significantly.

The diversity of DST ensemble comes from the fact that each ensemble member is trained independently with fully random initializations, random stochastic gradient descent (SGD) noise, etc. Moreover, each DST run converges to different sparse connectivities, promoting even more diversity over the naive dense Ensemble. The efficiency of DST Ensemble comes from the fact that all the ensemble learners are sparse throughout training, so that the training costs are far fewer than training a dense ensemble learner.

The DST method we choose for DST Ensemble is The Rigged Lottery (RigL) (Evci et al., 2020a), which is the state-of-the-art DST method, containing three main steps: sparse initialization, model weight optimization, and parameter exploration.

Sparse Initialization. Each subnetwork is randomly initialized with the *Erdős-Rényi-Kernel* (ERK) (Mocanu et al., 2018; Evci et al., 2020a) distribution at sparsity of S. The sparsity level of layer l is scaled with $1 - \frac{n^{l-1}+n^l+w^l+h^l}{n^{l-1} \times n^l \times w^l \times h^l}$, where n^l refers to the number of neurons/channels of layer l; w^l and h^l are the width and the height of the convolutional kernel in layer l. *Erdős-Rényi-Kernel* allocates higher sparsities to the layers with more parameters than the layers with fewer parameters.

Model Weight Optimization. After initialization, the activated weights are optimized with the standard optimizer SGD with momentum (Sutskever et al., 2013; Polyak, 1964) and the non-activated weights are forced to zero.

Parameter Exploration. After every ΔT iterations of training, we perform parameter exploration once to optimize the sparse connectivity. More concretely, we first prune p-proportion of weights from $\boldsymbol{\theta}_s$ with the smallest magnitude:

$$\boldsymbol{\theta}_s' = \text{TopK}(|\boldsymbol{\theta}_s|, \ 1-p) \tag{1}$$

where $\text{TopK}(v, k)$ returns the weight tensor retaining the top k-proportion of elements from v. Immediately after pruning, we grow the same number of new weights back with the largest magnitude gradient:

$$\boldsymbol{\theta}_s = \boldsymbol{\theta}_s' + \text{TopK}(|\mathbf{g}_{i \notin \boldsymbol{\theta}_s'}|, \ p) \tag{2}$$

where $\mathbf{g}_{i \notin \boldsymbol{\theta}_s'}$ are the gradients of the zero weights. We follow the suggestions in Liu et al. (2021b) and choose $p = 0.5$ and large update interval (T = 1000 for CIFAR-10/100 and T = 4000 for ImageNet to encourage an almost full exploration of all network parameters.

Algorithm 1 EDST Ensemble

Require: network f_Θ, dataset $\{x_i, y_i\}_{i=1}^{N}$, ensemble number M, sparsity distribution: $\mathbb{S} = \{s^1, \ldots, s^L\}$, update interval ΔT, DST exploration rate p, large exploration rate q to escape local minima
 1: $f(\boldsymbol{x}; \boldsymbol{\theta}_s) \leftarrow$ sparsely initialize $f(\boldsymbol{x}; \boldsymbol{\theta})$ with $\mathbb{S}$
 2: # (1) Exploration Phase
 3: **for** each exploration phase step t_{ex} **do**
 4:    $f(x; \boldsymbol{\theta}_s) \leftarrow \mathrm{SGD}(f(\boldsymbol{x}; \boldsymbol{\theta}_s))$
 5:    **if** $(t \bmod \Delta T) = 0$ **then**
 6:       DST parameter exploration using Eq. 1 & 2 with p
 7:    **end if**
 8: **end for**
 9: # (2) Refinement Phase
10: $j = 0$
11: **repeat**
12:    **for** each refinement phase step t_{re} **do**
13:       $f(\boldsymbol{x}; \boldsymbol{\theta}_s^j) \leftarrow \mathrm{SGD}(f(\boldsymbol{x}; \boldsymbol{\theta}_s^j))$
14:       **if** $(t \bmod \Delta T) = 0$ **then**
15:          DST parameter exploration using Eq. 1 & 2 with p
16:       **end if**
17:    **end for**
18:    Save the sparse subnetwork $f(\boldsymbol{x}; \boldsymbol{\theta}_s^j)$
19:    # Escape the local minima by largely exploring parameters with q
20:    $f(\boldsymbol{x}; \boldsymbol{\theta}_s^j) \leftarrow f(\boldsymbol{x}; \boldsymbol{\theta}_s^j; q)$
      $j = j + 1$
21: **until** $j \geq M$

3.3 EDST ENSEMBLE

While efficient, the number of the forward passes (complete training phases) required by DST Ensemble increases linearly with the number of subnetworks, leading to extra devices and resource requirements. To further reduce the training resources and the number of forward passes, we propose Efficient Dynamic Sparse Training Ensemble (EDST Ensemble) to yield many diverse sparse neural networks in **a single forward pass**.

The challenge of producing many free tickets serially in one single run locates in how to escape the current local minima during the typical DST training. Here, we force the model to escape the current local minima by heavily changing a large fraction of the converged sparse model, which is like adding significant perturbations to the model topology. The overall training procedure of EDST Ensemble is summarized in Algorithm 1. The training process of EDST Ensemble includes two major phases: (1) one exploration phase; and (2) M refinement phases. A subnetwork (free ticket) is naturally yielded at the end of each refinement phase.

Exploration phase. We first train a sparse network with DST using a large learning rate of 0.1 for a time of t_{ex}. The goal of this exploration phase is to explore a large range of the parameter space for a potentially good sparse connectivity. Training with a large learning rate allows DST to validly search a larger range of the parameter space, as the newly activated weights receive large updates and become more competitive at the next pruning iteration.

Refinement phase. After the exploration phase, we equally split the rest of training time by M to collect M free tickets. At each refinement phase, the sparse model is trained with decayed learning rates 0.01 and 0.001 for a time of t_{re}. We save the converged model and force the model to escape the local minima by exploring heavily a large fraction of $q = 80\%$ connectivity. The next refinement phase is then continued with small learning rates 0.01 and 0.001. We repeat this process several times until the target number of free tickets is reached. The number of subnetworks M that we obtain at the end of training is given by $M = \frac{t_{\mathrm{total}} - t_{\mathrm{ex}}}{t_{\mathrm{re}}}$.

The purpose of the large parameter exploration in line 20 of Algorithm 1 is to promote diversity among free tickets. Therefore, the exploration rate q in line 20 is much larger than the p in line 6

& 15, which refers to the standard DST parameter exploration. Given the fixed training time t_{total}, one advantage of EDST Ensemble is that we can adjust the combination of t_{ex} and t_{re} to yield more diverse sparse ensemble learners for a better predictive and uncertainty performance.

Different from DST Ensemble, the diversity of EDST Ensemble comes from the different sparse subnetworks (sparse connectivities together with the model weights) the model converges during each refinement phase. The number of training FLOPs required by EDST Ensemble is significantly smaller than training an individual dense network, as DST is efficient and the exploration phase is only performed once for all ensemble learners.

4 EXPERIMENTS

In this section, we demonstrate the improved predictive accuracy, robustness, uncertainty estimation, and efficiency achieved by $FreeTickets$. We mainly follow the experimental setting of the state-of-the-art ensemble method, MIMO (Havasi et al., 2021), shown as follows.

Baselines. We compare our methods against the dense ensemble, and various state-of-the-art efficient ensemble methods, including MIMO (Havasi et al., 2021), Monte Carlo Dropout (Gal & Ghahramani, 2016), BatchEnsemble (Wen et al., 2020), TreeNet (Lee et al., 2015). To highlight the fact that the free tickets are non-trivial to obtain, we further implement two sparsity-related ensemble methods: Static Sparse Ensemble (naively ensemble M static sparse networks) and Lottery Ticket Rewinding Ensemble (LTR Ensemble) (ensemble M winning tickets[1] trained with the same mask but different random seeds). While Static Sparse Ensemble can be diverse and efficient, it does not satisfy high expressibility (Evci et al., 2019). On the other hand, LTR Ensemble suffers from low diversity and prohibitive costs. See Appendix C for the implementation and hyperparameter details.

Architecture and Dataset. We evaluate our methods mainly with Wide ResNet28-10 (Zagoruyko & Komodakis, 2016) on CIFAR-10/100 and ResNet-50 (He et al., 2016) on ImageNet.

Metrics. To measure the predictive accuracy, robustness, and efficiency, we follow the Uncertainty Baseline[2] and report the overall training FLOPs required to obtain the target number of subnetworks. See Appendix D for more details.

Table 1: Wide ResNet28-10/CIFAR10: we mark the best results of one-pass efficient ensemble in bold and the best results of multi-pass efficient ensemble in blue. Results with * are obtained from Havasi et al. (2021).

Methods	Acc (↑)	NLL (↓)	ECE (↓)	cAcc (↑)	cNLL (↓)	cECE (↓)	# Training FLOPs (↓)	# Forward passes (↓)
Single Dense Model*	96.0	0.159	0.023	76.1	1.050	0.153	3.6e17	1
Monte Carlo Dropout*	95.9	0.160	0.024	68.8	1.270	0.166	1.00×	1
MIMO (M = 3)*	**96.4**	0.123	0.010	76.6	0.927	0.112	1.00×	1
EDST Ensemble (M = 3) (S = 0.8) (Ours)	96.3	0.127	0.012	**77.9**	0.814	0.093	0.61×	1
EDST Ensemble (M = 7) (S = 0.9) (Ours)	96.1	**0.122**	**0.008**	77.2	**0.803**	**0.081**	**0.57×**	1
TreeNet (M = 3)*	95.9	0.158	0.018	75.6	0.969	0.137	1.52×	1.5
BatchEnsemble (M = 4)*	96.2	0.143	0.021	77.5	1.020	0.129	1.10×	4
LTR Ensemble (M = 3) (S = 0.8)	96.2	0.133	0.015	76.7	0.950	0.118	1.75×	4
Static Sparse Ensemble (M = 3) (S = 0.8)	96.0	0.133	0.014	76.2	0.920	0.098	1.01×	3
DST Ensemble (M = 3) (S = 0.8) (Ours)	96.3	0.122	0.010	78.8	0.766	0.075	1.01×	3
Dense Ensemble (M = 4)*	96.6	0.114	0.010	77.9	0.810	0.087	4.00×	4

Table 2: Wide ResNet28-10/CIFAR100: we mark the best results of one-pass efficient ensemble in bold and the best results of multi-pass efficient ensemble in blue. Results with * are obtained from Havasi et al. (2021).

Methods	Acc (↑)	NLL (↓)	ECE (↓)	cAcc (↑)	cNLL (↓)	cECE (↓)	# Training FLOPs (↓)	# Forward passes (↓)
Single Dense Model*	79.8	0.875	0.086	51.4	2.700	0.239	3.6e17	1
Monte Carlo Dropout*	79.6	0.830	0.050	42.6	2.900	0.202	1.00×	1
MIMO (M = 3)*	82.0	0.690	**0.022**	53.7	2.284	**0.129**	1.00×	1
EDST Ensemble (M = 3) (S = 0.8) (Ours)	82.2	0.672	0.034	**54.0**	**2.156**	0.137	0.61×	1
EDST Ensemble (M = 7) (S = 0.9) (Ours)	**82.6**	**0.653**	0.036	52.7	2.410	0.170	**0.57×**	1
TreeNet (M = 3)*	80.8	0.777	0.047	53.5	2.295	0.176	1.52×	1.5
BatchEnsemble (M = 4)*	81.5	0.740	0.056	54.1	2.490	0.191	1.10×	4
LTR Ensemble (M = 3) (S = 0.8)	82.2	0.703	0.045	53.2	2.345	0.180	1.75×	4
Static Sparse Ensemble (M = 3) (S = 0.8)	81.4	0.691	0.035	52.5	2.468	0.167	1.01×	3
DST Ensemble (M = 3) (S = 0.8) (Ours)	83.3	0.623	0.018	55.0	2.109	0.104	1.01×	3
Dense Ensemble (M = 4)*	82.7	0.666	0.021	54.1	2.270	0.138	4.00×	4

---

[1]We rewind the tickets to the weights at 5% epoch as used in Frankle et al. (2020); Chen et al. (2020a).
[2]https://github.com/google/uncertainty-baselines

Table 3: ResNet50/ImageNet: we mark the best results of one-pass efficient ensemble in bold and the best results of multi-pass efficient ensemble in blue. Results with * are obtained from Havasi et al. (2021).

Methods	Acc (↑)	NLL (↓)	ECE (↓)	cAcc (↑)	cNLL (↓)	cECE (↓)	aAcc (↑)	aNLL (↓)	aECE (↓)	Training FLOPs (↓)	# Forward passes (↓)
Single Dense Model*	76.1	0.943	0.039	40.5	3.200	0.105	0.7	8.09	0.43	4.8e18	1
MIMO (M = 2) (ρ = 0.6)*	77.5	**0.887**	**0.037**	**43.3**	3.030	0.106	1.4	7.76	0.43	1.00×	1
EDST Ensemble (M = 2) (S = 0.8) (Ours)	76.9	0.974	0.060	41.3	3.074	**0.055**	3.7	4.90	0.37	**0.48×**	1
EDST Ensemble (M = 4) (S = 0.8) (Ours)	**77.7**	0.935	0.064	42.6	**2.987**	0.058	**4.0**	**4.74**	**0.35**	0.87×	1
TreeNet (M = 2)*	78.1	0.852	0.017	42.4	3.052	0.073	–	–	–	1.33×	1.5
BatchEnsemble (M = 4)*	76.7	0.944	0.050	41.8	3.180	0.110	–	–	–	1.10×	4
DST Ensemble (M = 2) (S = 0.8) (Ours)	78.3	0.914	0.060	43.7	2.910	0.057	4.8	4.69	0.35	1.12×	2
Dense Ensemble (M = 4)*	77.5	0.877	0.031	42.1	2.990	0.051	–	–	–	4.00×	4

(a) Dense Ensemble   (b) DST Ensemble (S=0.8)   (c) EDST Ensemble (S=0.8)   (d) EDST Ensemble (S=0.9)

Figure 2: Prediction disagreement between ensemble learners with Wide ResNet28-10 on CIFAR-100. Each subfigure shows the fraction of labels on which different ensemble learners disagree.

Results. The metrics on the CIFAR-10/100 and ImageNet are reported in Table 1, Table 2, and Table 3, respectively. For a fair comparison, we choose M = 3 for our methods at sparsity S = 0.8, which is the same as the one used in MIMO.

With multiple forward passes, DST Ensemble consistently outperforms other efficient ensemble methods, even the dense ensemble on accuracy, robustness and uncertainty performance, while using only 1/4 training FLOPs compared with the latter.

When the number of forward passes is limited to 1, EDST Ensemble consistently outperforms the single dense model by a large margin, especially in accuracy, with only 61% training FLOPs. Moreover, we observe that the performance of EDST Ensemble can further be improved by increasing the sparsity level. For instance, with a large sparsity level $S = 0.9$, EDST Ensemble can collect 7 ensemble learners, more than twice as many models compared with $S = 0.8$. Combining the prediction of these ensemble learners boosts the performance of EDST ensemble to the multiple forward pass ensembles with only 57% training FLOPs, beyond the reach of any efficient ensemble methods. Overall, EDST Ensemble can match the robustness of state-of-the-art MIMO on NNL and ECE, with about half of the computational cost.

To further verify the effectiveness of dynamic sparsity for promoting diversity, we also report the performance of two sparse ensemble methods that do not involve any dynamic sparsity – Static Sparse Ensemble and LTR Ensemble. Both of them yield worse accuracy and robustness than our methods, highlighting the superiority of $FreeTickets$ for Ensembles over the Lottery Tickets and static sparse networks. We argue that Lottery Tickets Hypothesis is not suitable for $FreeTickets$ since (1) it starts from a dense network, with the costly iterative train-prune-retrain process. Hence it is more expensive than training a dense network, in contrary to our pursuit of efficient training (our method sticks to training sparse networks end-to-end); (2) The series of sparse subnetworks yielded by iterative pruning is not diverse enough, since the latter sparse masks are always pruned from and thus nested in earlier masks.

5 FREE TICKETS ANALYSIS

5.1 DIVERSITY ANALYSIS

According to the ensembling theory (LeCun et al., 2015; Hansen & Salamon, 1990; Ovadia et al., 2019), more diversity among ensemble learners leads to better predictive accuracy and robustness. We follow the methods used in Fort et al. (2019) and analyze the diversity of the subnetworks collected by our methods in the function space.

Concretely, we measure the pairwise diversity of the subnetworks collected by our methods on the test data. The diversity is measured by:

$$\mathcal{D}_d = \mathbb{E}\left[d\left(\mathcal{P}_1(y|x_1, \cdots, x_N), \mathcal{P}_2(y|x_1, \cdots, x_N)\right)\right] \tag{3}$$

where $d(\cdot, \cdot)$ is a metric between predictive distributions and (x, y) are the test set. We use two metrics (1) Prediction Disagreement, and (2) Kullback–Leibler divergence.

Prediction Disagreement. Prediction Disagreement is defined as the fraction of test data the the prediction of models disagree on: $d_{\mathrm{dis}}(\mathcal{P}_1, \mathcal{P}_2) = \frac{1}{N} \sum_{i=1}^{N} (\arg\max_{\hat{y}_i} \mathcal{P}_1(\hat{y}_i) \neq \arg\max_{\hat{y}_i} \mathcal{P}_2(\hat{y}_i))$. We compare the prediction disagreement among the naive dense ensemble, DST Ensemble with sparsity $S = 0.8$, EDST Ensemble with sparsity $S = 0.8$ and $S = 0.9$. The comparison results on CIFAR-100 are shown in Figure 2 (see Appendix E for CIFAR-10). We find that the subnetworks discovered by DST Ensemble are even more diverse than the ones discovered by the traditional dense ensemble, confirming our hypothesis that dynamic sparsity can provide extra diversity in addition to random initializations. While the average functional diversity of the subnetworks discovered by EDST Ensemble is a bit lower compared with DST Ensemble, the diversity is still notable.

Kullback–Leibler Divergence. Kullback–Leibler Divergence (KL-divergence) (Kullback & Leibler, 1951) is defined as: $d_{\mathrm{KL}}(\mathcal{P}_1, \mathcal{P}_2) = \mathbb{E}_{\mathcal{P}_1} [\log \mathcal{P}_1(y) - \log \mathcal{P}_2(y)]$, a metric that is widely used to describe the diversity of two ensemble learners (Fort et al., 2019; Havasi et al., 2021). We measure the KL-divergence between the subnetworks collected by our methods and compare them with other efficient ensemble baselines with Wide ResNet28-10 on CIFAR-10 in Table 4. The results of TreeNet, BatchEnsemble, MIMO, and Dense Ensemble are obtained from Havasi et al. (2021). Again, the individual members learned by DST Ensemble are more diverse than the independently trained dense networks. Even though EDST Ensemble discovers M subnetworks in a single forward pass, its diversity is very close to the diversity of the dense ensemble, much larger than the other efficient ensemble methods e.g., TreeNet and BatchEnsemble.

Table 4: Prediction disagreement and Kullback–Leibler divergence of ensemble learners ($\mathcal{D}_d$) in different efficient ensemble methods with Wide ResNet28-10 on CIFAR-10 (M = 3, S = 0.8).

	d_{dis} (↑)	d_{KL} (↑)
TreeNet	0.010	0.010
BatchEnsemble	0.014	0.020
LTR Ensemble	0.026	0.057
EDST Ensemble (Ours)	0.031	0.073
MIMO	0.032	0.086
DST Ensemble (Ours)	**0.035**	**0.095**
Dense Ensemble	0.032	0.086

5.2 TRAINING TRAJECTORY

In this section, we use t-SNE (Van der Maaten & Hinton, 2008) to visualize the diversity of sparse networks discovered by our methods in function space. We save the checkpoints along the training trajectory of each subnetwork and take the softmax output on the test data of each checkpoint to represent the subnetwork's prediction. t-SNE maps the prediction to the 2D space. From Figure 3 we can observe that subnetworks of DST Ensemble converge to completely different local optima, and the local optima converged by EDST Ensemble are relatively closer to each other. Interestingly, even the last two subnetworks of EDST Ensemble (blue and green lines) start from similar regions, they end up in two different optima.

(a) DST on CIFAR-10   (b) EDST on CIFAR-10   (c) DST on CIFAR-100   (d) EDST on CIFAR-100

Figure 3: t-SNE projection of training trajectories of ensemble learners discovered by DST Ensemble and EDST Ensemble with Wide ResNet28-10 on CIFAR-10/100. The sparsity level is S = 0.8.

5.3 ABLATION STUDY OF PARAMETER EXPLORATION

We conduct an ablation study to analyze the effect of parameter exploration on promoting the model diversity. For comparison, we train the same number of subnetworks without any parameter exploration. As shown in Table 5, without parameter exploration, the diversity of the subnetworks consistently reduces, highlighting the effectiveness of parameter exploration on inducing diversity.

Table 5: Function diversity of DST-based Ensemble with and without parameter exploration (M = 3, S = 0.8).

	CIFAR10		CIFAR100	
	d_{dis} (↑)	d_{KL} (↑)	d_{dis} (↑)	d_{KL} (↑)
EDST Ensemble (w/o Parameter Exploration)	0.017	0.042	0.081	0.148
EDST Ensemble	**0.031**	**0.073**	**0.126**	**0.237**
DST Ensemble (w/o Parameter Exploration)	0.020	0.051	0.115	0.205
DST Ensemble	**0.035**	**0.095**	**0.166**	**0.411**
Dense Ensemble	0.032	0.086	0.145	0.338

5.4 EFFECT OF SPARSITY

We further study the effect of subnetworks sparsity on the ensemble performance and diversity, shown in Figure 4. While the individual networks learned by DST Ensemble and EDST Ensemble achieve similar test accuracy, the higher diversity of DST Ensemble boosts its ensemble performance over the EDST Ensemble significantly, highlighting the importance of diversity for ensemble. What's more, it is clear to see that the pattern of the ensemble accuracy is highly correlated with the accuracy of the individual subnetwork. This observation confirms our hypothesis in the introduction, that is, high expressibility is also a crucial desideratum for free tickets to guarantee superior ensemble performance.

| (a) DST on CIFAR-10 | (b) EDST on CIFAR-10 | (c) DST on CIFAR-100 | (d) EDST on CIFAR-100 |

Figure 4: Performance and KL divergence of the subnetworks and the ensemble of subnetworks as sparsity varies. The KL divergence is scaled to the test accuracy for better visualization.

5.5 EFFECT OF ENSEMBLE SIZE

In this section, we analyze the effect of the ensemble size (the number of ensemble learners) on our methods. For EDST Ensemble, we fix the total training time and vary the total number of ensemble learners M. The larger ensemble size M leads to shorter training time of each ensemble learner. For DST Ensemble, we simply train a different number of individual sparse models from scratch and report the ensemble performance.

The results are shown in Figure 5. "Individual Tickets" refers to the individual sparse subnetwork learned by DST and EDST. The prediction accuracy of DST Ensemble keeps increasing as the ensemble size increases, demonstrating the benefits of ensemble. As expected, the predictive accuracy of individual EDST subnetworks decreases as the ensemble size M increases likely due to the reduced training time of each subnetwork. Nevertheless, the ensemble performance of EDST is still quite robust to the ensemble size. Specifically, despite the poor individual performance with $M = 7$, the ensemble prediction is still higher than a single dense model. This behavior confirms our hypothesis mentioned

| (a) DST Ensemble | (b) EDST Ensemble |

Figure 5: Performance of the subnetworks and the ensemble of subnetworks as the ensemble size M varies (Wide ResNet28-10 on CIFAR-10).

before, i.e., multiple free tickets work better than one high-quality winning ticket or even a dense network.

5.6 EXPERIMENTS WITH OOD AND ADVERSARIAL ROBUSTNESS

We further test the performance of $FreeTickets$ on out-of-distribution (OOD) detection and adversarial robustness, reporting the results in Appendix F and Appendix G, respectively. Again, the results show that our proposed ensemble methods also bring performance gains to these two tasks.

6 CONCLUSION

We introduce $FreeTickets$, an efficient way to boost the performance of sparse training over the single dense network, even the dense ensemble, while using only half of the training FLOPs of a single dense model. $FreeTickets$ is built as a combination of all free tickets extracted during sparse training and achieves a co-win in terms of accuracy, robustness, uncertainty estimation, as well as training/inference efficiency. Our results provide insights into the strength of sparse neural networks, beyond the training/inference efficiency. We believe that sparse neural networks have great potential to enjoy many favorable properties that are absent in dense networks. Sparse neural network ensembles can serve as a starting point for new research areas.

7 REPRODUCIBILITY

Our algorithm is implemented based on the work of sparse momentum (Dettmers & Zettlemoyer, 2019) with the corresponding GitHub repository `https://github.com/TimDettmers/sparse_learning`. The training configurations and hyperparameters are shared in Appendix C. The metrics used to enable comparisons among different methods are given in Appendix D.

REFERENCES

Zahra Atashgahi, Ghada Sokar, Tim van der Lee, Elena Mocanu, Decebal Constantin Mocanu, Raymond Veldhuis, and Mykola Pechenizkiy. Quick and robust feature selection: the strength of energy-efficient sparse training for autoencoders. *arXiv preprint arXiv:2012.00560*, 2020.

Maximilian Augustin, Alexander Meinke, and Matthias Hein. Adversarial robustness on in-and out-distribution improves explainability. In *European Conference on Computer Vision*, pp. 228–245. Springer, 2020.

Guillaume Bellec, David Kappel, Wolfgang Maass, and Robert Legenstein. Deep rewiring: Training very sparse deep networks. In *International Conference on Learning Representations*, 2018. URL `https://openreview.net/forum?id=BJ_wN01C-`.

Leo Breiman. Bagging predictors. *Machine learning*, 24(2):123–140, 1996.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel Ziegler, Jeffrey Wu, Clemens Winter, Chris Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 1877–1901. Curran Associates, Inc., 2020. URL `https://proceedings.neurips.cc/paper/2020/file/1457c0d6bfcb4967418bfb8ac142f64a-Paper.pdf`.

Tianlong Chen, Jonathan Frankle, Shiyu Chang, Sijia Liu, Yang Zhang, Michael Carbin, and Zhangyang Wang. The lottery tickets hypothesis for supervised and self-supervised pre-training in computer vision models. *arXiv preprint arXiv:2012.06908*, 2020a.

Tianlong Chen, Jonathan Frankle, Shiyu Chang, Sijia Liu, Yang Zhang, Zhangyang Wang, and Michael Carbin. The lottery ticket hypothesis for pre-trained bert networks. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 15834–15846. Curran Associates, Inc., 2020b. URL `https://proceedings.neurips.cc/paper/2020/file/b6af2c9703f203a2794be03d443af2e3-Paper.pdf`.

Tianlong Chen, Yu Cheng, Zhe Gan, Lu Yuan, Lei Zhang, and Zhangyang Wang. Chasing sparsity in vision transformers: An end-to-end exploration. *arXiv preprint arXiv:2106.04533*, 2021.

Tim Dettmers and Luke Zettlemoyer. Sparse networks from scratch: Faster training without losing performance. *arXiv preprint arXiv:1907.04840*, 2019.

Anastasia Dietrich, Frithjof Gressmann, Douglas Orr, Ivan Chelombiev, Daniel Justus, and Carlo Luschi. Towards structured dynamic sparse pre-training of bert, 2021.

Thomas G. Dietterich. Ensemble methods in machine learning. In *Multiple Classifier Systems*, 2000.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations*, 2021. URL `https://openreview.net/forum?id=YicbFdNTTy`.

Paul Erdős and Alfréd Rényi. On random graphs i. *Publicationes Mathematicae (Debrecen)*, 6:290–297, 1959.

Utku Evci, Fabian Pedregosa, Aidan Gomez, and Erich Elsen. The difficulty of training sparse neural networks. *arXiv preprint arXiv:1906.10732*, 2019.

Utku Evci, Trevor Gale, Jacob Menick, Pablo Samuel Castro, and Erich Elsen. Rigging the lottery: Making all tickets winners. In *International Conference on Machine Learning*, pp. 2943–2952. PMLR, 2020a.

Utku Evci, Yani A Ioannou, Cem Keskin, and Yann Dauphin. Gradient flow in sparse neural networks and how lottery tickets win. *arXiv preprint arXiv:2010.03533*, 2020b.

Stanislav Fort, Huiyi Hu, and Balaji Lakshminarayanan. Deep ensembles: A loss landscape perspective. *arXiv preprint arXiv:1912.02757*, 2019.

Jonathan Frankle and Michael Carbin. The lottery ticket hypothesis: Finding sparse, trainable neural networks. In *International Conference on Learning Representations*, 2018.

Jonathan Frankle, Gintare Karolina Dziugaite, Daniel Roy, and Michael Carbin. Linear mode connectivity and the lottery ticket hypothesis. In *International Conference on Machine Learning*, pp. 3259–3269. PMLR, 2020.

Yarin Gal and Zoubin Ghahramani. Dropout as a bayesian approximation: Representing model uncertainty in deep learning. In *international conference on machine learning*, pp. 1050–1059. PMLR, 2016.

Trevor Gale, Erich Elsen, and Sara Hooker. The state of sparsity in deep neural networks. *arXiv preprint arXiv:1902.09574*, 2019.

Eva García-Martín, Crefeda Faviola Rodrigues, Graham Riley, and Håkan Grahn. Estimation of energy consumption in machine learning. *Journal of Parallel and Distributed Computing*, 134: 75–88, 2019.

Fredrik K. Gustafsson, Martin Danelljan, and Thomas B. Schön. Evaluating scalable Bayesian deep learning methods for robust computer vision. *ArXiv*, abs/1906.01620, 2019.

Lars Kai Hansen and Peter Salamon. Neural network ensembles. *IEEE transactions on pattern analysis and machine intelligence*, 12(10):993–1001, 1990.

Marton Havasi, Rodolphe Jenatton, Stanislav Fort, Jeremiah Zhe Liu, Jasper Snoek, Balaji Lakshminarayanan, Andrew Mingbo Dai, and Dustin Tran. Training independent subnetworks for robust prediction. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=OGg9XnKxFAH.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Matthias Hein, Maksym Andriushchenko, and Julian Bitterwolf. Why relu networks yield high-confidence predictions far away from the training data and how to mitigate the problem. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 41–50, 2019.

Dan Hendrycks and Thomas Dietterich. Benchmarking neural network robustness to common corruptions and perturbations. *arXiv preprint arXiv:1903.12261*, 2019.

Dan Hendrycks, Kevin Zhao, Steven Basart, Jacob Steinhardt, and Dawn Song. Natural adversarial examples. *arXiv preprint arXiv:1907.07174*, 2019.

Torsten Hoefler, Dan Alistarh, Tal Ben-Nun, Nikoli Dryden, and Alexandra Peste. Sparsity in deep learning: Pruning and growth for efficient inference and training in neural networks. *arXiv preprint arXiv:2102.00554*, 2021.

Gao Huang, Yixuan Li, Geoff Pleiss, Zhuang Liu, John E Hopcroft, and Kilian Q Weinberger. Snapshot ensembles: Train 1, get m for free. *arXiv preprint arXiv:1704.00109*, 2017.

Siddhant Jayakumar, Razvan Pascanu, Jack Rae, Simon Osindero, and Erich Elsen. Top-kast: Top-k always sparse training. *Advances in Neural Information Processing Systems*, 33, 2020.

Nal Kalchbrenner, Erich Elsen, Karen Simonyan, Seb Noury, Norman Casagrande, Edward Lockhart, Florian Stimberg, Aaron Oord, Sander Dieleman, and Koray Kavukcuoglu. Efficient neural audio synthesis. In *International Conference on Machine Learning*, pp. 2410–2419. PMLR, 2018.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

A. Krizhevsky and G. Hinton. Learning multiple layers of features from tiny images. *Master's thesis, Department of Computer Science, University of Toronto*, 2009.

Solomon Kullback and Richard A Leibler. On information and sufficiency. *The annals of mathematical statistics*, 22(1):79–86, 1951.

Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. In *NIPS*, 2017.

Yann LeCun, Yoshua Bengio, and Geoffrey Hinton. Deep learning. *Nature*, 521(7553):436–444, 2015.

Namhoon Lee, Thalaiyasingam Ajanthan, and Philip Torr. Snip: Single-shot network pruning based on connection sensitivity. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=B1VZqjAcYX.

Namhoon Lee, Thalaiyasingam Ajanthan, Stephen Gould, and Philip H. S. Torr. A signal propagation perspective for pruning neural networks at initialization. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=HJeTo2VFwH.

Stefan Lee, Senthil Purushwalkam, Michael Cogswell, David Crandall, and Dhruv Batra. Why m heads are better than one: Training a diverse ensemble of deep networks. *arXiv preprint arXiv:1511.06314*, 2015.

Esther Levin, Naftali Tishby, and Sara A Solla. A statistical approach to learning and generalization in layered neural networks. *Proceedings of the IEEE*, 78(10):1568–1574, 1990.

Shiwei Liu, Tim Van der Lee, Anil Yaman, Zahra Atashgahi, Davide Ferraro, Ghada Sokar, Mykola Pechenizkiy, and Decebal Constantin Mocanu. Topological insights into sparse neural networks. In *ECMLPKDD*, 2020.

Shiwei Liu, Decebal Constantin Mocanu, Yulong Pei, and Mykola Pechenizkiy. Selfish sparse rnn training. In *Proceedings of the 39th International Conference on Machine Learning*, pp. 6893–6904. PMLR, 2021a.

Shiwei Liu, Lu Yin, Decebal Constantin Mocanu, and Mykola Pechenizkiy. Do we actually need dense over-parameterization? in-time over-parameterization in sparse training. In *Proceedings of the 39th International Conference on Machine Learning*, pp. 6989–7000. PMLR, 2021b.

Alexander Meinke and Matthias Hein. Towards neural networks that provably know when they don't know. *arXiv preprint arXiv:1909.12180*, 2019.

Decebal Constantin Mocanu, Elena Mocanu, Phuong H Nguyen, Madeleine Gibescu, and Antonio Liotta. A topological insight into restricted boltzmann machines. *Machine Learning*, 104(2-3): 243–270, 2016.

Decebal Constantin Mocanu, Elena Mocanu, Peter Stone, Phuong H Nguyen, Madeleine Gibescu, and Antonio Liotta. Scalable training of artificial neural networks with adaptive sparse connectivity inspired by network science. *Nature Communications*, 9(1):2383, 2018.

Decebal Constantin Mocanu, Elena Mocanu, Tiago Pinto, Selima Curci, Phuong H Nguyen, Madeleine Gibescu, Damien Ernst, and Zita A Vale. Sparse training theory for scalable and efficient agents. *arXiv preprint arXiv:2103.01636*, 2021.

Hesham Mostafa and Xin Wang. Parameter efficient training of deep convolutional neural networks by dynamic sparse reparameterization. In *International Conference on Machine Learning*, 2019.

Yuval Netzer, Tao Wang, Adam Coates, Alessandro Bissacco, Bo Wu, and Andrew Y. Ng. Reading digits in natural images with unsupervised feature learning. In *NIPS Workshop on Deep Learning and Unsupervised Feature Learning 2011*, 2011. URL `http://ufldl.stanford.edu/housenumbers/nips2011_housenumbers.pdf`.

Johannes Von Oswald, Seijin Kobayashi, Joao Sacramento, Alexander Meulemans, Christian Henning, and Benjamin F Grewe. Neural networks with late-phase weights. In *International Conference on Learning Representations*, 2021. URL `https://openreview.net/forum?id=C0qJUx5dxFb`.

Yaniv Ovadia, Emily Fertig, Jie Ren, Zachary Nado, David Sculley, Sebastian Nowozin, Joshua V Dillon, Balaji Lakshminarayanan, and Jasper Snoek. Can you trust your model's uncertainty? evaluating predictive uncertainty under dataset shift. *arXiv preprint arXiv:1906.02530*, 2019.

Ozan Özdenizci and Robert Legenstein. Training adversarially robust sparse networks via bayesian connectivity sampling. In *International Conference on Machine Learning*, pp. 8314–8324. PMLR, 2021.

Michael P Perrone and Leon N Cooper. When networks disagree: Ensemble methods for hybrid neural networks. Technical report, BROWN UNIV PROVIDENCE RI INST FOR BRAIN AND NEURAL SYSTEMS, 1992.

Boris T Polyak. Some methods of speeding up the convergence of iteration methods. *Ussr computational mathematics and mathematical physics*, 4(5):1–17, 1964.

Md Aamir Raihan and Tor M Aamodt. Sparse weight activation training. *arXiv preprint arXiv:2001.01969*, 2020.

Alex Renda, Jonathan Frankle, and Michael Carbin. Comparing rewinding and fine-tuning in neural network pruning. In *8th International Conference on Learning Representations*, 2020.

Herbert Robbins and Sutton Monro. A stochastic approximation method. *The annals of mathematical statistics*, pp. 400–407, 1951.

Roy Schwartz, Jesse Dodge, Noah A Smith, and Oren Etzioni. Green ai. *arXiv preprint arXiv:1907.10597*, 2019.

Ghada Sokar, Decebal Constantin Mocanu, and Mykola Pechenizkiy. Spacenet: Make free space for continual learning. *Neurocomputing*, 439:1–11, 2021.

Thilo Strauss, Markus Hanselmann, Andrej Junginger, and Holger Ulmer. Ensemble methods as a defense to adversarial perturbations against deep neural networks. *arXiv preprint arXiv:1709.03423*, 2017.

Emma Strubell, Ananya Ganesh, and Andrew McCallum. Energy and policy considerations for deep learning in nlp. *arXiv preprint arXiv:1906.02243*, 2019.

Ilya Sutskever, James Martens, George Dahl, and Geoffrey Hinton. On the importance of initialization and momentum in deep learning. In *International conference on machine learning*, pp. 1139–1147. PMLR, 2013.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. *arXiv preprint arXiv:1312.6199*, 2013.

Hidenori Tanaka, Daniel Kunin, Daniel LK Yamins, and Surya Ganguli. Pruning neural networks without any data by iteratively conserving synaptic flow. In *Advances in Neural Information Processing Systems 33 pre-proceedings*, 2020.

Kale-ab Tessera, Sara Hooker, and Benjamin Rosman. Keep the gradients flowing: Using gradient flow to study sparse network optimization. *arXiv preprint arXiv:2102.01670*, 2021.

Hugo Touvron, Andrea Vedaldi, Matthijs Douze, and Hervé Jégou. Fixing the train-test resolution discrepancy: Fixefficientnet. *arXiv preprint arXiv:2003.08237*, 2020.

Hugo Touvron, Matthieu Cord, Matthijs Douze, Francisco Massa, Alexandre Sablayrolles, and Hervé Jégou. Training data-efficient image transformers & distillation through attention. In *International Conference on Machine Learning*, pp. 10347–10357. PMLR, 2021.

Laurens Van der Maaten and Geoffrey Hinton. Visualizing data using t-sne. *Journal of machine learning research*, 9(11), 2008.

Chaoqi Wang, Guodong Zhang, and Roger Grosse. Picking winning tickets before training by preserving gradient flow. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=SkgsACVKPH.

Yeming Wen, Dustin Tran, and Jimmy Ba. Batchensemble: an alternative approach to efficient ensemble and lifelong learning. *arXiv preprint arXiv:2002.06715*, 2020.

Florian Wenzel, Jasper Snoek, Dustin Tran, and Rodolphe Jenatton. Hyperparameter ensembles for robustness and uncertainty quantification. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 6514–6527. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper/2020/file/481fbfa59da2581098e841b7afc122f1-Paper.pdf.

Jingjing Xie, Bing Xu, and Chuang Zhang. Horizontal and vertical ensemble with deep representation for classification. *CoRR*, abs/1306.2759, 2013.

Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. In Edwin R. Hancock Richard C. Wilson and William A. P. Smith (eds.), *Proceedings of the British Machine Vision Conference (BMVC)*, pp. 87.1–87.12. BMVA Press, September 2016. ISBN 1-901725-59-6. doi: 10.5244/C. 30.87. URL https://dx.doi.org/10.5244/C.30.87.

Hangyu Zhu and Yaochu Jin. Multi-objective evolutionary federated learning. *IEEE transactions on neural networks and learning systems*, 31(4):1310–1322, 2019.

Michael Zhu and Suyog Gupta. To prune, or not to prune: exploring the efficacy of pruning for model compression. *arXiv preprint arXiv:1710.01878*, 2017.

A DYNAMIC SPARSE TRAINING

In this Appendix, we describe the full details of dynamic sparse training. See the survey of Mocanu et al. (2021) and (Hoefler et al., 2021) for more details.

A.1 ALGORITHM

Dynamic Sparse Training (DST) (Mocanu et al., 2018) is a class of methods that enable the end-to-end training of sparse neural networks. DST starts from a sparse network and simultaneously optimizes the sparse connectivity and model weights during training. Without loss of generality, we provide the general pseudocode of DST that can cover most of the existing DST methods in Algorithm 2.

While there is an upsurge in increasingly efficient ways for sparse training (Bellec et al., 2018; Mostafa & Wang, 2019; Dettmers & Zettlemoyer, 2019; Evci et al., 2020a; Liu et al., 2021a; Jayakumar et al., 2020; Liu et al., 2021b; Dietrich et al., 2021; Chen et al., 2021), most of DST methods contain three key components: sparse initialization, model weight optimization, and parameter exploration. We explain them below.

Algorithm 2 Dynamic Sparse Training

Require: Network f_Θ, dataset $\{x_i, y_i\}_{i=1}^N$, Layer-wise sparsity ratio: $\mathbb{S} = \{s^1, \ldots, s^L\}$, Update Interval ΔT, Exploration Rate p
1:   # Sparse Initialization
2:   $f(\boldsymbol{x}; \boldsymbol{\theta}_s) \leftarrow f(\boldsymbol{x}; \boldsymbol{\theta}; \mathbb{S})$
3:   **for** each training step t **do**
4:     # Model Weight Optimization
5:     $f(\boldsymbol{x}; \boldsymbol{\theta}_s) \leftarrow \text{SGD}(f(\boldsymbol{x}; \boldsymbol{\theta}_s))$
6:     **if** $(t \bmod \Delta T) = 0$ **then**
7:       # Parameter Exploration
8:       Pruning p percentage of parameters using Eq. 1
9:       Growing p percentage of parameters using Eq. 2
10:      Update exploration rate p
11:    **end if**
12: **end for**

A.1.1 SPARSE INITIALIZATION

Layer-wise Sparsity Ratio. Layer-wise sparsity ratio plays an important role for sparse training. Mocanu et al. (2018) first introduced *Erdős-Rényi* (ER) (Erdős & Rényi, 1959) from graph theory to the field of neural networks, achieving better performance than the uniform sparsity ratio. Evci et al. (2020a) further extended ER to CNN and brings significant gains to sparse CNN training with the *Erdős-Rényi-Kernel* (ERK) ratio. Specifically, the sparsity level of layer l is scaled with $1 - \frac{n^{l-1} + n^l + w^l + h^l}{n^{l-1} \times n^l \times w^l \times h^l}$, where n^l refers to the number of neurons/channels of layer l; w^l and h^l are the width and the height of layer l. Works with weight redistribution (Mostafa & Wang, 2019; Dettmers & Zettlemoyer, 2019; Liu et al., 2021a) starts with the uniform layer-wise ratio and dynamically change the layer-wise ratio according to heuristic criteria, ending up with non-uniform layer-wise ratios.

Weight Initialization. Weight initialization also affects the performance of sparse training. Unlike the dense network, sparse networks contain a partial of weights to be zero, breaking the appealing property of dense initialization such as dynamical isometry (Lee et al., 2020), gradient flow (Evci et al., 2020b; Tessera et al., 2021), etc.

A.1.2 MODEL WEIGHT OPTIMIZATION

After initializing the sparse model, we need to optimize the model weights to minimize the loss function. In general, dynamic sparse training is compatible with the most widely used optimizers, e.g., minibatch stochastic gradient descent (SGD) (Robbins & Monro, 1951), minibatch stochastic

gradient descent with momentum (Sutskever et al., 2013; Polyak, 1964), and Adam (Kingma & Ba, 2014).

However, extra attention needs to pay to average-based optimizers, such as Averaged Stochastic Gradient Descent (ASGD), which is widely used in the language modeling tasks with RNNs and LSTMs. Liu et al. (2021a) points out that ASGD seriously destroys the sparse connectivity optimization since the average operation brings the newly-grown weights immediately to zero, leading to an over-pruning situation. Moreover, Tessera et al. (2021) shows that optimizers that use an exponentially weighted moving average (EWMA) are sensitive to high gradient flow.

A.1.3 PARAMETER EXPLORATION

Dynamic sparse training outperforms static sparse training mainly due to the parameter exploration (Liu et al., 2021b). One simple yet effective heuristic used here is prune-and-grow. Removing p percentage of the existing weights and regrowing the same number of new weights allows DST gradually optimizing the sparse connectivity in a heuristic way.

Weight Prune: Although there exists various pruning criteria in pruning literature, the most common way for DST is the simple magnitude pruning. We also tried other criteria for pruning at initialization e.g., SNIP (Lee et al., 2019), GraSP (Wang et al., 2020), SynFlow (Tanaka et al., 2020). All of them fall short of the accuracy achieved by magnitude pruning.

Weight Grow: The most common ways to grow new weights are random-based growth (proposed in SET (Mocanu et al., 2018)) and gradient-based growth (proposed in RigL (Evci et al., 2020a) and SNFS (Dettmers & Zettlemoyer, 2019)). Random-based growth ensures purely sparse forward pass and backward pass, while it very likely needs more steps to find the important connectivity, especially for the very extreme sparsities. Gradient-based growth detects the weights that reduce the current loss fastest, whereas it involves the dense gradient calculation and likely to cause a collapse of the explored parameter space (Liu et al., 2021a;b; Dietrich et al., 2021).

It is worth noting that the choice of when-to-explore is also of importance for DST. The number of training iterations between two parameter exploration is controlled by update interval ΔT. Since the newly-grown weights are initialized to zero, large ΔT is necessary to guarantee that the new weights receive enough weight updates to survive at the next pruning iteration (Liu et al., 2021b).

B   PSEUDOCODE OF DST ENSEMBLE

Algorithm 3 DST Ensemble

Require: network f_Θ, dataset $\{x_i, y_i\}_{i=1}^N$, ensemble number M, sparsity distribution: $\mathbb{S} = \{s^1, \ldots, s^L\}$, update interval ΔT, DST exploration rate p

1: $j = 0$
2: **repeat**
3:      # Sparse Initialization
4:      $f(\boldsymbol{x}; \boldsymbol{\theta}_s^j) \leftarrow f(\boldsymbol{x}; \boldsymbol{\theta}^j; \mathbb{S})$
5:      **for** each training step t **do**
6:          # Model Weight Optimization
7:          $f(\boldsymbol{x}; \boldsymbol{\theta}_s^j) \leftarrow \text{SGD}(f(\boldsymbol{x}; \boldsymbol{\theta}_s^j))$
8:          **if** $(t \bmod \Delta\text{T}) = 0$ **then**
9:              # Parameter Exploration
10:             Prune p percentage of parameters using Eq. 1
11:             Grow p percentage of parameters using Eq. 2
12:             Update exploration rate p
13:         **end if**
14:     **end for**
15:     save the converged sparse subnetwork $f(\boldsymbol{x}; \boldsymbol{\theta}_s^j)$
        $j = j + 1$
16: **until** $j \geq$ M

C IMPLEMENTATION AND HYPERPARAMETERS

In this Appendix, we provide the hyperparameters used in Section 4.

We mentioned in the main content of paper that these free tickets (subnetowrks) are non-trivial to obtain due to the three key desiderata. To confirm this, we implement and test two sparsity-based efficient ensemble methods, Static Sparse Ensemble and Lottery Ticket Hypothesis (LTR) Ensemble.

Static Sparse Ensemble   Static Sparse Ensemble refers to directly training M sparse subnetworks from scratch and ensemble them for test. Even though it naturally satisfies the low training cost and high diversity, its insufficient accuracy leads to worse performance than the proposed DST/EDST Ensemble.

LTR Ensemble   Following Evci et al. (2020b), we use gradually magnitude pruning (GMP) (Zhu & Gupta, 2017; Gale et al., 2019) for LTR, which is a well studied and more efficient pruning method than iterative magnitude pruning (IMP). Concretely, we first use gradually magnitude pruning to prune the dense network to the target sparsity. After that, we retrain and rewind the subnetworks to the 5% epoch for M times. The converged subnetworks are further used for ensemble. Note that even GMP is much more efficient than IMP, the overall training FLOPs required by this method is much higher than directly training a single dense model. We expect that using IMP for Ensemble can be more accurate, but also leads to prohibitive training costs, in contrary to our pursuit of efficient ensemble.

Hyperparameters of DST Ensemble   For a fair comparison, we follow the training configuration of MIMO. For Wide ResNet28-10 on CIFAR, we train the sparse model for 250 epochs with a learning rate of 0.1 decayed by 10. We use a batch size of 128, weight decay of 5e-4. To achieve a good trade-off between ensemble accuracy and sparsity, we set sparsity as $S = 0.8$. Regarding the hyperparameters of DST, we choose a large update interval $\Delta T = 1000$ between two sparse connectivity updates and a constant DST exploration rate $p = 0.5$ to encourage a large sparse connectivity diversity.

For ResNet-50 on ImageNet, to the best of our knowledge, all the state-of-the-art DST approaches can not match the performance of the dense ResNet-50 on ImageNet with a standard training time. To guarantee sufficient predictive accuracy for the individual ensemble learners, we follow the training setups used in Liu et al. (2021b) and train each sparse ResNet-50 for 200 epochs with a batch size of 64. The learning rate is linearly increased to 0.1 with a warm-up in the first 5 epochs and decreased by a factor of 10 at epochs 60, 120, and 180. Even with a longer training time, it takes much fewer FLOPs to train sparse networks using DST compared to the dense network. We choose $\Delta T = 4000$ and a cosine annealing schedule for the exploration rate with an initial value $p = 0.5$.

Hyperparameters of EDST Ensemble   For Wide ResNet28-10 on CIFAR, we train the 80% sparse model for 450 epochs and 90% sparse model for 850 epochs with $t_{ex} = 150, t_{re} = 100$, so that we can get M = 3 subnetworks with sparsity of 0.8 and M = 7 subnetworks with sparsity of 0.9 for ensemble. The numbers of training FLOPs of this two settings are similar due to the different sparsity levels. The DST exploration rate is chosen as $p = 0.5$ which achieves the best performance as shown in (Evci et al., 2020a; Liu et al., 2021b). To encourage a large diversity between ensemble learners, we use a large exploration rate $q = 0.8$ to force the subnetowrk escape the local minima. We have also tested a larger exploration rate, i.e., $q = 0.9$. The results are similar with $q = 0.8$.

For ResNet-50 on ImageNet, we set $t_{ex} = 30$ and $t_{re} = 70$ so that we can obtain M = 2 subnetworks with 170 epochs and M = 4 subnetworks with 310 epochs, respectively. We set $p = 0.5$ and $q = 0.8$. The rest of hyperparameters are the same as DST Ensemble. Due to the limited resources, we only test the 80% sparsity for ResNet-50. We believe that the ensemble performance can further improve with lower sparsity.

D EXPERIMENTAL METRICS

To measure the predictive accuracy and robustness, we follow the Uncertainty Baseline[3] and focus on test accuracy (Acc), negative log-likelihood (NLL), and expected calibration error (ECE) on the i.i.d. test set, corrupted test sets (i.e., CIFAR-10-C and ImageNet-C) (Hendrycks & Dietterich, 2019) which contain 19 natural corruptions such as added blur, compression artifacts, frost effects, etc, as well as on the natural adversarial samples (i.e., ImageNet-A) (Hendrycks et al., 2019). We adopt {cAcc, cNLL, cECE} and {aAcc, aNLL, aECE} to denote the corresponding metrics on corrupted test sets and natural adversarial samples, respectively.

To compare the computational efficiency, we report the training FLOPs required to obtain the targeted number of subnetworks for all methods and normalize them with the FLOPs required by a dense model. Following RigL[4] (Evci et al., 2020a), the FLOPs are calculated with the total number of multiplications and additions layer by layer. Briefly speaking, with ERK distribution, the training FLOPs of a sparse Wide ResNet28-10 at sparsity $S = 0.8$ and $S = 0.9$ are 33.7% and 16.7% of the dense model, respectively. For sparse ResNet-50 at $S = 0.8$, the required training FLOPs is 42% of the dense model. We omit the additional computational cost for the extra inputs and the extra outputs of MIMO, as it is negligible compared with the whole training FLOPs. Moreover, we suppose the hardware can fully utilize large batch size so that BatchEnsemble incurs almost no additional computational overhead and memory cost.

---

[3] https://github.com/google/uncertainty-baselines

[4] More details can be found in the official repository of RigL https://github.com/google-research/rigl/tree/master/rigl/imagenet_resnet/colabs

E   PREDICTION DISAGREEMENT ON CIFAR-10

The prediction disagreement with Wide ResNet28-10 on CIFAR-10 is reported in Figure 6. Similar as CIFAR-100, DST Ensemble can match the prediction diversity of the dense ensemble. The predictions of free tickets discovered by EDST Ensemble are relatively more correlated than DST Ensemble. This actually makes sense since the free tickets generated by EDST are obtained within one single run and share part of sparse connectivity. Moreover, as expected, at a higher sparsity $S = 0.9$, the prediction diversity of EDST Ensemble slowly rises as the ensemble size M increases, and ends up with a similar diversity as the Dense Ensemble.

(a) Dense Ensemble   (b) DST Ensemble (S=0.8)   (c) EDST Ensemble (S=0.8)   (d) EDST Ensemble (S=0.9)

Figure 6: Prediction disagreement between ensemble learners with Wide ResNet28-10 on CIFAR-10. Each subfigure shows the fraction of labels on which the predictions from different ensemble learners disagree.

F EXPERIMENTS WITH OOD RESULTS

In this section, we report the performance of out-of-distribution (OOD) detection for single sparse networks and ensemble models. Specifically, we use datasets that are not seen during training time for OOD evaluation. Following the classic routines (Augustin et al., 2020; Meinke & Hein, 2019), SVHN (Netzer et al., 2011), CIFAR-100 (Krizhevsky & Hinton, 2009), and CIFAR-10 with random Gaussian noise (Hein et al., 2019) are adopted for models trained on CIFAR-10 (Krizhevsky & Hinton, 2009); SVHN, CIFAR-10, and CIFAR-100 with random Gaussian noise are used for models trained on CIFAR-100. The ROC-AUC performance (Augustin et al., 2020; Meinke & Hein, 2019) are reported over the respective out of distribution datasets, as shown in Table 6 and Table 7. As we expected, our proposed ensemble methods provide gains also to the OOD performance. DST Ensemble and EDST Ensemble can even surpasses the dense models by a clear margin in most cases.

Table 6: The ROC-AUC OOD performance for Wide ResNet-28-10 trained on CIFAR-10.

Methods	OOD dataset for CIFAR-10 trained models		
	SVHN	CIFAR-100	Gaussian Noise
Static Sparse Ensemble (M = 1) (S = 0.8)	0.8896	0.8939	0.9559
Static Sparse Ensemble (M = 3) (S = 0.8)	0.9229	0.9082	0.9910
DST Ensemble (M = 1) (S = 0.8)	0.9082	0.8957	0.9964
DST Ensemble (M = 3) (S = 0.8)	0.9533	0.9114	0.9969
EDST Ensemble (M = 1) (S = 0.8)	0.9461	0.8895	0.9607
EDST Ensemble (M = 3) (S = 0.8)	0.9487	0.9045	0.9928
EDST Ensemble (M = 1) (S = 0.9)	0.9439	0.8955	0.9817
EDST Ensemble (M = 7) (S = 0.9)	0.9658	0.9115	0.9956
Single Dense Models	0.9655	0.8847	0.9803

Table 7: The ROC-AUC OOD performance for Wide ResNet-28-10 trained on CIFAR-100.

Methods	OOD dataset for CIFAR-100 trained models		
	SVHN	CIFAR-10	Gaussian Noise
Static Sparse Ensemble (M = 1) (S = 0.8)	0.7667	0.8004	0.7858
Static Sparse Ensemble (M = 3) (S = 0.8)	0.8165	0.8141	0.9560
DST Ensemble (M = 1) (S = 0.8)	0.8284	0.8019	0.8131
DST Ensemble (M = 3) (S = 0.8)	0.8207	0.8221	0.8865
EDST Ensemble (M = 1) (S = 0.8)	0.7481	0.7941	0.8736
EDST Ensemble (M = 3) (S = 0.8)	0.8585	0.8137	0.9046
EDST Ensemble (M = 1) (S = 0.9)	0.7990	0.7937	0.8097
EDST Ensemble (M = 7) (S = 0.9)	0.8092	0.8148	0.9436
Single Dense Models	0.7584	0.8045	0.7374

G   EXPERIMENTS WITH ADVERSARIAL ROBUSTNESS

Table 8 presents the adversarial robustness performance of Wide ResNet-28-10 trained on CIFAR0-10 and CIFAR-100, where the Fast Gradient Sign Method (FGSM) (Szegedy et al., 2013) with step size $\frac{8}{255}$ is adopted. Following a similar routine as in Strauss et al. (2017), we craft adversarial examples for each single model and report the {min, mean, max} robust accuracy over generated attacks from different models. The results demonstrate that our proposed ensemble methods improve robustness accuracy as well, especially in terms of average robust accuracy. More surprisingly, the ensemble of static sparse models can even outperform DST-based Ensembles in this setting. Further analysis on this task serves as an interesting future work.

Table 8: The robust accuracy (%) for Wide ResNet-28-10 trained on CIFAR-10 and CIFAR-100.

Methods	Robust Accuracy (%) {min/mean/max}	
	CIFAR-10	CIFAR-100
Static Sparse Ensemble (M = 1) (S = 0.8)	33.68/38.40/41.29	11.89/15.21/17.01
Static Sparse Ensemble (M = 3) (S = 0.8)	39.28/39.46/39.77	16.44/16.81/17.19
DST Ensemble (M = 3) (S = 0.8)	37.30/38.49/39.12	14.96/15.59/15.90
EDST Ensemble (M = 3) (S = 0.8)	39.66/40.35/41.00	13.00/13.19/13.56
EDST Ensemble (M = 7) (S = 0.9)	35.68/37.74/38.67	14.45/14.93/15.56
Single Dense Models	44.20	11.82