Unsupervised Image-to-Image Translation with Density Changing Regularization

Abstract

Unsupervised image-to-image translation aims to translate an input image to another domain such that the output image looks like an image from another domain while important semantic information are preserved. Inferring the optimal mapping with unpaired data is impossible without making any assumptions. In this paper, we make a density changing assumption where image patches of high probability density should be mapped to patches of high probability density in another domain. Then we propose an efficient way to enforce this assumption: we train the flows as density estimators and penalize the variance of density changes. Despite its simplicity, our method achieves the best performance on benchmark datasets and needs only $56 - 86\%$ of training time of the existing state-of-the-art method.

1 Introduction

Unsupervised image-to-image translation aims to translate an input image to another domain such that the output image looks like an image from another domain while important semantic information are preserved. For example, in the task selfie→anime, we need to translate the selfie photo into anime style while the identity of input human is still preserved. In addition, many research problems can be reformulated as image translation tasks, such as domain adaptation [18, 34], medical image analysis [2] and image super-resolution [48].

In unsupervised image translation setting, we are given two collections of samples without pairing information and we need to learn a proper mapping from one domain to another. Unfortunately, given two marginal distributions, there can be infinite number of joint distributions that can derive the same marginals [30]. Therefore, assumptions are needed to address this ill-posed problems. One popular assumption is the cycle consistency [53, 26, 46], which assumes that the proper mapping is one-to-one. Cycle consistency has been shown to achieve impressive visual performance in many tasks [53, 25]. But sometimes the one-to-one assumption can be over restrictive, especially for some tasks that one domain has more information than another one [39]. As an alternative, contrastive learning based image translation is gaining wide attention [39]. CUT [39] employs infoNCE loss [42] to maximize the mutual information between two corresponding patches in the input and output images. Recent image translation methods are mostly trying to improve CUT, such as negative sample mining [43, 24], informative sample mining [20, 49] and dual embedding learning [16].

In this paper, we propose a different way to find the optimal mapping by looking at the neighboring information. DistanceGAN [4] proposes to maintain the pairwise distance between images after the mapping. But the pairwise distance is usually computed within mini-batches and the neighboring information can be inaccurate, which may leads to unsatisfactory performance as reported in [39]. We propose to consider the neighboring information from the density perspective: the probability density of an image or patch (a smaller piece of the image) is a good representation of its neighborhood. If the probability density of an image is high, it means that many samples are likely to be drawn from

Figure 1: Illustration of our constraint. The plotted densities are synthesized for illustration. On the top row, we show the patch density distribution of domain $\mathcal{X}$ and $\mathcal{Y}$. We assume that the patches of high density should still be mapped to patches with high density in another domain.For example, patches of building (blue box) in the input image are of higher density than patches of trees (orange box) in domain $\mathcal{X}$. Then we assume that the corresponding patch should also have higher density. If label flipping happens, buildings (high density) are mapped to trees (low density) and trees (low density) are mapped to buildings (high density), the variance of density changes can be very large. So we penalize the variance of density changes to find the optimal mapping. The ground truth photo is in line with our assumption.

its neighborhood. In light of this analysis, we propose our density changing regularization: *patches with high (low) density should be mapped to patches with high (low) density in another domain.* As illustrated in Figure 1, the gray area in input image (blue box) is of higher density than the green area (orange box), then our regularization encourages that the gray area is mapped to area with high density in another domain. In this example, the patch of building is of higher density than the patch of trees. Therefore, our regularization encourages the gray area to be mapped to the building and the green area to be mapped to the trees. As we can observe from the ground truth, it is exactly what the ground truth photo does. The regularization is implemented in a very simple way: we just train two density estimators and penalize the variance of the density changes of patches. We apply our method to different image translation tasks and the superior performance across tasks demonstrate the effectiveness of our method. In addition, our method needs only around 56-86% training time of state-of-the-art (SOTA) methods.

2   Related Work

Image Translation For unsupervised image-to-image translation, we are given only two collections of images and we need to learn a proper mapping from one domain to another. However, the number of possible mappings can be infinite and we need to introcue additional assumptions to reduce it. Cycle consistency [53, 46, 26] is one of the most popular assumptions. It enforces the mapping function to be one-to-one and has shown success in many tasks [25, 1, 7, 6]. However, it may be restrictive when the optimal mapping is not one-to-one, e.g., segmentation map to a real photo. To address this issue, CUT [39] proposes a contrastive learning based method. It maximizes the mutual information between two corresponding patches in the input and output image with the infoNCE loss [37]. Unlike CycleGAN [53], CUT doesn't need two mapping function and allows one-sided training. However, as many recent method revealed, the effectiveness of the method can be hampered by the negative samples used. Randomly selected negative samples might not be useful. Therefore, recent methods are mostly focusing on mining more meaningful negative samples or positive samples for better results [24, 43, 49, 20]. Unlike the mutual information based methods, our method focus on the neighboring information of patches and no negative sample are needed. There are also some methods arguably based on the neighborhood information. DistanceGAN [4] proposes to maintain the

Patch Density Changing Regularization

Figure 2: Patch Density Changing Regularization for unsupervised image translation. G is the generator, a_l^n and b_l^n denotes the patch representation extracted by the l-th layer of G of the input image x and generated image $G(x)$, respectively. $f_{\mathcal{X}}^l$ and $f_{\mathcal{Y}}^l$ are log-density estimators for patch representations at l-th layer in domain $\mathcal{X}$ and $\mathcal{Y}$, respectively. We penalize the variance of log-density changes such that patches with high (low) density are mapped to patches with high (low) density in another domain.

pairwise distance between images in the source domain and the translated domain. HarmonicGAN [50] proposes a smoothed distance objective inspired by [54]. F-LSeSIM [52] proposes to encourage the pairwise distance matrix of input and translated patch representations to be consistent. However, the pairwise distance loss may be inaccurate due to the insufficient sample and the training objective may also be dominated by the very distant pairs. In contrast, our method utilizes the probability density, which represents the neighborhood information of the whole dataset and we also avoid the possibly bad influence by the very distant pairs. There are also some powerful alternatives, such as the spatial transformation consistency [12, 45] and shared latent space assumption [30, 22, 29].

Flow+GAN FLOW-GAN [15] uses the normalizing flow as the generator. Then the generator can be trained by maximum likelihood and adversarial objectives hybridly. Based on FLOW-GAN, Alignflow[14] first translates the source image into a latent variable with flow and generate its corresponding image in the target domain by feeding the latent variable into another flow. Since flows are designed to be invertible, the mapping function is exactly invertible while CycleGAN [53] only enforces that property approximately. iFlowGAN [9] proposes to regularize the lipschitz norm of each layer and thus the mapping function is invertible and the inverse can be obtained by fixed-point theorem. Unfortunately, the flow model can take very long time to train and has inferior performance compared to GAN model in high-resolution image modeling. [32, 3, 27]. Our model doesn't need to train the flow as image modeling but we utilize its strong density estimation ability to regularize the GAN training.

Density Estimation Estimating the density $P(x)$ from a set of samples $\{x_i\}$ is an important problem in machine learning and computer vision. There have been many successful works that estimate the density with neural networks [38, 41, 28, 11, 21, 23, 31, 13, 44, 36, 19]. In this paper, we consider the autoregressive normalizing flow as our density estimator. The flow model f maps the data into Gaussian noise and the density of data x can be computed as $p(x) = p(z)|\det J_{f(x)}|$, where $z = f(x)$, $p(z)$ is the normal distribution density and $|\det J_{f(x)}|$ is the absolute value of determinant of the Jacobian matrix. With careful design of the architecture of the function f, the determinant can also be computed efficiently.

3 Proposed Method

Given images $\{x_i\} \in \mathcal{X}$ and images $\{y_j\} \in \mathcal{Y}$, our goal is learn a mapping $G : \mathcal{X} \to \mathcal{Y}$ such that $G(x)$ looks like images in the domain $\mathcal{Y}$ while preserving necessary semantic information. For

95 example, in translating a segmentation map to real-world photo, we need to ensure that generated
96 photo looks realistic while the contents (e.g., building, trees, roads) in the generated photo follow the
97 segmentation map.

3.1 Baseline GAN model

99 To achieve the first goal that $G(x)$ looks like an image in another domain $\mathcal{Y}$, we employ an adversarial
100 loss with the domain discriminator D to match the distribution between $P_{G(\mathcal{X})}$ and $P_{\mathcal{Y}}$,

$$\mathcal{L}_{\text{gan}} = \mathbb{E}_{x \sim \mathcal{X}}[\log(1 - D(G(x)))] + \mathbb{E}_{y \sim \mathcal{Y}}[\log(D(y))]. \tag{1}$$

101 We also additionally introduce an identity mapping loss to regularize the mapping function G, which
102 is widely adopted in existing image translation methods [53, 39].

$$\mathcal{L}_{\text{identity}} = \mathbb{E}_{y \sim \mathcal{Y}} \| G(y) - y \| \tag{2}$$

103 . By combing these two losses, we obtain an baseline GAN model for image translation. Unfortunately,
104 there are can still be infinite number of mappings that satisfy these objectives and we need further
105 constraints to reduce the number of possible mappings in the space [53].

3.2 Proposed Density Constraint

107 In this paper, we consider the neighboring information from the probability density perspective. We
108 first revisit the definition of density function: Let X be a continuous real-valued random variable. A
109 *density function* for X is a real-valued function f which satisfies

$$P(a \le X \le b) = \int_a^b f(x)dx, \tag{3}$$

110 for all $a, b \in \mathbb{R}$.

111 Given a value x of X, we have $P(x - \delta \le X \le x + \delta) = \int_{x-\delta}^{x+\delta} f(x)dx \approx 2\delta f(x)$. For a predefined
112 δ, if the density of x is high, then $P(x - \delta \le X \le x + \delta)$ is high. It means that there are will be
113 many samples that fall within the range $[x - \delta, x + \delta]$. Therefore, there will be many neighbors of
114 x in the sample space. It follows that the density $f(x)$ can be viewed as a measure of how many
115 neighbors (within δ distance) x will have.

116 In light of this observation, we propose our density changing constraint for unsupervised image-to-
117 image translation: *if the density $f(x)$ of a image x is high in the domain $\mathcal{X}$, then the translation $G(x)$*
118 *should also have high density $P(G(x))$ in domain $\mathcal{Y}$*. The density function provides us an elegant
119 way to utilize the neighboring information without computing the time-consuming and possibly
120 inaccurate pairwise distances. Given two density estimators $f_{\mathcal{X}}, f_{\mathcal{Y}}$ for two domains, we have our
121 constraint defined as

$$\mathcal{L}_{\text{density}} = \mathbb{V} \left(\frac{f_{\mathcal{X}}(X)}{f_{\mathcal{Y}}(G(X))} \right),$$

122 where $\mathbb{V}(.)$ is the variance function. It means that we would like the density changes for all images
123 to be close such that image with high density is still mapped to high density while image with low
124 density still mapped to low density. In the following sections, we provide an efficient way to get the
125 density estimators $f_{\mathcal{X}}, f_{\mathcal{Y}}$ and the density changing objective $\mathcal{L}_{\text{density}}$.

126 **Another perspective of density changing constraint**. From the definition, we can see that we
127 are enforcing constraint on the probability density ratios. If the density estimators are accurate,
128 i.e., $f_{\mathcal{X}}(x) = f(x), f_{\mathcal{Y}}(G(x)) = f(G(x))$ and the mapping function G is invertible, then we are
129 having $|\det(J_{G(x)})| = \frac{f(x)}{f(G(x))}$ according to the change of variable formula, where $|\det(J_{G(x)})|$ is the
130 absolute value of determinant of the Jacobian matrix of the mapping function $G(x)$. This term can
131 be viewed as a measure of volume changing caused by the function G in the space. Therefore, by
132 minimizing the $\mathcal{L}_{\text{density}}$ when G is invertible, we are enforcing that mapping function G have similar
133 volume changing for all samples.

3.3 Density Changing Regularized Unpaired Image Translation

To compute $\mathcal{L}_{\text{density}}$, we need density estimators $f_{\mathcal{X}}$ and $f_{\mathcal{Y}}$. There are many successful autoregressive flows for density estimation [21, 10]. However, density estimation for images is still an challenging task due to the high-dimensionality of images. Inspired by the recent patch-level image translation method [39], we propose to compute the densities in the patch level rather than image level. We first extract the feature maps at layer l of the generator G as $m^l(x) = G^l(x) \in \mathbb{R}^{c \times h \times w}$, where c is the number of channels of the feature map and h, w represents the height and width of the maps. Then we reshape $m^l(x)$ into patch representations $P^l(x) \in \mathbb{R}^{hw \times c}$. For each representation of size c, it corresponds to a patch in the input image. And we have hw patch representations. We denote the patch representations of input image $x \in \mathcal{X}$ as $P^l(x) = \{a_i^l\}$, input image $y \in \mathcal{Y}$ as $P^l(y) = \{c_i^l\}$, generated image $G(x)$ as $P^l(G(x)) = \{b_i^l\}$. We sometimes use a^l to denote the random variable whose values are a_i^l and similar for b^l and c^l.

For each layer l, we employ two density estimators $f_{\mathcal{X}}^l$ and $f_{\mathcal{Y}}^l$, which are parameterized as auto-regressive flows [10]. Given patch representations of real images $\{a_i^l\}$ and $\{b_i^l\}$, we train the density estimators with maximum likelihood estimation as

$$\mathcal{L}_{\text{nll}}(f_{\mathcal{X}}) = \sum_{l=1}^{L} \sum_{i=1}^{hw} -f_{\mathcal{X}}^l(a_i^l), \quad \mathcal{L}_{\text{nll}}(f_{\mathcal{Y}}) = \sum_{l=1}^{L} \sum_{i=1}^{hw} -f_{\mathcal{Y}}^l(c_i^l), \quad \mathcal{L}_{\text{nll}} = \mathcal{L}_{\text{nll}}(f_{\mathcal{X}}) + \mathcal{L}_{\text{nll}}(f_{\mathcal{Y}}) \quad (4)$$

where the outputs of the flows $f_{\mathcal{X}}$ and $f_{\mathcal{Y}}$ are log-probabilities and we need to minimize above loss to maximize the log-likelihood.

Given the density estimators, we can compute our density regularization easily as

$$\mathcal{L}_{\text{patch-density}} = \sum_{l=1}^{L} \mathbb{V}(f_{\mathcal{X}}^l(a^l) - f_{\mathcal{Y}}^l(b^l)). \quad (5)$$

The outputs of density estimators are log-likelihoods and therefore, $f_{\mathcal{X}}^l(a^l) - f_{\mathcal{Y}}^l(b^l)$ is equivalent to the probability ratios in the log-scale since $\log \frac{p}{q} = \log p - \log q$. Please note that a^l and c^l represents the corresponding patches in the input image x and output image $G(x)$. By minimizing $\mathcal{L}_{\text{patch-density}}$, we are encouraging the transformation from a^l to b^l should satisfy our assumption, i.e., patches with high density should be mapped to patches with high density.

Full Objective Our full objective for the generator consists of three terms

$$\mathcal{L}_{\text{full}}(G) = \mathcal{L}_{\text{gan}} + \lambda_{\text{idt}} \mathcal{L}_{\text{identity}} + \lambda_{\text{density}} \mathcal{L}_{\text{patch-density}}, \quad (6)$$

where λ_{idt} and λ_{density} are hyper-parameters that balance different losses.

For the discriminator, we train it to maximize the $\mathcal{L}_{\text{gan}}$ to distinguish the real from the generated images.

$$\mathcal{L}_{\text{dis}}(D) = -\mathcal{L}_{\text{gan}} \quad (7)$$

For the density estimators, we train them with $\mathcal{L}_{\text{nll}}$ as

$$\mathcal{L}_{\text{nll}}(\{f_{\mathcal{X}}^l, f_{\mathcal{Y}}^l\}_{l=1}^{L}) = \mathcal{L}_{\text{nll}}. \quad (8)$$

For brevity, we denote our method as DEnsity Changing rEgularized uNpaired image Translation (DECENT).

4 Implementation

Density Estimator. In our initial experiments, we consider three auto-regressive neural flows for density estimator: MAF [38], BNAF [10] and NSF [11]. But we observe that MAF and NSF sometimes reports NAN error, which may be caused by the exponential scaling function. BNAF further adopts the weight normalization technique to stablize the training. Therefore, we stick to BNAF in our experiments. We use the recommended hyper-parameters by BNAF: we set the hidden dim as 10, polyak averaging rate as 0.998. We use the AMSGrad optimizer with learning rate 0.001,

β_1=0.9, β_2 =0.999. To reduce the computation cost, we set the number of blocks in BNAF to 1. Since there are 5 layers used to extract patch representations, we employ 5 BNAF for each domain in total. The number of parameters of the 5 BNAFs is 4.280 M. As a reference, the number of parameters of the generator is 11.378M.

Generator and Discriminator. We follow the networks used in CUT [39]. For the generator, we adopt the 9-block ResNet as the backbone network. For the discriminator, we adopt the 3-layer PatchGAN discriminator. The learning rate is 0.0002 with $\beta_1 = 0.5$, $\beta_2 = 0.999$. The exception is the cat→dog task, which requires large shape changes. Following NEGCUT[43], we replace the patchGAN discriminator with a 6-layer discriminator, which captures more global information.

Hyper-parameters. We mostly follow the hyper-parameters in CUT [39]. We set $L = 5$ following CUT [39]. It means that we use five layers (0,4,8,12,16th) of the generator to extract patch representations. The layers correspond to receptive fields of sizes 1×1, 9×9, 15×15, 35×35, and 99×99. We also use 256 patches in each layer instead of all patches to save computation time and memory. The difference is λ_{idt}. CUT [39] uses contrastive learning to achieve this identity while we use L_1 reconstruction loss. Therefore, we set it to $\lambda_{\text{idt}} = 10$ following [53, 25]. The only hyper-parameter we introduce is λ_{density}. We initially set it to 1 but found that it is over-restrictive and causes model collapse. We next tried two values $\{0.01, 0.1\}$, and discovered both work pretty well, with 0.01 performing slightly better. We set $\lambda_{\text{density}} = 0.01$ across all tasks.

Training In each iteration, we first update the density estimators by minimizing $\mathcal{L}_{\text{mle}}$. Then we update the discriminator by $\mathcal{L}_{\text{dis}}$. When optimizing the generator, to compute $\mathcal{L}_{\text{patch-density}}$, we use the polyak averaged version of BNAF to estimate the density for patches. For $\mathcal{L}_{\text{gan}}$, we replace the vanilla GAN loss with the LSGAN [33] objective following CUT [39]. For all dataset, we resize images to 256×256. We keep the learning rate for the first half of the training and linearly decay it to 0 in the last half of training.

5 Experiments

5.1 Evaluation

We follow the evaluation protocols in [53, 39, 43, 20, 49] and run all tasks once. We report results of more runs in the supplementary material.

Datasets We follow the evaluation protocols in CUT [39] by running experiments on three benchmark datasets: label→city, cat→dog and horse→zebra. We further run experiment on selfie→anime dataset to fully verify the effectiveness of our method. The label→city dataset [8] consists of 2975 training images in each domain and 500 pairs for testing. The cat→dog [7] dataset contains around 5000 training images in each domain and 500 testing images. The horse→zebra dataset [53] contains around 1200 training images in each domain and around 100 testing images. The selfie→anime dataset [25] contains 3400 training images in each domain and 100 testing images. We run label→city and horse→zebra for 400 epochs, cat→dog and selfie→anime for 200 epochs.

Metrics For the label→city task, we follow [39] and evaluate the generated photos by a pre-trained segmentation model DRN [47]. The DRN model translates the generated photos into segmentation labels and then we can compare the output labels with the input labels. We compute mean average precision (mAP), pixel-wise accuracy (pAcc) and average class accuracy (cAcc).

To evaluate the visual quality of generated images, we also adopt the widely-used Frechet Inception Distance (FID) [17] and Kernel Inception Distance (KID) [5] scores. FID and KID both measure the distribution divergence between the generated images and the real images.

Baselines For the first three tasks, we compare our method with different assumptions: cycle consistency-CycleGAN [53], pairwise distance preservation – DistanceGAN and SelfDistance [4] and mutual information maximization – CUT[39], DCLGAN [16], FSeSIM [52], NEGCUT [43], MoNCE [49] and QS-Attn [20]. Please note that the MoNCE [49] and QS-Attn [20] are released less than two months before this submission and they serve as strong baselines.

For selfie→anime, we compare with CycleGAN [53], U-GAT-IT [25], CUT[39], CouncilGAN [35], ACL-GAN [51] and SpatchGAN [40]. For all tasks, we also run the Base-GAN model, i.e., $\lambda_{\text{density}} = 0$, to fully examine the effectiveness of our proposed regularization.

Table 1: Main experiment results. Abbreviations: (H)orse and (Z)ebra.

Method	label→city				cat → dog	H → Z	Speed
	mAP ↑	pAcc ↑	cAcc ↑	FID ↓	FID ↓	FID ↓	Sec/it ↓
CycleGAN [53]	22.37	57.27	29.86	66.7	146.85	76.9	0.171
DistanceGAN [4]	7.86	42.74	11.72	79.0	143.64	72.1	**0.035**
SelfDistance [4]	8.25	43.61	12.20	58.4	108.3	78.9	0.036
CUT [39]	27.79	70.70	35.90	56.4	76.2	45.5	0.137
DCLGAN [16]	27.75	68.19	36.72	49.4	61.6	42.2	0.225
FSeSim [52]	24.74	61.47	33.02	58.1	87.8	43.4	0.060
NEGCUT [43]	28.63	72.29	36.03	48.5	55.9	**39.7**	0.275
MoNCE [49]	29.12	72.35	36.48	54.7	-	41.9	0.231
QS-Attn [20]	29.75	71.76	37.95	50.2	80.6	42.0	0.182
Base-GAN	21.86	53.85	28.81	**47.4**	140.1	40.1	0.082
DECENT (Ours)	**30.97**	**72.93**	**39.33**	**47.4**	**55.2**	41.3	0.154
Testing Images	45.98	77.57	55.99	0	0	0	-

Table 2: Additional results

Method	selfie→anime	
	FID ↓	KID ↓
CycleGAN [53]	92.4	2.99
DistanceGAN [4]	94.5	2.36
CUT [39]	87.2	2.55
CouncilGAN [35]	92.4	2.65
ACL-GAN [51]	98.0	2.85
SpatchGAN [40]	83.3	2.14
Base-GAN	89.5	3.09
DECENT (Ours)	**80.7**	**1.42**
Training Images	76.7	0.30

Table 3: Ablation Study

Setting		label→city		
Model	λ	mAP ↑	pAcc ↑	cAcc ↑
Base-GAN	0	21.86	53.85	28.81
DECENT	0.001	28.15	64.82	35.40
	0.01	**30.97**	**72.93**	**39.33**
	0.1	30.29	71.51	38.67
	0.5	23.77	66.80	31.42
PatchDist	0.001	25.12	59.93	34.12
	0.01	22.10	54.75	29.73
	0.1	28.43	64.67	38.47
	0.5	25.87	67.87	33.92

5.2 Comparison against Baselines

We present the quantitative results in Table. 1 and 2. Among the four tasks, our method achieves the best performance on the label→city, cat→dog tasks and selfie→anime tasks. In particular, our method is the first one to improve mAP above 30 on the label→city task. Please note that all recent state-of-the-art methods are improved versions of CUT [39]. By contrast, we propose an effectiveness regularization which is orthogonal to the contrastive learning [39] and cycle consistency losses [53]. Our method brings substantial improvements over the Base-GAN model. For the label→city task, we outperform it by 41.7% on mAP, 35.4% on pAcc and 36.5% on cAcc. The significant improvements demonstrates that our proposed density regularization is able to preserve important semantic information in inputs. On the cat→dog task, our method improves the FID from 140.1 to 55.2. On the selfie→anime task, our method improves the FID from 89.5 to 80.7 and KID from 3.09 to 1.42. The encouraging results suggest that our regularization is also helpful in distribution matching.

We also present the generated samples in Figure. 3 and more samples are provided in the supplementary material. For the label→city task, we can observe that the SOTA method– QS-Attn [20] still faces some label flipping issue, i.e., mapping the gray area to the trees. By contrast, our method is able to map the gray area into the building accurately. For the cat→dog task, we can observe that the Base-GAN model suffers the well-known mode collapse issue while our method is able to avoid it by our proposed regularization. For the selfie→anime, our method learns to preserve the hair color of the first input person while keeping the headphone cable in the output image. Unlike CouncilGAN [35] and SpatchGAN [40], our method doesn't apply additional data augmentations, such as random brightness and hue offset.

5.3 Analysis

Sensitivity of λ_{density}. Although our method only introduces one loss, it is still important to investigate the sensitivity of the introduced hyper-parameter λ_{density}. We run our method on label→city task since

Figure 3: Visualization of samples generated by different methods: label→city, cat→dog, horse→zebra and selfie→anime. We provide more samples and more baseline results in the Supplementary material.

the testing images are paired. The results are shown in Table. 3. We can observe that our method is robust to the scale of λ. When $\lambda = 0.01$ or 0.1, we can achieve state-of-the-art results. When $\lambda = 0.0001$, it still improves the Base-GAN model from 21.86 to 28.15 on mAP metric. When we increase it to 0.5, which is quite far from the optimal value, we can still observe large improvements over the Base-GAN model.

Pairwise relationship vs Density We can observe that the performance of DistanceGAN and SelfDistance [4] are unsatisfactory in Table. 1. As we have argued in section 2, it may be caused by insufficient samples. Therefore, we build a stronger version of DistanceGAN – Patchdist. Patchdist is trained to preserve the pairwise distance between all patch representations now. Since many patches are available in each iteration, the pairwise relations should be more accurate. As shown in Table. 3, PatchDist can also bring improvements over Base-GAN model now (DistanceGAN and SelfDistance are worse). The improvements supports our argument that the neighboring information is very useful in image translation tasks. Our method still outperforms PatchDist by a large margin, which implies that the densities values are more informative than the pairwise relation in image translation tasks.

Training Time We run all methods on NVIDIA Tesla V100-SXM2 GPU and report their training speed in table 2. One may notice that DistanceGAN [4], SelfDistance [4] and FSeSim [52] are faster than the Base-GAN model. The main reason is that they don't apply the identity regularization. When compared to the three SOTA methods (NEGCUT [43], MoNCE [49] and QS-Attn [20]),

Figure 4: An example of the learned densities (best viewed in color) on label→city task. Densities increases as the color transition from blue to red. We provide the learned densities for more samples and tasks in the supplementary.

our method achieves the best performance with the highest training speed. NEGCUT needs to generate negative samples with additional networks, MoNCE needs to compute the entropy of all patch representations and MoNCE needs to address an optimal transport problem every iteration. In contrast, we only introduce the density estimators and avoids the heavy global information computation. As a consequence, our method only needs approximately 56%, 67% and 86% training time of NEGCUT [43], MoNCE [49] and QS-Attn [20], respectively.

Learned densities We visualize the learned densities in Figure.4. The densities increase as the color goes from blue to red. Firstly, we observe that our learned densities are consistent with human judgements and reveal the neighboring information accurately. For example, human can easily tell that gray patches should have more neighbors than green patches in the first row. The densities of gray patches shown in the second row are higher than the green patches.

Then we examine whether our method effectively enforces our assumption and whether it brings improvements. On the label→city task, we observe that the mapping of Base-GAN violates our assumption, i.e., Base-GAN maps the green patches (low density) to the building (high density) while gray patches (high density) to the trees (low density). As a consequence, it suffers the label-flipping issue when compared with the ground truth photo. In contrast, our method is able to find the correct mapping through our density regularization.

6   Limitation and Discussion

Although our method achieved state-of-the-art performance across many tasks, our method still suffers from some limitations: (1) the violation of the assumption; One may notice that the Base-GAN model achieves the second best FID on the horse→zebra task as shown in Table. 2. Although our method is slightly better than other SOTA methods, it still brings some performance degradation (40.1→41.3). This may be caused by the unmatched dataset statistics since it is reported that horse takes 18% pixel of the image and zebra takes 37% pixels in the dataset [39]. Therefore, patches of high density in the horse domain may not still be of high density. A possible solution can be adopting the attention module to only enforce our density regularization on the important patches. (2) patch correspondence. Using representation at patch level provides more samples than image level. But our method also faces the same limitation as patch-based methods [39, 20, 49]: the patches may not be well corresponded in some tasks. For example, when the first domain is the front face while the second domain is the face profiles, we need to learn the rotation mapping between two domains, which may cause patch-based methods to fail. A possible solution would be considering larger patches, i.e., increase the number of layer used to extract patch representations. Large patches ought to contain more global information and may address this issue. In summary, we propose a new method to address the unsupervised image translation problem. We test it on multiple tasks and they achieve best performance across tasks.

References

[1] Youssef Alami Mejjati, Christian Richardt, James Tompkin, Darren Cosker, and Kwang In Kim. Unsupervised attention-guided image-to-image translation. *Advances in neural information processing systems*, 31, 2018.

[2] Karim Armanious, Chenming Jiang, Marc Fischer, Thomas Küstner, Tobias Hepp, Konstantin Nikolaou, Sergios Gatidis, and Bin Yang. Medgan: Medical image translation using gans. *Computerized medical imaging and graphics*, 79:101684, 2020.

[3] Jens Behrmann, Will Grathwohl, Ricky TQ Chen, David Duvenaud, and Jörn-Henrik Jacobsen. Invertible residual networks. In *International Conference on Machine Learning*, pages 573–582. PMLR, 2019.

[4] Sagie Benaim and Lior Wolf. One-sided unsupervised domain mapping. *Advances in neural information processing systems*, 30, 2017.

[5] Mikołaj Bińkowski, Danica J Sutherland, Michael Arbel, and Arthur Gretton. Demystifying mmd gans. *arXiv preprint arXiv:1801.01401*, 2018.

[6] Yunjey Choi, Minje Choi, Munyoung Kim, Jung-Woo Ha, Sunghun Kim, and Jaegul Choo. Stargan: Unified generative adversarial networks for multi-domain image-to-image translation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 8789–8797, 2018.

[7] Yunjey Choi, Youngjung Uh, Jaejun Yoo, and Jung-Woo Ha. Stargan v2: Diverse image synthesis for multiple domains. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 8188–8197, 2020.

[8] Marius Cordts, Mohamed Omran, Sebastian Ramos, Timo Rehfeld, Markus Enzweiler, Rodrigo Benenson, Uwe Franke, Stefan Roth, and Bernt Schiele. The cityscapes dataset for semantic urban scene understanding. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 3213–3223, 2016.

[9] Longquan Dai and Jinhui Tang. iflowgan: An invertible flow-based generative adversarial network for unsupervised image-to-image translation. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2021.

[10] Nicola De Cao, Wilker Aziz, and Ivan Titov. Block neural autoregressive flow. In *Uncertainty in artificial intelligence*, pages 1263–1273. PMLR, 2020.

[11] Conor Durkan, Artur Bekasov, Iain Murray, and George Papamakarios. Neural spline flows. *Advances in neural information processing systems*, 32, 2019.

[12] Huan Fu, Mingming Gong, Chaohui Wang, Kayhan Batmanghelich, Kun Zhang, and Dacheng Tao. Geometry-consistent generative adversarial networks for one-sided unsupervised domain mapping. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 2427–2436, 2019.

[13] Will Grathwohl, Ricky TQ Chen, Jesse Bettencourt, Ilya Sutskever, and David Duvenaud. Ffjord: Free-form continuous dynamics for scalable reversible generative models. *arXiv preprint arXiv:1810.01367*, 2018.

[14] Aditya Grover, Christopher Chute, Rui Shu, Zhangjie Cao, and Stefano Ermon. Alignflow: Cycle consistent learning from multiple domains via normalizing flows. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 4028–4035, 2020.

[15] Aditya Grover, Manik Dhar, and Stefano Ermon. Flow-gan: Combining maximum likelihood and adversarial learning in generative models. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32, 2018.

[16] Junlin Han, Mehrdad Shoeiby, Lars Petersson, and Mohammad Ali Armin. Dual contrastive learning for unsupervised image-to-image translation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 746–755, 2021.

[17] Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. *Advances in neural information processing systems*, 30, 2017.

[18] Judy Hoffman, Eric Tzeng, Taesung Park, Jun-Yan Zhu, Phillip Isola, Kate Saenko, Alexei Efros, and Trevor Darrell. Cycada: Cycle-consistent adversarial domain adaptation. In *International conference on machine learning*, pages 1989–1998. PMLR, 2018.

[19] Emiel Hoogeboom, Rianne Van Den Berg, and Max Welling. Emerging convolutions for generative normalizing flows. In *International Conference on Machine Learning*, pages 2771–2780. PMLR, 2019.

[20] Xueqi Hu, Xinyue Zhou, Qiusheng Huang, Zhengyi Shi, Li Sun, and Qingli Li. Qs-attn: Query-selected attention for contrastive learning in i2i translation. *arXiv preprint arXiv:2203.08483*, 2022.

[21] Chin-Wei Huang, David Krueger, Alexandre Lacoste, and Aaron Courville. Neural autoregressive flows. In *International Conference on Machine Learning*, pages 2078–2087. PMLR, 2018.

[22] Xun Huang, Ming-Yu Liu, Serge Belongie, and Jan Kautz. Multimodal unsupervised image-to-image translation. In *Proceedings of the European conference on computer vision (ECCV)*, pages 172–189, 2018.

[23] Priyank Jaini, Kira A Selby, and Yaoliang Yu. Sum-of-squares polynomial flow. In *International Conference on Machine Learning*, pages 3009–3018. PMLR, 2019.

[24] Chanyong Jung, Gihyun Kwon, and Jong Chul Ye. Exploring patch-wise semantic relation for contrastive learning in image-to-image translation tasks. *arXiv preprint arXiv:2203.01532*, 2022.

[25] Junho Kim, Minjae Kim, Hyeonwoo Kang, and Kwanghee Lee. U-gat-it: Unsupervised generative attentional networks with adaptive layer-instance normalization for image-to-image translation. *arXiv preprint arXiv:1907.10830*, 2019.

[26] Taeksoo Kim, Moonsu Cha, Hyunsoo Kim, Jung Kwon Lee, and Jiwon Kim. Learning to discover cross-domain relations with generative adversarial networks. In *International conference on machine learning*, pages 1857–1865. PMLR, 2017.

[27] Durk P Kingma and Prafulla Dhariwal. Glow: Generative flow with invertible 1x1 convolutions. *Advances in neural information processing systems*, 31, 2018.

[28] Hugo Larochelle and Iain Murray. The neural autoregressive distribution estimator. In *Proceedings of the fourteenth international conference on artificial intelligence and statistics*, pages 29–37. JMLR Workshop and Conference Proceedings, 2011.

[29] Hsin-Ying Lee, Hung-Yu Tseng, Jia-Bin Huang, Maneesh Singh, and Ming-Hsuan Yang. Diverse image-to-image translation via disentangled representations. In *Proceedings of the European conference on computer vision (ECCV)*, pages 35–51, 2018.

[30] Ming-Yu Liu, Thomas Breuel, and Jan Kautz. Unsupervised image-to-image translation networks. *Advances in neural information processing systems*, 30, 2017.

[31] Qiao Liu, Jiaze Xu, Rui Jiang, and Wing Hung Wong. Density estimation using deep generative neural networks. *Proceedings of the National Academy of Sciences*, 118(15), 2021.

[32] Cheng Lu, Jianfei Chen, Chongxuan Li, Qiuhao Wang, and Jun Zhu. Implicit normalizing flows. *arXiv preprint arXiv:2103.09527*, 2021.

[33] Xudong Mao, Qing Li, Haoran Xie, Raymond YK Lau, Zhen Wang, and Stephen Paul Smolley. Least squares generative adversarial networks. In *Proceedings of the IEEE international conference on computer vision*, pages 2794–2802, 2017.

[34] Zak Murez, Soheil Kolouri, David Kriegman, Ravi Ramamoorthi, and Kyungnam Kim. Image to image translation for domain adaptation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 4500–4509, 2018.

[35] Ori Nizan and Ayellet Tal. Breaking the cycle-colleagues are all you need. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 7860–7869, 2020.

[36] Junier Oliva, Avinava Dubey, Manzil Zaheer, Barnabas Poczos, Ruslan Salakhutdinov, Eric Xing, and Jeff Schneider. Transformation autoregressive networks. In *International Conference on Machine Learning*, pages 3898–3907. PMLR, 2018.

[37] Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

[38] George Papamakarios, Theo Pavlakou, and Iain Murray. Masked autoregressive flow for density estimation. *Advances in neural information processing systems*, 30, 2017.

[39] Taesung Park, Alexei A Efros, Richard Zhang, and Jun-Yan Zhu. Contrastive learning for unpaired image-to-image translation. In *European Conference on Computer Vision*, pages 319–345. Springer, 2020.

[40] Xuning Shao and Weidong Zhang. Spatchgan: A statistical feature based discriminator for unsupervised image-to-image translation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 6546–6555, 2021.

[41] Benigno Uria, Marc-Alexandre Côté, Karol Gregor, Iain Murray, and Hugo Larochelle. Neural autoregressive distribution estimation. *The Journal of Machine Learning Research*, 17(1):7184–7220, 2016.

[42] Aaron Van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv e-prints*, pages arXiv–1807, 2018.

[43] Weilun Wang, Wengang Zhou, Jianmin Bao, Dong Chen, and Houqiang Li. Instance-wise hard negative example generation for contrastive learning in unpaired image-to-image translation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 14020–14029, 2021.

[44] Antoine Wehenkel and Gilles Louppe. Unconstrained monotonic neural networks. *Advances in neural information processing systems*, 32, 2019.

[45] Yanwu Xu, Shaoan Xie, Wenhao Wu, Kun Zhang, Mingming Gong, and Kayhan Batmanghelich. Maximum spatial perturbation consistency for unpaired image-to-image translation. *arXiv preprint arXiv:2203.12707*, 2022.

[46] Zili Yi, Hao Zhang, Ping Tan, and Minglun Gong. Dualgan: Unsupervised dual learning for image-to-image translation. In *Proceedings of the IEEE international conference on computer vision*, pages 2849–2857, 2017.

[47] Fisher Yu, Vladlen Koltun, and Thomas Funkhouser. Dilated residual networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 472–480, 2017.

[48] Yuan Yuan, Siyuan Liu, Jiawei Zhang, Yongbing Zhang, Chao Dong, and Liang Lin. Unsupervised image super-resolution using cycle-in-cycle generative adversarial networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition Workshops*, pages 701–710, 2018.

[49] Fangneng Zhan, Jiahui Zhang, Yingchen Yu, Rongliang Wu, and Shijian Lu. Modulated contrast for versatile image synthesis. *arXiv preprint arXiv:2203.09333*, 2022.

[50] Rui Zhang, Tomas Pfister, and Jia Li. Harmonic unpaired image-to-image translation. *arXiv preprint arXiv:1902.09727*, 2019.

[51] Yihao Zhao, Ruihai Wu, and Hao Dong. Unpaired image-to-image translation using adversarial consistency loss. In *European Conference on Computer Vision*, pages 800–815. Springer, 2020.

[52] Chuanxia Zheng, Tat-Jen Cham, and Jianfei Cai. The spatially-correlative loss for various image translation tasks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 16407–16417, 2021.

[53] Jun-Yan Zhu, Taesung Park, Phillip Isola, and Alexei A Efros. Unpaired image-to-image translation using cycle-consistent adversarial networks. In *Proceedings of the IEEE international conference on computer vision*, pages 2223–2232, 2017.

[54] Xiaojin Zhu, Zoubin Ghahramani, and John D Lafferty. Semi-supervised learning using gaussian fields and harmonic functions. In *Proceedings of the 20th International conference on Machine learning (ICML-03)*, pages 912–919, 2003.