Playing with Words, Improving with Rewards: Training Language Models for Creative Association

Abstract

Large Language Models (LLMs) are being applied to increasingly difficult problems and use cases. To navigate their vast solution spaces effectively, LLMs need to be creative. Yet the subjective nature of creativity and the limits of human judgment make training LLMs for creativity especially challenging. As a solution, we train LLMs on Codenames, a word-association game that exercises the two central axes of creativity, divergent and convergent thinking, while yielding objectively verifiable outcomes. This verifiability lets us bypass human judgment and train with Reinforcement Learning with Verifiable Rewards (RLVR). We train Qwen3-1.7B, 4B, and 8B models and evaluate them on ten creativity and four reasoning benchmarks. We find that the precision-diversity trade-off is scale-dependent: the 8B model prioritizes creativity over precision, while the 1.7B and 4B models gain reasoning precision at the cost of creativity. Concretely, the 8B model shows modest but consistent creativity gains (8 of 10 benchmarks) with only minor reasoning degradation, whereas the smaller models achieve substantial gains on reasoning tasks. Our study presents a scalable and effective solution to train LLMs for creativity.

1 Introduction

Large language models (LLMs) have advanced at a remarkable pace, expanding from fluent text generation to tackling challenging tasks such as solving complex mathematical problems to generating novel content (Bubeck et al., 2023; Ahn et al., 2024; Wu et al., 2026). Performance on these hard problems hinges on creativity, the capacity to navigate vast problem spaces and arrive at unconventional yet effective solutions (Yang et al., 2022; Beaty and Kenett, 2023; Tian et al., 2024). This exposes a central but unresolved question in contemporary AI research: how can we explicitly train LLMs to be genuinely creative, rather than merely hoping creativity emerges as a byproduct of scale?

A natural starting point comes from cognitive science, where human creativity has long been operationalized as an associative process over semantic memory (Beaty and Kenett, 2023; Mednick, 1962; Luchini et al., 2025). Novel ideas arise when distantly related concepts are combined into new, functional wholes. Computational and neurocognitive studies converge on a striking finding that highly creative individuals possess more densely connected semantic networks with shorter path distances between concepts, enabling the rapid linkage of remote ideas that underlie creative association (Kenett and Faust, 2019; Kenett et al., 2014). This architecture aligns with the principle of combinatorial creativity, where novelty emerges from the rearrangement and integration of existing knowledge components rather than from creation ex nihilo (Boden, 1998; Yang et al., 2022). LLMs, despite their architectural differences, also learn predominantly through association (Mikolov et al., 2013; Johnson et al., 2025; Barenholtz, 2026). This parallel motivates a concrete research question: can we systematically train LLMs to integrate the existing knowledge to improve not just creativity but complex problem-solving more broadly?

The central obstacle to training creativity directly is that creativity is inherently subjective (Vessel et al., 2018; Forthmann et al., 2017). Humans do not always agree on what constitutes creative work (Vessel et al., 2018; Cortes and Lawrence, 2021). We sidestep this difficulty (Casper et al., 2023) by turning to a structured environment where creative decision-making is inherent, but the outcomes of the decisions are objectively measurable: the word-association game Codenames. Codenames externalizes the two canonical stages of creative cognition — divergence (generating remote associations that span multiple concepts) and convergence (selecting the single best association that uniquely identifies the targets) — and grades each turn with an unambiguous outcome (Cropley, 2006). This

makes it an ideal testbed for putting an LLM's associative capacity under measurable pressure without the noise of subjective preference judgments.

In Codenames, a board of unrelated words is laid out, and a small subset is secretly designated as target words; the remaining words on the board, including some that must be actively avoided, are non-targets. One player, the spymaster, sees which words are targets and must produce a single clue word that points to as many targets as possible while steering teammates away from every non-target. The teammates, who see only the board, then guess which words the clue refers to. A good clue is semantically remote enough from the non-targets to disambiguate them, yet semantically close enough to several targets to link them through a shared latent dimension — a chair, an altar, and a stage might all be connected through the abstract concept of platform. Strong play, therefore, demands exactly the divergent-then-convergent associative leap that cognitive scientists identify as the core mechanism of creativity.

Casting creativity as a game with verifiable outcomes lets us bypass expensive human preference annotation entirely. Instead, we train with Reinforcement Learning with Verifiable Rewards (RLVR) (Guo et al., 2025), the paradigm that has recently driven step-change improvements in LLMs. Through RLVR training on Codenames, we fine-tune three Qwen3 models (1.7B, 4B, and 8B) to reorganize existing knowledge and discover unseen associations. We summarize our key contributions and findings below:

- **Creativity Training.** We cast creativity as a verifiable-reward game, train LLMs via RLVR without human annotation, and evaluate on ten creativity tasks and four reasoning benchmarks.
- **Precision-Diversity Trade-off.** We show this known trade-off is scale-dependent: smaller models gain reasoning precision at the cost of creativity, while the 8B model gains creativity with a slight precision loss.
- **Creativity Gains.** The 8B model shows modest but consistent creativity gains.
- **Reasoning Gains.** The 1.7B and 4B models show substantial gains on reasoning tasks.

2 Related Work

Improving LLM Creativity. Prior work has explored several routes toward more creative LLMs. A first line uses prompting and decoding strategies (Tian et al., 2024; Mehrotra et al., 2024; Nair et al., 2024; Summers-Stay et al., 2023; Franceschelli and Musolesi, 2024; Meister et al., 2023), including inference-time analogical reasoning that searches for cross-domain solutions (Shen et al., 2026). A second line uses multi-agent role-playing, such as the three-phase divergent-to-convergent ideation framework of Lu et al. (2024). A third line turns to learning: Fukuda et al. (2025) fine-tune on the Divergent Association Task and find gains only under specific conditions, while Ismayilzada et al. (2025) proposes CrPO, a preference-based alignment method optimizing novelty, diversity, and surprise on human creativity judgments. While some studies focus on data selection strategies to improve various dimensions of creativity (Lanchantin et al., 2025; Deshpande et al., 2025). Across these efforts, RLVR (Guo et al., 2025), the method most responsible for recent step-change gains and the most scalable since it needs no human preference annotation, remains unexplored as a route to creativity.

Games and Self-Improvement with RLVR. A core limitation of RLHF (Ouyang et al., 2022) is its dependence on human-curated data, which constrains scalability (Liu et al., 2025; Wang et al., 2025). Training LLMs on games through self-play with verifiable rewards (RLVR) holds the potential to address this bottleneck to a great extent (Schaul, 2024). A growing body of work has applied this paradigm across diverse environments, e.g., adversarial word games (Cheng et al., 2024), logic puzzles (Xie et al., 2025a; Wong et al., 2025), strategic board games (Hwang et al., 2025; Yuan et al., 2025), arcade-style visual games (Xie et al., 2025b; Tong et al., 2025), and zero-sum multi-turn games (Liu et al., 2025)—and a striking commonality is the consistent report of out-of-distribution (OOD) gains on reasoning benchmarks unrelated to the training games.

3 Method

3.1 Training Data

Game Environment We adopt Codenames, a word association game, as the training environment. The original board game places four sets of words on the board and involves two competing teams. Of these four sets, two are target sets, one assigned to each team. The remaining words form a neutral set and a single assassin word that ends the game. We simplify this setup by removing the neutral and

assassin words. This allows us to focus on a clean signal of word association, free from higher-level rules. Each team consists of one clue generator (the *Spymaster*) and one or more guess generators (the *Operatives*). Only the clue generator can see which target words belong to which team. Its goal is to find a common link, the clue, that connects multiple words in its team's target set. The guess generators, by contrast, cannot see how the separation between the two target sets. They have access to all words on the board along with the clue, and their goal is to deduce which words the clue refers to. Each team aims to correctly guess all of its target words before the opposing team.

In our training setup, we train a single LLM that plays the role of one team in the game environment. This is equivalent to having the LLM switch between both teams, intending to complete its assigned target set as quickly as possible while avoiding the words in the non-target set. In its natural form, Codenames for a single team is a multi-turn discussion. The clue generator has access to all context, while the guess generators cannot see the separation between the two target sets. These discussions can become extremely long. Thinking traces alone can easily reach several thousand tokens for a single turn. This increased length raises training cost and makes training instabilities more likely. To address this, we break the multi-turn discussions into multiple single-turn conversations. Specifically, we model clue generation and guess generation as single-turn tasks, and we strategically sample board positions to simulate every stage of the full end-to-end game.

More precisely, we model this training environment as a Markov Decision Process (MDP). Let w be any whitespace-separated English word that can be represented by one or more tokens in the LLM's vocabulary $\mathcal{V}$. Let $\mathcal{T}$ and $\mathcal{N}$ denote the target and non-target word sets, and let $\mathcal{B}$ denote the combined and shuffled set $\mathcal{T} \cup \mathcal{N}$. Let w_{clue} be a single whitespace-separable clue word, let $\mathcal{G}$ be the set of guesses, and g_{max} be the maximum number of allowed guesses in one chance. We represent the state set of the MDP as

$$\mathcal{S} = \{\mathcal{T}, \mathcal{N}, \mathcal{B}, w_{clue}, g_{max}\}. \quad (1)$$

During the clue generation task, $\mathcal{B}$, w_{clue}, g_{max} are null. During the guess generation task, $\mathcal{T}$ and $\mathcal{N}$ are empty. We define the action set as

$$\mathcal{A} = \{w_{clue}, \mathcal{T}_{selected}, \mathcal{G}\}. \quad (2)$$

During the clue generation task, the LLM generates w_{clue} for a subset of words in $\mathcal{T}$ i.e., $\mathcal{T}_{selected}$ (so $\mathcal{G} = \emptyset$). During the guess generation task, it generates only $\mathcal{G}$ (so $w_{clue} = \mathcal{T}_{selected} = \emptyset$). Note that, $\mathcal{T}_{selected} \subset \mathcal{T}$ and $1 \leq |\mathcal{T}_{selected}| = g_{max}$. We assume that the transition function $\mathcal{P}$ is not accessible for this MDP. In the following subsections, we present details on how we sample our state set and subsequently discuss details on reward functions.

Sampling State Set We loosely refer to both $\mathcal{B}$ and $\{\mathcal{T}, \mathcal{N}\}$ as board positions. The two differ in one important way: $\{\mathcal{T}, \mathcal{N}\}$ encodes the separation between $\mathcal{T}$ and $\mathcal{N}$, whereas $\mathcal{B}$ does not. Accordingly, $\{\mathcal{T}, \mathcal{N}\}$ is available only during clue generation, and $\mathcal{B}$ only during guess generation. A complete state also includes the clue word w_{clue}, which is required during guess generation. In a natural game, this clue would come from a preceding clue-generation turn. Because we train each turn as an independent single-turn task, no such preceding turn exists, so we must supply w_{clue} in advance. We therefore generate clue words automatically through a systematic three-step process.

- *Generate a Pool of Diverse Topics*: We begin by manually creating a seed list of 50 diverse topics, such as ocean, food, hobbies etc. With the help of Claude Opus, we then extend this list to roughly 1,000 unique topics. Each topic is a single whitespace-separable word that later serves as the clue in guess generation training examples.
- *Find Words Associated with Topics*: For each topic, we use Claude Opus to generate a list of directly associated words, which we stratify by frequency into common and rare words. For example, the topic *ocean* yields common words such as *tide*, *wave*, and *salt*, and rare words such as *pelagic*, *benthic*, and *halocline*. We store the top 10 common and 10 rare words per topic in a repository $\mathcal{R}$. For any topic t, $\mathcal{R}[t] = [W^{(t,c)}, W^{(t,r)}]$, where $W^{(t,c)}$ and $W^{(t,r)}$ are the common and rare words associated with t, and $|W^{(t,c)}| = |W^{(t,r)}| = 10$.
- *Sample State Sets*: To create a board position, we sample two topics, one for the words in $\mathcal{T}$ and one for the words in $\mathcal{N}$. This lets us maintain a coherent theme and a clear separation between the words on the board, which keeps the task tractable for LLMs, especially smaller ones. We then draw the size of each set independently from $[2, 6]$ (inclusive) and sample that many words

from the corresponding topic. Varying the set sizes lets us simulate the early and late game states encountered in a long single-turn progression. Finally, the topic word for $\mathcal{T}$ serves as the clue for the words in $\mathcal{T}$. Following this process, we sample the state sets (see Equation (1)) used to train the LLMs.

Difficulty of States When sampling the state sets, we apply four rules of increasing difficulty. Each rule changes only how the words in $\mathcal{T}$ are sampled, while the rule for $\mathcal{N}$ stays fixed. Let $t_{\mathcal{T}}$ and $t_{\mathcal{N}}$ denote the topics sampled for the target and non-target sets, and let $n_{\mathcal{T}} \sim U(2,6)$ and $n_{\mathcal{N}} \sim U(2,6)$ denote the number of words sampled for each set. The $n_{\mathcal{N}}$ non-target words are always drawn from the common pool $W^{(t_{\mathcal{N}},c)}$. The four rules control the target set as follows.

- *Simple*: all $n_{\mathcal{T}}$ words are drawn from the common pool $W^{(t_{\mathcal{T}},c)}$.

- *Moderate*: $\lfloor n_{\mathcal{T}}/2 \rfloor$ words are drawn from the common pool $W^{(t_{\mathcal{T}},c)}$, and the rest from the rare pool $W^{(t_{\mathcal{T}},r)}$.

- *Advanced*: all $n_{\mathcal{T}}$ words are drawn from the rare pool $W^{(t_{\mathcal{T}},r)}$.

- *Expert*: $\lfloor n_{\mathcal{T}}/2 \rfloor$ words are drawn from the rare pool $W^{(t_{\mathcal{T}},r)}$, and the rest from the common pool of the non-target topic, $W^{(t_{\mathcal{N}},c)}$.

We order the training data from the *Simple* rule to the *Expert* rule, forming a natural curriculum for the LLM. Intuitively, difficulty rises as target words shift from common to rare, and the *Expert* rule adds distractors that overlap with the non-target topic. Moreover, in all but the last rule, $\mathcal{T}_{selected} = \mathcal{T}$ and $g_{max} = |\mathcal{T}|$. In the case of the last rule, $\mathcal{T}_{selected} \subset \mathcal{T}$ and $g_{max} = \lfloor n_{\mathcal{T}}/2 \rfloor$.

Data Statistics Overall, we create 500 unique states per rule for each task, clue generation and guess generation. In total, this yields 4,000 examples, of which we use 3,680 for training and 320 for validation, balanced across rules and tasks. We represent our training dataset as a collection of $N = 3680$ examples,

$$\mathcal{D} = \{(\mathcal{T}, \mathcal{N}, w_{clue}, g_{max}, \mathcal{T}_{\text{sel}})_i\}_{i=1}^N, \quad (3)$$

where each tuple stores the target set $\mathcal{T}$, the non-target set $\mathcal{N}$, the precomputed clue w_{clue}, the maximum number of guesses g_{max}, and the selected target subset $\mathcal{T}_{\text{sel}} \subseteq \mathcal{T}$ that the clue is intended for. For exact prompts for each task, see Appendix A.

3.2 Reward Function

Clue Generation Task Reward Let π be the actor policy we train, which maps a state to an action over the spaces defined in Equation (1) and 2 ($\pi : \mathcal{S} \to \mathcal{A}$). To reward a generated clue, we run the full clue-then-guess loop and score the resulting guesses, which proceeds in three stages. First, in the clue generation state $\mathcal{S} = \{\mathcal{T}, \mathcal{N}\}$, the actor samples a clue for $\mathcal{T}_{selected}$ words conditioned on the separated target and non-target sets, $w_{clue}, \mathcal{T}_{selected} \sim \pi(\mathcal{T}, \mathcal{N})$. Second, we form the shuffled board $\mathcal{B} = \mathcal{T} \cup \mathcal{N}$ from the same two sets, pair it with the clue, and a bound for guesses $g_{max} = |\mathcal{T}_{selected}|$ to obtain the guess generation state $\mathcal{S} = \{\mathcal{B}, w_{clue}, g_{max}\}$, and pass this to a frozen judge policy ϕ that returns a set of guesses, $\mathcal{G} \sim \phi(\mathcal{B}, w_{clue}, g_{max})$. Third, we compare the guesses against the ground-truth sets $\mathcal{T}$ and $\mathcal{N}$ to compute a scalar reward $r = f(\mathcal{T}, \mathcal{N}, \mathcal{G})$.

The reward credits guesses that hit the target set and penalizes guesses that hit the non-target set or fall outside the board entirely:

$$f(\mathcal{T}, \mathcal{N}, \mathcal{G}) = \frac{|\mathcal{T} \cap \mathcal{G}|}{|\mathcal{T}|} - \frac{|\mathcal{N} \cap \mathcal{G}|}{|\mathcal{N}|} - \frac{|\mathcal{G} \setminus (\mathcal{T} \cup \mathcal{N})|}{|\mathcal{G}|} \quad (4)$$

The first term is the fraction of target words correctly recovered, the second is the fraction of non-target words mistakenly selected, and the third is the fraction of guesses that appear in neither set. The reward is therefore bounded in $[-2, 1]$, attaining its maximum of 1 only when the judge recovers every target word and selects nothing else.

Guess Generation Task Reward For guess generation, the actor policy produces guesses conditioned on the board and an a priori clue stored in our dataset, $\mathcal{G} \sim \pi(\mathcal{B}, w_{clue})$. For each guess generation example, we also retain the sets $\mathcal{T}$ and $\mathcal{N}$ that compose $\mathcal{B}$. After generation, we therefore have $\mathcal{T}$, $\mathcal{N}$, and $\mathcal{G}$, which is everything needed to compute the reward using the same function as before (Equation (4)).

Reward for Response Format Before computing the task reward, we run format checks on each response. For instance, a clue must not appear on the board. We apply 6 such checks to clues and 4 to guesses (see Appendix B). The task reward (Equation (4)) is computed only when all task-specific checks pass; otherwise, the reward is -1.

Summary   In summary, we cast our problem as a finite-horizon MDP,

$$\mathcal{M} = (\mathcal{S}, \mathcal{A}, \mathcal{P}, f), \qquad (5)$$

where $\mathcal{S}$ and $\mathcal{A}$ are the state and action sets (Equations (1) and (2)), $\mathcal{P}$ is the non-accessible transition function and f is the reward function. The horizon is bounded by the model's maximum generation length. To solve this problem, we adopt Reinforcement Learning with Verifiable Rewards (RLVR) (Guo et al., 2025), using the objective and hyperparameters of Yu et al. (2026) without modification. For a state $s \sim \mathcal{D}$, we sample a group of G responses $\{o_i\}_{i=1}^G \sim \pi_{\theta_{old}}(\cdot \mid s)$, where each response o_i is an action (a clue or a set of guesses) decoded as a token sequence. The policy is optimized by maximizing

$$\mathcal{J}(\theta) = \mathbb{E}_{\substack{s \sim \mathcal{D} \\ \{o_i\} \sim \pi_{\theta_{old}}}} \left[\frac{1}{\sum_i |o_i|} \sum_{i=1}^G \sum_{t=1}^{|o_i|} \mathcal{L}_{i,t}(\theta) \right], \qquad (6)$$

where the per-token surrogate is

$$\mathcal{L}_{i,t}(\theta) = \min\Big(r_{i,t} \hat{A}_i, \ \text{clip}\big(r_{i,t}, \ 1{-}\varepsilon_l, \ 1{+}\varepsilon_h\big) \hat{A}_i \Big) \qquad (7)$$

Here $r_{i,t} = \frac{\pi_\theta(o_{i,t} \mid s, o_{i,<t})}{\pi_{\theta_{old}}(o_{i,t} \mid s, o_{i,<t})}$ is the token-level importance ratio, and $\hat{A}_i = (R_i - \bar{R})/\sigma_R$ is the group-normalized advantage, with $R_i = f(\cdot)$ the response reward and $\bar{R}, \sigma_R$ the mean and standard deviation of $\{R_j\}_{j=1}^G$.

4   Experimental Setup

4.1   Training

Models.   We train three models from the Qwen3 family: Qwen3-1.7B, Qwen3-4B, and Qwen3-8B (Yang et al., 2025). For every model, we perform full-parameter fine-tuning in full bf16 precision, without parameter-efficient adapters or quantization. All training is implemented with the VeRL library (Sheng et al., 2025). For the judge model $\phi(\cdot)$, we use Google Gemini Flash-2.5, suitable for large inference volume.

Training Algorithm and Hyperparameters. We optimize the DAPO objective (Equation (6)) with the GRPO advantage estimator. For each prompt, we sample a group of $G = 32$ responses, and each optimization step uses a batch of 32 prompts, giving $32 \times 32 = 1024$ rollouts per step.

We train for 2 epochs over the 3,680 training examples, yielding 230 parameter update steps. We use a constant learning rate of 1×10^{-6} with no warmup or decay. Following DAPO, we decouple clipping bounds with $\varepsilon_l = 0.2$ and $\varepsilon_h = 0.28$ (clip-higher), aggregate the policy loss at the token level (token-mean), and remove the KL term entirely, using neither KL loss nor KL reward shaping.

Dynamic Sampling and Length Control.   We adopt DAPO's dynamic sampling: we oversample and discard prompt groups whose responses all receive the same reward, since such groups yield zero advantage and no learning signal, and we allow up to 10 oversampling batches per step to refill the effective batch. We cap the prompt length at $2,048$ tokens and the response length at $16,384$ tokens. We also apply DAPO's soft overlong reward shaping with a $4,096$-token buffer. Responses longer than 12,288 tokens incur a penalty that grows linearly with the overage and reaches its maximum at the 16384-token cap. This discourages runaway generations while avoiding hard truncation of otherwise useful reasoning traces.

Infrastructure.   We run experiments on a heterogeneous pool of GPUs based on availability on the Vast-AI platform. We train and evaluate Qwen3-1.7B on a single A100, train Qwen3-4B on $4\times$RTX 5090 and $4\times$RTX Pro 6000 GPUs, and train and evaluate Qwen3-8B on $4\times$RTX Pro 6000 GPUs. Approximately, the training runs for 4B and 8B models took 40-50 hours on $4\times$ RTX Pro 6000 GPUs, and the 1.7B model took ≈ 25 hours on $4\times$ RTX 5090. In total, we spent approximately $3,000$ USD for training and evaluation experiments.

4.2   Evaluation

Creativity Evaluation   We evaluate on a broad suite of creativity tasks. The suite spans divergent and convergent thinking, figurative language and humor understanding, creative problem solving, the generation of long and coherent narratives, and conceptual understanding. We group the tasks below by the construct that each one targets, and for each task, we describe its goal, a representative instance, and the metric we report.

- *Divergent thinking: AUT* (Alternate Uses Test) (Guilford, 1956) and *DAT* (Divergent Association Test) (Olson et al., 2021) probe the ability to produce many distinct ideas. In AUT, we prompt the model to generate 5 creative and novel uses

Dataset – Metric	1.7B			4B			8B		
	Base	Our FT	Δ	Base	Our FT	Δ	Base	Our FT	Δ
AUT – Creativity	2.5000	2.5000	=	2.8600	2.9333	+	**3.3733**	3.3533	−
AUT – Coherence	4.5667	4.7400	+	4.8733	4.7200	−	4.8800	**4.9000**	+
DAT – DSI	0.5519	0.5422	−	0.5381	0.5284	−	0.5837	**0.5886**	+
DAT – Vocab. Size	0.2010	0.1010	−	0.1580	0.1060	−	0.2590	**0.2830**	+
RAT – Accuracy	0.0554	0.0590	+	0.1144	0.1255	+	0.3432	**0.3506**	+
MUNCH (Gen.) – Recall	0.3539	0.3654	+	0.4423	0.4585	+	0.4653	**0.4785**	+
MUNCH (Sent. Implicit) – Accuracy	0.4202	0.4223	+	0.5040	0.4899	−	0.5282	**0.5436**	+
MUNCH (Sent. Mword) – Accuracy	0.4182	0.4189	+	0.5516	0.5489	−	0.5724	**0.5744**	+
MUNCH (Word) – Accuracy	0.6079	0.6046	−	0.5416	**0.5757**	+	0.5503	0.5664	+
NY-Caption (Explanation) – Score	2.0891	2.1859	+	2.4869	2.5499	+	2.7757	**2.8510**	+
NY-Caption (Matching) – Accuracy	0.4062	0.4326	+	0.5362	0.5392	+	0.5712	**0.5957**	+
MacGyver – Efficiency	3.3548	3.4921	+	4.1064	4.1642	+	4.3557	**4.3722**	+
MacGyver – Feasibility	2.8562	2.9691	+	2.7184	2.7479	+	2.9327	**2.9412**	+
NYT Connections – Group Acc.	0.2998	0.3217	+	0.5038	0.4889	−	**0.6794**	0.6515	−
NYT Connections – Perfect Match	0.1150	0.1166	+	0.2991	0.2761	−	**0.5077**	0.4724	−
CWT – Creativity	2.2794	2.1471	−	2.6714	2.6714	=	2.6714	**2.8571**	+
CWT – Coherence	4.0588	4.0882	+	4.4429	4.2571	−	4.7000	**4.7714**	+
CWT – DSI	0.7460	0.7433	−	0.7544	0.7567	+	0.7588	**0.7612**	+
CWT – MTLD	54.4920	54.0313	−	64.9288	66.8451	+	73.0871	**76.2662**	+
EQ-Bench – Creativity	31.4200	31.7100	+	39.2500	39.6100	+	48.2000	**48.8400**	+
Grounding (Non-sensorimotor) – Spearman-r	0.5605	0.5553	−	0.4827	0.4568	−	0.4902	**0.4990**	+
Grounding (Sensory) – Spearman-r	0.4142	0.4326	+	0.5843	0.5940	+	0.6056	**0.6131**	+
Grounding (Motor) – Spearman-r	0.4196	0.4104	−	0.5311	0.5258	−	0.5104	**0.5345**	+

Table 1: **Creativity Evaluation.** Performance on 10 creativity evaluation tasks across three models, Qwen3-1.7B, 4B and 8B. The "Base" and "Our FT" columns present results for off-the-shelf and trained (230 steps) checkpoints. The "Δ" column indicates whether our proposed training method improves (+) the base model or not (−).

for an everyday object, such as a belt or a brick. We score the five uses for creativity and coherence with an LLM judge, where higher is better. In DAT, we prompt the model to list 10 words that are as semantically dissimilar from one another as possible, and we sample 100 such lists. For each list, we compute Divergent Semantic Integration (DSI) (Johnson et al., 2023) and report the average over all 100 lists. We additionally report vocabulary size, the fraction of unique words across the full pool of 10×100 words. DSI captures semantic diversity, and vocabulary size captures lexical diversity; higher values are better for both.

- *Convergent thinking: RAT* (Remote Association Test) (Bowden and Jung-Beeman, 2003) evaluates the complementary ability to converge on a single associative link between distant concepts. Each instance presents three remote cue words, and the model must produce one word that associates with all three. We report accuracy against the reference answers.

- *Figurative language and humor understanding: MUNCH* (Metaphor Understanding Challenge) (Tong et al., 2024) evaluates whether a model can interpret metaphorical language. It comprises three multiple-choice variants and one open-ended generation variant. We report accuracy for the multiple-choice variants and recall for the generation variant. The *New Yorker Caption Contest* (Hessel et al., 2023) evaluates humor understanding. Each instance provides a description of a cartoon together with a caption. In the explanation task, the model must explain why the caption is funny, which we score with an LLM judge. In the matching task, the model selects the most suitable caption from several options, which we score with accuracy.

- *Creative problem solving: MacGyver* (Tian et al., 2024) presents an everyday problem together with a limited set of available tools, and the model must devise a creative solution that re-

spects the tool constraints. Following Tian et al. (2024), we score solutions for feasibility and efficiency with an LLM judge. *NYT Connections* (Lopez et al., 2025) requires partitioning 16 words into four themed groups of four. We report group-level accuracy and the exact-match rate over all four groups.

- *Narrative generation: CWT* (Creative Writing Test) (Prabhakaran et al., 2014) and *EQ-Bench* (Emotional Quotient Benchmark) (Paech, 2023) target short- and long-form story writing, respectively. In CWT, we give the model three words and ask for a 5-sentence story that uses all three, and we score the story for creativity and coherence with an LLM judge. In addition, we report DSI (semantic diversity) and MTLD (Measure of Textual Lexical Diversity) for the generated stories. In EQ-Bench, the model receives a topic and a narrative outline that specifies required details, for example *"Describe the gladiator's weapon of choice and its significance to them"*, and must produce a 1,000-word story. We use LLM-Judge to measure creativity and report the final score on a 0-100 scale, where higher is better.

- *Conceptual grounding:* Because grounded concept representations underpin both near and far associations, we test whether associative training strengthens them using the *LLM-Grounding* dataset of Xu et al. (2025). Each instance asks the model to rate the association between a word and a conceptual axis on an integer scale. To bound the evaluation cost, we subsample 1,000 examples from the original dataset, balanced across concepts and human ratings. We compute Spearman's correlation between the model's integer ratings and the mean human ratings, where higher values indicate stronger conceptual grounding.

Reasoning Evaluation To anchor our creativity findings against well-established ability, we evaluate the same checkpoints on a standard reasoning suite covering arithmetic, competition mathematics, graduate-level science, and multi-step narrative reasoning. All tasks are run through the `lighteval` (Habib et al., 2023) library with the original task formulations and metrics, and are evaluated 0-shot. *GSM8K* (Cobbe et al., 2021) comprises grade-school word problems requiring multi-step arithmetic, scored by extractive-match accuracy. *AIME 2024* and *AIME 2025* (Patel et al.,

2024) are olympiad mathematics problems with a single integer answer, also scored by extractive match. *GPQA-Diamond* (Rein et al., 2023) is a four-way multiple-choice benchmark of Google-proof graduate-level questions in physics, chemistry, and biology, scored by accuracy.

Prompts and Evaluation Hyperparameters We provide exact prompts for each dataset and for all uses of LLM-Judge models (Claude Opus 4.7) in Appendix D. We also provide an easy-to-read table that lists all tasks, related hyperparameters, and metrics in Appendix C.

5 Results

We first present our findings on the creativity tasks, and then on the reasoning benchmarks. Apart from RAT and NYT Connections, none of our evaluation tasks resemble the training task, and therefore probe the out-of-domain (OOD) transfer of our proposed setup.

5.1 Creativity Evaluation

The largest model yields modest but consistent creativity improvements (Table 1). Qwen3-8B improves on 20 of 23 creativity metrics after fine-tuning and is the only model to exhibit gains in divergent diversity, with both DAT DSI ($0.584 \rightarrow 0.589$) and vocabulary size ($0.259 \rightarrow 0.283$) increasing.

The 8B model regresses on NYT Connections despite its similarity to Codenames. Inspecting the traces reveals an overthinking tendency. With much longer reasoning, the model violates task constraints, particularly the "*one-word-one-group*" rule, with 17 violations for the tuned model versus 7 for the base model. This drives the performance regression. Confirming this diagnosis, with thinking disabled, the two checkpoints (base and the finetuned version) reach an identical perfect match (0.2730 vs. 0.2730) and group accuracy within 0.002 (0.4172 vs. 0.4187). On the 227 difficulty-tagged puzzles (easy < 3, medium $= 3$, hard ≥ 4), the tuned model degrades on every bucket with thinking on but improves on every bucket without it. The regression is, therefore, an overthinking artifact. For AUT, we find no convincing trace-level evidence explaining the minor drop in creativity.

Across scales, all three models improve on 8 of 23 dataset-metric pairs, and at least two improve on 15. Gains hold at every scale for humor understanding, creative problem solving (MacGyver), story

Dataset – Metric	1.7B			4B			8B		
	Base	Our FT	Δ	Base	Our FT	Δ	Base	Our FT	Δ
AIME24 – Accuracy	0.4333	0.5667	+	0.6667	0.7000	+	0.8000	0.6667	−
AIME25 – Accuracy	0.2667	0.3333	+	0.5667	0.6333	+	0.7333	0.7333	=
GPQA-Diamond – Accuracy	0.4141	0.4697	+	0.5253	0.5455	+	0.6111	0.5909	−
GSM8K – Extractive Match	0.8810	0.8923	+	0.9431	0.9416	−	0.9507	0.9500	−

Table 2: **Reasoning Evaluation.** Performance on 4 reasoning evaluation tasks across three models, Qwen3-1.7B, 4B and 8B. The "Base" and "Our FT" columns present results for off-the-shelf and trained (230 steps) checkpoints. The "Δ" column indicates whether our proposed training method improves (+) the base model or not (−).

writing, and metaphor understanding (MUNCH recall). Convergent search on RAT also improves across the board, though absolute accuracy stays low for the smaller models. At the smaller scales, DAT vocabulary collapses (1.7B: $0.20 \rightarrow 0.10$; 4B: $0.16 \rightarrow 0.11$), a known side effect of RLVR and RLHF training (Wu et al., 2025; Kirk et al., 2024). To trace the cause, we measure average per-token entropy over the full response (thinking and final answer) alongside response length; because per-token entropy in autoregressive LMs reduces with context length, the two interact. The FT-over-base length ratios are $\times 2.45$, $\times 1.52$, and $\times 1.36$, with entropy ratios $\times 1.07$, $\times 0.69$, and $\times 1.03$ (1.7B, 4B, 8B). At 1.7B, a 7% entropy gain is swamped by a $\times 2.45$ length increase. At 4B, entropy collapses (-31%) while length still grows ($\times 1.52$). Only at 8B do modest entropy and length growth coincide, and DSI holds.

5.2 Reasoning Evaluation

The reasoning results in Table 2 mirror the creativity picture in reverse: the gains concentrate in the smaller models. Qwen3-1.7B improves on all four, raising AIME24 accuracy from 0.43 to 0.57 and GPQA-Diamond by 5.6 points ($0.414 \rightarrow 0.470$). Qwen3-4B improves on three, with only a marginal decrement on GSM8K ($0.9431 \rightarrow 0.9416$). The 8B model moves in the opposite direction: it holds steady on AIME25 and GSM8K but drops by roughly 2 points on GPQA and 13 points on AIME24 ($0.80 \rightarrow 0.67$).

5.3 Synthesis: Associative Learning Meets RLVR

Taken together, the creativity and reasoning results reveal a coherent pattern shaped by the interaction of associative learning (Codenames) with RLVR (DAPO). RLVR is known to carry a diversity-precision trade-off (Wu et al., 2025), and we observe exactly this, except its direction flips with scale. The 8B model shifts toward diversity, gaining creativity at a slight cost to math and science precision, while the smaller models shift the other way, gaining robustly on precision-bound reasoning without consistently gaining creativity. We speculate that associative learning sets this split (Johnson et al., 2025): easy problems are solvable by association alone, so smaller models earn reward by precisely solving the problems now within reach, while larger models, already solving these, pursue diversity for the harder ones. A length test on the 1.7B responses to the reasoning dataset supports this. Its traces lengthen overall (ratio 1.42) but stay shorter on problems it newly solves (1.13) and fall below the base model on AIME (< 1.0), converging faster on likely easy problems. Together, these results point to a method that pays off at every scale. One associative-RLVR recipe, with no task-specific tuning, delivers substantial reasoning gains in smaller models and consistent creativity gains in larger ones. The scale-dependent trade-off is a key property that we highlight with our results: *each model gains where it can*.

6 Conclusion

We set out to train creativity without human judgment, and found that a single game, Codenames, reshapes what a model improves at depending on its size. The same associative reward sharpens reasoning in smaller models and broadens creativity in the largest, exposing a scale-dependent precision-diversity trade-off rather than a uniform win. Concretely, fine-tuning improved the 8B model across the large majority of creativity metrics. The 1.7B and 4B models instead showed strong improvements in math and science reasoning. A single, verifiable word game thus provides a practical and scalable lever for strengthening LLMs.

Limitations

Our work has several limitations. First, we simplify Codenames by removing the neutral and assassin words and by decomposing multi-turn play into single-turn tasks, which may omit dynamics present in the full game. Training with fewer constraints to satisfy may also explain the constraint failures we observed on NYT Connections, where the tuned model violated task rules it was never pressured to respect. Second, our training combines a chain-of-thought scaffold with generic RLVR, and, primarily due to experimental cost, we do not run an ablation that isolates the associative component; part of the observed effect may therefore stem from RLVR or the reasoning format alone. Third, we include no representational probe, which could clarify how distant concepts interact internally and how that interaction shapes the final generations. Fourth, many creativity metrics rely on an LLM judge, and the clue-generation reward itself depends on a frozen judge model, so judge bias may influence both training and evaluation. Finally, several reasoning results rest on small test sets, notably AIME with its 30 problems, where a shift of only a few items changes accuracy substantially; these deltas should be read with corresponding caution.

Ethics Statement

Our work focuses on training language models for creative association, improving the diversity of outputs in open-ended tasks. As our results show, creative diversity can trade off against precision, so we caution against using our models or data where factual accuracy is critical, such as medical advice, legal reasoning, or scientific fact-checking. Our training data consists of topics and word lists generated synthetically with a large language model and contains no personal, sensitive, or human-subjects data, and all evaluation benchmarks are publicly available and used in accordance with their licenses. Because several rewards and creativity metrics rely on LLM judges, which can encode cultural and linguistic biases, and because our tasks are English-centric, our results may not generalize across languages or contexts. A key motivation behind our approach is accessibility: by relying on verifiable rewards rather than human preference annotation, using a small training set, and showing gains on models as small as 1.7B, we aim to lower the resource barrier for creativity research. Finally, while we used proprietary language models (Claude Opus) to assist in experimental setup, data curation, and manuscript editing, no portion was generated entirely by an LLM; all content was written, reviewed, and edited by the authors.

References

Janice Ahn, Rishu Verma, Renze Lou, Di Liu, Rui Zhang, and Wenpeng Yin. 2024. Large language models for mathematical reasoning: Progresses and challenges. In *Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics: Student Research Workshop*, pages 225–237.

Elan Barenholtz. 2026. World properties without world models: Recovering spatial and temporal structure from co-occurrence statistics in static word embeddings. *arXiv preprint arXiv:2603.04317*.

Roger E Beaty and Yoed N Kenett. 2023. Associative thinking at the core of creativity. *Trends in cognitive sciences*, 27(7):671–683.

Margaret A Boden. 1998. Creativity and artificial intelligence. *Artificial intelligence*, 103(1-2):347–356.

Edward M Bowden and Mark Jung-Beeman. 2003. Normative data for 144 compound remote associate problems. *Behavior research methods, instruments, & computers*, 35(4):634–639.

Sébastien Bubeck, Varun Chandrasekaran, Ronen Eldan, Johannes Gehrke, Eric Horvitz, Ece Kamar, Peter Lee, Yin Tat Lee, Yuanzhi Li, Scott Lundberg, and 1 others. 2023. Paper review:'sparks of artificial general intelligence: Early experiments with gpt-4'.

Stephen Casper, Xander Davies, Claudia Shi, Thomas Krendl Gilbert, Jérémy Scheurer, Javier Rando, Rachel Freedman, Tomasz Korbak, David Lindner, Pedro Freire, and 1 others. 2023. Open problems and fundamental limitations of reinforcement learning from human feedback. *arXiv preprint arXiv:2307.15217*.

Pengyu Cheng, Yong Dai, Tianhao Hu, Han Xu, Zhisong Zhang, Lei Han, Nan Du, and Xiaolong Li. 2024. Self-playing adversarial language game enhances llm reasoning. *Advances in Neural Information Processing Systems*, 37:126515–126543.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, and 1 others. 2021. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*.

Corinna Cortes and Neil D Lawrence. 2021. Inconsistency in conference peer review: Revisiting the 2014 neurips experiment. *arXiv preprint arXiv:2109.09774*.

Arthur Cropley. 2006. In praise of convergent thinking. *Creativity research journal*, 18(3):391–404.

Vijeta Deshpande, Debasmita Ghose, John D Patterson, Roger E Beaty, and Anna Rumshisky. 2025. Diverse, not short: A length-controlled data selection strategy for improving response diversity of language models. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 33905–33926.

Boris Forthmann, Heinz Holling, Nima Zandi, Anne Gerwig, Pınar Çelik, Martin Storme, and Todd Lubart. 2017. Missing creativity: The effect of cognitive workload on rater (dis-) agreement in subjective divergent-thinking scores. *Thinking Skills and Creativity*, 23:129–139.

Giorgio Franceschelli and Mirco Musolesi. 2024. Creative beam search: Llm-as-a-judge for improving response generation. *arXiv preprint arXiv:2405.00099*.

So Fukuda, Hayato Ogawa, Kaito Horio, Daisuke Kawahara, and Tomohide Shibata. 2025. Building Japanese creativity benchmarks and applying them to enhance LLM creativity. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 4: Student Research Workshop)*, pages 939–957, Vienna, Austria. Association for Computational Linguistics.

Joy Paul Guilford. 1956. The structure of intellect. *Psychological bulletin*, 53(4):267.

Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Peiyi Wang, Qihao Zhu, Runxin Xu, Ruoyu Zhang, Shirong Ma, Xiao Bi, and 1 others. 2025. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*.

Nathan Habib, Clémentine Fourrier, Hynek Kydlíček, Thomas Wolf, and Lewis Tunstall. 2023. Lighteval: A lightweight framework for llm evaluation.

Jack Hessel, Ana Marasović, Jena D Hwang, Lillian Lee, Jeff Da, Rowan Zellers, Robert Mankoff, and Yejin Choi. 2023. Do androids laugh at electric sheep? humor "understanding" benchmarks from the new yorker caption contest. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 688–714.

Dongyoon Hwang, Hojoon Lee, Jaegul Choo, Dongmin Park, and Jongho Park. 2025. Can large language models develop strategic reasoning? post-training insights from learning chess. *arXiv preprint arXiv:2507.00726*.

Mete Ismayilzada, Antonio Laverghetta Jr, Simone A Luchini, Reet Patel, Antoine Bosselut, Lonneke Van Der Plas, and Roger Beaty. 2025. Creative preference optimization. *arXiv preprint arXiv:2505.14442*.

Dan R Johnson, James C Kaufman, Brendan S Baker, John D Patterson, Baptiste Barbot, Adam E Green, Janet van Hell, Evan Kennedy, Grace F Sullivan, Christa L Taylor, and 1 others. 2023. Divergent semantic integration (dsi): Extracting creativity from narratives with distributional semantic modeling. *Behavior research methods*, 55(7):3726–3759.

Tamar Johnson, Mathilde ter Veen, Rochelle Choenni, Han van der Maas, Ekaterina Shutova, and Claire E Stevenson. 2025. Do large language models solve verbal analogies like children do? In *Proceedings of the 29th Conference on Computational Natural Language Learning*, pages 627–639.

Yoed N Kenett, David Anaki, and Miriam Faust. 2014. Investigating the structure of semantic networks in low and high creative persons. *Frontiers in human neuroscience*, 8:407.

Yoed N Kenett and Miriam Faust. 2019. A semantic network cartography of the creative mind. *Trends in cognitive sciences*, 23(4):271–274.

Robert Kirk, Ishita Mediratta, Christoforos Nalmpantis, Jelena Luketina, Eric Hambro, Edward Grefenstette, and Roberta Raileanu. 2024. Understanding the effects of rlhf on llm generalisation and diversity. In *International Conference on Learning Representations*, volume 2024, pages 20620–20653.

Jack Lanchantin, Angelica Chen, Shehzaad Dhuliawala, Ping Yu, Jason Weston, Sainbayar Sukhbaatar, and Ilia Kulikov. 2025. Diverse preference optimization. *arXiv preprint arXiv:2501.18101*.

Bo Liu, Leon Guertler, Simon Yu, Zichen Liu, Penghui Qi, Daniel Balcells, Mickel Liu, Cheston Tan, Weiyan Shi, Min Lin, and 1 others. 2025. Spiral: Self-play on zero-sum games incentivizes reasoning via multi-agent multi-turn reinforcement learning. *arXiv preprint arXiv:2506.24119*.

Angel Yahir Loredo Lopez, Tyler McDonald, and Ali Emami. 2025. Nyt-connections: A deceptively simple text classification task that stumps system-1 thinkers. In *Proceedings of the 31st International Conference on Computational Linguistics*, pages 1952–1963.

Li-Chun Lu, Shou-Jen Chen, Tsung-Min Pai, Chan-Hung Yu, Hung-yi Lee, and Shao-Hua Sun. 2024. Llm discussion: Enhancing the creativity of large language models via discussion framework and role-play. *arXiv preprint arXiv:2405.06373*.

Simone A Luchini, James C Kaufman, Benjamin Goecke, Oliver Wilhelm, Yoed N Kenett, Daisy Lei, Mathias Benedek, Janet G van Hell, and Roger E Beaty. 2025. Creativity supports learning through associative thinking. *npj Science of Learning*, 10(1):42.

Sarnoff Mednick. 1962. The associative basis of the creative process. *Psychological review*, 69(3):220.

Pronita Mehrotra, Aishni Parab, and Sumit Gulwani. 2024. Enhancing creativity in large language models through associative thinking strategies. *arXiv preprint arXiv:2405.06715*.

Clara Meister, Tiago Pimentel, Gian Wiher, and Ryan Cotterell. 2023. Locally typical sampling. *Transactions of the Association for Computational Linguistics*, 11:102–121.

Tomas Mikolov, Ilya Sutskever, Kai Chen, Greg S Corrado, and Jeff Dean. 2013. Distributed representations of words and phrases and their compositionality. *Advances in neural information processing systems*, 26.

Lakshmi Nair, Evana Gizzi, and Jivko Sinapov. 2024. Creative problem solving in large language and vision models - what would it take? In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 11978–11994, Miami, Florida, USA. Association for Computational Linguistics.

Jay A Olson, Johnny Nahas, Denis Chmoulevitch, Simon J Cropper, and Margaret E Webb. 2021. Naming unrelated words predicts creativity. *Proceedings of the National Academy of Sciences*, 118(25):e2022340118.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, and 1 others. 2022. Training language models to follow instructions with human feedback. *Advances in neural information processing systems*, 35:27730–27744.

Samuel J Paech. 2023. Eq-bench: An emotional intelligence benchmark for large language models. *arXiv preprint arXiv:2312.06281*.

Bhrij Patel, Souradip Chakraborty, Wesley A Suttle, Mengdi Wang, Amrit Singh Bedi, and Dinesh Manocha. 2024. Aime: Ai system optimization via multiple llm evaluators. *arXiv preprint arXiv:2410.03131*.

Ranjani Prabhakaran, Adam E Green, and Jeremy R Gray. 2014. Thin slices of creativity: Using single-word utterances to assess creative cognition. *Behavior research methods*, 46(3):641–659.

David Rein, Betty Li Hou, Asa Cooper Stickland, Jackson Petty, Richard Yuanzhe Pang, Julien Dirani, Julian Michael, and Samuel R Bowman. 2023. Gpqa: A graduate-level google-proof q&a benchmark. *arXiv preprint arXiv:2311.12022*.

Tom Schaul. 2024. Boundless socratic learning with language games. *arXiv preprint arXiv:2411.16905*.

Andrew Shen, Shaul Druckmann, and James Zou. 2026. Unlocking llm creativity in science through analogical reasoning. *arXiv preprint arXiv:2605.11258*.

Guangming Sheng, Chi Zhang, Zilingfeng Ye, Xibin Wu, Wang Zhang, Ru Zhang, Yanghua Peng, Haibin Lin, and Chuan Wu. 2025. Hybridflow: A flexible and efficient rlhf framework. In *Proceedings of the Twentieth European Conference on Computer Systems*, pages 1279–1297.

Douglas Summers-Stay, Clare R. Voss, and Stephanie M. Lukin. 2023. Brainstorm, then select: a generative language model improves its creativity score. In *The AAAI-23 Workshop on Creative AI Across Modalities*.

Yufei Tian, Abhilasha Ravichander, Lianhui Qin, Ronan Le Bras, Raja Marjieh, Nanyun Peng, Yejin Choi, Thomas L Griffiths, and Faeze Brahman. 2024. Macgyver: Are large language models creative problem solvers? In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 5303–5324.

Jingqi Tong, Jixin Tang, Hangcheng Li, Yurong Mou, Ming Zhang, Jun Zhao, Yanbo Wen, Fan Song, Jiahao Zhan, Yuyang Lu, and 1 others. 2025. Game-rl: Synthesizing multimodal verifiable game data to boost vlms' general reasoning. *arXiv preprint arXiv:2505.13886*.

Xiaoyu Tong, Rochelle Choenni, Martha Lewis, and Ekaterina Shutova. 2024. Metaphor understanding challenge dataset for llms. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 3517–3536.

Edward A Vessel, Natalia Maurer, Alexander H Denker, and G Gabrielle Starr. 2018. Stronger shared taste for natural aesthetic domains than for artifacts of human culture. *Cognition*, 179:121–131.

Qinsi Wang, Bo Liu, Tianyi Zhou, Jing Shi, Yueqian Lin, Yiran Chen, Hai Helen Li, Kun Wan, and Wentian Zhao. 2025. Vision-zero: Scalable vlm self-improvement via strategic gamified self-play. *arXiv preprint arXiv:2509.25541*.

Zhen Hao Wong, Jingwen Deng, Runming He, Zirong Chen, Qijie You, Hejun Dong, Hao Liang, Chengyu Shen, Bin Cui, and Wentao Zhang. 2025. Logicpuzzlerl: cultivating robust mathematical reasoning in llms via reinforcement learning. *arXiv preprint arXiv:2506.04821*.

Fang Wu, Weihao Xuan, Ximing Lu, Mingjie Liu, Yi Dong, Zaid Harchaoui, and Yejin Choi. 2025. The invisible leash: Why rlvr may or may not escape its origin. *arXiv preprint arXiv:2507.14843*.

Yuning Wu, Jiahao Mei, Ming Yan, Chenliang Li, Shaopeng Lai, Yuran Ren, Zijia Wang, Ji Zhang, Mengyue Wu, Qin Jin, and 1 others. 2026. Writing-bench: A comprehensive benchmark for generative writing. *Advances in Neural Information Processing Systems*, 38.

Tian Xie, Zitian Gao, Qingnan Ren, Haoming Luo, Yuqian Hong, Bryan Dai, Joey Zhou, Kai Qiu, Zhirong Wu, and Chong Luo. 2025a. Logic-rl: Unleashing llm reasoning with rule-based reinforcement learning. *arXiv preprint arXiv:2502.14768*.

Yunfei Xie, Yinsong Ma, Shiyi Lan, Alan Yuille, Junfei Xiao, and Chen Wei. 2025b. Play to generalize: Learning to reason through game play. *arXiv preprint arXiv:2506.08011*.

Qihui Xu, Yingying Peng, Samuel A Nastase, Martin Chodorow, Minghua Wu, and Ping Li. 2025. Large language models without grounding recover non-sensorimotor but not sensorimotor features of human concepts. *Nature human behaviour*, 9(9):1871–1886.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, and 1 others. 2025. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*.

Wenjing Yang, Adam E Green, Qunlin Chen, Yoed N Kenett, Jiangzhou Sun, Dongtao Wei, and Jiang Qiu. 2022. Creative problem solving in knowledge-rich contexts. *Trends in Cognitive Sciences*, 26(10):849–859.

Qiying Yu, Zheng Zhang, Ruofei Zhu, Yufeng Yuan, Xiaochen Zuo, Yu Yue, Weinan Dai, Tiantian Fan, Gaohong Liu, Lingjun Liu, and 1 others. 2026. Dapo: An open-source llm reinforcement learning system at scale. *Advances in Neural Information Processing Systems*, 38:113222–113244.

Huining Yuan, Zelai Xu, Zheyue Tan, Xiangmin Yi, Mo Guang, Kaiwen Long, Haojia Hui, Boxun Li, Xinlei Chen, Bo Zhao, and 1 others. 2025. Marshal: Incentivizing multi-agent reasoning via self-play with strategic llms. *arXiv preprint arXiv:2510.15414*.

A Training Prompts

In this section, we provide the exact prompts used in our data for Codenames RLVR training.

System Prompt

```
You are an AI assistant that uses a
    ↪ structured Chain of Thought (CoT)
    ↪ approach to answer queries
    ↪ accurately and concisely.
Follow these steps in order:
1. **Think** - Identify what the problem is
    ↪ asking and outline your initial
    ↪ approach.
2. **Reason** - Work through the problem
    ↪ step by step, keeping each step
    ↪ focused and atomic.
3. **Reflect** - Check your reasoning for
    ↪ errors, gaps, or improvements.
4. **Adjust** - If your reflection
    ↪ identified an issue, explicitly
    ↪ correct it here. If no issues were
```

```
    ↪ found, state that clearly.
5. **Output** - Provide your final answer.
    ↪ This must be fully self-contained
    ↪ and readable without any context
    ↪ from the sections above.

---
Use the following format exactly:
---
<thinking>
[What is the problem asking? What is your
    ↪ initial approach?]
</thinking>

<reasoning>
[Step-by-step reasoning. Each step should be
    ↪ atomic and clearly follow from the
    ↪ previous one. Add as many steps as
    ↪ needed.]
</reasoning>

<reflection>
[Review your reasoning. Are there errors,
    ↪ missing cases, or better approaches?
    ↪ Be critical.]
</reflection>

<adjustment>
[If reflection found an issue: restate the
    ↪ corrected reasoning here.
If no issues were found: explicitly state "
    ↪ No adjustments needed."]
</adjustment>

<output>
[Your final, concise, self-contained answer.
    ↪ If uncertain, state your
    ↪ uncertainty clearly.]
</output>

---
Rules:
- All five sections must always appear in
    ↪ order.
- Only use information given in the problem.
    ↪ Flag missing information rather
    ↪ than assuming.
- Do not state conclusions before completing
    ↪ your reasoning.
- If considering multiple approaches,
    ↪ evaluate each against the original
    ↪ question.
- If uncertain after reflection, say so in <
    ↪ output> rather than guessing.
---
```

User Prompt (Clue Gen.)

```
Codenames Clue Generation Task: You are
    ↪ given a [Target-Set] and a [Non-
    ↪ Target-Set] of words.
Generate a single-word clue that connects to
    ↪ as many [Target-Set] words as
    ↪ possible while avoiding any
    ↪ association with [Non-Target-Set]
    ↪ words.
```

```
"Connection" is intentionally broad:
    ↪ semantic, conceptual, thematic,
    ↪ associative, phonetic, cultural, any
    ↪  defensible link counts.

Objective:
  - Maximize the number of [Target-Set]
    ↪ words your clue connects to (you may
    ↪  select as few as one).
  - Minimize any plausible connection
    ↪ between your clue and ANY [Non-
    ↪ Target-Set] word, under any common
    ↪ interpretation of the clue.
  - When these goals conflict, weigh the
    ↪ trade-off carefully and thoughtfully.
    ↪

Clue constraints (violating any of these
    ↪ makes the clue invalid):
  - Must be exactly one real English word (
    ↪ no proper nouns, no hyphenated or
    ↪ compound words, no made-up words).
  - Must NOT appear in either set.
  - Must NOT be a morphological variant (
    ↪ inflection, derivation),
    ↪ abbreviation, or direct translation
    ↪ of any word in either set.
    Example: if SWIM is in a set, SWIMMING,
    ↪ SWIMMER, SWAM are all invalid.

Strategy:
  1. Brainstorm several candidate clues.
  2. For each candidate, mentally check it
    ↪ against every word in BOTH sets.
  3. Discard any candidate that has a
    ↪ plausible link to a [Non-Target-Set]
    ↪  word, even under uncommon meanings.
  4. Among the remaining candidates, choose
    ↪ the one that connects to the most [
    ↪ Target-Set] words.

---

Respond using exactly this format:
[CODENAMES-CLUE-START]
[Clue]: <single-word clue>
[Selected-Targets]: <list of target words
    ↪ your clue relates to, e.g., [WORD1,
    ↪ WORD2]>
[CODENAMES-CLUE-END]

---
Here are the word sets:
[Target-Set]: REFRACT, LENS
[Non-Target-Set]: TAIL, SING
```

1047

User Prompt (Guess Gen.)

```
Codenames Guess Generation Task: You are
    ↪ given a single-word [Clue] and a
    ↪ list of [All-Words] on the board.
Your task is to guess which words the clue-
    ↪ giver intended by listing words from
    ↪  [All-Words] by their connection to
    ↪ the [Clue].
```

1048

```
"Connection" is intentionally broad:
    ↪ semantic, conceptual, thematic,
    ↪ associative, phonetic, cultural, any
    ↪  defensible link counts.

Objective:
  - Identify the words in [All-Words] that
    ↪ the clue-giver most plausibly
    ↪ intended with [Clue].
  - Return up to [Max-Guesses] guesses,
    ↪ ordered from most confident to least
    ↪  confident.
  - You may return fewer than [Max-Guesses]
    ↪ if you are not confident in
    ↪ additional guesses.

Strategy:
  1. For each word in [All-Words], assess
    ↪ how strongly it connects to [Clue].
  2. Consider ALL possible interpretations
    ↪ of [Clue], the clue-giver may be
    ↪ using an uncommon meaning, thematic
    ↪ link, or lateral association.
  3. Rank candidates by connection strength.
    ↪  Include a word only if you believe
    ↪ the clue-giver plausibly chose [Clue
    ↪ ] to point to it.
  4. Be especially cautious with lower-
    ↪ ranked guesses, each additional
    ↪ guess carries increasing risk of
    ↪ selecting an unintended word.

---

Respond using exactly this format:
[CODENAMES-GUESS-START]
[Guesses]: [first guess, second guess, ...]
[CODENAMES-GUESS-END]

---
Here are the word sets:
[All-Words]: BLADE, FEEL, GARDEN, LOSS
[Clue]: FROND
[Max-Guesses]: 2
```

1049

B Checks Performed on the Generated Responses

Before the calculation of the reward, we first perform a comprehensive validity check on the generated responses. In Table 3, we provide a list of all checks.

C Evaluation Dataset Catalog

In this section, we provide a catalog of dataset-specific details and hyperparameters, refer to Table 4.

1050
1051
1052
1053
1054
1055
1056
1057
1058
1059

Task	Check
Clue generation	
Response Format	Clue tags (`[CODENAMES-CLUE-START]`, `[CODENAMES-CLUE-END]`, `[Clue]`, `[Selected-Targets]`) are present in the generated response
Single Word	Clue is a single white-space separable English word.
No Hyphen	Clue does not have a hyphen
Non-Board Word	Clue must not be present in the existing words ($\mathcal{B}$) on the board.
Morphological Variant	Clue must not be a morphological variant of the existing words ($\mathcal{B}$) on the board.
Selected Targets	Clue is generated for 1 or more words present in the target word set $\mathcal{T}$
Valid Selected Targets	Selected target words must be present in the target word set $\mathcal{T}$
Guessing	
Response Format	Guess tags (`[CODENAMES-GUESS-START]`, `[CODENAMES-GUESS-END]`, `[Guesses]`) are present in the generated response.
Non-empty	There must be at least one guess generated by the model.
Non-Board Word	Generated guesses must be present on the board ($\mathcal{B}$).
Bound	Generated guesses must be less than the maximum number ($g_{max} = \mathcal{T}_{selected}$) provided in the input prompt.

Table 3: Format and basic validity check on the generated responses. These checks are applied before the reward calculation.

Table 4: Per-dataset evaluation configuration. The *Generation* column lists the policy-model sampling parameters used at evaluation time (temperature T, nucleus p, top-k, number of samples per item n, and in-context examples k-shot). When a task uses an LLM-as-a-Judge, the judge sampling parameters are listed in italics on a second line. For all custom (creativity) tasks the policy model is run in *thinking* mode (Qwen3 chat-template default) with `top_p` and `top_k` unset so the model's recommended thinking-mode defaults apply; for all reasoning tasks (`lighteval`) the policy is sampled in thinking mode with the default choices $T=0.6$, $p=0.95$, $n=1$, k-shot$=0$, and a 32,768-token generation budget. The judge model for all custom tasks is `Claude Opus-4.7`.

Dataset	Goal (what it measures)	Size	Generation type	Generation configuration	Metrics
Creativity tasks					
AUT	Divergent thinking: five novel uses per everyday object.	15	Open-ended	$T=1.0$, p=none, k=none, $n=10$, k-shot$=0$ *Judge: $T=0.0$, $p=0.95$, $n=1$*	LLM-judge for creativity and coherence.
DAT	Divergent thinking: ten maximally distant nouns.	1	Open-ended	$T=1.0$, p=none, k=none, $n=100$, k-shot$=0$ *(no judge)*	DSI; vocabulary size.
RAT	Convergent semantic search: one word linking three cues.	271	Open-ended (single word)	$T=1.0$, p=none, k=none, $n=1$, k-shot$=0$ *(no judge)*	Exact-match accuracy.
CWT	Narrative creativity: short story using three cue words.	7	Open-ended	$T=1.0$, p=none, k=none, $n=10$, k-shot$=0$ *Judge: $T=0.0$, $p=0.95$, $n=1$*	DSI; LLM-judge for creativity and coherence; Measure of Textual Lexical Diversity (MTLD).
EQ-Bench CW v3	Long-form creative writing across genres.	32	Open-ended (~1000 words)	$T=1.0$, p=none, k=none, $n=3$, k-shot$=0$ *Judge: $T=0.0$, $p=0.95$, $n=1$*	22-criterion rubric score (0–100).
MacGyver	Tool-use creativity: stepwise plan from a constrained tool inventory.	1,683	Open-ended	$T=1.0$, p=none, k=none, $n=1$, k-shot$=0$ *Judge: $T=0.0$, $p=0.95$, $n=1$*	LLM-judge feasibility / efficiency.
MUNCH (word)	Metaphor: 4-way MCQ word substitution.	1,492	MCQ (A/B/C/D)	$T=1.0$, p=none, k=none, $n=1$, k-shot$=0$ *(no judge)*	Accuracy (chance 25%).
MUNCH (sent-impl)	Metaphor: 4-way MCQ implicit sentence paraphrase.	1,492	MCQ (A/B/C/D)	$T=1.0$, p=none, k=none, $n=1$, k-shot$=0$ *(no judge)*	Accuracy (chance 25%).
MUNCH (sent-mword)	Metaphor: 4-way MCQ paraphrase with metaphorical-word marker.	1,492	MCQ (A/B/C/D)	$T=1.0$, p=none, k=none, $n=1$, k-shot$=0$ *(no judge)*	Accuracy (chance 25%).
MUNCH (gen)	Metaphor: open-ended one-word literal replacement.	2,953	Open-ended (single word)	$T=1.0$, p=none, k=none, $n=1$, k-shot$=0$ *(no judge)*	Recall@1 vs. human reference set.
NYC matching	Humor: 5-way MCQ identifying winning caption from description.	2,691	MCQ (A–E)	$T=1.0$, p=none, k=none, $n=1$, k-shot$=0$ *(no judge)*	Accuracy (chance 20%).
NYC ranking	Humor: 2-way MCQ funnier-of-two caption.	2,616	MCQ (A/B)	$T=1.0$, p=none, k=none, $n=1$, k-shot$=0$ *(no judge)*	Accuracy (chance 50%; overall, NY-editorial, crowd-rated).
NYC explanation	Humor: free-form explanation of a winning caption.	651	Open-ended (2–3 sentences)	$T=1.0$, p=none, k=none, $n=1$, k-shot$=0$ *Judge: $T=0.0$, $p=0.95$, $n=1$*	LLM-judge (1–5).
NYT Connections	Deliberate combinatorial grouping: 16 words → 4 themed groups.	652	Open-ended (4×4 partition)	$T=1.0$, p=none, k=none, $n=1$, k-shot$=0$ *(no judge)*	Perfect-match; group accuracy.

Continued on next page

Dataset	Goal (what it measures)	Size	Generation type	Generation configuration	Metrics
LLM-Grounding	Word–concept alignment: rate words on 18 psycholinguistic dimensions.	1,000	Open-ended (integer rating)	T=1.0, p=none, k=none, n=4, k-shot=0 *(no judge)*	Spearman ρ vs. human norms.

Reasoning tasks (`lighteval`)

Dataset	Goal (what it measures)	Size	Generation type	Generation configuration	Metrics
GSM8K	Grade-school multi-step arithmetic.	1,319	Open-ended	T=0.6, p=0.95, k=none, n=1, k-shot=0	Extractive-match.
AIME 2024	High-school olympiad math (integer answer).	30	Open-ended (boxed integer)	T=0.6, p=0.95, k=none, n=1, k-shot=0	Extractive-match.
AIME 2025	High-school olympiad math (integer answer).	30	Open-ended (boxed integer)	T=0.6, p=0.95, k=none, n=1, k-shot=0	Extractive-match.
GPQA-Diamond	Graduate-level science MCQ (physics, chemistry, biology).	198	MCQ (A–D)	T=0.6, p=0.95, k=none, n=1, k-shot=0	Accuracy (chance 25%).
MuSR murder-myst.	Multi-step suspect identification from narrative.	250	MCQ (2-way)	T=0.6, p=0.95, k=none, n=1, k-shot=0	Accuracy (chance 50%).
MuSR object-plac.	Theory-of-mind: predict object search location.	256	MCQ (4-way)	T=0.6, p=0.95, k=none, n=1, k-shot=0	Accuracy (chance 25%).
MuSR team-alloc.	Constraint satisfaction: assign roles to candidates.	250	MCQ (3-way)	T=0.6, p=0.95, k=none, n=1, k-shot=0	Accuracy (chance $\sim$33%).

D Evaluation Prompts

In this section, we provide the exact prompts used for evaluation on various creativity and reasoning datasets.

Alternate Uses Test (AUT)

```
Prompt:

[Task Description]: For this task, you'll be
    ↪  asked to come up with as many
    ↪ original and creative uses for an
    ↪ object as you can.
The goal is to come up with creative ideas,
    ↪ which are ideas that strike people
    ↪ as clever, unusual, interesting,
    ↪ uncommon, humorous, innovative, or
    ↪ different.
You must provide exactly five (5) uses for
    ↪ the object.
---
Your final answer should be in the following
    ↪  format:
[Answer-Start]
[Use-1]: <less than 5 sentences describing
    ↪ the first use>
[Use-2]: <less than 5 sentences describing
    ↪ the second use>
...
[Use-5]: <less than 5 sentences describing
    ↪ the fifth use>
[Answer-End]
---

[Object]: belt

--------------------------

Example response

[Use-1]: A belt can be transformed into a
    ↪ portable plant hanger by attaching
    ↪ small hooks to its loops, allowing
    ↪ it to suspend potted plants from
    ↪ ceilings or doorframes.
[Use-2]: Use the belt as a makeshift drum by
    ↪  securing a hollow object (like a
    ↪ bucket) to its buckle and striking
    ↪ it with sticks for rhythmic beats
    ↪ during gatherings.
[Use-3]: Attach the belt to a skateboard or
    ↪ wheelchair to create a makeshift
    ↪ harness, enabling users to propel
    ↪ themselves with a push-and-pull
    ↪ motion.
[Use-4]: Convert the belt into a temporary
    ↪ fire-starting tool by rubbing the
    ↪ leather against a flint or steel (if
    ↪  dry) to generate sparks.
[Use-5]: Use the belt as a dog training tool
    ↪  by attaching a small leash to its
    ↪ buckle, allowing it to guide pets
    ↪ during outdoor activities.
```

AUT - Judge Prompt (Creativity)

```
Prompt:

You are an expert judge evaluating the
    ↪ CREATIVITY and DIVERSITY of proposed
uses for an everyday object.
You will be given:
[Problem]: The task instructions and the
    ↪ object.
[Response]: Five proposed uses for that
    ↪ object.

Judge ONLY creativity and diversity --
    ↪ ignore grammar and writing mechanics:
    ↪
  - Originality: are the uses clever,
    ↪ unusual, and surprising, rather than
    obvious everyday uses of the object?
  - Diversity: do the five uses span
    ↪ genuinely different ideas, rather
    ↪ than
    being minor variations on a single theme
    ↪ ?
  - Validity: each use must be a real,
    ↪ physically plausible use of the
    actual object. Uses that are irrelevant
    ↪ to the object or impossible do
    not count as creative.

Scoring (1-5):
5 -- Five distinct, highly original uses;
    ↪ all valid and clearly varied.
4 -- Mostly original and varied uses, with a
    ↪  clear creative element.
3 -- Uses are valid but mostly conventional,
    ↪  or several overlap in idea.
2 -- Largely obvious uses, much repetition,
    ↪ or several invalid uses.
1 -- No discernible creativity, or few/no
    ↪ valid uses.

Provide a brief rationale (2-4 sentences),
    ↪ then:
[Score]: <number from 1 to 5>

[Problem]: <task instructions and object
    ↪ label>

[Response]: <model's five proposed uses>

--------------------------

(A second judge pass with an analogous
    ↪ COHERENCE rubric scores the same
    ↪ response on
writing mechanics. Both passes use Google
    ↪ gemini-2.5-flash at T=0.0, top_p
    ↪ =0.95, n=1.)
```

Divergent Association Test (DAT)

```
Prompt:

[Task description]: Please generate 10 words
    ↪  that are as different from each
    ↪  other as possible, in all meanings
    ↪  and uses of the words.
Rules:
- Only single words in English. Only nouns (
    ↪  e.g., things, objects, concepts).
- No proper nouns (e.g., no specific people
    ↪  or places).
- No specialized vocabulary (e.g., no
    ↪  technical terms).
Make a list of these 10 words, without any
    ↪  repetition.
---
Your final answer should be in the following
    ↪  format:
[Answer-Start]
[Answer]: word-1, word-2, ..., word-10
[Answer-End]
---

--------------------------

Example response

star, mountain, chair, spoon, book, love,
    ↪  time, freedom, smoke, fruit
```

Remote Association Test (RAT)

```
Prompt:

You will be given three words. Find a single
    ↪  word that associates with all three
    ↪  words.

For example: 'cottage', 'swiss', 'cake' -> '
    ↪  cheese' (cottage cheese, swiss
    ↪  cheese, cheesecake).

Words: cottage / swiss / cake

---
Answer format: Your answer must be a single
    ↪  word.
[Answer-Start]
[Answer]: <solution word>
[Answer-End]
---

--------------------------

Example response

cheese
```

Creative Writing Test (CWT)

```
Prompt:

[Task Description]: For this task, you will
    ↪  write a very short story. You will
    ↪  be given 3 words, and must write a
    ↪  story that includes all 3 words.
    ↪  Your story should be about 5
    ↪  sentences long.
Use your imagination and be creative when
    ↪  writing your story. But, also be
    ↪  sure your story makes sense.
---
Your final answer should be in the following
    ↪  format:
[Answer-Start]
[Answer]: <a short story, about 5 sentences
    ↪  long, that includes all 3 words>
[Answer-End]
---

[Words]: stamp, letter, send

--------------------------

Example response

Elena found an old stamp hidden in her
    ↪  grandmother's drawer, its design
    ↪  shimmering with forgotten magic. She
    ↪   wrote a letter to a distant friend,
    ↪   her words filled with longing. As
    ↪  she prepared to send it, the stamp
    ↪  glowed, sealing the letter in a
    ↪  burst of light. The letter floated
    ↪  through the air, carrying her
    ↪  message across the world. When her
    ↪  friend received it, they smiled,
    ↪  knowing it had been sent by a heart
    ↪  full of hope.
```

CWT - Judge Prompt (Creativity)

```
Prompt:

You are an expert judge evaluating the
    ↪  CREATIVITY of a very short story.
You will be given:
[Problem]: The task instructions and the
    ↪  three required words.
[Response]: A short story that should weave
    ↪  in all three words.

Judge ONLY creativity -- ignore grammar,
    ↪  spelling, and writing mechanics:
  - Originality: is the premise or idea
    ↪  fresh and unexpected, not cliched?
  - Imagination: are the characters, setting
    ↪  , or events inventive?
```

```
    - Engagement: is the story interesting,
      ↪ with a narrative arc or twist?
    - Use of the three words: are they woven
      ↪ in naturally and inventively,
      rather than dropped in mechanically? A
      ↪ story that ignores one or more
      of the required words cannot score above
      ↪  2.

Scoring (1-5):
5 -- Highly original and imaginative; the
      ↪ three words are woven in cleverly.
4 -- Creative and engaging, with a clear
      ↪ inventive element.
3 -- Competent but conventional; a
      ↪ predictable idea.
2 -- Largely cliched or flat, or a required
      ↪ word feels forced or missing.
1 -- No discernible creativity, or required
      ↪ words are ignored.

Provide a brief rationale (2-4 sentences),
      ↪ then:
[Score]: <number from 1 to 5>

[Problem]: <task instructions and the three
      ↪ cue words>

[Response]: <model's short story>

---------------------------

(A second judge pass with a COHERENCE rubric
      ↪  scores the same response on prose
mechanics. Both passes use gemini-2.5-flash
      ↪ at T=0.0, top_p=0.95, n=1.)
```

1070

EQ-Bench Creative Writing v3

```
Prompt:

Historical Fiction: Write a scene from a
      ↪ story set during the height of the
      ↪ Roman Empire, focusing on a slice of
      ↪  a day in the life of a gladiator.
      ↪ Do not write a combat scene. Use
      ↪ sensory details to capture the
      ↪ sights, sounds, and smells of
      ↪ ancient Rome. Explore the gladiator'
      ↪ s thoughts and emotions. The story
      ↪ should also touch on the larger
      ↪ political and social issues of the
      ↪ time period. The piece should feel
      ↪ like a slice of a larger story.
      ↪ Describe the gladiator's weapon of
      ↪ choice and its significance to them.
      ↪  First person, past tense, 1000
      ↪ words.

---------------------------

Example response (truncated; full generation
      ↪  ~1000 words)
```

1071

```
**The Weight of the Spear**

The first thing I notice is the scent of
      ↪ sweat and iron, clinging to the air
      ↪ like a shroud. I'm still in my cot,
      ↪ the thin linen sheets damp from the
      ↪ night's perspiration, when the sun
      ↪ spills through the cracks in the
      ↪ arena's wooden roof. Its warmth is
      ↪ sharp, almost cruel, as if the gods
      ↪ themselves are watching me through
      ↪ the cracks, judging. I stretch my
      ↪ limbs, the stiffness in my back a
      ↪ familiar companion, and roll my
      ↪ shoulders. The sand beneath my feet
      ↪ is cool, gritty, and already
      ↪ beginning to burn where my toes
      ↪ press into it.

I rise, my body groaning in protest, and
      ↪ reach for the waterskin slung beside
      ↪  my cot. The water is lukewarm, flat,
      ↪  and smells of something I can't
      ↪ quite name -- like the sweat of a
      ↪ hundred men and the decay of the
      ↪ arena floor. I drink deeply, the
      ↪ liquid running down my throat like
      ↪ the last drop of a promise. My eyes
      ↪ flick to the spear leaning against
      ↪ the wall, its wooden shaft polished
      ↪ smooth by years of use, the iron tip
      ↪  gleaming dully in the light. It's
      ↪ my weapon, my inheritance, the only
      ↪ thing I have that feels like it
      ↪ belongs to me. My father gave it to
      ↪ me before he was sold into slavery,
      ↪ his hands trembling as he passed it
      ↪ down. He said it was a Thracian gift,
      ↪  a symbol of my people's courage. I
      ↪ used to believe that.

[...continues for ~700 more words spanning
      ↪ the training yard, the social
      ↪ commentary on slavery and the Roman
      ↪ political system, and the gladiator'
      ↪ s reflection on whether the spear
      ↪ truly represents his people or only
      ↪ his servitude.]
```

1072

EQ-Bench - Judge Prompt

```
Prompt:

You are an expert evaluator of creative
      ↪ writing. Read the writing prompt and
      ↪  the candidate story below, then
      ↪ judge the story's overall creativity
      ↪  using the four criteria below. Each
      ↪  criterion is defined at four
      ↪ quality levels (Novice = 1,
      ↪ Apprentice = 2, Proficient = 3,
      ↪ Exceptional = 4).

[Criteria]
```

1073

1. Originality & Imagination
   - 4 (Exceptional): The plot features
     ↪ highly original, unpredictable
     ↪ twists. The core concept avoids
     ↪ clichs, offering a unique
     ↪ perspective or inventive treatment
     ↪ of the theme.
   - 3 (Proficient): Contains several
     ↪ imaginative ideas, though the
     ↪ premise or progression may follow
     ↪ familiar narrative tropes.
   - 2 (Apprentice): Relies heavily on
     ↪ familiar clichs or predictable
     ↪ tropes. The narrative feels
     ↪ derivative rather than inspired.
   - 1 (Novice): Shows little to no evidence
     ↪ of creative thought. The story is
     ↪ overly basic or entirely mimics
     ↪ another well-known work.

2. Sensory Detail & Word Choice (Show, Don't
   ↪ Tell)
   - 4 (Exceptional): Word choice is
     ↪ sophisticated and deliberate. The
     ↪ author uses vivid imagery and
     ↪ figurative language to immerse the
     ↪ reader in the story-world.
   - 3 (Proficient): Uses effective
     ↪ descriptions to paint a clear
     ↪ picture, though some moments may
     ↪ rely on telling rather than showing.
   - 2 (Apprentice): Lacks descriptive
     ↪ language. Relies on repetitive
     ↪ vocabulary or generalized statements
     ↪ rather than sensory details.
   - 1 (Novice): Little to no strength in
     ↪ vocabulary or description. The
     ↪ writing is flat and unengaging.

3. Character & Conflict Development
   - 4 (Exceptional): Characters are
     ↪ memorable, complex, and respond to
     ↪ events in highly unique ways. The
     ↪ conflict is compelling and drives an
     ↪ organic narrative arc.
   - 3 (Proficient): Main characters are
     ↪ adequately developed, and the
     ↪ primary conflict is clear and easily
     ↪ understood.
   - 2 (Apprentice): Characters lack depth
     ↪ or distinguishable personality
     ↪ traits. The conflict feels forced or
     ↪ uninteresting.
   - 1 (Novice): Characters are
     ↪ unidentifiable, and the central
     ↪ conflict is nonexistent or
     ↪ impossible to understand.

4. Narrative Arc & Pacing
   - 4 (Exceptional): Pacing is perfectly
     ↪ managed within the 1000-word
     ↪ constraint. Transitions between
     ↪ scenes are seamless, leading to an
     ↪ effective, satisfying resolution.
   - 3 (Proficient): Has a clear beginning,
     ↪ middle, and end. Ideas flow
     ↪ logically, though pacing may

     ↪ occasionally rush or drag.
   - 2 (Apprentice): Difficult to follow.
     ↪ Ideas or scenes feel randomly
     ↪ arranged, lacking clear transitions.
   - 1 (Novice): Disjointed structure. The
     ↪ story lacks a cohesive beginning,
     ↪ middle, or end.

[Writing Prompt]

{problem}

[Candidate Story]

{response}

[Instructions]

Weigh the four criteria together to form a
   ↪ single, comprehensive creativity
   ↪ judgment. Map the overall quality
   ↪ onto a 1-100 scale using this anchor:
   ↪
  - 1-25 = Novice (all/most criteria at
    ↪ level 1)
  - 26-50 = Apprentice (most criteria at
    ↪ level 2)
  - 51-75 = Proficient (most criteria at
    ↪ level 3)
  - 76-100 = Exceptional (most criteria at
    ↪ level 4)

Be a strict but fair critic. Penalize
   ↪ cliched plots, telling-not-showing,
   ↪ flat characters, and incoherent
   ↪ pacing. Do not penalize NSFW or dark
   ↪ content; assess it on its merits.

Output format (exactly):

[Analysis]
<3-5 sentences covering the four criteria>

[Score]: <single integer between 1 and 100>

(The 22 criterion scores are aggregated into
   ↪ a Rubric Score on a 0-100 scale.
Judge is Claude Opus 4.7 at T=0.0, top_p
   ↪ =0.95, n=1, max_tokens=8192.)

MacGyver

Prompt:

[Task Description]: In this task you will be
   ↪ presented with a problem. Your task
   ↪ is to clearly understand the
   ↪ problem and provide a solution, if
   ↪ the problem is solvable. The
   ↪ solution you provide must be valid,
   ↪ feasible, efficient and must be
   ↪ presented in step-wise format (Step

```
           ↪ -1: ..., Step-2: ...). Use as few
           ↪ steps as possible and the answer
           ↪ should ideally be less than 100
           ↪ words. If you think the problem is
           ↪ not solvable, provide a very short
           ↪ and succinct justification.
---
Final answer format should be:
[SOLUTION-START]
[Solvable]: True/False
[Solution]: (only if solvable)
Step-1: one brief sentence ...
Step-2: one brief sentence ...
...
[Justification]: (only if not solvable)
[SOLUTION-END]
---

[Problem]: You spilled red wine on the hotel
       ↪  carpet and want to clean it up
       ↪ before the housekeeping staff
       ↪ reports this. Tools available: a
       ↪ bottle opener, a plastic cup, a
       ↪ toothbrush, a bottle of mineral
       ↪ water that is sealed shut, a pack of
       ↪  sugar, a white bath towel, a bar of
       ↪  soap, a hair dryer. How do you
       ↪ clean up the wine stain using only
       ↪ these items?

---------------------------

Example response

[Solvable]: True
[Solution]: Step-1: Use the white towel to
       ↪ blot and absorb as much wine as
       ↪ possible. Step-2: Open the mineral
       ↪ water bottle with the opener, pour
       ↪ into the cup, and mix with soap to
       ↪ create a cleaning solution. Step-3:
       ↪ Scrub the stain with the toothbrush
       ↪ and solution. Step-4: Blot again
       ↪ with the towel. Step-5: Dry with the
       ↪  hair dryer.
[Justification]:
```

MacGyver - Judge Prompt (Feasibility)

```
Prompt:

You are an expert judge evaluating the
       ↪ FEASIBILITY of a proposed solution
       ↪ to a problem.
You will be given:
[Problem]: The original problem statement (
       ↪ states whether it is solvable).
[Response]: The model-generated answer to
       ↪ evaluate.

Judge ONLY feasibility -- does the proposed
       ↪ solution actually work given the
       ↪ available tools? Ignore efficiency (
```

```
           ↪ judged separately).

Scoring (1-5):
5 -- Correct solvability call AND a fully
       ↪ feasible, logically correct solution
       ↪  (or a correct, sufficient
       ↪ justification when the problem is
       ↪ unsolvable).
4 -- Correct solvability call with a mostly
       ↪ feasible solution; minor gaps or
       ↪ unstated assumptions.
3 -- Correct solvability call but the
       ↪ solution has a clear feasibility
       ↪ flaw (missing step, mis-used tool)
       ↪ that could still be patched.
2 -- Major feasibility errors: the solution
       ↪ would not work as written.
1 -- Mis-identifies solvability (claims a
       ↪ solvable problem is unsolvable or
       ↪ vice-versa).

Provide a brief rationale (2-4 sentences),
       ↪ then:
[Score]: <number from 1 to 5>

[Problem]: <problem statement, including
       ↪ solvability label>

[Response]: <model's stepwise solution>

---------------------------

(A second judge pass with an EFFICIENCY
       ↪ rubric scores the same response on
       ↪ path
length. Both passes use gemini-2.5-flash at
       ↪ T=0.0, top_p=0.95, n=1.)
```

MUNCH - Word (4-way MCQ)

```
Prompt:

[Task Description]: Choose which of two
       ↪ words best replaces a highlighted
       ↪ metaphorical word in a sentence
       ↪ without changing the meaning. You
       ↪ will be given a sentence and two
       ↪ options; respond with a single
       ↪ letter.

Choose the option that can replace the
       ↪ highlighted word in the given
       ↪ sentence without changing the
       ↪ meaning.

Sentence: While he suggests in apocalyptic *
       ↪ tones* in The Problem of Method that
       ↪  this process of self-consciousness
       ↪ is at last beginning to take place,
       ↪ and that civil, foreign and colonial
       ↪  wars are becoming apparent as
       ↪ different forms of a single class
       ↪ struggle, Sartre also admits that
       ↪ the divorce between theory and
```

MUNCH - Judge Sentence (Implicit Paraphrase)

Prompt:

[Task Description]: Choose which of two
↪ sentences is a paraphrase of a given
↪ sentence. You will be given the
↪ original sentence and two
↪ alternatives; respond with a single
↪ letter.

Choose the sentence that is a paraphrase of
↪ the given sentence.

Original: While he suggests in apocalyptic
↪ tones in The Problem of Method that
↪ this process of self-consciousness
↪ is at last beginning to take place,
↪ and that civil, foreign and colonial
↪ wars are becoming apparent as
↪ different forms of a single class
↪ struggle, Sartre also admits that
↪ the divorce between theory and
↪ praxis which ensued under Stalinism
↪ has generally prevented any clear
↪ self-consciousness among the masses.
A. While he suggests in apocalyptic language
↪ in The Problem of Method that this
↪ process of self-consciousness is at
↪ last beginning to take place, and
↪ that civil, foreign and colonial
↪ wars are becoming apparent as
↪ different forms of a single class
↪ struggle, Sartre also admits that
↪ the divorce between theory and
↪ praxis which ensued under Stalinism
↪ has generally prevented any clear
↪ self-consciousness among the masses.
B. While he suggests in apocalyptic speeches
↪   in The Problem of Method that this

MUNCH - Sentence (Metaphorical-Word Marker)

Prompt:

[Task Description]: Choose which of two
↪ sentences is a paraphrase of a given
↪ sentence. You will be given the
↪ original sentence and two
↪ alternatives; respond with a single
↪ letter.

You are given a sentence in which the
↪ highlighted word is used
↪ metaphorically. Choose the sentence
↪ that is a paraphrase of it.

Original: While he suggests in apocalyptic *
↪ tones* in The Problem of Method that
↪ this process of self-consciousness
↪ is at last beginning to take place,
↪ and that civil, foreign and colonial
↪ wars are becoming apparent as
↪ different forms of a single class
↪ struggle, Sartre also admits that
↪ the divorce between theory and
↪ praxis which ensued under Stalinism
↪ has generally prevented any clear
↪ self-consciousness among the masses.
A. While he suggests in apocalyptic language
↪ in The Problem of Method that ...
B. While he suggests in apocalyptic speeches
↪ in The Problem of Method that ...
C. Both A and B
D. Neither A nor B

```
---
Your final answer MUST be a single letter: A
     ↪ , B, C, or D.
Write it wrapped in answer tags, exactly
     ↪ like this:
[Answer-Start]
[Answer]: <single letter A, B, C, or D>
[Answer-End]
---

---------------------------

Example response

A
```

MUNCH - Generation (Single-Word Paraphrase)

```
Prompt:

[Task Description]: Paraphrase a sentence by
     ↪  replacing a highlighted
     ↪ metaphorical word with a single
     ↪ synonym that preserves the meaning.
     ↪ Respond with only the replacement
     ↪ word.

Paraphrase the given sentence by
     ↪ substituting the highlighted word
     ↪ with another word.

Sentence: Leaders on Capitol Hill virtually
     ↪ put all other business on *hold* as
     ↪ it sought to hammer out a debt
     ↪ ceiling increase.

---
Your final answer MUST be a single word (the
     ↪  replacement for the highlighted
     ↪ word).
Write it wrapped in answer tags, exactly
     ↪ like this:
[Replacement-Word-Start]
[Replacement Word]: <single word>
[Replacement-Word-End]
---

---------------------------

Example response

pause
```

New Yorker Caption Contest - Matching

```
Prompt:

You are CaptionContestGPT, an expert
     ↪ language model at understanding the
```

```
     ↪ famous New Yorker caption contest.
     ↪ You follow the contest each week,
     ↪ and understand what makes for a
     ↪ humorous caption for each cartoon.
     ↪ You are aware of the various
     ↪ theories of humor, and read/anaylze
     ↪ the caption contest entries and
     ↪ winners each week.

Some things to remember:

- You're well versed in the history of the
     ↪ New Yorker Caption contest, and the
     ↪ types of captions that are selected
     ↪ as finalists/winners vs. those that
     ↪ are not.
- You think step-by-step, but aren't overly
     ↪ verbose.
- You can express uncertainty in your
     ↪ thinking, but in the end, pick the
     ↪ single best answer in the requested
     ↪ format.

I will describe a New Yorker cartoon to you.
     ↪  Then, I will give you 5 choices (
     ↪ labelled A-E) for captions. One of
     ↪ the captions was the winning caption
     ↪  for that cartoon, the other
     ↪ captions do not correspond to this
     ↪ cartoon. Your job is to first reason
     ↪  step-by-step about which answer
     ↪ might be correct, and, in the end,
     ↪ pick the single best match.

Here is a description of the cartoon
     ↪ followed by the five choices.

scene location: path
description: Two soldiers are on horseback
     ↪ in a field. A bunch of businessmen
     ↪ are trailing along behind them.
uncanny description: The businessmen are in
     ↪ the wrong time period.
entities: Mongols, Businessperson

Choices:
A: Evolution can be so tacky.
B: Let's pick up the pace. They're billing
     ↪ by the hour.
C: Well, five acres of popcorn back there
     ↪ says you were.
D: I'm sure it works. I was involved in the
     ↪ original research.
E: Just water for me, thanks.

Which of the 5 options (A, B, C, D, or E) is
     ↪  the best fit? Think step-by-step.

---
Your final answer MUST be a single letter (A
     ↪ , B, C, D, or E).
Write it wrapped in answer tags, exactly
     ↪ like this:
[Answer-Start]
[Answer]: <single letter A-E>
[Answer-End]
---
```

```
--------------------------

Example response

B
```

New Yorker Caption Contest - Ranking

```
Prompt:

You are CaptionContestGPT, an expert
     ↪ language model at understanding the
     ↪ famous New Yorker caption contest.
     ↪ ...

I will describe a New Yorker cartoon to you.
     ↪  Then, I will give you 2 choices (
     ↪ labelled A and B) for captions. One
     ↪ of the two captions was selected as
     ↪ a winning caption for that cartoon,
     ↪ while the other one is less funny.
     ↪ Your job is to first reason step-by-
     ↪ step about which caption might be
     ↪ funnier, and, in the end, select the
     ↪  one that you think humans found
     ↪ funnier.

Here is a description of the cartoon
     ↪ followed by the two choices.

scene location: the pyramids
description: A man is giving a hot dog to a
     ↪ woman outside a pyramid. On top,
     ↪ there is a vendor.
uncanny description: The top of a pyramid is
     ↪  an odd location for a vendor.
entities: Tourism, Food cart, Hot dog

Choices:
A: I'll admit, the grill marks really could
     ↪ pass for hieroglyphs.
B: Of course it's kosher -- who do you think
     ↪  built this place?

Which of the 2 options (A or B) is funnier?
     ↪ Think step-by-step.

---
Your final answer MUST be a single letter (A
     ↪  or B).
Write it wrapped in answer tags, exactly
     ↪ like this:
[Answer-Start]
[Answer]: <single letter A or B>
[Answer-End]
---

--------------------------

Example response

A
```

New Yorker Caption Contest - Explanation

```
Prompt:

You are CaptionContestGPT, an expert
     ↪ language model at understanding the
     ↪ famous New Yorker caption contest.
     ↪ ...

I will describe a New Yorker cartoon to you.
     ↪  Then, I will give you a high
     ↪ quality caption for that cartoon.
     ↪ Your job is to explain the joke in
     ↪ 2-3 sentences as if you were
     ↪ explaining to a friend who doesn't
     ↪ get the joke yet. First reason step-
     ↪ by-step about how the caption
     ↪ relates to the cartoon, and, in the
     ↪ end, write your 2-3 sentence
     ↪ explanation.

Here is a description of the cartoon
     ↪ followed by the winning caption.

scene location: mount sinai
description: A man is standing on a hill. A
     ↪ cloud with Groucho glasses and a
     ↪ hand reaching out of it is handing
     ↪ him a tablet.
uncanny description: The cloud has a funny
     ↪ disguise on.
entities: Moses, Groucho glasses, God

Winning caption: Remember, it's all in the
     ↪ timing.

Think step-by-step to figure out why the
     ↪ caption is funny for the cartoon.

---
Your final answer MUST be a 2-3 sentence
     ↪ explanation of the joke.
Write it wrapped in answer tags, exactly
     ↪ like this:
[Explanation-Start]
<your 2-3 sentence explanation>
[Explanation-End]
---

--------------------------

Example response

The cartoon reimagines Moses receiving the
     ↪ Ten Commandments from a cloud
     ↪ wearing Groucho Marx's iconic
     ↪ glasses, blending biblical lore with
     ↪  comedic absurdity. The caption "
     ↪ Remember, it's all in the timing"
     ↪ playfully nods to the classic Marx
     ↪ Brothers line, humorously framing
     ↪ the divine delivery as a timing act
     ↪ -- mixing religious imagery with
     ↪ slapstick humor and a witty pop
     ↪ culture reference.
```

New Yorker Explanation - Judge Prompt

```
Prompt:

You are an expert judge evaluating
    ↪ explanations of why a New Yorker
    ↪ caption-contest cartoon is funny.

You will be given:
[Problem]: a description of a cartoon, its
    ↪ winning caption, and a high-quality
    ↪ human-written reference explanation
    ↪ of the joke.
[Response]: a model-generated explanation of
    ↪  the same joke.

A good explanation makes the joke
    ↪ understandable to a friend who does
    ↪ not get it yet: it correctly
    ↪ identifies what is unexpected or
    ↪ incongruous in the cartoon and
    ↪ clearly connects the caption to that
    ↪  incongruity. Judge ONLY the model-
    ↪ generated explanation in [Response];
    ↪  use the human reference only as a
    ↪ guide to the correct interpretation
    ↪ of the joke.

Score the model explanation from 1 to 5:
5 = fully correct interpretation, clearly
    ↪ explains the humor, as good as or
    ↪ better than the reference.
4 = correct interpretation, explains the
    ↪ humor well with minor gaps.
3 = partially correct; gets the gist but
    ↪ misses or muddles a key element.
2 = largely incorrect or vague;
    ↪ misidentifies why the joke works.
1 = wrong, irrelevant, empty, or does not
    ↪ explain the joke at all.

Provide a brief rationale (2-4 sentences),
    ↪ then state your score as:
[Score]: <number from 1 to 5>

[Problem]: <cartoon description, winning
    ↪ caption, and reference explanation>

[Response]: <model's 2-3 sentence
    ↪ explanation>

---------------------------

(Judge is Google gemini-2.5-flash at T=0.0,
    ↪ top_p=0.95, n=1.)
```

NYT Connections

```
Prompt:
```

```
[Task Description]: Group 16 words into 4
    ↪ categories of 4 closely related
    ↪ words each. Every word belongs to
    ↪ exactly one group.

You are playing the New York Times
    ↪ Connections puzzle. In this game:
- You are given 16 words.
- Your goal is to find 4 groups of 4 words,
    ↪ where each group shares a specific
    ↪ theme or relationship.
- Every word belongs to exactly one group --
    ↪  no word is left over.
- Be careful: the puzzle is designed to
    ↪ mislead. Some words may seem to fit
    ↪ multiple groups. Only one complete
    ↪ grouping of all 16 words is correct.
- Think carefully and deliberately before
    ↪ committing to a group.

---
Solve this puzzle:
Words: LASER, PLUCK, THREAD, WAX, COIL,
    ↪ SPOOL, WIND, WRAP, HONEYCOMB,
    ↪ ORGANISM, SOLAR PANEL, SPREADSHEET,
    ↪ BALL, MOVIE, SCHOOL, VITAMIN

Think through the possible connections. Then
    ↪  provide your final answer.

---
Your final answer MUST follow this exact
    ↪ format:
[FINAL-GROUPING-START]
[Group-1]: word1, word2, word3, word4
[Group-2]: word1, word2, word3, word4
[Group-3]: word1, word2, word3, word4
[Group-4]: word1, word2, word3, word4
[FINAL-GROUPING-END]
---

---------------------------

Example response

[FINAL-GROUPING-START]
[Group-1]: WIND, WRAP, COIL, SPOOL
[Group-2]: PLUCK, WAX, THREAD, HONEYCOMB
[Group-3]: SOLAR PANEL, SPREADSHEET, LASER,
    ↪ VITAMIN
[Group-4]: BALL, MOVIE, SCHOOL, ORGANISM
[FINAL-GROUPING-END]
```

LLM-Grounding (Psycholinguistic Rating)

```
Prompt:

[Task Description]: Rate how arousing a
    ↪ given word is to human beings on a
    ↪ numeric scale. You will be given one
    ↪  word and must respond with a single
    ↪  number.
```

```
Arousal is a measure of excitement versus
    ↪ calmness. A word is AROUSING if it
    ↪ makes you feel stimulated, excited,
    ↪ frenzied, jittery or wide awake. A
    ↪ word is UNAROUSING if it makes you
    ↪ feel relaxed, calm, sluggish, dull
    ↪ or sleepy. Please indicate how
    ↪ arousing human beings think each
    ↪ word is on a 9-point scale of VERY
    ↪ UNAROUSING (1) to VERY AROUSING (9),
    ↪  with the midpoint representing
    ↪ moderate arousal.

---
Word: barrage

---
End your response with your rating on its
    ↪ own line in this exact format:
[Rating]: <a single integer>

---------------------------

Example response

7
```

GSM8K

```
Prompt:

Question: Jordan has 2 children who wear
    ↪ diapers. Each child requires 5
    ↪ diaper changes per day. Jordan's
    ↪ wife changes half of the diapers.
    ↪ How many diapers does Jordan change
    ↪ per day?
Answer:

---------------------------

Example response

Jordan has 2 children, each requiring 5
    ↪ diaper changes per day.

**Total diaper changes per day** = 2
    ↪ children x 5 changes = **10 changes
    ↪ **.

Jordan's wife changes half of the diapers,
    ↪ so Jordan changes the other half:

**Diapers Jordan changes per day** = 10
    ↪ total changes / 2 = **5 changes**.

**Answer:** Jordan changes **5** diapers per
    ↪  day.
```

AIME 2024

```
Prompt:

Solve the following math problem efficiently
    ↪  and clearly. The last line of your
    ↪ response should be of the following
    ↪ format: 'Therefore, the final answer
    ↪  is: $\boxed{ANSWER}$. I hope it is
    ↪ correct' (without quotes) where
    ↪ ANSWER is just the final number or
    ↪ expression that solves the problem.
    ↪ Think step by step before answering.

Let $\omega \neq 1$ be a 13th root of unity.
    ↪  Find the remainder when
\[ \prod_{k=0}^{12}(2 - 2\omega^k + \omega
    ↪ ^{2k}) \]
is divided by 1000.

---------------------------

Example response (truncated; full generation
    ↪  reaches the boxed integer answer)

To solve the problem, we are given a 13th
    ↪ root of unity $\omega \neq 1$, and
    ↪ we are asked to compute the
    ↪ remainder when the product
$$ \prod_{k=0}^{12} (2 - 2\omega^k + \omega
    ↪ ^{2k}) $$
is divided by 1000.

### Step 1: Understanding the Structure of
    ↪ the Product
Let us define $P(x) = x^2 - 2x + 2$. Then
    ↪ the product becomes $\prod_{k=0}^{12}
    ↪ P(\omega^k)$, evaluated over the 13
    ↪  roots of unity. Using resultant
    ↪ identities and the factorisation $x
    ↪ ^{13} - 1 = \prod_k (x - \omega^k)$,
    ↪  the product reduces to $\text{Res}(
    ↪ P, x^{13}-1)$.

[...continues with computing the resultant,
    ↪ taking modulus 1000, and concluding
    ↪ :]

Therefore, the final answer is: $\boxed{321}
    ↪ $. I hope it is correct
```

AIME 2025

```
Prompt:

Solve the following math problem efficiently
    ↪  and clearly. The last line of your
    ↪ response should be of the following
    ↪ format: 'Therefore, the final answer
    ↪  is: $\boxed{ANSWER}$. I hope it is
    ↪ correct' (without quotes) where
    ↪ ANSWER is just the final number or
```

```
        ↪ expression that solves the problem.
        ↪ Think step by step before answering.

Let $N$ denote the number of ordered triples
        ↪  of positive integers $(a, b, c)$
        ↪ such that $a, b, c \leq 3^6$ and $a
        ↪ ^3 + b^3 + c^3$ is a multiple of $3
        ↪ ^7$. Find the remainder when $N$ is
        ↪ divided by $1000$.

---------------------------

Example response (truncated)

To solve, we count ordered triples $(a, b, c
        ↪ )$ with $1 \leq a, b, c \leq 729$
        ↪ such that $a^3 + b^3 + c^3 \equiv 0 \
        ↪ pmod{3^7}$. Writing each integer as
        ↪ $x = 3^k m$ with $\gcd(m, 3) = 1$,
        ↪ we have $x^3 = 3^{3k} m^3$, so the 3-
        ↪ adic valuation of the sum depends on
        ↪  the $k$-pattern of the triple.

[...case analysis over k-pattern
        ↪ combinations and counting residues
        ↪ yields the count modulo 1000.]

Therefore, the final answer is: $\boxed{735}
        ↪ $. I hope it is correct
```

GPQA-Diamond

```
Prompt:

Answer the following multiple choice
        ↪ question. The last line of your
        ↪ response should be of the following
        ↪ format: 'Answer: $LETTER' (without
        ↪ quotes) where LETTER is one of ABCD.
        ↪  Think step by step before answering.
        ↪

In a parallel universe where a magnet can
        ↪ have an isolated North or South pole,
        ↪  Maxwell's equations look different.
        ↪  But, specifically, which of those
        ↪ equations are different?

A) The ones related to the circulation of
        ↪ the electric field and the
        ↪ divergence of the magnetic field.
B) The ones related to the divergence and
        ↪ the curl of the magnetic field.
C) The one related to the divergence of the
        ↪ magnetic field.
D) The one related to the circulation of the
        ↪  magnetic field and the flux of the
        ↪ electric field.

---------------------------

Example response
```

```
In our universe, Maxwell's equations assume
        ↪ the absence of magnetic monopoles,
        ↪ which means the divergence of the
        ↪ magnetic field (Gauss's Law for
        ↪ Magnetism) is zero: del . B = 0. In
        ↪ the hypothetical parallel universe
        ↪ where magnetic monopoles exist, this
        ↪  equation changes to del . B = rho_m
        ↪  / mu_0, where rho_m represents
        ↪ magnetic charge density. This
        ↪ modification directly alters the
        ↪ divergence of the magnetic field.

Other equations, such as Faraday's Law (
        ↪ circulation of the electric field)
        ↪ and Ampere's Law (curl of the
        ↪ magnetic field), remain unchanged
        ↪ unless additional terms are
        ↪ introduced for magnetic currents or
        ↪ monopole effects, which are not
        ↪ explicitly mentioned in the question.
        ↪  Therefore, the only equation that
        ↪ differs is the one related to the
        ↪ divergence of the magnetic field.

Answer: C
```

MuSR - Murder Mysteries

```
Prompt (truncated; full narrative ~800 words
        ↪ )

In a shocking twist of events, Faith has
        ↪ been gruesomely murdered by a
        ↪ lawnmower in her own kitchen and now,
        ↪  Detective Winston must unravel the
        ↪ tangled web of suspicion entangling
        ↪ Clyde and Paul.

[...detailed narrative describing (i) Clyde,
        ↪  an army veteran with weapon
        ↪ training, an obsessive cleanliness
        ↪ habit, a history of guests' items
        ↪ going missing, and a public-
        ↪ humiliation grudge against Faith; (
        ↪ ii) Paul, a barber with sharp-blade
        ↪ familiarity, regular kitchen access
        ↪ while doing Faith's yard work,
        ↪ mounting debts, and named as sole
        ↪ beneficiary of an unusually large
        ↪ insurance policy Faith recently took
        ↪  out...]

Who is the most likely murderer?

1 - Clyde
2 - Paul
Answer:

---------------------------

Example response (lighteval evaluates this
        ↪ task via log-likelihood ranking over
        ↪  the
```

```
provided choices; no free-form generation is
    ↪  produced -- the model implicitly
    ↪  selects
the choice with the highest conditional log-
    ↪  likelihood):

Model selection: 2 -> Paul (correct; means +
    ↪  motive + opportunity + financial
    ↪  windfall)
```

MuSR - Object Placements

```
Prompt (truncated; full narrative ~600 words
    ↪  )

Lisa and John were in the throes of
    ↪  preparation for their anticipated
    ↪  weekend adventure -- pedaling
    ↪  through nature trails on their
    ↪  trusted tandem bicycle.

[...narrative describes a sequence of object
    ↪  moves in a garage: (i) helmets
    ↪  start in the storage closet; (ii)
    ↪  Lisa carries them to a nearby bench
    ↪  to inspect them; (iii) Lisa leaves
    ↪  the garage briefly to look for
    ↪  sunscreen; (iv) Ellie, the
    ↪  housekeeper, returns the helmets
    ↪  from the bench back into the storage
    ↪   closet while Lisa is away; (v) Lisa
    ↪   returns. The question asks where
    ↪  Lisa will look for the helmets,
    ↪  requiring tracking what Lisa
    ↪  observed vs. what Ellie did out of
    ↪  her sight...]

Which location is the most likely place Lisa
    ↪   would look to find the helmets
    ↪  given the story?

1 - bench
2 - driveway
3 - storage closet
4 - wall
Answer:

--------------------------

Example response (log-likelihood selection
    ↪  over choices):

Model selection: 3 -> storage closet (
    ↪  correct)
```

MuSR - Team Allocation

```
Prompt (truncated; full narrative ~600 words
    ↪  )
```

```
Welcome to the story of a charming,
    ↪  fledgling diner, where the scent of
    ↪  new upholstery mingled with the
    ↪  promise of fresh beginnings.

[...character profiles: Jessica is a
    ↪  culinary perfectionist with award-
    ↪  winning cooking skill but clashes
    ↪  with the temperaments of both co-
    ↪  workers; Rebecca is a calm cook who
    ↪  is also exceptional with customer
    ↪  memory and service; Samuel is a
    ↪  former kitchen assistant who waited
    ↪  tables at a five-star restaurant and
    ↪   works best under Rebecca's
    ↪  mentorship. The puzzle requires
    ↪  choosing the allocation of chef vs.
    ↪  server roles that best accounts for
    ↪  skill fit and interpersonal dynamics
    ↪  ...]

Given the story, how would you uniquely
    ↪  allocate each person to make sure
    ↪  both tasks are accomplished
    ↪  efficiently?

1 - Cooking meals: Samuel, Serving customers
    ↪  : Jessica and Rebecca
2 - Cooking meals: Rebecca, Serving
    ↪  customers: Jessica and Samuel
3 - Cooking meals: Jessica, Serving
    ↪  customers: Rebecca and Samuel
Answer:

--------------------------

Example response (log-likelihood selection
    ↪  over choices):

Model selection: 3 -> Cooking meals: Jessica
    ↪  , Serving customers: Rebecca and
    ↪  Samuel (correct)
```

E   Example Appendix

This is an appendix.