PROVABLE RL WITH EXOGENOUS DISTRACTORS VIA MULTISTEP INVERSE DYNAMICS

ABSTRACT

Many real-world applications of reinforcement learning (RL) require the agent to deal with high-dimensional observations such as those generated from a megapixel camera. Prior work has addressed such problems with representation learning, through which the agent can provably extract endogenous, latent state information from raw observations and subsequently plan efficiently. However, such approaches can fail in the presence of temporally correlated noise in the observations, a phenomenon that is common in practice. We initiate the formal study of latent state discovery in the presence of such *exogenous* noise sources by proposing a new model, the Exogenous Block MDP (EX-BMDP), for rich observation RL. We start by establishing several negative results, by highlighting failure cases of prior representation learning based approaches. Then, we introduce the Predictive Path Elimination (PPE) algorithm, that learns a generalization of inverse dynamics and is provably sample and computationally efficient in EX-BMDPs when the endogenous state dynamics are near deterministic. The sample complexity of PPE depends polynomially on the size of the latent endogenous state space while not directly depending on the size of the observation space, nor the exogenous state space. We provide experiments on challenging exploration problems which show that our approach works empirically.

1 INTRODUCTION

In many real-world applications such as robotics there can be large disparities in the size of agent's observation space (for example, the image generated by agent's camera), and a much smaller latent state space (for example, the agent's location and orientation) governing the rewards and dynamics. This size disparity offers an opportunity: how can we construct reinforcement learning (RL) algorithms which can learn an optimal policy using samples that scale with the size of the latent state space rather than the size of the observation space? Several families of approaches have been proposed based on solving various ancillary prediction problems including autoencoding (Tang et al., 2017; Hafner et al., 2019), inverse modeling (Pathak et al., 2017; Burda et al., 2018), and contrastive learning (Laskin et al., 2020) based approaches. These works have generated some significant empirical successes, but are there provable (and hence more reliable) foundations for their success? More generally, what are the right principles for learning with latent state spaces?

In real-world applications, a key issue is robustness to noise in the observation space. When noise comes from the observation process itself, such as due to measurement error, several approaches have been recently developed to either explicitly identify (Du et al., 2019; Misra et al., 2020; Agarwal et al., 2020a) or implicitly leverage (Jiang et al., 2017) the presence of latent state structure for provably sample-efficient RL. However, in many real-world scenarios, the observations consist of many elements (e.g. weather, lighting conditions, etc.) with temporally correlated dynamics (see e.g. Fig. 1 and the example below) that are entirely independent of the agent's actions and rewards. The temporal dynamics of these elements precludes us from treating them as uncorrelated noise, and as such, most previous approaches resort to modeling their dynamics. However, this is clearly wasteful as these elements have no bearing on the RL problem being solved.

Figure 1: **Left:** Shows an example where an agent is walking next to a pond in a park and observes the world as an image (x). The world consists of a latent endogenous state, containing variable such as agent's position, and a much larger latent exogenous state containing variables such as motion of ducks, changes in sunlight, ripples in the water, etc. **Center:** The novel *exogenous block MDP* setting introduced here. The exogenous state is unaffected by agent's action. **Right:** We show that PPE learns a generalized form of inverse dynamics that is able to recover the endogenous state.

As an example, consider the setting in Figure 1. An agent is walking in a park on a lonely sidewalk next to a pond. The agent's observation space is the image generated by its camera, the latent endogenous state is its position on the sidewalk, and the exogenous noise is provided by motion of ducks or people in the background, swaying of trees and changes in lighting conditions, typically unaffected by the agent's actions. While there is a line of recent empirical work that aims to remove causally irrelevant aspects of the observation (Gelada et al., 2019; Zhang et al., 2020), theoretical treatment is quite limited (Dietterich et al., 2018) and no prior works address sample-efficient learning with provable guarantees. Given this, the key question here is:

How can we learn using an amount of data scaling with just the size of the endogenous *latent state, while ignoring the temporally correlated* exogenous *observation noise?*

We initiate a formal treatment of RL settings where the learner's observations are jointly generated by a latent endogenous state and an uncontrolled exogenous state, which is unaffected by the agent's actions and does not affect the agent's task. We study a subset of such problems called Exogenous Block MDPs (EX-BMDPs) (defined in Section 2), where the endogenous state is discrete and decodable from the observations. We first highlight the challenges in solving EX-BMDPs by illustrating the failures of many prior representation learning approaches (Pathak et al., 2017; Misra et al., 2020; Jiang et al., 2017; Agarwal et al., 2020a; Zhang et al., 2020). These failure happen either due to creating too many latent states, such as one for each combination of ducks and passers-by in the example above leading to sample inefficiency in exploration, or due to lack of exhaustive exploration. Then, we identify one recent approach developed by Du et al. (2019) with favorable properties for a class of EX-BMDPs with near-deterministic latent state dynamics. In Section 4 and Section 5, we develop a variation of their algorithm and analyze its performance for near-deterministic EX-BMDPs. The algorithm, call PPE, learns a form of *multi-step inverse dynamics* by predicting the identity of the path that generates an observation. For the near-deterministic EX-BMDPs we prove PPE successfully explores the environment using $O((SA)^2 H \log(|\mathcal{F}|/\delta))$ samples where S is the cardinality of the latent *endogenous* state space, A is the number of actions, H is the horizon and $\mathcal{F}$ is a function class employed to solve a maximum likelihood problem of inferring the path which generated an observation.

Empirically, in Section 6, we demonstrate the performance of PPE and various prior baselines in a challenging exploration problem with exogenous noise. We show that baselines fail to decode the endogenous state and either end up overabstracting (creating an abstract state which aliases essentially-different states) or underabstracting (creating essentially the same clones of states). We further, show that PPE is able to recover the latent endogenous model in a visually complex navigation problem, in accordance with the theory.

2 EXOGENOUS BLOCK MDP SETTING

We introduce a novel *Exogenous Block Markov Decision Process* (EX-BMDP) setting to model environments with exogenous noise. We briefly describe notations before presenting a formal treatment of EX-BMDP.

Notations: For a given set $\mathcal{U}$, we use $\Delta(\mathcal{U})$ to denote the set of all probability distributions over $\mathcal{U}$. For a given natural number $N \in \mathbb{N}$, we use the notation $[N]$ to denote the set $\{1, 2, \cdots, N\}$. Lastly, for a probability distribution $p \in \Delta(\mathcal{U})$, we define its support as $supp\, p = \{u \mid p(u) > 0, u \in \mathcal{U}\}$.

We start with describing the Block Markov Decision Process (BMDP), introduced in Du et al. (2019). This process consists of a finite set of observations $\mathcal{X}$, a set of *latent* states $\mathcal{Z}$ with cardinality Z, a finite set of actions $\mathcal{A}$ with cardinality A, a transition function $T : \mathcal{Z} \times \mathcal{A} \rightarrow \Delta(\mathcal{Z})$, an emission function $q : \mathcal{Z} \times \mathcal{A} \rightarrow \Delta(\mathcal{X})$, a reward function $R : \mathcal{X} \times \mathcal{A} \rightarrow [0, 1]$, a horizon $H \in \mathbb{N}$, and a start state distribution $\mu \in \Delta(\mathcal{Z})$. The agent interacts with the environment by repeatedly generating H-step trajectories $(z_1, x_1, a_1, r_1, \cdots, z_H, x_H, a_H, r_H)$ where $z_1 \sim \mu(\cdot)$ and for every $h \in [H]$ we have $x_h \sim q(\cdot \mid z_h)$, $r_h = R(x_h, a_h)$, and if $h < H$, then $z_{h+1} \sim T(\cdot \mid z_h, a_h)$. The agent does not observe the states $(z_1, \cdots, z_H)$, instead receiving only the observations $(x_1, \cdots, x_H)$ and rewards $(r_1, \cdots, r_H)$. We assume that the emission distributions of any two latent states are disjoint (usually referred as the block assumption):

$$supp(q(\cdot \mid z_1)) \cap supp(q(\cdot | z_2)) = \emptyset \text{ when } z_1 \neq z_2.$$

The agent chooses actions using a policy $\pi : \mathcal{X} \rightarrow \Delta(\mathcal{A})$. We also define the set of non-stationary policies $\Pi_{\text{NS}} = \Pi^H$ as a H-length tuple, with $(\pi_1, \cdots, \pi_H) \in \Pi_{\text{NS}}$ denoting that the action at time step h is taken as $a_h \sim \pi_h(\cdot \mid x_h)$. The value $V(\pi)$ of a policy π is the expected episodic sum of rewards $V(\pi) := \mathbb{E}_\pi[\sum_{h=1}^H R(x_h, a_h)]$. The optimal policy is given by $\pi^\star = \arg\max_{\pi \in \Pi_{\text{NS}}} V(\pi)$. We denote by $\mathbb{P}_h(x | \pi)$ the probability distribution over observations x at time step h when following a policy π. Lastly, we refer to an *open loop* policy as an element in all $\mathcal{A}^H$ sequences of actions. An open loop policy follows a pre-determined sequence of actions $\{a_1, .., a_H\}$ for H time steps, unaffected by state information.

Given the aforementioned definitions, we define an EX-BMDP as follows:

Definition 1 (Exogenous Block Markov Decision Processes)**.** *An EX-BMDP is a BMDP such that the latent state can be decoupled into two parts $z = (s, \xi)$ where $s \in \mathcal{S}$ is the endogenous state and $\xi \in \Xi$ is the exogenous state. For $z \in \mathcal{Z}$ the initial distribution and transition functions are decoupled, that is: $\mu(z) = \mu(s)\mu_\xi(\xi)$, and $T(z' \mid z, a) = T(s' \mid s, a)T_\xi(\xi' \mid \xi)$.*

The observation space $\mathcal{X}$ can be arbitrarily large to model which could be a high-dimensional real vector denoting an image, sound, or haptic data in an EX-BMDP. The endogenous state s captures the information that can be manipulated by the agent. Figure 1, center, visualizes the transition dynamics factorization. We assume that the set of all endogenous states $\mathcal{S}$ is finite with cardinality S. The exogenous state ξ captures all the other information that the agent cannot control and does not affect the information it can manipulate. Again, we make no assumptions on the exogenous dynamics nor on its cardinality $|\Xi|$ which may be arbitrarily large. We note that the block assumption of the EX-BMDP implies the existence of two inverse mappings: $\phi_e^\star : \mathcal{X} \rightarrow \mathcal{S}$ to map an observation to its endogenous state, and $\phi_g^\star : \mathcal{X} \rightarrow \Xi$ to map it to its exogenous state.

Justification of Assumptions. The block assumption has been made by prior work (e.g., Du et al. (2019), Zhang et al. (2020)) to model many real-world settings where the observation is *rich*, i.e., it contains enough information to decode the latent state. The decoupled dynamics assumption made in the EX-BMDP setting is a natural way to characterize exogenous noise; the type of noise that is not affected by our actions nor affects the endogenous state but may have non-trivial dynamic. This decoupling captures the movement of ducks, captured in the visual field of the agent in Figure 1, and many additional exogenous processes (e.g., movement of clouds in a navigation task).

Goal. Our formal objective is reward-free learning. We wish to find a set of policies that can be used to explore the entire state space. Consistent with prior works (Du et al., 2019; Misra et al., 2020; Agarwal et al., 2020a), we refer to such a set as a *policy cover* and formally define it below:

Definition 2 (α-policy cover). *Let Ψ_h be a finite set of non-stationary policies. We say Ψ_h is an α-policy cover for the h^{th} time step if for all $z \in \mathcal{Z}$ it holds that $\max_{\pi \in \Psi_h} \mathbb{P}_h(z|\pi) \geq \max_{\pi \in \Pi_{NS}} \mathbb{P}_h(z|\pi) - \alpha$. If $\alpha = 0$ we call Ψ_h an exact policy cover or simply a policy cover.*

Given a policy cover, and for any reward function, we can find a near optimal policy by applying dynamic-programming (e.g., Bagnell et al. (2004)), policy optimization (e.g., Kakade and Langford, 2002; Agarwal et al., 2020b; Shani et al., 2020) or value (e.g., Antos et al., 2008; Chen and Jiang, 2019) based methods.

3 FAILURES OF PRIOR APPROACHES

We now describe the limitation of prior RL approaches in the presence of exogenous noise. We provide an intuitive analysis over here, and defer a formal statement and proof to Appendix A.

Limitation of Noise-Contrastive Learning. Noise-contrastive learning has been used in RL to learn a state abstraction by exploiting the temporal information available to the agent. Specifically, the HOMER algorithm (Misra et al., 2020) trains a model to distinguish between *real* and *imposter* transitions. This is done by collecting a dataset of quads (x, a, x', y) where $y = 1$ means the transition was (x, a, x') was observed and $y = 0$ means that (x, a, x') was not observed. HOMER then trains a model $p_\theta(y \mid x, a, \phi_\theta(x'))$ with parameters θ, on the dataset, by predicting whether a given pair of transition was observed or not. This provides a state abstraction $\phi_\theta : \mathcal{X} \to \mathbb{N}$ for exploring the environment. HOMER can provably solve Block MDPs. Unfortunately, in the presence of exogenous noise, HOMER can distinguish between two transitions that represent transition between the same latent endogenous states but different exogenous states. In our walk in the park example, even if the agent moves between same points in two transitions, the model maybe able to tell these transitions apart by looking at the position of ducks which may have different behaviour in the two transitions. This results in the HOMER creating $\mathcal{O}(|\mathcal{Z}|)$ many abstract states. We call this the *over-abstraction* problem.

Limitation of Inverse Dynamics. Another common approach in empirical works is based on modeling the inverse dynamics of the system, where a representative example is the ICM module of Pathak et al. (2017). In such approaches, we learn a representation by using consecutive observations to predict the action that was taken between them. Such a representation can ignore all information that is not relevant for action prediction, which includes all exogenous/uncontrollable information. However, it can also ignore some controllable information, which may result in a failure to sufficiently explore the environment. In this sense, inverse dynamics approaches result in an *under-abstraction* problem where observations from different endogenous states can be mapped to the same abstract state. To concretely demonstrate this, consider an agent is trying to cross a river with two bridges. On any given day, one of the bridges is closed at random, while the agent starts several steps away from both bridges. Since the agent cannot get close to either bridge in a single time step, a bridge closure does not affect the first transition, which means that the inverse dynamics approach can ignore this information. However once this information is forgotten at the initial state, it is no longer possible to express the optimal policy. This information erasure observation has been shown to persist even in exploring agents (Misra et al., 2020).

Limitation of Bisimulation. Zhang et al. (2020) proposed learning a bisimulation metric to learn a representation which is invariant to exogenous noise. Unfortunately, it is known that bisimulation metric cannot be learned in a sample-efficient manner (Modi et al. (2020), Proposition B.1). Intuitively, when the reward is same everywhere, then bisimulation merges all states into a single abstract state. This creates exploration issue in sparse reward settings, since the agent can merge all states into a single abstract state until it receives a non-trivial reward. Hence, the learned abstract states provide no help in exploring the environment.

Algorithm 1 PPE(δ, η): Predictive Path Elimination

1: Set $\Psi_1 = \{\bot\}$, stochasticity level $\eta \leq \frac{1}{4SH}$ // $\bot$ denotes an empty path

2: **for** $h = 2, \ldots, H$ **do**

3:      Set $N = 16 \left(|\Psi_{h-1}|A\right)^2 \log\left(\frac{|\mathcal{F}||\Psi_{h-1}|AH}{\delta}\right)$

4:      Collect a dataset $\mathcal{D}$ of N *i.i.d.* tuples (x, υ) where $\upsilon \sim \mathtt{Unf}(\Psi_{h-1} \circ \mathcal{A})$ and $x \sim \mathbb{P}(x_h \mid \upsilon)$.

5:      Solve multi-class classification problem: $\hat{f}_h = \arg\max_{f \in \mathcal{F}} \sum_{(x,\upsilon) \in \mathcal{D}} \ln f(\mathrm{idx}(\upsilon) \mid x)$.

6:      **for** $1 \leq i < j \leq |\Psi_{h-1} \circ \mathcal{A}|$ **do**

7:          Calculate the path prediction gap: $\widehat{\Delta}(i,j) = \frac{1}{N} \sum_{(x,\upsilon) \in \mathcal{D}} \left| \hat{f}_h(i|x) - \hat{f}_h(j|x) \right|$.

8:          If $\widehat{\Delta}(i,j) \leq \frac{5/8}{|\Upsilon_h|}$, then eliminate path υ with $\mathrm{idx}(\upsilon) = j$.   // υ_i and υ_j visit the same state s.

9:      Ψ_h is defined as the set of all paths in $\Psi_{h-1} \circ \mathcal{A}$ that have not been eliminated in line 8.

Bellman rank might depend on $|\Xi|$. The Bellman rank was introduced in Jiang et al. (2017) as a complexity measure for the learnability of an RL problem with function approximations. To date, most of the learnable RL problems have a small Bellman rank. However, we show in Appendix A that Bellman rank for Ex-BMDP can scale as $\mathcal{O}(|\Xi|)$. This shows that EX-BMDP is a highly non-trivial setting as we don't even have sample-efficient algorithms that can solve it without being computationally-efficient.

In Appendix A we also describe failures of other methods such as generative modeling (Agarwal et al. (2020a)) and autoencoding (Tang et al. (2017)).

4   REINFORCEMENT LEARNING FOR EX-BMDPS

In this section, we present an algorithm *Predictive Path Elimination* (PPE) that we later show can provably solve any EX-BMDP with nearly deterministic dynamics and start state distribution of the endogenous state, while making no assumptions on the dynamics or start state distribution of the exogenous state (Algorithm 1). Before describing PPE, we highlight that PPE can be thought of as a computationally-efficient and simpler alternative to Algorithm 4 of Du et al. (2019) who studied rich-observation setting without exogenous noise.[1] Due to the apparent difference of the algorithms we keep the presentation of our algorithm fully self-contained.

PPE performs iterations over the time steps $h \in \{2, \cdots, H\}$. In the h^{th} iteration, it learns a policy cover Ψ_h for time step h containing open-loop policies. This is done by first augmenting the policy cover for previous time step by one step. Formally, we define $\Upsilon_h = \Psi_{h-1} \circ \mathcal{A} = \{\pi \circ a \mid \pi \in \Psi_{h-1}, a \in \mathcal{A}\}$ where $\pi \circ a$ is an open-loop policy that follows π till time step $h-1$ and then takes action a. Since we assume the transition dynamics to be near-deterministic, therefore, we know that there exists a policy cover for time step h that is a subset of Υ_h and whose size is equal to the number of reachable states at time step h. Further, as the transitions are near-deterministic, we refer to an open-loop policy as a path, as we can view the policy as tracing a path in the latent transition model. PPE works by eliminating paths in Υ_h so that we are left with just a single path for each reachable state. This is done by collecting a dataset $\mathcal{D}$ of tuples (x, υ) where υ is a uniformly sampled from Υ_h and $x \sim \mathbb{P}_h(x \mid \upsilon)$ (line 4). We train a classifier $\hat{f}_h$ using $\mathcal{D}$ by predicting the index $\mathrm{idx}(\upsilon)$ of the path υ from the observation x (line 5). Intuitively, if $\hat{f}_h(i \mid x)$ is sufficiently large, then we can hope that the path υ_i visits the state $\phi_e^\star(x)$. Further, we can view this prediction problem as learning a multistep inverse dynamics model since the open-loop policy contains information about all previous actions

---

[1] Alg. 4 has a computational complexity of $\mathcal{O}(S^4 A^4 H)$ compared to $\mathcal{O}(S^3 A^3 H)$ for PPE. Furthermore, Alg. 4 needs access to an upper bound on the number of states, whereas PPE is adaptive to it.

and not just the last action. For every pair of paths in Υ_h, we first compute a path prediction gap $\widehat{\Delta}$(line 7). If the gap is too small, then we can view these paths as visiting the same endogenous state, hence we eliminate a redundant path (line 8). To avoid eliminating all paths going to an endogenous state, we always eliminate the path with higher index. Eliminating a path does not delete it from Υ_h and hence indices of all paths remain unchanged. Finally, Ψ_h is defined as the set of all paths in Υ_h which were not eliminated. PPE reduces RL to performing H standard classification problems. Further, the algorithm is very simple and in practice requires just a single hyperparameter (N). We believe these properties will make it well-suited for many problems.

Recovering latent transition dynamics. We can directly recover a latent deterministic transition model $\hat{T}_h$ for each time step h from PPE by carefully tracking how each path is eliminated. We provide full details in Appendix D. Further, we can also recover a state decoder $\hat{\phi}_h : \mathcal{X} \to \mathbb{N}$ for time step h as: $\hat{\phi}_h(x) = \min_i \left\{ i \mid \hat{f}_h(i \mid x) \geq \max_j \hat{f}_h(j \mid x) - \mathcal{O}(1/|\Upsilon_h|), i \in |\Upsilon_h| \right\}$. Intuitively, this assigns the observation to the path with smallest index that has the highest chance of visiting x.

Learning an optimal policy. If the reward function depends only on the endogenous state then planning can be efficiently carried out in the learned model since there always exists an endogenous optimal policy (see Proposition 4 and Appendix D.2). For more general rewards, model-free planning using data collected by the policy cover can still be carried out, using algorithms such as PSDP (Bagnell et al., 2004) or FQI (Ernst et al., 2005) which we analyze in Appendix D.1.

5 THEORETICAL ANALYSIS AND DISCUSSION

In this section, we provide the main sample complexity guarantee for PPE as well as some intuition for why it works. We analyze the algorithm in near-deterministic MDPs defined as follows: We say that two transition functions T_1 and T_2 are η-close if for all $h \in [H], a \in \mathcal{A}, s \in \mathcal{S}_h$ it holds that $||T_1(\cdot \mid s, a) - T_2(\cdot \mid s, a)||_1 \leq \eta$. Analogously, two starting distribution μ_1 and μ_2 are η-close if $||\mu_1(\cdot) - \mu_2(\cdot)||_1 \leq \eta$. We assume that the dynamics of the endogenous state space is η-close to some deterministic dynamics. We emphasize that near-deterministic dynamics are quite common in real-world applications like robotics.

Assumption 1 (Near deterministic endogenous dynamics). *We assume the endogenous dynamics is η-close to a deterministic model $(\mu_{D,\eta}, T_{D,\eta})$ where $\eta \leq 1/(4SH)$.*

We also make a realizability assumption for the regression problem solved by PPE (line 5). We assume that $\mathcal{F}$ is expressive enough to represent the Bayes optimal classifier of the regression problems created by PPE.

Assumption 2 (Realizability). *For any $h \in [H]$, and any set of paths $\Upsilon \subseteq \mathcal{A}^h$ with $|\Upsilon| \leq SA$ and where $\mathcal{A}^h$ denotes the set of all paths of length h, there exists $f_{\Upsilon,h} \in \mathcal{F}$ such that: $f_{\Upsilon,h}(\mathrm{idx}(\upsilon) \mid x) = \frac{\mathbb{P}(\phi_e^\star(x)|\upsilon)}{\sum_{\upsilon' \in \Upsilon} \mathbb{P}(\phi_e^\star(x)|\upsilon')}, \text{for all } \upsilon \in \Upsilon \text{ and } x \in \mathcal{X} \text{ with } \sum_{\upsilon' \in \Upsilon} \mathbb{P}(\phi_e^\star(x) \mid \upsilon') > 0.$*

In this assumption, the function $f_{\Upsilon,h}(\upsilon \mid x)$ denotes the Bayes optimal classifier for the regression problem in the h^{th} iteration when $\Upsilon_h = \Upsilon$. Realizability assumptions are common in theoretical analysis (e.g., Misra et al. (2020), Agarwal et al. (2020a)). In practice, we use expressive neural networks to solve the regression problem, so we expect the realizability assumption to hold. Note that there are at most $A^{S(H+1)}$ Bayes classifiers for different prediction problems. However, this is acceptable since our guarantees will scale as $\ln |\mathcal{F}|$ and, therefore, the function class $\mathcal{F}$ can be exponentially large to accommodate all of them.

We now state the formal sample complexity guarantees for PPE below.

Theorem 1 (Sample Complexity). *Fix $\delta \in (0, 1)$. Then, with probability greater than $1 - \delta$, PPE returns a policy cover $\{\Psi_h\}_{h=1}^H$ such that for any $h \in [H]$, Ψ_h is a ηH-policy cover for time step h and $|\Psi_h| \leq S$, which gives the total number of episodes used by PPE as $\mathcal{O}\left(S^2 A^2 H \ln \frac{|\mathcal{F}|SAH}{\delta} \right)$.*

(a) Combination lock ($H = 2$).   (b) Regret plot   (c) State decoding accuracy

Figure 2: Results on combination lock. **Left:** We show the latent transition dynamics of combination lock. Observations are not shown for brevity. **Center:** Shows minimal number of episodes needed to achieve a mean regret of at most $V(\pi^\star)/2$. **Right:** State decoding accuracy (in percent) of decoders learned by different methods. Solid lines implies no exogenous dimension while dashed lines imply an exogenous dimension of 100.

We defer the proof to Appendix C. Our sample complexity guarantees do not depend directly on the size of observation space or the exogenous space. Further, since our analysis only uses standard uniform convergence arguments, it extends straightforwardly to infinitely large function classes by replacing $\ln |\mathcal{F}|$ with other suitable complexity measures such as Rademacher complexity.

Why does PPE **work?**. We provide an asymptotic analysis to explain why PPE works. Consider a deterministic setting and the h^{th} iteration. Assume by induction that Ψ_{h-1} is an exact policy cover and has exactly one policy for every endogenous state reachable at time step $h - 1$. The Bayes optimal classifier of the prediction problem can be derived as:

$$f^\star(\mathrm{idx}(\upsilon) \mid x) = \mathbb{P}(\upsilon \mid x) = \frac{\mathbb{P}(x \mid \upsilon)\mathbb{P}(\upsilon)}{\sum_{\upsilon' \in \Upsilon_h} \mathbb{P}(x \mid \upsilon')\mathbb{P}(\upsilon')} = \frac{\mathbb{P}(x \mid \upsilon)}{\sum_{\upsilon' \in \Upsilon_h} \mathbb{P}(x \mid \upsilon')} = \frac{\mathbb{P}(\phi_e^\star(x) \mid \upsilon)}{\sum_{\upsilon' \in \Upsilon_h} \mathbb{P}(\phi_e^\star(x) \mid \upsilon')},$$

where the third equality uses the fact that all paths are chosen uniformly, and the last equality critically uses that for any open-loop policy υ we have: $\mathbb{P}(x \mid \upsilon) = q(x \mid \phi_e^\star(x), \phi_d^\star(x))\mathbb{P}(\phi_e^\star(x) \mid \upsilon)\mathbb{P}(\phi_d^\star(x))$. Thus, the Bayes optimal classifier of the prediction problem only depends on the exogenous noise and there is no signal available to separate observations from the same endogenous state, so there is no over abstraction issue. In addition, we can show that there is signal available to separate any two endogenous states, so there is no under abstraction like in inverse dynamics approaches. Intuitively, no path can visit two different endogenous states. Hence, for two observations x_1 and x_2 coming from different endogenous states, if υ_1 visits $\phi_e^\star(x_1)$ then $f^\star(\upsilon_1 \mid x_1)$ would be non-zero, in fact we can show it to be at least $1/|\Upsilon_h|$ and $f^\star(\upsilon_2 \mid x_2)$ would 0. This gap provides a signal to separate different endogenous states from observations.

The above factorization relies heavily on the use of open-loop policies and does not hold for an arbitrary policy class. This is the main reason why we use a policy cover with open-loop policies.

Guarantees for policy learning. Given the policy recover returned by PPE, we prove in Appendix D that PSDP (Bagnell et al. (2004)), a dynamic programming based RL algorithm, can learn a near optimal policy w.r.t. a general reward function that may depend on the *full observation* x. However, when the reward depends only on the endogenous state and action, we show that a simpler value iteration procedure suffices.

6   EXPERIMENTS

We evaluate PPE on two domains: a challenging exploration problem called *combination lock* to test whether PPE can learn an optimal policy and an accurate state decoder, and a visual-grid world with complex visual representations to test whether PPE is able to recover the latent dynamics.

Combination Lock Experiments. The combination lock problem is defined for a given horizon H by an endogenous state space $\mathcal{S} = \{s_{1,a}\} \cup \{s_{h,a}, s_{h,b}, s_{h,c}\}_{h=2}^H$, an exogenous state space $\Xi = \{0,1\}^H$, an action space $\mathcal{A}$ with 10 actions, and a deterministic endogenous start state of $s_{1,a}$. For any state $s_{h,g}$ we call g as its *type* which can be a, b or c. States with type a and b are considered *good* states and those with type c are considered *bad* states. Each instance of this problem is defined by two good action sequences $(a_h)_{h=2}^H, (a_h')_{h=2}^H$ with $a_h \neq a_h'$, which are chosen uniformly randomly and kept fixed throughout training. At $h = 1$, the agent is in $s_{1,a}$ and action a_1 leads to $s_{2,a}$, a_h' leads to $s_{2,b}$, and all other actions lead to $s_{2,c}$. For $h > 2$, taking action a_h in $s_{h,a}$ leads to $s_{h+1,a}$ and taking action a_h' in $s_{h,b}$ leads to $s_{h+1,b}$. In all other cases involving taking an action in a state $s_{h,g}$, we transition to the next bad state $s_{h+1,c}$. We visualize the latent endogenous dynamics in Figure 2a. The exogenous state evolves as follows: we sample ξ_1 as a vector in $\{0,1\}^H$ by selecting the value of each dimension independently uniformly in $\{0,1\}$. At time step h, ξ_h is generated from ξ_{h-1} by uniformly flipping each bit in ξ_{h-1} independently with probability 0.1. There is a reward of 1.0 on taking the good action $a_{H,a}$ in $s_{H,a}$ and a reward of 0.1 on taking action $a_{H,b}$ in $s_{H,b}$, and in all other cases the agent gets a reward of 0. This gives a $V(\pi^\star) = 1$, and the probability that a random open loop policy gets this optimal return is 10^{-H}.

An observation x is generated stochastically from a latent state $z = (s, \xi)$. We first map s to a vector w encoding the identity of the state. We concatenate (w, ξ), add Gaussian noise to each dimension, and multiply the result with a Hadamard matrix to generate x. See Appendix F for full details. Our construction is inspired by similar combination lock problems in prior work (Du et al., 2019; Misra et al., 2020). However, these previous constructions do not consider exogenous distractors.

Baseline. We compare PPE with four baselines on the combination lock problem. These include PPO (Schulman et al., 2017) which is an actor-critic algorithm, PPO + RND (Burda et al., 2019) which adds an exploration bonus to PPO using prediction errors, Homer which is the algorithm of Misra et al. (2020) that uses contrastive learning, and another algorithm ID which is similar to Homer but instead of noise-contrastive learning it learns an inverse dynamics model to recover the state abstraction. We use existing publicly available codebases for these baselines. Our implementation of PPE very closely follows the pseudo-code in Algorithm 1. We model $\mathcal{F}$ using a two-layer feed-forward network with ReLU non-linearity. We train $\mathcal{F}$ with Adam optimization and use a validation set to do model selection. We refer readers to Appendix F for additional experimental details.

Results. Figure 2b shows results for different values of H. For each value of H, we plot the minimal number of episodes n needed to achieve a mean regret of at most $V(\pi^\star)/2 = 0.5$. We run each algorithm 5 times with different seeds and report the median performance. If an algorithm is unable to achieve the desired regret in 5×10^5 episodes then we set $n = \infty$. We observe that PPO is unable to solve the problem at $H = 5$. PPO + RND is able to solve the problem at $H = 5$ and $H = 10$, showing the exploration bonus induced by random network distillation helps. However, it is unable to solve the problem for larger values of H. We observe that Homer and ID are also unable to solve the problem for any value of H. Lastly, PPE is able to solve the problem for all values of H and is significantly more sample efficient than baselines.

In order to understand the failure of Homer and ID, we investigate the accuracy of the state abstraction learned by these methods and compare that with PPE. We focus on the combination lock setting with $H = 2$ and evaluate the learned decoder for the last time step. As the state abstraction models are invariant to label permutation, therefore, we use the following evaluation metric: given a learned state abstraction $\hat{\phi} : \mathcal{X} \to [N]$ we compute $1/m \sum_{i=1}^m \mathbf{1}\{\hat{\phi}(x_{i,1}) = \hat{\phi}(x_{i,2}) \Leftrightarrow \phi_e^\star(x_{i,1}) = \phi_e^\star(x_{i,2})\}$, where $\{x_{i,1}, x_{i,2}\}_{i=1}^m$ are drawn independently from a fixed distribution D with good support over all states. We report the percentage accuracy in Figure 2c. When there is no exogenous noise, Homer is able to learn a good state decoder with enough samples while ID fails to learn, in accordance with the theory. On inspection, we found that ID suffers from the under-abstraction issue highlighted earlier as it has difficulty separating observations from s_{3a} and s_{3b}. On adding exogenous noise, the accuracy of Homer plummets significantly. The accuracy of ID also drops but this drop is mild since unlike Homer, the ID objective is able to filter exogenous noise. Lastly, we observe that PPE is always able to learn a good decoder and is more sample efficient than baselines.

(a) Visual Grid World $h = 1$. (b) Visual Grid World $h = 2$.   (c) Regret plot

Figure 3: Results on visual grid world. **Left and center:** Shows sampled observations for the first two steps from the visual gridworld domain. The agent is depicted as a red-triangle, lava in orange, walls in grey, and the goal in green. **Right:** Shows errors of type 1 and type 2 made by the PPE in recovering the latent endogenous dynamics. (see Section 6)

Visual Grid World Experiments. We test the ability of PPE to recover the latent endogenous transition dynamics in visual grid-world problem.[2] The agent navigates in a $N \times N$ grid world where each grid can contain a stationary object, the goal, or the agent. The agent's endogenous state is given by its position in the grid and its direction amongst four possible canonical directions. The agent can take five different actions for navigation. The world is visible to the agent as a $8N \times 8N$ sized RGB image. We add exogenous noise as follows: at the beginning of each episode, we independently sample position, size and color of 5 ellipses. The position and size of these ellipses is perturbed after each time step independent of the action. We project these ellipses on top of the world's image. Figure 3 shows sampled observations from the 7×7 gridworld that we experiment on. The exogenous state is given by the position, size and color of ellipses and is much larger than $|\mathcal{S}| \leq 4N^2$. We model $\mathcal{F}$ using a two-layer convolutional neural network and train it using Adam optimization. We defer the full details of setup to Appendix F.

Since the problem has deterministic dynamics, we can evaluate the accuracy of the learned transition model by measuring it in terms of accuracy of the elimination step (Algorithm 1, line 8), since this step induces our algorithm's mapping from observations to endogenous latent states. For a fixed $h \in \{2, \cdots, H\}$, let ν_i and ν_j be two paths in $\Psi_{h-1} \circ \mathcal{A}$. We compute two type of errors. Type 1 error computes whether PPE merged these paths, i.e., predicted them as mapping to the same abstract state, when they go to *different endogenous* states. Type 2 error computes whether PPE predicted the paths as mapping to different abstract states, when they map to the *same endogenous* state. We report the total number of errors of both types by summing over all values of h and all pairs of different paths in $\Psi_{h-1} \circ \mathcal{A}$. Type 1 errors are more harmful, since they can lead to exploration failure. Specifically, merging paths going to different states may result in the algorithm avoiding one of the two states when exploring at the next time step. Type 2 errors are less serious but lead to inefficiency due to using redundant paths for exploration. When both errors are 0, then the model recovers the exact latent model up to relabeling.

Results. We report results in Figure 3c. We see that PPE is able to reduce the number of type 1 errors down to 0 using 2×10^5 episodes per time step. This is important since even a single type 1 error can cause exploration failures. Similarly, PPE is able to reduce type 2 errors and is able to get them down to 56 with 5×10^5 episodes. This is acceptable since type 2 errors do not cause exploration failures but only cause redundancy. Therefore, at 2×10^5 samples, the algorithm makes 0 type 1 errors and just a handful type 2 errors. This is remarkable considering that PPE compares roughly 2×10^5 pairs of paths in the entire run. Hence, it makes only $\leq 0.03\%$ type 2 errors. Further, the agent is able to plan using the learned transition model and receive the optimal return.

---

[2]We use the following popular gridworld codebase: https://github.com/maximecb/gym-minigrid

REFERENCES

Alekh Agarwal, Daniel Hsu, Satyen Kale, John Langford, Lihong Li, and Robert E Schapire. Taming the monster: A fast and simple algorithm for contextual bandits. In *International Conference on Machine Learning*, 2014.

Alekh Agarwal, Sham Kakade, Akshay Krishnamurthy, and Wen Sun. Flambe: Structural complexity and representation learning of low rank mdps. *Advances in Neural Information Processing Systems*, 2020a.

Alekh Agarwal, Sham M Kakade, Jason D Lee, and Gaurav Mahajan. Optimality and approximation with policy gradient methods in markov decision processes. In *Conference on Learning Theory*, 2020b.

András Antos, Csaba Szepesvári, and Rémi Munos. Learning near-optimal policies with bellman-residual minimization based fitted policy iteration and a single sample path. *Machine Learning*, 2008.

J Andrew Bagnell, Sham M Kakade, Jeff G Schneider, and Andrew Y Ng. Policy search by dynamic programming. In *Advances in Neural Information Processing Systems*, 2004.

Yuri Burda, Harri Edwards, Deepak Pathak, Amos Storkey, Trevor Darrell, and Alexei A Efros. Large-scale study of curiosity-driven learning. In *International Conference on Learning Representations*, 2018.

Yuri Burda, Harrison Edwards, Amos Storkey, and Oleg Klimov. Exploration by random network distillation. In *International Conference on Learning Representations*, 2019.

Jinglin Chen and Nan Jiang. Information-theoretic considerations in batch reinforcement learning. In *International Conference on Machine Learning*, 2019.

Christoph Dann, Tor Lattimore, and Emma Brunskill. Unifying PAC and regret: Uniform PAC bounds for episodic reinforcement learning. In *Advances in Neural Information Processing Systems*, 2017.

Christoph Dann, Nan Jiang, Akshay Krishnamurthy, Alekh Agarwal, John Langford, and Robert E Schapire. On oracle-efficient PAC RL with rich observations. In *Advances in Neural Information Processing Systems*, 2018.

Thomas G Dietterich, George Trimponias, and Zhitang Chen. Discovering and removing exogenous state variables and rewards for reinforcement learning. *arXiv preprint arXiv:1806.01584*, 2018.

Simon S Du, Akshay Krishnamurthy, Nan Jiang, Alekh Agarwal, Miroslav Dudík, and John Langford. Provably efficient RL with rich observations via latent state decoding. In *International Conference on Machine Learning*, 2019.

Yonathan Efroni, Nadav Merlis, and Shie Mannor. Reinforcement learning with trajectory feedback. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2021.

Damien Ernst, Pierre Geurts, and Louis Wehenkel. Tree-based batch mode reinforcement learning. *Journal of Machine Learning Research*, 2005.

Carles Gelada, Saurabh Kumar, Jacob Buckman, Ofir Nachum, and Marc G Bellemare. Deepmdp: Learning continuous latent space models for representation learning. In *International Conference on Machine Learning*, 2019.

Robert Givan, Thomas Dean, and Matthew Greig. Equivalence notions and model minimization in markov decision processes. *Artificial Intelligence*, 2003.

Danijar Hafner, Timothy Lillicrap, Ian Fischer, Ruben Villegas, David Ha, Honglak Lee, and James Davidson. Learning latent dynamics for planning from pixels. In *International Conference on Machine Learning*, 2019.

Nan Jiang, Akshay Krishnamurthy, Alekh Agarwal, John Langford, and Robert E Schapire. Contextual decision processes with low Bellman rank are PAC-learnable. In *International Conference on Machine Learning*, 2017.

Sham M Kakade and John Langford. Approximately optimal approximate reinforcement learning. In *International Conference on Machine Learning*, 2002.

John Langford and Tong Zhang. The epoch-greedy algorithm for multi-armed bandits with side information. In *Advances in Neural Information Processing Systems*, 2008.

Michael Laskin, Aravind Srinivas, and Pieter Abbeel. Curl: Contrastive unsupervised representations for reinforcement learning. In *International Conference on Machine Learning*. PMLR, 2020.

Dipendra Misra, Mikael Henaff, Akshay Krishnamurthy, and John Langford. Kinematic state abstraction and provably efficient rich-observation reinforcement learning. In *International conference on machine learning*, pages 6961–6971. PMLR, 2020.

Aditya Modi, Nan Jiang, Ambuj Tewari, and Satinder Singh. Sample complexity of reinforcement learning using linearly combined model ensembles. In *International Conference on Artificial Intelligence and Statistics*. PMLR, 2020.

Deepak Pathak, Pulkit Agrawal, Alexei A Efros, and Trevor Darrell. Curiosity-driven exploration by self-supervised prediction. In *International Conference on Machine Learning*, 2017.

Aviv Rosenberg and Yishay Mansour. Online convex optimization in adversarial markov decision processes. In *International Conference on Machine Learning*, 2019.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv:1707.06347*, 2017.

Lior Shani, Yonathan Efroni, and Shie Mannor. Adaptive trust region policy optimization: Global convergence and faster rates for regularized mdps. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2020.

Haoran Tang, Rein Houthooft, Davis Foote, Adam Stooke, OpenAI Xi Chen, Yan Duan, John Schulman, Filip DeTurck, and Pieter Abbeel. #Exploration: A study of count-based exploration for deep reinforcement learning. In *Advances in Neural Information Processing Systems*, 2017.

Amy Zhang, Rowan McAllister, Roberto Calandra, Yarin Gal, and Sergey Levine. Learning invariant representations for reinforcement learning without reconstruction. *arXiv preprint arXiv:2006.10742*, 2020.