Learning to See by Looking at Noise

Abstract

Current vision systems are trained on huge datasets, and these datasets come with costs: curation is expensive, they inherit human biases, and there are concerns over privacy and usage rights. To counter these costs, interest has surged in learning from cheaper data sources, such as unlabeled images. In this paper we go a step further and ask if we can do away with real image datasets entirely, instead learning from procedural noise processes. We investigate a suite of image generation models that produce images from simple random processes. These are then used as training data for a visual representation learner with a contrastive loss. In particular, we study statistical image models, randomly initialized deep generative models, and procedural graphics models. Our findings show that it is important for the noise to capture certain structural properties of real data but that good performance can be achieved even with processes that are far from realistic. We also find that diversity is a key property to learn good representations.

1 Introduction

The importance of data in modern computer vision is hard to overstate. Time and again we have seen that better models are empowered by bigger data. The ImageNet dataset [1], with its 1.4 million labelled images, is widely thought to have spurred the era of deep learning, and since then the scale of vision datasets has been increasing at a rapid pace; current models are trained on up to one billion images [2]. In this paper we question the necessity of such massive training sets of real images.

Instead, we investigate a suite of procedural noise models that generate images from simple random processes. These are then used as training data for a visual representation learner.

We identify two key properties that make for good synthetic data for training vision systems: 1) naturalism, 2) diversity. Interestingly, the most naturalistic data is not always the best, since naturalism can come at the cost of diversity. The fact that naturalistic data helps may not be surprising, and it suggests that indeed, large-scale real data has value. However, we find that what is crucial is not that the data be *real* but that it be *naturalistic*, i.e. it must capture certain structural properties of real data. Many of these properties can be captured in simple noise models (Fig. 1).

The implications of our work are several fold. First, our results call into question the true complexity of the problem of vision – if very short programs can generate and train a high-performing vision system, then vision may be simpler than we thought, and might not require huge data-driven systems to achieve adequate performance. Second, our methods open the door to training vision systems without reliance on datasets. The value in this is that datasets are encumbered by numerous costs: they may be expensive, biased, private, or simply intractable to collect. We do not argue for removing datasets from computer vision entirely (as real data might be required for evaluation), but rather reconsidering what can be done in their absence.

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

Figure 1: Which of these image crops come from real photos and which are noise? See footnote for answers[1]. These crops are examples of what MoCo v2 [3] sees as input in our experiments.

2 Related work

2.1 A short history of image generative models

Out of the $\mathbb{R}^{3n^2}$ dimensional space spanned by $3 \times n^2$ color images, natural images occupy a small part of that space, the rest is mostly filled by noise. During the last decades, researchers have studied the space of natural images in order to build models capable of compressing, denoising and generating images. The result of this research is a sequence of generative image models of increasing complexity narrowing down the space occupied by natural images within $\mathbb{R}^{3n^2}$.

One surprising finding is that natural images follow a power law on the magnitude of their Fourier transform [4, 5]. This is the basis of Wiener image denoising [6] and scale invariant models of natural images [7, 8]. Dead leaves model [8, 9] were an attempt at generating images that explained the power law found in natural images and inspired the Retinex algorithm [10]. The multiscale and self-similar nature of natural images inspired the use of fractals [11, 12, 13] as image models.

Coding research for TV [5] and image modeling [6, 14, 15, 16] showed another remarkable property of natural images: the output values of zero mean wavelets to natural images is sparse and follows a generalized Laplacian distribution [6]. Color and intensity distributions in natural images have also been studied and found to follow rules that deviate from random noise [10, 17]. Research in texture synthesis showed how these statistical image models produced more realistic looking textures [18, 19]. Those required fitting the image model parameters to specific images to sample more "like it". Recently, GANs [20] have shown remarkable image synthesis results [21]. Although GANs need real images in order to learn the network parameters, we show in this paper that they introduce a structural prior useful to encode image properties without requiring any training.

2.2 Training without real data / training with synthetic data

Through the above progression, generative models have become increasingly complex, with more parameters and more training data needed to fit these parameters. The same has happened with vision systems in general: state-of-the-art systems like BiT [22], CLIP [23], and SEER [2] obtain their best results on 300 million, 400 million, and 1 billion images respectively. These papers further show that such large data is critical to getting the best performance.

While this may be true, other work has shown that much smaller data is sufficient to already get decent performance. A single image can be enough to train, from scratch, a compelling generative model [24, 25] or visual representation [26], and, *even with no training data at all*, deep architectures already encode useful image priors that can be exploited for low-level vision tasks [27] or for measuring perceptual similarity [28]. Our results, using an untrained StyleGANv2 [29] to generate training data, further affirm the utility of the structural priors in neural net architectures.

An alternative to training with real data is to train on synthetic data. This approach has been widely used in low-level tasks like depth, stereo, or optical flow estimation [30, 31, 32, 33], where 3D rendering engines can provide densely annotated data to learn from. Interestingly, for this class of tasks diversity has been shown to be more important than realism [34], making procedurally generated scenes an effective alternative to renderings designed by professional 3D artists [35, 36].

In this paper we push even further away from realism, generating synthetic data from simple noise processes. The closest prior work in this direction is [37], which used automatically generated fractals to pre-train neural networks that converge faster than their randomly initialized counterparts. While they demonstrated that fractals can be effective for pre-training, there is still a large gap compared

---

[1]Answers: 1,3,4,5,6,8,14 are from ImageNet images.

to pre-training on real data. We explore a much broader range of noise processes, including many classic models from the image coding and texture synthesis literature.

The use of randomized training data has also been explored under the heading of domain randomization [38], where, 3D synthetic data is rendered under a variety of lighting conditions to transfer to real environments where the lighting may be unknown. Our approach can be viewed as an extreme form of domain randomization that does away with the simulation engine entirely: make the training data so diverse that a natural image will just look like a sample from the noise process.

There is some evidence that biology takes a similar approach during the prenatal development of the vision system. "Retinal waves" – spontaneous, semi-random activations of the retina – are thought to entrain edge detectors and other simple structures in the developing mammalian brain [39].

3 A progression of image generative models

Here we provide the details for the image models we will use in this paper. We test a suite of generative models of the form $g_\theta : \mathbf{z} \to \mathbf{x}$, where $\mathbf{z}$ are stochastic latent variables and $\mathbf{x}$ is an image. We will treat image generation as a hierarchical process in which first the parameters of a model, θ, are sampled, and then the image is sampled given these parameters and stochastic noise. The parameters θ define properties of the distribution from which we will sample images, for example the mean color of the image. The sampling process is as follows: $\theta \sim p(\theta)$, $\mathbf{z} \sim p(\mathbf{z})$, and $\mathbf{x} = g_\theta(\mathbf{z})$, which corresponds to sampling images from the distribution $p(\mathbf{x}, \theta) = p(\mathbf{x}|\theta)p(\theta)$. The parameters θ that define the model may be fit to real data or not. We will explore the case where the parameters are not fit to real data but instead sampled from simple prior distributions. Next we describe the generative image models that we will evaluate in this paper (Fig. 2).

3.1 Procedural image models

The first class of models belong to the family of procedural image models. Procedural models are capable of generating very realistic looking images in specific image domains. We include in this set also fractals, although they could make a class on its own.

Fractals: Fractals have been shown to capture geometric properties of elements found in nature [40]. Consequently, image models consisting in renderings of human designed shapes with fractal structure [37] are likely to reproduce patterns found in natural images.

CG: Simulators and game engines rely on a mixture of human driven design and procedural methods to generate environments simulating real world properties such as illumination, 3D, and semantics. Here we include three CG models popular in computer vision with available datasets: CLEVR [41], DMLab [42] and MineRL [43].

3.2 Dead leaves image models

The second family of models are Dead leaves, one of the simplest image models. We consider simple shapes (leaves) like circles, triangles and squares, which are positioned uniformly at random in the image canvas until it is covered. To produce each shape, we circumscribe it in a circle with a radius following an exponential distribution of parameter λ. This procedure has been shown to produce images that have similar statistics to natural images, such as having a $1/|f|^\alpha$ power spectrum [8] and non-gaussian distribution of derivatives and wavelet coefficients [44].

In this study we will consider four dead leaves models: **Dead leaves - Squares:** Only uses squares axis aligned. **Dead leaves - Oriented:** Squares are randomly rotated. **Dead leaves - Shapes:** Leaves can be circles, triangles and rectangles. **Dead leaves - Textured:** uses square leaves filled with a texture sampled from the statistical image models described in the next section.

3.3 Statistical image models

The third family of models is statistical image models with increasing complexity. Several generative models can be composed by using different combinations of properties.

Figure 2: Samples from our synthetic datasets: a-d) CG synthetic images, e-h) Dead-leave models, i-l) Statistical image models, m-p) StyleGAN-based models with different weight initializations, and q-r) Feature visualizations.

Spectrum: The magnitude of the Fourier transform of many natural images follows a power law, $1/|f|^\alpha$, where α is a constant close to 1 [4]. In this generative model we will sample random noise images constrained to have FT magnitude following $1/(|f_x|^a + |f_y|^b)$ with a and b being two random numbers uniformly sampled in the range $[0.5, 3.5]$. This model introduces a bias towards horizontal and vertical image orientations typical of natural images [45]. To generate color images we first sample three random orthogonal color directions and then generate power-law-noise on each channel independently. Samples from this model are shown in Fig. 2(i).

Wavelet-marginal model (WMM): Following [46], we generate textures by modelling their histograms of wavelet coefficients. To produce a texture, we create marginal histograms for the coefficients c_i at N scales ($i \in \{0...N-1\}$) and 4 orientations following a Generalized normal distribution centered at zero, thus $p(c_i) \propto \exp((-|c_i|/\alpha_i)^{\beta_i})$. Each scale i represents the image down-scaled by factor of 2^i, and the parameters α_i and β_i for each scale are $\alpha_i = 4^{2^i}$ and $\beta_i \sim 0.4 + \mathcal{U}(0, 0.4)$. In practice we use $N = 3$ and $N = 4$ for generating 128×128 and 256×256 resolution images respectively. Once we have sampled a marginal distribution of wavelet coefficients for each of the three channels, we do histogram matching iteratively starting from a Gaussian noise image following [47]. Fig. 2(j) shows samples from this model.

Color histograms: Here we take a generative model that follows the color distribution of the dead-leaves model. First we sample a number of regions $N \sim 3 + \lfloor \mathcal{U}(0, 20) \rfloor$, their relative sizes $S \sim 0.001 + \mathcal{U}(0, 1)$ and color at uniform. This results in a color distribution different from uniform.

Combining all these different models allows capturing color distributions, spectral components and wavelet distributions that mimic those typical of natural images. Fig. 2(k) shows the result of sampling from a model that enforces random white noise to have the power-law spectrum and the color histogram according to this model. Fig. 2(l) shows samples from a model incorporating all of those properties (spectrum, color and WMM). Those models produce intriguing images but fail to capture the full richness of natural images as shown in Fig. 2(i-l).

3.4 Generative adversarial networks

The fourth family of models is based on the architecture of GANs. Commonly, the parameters of GANs are trained in order to generate realistic samples of a given training distribution. Here, *we do not use adversarial training or any training data.* Instead, we explore different types of initializations, study the usefulness of the GAN architecture as a prior for image generation, and show that effective data generators can be formed by sampling the model parameters from simple prior distributions. We use an untrained StyleGANv2 [29], and modify its initialization procedure to obtain images with different characteristics. This results in four classes of StyleGAN initializations:

StyleGAN-Random is the default initialization. Fig. 2(m) shows samples from this model. They lack high frequency image content, since the noise maps are not applied at initialization.

StyleGAN-High-freq. In this model, we increase high-frequency image content by sampling the noise maps as $1/f^\alpha$ noise with $\alpha \sim \mathcal{U}(0.5, 2)$, which models the statistics of natural images [4]. Additionally, the convolutional filters on all layers are randomly sampled from a bank of 3×3 wavelet filters, and each sampled wavelet is multiplied by a random amplitude $\sim \mathcal{N}(0, 1)$. Note that using Wavelets as spatial filter is a common practice when hand-designing networks [48, 49] and seems to well capture the underlying general structure of visual data. The samples in Fig. 2(n) show that this model generates high-frequency structures which are fairly uniformly distributed across the image.

StyleGAN-Sparse. Natural images exhibit a high degree of sparsity. In this model, we increase sparsity of the images through two modifications. First, we modulate the $1/f^\alpha$ noise maps using a Laplacian envelope. We sample a 4×4 grid of i.i.d. Laplacian noise, resize it to the desired noise map resolution using bicubic upsampling, and multiply this envelope with the original sampled $1/f^\alpha$ noise. Second, at each convolution, we add a random bias $\sim \mathcal{U}(-0.2, 0.2)$, which, in conjunction with the nonlinearities, further increases sparsity. Fig. 2(o) shows that the images created by this model indeed appear sparser. Yet, they are still lacking discernible image structures.

StyleGAN-Oriented. Oriented structures are a crucial component of natural images. We found that an effective way to introduce such structures to the previous models is to tie the wavelets, i.e. to use the same wavelet for all output channels. Under tied wavelets, the standard convolution becomes $y_k = \sum_l [a_{k,l} (x_l \star f_l)] + b_k$, where y_k denotes output channel k, x_l denotes input channel l, b_k is a bias term, $a_{k,l} \sim \mathcal{N}(0, 1)$ is a random amplitude multiplier and the wavelet f_l depends only on the input channel, but is shared across all output channels. As can be seen in Fig. 2(p), this creates visible, oriented structures in the output images.

3.5 Feature visualizations

The final class of models we study is feature visualizations [50]. CNNs can be used to produce novel images by optimizing the output of single or multiple units with respect to the input image, which is initialized with noise. Although these methods are commonly used to interpret and visualize the internal representation of a network, here we can use it as an image generative process. Following the procedure in [51], we obtain feature visualizations by optimizing the value of a single or a combination of two units of a neural network. We select those units from the layer that is typically used as feature extractor (i.e. the output of the penultimate linear layer), as we have empirically found this to yield more image-like visualizations compared to shallower layers. We create two datasets using this technique. **Feature vis. - Random:** ResNet50 with the default random initialization, shown in Fig. 2(q) and, 2) **Feature vis. - Dead leaves:** ResNet50 trained with dead leaves with diverse shapes, using MoCo v2 [3] and 1.3M sampled images. Samples are shown in Fig. 2(r).

4   Experiments

To study the proposed image generation processes, we train an AlexNet-based encoder using the Alignment and Uniformity loss proposed in [52], which is a form of contrastive loss theoretically equivalent to the popular InfoNCE loss [53]. We generate 105k samples using the proposed image models at 128×128 resolution, which are then downsampled to 96×96 and cropped to 64×64 before being fed to the encoder. After unsupervised training, we evaluate linear training performance (without finetuning) on the representation right before the projection layer, following standard practice [52, 53]. We fix a common set of hyperparameters for all the methods under test to the values found to perform well by the authors of [52]. Further details of the training are provided in the Sup.Mat.

Figure 3: Top-1 accuracy for the different models proposed and baselines for Imagenet-100 [54]. The horizontal axis shows generative models sorted by performance. The two dashed lines represent approximated upper and lower bounds in performance that one can expect from a system trained from samples of a generic generative image model.

Figure 4: Average top-1 accuracy across the tasks in each of the three groups of tasks in VTAB [55]. The horizontal axis shows the different image generative models sorted by the average performance across all tasks. DMLab and CLEVR trained networks are not tested, as these datasets are present on some VTAB tasks.

We evaluate performance using Imagenet-100 [54] and the Visual Task Adaptation Benchmark [55]. VTAB consists in 19 classification tasks which are grouped into three categories: a) Natural, consisting in images of the world taken with consumer cameras b) Specialized, consisting in images of specialized domains, such as medical or aerial photography and c) Structured, where the classification tasks requires understanding specific properties like shapes or distances. For each of the datasets in VTAB, we fix the number of training and validation samples to 10k at random for the datasets where there are more samples available.

As an upper-bound for the maximum expected performance with synthetic images, we consider the same training procedure but using the following real datasets: 1) Places365 [56] consisting of a wide set of classes, but a different domain 2) STL-10 [57], consisting of only 10 classes of natural images and 3) Imagenet1k [1], a superset of Imagenet100. As baselines we use mean image colors, raw pixels and features obtained by an untrained Alexnet (denoted CNN - Random).

4.1 Image model comparison

Figures 3 and 4 show the performance for the proposed fully generative methods from noise on Imagenet100 and VTAB (Tables can be found in the Sup.Mat.). The results on both datasets show an increasing performance for Natural dataset (Imagenet100 and the Natural tasks in VTAB) that match the qualitative complexity and diversity of samples as seen in Fig. 2. In the other hand, Structured and Specialized tasks do not benefit as much from natural data (as seen in the middle and right-most plots in Fig. 4), and our models perform similarly for the tasks under test in this setting.

4.2 Large scale experiments

Finally, we test one of the best performing methods for each type on a large scale experiment using a Resnet50 encoder instead of AlexNet. We generate 1.3M samples of the datasets at 256×256

	Pretraining dataset							
	Real images		Procedural images			Other		
Testset	ImageNet	Places	CNN -Random	FractalDB	Dead leaves -Shapes	Feature Vis -Dead leaves	Spectrum +C+WMM	StyleGAN -Oriented
Imagenet-1K	67.50	55.59	4.36	23.86	20.00	28.49	35.28	38.12
Imagenet-100	86.12	76.00	10.84	44.06	38.34	49.48	56.04	58.70

Table 1: Performance of linear transfer for a ResNet50 pre-trained on different image models using MoCo-v2.

Figure 5: Feature visualizations for AlexNet-based encoder trained on some of the proposed datasets, for the 3rd and 5th (last) convolutional layer, using the procedure in [51].

resolution, and train using the procedure described in MoCo v2 [3] with the default hyperparameters for Imagenet1k. The results in Table 1 show that the relative performance for the experiments with the Alexnet-based encoder is approximately preserved (except for dead leaves, which underperforms FractalDB-1k). Despite using the MoCo v2 hyperparameters found to be good for Imagenet1k (which may not be optimal for our datasets) and not using any real data, our best performing model achieves 38.12% top-1 accuracy on linear classification on top of the learnt features.

5 What properties make for good generated data?

As we have seen, representations learned from noise-like images can be surprisingly powerful. Why is this the case? Intuitively, one might think that the features learned from these datasets themselves resemble noise. Interestingly, this is not the case. Fig. 5 shows the diversity of feature activations learned with the different datasets, extracted using the same procedure as described in Section 3.5. Though some datasets fail to capture certain properties (e.g. the Dead leaves squares dataset only reacts to axis-aligned images), feature visualizations qualitatively show that our datasets contain sufficient structure to learn a variety of complex features.

Yet, not all of our datasets reach the same performance, which raises the question what makes a generated dataset good. Which properties are strongly correlated with performance? In the following, we investigate the statistical properties of individual images (5.1) and datasets as a whole (5.2)

5.1 Properties of individual images

Across our datasets, the image appearance varies significantly (see Fig. 2): They contain different structures and shapes, different color profiles, different levels of "realism", and different effects such as occlusions. How much of the difference in performance can be attributed to such low-level, per-image appearance characteristics?

Color profile. The first and most basic question is how important the color characteristics of our datasets are, since even in such a basic dimension as color, the datasets differ greatly (see Fig. 2). To test the impact of color characteristics on performance, we measure color similarity between the test dataset (here, ImageNet-100) and each of our pretraining datasets. First, we extract L*a*b values

(a) Color distance to ImageNet   (b) Sparsity of images   (c) Variation within images

Figure 6: Different properties of the images have different impact on accuracy. (a) Having a similar color distribution to natural images is important. (b) The spectral properties of dataset images are weakly correlated with accuracy, as long as they are within the right range. (c) There exists a sweet spot for variation within the images; having a higher variation results in less successful contrastive learning and decreased performance.

from 50K images from all datasets and from ImageNet-100[2]. The color distribution of each dataset can then be modelled as a three-dimensional Gaussian, and the color difference between two datasets can be computed as the symmetric KL divergence between those distributions. Fig. 6(a) shows that the color similarity of most of our datasets to natural images is in fact fairly low; at the same time we see a clear negative correlation between performance and color distance ($r = -0.57$).

Image spectrum. It is well known that the spectrum of natural images can be modelled as a heavy tailed function $A/|f|^\alpha$, with A a scaling factor and typically $\alpha \in [0.5, 2.0]$ [45]. How well do our datasets resemble these statistics, and how much does this impact performance? Fig. 6(b) shows that the statistics of most of our datasets fall within this range, with the exception of Stylegan-default. However, while an exponent $\alpha \in [1.4, 1.7]$ seems to benefit performance, the correlation is weak.

Image coherence. Contrastive Learning utilizes different views as positive pairs during training, which are commonly generated using random augmentations of the same input image. For this to work, the images need a degree of global coherence, i.e. two views of the same image should be more similar than two views from different images. To test the amount of coherence in our datasets and how this impacts downstream accuracy, we first compute the average perceptual variation within a dataset as $\frac{1}{N} \sum \text{LPIPS}\left(f\left(I_n\right), g\left(I_n\right)\right)$, where f, g are two random crops of the same image and LPIPS is the perceptual distance from [28]. Fig. 6(c) shows the results. Interestingly, there seems to be a sweet spot of perceptual variation around 0.37; for datasets with lower variation, perceptual variation is strongly correlated with accuracy ($r = 0.75$). Going beyond this sweet spot decreases accuracy, since now two augmentations of the same image are too dissimilar to provide good information. Finding a similar effect, [58] showed that there is a sweet spot for augmentation strength in contrastive learning.

5.2 Properties of the datasets

Beyond the properties of individual images, it is important to ask which properties of a dataset as a whole explain its level of performance. The first obvious predictor for good performance on a given test task is the distance of the training data distribution to the test data. We can quantify this using the Fréchet Inception Distance [59], which measures the distance between two sets of images by fitting Gaussians to the distribution of Inception features and measuring the difference between those Gaussians. As shown in Fig. 7(a), FID is strongly negatively correlated ($r = -.85$) with accuracy.

An ideal pretraining dataset would therefore resemble the test dataset as closely as possible, achieving a low FID as well as high precision and recall to the test dataset [60]. Interestingly, the trend we observe in our data points in a different direction: Precision is *negatively* correlated with accuracy ($r = -0.67$), and the data shows a strong negative correlation between precision and recall ($r = -0.88$). This can be explained by the fact that our methods are not capable of perfectly reproducing the entirety of ImageNet, leaving two possible scenarios: Either a dataset is concentrated in a small

---

[2]In this and the next section, all measures were computed on 50K random images from the respective datasets, and, where applicable, compared against the reference statistics of ImageNet-100. To avoid distortions, correlations are always computed without taking the datasets ImageNet-100 and ImageNet1k into account.

(a) FID	(b) Precision vs volume	(c) Recall vs volume

Figure 7: Properties of the datasets as a whole. (a) Resembling the test data is the best predictor of performance. Since a perfect overlap with the test data cannot be achieved, recall and precision are negatively correlated; (b) a high precision corresponds to datasets with small volume, resulting in low performance. (c) Recall is positively correlated with both volume and accuracy.

part of the image manifold (images from CLEVR and DMLAB look naturalistic, yet are severely restricted in their diversity compared to natural images), or the dataset overshoots the manifold of test images, containing as much diversity as possible, in the limit encompassing the test dataset as a subset. Should a dataset be as realistic (i.e. maximize precision), or as diverse as possible?

An extreme version of the first case would be a training dataset that is concentrated around a few points of the test dataset, which would achieve high precision but low recall, and generally have low diversity. Given a distribution of features, we can measure the diversity of the dataset as $|\Sigma|$, i.e. the determinant of the covariance matrix in this feature space. Here, we use the same inception features as for the FID (see above). Fig. 7(b) shows precision vs. log-volume for all datasets; color indicates the performance on ImageNet-100. As can be seen, datasets with a high precision tend to not be particularly diverse, and are negatively correlated with log-volume ($r = -0.84$). As volume increases, precision decreases, yet performance benefits.

Considering Recall, the picture changes. As shown in Fig. 7(c), higher recall is (after a certain point) positively correlated with both log-volume ($r = .79$) and accuracy ($r = .83$). Interestingly, this does *not* mean that precision is irrelevant – when controlling for recall, precision is again positively correlated with accuracy, albeit more weakly ($r = .22$). The reason for this behavior is that in case of our datasets, precision and recall are negatively correlated, and thus present a trade-off. If such a trade-off is necessary when designing datasets for pretraining, our results indicate that maximizing recall might be more important than maximizing precision. Interestingly, despite a completely different setting, the same effect was observed in [34].

6   Conclusion

Can we learn visual representations without using real images? The datasets presented in this paper are composed of images with different types of structured noise. We have shown that, when designed using results from past research on natural image statistics, these datasets can successfully train visual representations. We hope that this paper will motivate the study of new generative models capable of producing structured noise achieving even higher performance when used in a diverse set of visual tasks. Would it be possible to match the performance obtained with ImageNet pretraining? In fact, maybe in the absence of a large training set specific to a particular task, the best pre-training might not be using a standard real dataset such as ImageNet.

Although it might be tempting to believe that the datasets presented in this paper might reduce the impact of dataset bias, bias might still exist (although they might not come from social biases, they might still impact differently subsets of the test data) and it will be important to characterize it for each particular application.

References

[1] Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, Alexander C. Berg, and Li Fei-Fei. ImageNet Large Scale Visual Recognition Challenge. *International Journal of Computer Vision (IJCV)*, 115(3):211–252, 2015.

[2] Priya Goyal, Mathilde Caron, Benjamin Lefaudeux, Min Xu, Pengchao Wang, Vivek Pai, Mannat Singh, Vitaliy Liptchinsky, Ishan Misra, Armand Joulin, and Piotr Bojanowski. Self-supervised pretraining of visual features in the wild, 2021.

[3] Xinlei Chen, Haoqi Fan, Ross Girshick, and Kaiming He. Improved baselines with momentum contrastive learning, 2020.

[4] G. J. Burton and Ian R. Moorhead. Color and spatial structure in natural scenes. *Appl. Opt.*, 26(1):157–170, Jan 1987.

[5] E. R. Kretzmer. Statistics of television signals. *Bell System Technical Journal*, 31(4):751–763, 1952.

[6] E P Simoncelli. Statistical modeling of photographic images. In Alan Bovik, editor, *Handbook of Image and Video Processing*, chapter 4.7, pages 431–441. Academic Press, May 2005. 2nd edition.

[7] David J Field. *Scale-invariance and Self-similar 'Wavelet' Transforms: an Analysis of Natural Scenes and Mammalian Visual Systems.*, pages 151–193. Oxford University Press., 1993.

[8] Daniel L. Ruderman. Origins of scaling in natural images. *Vision Research*, 37(23):3385–3398, 1997.

[9] A. B Lee, D. Mumford, and J. Huang. Occlusion models for natural images: A statistical study of a scale-invariant dead leaves model. *International Journal of Computer Vision*, 41(1):35—59, 2001.

[10] Edwin H. Land and John J. McCann. Lightness and retinex theory. *J. Opt. Soc. Am.*, 61(1):1–11, Jan 1971.

[11] A.P. Pentland. *Fractal-based Description of Natural Scenes*. Technical note. Defense Advanced Research Projects Agency, 1983.

[12] Antonio Turiel, Nestor Parga, Daniel L. Ruderman, and Thomas W. Cronin. Multiscaling and information content of natural color images. *Physical Review E*, 62(1):1138, 2000. Copyright (C) 2009 The American Physical Society; Please report any problems to prola@aps.org.

[13] Christoph Redies, Jens Hasenstein, and Joachim Denzler. Fractal-like image statistics in visual art: similarity to natural scenes. *Spatial Vision*, 21(1-2):137–48, 2007. PMID: 18073055.

[14] P. Burt and E. Adelson. The laplacian pyramid as a compact image code. *IEEE Transactions on Communications*, 31(4):532–540, 1983.

[15] D. J. Field. Relations between the statistics of natural images and the response properties of cortical cells. *J Opt Soc Am A*, 4(12):2379—2394, 1987.

[16] Bruno A Olshausen and David J Field. Sparse coding of sensory inputs. *Curr Opin Neurobiol*, 14(4):481—487, 2004.

[17] Fuhui Long, Zhiyong Yang, and Dale Purves. Spectral statistics in natural scenes predict hue, saturation, and brightness. *Proceedings of the National Academy of Sciences of the United States of America*, 103(15):6013–8, 2006. PMID: 16595630.

[18] David J. Heeger and James R. Bergen. Pyramid-based texture analysis/synthesis. In *Proceedings of the 22nd Annual Conference on Computer Graphics and Interactive Techniques*, SIGGRAPH '95, page 229–238, New York, NY, USA, 1995. Association for Computing Machinery.

[19] J. Portilla and E. P Simoncelli. A parametric texture model based on joint statistics of complex wavelet coefficients. *International Journal of Computer Vision*, 40(1):49—70, 2000.

[20] Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In Z. Ghahramani, M. Welling, C. Cortes, N. Lawrence, and K. Q. Weinberger, editors, *Advances in Neural Information Processing Systems*, volume 27. Curran Associates, Inc., 2014.

[21] Tero Karras, Samuli Laine, and Timo Aila. A style-based generator architecture for generative adversarial networks. *CoRR*, abs/1812.04948, 2018.

[22] Alexander Kolesnikov, Lucas Beyer, Xiaohua Zhai, Joan Puigcerver, Jessica Yung, Sylvain Gelly, and Neil Houlsby. Big transfer (bit): General visual representation learning. *arXiv preprint arXiv:1912.11370*, 6(2):8, 2019.

[23] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. *arXiv preprint arXiv:2103.00020*, 2021.

[24] Assaf Shocher, Shai Bagon, Phillip Isola, and Michal Irani. Ingan: Capturing and remapping the "dna" of a natural image. *ICCV*, 2019.

[25] Tamar Rott Shaham, Tali Dekel, and Tomer Michaeli. Singan: Learning a generative model from a single natural image. In *ICCV*, 2019.

[26] Yuki M Asano, Christian Rupprecht, and Andrea Vedaldi. A critical analysis of self-supervision, or what we can learn from a single image. *ICLR*, 2020.

[27] Dmitry Ulyanov, Andrea Vedaldi, and Victor Lempitsky. Deep image prior. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2018.

[28] Richard Zhang, Phillip Isola, Alexei A Efros, Eli Shechtman, and Oliver Wang. The unreasonable effectiveness of deep features as a perceptual metric. In *CVPR*, 2018.

[29] Tero Karras, Samuli Laine, Miika Aittala, Janne Hellsten, Jaakko Lehtinen, and Timo Aila. Analyzing and improving the image quality of stylegan. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2020.

[30] J.L. Barron, D.J. Fleet, and S.S. Beauchemin. Performance of optical flow techniques. *International Journal of Computer Vision*, 12:43–77, 1994.

[31] B McCane, K Novins, D Crannitch, and B Galvin. On benchmarking optical flow. *Computer Vision and Image Understanding*, 84(1):126–143, 2001.

[32] Simon Baker, Stefan Roth, Daniel Scharstein, Michael J. Black, J.P. Lewis, and Richard Szeliski. A database and evaluation methodology for optical flow. In *2007 IEEE 11th International Conference on Computer Vision*, 2007.

[33] D. J. Butler, J. Wulff, G. B. Stanley, and M. J. Black. A naturalistic open source movie for optical flow evaluation. In A. Fitzgibbon et al. (Eds.), editor, *European Conf. on Computer Vision (ECCV)*, Part IV, LNCS 7577, pages 611–625. Springer-Verlag, October 2012.

[34] Nikolaus Mayer, Eddy Ilg, Philipp Fischer, Caner Hazirbas, Daniel Cremers, Alexey Dosovitskiy, and Thomas Brox. What makes good synthetic training data for learning disparity and optical flow estimation? *International Journal of Computer Vision*, 126(9):942–960, Sep 2018.

[35] A. Dosovitskiy, P. Fischer, E. Ilg, P. Häusser, C. Hazırbaş, V. Golkov, P. v.d. Smagt, D. Cremers, and T. Brox. Flownet: Learning optical flow with convolutional networks. In *IEEE International Conference on Computer Vision (ICCV)*, 2015.

[36] Nikolaus Mayer, Eddy Ilg, Philip Häusser, Philipp Fischer, Daniel Cremers, Alexey Dosovitskiy, and Thomas Brox. A large dataset to train convolutional networks for disparity, optical flow, and scene flow estimation. In *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 4040–4048, 2016.

[37] Hirokatsu Kataoka, Kazushige Okayasu, Asato Matsumoto, Eisuke Yamagata, Ryosuke Yamada, Nakamasa Inoue, Akio Nakamura, and Yutaka Satoh. Pre-training without natural images, 2021.

[38] Josh Tobin, Rachel Fong, Alex Ray, Jonas Schneider, Wojciech Zaremba, and Pieter Abbeel. Domain randomization for transferring deep neural networks from simulation to the real world, 2017.

[39] James B Ackman, Timothy J Burbridge, and Michael C Crair. Retinal waves coordinate patterned activity throughout the developing visual system. *Nature*, 490(7419):219–225, 2012.

[40] Benoit B Mandelbrot. *The fractal geometry of nature*. Freeman, San Francisco, CA, 1982.

[41] Justin Johnson, Bharath Hariharan, Laurens van der Maaten, Li Fei-Fei, C. Lawrence Zitnick, and Ross Girshick. CLEVR: A Diagnostic Dataset for Compositional Language and Elementary Visual Reasoning. In *2017 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 1988–1997, 2017.

[42] Xiaohua Zhai, Joan Puigcerver, Alexander Kolesnikov, Pierre Ruyssen, Carlos Riquelme, Mario Lucic, Josip Djolonga, Andre Susano Pinto, Maxim Neumann, Alexey Dosovitskiy, Lucas Beyer, Olivier Bachem, Michael Tschannen, Marcin Michalski, Olivier Bousquet, Sylvain Gelly, and Neil Houlsby. The visual task adaptation benchmark. 2019.

[43] William H. Guss, Brandon Houghton, Nicholay Topin, Phillip Wang, Cayden Codel, Manuela Veloso, and Ruslan Salakhutdinov. MineRL: A large-scale dataset of Minecraft demonstrations. *Twenty-Eighth International Joint Conference on Artificial Intelligence*, 2019.

[44] Xaq Pitkow. Exact feature probabilities in images with occlusion, 2010.

[45] Antonio Torralba and Aude Oliva. Statistics of natural image categories. *Network: Computation in Neural Systems*, 14(3):391–412, 2003. PMID: 12938764.

[46] Eero P. Simoncelli. Modeling the joint statistics of images in the wavelet domain. In Michael A. Unser, Akram Aldroubi, and Andrew F. Laine, editors, *Wavelet Applications in Signal and Image Processing VII*, volume 3813, pages 188 – 195. International Society for Optics and Photonics, SPIE, 1999.

[47] D.J. Heeger and J.R. Bergen. Pyramid-based texture analysis/synthesis. In *Proceedings., International Conference on Image Processing*, volume 3, pages 648–651 vol.3, 1995.

[48] Joan Bruna and Stephane Mallat. Invariant scattering convolution networks. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 35(8):1872–1886, 2013.

[49] Matej Ulicny, Vladimir A. Krylov, and Rozenn Dahyot. Harmonic convolutional networks based on discrete cosine transform. *CoRR*, abs/2001.06570, 2020.

[50] Dumitru Erhan, Yoshua Bengio, Aaron Courville, and Pascal Vincent. Visualizing higher-layer features of a deep network. Technical Report 1341, University of Montreal, June 2009. Also presented at the ICML 2009 Workshop on Learning Feature Hierarchies, Montréal, Canada.

[51] Chris Olah, Alexander Mordvintsev, and Ludwig Schubert. Feature visualization. *Distill*, 2017. https://distill.pub/2017/feature-visualization.

[52] Tongzhou Wang and Phillip Isola. Understanding contrastive representation learning through alignment and uniformity on the hypersphere. 119:9929–9939, 13–18 Jul 2020.

[53] Aäron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *CoRR*, abs/1807.03748, 2018.

[54] Yonglong Tian, Dilip Krishnan, and Phillip Isola. Contrastive multiview coding. *CoRR*, abs/1906.05849, 2019.

[55] Xiaohua Zhai, Joan Puigcerver, Alexander Kolesnikov, Pierre Ruyssen, Carlos Riquelme, Mario Lucic, Josip Djolonga, Andre Susano Pinto, Maxim Neumann, Alexey Dosovitskiy, Lucas Beyer, Olivier Bachem, Michael Tschannen, Marcin Michalski, Olivier Bousquet, Sylvain Gelly, and Neil Houlsby. A large-scale study of representation learning with the visual task adaptation benchmark, 2020.

[56] Bolei Zhou, Agata Lapedriza, Aditya Khosla, Aude Oliva, and Antonio Torralba. Places: A 10 million Image Database for Scene Recognition. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2017.

[57] Adam Coates, Andrew Ng, and Honglak Lee. An Analysis of Single-Layer Networks in Unsupervised Feature Learning. In Geoffrey Gordon, David Dunson, and Miroslav Dudík, editors, *Proceedings of the Fourteenth International Conference on Artificial Intelligence and Statistics*, volume 15 of *Proceedings of Machine Learning Research*, pages 215–223, Fort Lauderdale, FL, USA, 11–13 Apr 2011. PMLR.

[58] Yonglong Tian, Chen Sun, Ben Poole, Dilip Krishnan, Cordelia Schmid, and Phillip Isola. What makes for good views for contrastive learning? In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 6827–6839. Curran Associates, Inc., 2020.

[59] Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. GANs Trained by a Two Time-Scale Update Rule Converge to a Local Nash Equilibrium. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017.

[60] Tuomas Kynkäänniemi, Tero Karras, Samuli Laine, Jaakko Lehtinen, and Timo Aila. Improved Precision and Recall Metric for Assessing Generative Models. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019.