Semi-relaxed Gromov-Wasserstein divergence with applications on graphs

Abstract

Comparing structured objects such as graphs is a fundamental operation involved in many learning tasks. To this end, the Gromov-Wasserstein (GW) distance, based on Optimal Transport (OT), has proven to be successful in handling the specific nature of the associated objects. More specifically, through the nodes connectivity relations, GW operates on graphs, seen as probability measures over specific spaces. At the core of OT is the idea of conservation of mass, which imposes a coupling between all the nodes from the two considered graphs. We argue in this paper that this property can be detrimental for tasks such as graph dictionary or partition learning, and we relax it by proposing a new semi-relaxed Gromov-Wasserstein divergence. Aside from immediate computational benefits, we discuss its properties, and show that it can lead to an efficient graph dictionary learning algorithm. We empirically demonstrate its relevance for complex tasks on graphs such as partitioning, clustering and completion.

1 Introduction

One of the main challenges in machine learning (ML) is to design efficient algorithms that are able to learn from structured data (Battaglia et al., 2018). Learning from datasets containing such non-vectorial objects is a difficult task that involves many areas of data analysis such as signal processing (Shuman et al., 2013), Bayesian and kernel methods on graphs (Ng et al., 2018; Kriege et al., 2020) or more recently geometric deep learning (Bronstein et al., 2017; 2021) and graph neural networks (Wu et al., 2020). In terms of applications, building algorithms that go beyond Euclidean data has led to many progresses, *e.g.* in image analysis (Harchaoui & Bach, 2007), brain connectivity (Ktena et al., 2017), social networks analysis (Yanardag & Vishwanathan, 2015) or for protein structure prediction (Jumper et al., 2021).

Learning from graph data is ubiquitous in a number of ML tasks. A first one is to learn graph representations that can encode the graph structure (a.k.a. *graph representation learning*). In this domain, advances on graph neural networks provided end-to-end embeddings showing state-of-the-art results given sufficiently labeled data (Ying et al., 2018; Morris et al., 2019; Gao & Ji, 2019; Wu et al., 2020). Another problem is to find a meaningful notion of *similarity/distance* between graphs. A way to address this problem is by leveraging geometric or signal properties though the use of graph kernels (Kriege et al., 2020) or other embeddings that deal with graph isomorphisms (Zambon et al., 2020). Finally, it is often interesting to establish meaningful structural correspondences between the nodes of the different graphs, also known as *graph matching* (Zhou & De la Torre, 2012; Maron & Lipman, 2018; Bernard et al., 2018; Yan et al., 2016) or to find a representative partition of the nodes of a graph, as tackled by *graph partitioning* or graph clustering methods (Chen et al., 2014; Nazi et al., 2019; Kawamoto et al., 2018; Bianchi et al., 2020).

Optimal Transport for structured data. A novel approach to graph modeling, based on the theory of Optimal Transport (OT, Peyré & Cuturi, 2019), has recently emerged from a series of works. Informally, the goal of OT is to match two probability distributions under the constraint of mass conservation and in order to minimize a given matching cost. OT originally tackles the problem of comparing probability distributions whose supports lie on the *same* metric space, by means of the so-called Wasserstein distance. Extensions to graph data analysis were introduced by either embedding the graphs in a space endowed with Wasserstein geometry (Nikolentzos et al., 2017;

Figure 1: Comparison of the GW matching (left) and asymmetric srGW matchings (middle and right) between graphs C and $\overline{C}$ with uniform distributions. Nodes of the source graph are colored based on their clusters. The OT from the source to the target nodes is represented by lines colored depending on the corresponding source node color. Nodes of the target graph are colored by average rgb color of the source nodes weighted by the OT entries.

Togninalli et al., 2019; Petric Maretic et al., 2019) or relying on the Gromov-Wasserstein (GW) distance (Mémoli, 2011; Sturm, 2012). The latter approach is a variant of the classical OT in which one aims at comparing probability distributions whose supports lie on *different* metric spaces by finding a matching of these distributions that is as close as possible to an isometry. By expressing graphs as probability measures over spaces specific to their topology, where the structure of a graph is represented through a pairwise distance/similarity matrix between its nodes, the GW distance computes both a soft assignment matrix between the nodes of the two graphs and a notion of distance between them (see the left part of Figure 1). These properties have proven to be useful for a wide range of tasks such as graphs matching and partitioning (Xu et al., 2019a; Chowdhury & Needham, 2021; Vayer et al., 2019), estimation of nonparametric graph models (*graphons*, Diaconis & Janson, 2007; Xu et al., 2021) or for graphs dictionary learning (Vincent-Cuaz et al., 2021; Xu, 2020a). GW has also been studied for directed graphs in Chowdhury & Mémoli (2019) and has been extended to labeled graphs thanks to the Fused Gromov-Wasserstein (FGW) distance in (Vayer et al., 2020).

Despite those recent successes, applications of GW to graph modeling still have several limitations. First, finding the GW distance remains challenging, as it boils down to solving a difficult non-convex quadratic program (Peyré et al., 2016; Solomon et al., 2016; Vayer et al., 2019), which, in practice, limits the size of the graphs that can be processed. A second limit naturally emerges when a probability mass function is introduced over the set of the graph nodes. The mass associated with a node refers to its relative importance and, without prior knowledge, each node is either assumed to share the same probability mass or to have one proportional to its degree. In this paper, we somehow argue that these choices can be suboptimal in several cases, and should be relaxed, with the additional benefit of lowering the computational complexity. As an illustration, consider Figure 1, where on the left image the GW matching is given between two graphs, with respectively two and three clusters, associated to uniform weights on the nodes. By relaxing the weight constraints over the second (middle image) or first graph (right image) we obtain different matchings, that can better preserve the structure of the source graph by reweighing the target nodes and thus selecting a meaningful sub-graph.

Contributions. We introduce a new transport based divergence between graphs derived from the GW distance, that we call the **semi-relaxed Gromov-Wasserstein (**srGW**)** divergence. After presenting its properties and motivating its use for ML applications, we propose an efficient solver for the corresponding optimization problem which better fits to modern parallel programming than exact solvers for GW. We empirically demonstrate the relevance of our divergence for graph partitioning tasks, Dictionary Learning (DL), clustering of graphs and graph completion datasets. With srGW, we recover SOTA performances at a significantly lower computational cost compared to methods based on GW.

2 MODELING GRAPHS WITH THE GROMOV-WASSERSTEIN DIVERGENCE

In this section we introduce more formally the GW distance and discuss two of its applications on graphs, namely graph partitioning and unsupervised graph representation learning. In the following the probability simplex with N-bins is denoted as $\Sigma_N := \{\boldsymbol{h} \in \mathbb{R}_+^N | \sum_i h_i = 1\}$.

GW as graphs similarity. In the OT context, a graph $\mathcal{G}$ with n nodes can be modeled as a couple $(\boldsymbol{C}, \boldsymbol{h})$ where $\boldsymbol{C} \in \mathbb{R}^{n \times n}$ is a matrix encoding the connectivity between nodes and $\boldsymbol{h} \in \Sigma_n$ is a histogram, referred here as distribution, modeling the relative importance of the nodes within the graph. The matrix $\boldsymbol{C}$ can be arbitrarily chosen as the graph adjacency matrix, or any other matrix describing the relationships between the nodes in the topology of the graph (*e.g.* shortest-path, Laplacian). The distribution is often considered as uniform ($\boldsymbol{h} = \frac{1}{n}\boldsymbol{1}_n$) but can also convey prior knowledge *e.g.* using the normalized degree distribution (Xu et al., 2019a). Consider now two graphs $\mathcal{G} = (\boldsymbol{C}, \boldsymbol{h})$ and $\overline{\mathcal{G}} = (\overline{\boldsymbol{C}}, \overline{\boldsymbol{h}})$, respectively with n and m nodes, potentially different ($n \neq m$). The GW distance between $\mathcal{G}$ and $\overline{\mathcal{G}}$ is defined as the result of the following optimization problem:

$$\mathrm{GW}_2^2(\boldsymbol{C}, \boldsymbol{h}, \overline{\boldsymbol{C}}, \overline{\boldsymbol{h}}) = \min_{\substack{\boldsymbol{T}\boldsymbol{1}_m = \boldsymbol{h} \\ \boldsymbol{T}^\top \boldsymbol{1}_n = \overline{\boldsymbol{h}}}} \sum_{ijkl} \left| C_{ij} - \overline{C}_{kl} \right|^2 T_{ik} T_{jl} \quad \text{with} \quad \boldsymbol{T} \in \mathbb{R}_+^{n \times m} \tag{1}$$

The optimal coupling $\boldsymbol{T}^\star$ acts as a probabilistic matching of nodes which tends to associate pairs of nodes that have similar pairwise relations in $\boldsymbol{C}$ and $\overline{\boldsymbol{C}}$ respectively, while preserving masses $\boldsymbol{h}$ and $\overline{\boldsymbol{h}}$ through its marginals constraints. GW defines a distance on the space of *metric measure* spaces invariant to measure preserving isometries such as nodes permutation (Mémoli, 2011; Sturm, 2012).

First applications of GW to ML on graphics problems (Peyré et al., 2016; Solomon et al., 2016) motivated further connections with graph partitioning. In the GW sense, this paradigm is illustrated by finding an ideally partitioned graph $\overline{\mathcal{G}} = (\overline{\boldsymbol{D}}, \overline{\boldsymbol{h}})$ of m clusters whose structure is a diagonal matrix $\overline{\boldsymbol{D}}$, representing the cluster's connections, and its distribution $\overline{\boldsymbol{h}}$ estimates the proportion of the nodes in each cluster (Xu et al., 2019a). The OT plan between a graph $\mathcal{G} = (\boldsymbol{C}, \boldsymbol{h})$ represented by its *adjacency matrix* $\boldsymbol{C}$ to this ideal graph can be used to recover $\mathcal{G}$'s clusters, if their number and proportions match the number and the weights of $\overline{\mathcal{G}}$'s nodes. Xu et al. (2019a) suggested to empirically refine both graph distribution by choosing $\boldsymbol{h}$ based on power-law transformations of the degree distribution of $\mathcal{G}$ and to deduce $\overline{\boldsymbol{h}}$ from $\boldsymbol{h}$ by linear interpolation. Chowdhury & Needham (2020) proposed to use heat kernels from the Laplacian of $\mathcal{G}$ instead of its adjacency binary representation, and proved that the resulting GW partitioning is closely related to the well-known spectral clustering (Fiedler, 1973).

The GW distance has been extended to graphs with node attributes (typically $\mathbb{R}^d$ vectors) thanks to the Fused Gromov-Wasserstein distance (FGW) (Vayer et al., 2019). In this context, an attributed graph $\mathcal{G}$ with n nodes is a tuple $\mathcal{G} = (\boldsymbol{C}, \boldsymbol{F}, \boldsymbol{h})$ where $\boldsymbol{F} \in \mathbb{R}^{n \times d}$ is its matrix of nodes features. FGW between two attributed graphs aims at finding an OT by minimizing a weighted sum of a GW cost on structures and a Wasserstein cost on features (balanced by a parameter $\alpha \in [0, 1]$). Most of the applications of GW can be naturally extended with FGW to attributed graphs.

GW for Unsupervised Graph Representation Learning. More recently, GW has been used as a data fitting term for unsupervised graph representation learning by means of Dictionary Learning (DL) (Mairal et al., 2009; Schmitz et al., 2018). While DL methods mainly focus on vectorial data (Ng et al., 2002; Candès et al., 2011; Bobadilla et al., 2013), DL applied to graphs datasets consists in factorizing them as composition of graph primitives (or atoms) encoded as $\{(\overline{\boldsymbol{C}}_k, \overline{\boldsymbol{h}}_k)\}_{k \in [\![K]\!]}$. The first approach proposed by (Xu, 2020a) consists in a non-linear DL based on entropic GW barycenters. On the other hand, Vincent-Cuaz et al. (2021) proposed a *linear* DL method by modeling graphs as a linear combination of graph atoms thus reducing the computational cost. In both cases, the *embedding problem* that consists in the projection of any graph on the learned graph subspace requires solving a computationally intensive optimization problem.

3 SEMI-RELAXED GROMOV-WASSERSTEIN DIVERGENCE

3.1 DEFINITION AND PROPERTIES

Given two observed graphs $\mathcal{G} = (\boldsymbol{C}, \boldsymbol{h})$ and $\overline{\mathcal{G}} = (\overline{\boldsymbol{C}}, \overline{\boldsymbol{h}})$ of n and m nodes, we propose to find a correspondence between them while relaxing the weights $\overline{\boldsymbol{h}}$ on the second graph. To this end we introduce the *semi-relaxed Gromov-Wasserstein divergence* as :

$$\mathrm{srGW}_2^2(\boldsymbol{C}, \boldsymbol{h}, \overline{\boldsymbol{C}}) = \min_{\overline{\boldsymbol{h}} \in \Sigma_m} \mathrm{GW}_2^2(\boldsymbol{C}, \boldsymbol{h}, \overline{\boldsymbol{C}}, \overline{\boldsymbol{h}}) \tag{2}$$

This means that we search for a reweighing of the nodes of $\overline{\mathcal{G}}$ leading to a graph with structure $\overline{C}$ with minimal GW distance from $\mathcal{G}$. While the optimization problem (2) above might seems complex to solve, it is actually equivalent to a GW problem where the mass constraints on the second marginal of T are relaxed, reducing the problem to:

$$\text{srGW}_2^2(C, h, \overline{C}) = \min_{T\mathbf{1}_m = h} \sum_{ijkl} |C_{ij} - \overline{C}_{kl}|^2 T_{ik}T_{jl} \quad \text{with} \quad T \in \mathbb{R}_+^{n \times m}. \tag{3}$$

From an optimal coupling $T^\star$ of problem (3), the optimal weights $\overline{h}^\star$ expressed in problem (2) can be recovered by computing $T^\star$'s second marginal, *i.e* $\overline{h}^\star = T^{\star\top}\mathbf{1}_n$. We refer the reader interested in the proof of this equivalence to the annex. This reformulation with relaxed marginal has been investigated in the context of the Wasserstein distance (Rabin et al., 2014; Flamary et al., 2016) but never investigated for the GW distance. To the best of our knowledge, the most similar related work is the Unbalanced GW Séjourné et al. (2020); Liu et al. (2020); Chapel et al. (2019) where one could recover srGW with different weighting over the marginal relaxations (∞ on the first marginal and 0 on the second) but this specific case was not discussed nor studied in these works.

A first interesting property of srGW is that since $\overline{h}$ is optimized in the the simplex Σ_m, its optimal value $\overline{h}^\star$ can be sparse. As a consequence, parts of the graph $\overline{\mathcal{G}}$ can be omitted in the comparison, similarly to a partial matching. This behavior is illustrated in the Figure 1, where two graphs with uniform distributions and structures C and $\overline{C}$ forming respectively 2 and 3 clusters are matched. The GW matching (left) between both graphs forces nodes of different clusters from C to be transported on one of the three clusters of $\overline{C}$, leading to a high GW cost where clusters are not preserved. Whereas srGW can find a reasonable approximation of the structure of the left graph either though transporting on only two clusters (middle) or finding a structure with 3 clusters in a subgraph of the target graph with two clusters (right). A second natural observation resulting from the dependence of srGW$_2$ of only one input distributions is its asymmetry, *i.e.* srGW$_2(C, h, \overline{C}) \neq$ srGW$_2(\overline{C}, \overline{h}, C)$. Interestingly, srGW$_2$ shares similar properties than GW as described in the next proposition:

Proposition 1 *Let $C \in \mathbb{R}^{n \times n}$ and $\overline{C} \in \mathbb{R}^{m \times m}$ and $h \in \Sigma_n$ with $\text{supp}(h) = [\![n]\!]$. Then* srGW$_2(C, h, \overline{C}) = 0$ *iff there exists $\overline{h} \in \Sigma_m$ such that* GW$_2(C, h, \overline{C}, \overline{h}) = 0$. *As a consequence, if $C, \overline{C}$ are distances* srGW$_2(h, C, \overline{C}) = 0$ *iff there exists $T \in \mathbb{R}_+^{n \times m}$ with $n \leq m$, with first marginal h and whose second marginal $\overline{h} \in \Sigma_m$ is such that $\left|\text{supp}(\overline{h})\right| = n$ and there is a bijection $\sigma : \text{supp}(\overline{h}) \to [\![n]\!]$ which satisfies:*

$$\forall i \in [\![n]\!], \forall j \in [\![m]\!], \quad T_{ij} = \begin{cases} h(\sigma(j)) & \text{if } j \in \text{supp}(\overline{h}) \\ 0 & \text{otherwise.} \end{cases} \tag{4}$$

And:
$$\forall k, l \in \text{supp}(\overline{h})^2, \overline{C}_{kl} = C_{\sigma(k)\sigma(l)}. \tag{5}$$

In other words srGW$_2(C, h, \overline{C})$ vanishes iff there exists a reweighting $\overline{h}^\star \in \Sigma_m$ of the nodes of the second graph which cancels the GW distance. When it is the case, the induced graphs (C, h) and $(\overline{C}, \overline{h}^\star)$ are thus isomorphic (Mémoli, 2011; Sturm, 2012).

3.2 Optimization and algorithms

In this section we discuss the computational aspects of the srGW divergence and propose an algorithm to solve the related optimization problem (3). We also discuss variations resulting from entropic or/and sparse regularization of the initial quadratic problem.

Solving for the semi-relaxed GW. The optimization problem related to the calculation of srGW$_2^2(C, h, \overline{C})$ is a non-convex quadratic program similar to the one of GW with the important difference that the linear constraints are independent. Consequently, we propose to solve (3) with a Conditional Gradient (CG) algorithm (Jaggi, 2013) that can benefit from those independent constraints and is known to converge to local stationary point on non-convex problems (Lacoste-Julien, 2016). This algorithm, provided in Alg. 1, consists in solving at each iteration a linearization $\langle X, G \rangle$ of the problem (3) where G is the gradient of the objective in (3).

The solution of the linearized problem provides a *descent direction* $\boldsymbol{X}^\star - \boldsymbol{T}$, and a linesearch whose optimal step can be found in closed form to update the current solution $\boldsymbol{T}$ (Vayer et al., 2019). While both srGW and GW CG require at each iteration the computation of a gradient with complexity $O(n^2 m + m^2 n)$, the main source of efficiency of our algorithm comes from the computation of the descent directions. In the GW case, one needs to solve an exact linear OT problem, while in our case, one just needs to

---

Algorithm 1 CG solver for srGW

1: **repeat**
2:    $\boldsymbol{G}^{(t)} \leftarrow$ Compute gradient w.r.t $\boldsymbol{T}$ of (2).
3:    Get direction $\boldsymbol{X}^{(t)}$ problem: Solve independent subproblems on rows of $\boldsymbol{G}^{(t)}$.
4:    $\boldsymbol{T}^{(t+1)} \leftarrow (1-\gamma^\star)\boldsymbol{T}^{(t)} + \gamma^\star \boldsymbol{X}^{(t)}$ with $\gamma^\star \in [0,1]$ from exact-line search.
5: **until** convergence.

---

solve several independent linear problems under a simplex constraint. This simply amounts to finding the minimum on the lines of $\boldsymbol{G}$, within $O(mn)$ operations, with potential parallelization with GPUs. Performance gains are illustrated in the experimental section.

Entropic regularization. Recent OT applications have shown the interest of adding an entropic regularization to the exact problem (3) ,*e.g.* (Cuturi, 2013; Peyré et al., 2016). Entropic regularization makes the optimization problem smooth and more robust while densifying the optimal transport plan. Similar to (Peyré et al., 2016; Xu et al., 2019b; Xie et al., 2020), we can use a *mirror-descent scheme w.r.t.* the Kullback-Leibler divergence (KL) to solve entropic regularized srGW. The problem boils down to find, at iteration t the coupling $\boldsymbol{T}^{(t+1)} \leftarrow \arg\min_{\boldsymbol{T}\boldsymbol{1}_m=\boldsymbol{h};\boldsymbol{T}\geq 0}\langle \boldsymbol{T}, \boldsymbol{G}^{(t)}\rangle + \epsilon\,\mathrm{KL}(\boldsymbol{T}|\boldsymbol{T}^{(t)})$ where $\epsilon > 0$, $\boldsymbol{G}^{(t)}$ denotes the gradient of the GW loss at iteration t and $\mathrm{KL}(\boldsymbol{T}|\boldsymbol{T}^{(t)})$ is the KL divergence. These updates can be solved using the following closed-form Bregman Projections :

$$\boldsymbol{T}^{(t+1)} \leftarrow \underset{\boldsymbol{T}\boldsymbol{1}_m=\boldsymbol{h};\boldsymbol{T}\geq 0}{\arg\min}\ \epsilon\,\mathrm{KL}(\boldsymbol{T}|\boldsymbol{K}^{(t+1)}) \quad \Leftrightarrow \quad \boldsymbol{T}^{(t+1)} \leftarrow \mathrm{diag}\left(\frac{\boldsymbol{h}}{\boldsymbol{K}^{(t)}\boldsymbol{1}_m}\right)\boldsymbol{K}^{(t)}. \quad (6)$$

where $\boldsymbol{K}^{(t)} = \exp\left(\boldsymbol{G}^{(t)} - \epsilon\log(\boldsymbol{T}^{(t)})\right)$ (exp and log are applied componentwise). Unlike existing solvers for GW based on entropic regularization (Peyré et al., 2016; Solomon et al., 2016) that rely on a Sinkhorn's matrix scaling algorithm on $\boldsymbol{K}^{(t)}$ *at each iteration*, our problem requires only one (left) scaling of $\boldsymbol{K}^{(t)}$ per iteration. We denote by $\mathrm{srGW}_e(\boldsymbol{C}, \boldsymbol{h}, \overline{\boldsymbol{C}})$ the result of this procedure.

Sparsity promoting regularization. As illustrated in Figure 1, srGW naturally leads to sparse solutions in $\bar{\boldsymbol{h}}$. To compress even more the localization over a few nodes of $\overline{\boldsymbol{C}}$, we can promote the sparsity of $\overline{\boldsymbol{h}}$ through a penalization $\Omega(\boldsymbol{T}) = \sum_j |\bar{h}_j|^{1/2}$ which defines a concave function in the positive orthant $\mathbb{R}_+$. We adapt the Majorisation-Minimisation (MM) of Courty et al. (2014) that was introduced to solve classical OT with a similar regularizer. The resulting algorithm, which relies on a local linearization of $\Omega(\boldsymbol{T}^{(t)})$, consists in iteratively solving the srGW or srGW$_e$ problems, regularized at iteration $t+1$ by a linear OT cost of components $R_{i,j}^{(t)} = \frac{\lambda_g}{2}(\bar{h}_j^{(t)})^{-1/2}$ (see annex).

4 LEARNING THE TARGET STRUCTURE

A dataset of K graphs $\mathcal{D} = \{(\boldsymbol{C}_k, \boldsymbol{h}_k)\}_{k\in[\![K]\!]}$ is now considered, with heterogeneous structures and a variable number of nodes, denoted by $(n_k)_{k\in[\![K]\!]}$. We introduce in the following a novel graph dictionary learning (DL) that has the peculiarity to learn *a unique* dictionary element. Then we discuss how this dictionary can be used to perform graph completion, *i.e.* reconstruct the full structure of a graph from an observed sub-graph.

4.1 A NEW GRAPH DICTIONARY LEARNING

Semi-relaxed Gromov-Wasserstein embedding. We first discuss how an observed graph can be represented in a dictionary with a unique element (or *atom*) $\overline{\boldsymbol{C}} \in \mathbb{R}^{m\times m}$, assumed to be known or designed through expert knowledge. First, one computes $\mathrm{srGW}_2^2(\boldsymbol{C}_k, \boldsymbol{h}_k, \overline{\boldsymbol{C}})$ using the algorithmic solutions and regularization strategies detailed in Section 3.1. From the resulting optimal coupling $\boldsymbol{T}_k^\star$, the optimal weights for the target graph $\overline{\boldsymbol{C}}$ are recovered with $\overline{\boldsymbol{h}}_k^\star = \boldsymbol{T}_k^{\star\top}\boldsymbol{1}_{n_k}$. The graph $(\overline{\boldsymbol{C}}, \overline{\boldsymbol{h}}_k^\star)$ can be seen as a projection of $(\boldsymbol{C}_k, \boldsymbol{h}_k)$ in the GW sense and the distribution on the nodes $\overline{\boldsymbol{h}}_k^\star$ is

---

Algorithm 2 Stochastic update of the dictionary atom $\overline{C}$

1: Sample a minibatch of graphs $\mathcal{B} := \{(C^{(k)}, h^{(k)})\}_k$.
2: Get transports $\{T_k^\star\}_{k \in \mathcal{B}}$ from $\mathrm{srGW}(C_k, h_k, \overline{C})$ with Alg.1.
3: Compute the gradient $\widetilde{\nabla}_{\overline{C}}$ of srGW with fixed $\{T_k^\star\}_{k \in \mathcal{B}}$ and perform a projected gradient step on symmetric non-negative matrices $\mathcal{S}$:

$$\overline{C} \leftarrow \mathrm{Proj}_{\mathcal{S}}(\overline{C} - \eta \widetilde{\nabla}_{\overline{C}}) \tag{7}$$

---

an embedding of the graph (C_k, h_k). Representing a graph as a vector of weights $\overline{h}_k^\star$ on a graph $\overline{C}$ is a new and elegant way to define a graph subspace that is orthogonal to other DL methods that either rely on GW barycenters Xu (2020a) or linear models Vincent-Cuaz et al. (2021). One particularly interesting aspect of this modeling is that when $\overline{h}_k^\star$ sparse, only a subpart or subgraph of $\overline{C}$, corresponding to the nodes with non-zero weights in $\overline{h}_k^\star$, is used in the model.

srGW Dictionary Learning and online algorithm. Given a dataset of graphs $\mathcal{D} = \{(C_k, h_k)\}_{k \in [K]}$, we propose to learn the graph dictionary $\overline{C} \in \mathbb{R}^{m \times m}$ from the observed data, by optimizing:

$$\min_{\overline{C} \in \mathbb{R}^{m \times m}} \frac{1}{K} \sum_{k=1}^{K} \mathrm{srGW}_2^2(C_k, h_k, \overline{C}). \tag{8}$$

This problem is denoted as **srGW Dictionary Learning**. It can be seen as a srGW barycenter problem (Peyré et al., 2016) where we search for a graph structure $\overline{C}$ for which there exists node weights $(\overline{h}_k^\star)_{k \in [\![K]\!]}$ leading to a minimal GW error. Interestingly this DL model requires only to solve the srGW problem to compute the embedding $\overline{h}_k^\star$ since it can be recovered from the solution $\overline{T}_k^\star$ of the problem.

We solve this non-convex optimization problem above with an online algorithm similar to the one first proposed in (Mairal et al., 2009) for vectorial data and adapted by Vincent-Cuaz et al. (2021) for graphs data. The core of the stochastic algorithm is depicted in Alg. 2. The main idea is to use batches of graphs to independently solve the embedding problems (via Alg.1), then compute estimates of the gradient $\widetilde{\nabla}_{\overline{C}}$ with respect to $\overline{C}$ on each batch $\mathcal{B}$. Finally a projected gradient on the set $\mathcal{S}$ of symmetric non-negative matrices is performed to update $\overline{C}$. In practice we use Adam optimizer (Kingma & Ba, 2015) in all our experiments. The complexity of this stochastic algorithm is mostly bounded by computing the gradients, which can be done in $O(n_k^2 m + m^2 n_k)$ (see Section 3.2). Hence, in a factorization context *i.e.* $\max_k (n_k) >> m$, the overall learning procedure has a quadratic complexity *w.r.t.* the maximum graphs size. Since the embedding $\overline{h}_k^\star$ is a by-product of computing the different srGW, we do not need an iterative solver to estimate it. Consequently, it leads to a speed up on CPU of 2 to 3 orders of magnitude compared to our main competitors (see Section 5.3) which DL methods require such iterative scheme.

4.2 DL-BASED MODEL FOR GRAPHS COMPLETION

The structure $\overline{C}$ estimated on the dataset $\mathcal{D}$ can be used to infer/complete a new graph from the dataset being only partially observed. In this setting, we aim at recovering the full structure $C \in \mathbb{R}^{n \times n}$ while only a subset of relations between $n_{obs} < n$ nodes is observed, denoted as $C_{obs} \in \mathbb{R}^{n_{obs} \times n_{obs}}$. This amounts to solve:

$$\min_{C_{imp}} \quad \mathrm{srGW}_2^2\left(\widetilde{C}, h, \overline{C}\right), \text{ where } \widetilde{C} = \begin{bmatrix} C_{obs} & \vdots \\ \cdots & C_{imp} \end{bmatrix}, \tag{9}$$

where only the $n^2 - n_{obs}^2$ coefficients collected into C_{imp} are optimized (and thus imputed). We solve the optimization problem above by a classical projected gradient descent thanks to the Envelope Theorem. Indeed the gradient of srGW *w.r.t* $\overline{C}_{imp}$ can be obtained as the gradient of the srGW cost function evaluated at a fixed optimal coupling $T^\star$. The projection step is here to enforce known properties of C, such as positivity and symmetry. In practice the estimated C_{imp} will have continuous

Figure 2: GW vs srGW partitioning of $\mathcal{G} = (\boldsymbol{C}, \boldsymbol{h} = \boldsymbol{1}_n/n)$ with 3 clusters of varying proportions to $\overline{\mathcal{G}} = (\boldsymbol{I}_q, \overline{\boldsymbol{h}})$ where $\overline{\boldsymbol{h}}$ is fixed to uniform for GW (left) and estimated for for srGW (right) for $q = 3$ and $q = 4$. Nodes of $\mathcal{G}$ are colored based on their cluster assignments while those of $\overline{\mathcal{G}}$ are interpolated based on linear interpolation of node colors of $\mathcal{G}$ linked to them through their OT (colored line between nodes) if these links exist, otherwise default nodes color is black. Node sizes of both graphs $\mathcal{G}$ and $\overline{\mathcal{G}}$ depend on their respective masses $\boldsymbol{h}$ and $\overline{\boldsymbol{h}}$.

values, so one has to apply a thresholding (with value 0.5) on $\boldsymbol{C}_{imp}$ to recover a binary adjacency matrix. The method can be easily extended to labeled graphs by also optimizing the node features of non-observed nodes.

5 NUMERICAL EXPERIMENTS

This section illustrates the behavior of srGW on graph partitioning (a.k.a. nodes clustering), clustering of graphs and graph completion. All the Python implementations in the experiments will be released on Github. For all experiments we provide more details about validation grids and initialization in the annex.

5.1 GRAPH PARTITIONING

As discussed in Section 2, it is possible to achieve graph partitioning via OT by estimating a GW matching between the graph to partition $\mathcal{G} = (\boldsymbol{C}, \boldsymbol{h})$ (n nodes) and a smaller graph $\overline{\mathcal{G}} = (\boldsymbol{I}_q, \overline{\boldsymbol{h}})$, with $q \ll n$ nodes. The atom $\boldsymbol{I}_q$ is set as the identity matrix to enforce the emergence of densely connected groups (i.e. *communities*). The distributions $\overline{\boldsymbol{h}}$ estimates the proportion of nodes in each cluster. We recall that $\overline{\boldsymbol{h}}$ must be given to compute the GW distance, whereas it is estimated with srGW. All partitioning performances are measured by Adjusted Mutual Information (AMI, Vinh et al., 2010).

Simulated data. In Figure 2, we illustrate the behavior of GW and srGW partitioning on a toy graph, simulated according to SBM (Holland et al., 1983) with 3 clusters of different proportions. We see that miss-classification occurs either when the proportions $\overline{\boldsymbol{h}}$ do not fit the true ones or when $q \neq 3$. On the other hand, clustering from srGW can simultaneously recover any cluster proportions (since it estimates them) and select the actual number of clusters, using the sparse properties of $\overline{\boldsymbol{h}}$.

Real-world datasets. In order to benchmark the srGW partitioning on real (directed and undirected) graphs, we consider 4 datasets: a Wikipedia hyperlink network (Yang & Leskovec, 2015); a directed graph of email interactions between departments of a European research institute (Yin et al., 2017); an Amazon product network (Yang & Leskovec, 2015); a network of interactions between indian villages (Banerjee et al., 2013). For the directed graphs, we adopt the symmetrization procedure described in Chowdhury & Needham (2021). Our main competitors are the two GW based partitioning methods proposed by Xu et al. (2019b) and Chowdhury & Needham (2021). The former (GWL) relies on adjacency matrices, the latter (SpecGWL) adopts heat kernels on the graph normalized laplacians (SpecGWL). The GW

Table 1: Partitioning performances on real datasets measured by AMI. We see in bold (resp. italic) the first (resp. second) best method. NA: non applicable.

	Wikipedia		EU-email		Amazon	Village
	asym	sym	asym	sym	sym	sym
srGW (ours)	*56.92*	56.92	**49.94**	50.11	48.28	81.84
srSpecGW	50.74	**63.07**	49.08	50.60	76.26	*87.53*
srGW$_e$	**57.13**	*57.55*	**54.75**	*55.05*	50.00	83.18
srSpecGW$_e$	53.76	61.38	*54.27*	50.89	*85.10*	84.31
GWL	38.67	35.77	47.23	46.39	38.56	68.97
SpecGWL	40.73	48.98	45.89	49.02	65.16	77.85
FastGreedy	NA	55.30	NA	45.89	77.21	**93.66**
Louvain	NA	54.72	NA	**56.12**	76.30	**93.66**
InfoMap	46.43	46.43	54.18	49.10	**94.33**	**93.66**

Table 2: Clustering performances on real datasets measured by Rand Index. In bold (resp. italic) we highlight the first (resp. second) best method.

MODELS	NO ATTRIBUTE		DISCRETE ATTRIBUTES		REAL ATTRIBUTES			
	IMDB-B	IMDB-M	MUTAG	PTC-MR	BZR	COX2	ENZYMES	PROTEIN
srGW (ours)	51.59(0.10)	54.94(0.29)	71.25(0.39)	51.48(0.12)	62.60(0.96)	60.12(0.27)	*71.68(0.12)*	59.66(0.10)
srGW$_g$	**52.44(0.46)**	**56.70(0.34)**	72.31(0.51)	51.76(0.39)	66.75(0.38)	**62.15(0.27)**	**72.51(0.10)**	*60.67(0.29)*
srGW$_e$	51.75(0.56)	55.36(0.14)	*74.41(0.84)*	*52.35(0.42)*	67.63(1.17)	59.75(0.39)	70.93(0.33)	59.97(0.21)
srGW$_{e+g}$	*52.23(0.83)*	*55.90(0.68)*	**74.69(0.73)**	**52.53(0.47)**	**67.81(0.94)**	*60.53(0.36)*	71.31(0.52)	**60.81(0.43)**
GDL	51.34(0.27)	55.14(0.35)	70.28(0.25)	51.49(0.31)	62.84(1.60)	58.39(0.52)	69.83(0.33)	60.19(0.28)
GDL$_{reg}$	51.69(0.56)	55.43(0.22)	70.92(0.11)	51.82(0.47)	66.30(1.71)	59.61(0.74)	71.03(0.36)	60.46(0.65)
GWF-r	51.02(0.30)	55.09(0.46)	69.07(1.02)	51.47(0.59)	52.45(2.41)	56.91(0.46)	72.09(0.21)	59.97(0.11)
GWF-f	50.43(0.29)	54.18(0.27)	59.13(1.87)	50.82(0.81)	51.75(2.84)	52.84(0.53)	71.58(0.31)	58.92(0.41)
GW-k	50.31(0.03)	53.67(0.07)	57.62(1.45)	50.42(0.33)	56.77(0.53)	52.45(0.13)	66.35(1.37)	50.08(0.01)

Table 3: Embedding computation times (in ms) averaged over whole datasets at a convergence precision of 10^{-5} on learned dictionaries. $(-)$ (resp. $(+)$) denotes the fastest (resp. slowest) runtimes regarding DL configurations. We report here runtimes using $FGW_{0.5}$ for datasets with nodes attributes. Measures taken on Intel(R) Core(TM) i7-4510U CPU @ 2.00GHz.

	NO ATTRIBUTE				DISCRETE ATTRIBUTES				REAL ATTRIBUTES							
	IMDB-B		IMDB-M		MUTAG		PTC-MR		BZR		COX2		ENZYMES		PROTEIN	
	(-)	(+)	(-)	(+)	(-)	(+)	(-)	(+)	(-)	(+)	(-)	(+)	(-)	(+)	(-)	(+)
srGW (ours)	1.51	2.62	0.83	1.59	0.86	1.83	0.40	1.01	0.43	0.79	0.51	0.90	0.62	0.95	0.46	0.60
srGW$_g$	1.95	6.11	1.06	5.53	3.68	5.98	1.65	3.38	0.89	2.88	0.97	4.60	1.35	4.73	1.57	2.96
GWF-f	219	651	103	373	236	495	191	477	181	916	129	641	93	627	78	322
GDL	108	236	43.8	152	102	514	100	509	73.2	532	48.7	347	38	301	29	151

solver of Flamary et al. (2021) was used for these methods. For fairness, we also consider these two representations for srGW partitioning (namely srGW and srSpecGW). Finally, three competing methods specialized in graph partitioning are also considered: FastGreedy (Clauset et al., 2004), Louvain (with validation of its resolution parameter, Blondel et al., 2008) and Infomap (Rosvall & Bergstrom, 2008).

The graph partitioning results are reported in Table 1. Our method srGW always outperforms the GW based approaches and on this application the entropic regularization seems to improve the performance. We want to stress that our *general purpose* divergence srGW outperforms methods that have been specifically designed for nodes clustering tasks on 3 out of 6 datasets .

5.2 CLUSTERING OF GRAPHS DATASETS

Datasets and methods. We now show how the embeddings $(\overline{\boldsymbol{h}}_k^\star)_{k \in [\![K]\!]}$ provided by the srGW Dictionary Learning can be particularly useful for the task of graphs clustering. We considered here three types of datasets: i) social networks from IMDB-B and IMDB-M (Yanardag & Vishwanathan, 2015); ii) graphs with discrete features representing chemical compounds from MUTAG (Debnath et al., 1991) and cuneiform signs from PTC-MR (Krichene et al., 2015); iii) graphs with continuous features, namely BZR, COX2 (Sutherland et al., 2003) and PROTEINS, ENZYMES (Borgwardt & Kriegel, 2005). Our main competitors are the following OT-based SOTA models: i) GDL (Vincent-Cuaz et al., 2021) and its regularized version, namely GDL$_\lambda$; ii) GWF (Xu, 2020a), with both fixed (GWF-f) and random (GWF-r, default setting for the method) atom size; iii) GW kmeans (GW-k), a k-means equipped with GW distances and barycenters (Peyré et al., 2016).

Experimental settings. For all experiments we follow the benchmark proposed in Vincent-Cuaz et al. (2021). The clustering performances are measured by means of Rand Index (RI, Rand, 1971). The standard Euclidean distance is used to implement k-means over srGW and GWFs embeddings, but we use for GDL the dedicated Mahalanobis distance as described in Vincent-Cuaz et al. (2021). GW-k does not use any embedding since it directly computes (a GW) k-means over the input graphs. For each parameter configuration (number of atoms, number of nodes and regularization parameter) we run each experiment five times, independently. The mean RI over the five runs is computed and the dictionary configuration leading to the highest RI for each method is reported.

Results and discussion. Clustering performances and running times are reported in Tables 2 and 3, respectively. All variants of srGW DL are at least comparable with the SOTA GW based methods. Remarkably, the sparsity promoting variants always outperform other methods. Notably Table 3

Figure 3: Completion performances for IMDB-B (left) and MUTAG (right) datasets, measured by means of accuracy for structures and Mean Squared Error for node features, respectively averaged over all imputed graphs.

shows embedding computation times of the order of the millisecond for srGW, two order of magnitude faster than the competitors.

5.3 Graphs completion

Finally, we present graph completion results on the real world datasets IMDB-B and MUTAG, using the approach proposed in 4.2. Since this completion problem has never been investigated by existing GW graph methods, we adapted the learning procedure used for srGW to GDL (Vincent-Cuaz et al., 2021).

Experimental setting. Since the datasets do not explicitly contain graphs with missing nodes, we proceed as follow: first we split the dataset into a training dataset ($\mathcal{D}_{train}$) used to learn the dictionary and a test dataset ($\mathcal{D}_{test}$) reserved for the completion tasks. For each graph of $C \in \mathcal{D}_{test}$, we created incomplete graphs C_{obs} by independently removing 10% and 20% of their nodes, uniformly at random. The partially observed graphs are then reconstructed using the procedure described in Section 4.2 and the average performance of each method is computed for 5 different dataset splits.

Results. The graph completion results are reported in Figure 3. Our srGW dictionary learning outperforms GDL consistently, when enough data is available to learn the atoms. When the proportion of train/test data varies, we can see that the linear GDL model that maintains the marginal constraints tends to be less sensitive to the scarcity of data. This can come form the fact that srGW is more flexible thanks to the optimization of $\overline{h}$ but can slightly overfit when few data is available. Sparsity promoting regularization can clearly compensate this overfitting and systematically leads to the best completion performances (high accuracy, low Means Square Error).

6 Conclusion

We introduce a new transport based divergence between structured data by relaxing the mass constraint on the second distribution of the Gromov-Wasserstein problem. After designing efficient solvers to estimate this divergence, called the semi-relaxed Gromov-Wasserstein (srGW), we suggest to learn a unique structure to describe a dataset of graphs in the srGW sense. This novel modeling can be seen as a Dictionary Learning approach where graphs are embedded as a subgraph of a single atom. Numerical experiments highlight the interest of our methods for graph partitioning, and unsupervised representation learning whose evaluation is conducted through clustering and completion of graphs.

We believe that this new divergence will unlock the potential of GW for graphs with unbalanced proportions of nodes. The associated fast numerical solvers allow to handle large size graph datasets, which was not possible with current GW solvers. One interesting future research direction includes an analysis of srGW to perform parameters estimation of stochastic block models. Also, as relaxing the second marginal constraint in the original optimization problem gives more degrees of freedom to the underlying problem, one can expect dedicated regularization schemes, over *e.g.* the level of sparsity of $\overline{h}$, to address a variety of application needs. Finally, our method can be seen as a special relaxation of the subgraph isomorphism problem. It remains to be understood theoretically in which sense this relaxation holds.

REFERENCES

Abhijit Banerjee, Arun G Chandrasekhar, Esther Duflo, and Matthew O Jackson. The diffusion of microfinance. *Science*, 341(6144), 2013.

Peter W. Battaglia, Jessica B. Hamrick, Victor Bapst, Alvaro Sanchez-Gonzalez, Vinicius Zambaldi, Mateusz Malinowski, Andrea Tacchetti, David Raposo, Adam Santoro, Ryan Faulkner, Caglar Gulcehre, Francis Song, Andrew Ballard, Justin Gilmer, George Dahl, Ashish Vaswani, Kelsey Allen, Charles Nash, Victoria Langston, Chris Dyer, Nicolas Heess, Daan Wierstra, Pushmeet Kohli, Matt Botvinick, Oriol Vinyals, Yujia Li, and Razvan Pascanu. Relational inductive biases, deep learning, and graph networks, 2018.

Jean-David Benamou, Guillaume Carlier, Marco Cuturi, Luca Nenna, and Gabriel Peyré. Iterative Bregman Projections for Regularized Transportation Problems. *SIAM Journal on Scientific Computing*, 37(2):A1111–A1138, January 2015. ISSN 1064-8275, 1095-7197. doi: 10.1137/141000439.

Florian Bernard, Christian Theobalt, and Michael Moeller. Ds*: Tighter lifting-free convex relaxations for quadratic matching problems. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 4310–4319, 2018.

Filippo Maria Bianchi, Daniele Grattarola, and Cesare Alippi. Spectral clustering with graph neural networks for graph pooling. In *International Conference on Machine Learning*, pp. 874–883. PMLR, 2020.

Vincent D Blondel, Jean-Loup Guillaume, Renaud Lambiotte, and Etienne Lefebvre. Fast unfolding of communities in large networks. *Journal of statistical mechanics: theory and experiment*, 2008 (10):P10008, 2008.

Jesús Bobadilla, Fernando Ortega, Antonio Hernando, and Abraham Gutiérrez. Recommender systems survey. *Knowledge-based systems*, 46:109–132, 2013.

Karsten M Borgwardt and Hans-Peter Kriegel. Shortest-path kernels on graphs. In *Fifth IEEE international conference on data mining (ICDM'05)*, pp. 8–pp. IEEE, 2005.

M. Bronstein, Joan Bruna, T. Cohen, and Petar Velivckovi'c. Geometric deep learning: Grids, groups, graphs, geodesics, and gauges. *ArXiv*, abs/2104.13478, 2021.

Michael M Bronstein, Joan Bruna, Yann LeCun, Arthur Szlam, and Pierre Vandergheynst. Geometric deep learning: going beyond euclidean data. *IEEE Signal Processing Magazine*, 34(4):18–42, 2017.

Emmanuel J Candès, Xiaodong Li, Yi Ma, and John Wright. Robust principal component analysis? *Journal of the ACM (JACM)*, 58(3):1–37, 2011.

Laetitia Chapel, Mokhtar Z Alaya, and Gilles Gasso. Partial gromov-wasserstein with applications on positive-unlabeled learning. *arXiv preprint arXiv:2002.08276*, 2019.

Yudong Chen, Sujay Sanghavi, and Huan Xu. Improved graph clustering. *IEEE Transactions on Information Theory*, 60(10):6440–6455, 2014.

Samir Chowdhury and Facundo Mémoli. The gromov–wasserstein distance between networks and stable network invariants. *Information and Inference: A Journal of the IMA*, 8(4):757–787, 2019.

Samir Chowdhury and Tom Needham. Generalized Spectral Clustering via Gromov-Wasserstein Learning. *arXiv:2006.04163 [cs, math, stat]*, June 2020. arXiv: 2006.04163.

Samir Chowdhury and Tom Needham. Generalized spectral clustering via gromov-wasserstein learning. In *International Conference on Artificial Intelligence and Statistics*, pp. 712–720. PMLR, 2021.

Aaron Clauset, Mark EJ Newman, and Cristopher Moore. Finding community structure in very large networks. *Physical review E*, 70(6):066111, 2004.

Nicolas Courty, Rémi Flamary, and Devis Tuia. Domain adaptation with regularized optimal transport. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pp. 274–289. Springer, 2014.

Marco Cuturi. Sinkhorn distances: Lightspeed computation of optimal transport. In *Advances in neural information processing systems*, pp. 2292–2300, 2013.

Asim Kumar Debnath, Rosa L Lopez de Compadre, Gargi Debnath, Alan J Shusterman, and Corwin Hansch. Structure-activity relationship of mutagenic aromatic and heteroaromatic nitro compounds. correlation with molecular orbital energies and hydrophobicity. *Journal of medicinal chemistry*, 34 (2):786–797, 1991.

Persi Diaconis and Svante Janson. Graph limits and exchangeable random graphs. *arXiv preprint arXiv:0712.2749*, 2007.

Miroslav Fiedler. Algebraic connectivity of graphs. *Czechoslovak mathematical journal*, 23(2): 298–305, 1973.

Rémi Flamary, Cédric Févotte, Nicolas Courty, and Valentin Emiya. Optimal spectral transportation with application to music transcription. In *Proceedings of the 30th International Conference on Neural Information Processing Systems*, NIPS'16, pp. 703711, Red Hook, NY, USA, 2016. Curran Associates Inc. ISBN 9781510838819.

Rémi Flamary, Nicolas Courty, Alexandre Gramfort, Mokhtar Zahdi Alaya, Aurélie Boisbunon, Stanislas Chambon, Laetitia Chapel, Adrien Corenflos, Kilian Fatras, Nemo Fournier, et al. Pot: Python optimal transport. *Journal of Machine Learning Research*, 22(78):1–8, 2021.

Hongyang Gao and Shuiwang Ji. Graph u-nets. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pp. 2083–2092. PMLR, 09–15 Jun 2019.

Saeed Ghadimi, Guanghui Lan, and Hongchao Zhang. Mini-batch stochastic approximation methods for nonconvex stochastic composite optimization. *Mathematical Programming*, 155:267–305, 2016.

Zaïd Harchaoui and Francis Bach. Image classification with segmentation graph kernels. In *2007 IEEE Conference on Computer Vision and Pattern Recognition*, pp. 1–8. IEEE, 2007.

Paul W Holland, Kathryn Blackmond Laskey, and Samuel Leinhardt. Stochastic blockmodels: First steps. *Social networks*, 5(2):109–137, 1983.

David R Hunter and Kenneth Lange. A tutorial on mm algorithms. *The American Statistician*, 58(1): 30–37, 2004.

Martin Jaggi. Revisiting frank-wolfe: Projection-free sparse convex optimization. In *International Conference on Machine Learning*, pp. 427–435. PMLR, 2013.

John Jumper, Richard Evans, Alexander Pritzel, Tim Green, Michael Figurnov, Olaf Ronneberger, Kathryn Tunyasuvunakool, Russ Bates, Augustin Žídek, Anna Potapenko, et al. Highly accurate protein structure prediction with alphafold. *Nature*, 596(7873):583–589, 2021.

Tatsuro Kawamoto, Masashi Tsubaki, and Tomoyuki Obuchi. Mean-field theory of graph neural networks in graph partitioning. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, NIPS'18, pp. 43664376, Red Hook, NY, USA, 2018. Curran Associates Inc.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In Yoshua Bengio and Yann LeCun (eds.), *3rd International Conference on Learning Representations, ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Conference Track Proceedings*, 2015.

Walid Krichene, Syrine Krichene, and Alexandre Bayen. Efficient bregman projections onto the simplex. In *2015 54th IEEE Conference on Decision and Control (CDC)*, pp. 3291–3298. IEEE, 2015.

Nils M Kriege, Fredrik D Johansson, and Christopher Morris. A survey on graph kernels. *Applied Network Science*, 5(1):1–42, 2020.

Sofia Ira Ktena, Sarah Parisot, Enzo Ferrante, Martin Rajchl, Matthew Lee, Ben Glocker, and Daniel Rueckert. Distance metric learning using graph convolutional networks: Application to functional brain networks. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pp. 469–477. Springer, 2017.

Simon Lacoste-Julien. Convergence rate of frank-wolfe for non-convex objectives. *arXiv preprint arXiv:1607.00345*, 2016.

Weijie Liu, Chao Zhang, Jiahao Xie, Zebang Shen, Hui Qian, and Nenggan Zheng. Partial gromov-wasserstein learning for partial graph matching. *arXiv preprint arXiv:2012.01252*, 2020.

Julien Mairal, Francis Bach, Jean Ponce, and Guillermo Sapiro. Online dictionary learning for sparse coding. In *Proceedings of the 26th annual international conference on machine learning*, pp. 689–696, 2009.

Haggai Maron and Yaron Lipman. (probably) concave graph matching. In *Advances in Neural Information Processing Systems*, pp. 408–418, 2018.

Facundo Mémoli. Gromov–wasserstein distances and the metric approach to object matching. *Foundations of computational mathematics*, 11(4):417–487, 2011.

Christopher Morris, Martin Ritzert, Matthias Fey, William L Hamilton, Jan Eric Lenssen, Gaurav Rattan, and Martin Grohe. Weisfeiler and leman go neural: Higher-order graph neural networks. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pp. 4602–4609, 2019.

Azade Nazi, Will Hang, Anna Goldie, Sujith Ravi, and Azalia Mirhoseini. Gap: Generalizable approximate graph partitioning framework. *arXiv preprint arXiv:1903.00614*, 2019.

Andrew Y Ng, Michael I Jordan, Yair Weiss, et al. On spectral clustering: Analysis and an algorithm. *Advances in neural information processing systems*, 2:849–856, 2002.

Yin Cheng Ng, Nicolò Colombo, and Ricardo Silva. Bayesian semi-supervised learning with graph gaussian processes. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc., 2018.

Giannis Nikolentzos, Polykarpos Meladianos, and Michalis Vazirgiannis. Matching node embeddings for graph similarity. In *Proceedings of the Thirty-First AAAI Conference on Artificial Intelligence, February 4-9, 2017, San Francisco, California, USA.*, pp. 2429–2435, 2017.

Hermina Petric Maretic, Mireille El Gheche, Giovanni Chierchia, and Pascal Frossard. Got: An optimal transport framework for graph comparison. *Advances in Neural Information Processing Systems*, 32:13876–13887, 2019.

Gabriel Peyré and Marco Cuturi. Computational optimal transport. *Foundations and Trends in Machine Learning*, 11:355–607, 2019.

Gabriel Peyré, Marco Cuturi, and Justin Solomon. Gromov-wasserstein averaging of kernel and distance matrices. In *International Conference on Machine Learning*, pp. 2664–2672, 2016.

Julien Rabin, Sira Ferradans, and Nicolas Papadakis. Adaptive color transfer with relaxed optimal transport. In *2014 IEEE International Conference on Image Processing (ICIP)*, pp. 4852–4856, 2014. doi: 10.1109/ICIP.2014.7025983.

William M Rand. Objective criteria for the evaluation of clustering methods. *Journal of the American Statistical association*, 66(336):846–850, 1971.

Martin Rosvall and Carl T Bergstrom. Maps of random walks on complex networks reveal community structure. *Proceedings of the National Academy of Sciences*, 105(4):1118–1123, 2008.

Morgan A Schmitz, Matthieu Heitz, Nicolas Bonneel, Fred Ngole, David Coeurjolly, Marco Cuturi, Gabriel Peyré, and Jean-Luc Starck. Wasserstein dictionary learning: Optimal transport-based unsupervised nonlinear dictionary learning. *SIAM Journal on Imaging Sciences*, 11(1):643–678, 2018.

Thibault Séjourné, François-Xavier Vialard, and Gabriel Peyré. The unbalanced gromov wasserstein distance: Conic formulation and relaxation. *arXiv preprint arXiv:2009.04266*, 2020.

David I. Shuman, Sunil K. Narang, Pascal Frossard, Antonio Ortega, and Pierre Vandergheynst. The emerging field of signal processing on graphs: Extending high-dimensional data analysis to networks and other irregular domains. *IEEE Signal Processing Magazine*, 30:83–98, 2013.

Justin Solomon, Gabriel Peyré, Vladimir G Kim, and Suvrit Sra. Entropic metric alignment for correspondence problems. *ACM Transactions on Graphics (TOG)*, 35(4):1–13, 2016.

Karl-Theodor Sturm. The space of spaces: curvature bounds and gradient flows on the space of metric measure spaces. *arXiv preprint arXiv:1208.0434*, 2012.

Jeffrey J Sutherland, Lee A O'brien, and Donald F Weaver. Spline-fitting with a genetic algorithm: A method for developing classification structure- activity relationships. *Journal of chemical information and computer sciences*, 43(6):1906–1915, 2003.

Matteo Togninalli, Elisabetta Ghisu, Felipe Llinares-López, Bastian Rieck, and Karsten Borgwardt. Wasserstein weisfeiler–lehman graph kernels. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 32 (NeurIPS)*, pp. 6436–6446. Curran Associates, Inc., 2019.

Titouan Vayer, Nicolas Courty, Romain Tavenard, and Rémi Flamary. Optimal transport for structured data with application on graphs. In *International Conference on Machine Learning*, pp. 6275–6284. PMLR, 2019.

Titouan Vayer, Laetitia Chapel, Remi Flamary, Romain Tavenard, and Nicolas Courty. Fused gromov-wasserstein distance for structured objects. *Algorithms*, 13(9), 2020. ISSN 1999-4893. doi: 10.3390/a13090212.

Cédric Villani. *Topics in optimal transportation*. Number 58. American Mathematical Soc., 2003.

Cédric Vincent-Cuaz, Titouan Vayer, Rémi Flamary, Marco Corneli, and Nicolas Courty. Online graph dictionary learning. In Marina Meila and Tong Zhang (eds.), *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pp. 10564–10574. PMLR, 18–24 Jul 2021.

Nguyen Xuan Vinh, Julien Epps, and James Bailey. Information theoretic measures for clusterings comparison: Variants, properties, normalization and correction for chance. *The Journal of Machine Learning Research*, 11:2837–2854, 2010.

Zonghan Wu, Shirui Pan, Fengwen Chen, Guodong Long, Chengqi Zhang, and S Yu Philip. A comprehensive survey on graph neural networks. *IEEE Transactions on Neural Networks and Learning Systems*, 2020.

Yujia Xie, Xiangfeng Wang, Ruijia Wang, and Hongyuan Zha. A fast proximal point method for computing exact wasserstein distance. In Ryan P. Adams and Vibhav Gogate (eds.), *Proceedings of The 35th Uncertainty in Artificial Intelligence Conference*, volume 115 of *Proceedings of Machine Learning Research*, pp. 433–453. PMLR, 22–25 Jul 2020.

Hongteng Xu, Dixin Luo, and Lawrence Carin. Scalable gromov-wasserstein learning for graph partitioning and matching. *Advances in neural information processing systems*, 32:3052–3062, 2019a.

Hongteng Xu, Dixin Luo, Hongyuan Zha, and Lawrence Carin Duke. Gromov-wasserstein learning for graph matching and node embedding. In *International conference on machine learning*, pp. 6932–6941. PMLR, 2019b.

Hongteng Xu, Dixin Luo, Lawrence Carin, and Hongyuan Zha. Learning graphons via structured gromov-wasserstein barycenters. *Proceedings of the AAAI Conference on Artificial Intelligence*, 35(12):10505–10513, May 2021.

Hongtengl Xu. Gromov-wasserstein factorization models for graph clustering. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 6478–6485, 2020a.

Hongtengl Xu. Gromov-wasserstein factorization models for graph clustering. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 6478–6485, 2020b.

Junchi Yan, Xu-Cheng Yin, Weiyao Lin, Cheng Deng, Hongyuan Zha, and Xiaokang Yang. A short survey of recent advances in graph matching. In *Proceedings of the 2016 ACM on International Conference on Multimedia Retrieval*, pp. 167–174, 2016.

Pinar Yanardag and SVN Vishwanathan. Deep graph kernels. In *Proceedings of the 21th ACM SIGKDD international conference on knowledge discovery and data mining*, pp. 1365–1374, 2015.

Jaewon Yang and Jure Leskovec. Defining and evaluating network communities based on ground-truth. *Knowledge and Information Systems*, 42(1):181–213, 2015.

Hao Yin, Austin R Benson, Jure Leskovec, and David F Gleich. Local higher-order graph clustering. In *Proceedings of the 23rd ACM SIGKDD international conference on knowledge discovery and data mining*, pp. 555–564, 2017.

Rex Ying, Jiaxuan You, Christopher Morris, Xiang Ren, William L. Hamilton, and Jure Leskovec. Hierarchical graph representation learning with differentiable pooling. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, NIPS'18, pp. 48054815, Red Hook, NY, USA, 2018. Curran Associates Inc.

Daniele Zambon, C. Alippi, and Lorenzo Livi. Graph random neural features for distance-preserving graph representations. In *ICML*, 2020.

Feng Zhou and Fernando De la Torre. Factorized graph matching. In *2012 IEEE Conference on Computer Vision and Pattern Recognition*, pp. 127–134. IEEE, 2012.

7 APPENDIX

7.1 NOTATIONS & DEFINITIONS

In this section we recall the notations used in the rest of the appendix.

Notations. For a vector $\boldsymbol{h} \in \mathbb{R}^m$ we define its support as $\mathrm{supp}(\boldsymbol{h}) = \{i \in [\![m]\!] \mid h_i \neq 0\}$. Note that if $\boldsymbol{h} \in \Sigma_m$ we have $\mathrm{supp}(\boldsymbol{h}) = \{i \in [\![m]\!] \mid h_i > 0\}$. The cardinal of a discrete set A is denoted $|A|$.

For a 4-D tensor $\boldsymbol{L} = (L_{ijkl})_{ijkl}$ we denote $\otimes$ the tensor-matrix multiplication such that for a given matrix $\boldsymbol{M}$, $\boldsymbol{L} \otimes \boldsymbol{M}$ is the matrix with entries $(\sum_{kl} L_{ijkl} M_{kl})_{ij}$.

Cosntraints on couplings. We introduce $\mathcal{U}(\boldsymbol{h}, \overline{\boldsymbol{h}})$ the set of all admissible couplings between $\boldsymbol{h}$ and $\overline{\boldsymbol{h}}$, i.e the set

$$\mathcal{U}(\boldsymbol{h}, \overline{\boldsymbol{h}}) := \{\boldsymbol{T} \in \mathbb{R}_+^{n \times m} \mid \boldsymbol{T}\boldsymbol{1}_m = \boldsymbol{h}, \boldsymbol{T}^\top \boldsymbol{1}_n = \overline{\boldsymbol{h}}\}.$$

We also introduce for any $\boldsymbol{h} \in \Sigma_n$ and $m \in \mathbf{N}^*$, $\mathcal{U}(\boldsymbol{h}, m)$ the set of all admissible couplings between $\boldsymbol{h}$ and any histogram of Σ_m, i.e the set

$$\mathcal{U}(\boldsymbol{h}, m) := \{\boldsymbol{T} \in \mathbb{R}_+^{n \times m} \mid \boldsymbol{T}\boldsymbol{1}_m = \boldsymbol{h}\},$$

such that $\forall \boldsymbol{T} \in \mathcal{U}(\boldsymbol{h}, m)$, the second marginal $\overline{\boldsymbol{h}}(= \boldsymbol{T}^\top \boldsymbol{1}_n)$ belongs to Σ_m.

Gromov-Wassrestein distance. For any $q \geq 1$, the Gromov-Wasserstein distance of order q between (C, h) and $(\overline{C}, \overline{h})$ is defined by:

$$\mathrm{GW}_q^q(C, h, \overline{C}, \overline{h}) = \min_{T \in \mathcal{U}(h, \overline{h})} \mathcal{L}_q(C, \overline{C}, T)$$

where

$$\mathcal{L}_q(C, \overline{C}, T) = \sum_{i,j \in [\![n]\!]^2} \sum_{k,l \in [\![m]\!]^2} |C_{ij} - \overline{C}_{kl}|^q T_{ik} T_{jl}$$

Note that this is equivalent to

$$GW_q^q(C, h, \overline{C}, \overline{h}) = \min_{T \in \mathcal{U}(h, \overline{h})} \langle L_q(C, \overline{C}) \otimes T, T \rangle \tag{10}$$

where $L_q(C, \overline{C})$ is the 4-D tensor such that $L_q(C, \overline{C}) = \left((C_{ij} - \overline{C}_{kl})^q \right)_{ijkl}$.

Semi-relaxed Gromov-Wasserstein divergence. The semi-relaxed Gromov-Wasserstein divergence of order q satisfies the following equation:

$$\mathrm{srGW}_q^q(C, h, \overline{C}) = \min_{T \in \mathcal{U}(h, m)} \mathcal{L}_q(C, \overline{C}, T)$$

or equivalently

$$\mathrm{srGW}_q^q(C, h, \overline{C}) = \min_{T \in \mathcal{U}(h, m)} \langle L_q(C, \overline{C}) \otimes T, T \rangle \tag{11}$$

Fused Gromov-Wasserstein distance. For attributed graphs i.e with nodes features, we use the Fused Gromov-Wasserstein distance (Vayer et al., 2019). Consider two attributed graphs $\mathcal{G} = (C, F, h)$ and $\overline{\mathcal{G}} = (\overline{C}, \overline{F}, \overline{h})$ where $F = (F_i)_{i \in [\![n]\!]} \in \mathbb{R}^{n \times d}$ and $\overline{F} = (\overline{F}_j)_{j \in [\![m]\!]} \in \mathbb{R}^{m \times d}$ are their respective matrix of features which rows . Given a trade-off parameter between structures and features denoted $\alpha \in [0, 1]$, the $FGW_{q,\alpha}^q$ distance is defined as the result of the following optimization problem

$$\min_{T \in \mathcal{U}(h, \overline{h})} (1 - \alpha) \sum_{ij} \|F_i - \overline{F}_j\|_q^q T_{ij} + \alpha \sum_{ijkl} |C_{ij} - \overline{C}_{kl}|^q T_{ik} T_{jl} \tag{12}$$

which is equivalent to

$$\min_{T \in \mathcal{U}(h, \overline{h})} \langle (1 - \alpha) M_q(F, \overline{F}) + \alpha L_q(C, \overline{C}) \otimes T, T \rangle \tag{13}$$

where $M_q(F, \overline{F})$ is a matrix with entries $M_q(F, \overline{F})_{ij} = \|F_i - \overline{F}_j\|_q^q$.

Semi-relaxed Gromov-Wasserstein distance. Then in a similar way than for the Gromov-Wasserstein distance, the semi-relaxed Fused Gromov-Wasserstein of order q is defined for any trade-off parameter $\alpha \in [0, 1]$ as the result of the following optimization problem

$$srFGW_{q,\alpha}^q(C, F, h, \overline{C}, \overline{F}) = \min_{T \in \mathcal{U}(h, m)} \langle (1 - \alpha) M_q(F, \overline{F}) + \alpha L_q(C, \overline{C}) \otimes T, T \rangle \tag{14}$$

Note that these problems come down to regularizing the quadratic problem of GW or srGW with a linear term in T taking into account a similarity measure between features of attributed graphs.

7.2 SEMI-RELAXED (FUSED) GROMOV-WASSERSTEIN PROPERTIES

7.2.1 EQUIVALENCE OF THE OPTIMIZATION PROBLEMS

First of all let us begin with proving the equivalence between the optimization problems defining our semi-relaxed Gromov-Wasserstein divergence. Consider two observed graph (C, h) and $(\overline{C}, \overline{h})$ of n and m nodes. The first problem reads as

$$\overline{h}^\star \in \arg\min_{\overline{h} \in \Sigma_m} \mathrm{GW}_q^q(C, h, \overline{C}, \overline{h}) \tag{15}$$

The second optimization problem coming from the relaxation of the marginal constraint on admissible couplings $\boldsymbol{T}$ over the target distribution $\overline{\boldsymbol{h}}$, reads as

$$\min_{\boldsymbol{T} \in \mathcal{U}(\boldsymbol{h}, m)} \sum_{ijkl} |C_{ij} - \overline{C}_{kl}|^2 T_{ik} T_{jl} \tag{16}$$

Note that in the following proofs we always assume that graphs correspond to finite discrete measures and that their geometry is well-defined in the sense that entries of $\boldsymbol{C}$ and $\overline{\boldsymbol{C}}$ are always finite. This implies that graphs define compact spaces ensuring existence of that optimal solutions for both problems.

Proposition 2 *Problems 15 and 16 are equivalent.*

Proof. Consider a solution of problem 15 denoted $(\overline{\boldsymbol{h}}_1^\star, \boldsymbol{T}_1)$ note that the definition implies that $\boldsymbol{T}_1 \in \mathcal{U}(\boldsymbol{h}, \overline{\boldsymbol{h}}_1^\star)$. Another observation is that given $\overline{\boldsymbol{h}}_1^\star$, the transport plan $\boldsymbol{T}_1$ also belongs to $\arg\min_{\boldsymbol{T} \in \mathcal{U}(\boldsymbol{h}, \overline{\boldsymbol{h}}_1^\star)} \mathcal{L}_q(\boldsymbol{C}, \overline{\boldsymbol{C}}, \boldsymbol{T})$ hence is an optimal solution of $\mathrm{GW}_q(\boldsymbol{C}, \boldsymbol{h}, \overline{\boldsymbol{C}}, \overline{\boldsymbol{h}}_1^\star)$.

Now consider a solution of problem 16 denoted $\boldsymbol{T}_2$ with second marginal $\overline{\boldsymbol{h}}_2^\star$. By definition the couple $(\overline{\boldsymbol{h}}_2^\star, \boldsymbol{T}_2)$ is suboptimal for problem (15) i.e

$$\mathcal{L}_q(\boldsymbol{C}, \overline{\boldsymbol{C}}, \boldsymbol{T}_1) \leq \mathcal{L}_q(\boldsymbol{C}, \overline{\boldsymbol{C}}, \boldsymbol{T}_2) \tag{17}$$

And the symmetric also holds as $\boldsymbol{T}_1$ is a suboptimal admissible coupling for problem 16 i.e ,

$$\mathcal{L}_q(\boldsymbol{C}, \overline{\boldsymbol{C}}, \boldsymbol{T}_1) \leq \mathcal{L}_q(\boldsymbol{C}, \overline{\boldsymbol{C}}, \boldsymbol{T}_2) \tag{18}$$

Hence implying that $\mathcal{L}_q(\boldsymbol{C}, \overline{\boldsymbol{C}}, \boldsymbol{T}_1) = \mathcal{L}_q(\boldsymbol{C}, \overline{\boldsymbol{C}}, \boldsymbol{T}_2)$. Which implies that $\boldsymbol{T}_1 \in \arg\min_{\boldsymbol{T} \in \mathcal{U}(\boldsymbol{h}, m)} \mathcal{L}_q(\boldsymbol{C}, \overline{\boldsymbol{C}}, \boldsymbol{T})$, also $(\overline{\boldsymbol{h}}_2^\star, \boldsymbol{T}_2) \in \arg\min_{\overline{\boldsymbol{h}} \in \Sigma_m, \boldsymbol{T} \in \mathcal{U}(\boldsymbol{h}_1, \overline{\boldsymbol{h}})} \mathcal{L}_q(\boldsymbol{C}, \overline{\boldsymbol{C}}, \boldsymbol{T})$ and then $\mathrm{GW}_q(\boldsymbol{C}, \boldsymbol{h}, \overline{\boldsymbol{C}}, \overline{\boldsymbol{h}}_1^\star) = \mathrm{GW}_q(\boldsymbol{C}, \boldsymbol{h}, \overline{\boldsymbol{C}}, \overline{\boldsymbol{h}}_2^\star)$. Therefore by double inclusion we have

$$\arg\min_{\boldsymbol{T} \in \mathcal{U}(\boldsymbol{h}, m)} \mathcal{L}_q(\boldsymbol{C}, \overline{\boldsymbol{C}}, \boldsymbol{T}) = \arg\min_{\overline{\boldsymbol{h}} \in \Sigma_m, \boldsymbol{T} \in \mathcal{U}(\boldsymbol{h}, \overline{\boldsymbol{h}})} \mathcal{L}_q(\boldsymbol{C}, \overline{\boldsymbol{C}}, \boldsymbol{T}) \tag{19}$$

which is enough to prove that both problems are equivalent.

The equivalence between analog problems for the **semi-relaxed Fused Gromov-Wasserstein divergence** can be proved in the exact same way.

7.2.2 ZERO CONDITIONS OF (FUSED) SRGW

We prove the following result:

Proposition 3 *Let $\boldsymbol{C} \in \mathbb{R}^{n \times n}$ and $\overline{\boldsymbol{C}} \in \mathbb{R}^{m \times m}$ and $\boldsymbol{h} \in \Sigma_n$ with $\mathrm{supp}(\boldsymbol{h}) = n$. Then $\mathrm{srGW}_2(\boldsymbol{C}, \boldsymbol{h}, \overline{\boldsymbol{C}}) = 0$ iff there exists $\overline{\boldsymbol{h}} \in \Sigma_m$ such that $\mathrm{GW}_2(\boldsymbol{C}, \boldsymbol{h}, \overline{\boldsymbol{C}}, \overline{\boldsymbol{h}}) = 0$. As a consequence, if $\boldsymbol{C}, \overline{\boldsymbol{C}}$ are distance $\mathrm{srGW}_2(\boldsymbol{h}, \boldsymbol{C}, \overline{\boldsymbol{C}}) = 0$ iff there exists $\boldsymbol{T} \in \mathbb{R}_+^{n \times m}$ with $n \leq m$, with first marginal $\boldsymbol{h}$ and whose second marginal $\overline{\boldsymbol{h}} \in \Sigma_m$ is such that $\left|\mathrm{supp}(\overline{\boldsymbol{h}})\right| = n$ and there is a bijection $\sigma : \mathrm{supp}(\overline{\boldsymbol{h}}) \to [\![n]\!]$ which satisfies:*

$$\forall i \in [\![n]\!], \forall j \in [\![m]\!], \quad T_{ij} = \begin{cases} h(\sigma(j)) & \text{if } j \in \mathrm{supp}(\overline{\boldsymbol{h}}) \\ 0 & \text{otherwise.} \end{cases} \tag{20}$$

And:

$$\forall k, l \in \mathrm{supp}(\overline{\boldsymbol{h}})^2, \overline{C}_{kl} = C_{\sigma(k)\sigma(l)}. \tag{21}$$

Proof. The first point is a direct consequence of the definition of srGW as $\min_{\overline{\boldsymbol{h}} \in \Sigma_m} \mathrm{GW}_q^q(\boldsymbol{C}, \boldsymbol{h}, \overline{\boldsymbol{C}}, \overline{\boldsymbol{h}})$. For the second point: ($\Rightarrow$) Assume there exists $\boldsymbol{T} \in \mathcal{U}(\boldsymbol{h}, m)$ such that $\mathcal{L}_q(\boldsymbol{C}, \overline{\boldsymbol{C}}, \boldsymbol{T}) = 0$. Let us denote $\overline{\boldsymbol{h}} = \boldsymbol{T}^\top \mathbf{1}_n$ the second marginal of this coupling. Then we have $\mathrm{GW}_q(\boldsymbol{C}, \boldsymbol{h}, \overline{\boldsymbol{C}}, \overline{\boldsymbol{h}}) = 0$. By virtue to Gromov-Wasserstein properties (Sturm, 2012, Lemma 1.10) there exists a bijection σ between the support of the distributions which is distance preserving. In other words, there exists $\sigma : \mathrm{supp}(\overline{\boldsymbol{h}}) \to \mathrm{supp}(\boldsymbol{h}) = [\![n]\!]$ such that $\overline{h}(j) = h(\sigma(j))$ for all

---

Algorithm 3 CG solver for srGW, optionally with a linear regularization term $\boldsymbol{D} \in \mathbb{R}^{n \times n}$. Note that $\boldsymbol{D} = \boldsymbol{0}$ for unregularized version of srGW of equation 25.

1: **repeat**
2:    $\boldsymbol{G}^{(t)} \leftarrow$ Compute gradient w.r.t $\boldsymbol{T}$ of (24) satisfying equation 26 applied in $\boldsymbol{T}^{(t)}$.
3:    Get direction $\boldsymbol{X}^{(t)}$ problem: Solve independent subproblems on rows of $\boldsymbol{G}^{(t)}$ thanks to the equivalence stated here

$$\boldsymbol{X}^{(t)} \leftarrow \underset{\boldsymbol{X} \in \mathcal{U}(\boldsymbol{h}, m)}{\arg\min} \langle \boldsymbol{X}, \boldsymbol{G}^{(t)} + \boldsymbol{D} \rangle$$
$$\Leftrightarrow \boldsymbol{X}^{(t)} = (h_i \boldsymbol{x}_i^{(t)})_{i \in [\![n]\!]} \leftarrow \underset{\boldsymbol{x}_i \in \Sigma_m}{\arg\min} \langle \boldsymbol{x}_i, \boldsymbol{G}_i^{(t)} + \boldsymbol{D}_i \rangle \tag{22}$$

4:    Get optimal step size $\gamma^\star$ for the descent direction $\boldsymbol{X}^{(t)} - \boldsymbol{T}^{(t)}$: for any $\alpha \in [0, 1]$ let us denote $\boldsymbol{Z}^{(t)}(\gamma) = \boldsymbol{T}^{(t)} + \gamma(\boldsymbol{X}^{(t)} - \boldsymbol{T}^{(t)})$, then $\gamma^\star$ satisfies:

$$\underset{\gamma \in [0,1]}{\arg\min} \langle \boldsymbol{L}(\boldsymbol{C}, \overline{\boldsymbol{C}}) \otimes \boldsymbol{Z}^{(t)}(\gamma), \boldsymbol{Z}^t(\gamma) \rangle + \langle \boldsymbol{D}, \boldsymbol{Z}^{(t)}(\gamma) \rangle \tag{23}$$

   factored as a second-order polynomial function of the form $a\gamma^2 + b\gamma + c$, by using linearity of the tensor-multiplication $\otimes$ and of the scalar product. Then the closed form is obtained by simple analysis of coefficients a and b as in (Vayer et al., 2019).
5:    $\boldsymbol{T}^{(t+1)} \leftarrow \boldsymbol{Z}^{(t)}(\gamma^\star) = (1 - \gamma^\star)\boldsymbol{T}^{(t)} + \gamma^\star \boldsymbol{X}^{(t)}$.
6: **until** convergence decided based on relative variation of the loss between step t and $t + 1$.

$j \in \text{supp}(\overline{\boldsymbol{h}})$ and $\overline{C}_{kl} = C_{\sigma(k)\sigma(l)}$ for all $k, l \in \text{supp}(\overline{\boldsymbol{h}})^2$. We can conclude by observing that the permutation σ induce an optimal coupling $\boldsymbol{T}$ as defined in (20).

($\Leftarrow$) Consider $\boldsymbol{T} \in \mathcal{U}(\boldsymbol{h}, \overline{\boldsymbol{h}})$ and the induced bijection σ satisfying equations 20 and 21. It is trivial to verify that $\mathcal{L}(\boldsymbol{C}, \overline{\boldsymbol{C}}, \boldsymbol{T}) = 0$ implying that $\text{GW}_q(\boldsymbol{C}, \boldsymbol{h}, \overline{\boldsymbol{C}}, \overline{\boldsymbol{h}}) = 0$. Moreover as $\boldsymbol{T} \in \mathcal{U}(\boldsymbol{h}, m)$ since $\mathcal{U}(\boldsymbol{h}, \overline{\boldsymbol{h}}) \subset \mathcal{U}(\boldsymbol{h}, m)$ and the because same cost is involved in both transport problems, we have:

$$0 \leq \text{srGW}_q(\boldsymbol{C}, \boldsymbol{h}, \overline{\boldsymbol{C}}) \leq \text{GW}_q(\boldsymbol{C}, \boldsymbol{h}, \overline{\boldsymbol{C}}, \overline{\boldsymbol{h}}^\star) = 0 \implies \text{srGW}_q(\boldsymbol{C}, \boldsymbol{h}, \overline{\boldsymbol{C}}) = 0.$$

7.3 ALGORITHMIC DETAILS

We provide in this section the algorithmic details completing our explanations given in the main paper (see subsection 3.2). Note that for all numerical experiments we considered $q = 2$, so the following algorithms are specific to this scenario.

7.3.1 CONDITIONAL GRADIENT SOLVER FOR SRGW AND SRFGW

The optimization problem related to computing $\text{srGW}_2^2(\boldsymbol{C}, \boldsymbol{h}, \overline{\boldsymbol{C}})$ can be reformulated as

$$\min_{\substack{\boldsymbol{T}\boldsymbol{1}_m = \boldsymbol{h} \\ \boldsymbol{T} \geq 0}} \text{vec}(\boldsymbol{T})^\top \left(\overline{\boldsymbol{C}}^2 \otimes_K \boldsymbol{1}_n \boldsymbol{1}_n^\top - 2\overline{\boldsymbol{C}} \otimes_K \boldsymbol{C} \right) \text{vec}(\boldsymbol{T}). \tag{24}$$

where $\otimes_K$ denotes the Kronecker product of two matrices, vec the column-stacking operator and the power operation on $\overline{\boldsymbol{C}}$ is applied element-wise. For simplicity let us use the other equivalent formulation using the 4-D tensor notation i.e

$$\min_{\boldsymbol{T} \in \mathcal{U}(\boldsymbol{h}, \overline{\boldsymbol{h}})} \langle \boldsymbol{L}(\boldsymbol{C}, \overline{\boldsymbol{C}}) \otimes \boldsymbol{T}, \boldsymbol{T} \rangle \tag{25}$$

where $\boldsymbol{L}(\boldsymbol{C}, \overline{\boldsymbol{C}}) = \left((C_{ij} - \overline{C}_{kl})^2 \right)_{ijkl}$. This is a non-convex optimization problem with the same objective and gradient $\boldsymbol{G}$ than GW which can be expressed in the general case as

$$\boldsymbol{G} = \boldsymbol{L}(\boldsymbol{C}, \overline{\boldsymbol{C}}) \otimes \boldsymbol{T} + \boldsymbol{L}(\boldsymbol{C}^\top, \overline{\boldsymbol{C}}^\top) \otimes \boldsymbol{T}. \tag{26}$$

Note that if $\boldsymbol{C}$ and $\overline{\boldsymbol{C}}$ are symmetric matrices the gradient can be factored to

$$\boldsymbol{G} = 2\boldsymbol{L}(\boldsymbol{C}, \overline{\boldsymbol{C}}) \otimes \boldsymbol{T}. \tag{27}$$

Algorithm 4 MD solver for entropic srGW, optionally with a linear regularization term $\boldsymbol{D} \in \mathbb{R}^{n \times n}$. Note that $\boldsymbol{D} = \boldsymbol{0}$ for unregularized version of srGW of equation 25.

1: **repeat**
2:    $\boldsymbol{G}^{(t)} \leftarrow$ Compute gradient w.r.t $\boldsymbol{T}$ of (24) satisfying equation 26 applied in $\boldsymbol{T}^{(t)}$.
3:    Compute the matrix $\boldsymbol{K}^{(t)}(\epsilon)$ following equations (34) and (36).
4:    Get $\boldsymbol{T}^{(t+1)}$ with the scaling of $\boldsymbol{K}^{(t)}(\epsilon)$ following equation (35).
5: **until** convergence decided based on relative variation of the loss between step t and $t+1$.

Note that we implemented both versions as this factorization reduces slightly computation times in practice. We propose to use a Conditional Gradient (CG) algorithm Jaggi (2013) to solve this problem, provided in Alg. 3.

For the sake of conciseness, we also introduce here a linear regularization term of the form $\langle \boldsymbol{D}, \boldsymbol{T} \rangle$ which will be used while enforcing sparsity promoting regularization on srGW or for adapting this algorithm to srFGW where $\boldsymbol{D}$ results from distances between features (up to proper scaling with the trade-off parameter α).

Then in this general case, our CG algorithm consists in solving at each iteration t a linearization $\langle \boldsymbol{X}, \boldsymbol{G}^{(t)} + \boldsymbol{D} \rangle$ of the problem (24), aside from the regularization term, where $\boldsymbol{G}^{(t)}$ is the gradient at $\boldsymbol{T}^{(t)}$ of (24). This is efficiently achieved thanks to the trivial equivalence stated in equation 22. The solution of the linearized problem provides a *descent direction* $\boldsymbol{X}^{(t)} - \boldsymbol{T}^{(t)}$, and a line-search is performed to get the optimal step size as described in equation 23. Note that the gradients at time step $\boldsymbol{T}^{(t)}$ and $\boldsymbol{T}^{(t+1)}$ have a simple linear relation, which we used in our implementation for conciseness but it is rather equivalent to the more classical implementation literally expressing terms involved in the line-search part.

Extension to srFGW. Let us denote two attributed graphs $\mathcal{G} = (\boldsymbol{C}, \boldsymbol{F}, \boldsymbol{h})$ and $(\overline{\boldsymbol{C}}, \overline{\boldsymbol{F}}, \overline{\boldsymbol{h}})$, of n and m nodes respectively. Then the semi-relaxed Fused Gromov-Wasserstein of order 2 is defined for any trade-off parameter $\alpha \in [0, 1]$ as the result of the following optimization problem

$$\text{srFGW}^2_\alpha(\boldsymbol{C}, \boldsymbol{F}, \boldsymbol{h}, \overline{\boldsymbol{C}}, \overline{\boldsymbol{F}}) = \min_{\boldsymbol{T} \in \mathcal{U}(\boldsymbol{h}, m)} \langle (1 - \alpha) \boldsymbol{M}(\boldsymbol{F}, \overline{\boldsymbol{F}}) + \alpha \boldsymbol{L}(\boldsymbol{C}, \overline{\boldsymbol{C}}) \otimes \boldsymbol{T}, \boldsymbol{T} \rangle \quad (28)$$

where $\boldsymbol{M}(\boldsymbol{F}, \overline{\boldsymbol{F}})$ denote the matrix of euclidean distances between features of $\boldsymbol{F}$ and $\overline{\boldsymbol{F}}$, *i.e.* $M_{ij} = \|F_i - \overline{F}_j\|_2^2$. As a side note, one efficient way to compute this matrix in practice is by using the following factorization $\boldsymbol{M}(\boldsymbol{F}, \overline{\boldsymbol{F}}) = (\boldsymbol{F} \odot \boldsymbol{F}) \mathbf{1}_d \mathbf{1}_m^\top + \mathbf{1}_n \mathbf{1}_d^\top (\overline{\boldsymbol{F}} \odot \overline{\boldsymbol{F}}) - 2 \boldsymbol{F} \overline{\boldsymbol{F}}^\top$, where $\odot$ denotes the Hadamard product. The problem in equation 28 is a nonconvex quadratic problem which gradient *w.r.t.* $\boldsymbol{T}$ reads as :

$$\alpha \boldsymbol{G} + (1 - \alpha) \boldsymbol{M}(\boldsymbol{F}, \overline{\boldsymbol{F}}) \quad (29)$$

where $\boldsymbol{G}$ corresponds to the gradient of the GW cost satisfying equation 26. Therefore we propose to tackle this problem by a straight-forward adaptation of the CG algorithm 3 detailed above by adding the multiplier α to the GW cost and setting $\boldsymbol{D} = (1 - \alpha) \boldsymbol{M}(\boldsymbol{F}, \overline{\boldsymbol{F}})$.

7.3.2 ALGORITHMIC DETAILS AND GUARANTIES ON ENTROPIC SRGW.

Recent OT applications have shown the interest of adding an entropic regularization to the exact problem (24) Cuturi (2013); Peyré et al. (2016). We detail here how to design a *mirror-descent scheme w.r.t.* the Kullback-Leibler divergence (KL) to solve (24), in the same vein than Peyré et al. (2016); Xu et al. (2019b); Xie et al. (2020).

Algorithmic details. Indeed in order to solve the srGW problem stated in 16, we can use a mirror-descent scheme *w.r.t.* the KL geometry. At iteration t, the update the current transport plan $\boldsymbol{T}^{(t)} \in \mathcal{U}(\boldsymbol{h}, m)$ results from the following optimization problem

$$\boldsymbol{T}^{(t+1)} \leftarrow \underset{\boldsymbol{T} \in \mathcal{U}(\boldsymbol{h}, m)}{\arg\min} \langle \boldsymbol{G}(\boldsymbol{T}^{(t)}), \boldsymbol{T} \rangle + \epsilon \, \text{KL}(\boldsymbol{T} | \boldsymbol{T}^{(t)}) \quad (30)$$

Where $\boldsymbol{G}$ satisfies 26 and $\mathrm{KL}(\boldsymbol{T}|\boldsymbol{T}^{(t)}) = \sum_{ij} T_{i,j} \log(\frac{T_{i,j}}{T_{i,j}^{(t)}}) - T_{i,j} + T_{i,j}^{(t)}$. Let us denote the entropy of any $\boldsymbol{T} \in \mathbb{R}_+^{n \times m}$ by $\mathrm{H}(\boldsymbol{T}) = -\sum_{ij} T_{ij}(\log T_{ij} - 1)$, one can simply prove the the following relation:

$$\langle \boldsymbol{M}, \boldsymbol{T} \rangle - \epsilon \, \mathrm{H}(\boldsymbol{T}) = \epsilon \, \mathrm{KL}(\boldsymbol{T} | \exp(-\frac{\boldsymbol{M}}{\epsilon})) \Leftrightarrow \epsilon \, \mathrm{KL}(\boldsymbol{T}|\boldsymbol{M}) = \langle -\epsilon \log \boldsymbol{M}, \boldsymbol{T} \rangle - \epsilon \, \mathrm{H}(\boldsymbol{T}) \quad (31)$$

Then using this relation, the problem in 30 is equivalent to

$$\boldsymbol{T}^{(t+1)} \leftarrow \underset{\boldsymbol{T} \in \mathcal{U}(\boldsymbol{h}, m)}{\arg\min} \langle \boldsymbol{G}(\boldsymbol{T}^{(t)}) - \epsilon \log \boldsymbol{T}^{(t)}, \boldsymbol{T} \rangle - \epsilon \, \mathrm{H}(\boldsymbol{T}) \quad (32)$$

Denoting $\boldsymbol{M}^{(t)}(\epsilon) = \boldsymbol{G}(\boldsymbol{T}^{(t)}) - \epsilon \log \boldsymbol{T}^{(t)}$, overall we end up with the following iterations

$$\boldsymbol{T}^{(t+1)} \leftarrow \underset{\boldsymbol{T} \in \mathcal{U}(\boldsymbol{h}, m)}{\arg\min} \langle \boldsymbol{M}^{(t)}(\epsilon), \boldsymbol{T} \rangle - \epsilon \, \mathrm{H}(\boldsymbol{T}) \quad (33)$$

Which is equivalent thanks to the relation stated above to

$$\boldsymbol{T}^{(t+1)} \leftarrow \underset{\boldsymbol{T} \in \mathcal{U}(\boldsymbol{h}, m)}{\arg\min} \epsilon \, \mathrm{KL}(\boldsymbol{K}^{(t)}(\epsilon)|\boldsymbol{T}) \quad \text{where} \quad \boldsymbol{K}^{(t)}(\epsilon) := \exp\{-\boldsymbol{M}^{(t)}(\epsilon)/\epsilon\} \quad (34)$$

Following the seminal work of (Benamou et al., 2015), the optimal $\boldsymbol{T}^{(t+1)}$ is given by a simple scaling of the matrix $\boldsymbol{K}^{(t)}(\epsilon)$ reading as

$$\boldsymbol{T}^{(t+1)} = \mathrm{diag}\left(\frac{\boldsymbol{h}}{\boldsymbol{K}^{(t)}(\epsilon)\boldsymbol{1}_m}\right) \boldsymbol{K}^{(t)}(\epsilon). \quad (35)$$

Note that an analog scheme is achievable while penalizing the srGW problem with a linear term of the form $\langle \boldsymbol{D}, \boldsymbol{T} \rangle$. Which would simply result in a modification of the matrix $\boldsymbol{M}^{(t)}(\epsilon)$ such that

$$\boldsymbol{M}^{(t)}(\epsilon) = \boldsymbol{G}(\boldsymbol{T}^{(t)}) + \boldsymbol{D} - \epsilon \log \boldsymbol{T}^{(t)} \quad (36)$$

This more general setting is summarized in algorithm 4.

Similarly than for the CG algorithm 3, it is straight-forward to adapt the MD algorithm 4 to the **semi-relaxed Fused Gromov-Wasserstein** using FGW cost expressed in 29.

7.3.3 SPARSITY PROMOTING REGULARIZATION OF SRGW

In order to promote sparsity of the estimated target distribution while matching $(\boldsymbol{C}, \boldsymbol{h})$ to the structure $\overline{\boldsymbol{C}}$ using srGW, we suggest to use $\Omega(\boldsymbol{T}) = \sum_j |\overline{h}_j|^{1/2}$ which defines a concave function in the positive orthant $\mathbb{R}_+$. This results to the following optimization

$$\min_{\boldsymbol{T} \in \mathcal{U}(\boldsymbol{h}, m)} \langle \boldsymbol{L}(\boldsymbol{C}, \overline{\boldsymbol{C}}) \otimes \boldsymbol{T}, \boldsymbol{T} \rangle + \lambda_g \Omega(\boldsymbol{T}) \quad (37)$$

with $\lambda_g \in \mathbb{R}_+$ an hyperparameter. As mentioned in the main paper, equation 37 can be tackled with a majorisation-minimisation (MM) algorithm. MM consists of iteratively minimising an upper bound of the objective function which is tight at the current iterate (Hunter & Lange, 2004). With this procedure, the objective function is guaranteed to decrease at every iteration. In our case, we only need to majorize the penalty term $\Omega(\boldsymbol{T})$ to obtain a tractable function. Denoting $\overline{\boldsymbol{h}}^{(t)} = \boldsymbol{T}^{(t)\top} \boldsymbol{1}_n$, the estimate at iteration t, one can simply apply the tangent inequality

$$\sum_j \sqrt{\overline{h}_j} \leq \sum_j \sqrt{\overline{h}_j^{(t)}} + \frac{1}{2 \sum_j \sqrt{\overline{h}_j^{(t)}}} (\overline{\boldsymbol{h}} - \overline{\boldsymbol{h}}^{(t)})^\top \boldsymbol{1}_m. \quad (38)$$

Using this inequality is equivalent to linearize the regularization term at $\overline{\boldsymbol{h}}^{(t)}$ whose contribution can be absorbed into the inner product as $\langle \boldsymbol{L}(\boldsymbol{C}, \overline{\boldsymbol{C}}) \otimes \boldsymbol{T} + \boldsymbol{R}^{(t)}, \boldsymbol{T} \rangle$ where $\boldsymbol{R}^{(t)} = \frac{\lambda_g}{2} (\overline{\boldsymbol{h}}_j^{(t)})_{ij}^{-1/2}$. The overall optimization procedure is summarized in 7. Note that the same procedure is used for promoting sparsity of srFGW using the adaptation of our CG solver 3 and MD solver 4 to this scenario.

Algorithm 5 MM solver for srGW_g and srGW_{e+g}

1: Set $\boldsymbol{R}^{(0)} = \boldsymbol{0}$.
2: **repeat**
3:      Get optimal transport $\boldsymbol{T}^{(t)}$ with second marginal $\overline{\boldsymbol{h}}^{(t)}$ from CG solver 3 (srGW_g) or MD solver 4 (srGW_{e+g}) with $\boldsymbol{D} = \boldsymbol{R}^{(t)}$.
4:      Compute $\boldsymbol{R}^{(t+1)} = \frac{\lambda_g}{2}(\overline{\boldsymbol{h}}_j^{(t)})_{ij}^{-1/2}$ the new local linearization of $\Omega(\boldsymbol{T}^{(t)})$.
5: **until** convergence.

Algorithm 6 Stochastic update of the atom $\overline{\boldsymbol{C}}$

1: Sample a minibatch of graphs $\mathcal{B} := \{(\boldsymbol{C}^{(k)}, \boldsymbol{h}^{(k)})\}_k$.
2: Get transports $\{\boldsymbol{T}_k^\star\}_{k \in \mathcal{B}}$ from $\mathrm{srGW}(\boldsymbol{C}_k, \boldsymbol{h}_k, \overline{\boldsymbol{C}})$ with Alg.1.
3: Compute the gradient $\widetilde{\nabla}_{\overline{\boldsymbol{C}}}$ of srGW with fixed $\{\boldsymbol{T}_k^\star\}_{k \in \mathcal{B}}$ and perform a projected gradient step on symmetric non-negative matrices $\mathcal{S}$:
$$\overline{\boldsymbol{C}} \leftarrow \mathrm{Proj}_{\mathcal{S}}(\overline{\boldsymbol{C}} - \eta \widetilde{\nabla}_{\overline{\boldsymbol{C}}}) \tag{39}$$

7.4   LEARNING THE TARGET STRUCTURE

We detail in the following the algorithms for the **srGW Dictionary Learning** and its application to graphs completion.

7.4.1   SRGW DICTIONARY LEARNING.

We propose to learn the graph atom $\overline{\boldsymbol{C}} \in \mathbb{R}^{m \times m}$ from the observed data $\mathcal{D} = \{(\boldsymbol{C}_k, \boldsymbol{h}_k)\}_{k \in [K]}$, by optimizing

$$\min_{\overline{\boldsymbol{C}} \in \mathbb{R}^{m \times m}} \frac{1}{K} \sum_{k=1}^{K} \mathrm{srGW}_2^2(\boldsymbol{C}_k, \boldsymbol{h}_k, \overline{\boldsymbol{C}}), \tag{40}$$

This is a nonconvex problem that we propose to tackle thanks to a stochastic gradient algorithm summarized in 6. At each iteration it consists in sampling a batch of graphs $\mathcal{B} = \{(\boldsymbol{C}_k, \boldsymbol{h}_k)\}_{k \in [\![B]\!]}$ from the dataset and to embed each graph where $\overline{\boldsymbol{h}}_k = \boldsymbol{T}_k^\top \boldsymbol{1}_n$ by solving independent srGW problems for the current state of the dictionary. Then we compute the estimate of the gradient over $\overline{\boldsymbol{C}}$ reading as

$$\widetilde{\nabla}_{\overline{\boldsymbol{C}}}(.) = \frac{2}{B} \sum_{k \in [\![B]\!]} \left(\overline{\boldsymbol{C}} \odot \overline{\boldsymbol{h}}_k \overline{\boldsymbol{h}}_k^\top - \boldsymbol{T}_k^\top \boldsymbol{C}_k \boldsymbol{T}_k \right). \tag{41}$$

Note that only the entries (i, j) of $\overline{\boldsymbol{C}}$ such that i and j belongs to $\cup_k \mathrm{supp}(\overline{\boldsymbol{h}}_k)$ can have a non-null gradient. Finally depending on the input structures we consider we apply a projection on an adequate set $\mathcal{S}$, for instance if input structures are adjacency matrices we consider $\mathcal{S}$ as the set of non-negative symmetric matrices (iterates can preserve symmetry but not necessarily non-negativity depending on the chosen learning rate).

Extension to attributed graphs. The stochastic algorithm described above can be adapted to a dataset of attributed graph $\mathcal{D} = \{(\boldsymbol{C}_k, \boldsymbol{F}_k, \boldsymbol{h}_k)\}_{k \in [\![K]\!]}$ with nodes features in $\mathbb{R}^d$, by learning an attributed graph atom $(\overline{\boldsymbol{C}}, \overline{\boldsymbol{F}})$. The optimization problem would now read as

$$\min_{\overline{\boldsymbol{C}} \in \mathbb{R}^{m \times m}, \overline{\boldsymbol{F}} \in \mathbb{R}^{m \times d}} \frac{1}{K} \sum_{k \in [\![K]\!]} \mathrm{srFGW}_{2,\alpha}^2(\boldsymbol{C}_k, \boldsymbol{F}_k, \boldsymbol{h}_k, \overline{\boldsymbol{C}}, \overline{\boldsymbol{F}}) \tag{42}$$

for any $\alpha \in [0, 1]$. The stochastic algorithm 6 is then adapted by first computing embeddings based on srFGW instead of srGW. Then *simultaneously* updating $\overline{\boldsymbol{C}}$ following (42) up to the factor α and $\overline{\boldsymbol{F}}$ thanks to the following equation

$$\widetilde{\nabla}_{\overline{\boldsymbol{F}}}(.) = \frac{2}{K} \sum_{k \in [\![B]\!]} \left(\mathrm{diag}(\overline{\boldsymbol{h}}_k) \overline{\boldsymbol{F}} - \boldsymbol{T}_k^\top \boldsymbol{F}_k \right). \tag{43}$$

Algorithm 7 MM solver for srGW_g and srGW_{e+g}

1: Set $\boldsymbol{R}^{(0)} = \boldsymbol{0}$.
2: **repeat**
3:     Get optimal transport $\boldsymbol{T}^{(t)}$ with second marginal $\overline{\boldsymbol{h}}^{(t)}$ from CG solver 3 (srGW_g) or MD solver 4 (srGW_{e+g}) with $\boldsymbol{D} = \boldsymbol{R}^{(t)}$.
4:     Compute $\boldsymbol{R}^{(t+1)} = \frac{\lambda_g}{2}(\overline{\boldsymbol{h}}_j^{(t)})_{ij}^{-1/2}$ the new local linearization of $\Omega(\boldsymbol{T}^{(t)})$.
5: **until** convergence.

Algorithm 8 Algorithms for graphs completion using DL from srGW or GDL

1: Initialize randomly the entries $\boldsymbol{C}_{imp}$ by iid sampling from $\mathcal{N}(0.5, 0.01)$ (In a symmetric manner if $\boldsymbol{C}_{obs}$ is symmetric).
2: **repeat**
3:     Compute the optimal representations $\widetilde{G}^{(t)}$ of the $(\boldsymbol{C}^{(t)}, \boldsymbol{h})$ onto the dictionary and optimal transport $\boldsymbol{T}^{(t)}$ between $(\boldsymbol{C}^{(t)}, \boldsymbol{h})$ and $\widetilde{G}^{(t)}$:

$$(\mathrm{srGW}) : \widetilde{G}^{(t)} = (\overline{\boldsymbol{C}}, \overline{\boldsymbol{h}}^{(t)} = \boldsymbol{T}^{(t)\top} \mathbf{1}_n) \quad \text{where} \quad \boldsymbol{T}^{(t)} \leftarrow \mathrm{srGW}(\boldsymbol{C}^{(t)}, \boldsymbol{h}, \overline{\boldsymbol{C}})$$

$$(\mathrm{GDL}) : \widetilde{G}^{(t)} = (\sum_{s \in [\![s]\!]} w_s^{(t)} \overline{\boldsymbol{C}}_s, \overline{\boldsymbol{h}}) \quad \text{where} \quad (\boldsymbol{w}^{(t)}, \boldsymbol{T}^{(t)}) \leftarrow \min_{\boldsymbol{w} \in \Sigma_S} \mathrm{GW}(\boldsymbol{C}^{(t)}, \boldsymbol{h}, \sum_{s \in [\![s]\!]} w_s \overline{\boldsymbol{C}}_s, \overline{\boldsymbol{h}})$$

    (44)

4:     Get $\boldsymbol{C}^{(t+1)}$ from a projected gradient step *w.r.t.* the GW distance between $(\boldsymbol{C}^{(t)}, \boldsymbol{h})$ and $\widetilde{G}^{(t)}$ with the optimal coupling $\boldsymbol{T}^{(t)}$.
5: **until** convergence.

7.4.2 DL-BASED MODEL FOR GRAPHS COMPLETION

The estimated structure $\overline{\boldsymbol{C}}$, learned on the dataset $\mathcal{D}$ can be used to infer/complete a new graph form the dataset being only partially observed. Let us say that we want to recover the structure $\boldsymbol{C} \in \mathbb{R}^{n \times n}$ but we only observed the relations between $n_{obs} < n$ nodes denoted as $\boldsymbol{C}_{obs} \in \mathbb{R}^{n_{obs} \times n_{obs}}$. We propose to solve the following optimization problems to recover the full matrix $\boldsymbol{C}$ while modeling graphs with our srGW Dictionary Learning

$$\min_{\boldsymbol{C}_{imp}} \quad \mathrm{srGW}_2^2 \left(\widetilde{\boldsymbol{C}}, \boldsymbol{h}, \overline{\boldsymbol{C}} \right), \text{ where } \widetilde{\boldsymbol{C}} = \begin{bmatrix} \boldsymbol{C}_{obs} & \vdots \\ \cdots & \boldsymbol{C}_{imp} \end{bmatrix}, \tag{45}$$

Graph comletion with GDL For the linear dictionary GDL (Vincent-Cuaz et al., 2021) with several atoms denoted $\{\overline{\boldsymbol{C}}_s\}_{s \in [\![S]\!]}$ sharing the same weights $\overline{\boldsymbol{h}}$ we adapted our formulation to their model:

$$\min_{\boldsymbol{C}_{imp}} \min_{\boldsymbol{w} \in \Sigma_s} GW_2^2 \left(\boldsymbol{C}, \boldsymbol{h}, \sum_{s \in [\![S]\!]} w_s \overline{\boldsymbol{C}}_s, \overline{\boldsymbol{h}} \right) \tag{46}$$

The matrix $\boldsymbol{C}$ has only the $n^2 - n_{obs}^2$ coefficients collected into C_{imp} are optimized (and thus imputed). This way $\boldsymbol{C}_{imp}$ expresses the connections between the imputed nodes, and between these nodes and the observed ones in $\boldsymbol{C}_{obs}$. We tackle the non-convex problems above following the procedure described in Algorithm 8.

It consists in an alternating scheme where at each iteration t, we embed the current estimated graph $\boldsymbol{C}^{(t)}$ on the dictionary depending on the chosen model (see (44)). Let us denote $\widetilde{G}^{(t)} = (\widetilde{\boldsymbol{C}}^{(t)}, \widetilde{\boldsymbol{h}}^{(t)})$ this representation which respectively reads for srGW as $\widetilde{G}^{(t)} = (\overline{\boldsymbol{C}}, \overline{\boldsymbol{h}}^{(t)})$ and for GDL as $\widetilde{G}^{(t)} = (\sum_{s \in [\![S]\!]} w_s^{(t)} \overline{\boldsymbol{C}}_s, \overline{\boldsymbol{h}})$. Note that from this embedding step we also get the optimal transport $\boldsymbol{T}^{(t)}$ from the GW distance between $(\boldsymbol{C}^{(t)}, \boldsymbol{h})$ and $\widetilde{G}^{(t)}$. Then we can update the imputed part $\boldsymbol{C}_{imp}^{(t)}$ of $\boldsymbol{C}^{(t)}$

while keeping fixed $\boldsymbol{C}_{obs}$ thanks to a projected gradient step with gradient *w.r.t.* $\boldsymbol{C}$ reading as

$$2\left(\boldsymbol{C}^{(t)} \odot \boldsymbol{h}\boldsymbol{h}^\top - \boldsymbol{T}^{(t)}\widetilde{\boldsymbol{C}}^{(t)}\boldsymbol{T}^{(t)\top}\right) \tag{47}$$

7.5 DETAILS ON THE NUMERICAL EXPERIMENTS.

7.5.1 GRAPH PARTITIONING

Table 4: Partitioning benchmark: Datasets statistics.

Datasets	# nodes	# communities	connectivity rate (%)
Wikipedia	1998	15	0.09
EU-email	1005	42	3.25
Amazon	1501	12	0.41
Village	1991	12	0.42

Table 5: Partitioning performances on real datasets measured by AMI. Comparison between srGW and Kmeans whose hard assignments are used to initialize srGW.

	Wikipedia		EU-email		Amazon	Village
	asym	sym	asym	sym	sym	sym
srGW (ours)	56.92	56.92	49.94	50.11	48.28	81.84
srGW$_e$	**57.13**	57.55	**54.75**	55.05	50.00	83.18
Kmeans (adj)	29.40	29.40	36.59	34.35	34.36	60.83

We detail here the benchmark between srGW and state-of-the-art methods for graph partitioning on real (directed and undirected) graphs. We replicated the benchmark from (Chowdhury & Needham, 2021) using the 4 datasets whose preprocessing is detailed in their paper and resulting statistics are provided in Table 4. We considered the two GW based partitioning methods proposed by (Xu et al., 2019a) (GWL) and (Chowdhury & Needham, 2021) (SpecGWL). We benchmarked our method denoted srGW and srSpecGW which respectively use adjacency and heat kernels on normalized laplacian matrices as inputs since they were both use by competitors. All these OT based methods depend on hyperparameters which can be tuned in an unsupervised way (*i.e.* without knowing the ground truth partition) based on modularity maximization (Chowdhury & Needham, 2021). Following their numerical experiments, we considered as input distribution $\boldsymbol{h}$ for the observed graph the parameterized power-law transformations of the form $h_i = \frac{p_i}{\sum_i p_i}$ where $p_i = (deg(i) + a)^b$, with $deg(i)$ the i-th node degree and real parameters $a \in \mathbb{R}$ and $b \in [0,1]$. If the graph has no isolated nodes we chose $a = 0$ and $a = 1$ otherwise. b is validated within these 10 values $\{0, 0.0001, 0.005, ..., 0.1, 0.5, 1\}$ which progressively transform the input distribution from the uniform one to the normalized degrees distribution. The heat parameter for SpecGWL and srSpecGW is tuned for each dataset within the range $[1, 100]$ by recursively splitting this range into 5 values, find the parameter leading to maximum modularity, and repeat the same process on the induced new interval with this best parameter as center. This process is stopped based on the relative variation of maximum modularity between two successive iterates of precision 10^{-3}. A similar scheme can be used to fine-tune the entropic parameter. (Chowdhury & Needham, 2021) also discussed the sensitivity of GW solvers to the initialization and showed that GW matchings with heat kernels have considerably less spurious local minimum than those using adjacency matrices. This way it is arguable to compare both methods by using the product $\boldsymbol{h}\overline{\boldsymbol{h}}^\top$ as default initialization. We observed for srGW that using an initialization based on the hard assignments of a kmeans on the rows of the input representations (up to the left scaling $\text{diag}(\boldsymbol{h})$), was a better trade-off for both kinds of representations. Hence we applied this scheme for our method in this benchmark. We illustrate in Table 4 how srGW refines these hard assignments by soft ones through OT.

7.5.2 EXPERIMENTS BASED ON DICTIONARY LEARNING

We report in table 6 the statistics of the datasets used for our benchmark on clustering of datasets graphs and graphs completion.

Detailed settings for the clustering benchmark. We detail now the experimental setting used in the clustering benchmark derived from the benchmark conducted by Vincent-Cuaz et al. (2021).

Table 6: Clustering and Completion benchmark: Datasets descriptions

datasets	features	#graphs	#classes	mean #nodes	min #nodes	max #nodes	median #nodes	mean connectivity rate
IMDB-B	None	1000	2	19.77	12	136	17	55.53
IMDB-M	None	1500	3	13.00	7	89	10	86.44
MUTAG	$\{0..2\}$	188	2	17.93	10	28	17.5	14.79
PTC-MR	$\{0,..,17\}$	344	2	14.29	2	64	13	25.1
BZR	$\mathbb{R}^3$	405	2	35.75	13	57	35	6.70
COX2	$\mathbb{R}^3$	467	2	41.23	32	56	41	5.24
PROTEIN	$\mathbb{R}^{29}$	1113	2	29.06	4	620	26	23.58
ENZYMES	$\mathbb{R}^{18}$	600	6	32.63	2	126	32	17.14

For the datasets with attributes involving FGW, we validated 15 values of the trade-off parameter α via a logspace search in $(0, 0.5)$ and symmetrically $(0.5, 1)$. For DL based approaches, a first step consists into learning the atoms. srGW dictionary sizes are tested in $M \in \{10, 20, 30, 40, 50\}$, the atom is initialized by randomly sampling its entries from $\mathcal{N}(0.5, 0.01)$ and made symmetric. The extension of srGW to attributed graphs, namely srFGW, is referred as srGW for conciseness in 2 of the main paper. One efficient way to initialize atoms features for minimizing our resulting reconstruction errors is to use a Kmeans algorithm seeking for M clusters on the nodes features observed in the dataset. For GDL and GWF, a variable number of $S = \beta k$ atoms is validated, where k denotes the number of classes and $\beta \in \{2, 4, 6, 8\}$. The size of the atoms M is set to the median of observed graph sizes within the dataset for GDL and GWF-f. These methods initialize their atoms by sampling observed graphs within the dataset, with adequate sizes for GDL and GWF-f, while sizes of GWF-r are just determined by this random sampling procedure independently of the number of nodes distribution. For $\text{srGW}_g, \text{srGW}_{e+g}$ and GDL_λ, the coefficient of our respective sparsity promoting regularizers is validated within $\{0.001, 0.01, 0.1, 1.0\}$. Then for $\text{srGW}_e, \text{srGW}_{e+g}$, GWF-f and GWF-r, the entropic regularization coefficient is validated also within $\{0.001, 0.01, 0.1, 1.0\}$. Finally, we considered the same settings for the stochastic algorithm hyperparameters across all methods: learning rates are validated within $\{0.01, 0.001\}$ while the batch size is validated within $\{16, 32\}$; We learn all models fixing a maximum number of epochs of 100 (over convergence requirements) and implemented an (*unsupervised*) early-stopping strategy which consists in computing the respective unmixings every 5 epochs and stop the learning process if the cumulated reconstruction error (Err_t) does not improve anymore over 2 consecutive evaluations (*i.e.* $Err_t \leq Err_{t+1}$ and $Err_t \leq Err_{t+2}$).

Visualization of srGW embeddings. We provide in Figure 4 some examples of graphs embeddings from the dataset IMDB-B learned on a srGW dictionary $\overline{C}$ of 10 nodes. We assigned different colors to each nodes of the graph atom (forth column) in order to visualize the correspondences recovered by the OT plan $T^\star$ resulting from the projection of the respective sample (C, h) onto $\overline{C}$ in the srGW sense (third column). As the atom has continuous values we set the edges intensity of grey proportionally to the entries of $\overline{C}$. By coloring nodes of the observed graphs based on the OT to its respective embedding $(\overline{C})$(second column) we clearly observe that key subgraphs information, such as clusters and hubs are captured within the embedding. Note that if we increase the size of the dictionary, our embeddings are refined and can bring complementary structural information at a higher resolution *e.g.* finding substructures or variable connectivity between nodes in the same cluster.

Experiment details on graphs completion. For these completion experiments the exact same scheme, than in our clustering benchmark, is applied for learning srGW and GDL dictionaries on formed datasets $\mathcal{D}_{train}$. On interesting specificity used on dataset IMDB-B was for the initialization. Indeed instead of initializing the structure atom iid from $\mathcal{N}(0.5, 0.01)$, we initialized the entries of C_{imp} denoting connections *only* between the new imputed nodes randomly. Then we initialized entries representing connections of these nodes to the ones of C_{obs} seeing the degree (scaled by maximum observed degrees) of each observed node as initial probability for a new node to be connected to this observed node. Then for each entries (i, j) where x_i belongs to C_{obs} and x_j to C_{imp}, C_{ij} is initialized as $\mathcal{N}(\frac{deg(x_i)}{\max_{i_{obs}} deg(x_i)}, 0.01)$. This initialization led to better performances for both model so might be a first good practice to tackle completion of clustered graph using OT. For MUTAG we sticked with the initialization used for our and initialized imputed features randomly in the range of locally observed features.

Figure 4: Illustration of the embedding of different graphs from the IMDB dataset on the estimated dictionary $\overline{C}$. Each row corresponds to one observed graph and we show its graph (left), its graph with nodes colored corresponding to the OT plan (center left), the projected graph on the dictionary with optimal weight $\overline{h}^\star$ and the full dictionary with uniform mass (right).