Learning with Holographic Reduced Representations

Abstract

Holographic Reduced Representations (HRR) are a method for performing symbolic AI on top of real-valued vectors [1] by associating each vector with an abstract concept, and providing mathematical operations to manipulate vectors as if they were classic symbolic objects. This method has seen little use outside of older symbolic AI work and cognitive science. Our goal is to revisit this approach to understand if it is viable for enabling a hybrid neural-symbolic approach to learning as a differential component of a deep learning architecture. HRRs today are not effective in a differential solution due to numerical instability, a problem we solve by introducing a projection step that forces the vectors to exist in a well behaved point in space. In doing so we improve the concept retrieval efficacy of HRRs by over $100\times$. Using multi-label classification we demonstrate how to leverage the symbolic HRR properties to develop a output layer and loss function that is able to learn effectively, and allows us to investigate some of the pros and cons of an HRR neuro-symbolic learning approach.

1 Introduction

Symbolic and connectionist (or "neural") based approaches to Artificial Intelligence (AI) and Machine Learning (ML) have often been treated as two separate, independent methods of approaching AI/ML. This does not need to be the case, and our paper proposes to study the viability of a hybrid approach to propagation based learning. In particular, we make use of the Holographic Reduced Representation (HRR) approach originally proposed by Plate [1]. Plate proposed using circular convolution as a "binding" operator. Given two vectors in a d dimensional feature space, $\boldsymbol{x}, \boldsymbol{y} \in \mathbb{R}^d$, they can be "bound" together using circular convolution, which we denote as $\boldsymbol{s} = \boldsymbol{x} \circledast \boldsymbol{y}$. This gives us a new result $\boldsymbol{s} \in \mathbb{R}^d$. The HRR approach also includes an inversion operation $\dagger$ that maps $\mathbb{R}^d \to \mathbb{R}^d$.

With this binding and inverse operation, Plate showed that we can assign vectors to have a conceptual symbolic meaning and construct *statements* (or "sentences") from these representations. For example, we can construct $S = red \circledast cat + blue \circledast dog$ to represent "a red cat and a blue dog". HRRs can also *query* the statement representation S. To ask which animal was red, we compose $S \circledast red^{\dagger} \approx cat$ which gives us a numeric output approximately equal to the vector representing "cat".

Backpropagating through HRRs is ineffective if done naively, and our goal is to show how to rectify this issue with a simple projection step and build viable loss functions out of HRR operations. We choose to do this with eXtreme Multi-Label (XML) classification tasks as one that is impossible for HRRs to tackle today. XML tasks have an input $\boldsymbol{x}$, from which we have a large number L of binary prediction problems $\mathcal{Y}_1, \mathcal{Y}_2, \ldots, \mathcal{Y}_L$. Our approach will be to represent each of the L classes as a HHR concept vector, and construct an alternative to a fully connected output layer that uses the HRR framework for learning. Our experiments and ablations will focus on the impact of replacing a simple output layer with HRRs and other changes to the HRR approach to better understand its behaviors. State-of-the-art XML performance is not a goal.

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

Our contributions and the rest of our paper are organized as follows. In §2 we discuss prior approaches related to our own, and how our work differs from these methods. In §3 we give a brief overview of the HRR operator's details given it's niche recognition within the AI/ML community, and introduce a simple improvement that increases the binding stability and effectiveness by $100\times$. Then in §4 we show how we can leverage HRR's symbolic nature to create a new output layer and loss function combination that provides several benefits to deep extreme multi-label models. With this new method we demonstrate in §5 that compared to a simple fully-connected output layer we can reduce the output size by as much as 99.55%, resulting in a total reduction in model size by up to 42.09%, reduce training time by 41.86%, and obtain similar or improved relative accuracy by up to 30%. We also show that these results are often competitive with more advanced approaches for XML classification, though do still suffer at the largest output spaces with $670k$ labels. Finally we conclude in §6.

2   Related Work

The HRR operation has found significant use in cognitive science to create biologically plausible models of human cognition [2–5]. These approaches use the HRR's operations in a primarily symbolic fashion to demonstrate human like performance on a number of cognitive science tasks [6]. The vector representation is used as the foundation for biological plausibility after establishing that the operations required to implement HRR are within the plausible sphere of a biological substrate [7]. When learning has been incorporated in these models it has been primarily through examples of Hebbian updates of spiking models on the outputs of HRR, rather than back-propagation through the HRR operations and preceding inputs/layers [8]. In our work we advance the understanding of how to learn through the HRR through propagation in an effective manner and how HRR can be leveraged as an integral part of a neural-symbolic approach.

Little work exists on gradient based learning with HRR operations explicitly. The only work we are aware that attempts to leverage the symbolic properties of the HRR is by Nickel et al. [9], who use the binding operations to connect elements in a knowledge graph as a kind of embedding that combines two vectors of information without expanding the dimension of the representation (e.g., concatenation would combine but double the dimension). More recently Liao and Yuan [10] used circular convolution as a direct replacement of normal convolution to reduce model size and inference time, without any leverage of the symbolic properties available within HRRs. While Danihelka et al. [11] purport to embed the HRR into an LSTM, their approach only augments an LSTM by including complex weights and activations[1], and does not actually use HRR as it lacks circular convolution, and all three works do not leverage the inverse operation † or seek to leverage any symbolic manipulations. By contrast our work explicitly requires the symbolic manipulation properties of HRR to create a vector-symbolic loss function, and we need to leverage the inverse operator †, meaning we use the entire HRR framework. We also demonstrate new insights into learning with HRR operations that make them more effective, where prior works have simply used the $\circledast$ operator on ≤ 2 components without further study.

Our use of extreme multi-label classification problems is due to it being out-of-reach of current HRR methods, which we found produced random-guessing performance in all cases. There exists a rich literature of XML methods that tackle the large output space from the perspective of decision trees/ensembles [12–16], label embedding regression [17–20], naive bayes [21], and linear classifiers [22, 23]. There also exist deep learning XML methods that use either a fully-connected output layer [24] and others that use a variety of alternative approaches to dealing with the large output space [25–32]. The variety of approaches is orthogonal to the purpose of this work, which is to investigate HRRs. We will leverage only some of these works to modify their architectures to use a fully-connected output layer (if they do not already) and to use our HRR approach, so that we can observe the impact of the HRR specifically on the model. In our experimentation we found that the mechanisms for handling the high cardinally of outputs is high architecture tuned and specific, making it difficult to do broader comparisons. Our work will explore fully-connected, convolutional, and recurrent architectures to show that our HRR approach can work broadly across many types of architectures that have been used, but it is not our goal to be the "best" at XML by any metric. The XML task's value to our study is a problem that current HRR methods could not tackle, and where we can apply the symbolic properties of HRR in developing the solution in a way that demonstrates how one may design HRR based networsk for other tasks.

---

[1]HRRs & circular convolution can naturally exist in the reals.

3 Holographic Reduced Representation

The original paper by Plate [1] introduced the HRR approach and developed significant theory for it's use as a symbolic approach to AI on a neural substrate. We will quickly review its foundation & numerical issues that lead to our projection based improvement. The HRR starts with circular convolution as a "binding" operator. We use Plate's notation of $\circledast$, and a definition of circular convolution using an FFT $\mathcal{F}$ and inverse FFT ($\mathcal{F}^{-1}$) is given in eq. (1). It is easy to see that the binding operator of circular convolution $\circledast$ is commutative. What is particularly interesting is the ability to *unbind* terms that have been bound by this operator. Let $\mathcal{F}(\boldsymbol{a})_i$ denote the i'th complex feature of the FFT of $\boldsymbol{a}$. By defining an identity function $\mathcal{F}(\boldsymbol{a}^\dagger)_i \mathcal{F}(\boldsymbol{a})_i = 1$, we can derive the inverse function eq. (2), where we raise each complex coefficient z_i of the FFT to the z_i^{-1} power before going back to the real domain.

103

$$\boldsymbol{a} \circledast \boldsymbol{b} = \mathcal{F}^{-1}\left(\mathcal{F}(\mathbf{a}) \odot \mathcal{F}(\mathbf{b})\right) \qquad (1) \qquad\qquad \boldsymbol{a}^\dagger = \mathcal{F}^{-1}\left(\frac{1}{\mathcal{F}(\boldsymbol{a})}\right) \qquad (2)$$

Using this Plate [1] showed that one can compose sentences like our example $S = red \circledast cat + blue \circledast dog$ by assigning concepts to vectors in a d dimensional space. We can unbind components with the inverse operation, giving $S \circledast cat^\dagger \approx red$, or we can check for the existence of a term by checking that $S^\top cat^\dagger \approx 1$. A term not present, like "cow", would behave as $S^\top cow^\dagger \approx 0$.

These sentences can be constructed with more complex logic. The binding is also distributive (and associative), so $\boldsymbol{a} \circledast (\boldsymbol{x} + \boldsymbol{y}) = \boldsymbol{a} \circledast \boldsymbol{x} + \boldsymbol{a} \circledast \boldsymbol{y}$. This allows us to construct complex sybmolic relationships. As an example, we could have: $S = first \circledast (name \circledast Jane + age \circledast 30) + second \circledast (name \circledast Joe + age \circledast 33)$, and to determine the name of the first person we can perform $first^\dagger \circledast name^\dagger \circledast S \approx Jane$.

To make this symbolic manipulations effective, Plate [1] introduced two points of necessity. First, a vector $\boldsymbol{a}$ used for HRR operations should have it's values sampled from a normal distribution: $\boldsymbol{a} \sim \mathcal{N}\left(0, \mathrm{I}_d \cdot d^{-1}\right)$. This allows binding and unbinding to work in expectation. Second, is that the inverse $\dagger$ is numerically unstable. The remedy developed is the *pseudo* inverse $*$, given by $\boldsymbol{a}^* = [a_1, a_d, a_{d-1}, \ldots, a_2]$. This approximation was justified by noting that in polar form one obtains $\mathcal{F}_j\left(\mathbf{a}^\dagger\right) = \frac{1}{r_j}e^{-i\theta_j}$ and $\mathcal{F}_j\left(\mathbf{a}^*\right) = r_j e^{-i\theta_j}$, which are off by the reciprocal of the complex magnitude. Plate and others [6] use the pseudo inverse $*$ exclusively as the error due to approximation of $\dagger$ was smaller than the errors caused by numerical instability.

3.1 Improved HRR Learning

The only prior work backpropogating through $\circledast$ only needed to bind two items together at a time [9], where we need to bind and represent tens-to-hundreds of thousands of concepts. Prior work also made no use of the unbinding with $\dagger$, which we require. We found that the default method proposed by Plate [1] was not sufficient for our work, and needed improvement. In particular, we needed better detection if a vector $\boldsymbol{y}$ (read, *label*) has been bound to a statement S (read, *output*). We achieve this by defining a new *complex unit magnitude projection*, which is given by eq. (3).

$$\pi(\boldsymbol{x}) = \mathcal{F}^{-1}\left(\ldots, \frac{\mathcal{F}(\boldsymbol{x})_j}{|\mathcal{F}(\boldsymbol{x})_j|}, \ldots\right) \qquad (3)$$

We change the initialization to $\boldsymbol{a} \sim \pi\left(\mathcal{N}\left(0, \mathrm{I}_d \cdot d^{-1}\right)\right)$ which ensures the vectors we use for HRR operations are unitary, meaning the complex magnitude is one. In this case we obtain $\boldsymbol{a}^\dagger = \boldsymbol{a}^*$ because in polar form we have $r_j = 1 \; \forall j$, giving $\mathcal{F}_j\left(\mathbf{a}^\dagger\right) = \frac{1}{1}e^{-i\theta_j} = \mathcal{F}_j\left(\mathbf{a}^*\right) = 1e^{-i\theta_j}$.

This has a number of benefits. First, we make the numerically stable $*$ have a mathematically equivalent result to the true inverse, removing that source of error. Second, the $*$ is faster to calculate requiring a simple shift of values that takes $\mathcal{O}(d)$ time to perform, compared to $\mathcal{O}(d \log d)$ for the FFTs in $\dagger$. Third, we find that this complex projection significantly increases the number of concepts that can be bound together and the accuracy of retrieving them. Using standard HRR initialization we found it difficult to use more than 10 bindings in a statement, but our simple change allows us to improve query accuracy by up to $100\times$ as many bound vectors.

To demonstrate the effectiveness of our projection step, we create a statement vector $S = \sum_{i=1}^{T} \boldsymbol{a}_i \oplus \boldsymbol{b}_i$. We can ask if two vectors $\boldsymbol{x} \oplus \boldsymbol{y} \in S$ by checking that $\boldsymbol{x}^\top (S \oplus \boldsymbol{y}^\dagger) \approx 1$. If the pair are not bound in S, then $\boldsymbol{x}^\top (S \oplus \boldsymbol{y}^\dagger) \approx 0$ meaning $\boldsymbol{x} \oplus \boldsymbol{y} \notin S$. We explicitly use this problem formulation because it is integral to our approach to XML. This is shown for a 256 dimension space in Fig. 1 where the black dashed line marks the "in" case and the dotted black line the "not in" case. Notice that the naive HRR approach has present values that look absent, and absent values that look present, with unexpectedly large and small magnitudes. The variance of naive HRR also increases as the number of terms bound together increases. In contrast, our projection π keeps the response tightly around 1 and 0 for present and absent tokens respectively, even when binding 1024 vectors in only 256 dimensions. This is critical for us to represent large output spaces in a smaller source dimension, and removes the need for complex averaging and associative cleanup approaches attempt by Danihelka et al. [11].

Figure 1: Demonstrating of the neuro-symbolic HRR query checking if $\boldsymbol{x} \oplus \boldsymbol{y}$ is in the HRR vector S. If present, the response value (y-axis) should return ≈ 1.0 (dashed line). If absent, the response should ≈ 0 (dotted line). Naive use of HRR (blue & green) results in more noise as more pairs are bound (x-axis), with present and absent results both returning values far above and below the expected range $[0, 1]$. Our projection π (orange & red) keeps values stable and near their expected values.

4   Dense Label Representations

Now we will define our new neuro-symbolic approach to XML tasks by leveraging the HRR operations with our improved initialization from §3.1. We define L as the number of symbols (or labels) in the given task dataset. We will use a $d' \ll L$ dimensional output space $\mathbb{R}^{d'}$, which is a hyper-parameter we can choose. We will define two vectors $\boldsymbol{p}, \boldsymbol{m} \in \mathbb{R}^d$ to represent the concepts of a class being *present* and *missing* (or "negative" / "absent") from the label space $\mathcal{Y}_{1,\dots,L}$. We initialize $\boldsymbol{p} \sim \pi(\mathcal{N}(0, \mathrm{I}_d \cdot d'^{-1}))$, and then select m to be any vector orthogonal to $\boldsymbol{p}$.

We now define some additional notation and terms to describe our approach. We will use $\mathcal{Y}^p$ to denote the set of ground truth labels present for a given datapoint $\boldsymbol{x}$ and $\mathcal{Y}^m$ for the missing labels, where $\mathcal{Y}^p \cup \mathcal{Y}^m = \mathcal{Y}_{1,2,\dots,L}$. For every individual classification problem $\mathcal{Y}_i$, we will use $\boldsymbol{c}_i \sim \pi(\mathcal{N}(0, \mathrm{I}_d \cdot d'^{-1}))$ to represent each class with a vector. The vectors $\boldsymbol{p}, \boldsymbol{m}, \boldsymbol{c}_{1,2,\dots,L}$ will all be initialized how we have described, and will not be altered during training. To denote the neural network we will train and it's output, we will use $f(\boldsymbol{x}) = \hat{\boldsymbol{s}} \in \mathbb{R}^{d'}$.

HRR Label Vector: We begin by converting the labels for a data point $\boldsymbol{x}$ into a *labels vector* $\boldsymbol{s} \in \mathbb{R}^{d'}$. This vector $\boldsymbol{s}$ will be constructed using the HRR framework to be a neuro-symbolic representation of the original labels, and is defined by eq. (4). Thanks to the the commutative property of $\oplus$, the "present" vector $\boldsymbol{p}$ can move outside the summation and be bound with all present classes, and the non-present vector $\boldsymbol{m}$ can be bound with every item not present. This will create a statement $\boldsymbol{s}$ with technically hundreds of thousands of bound components that we could query. We can compute this efficiently in $\mathcal{O}(|\mathcal{Y}^p|)$ by computing once the "all labels" vector $\mathcal{A} = \sum_{i=1}^{L} \boldsymbol{c}_i$. This is done once at initialization, and then we can re-write eq. (4) into the more efficient form of eq. (5), leveraging the symbolic properties of HRR to avoid computation.

$$\boldsymbol{s} = \overbrace{\sum_{\boldsymbol{c}_p \in \mathcal{Y}^p} \mathbf{p} \oplus \boldsymbol{c}_p}^{\text{Labels present}} + \overbrace{\sum_{\boldsymbol{c}_m \in \mathcal{Y}^m} \boldsymbol{m} \oplus \mathbf{c}_m}^{\text{Labels absent}} \quad (4) \qquad = \mathbf{p} \oplus \sum_{\boldsymbol{c}_p \in \mathcal{Y}^p} \boldsymbol{c}_p + \boldsymbol{m} \oplus \left(\mathcal{A} - \sum_{\boldsymbol{c}_p \in \mathcal{Y}^p} \boldsymbol{c}_p \right) \quad (5)$$

HRR XML Loss: We now have the output of our network $\hat{\boldsymbol{s}}$ and a target vector $\boldsymbol{s}$ that exist in a $d' \ll L$ dimensional space. A straightforward idea would be to take an embedding style approach to make the loss function $\ell(\boldsymbol{s}, \hat{\boldsymbol{s}}) = \|\boldsymbol{s} - \hat{\boldsymbol{s}}\|_2^2$. This is intuitive and matches prior approaches to XML

[17, 19]. However, we found that such an approach resulted in no learning and degenerate random-guessing performance. This is because the regression formulation targets the overall errors in exact values, rather than the real goal of being able to extract the present classes from $\hat{s}$. Because binding many values in a fixed dimension d' introduces noise, the regression approach attempts to learn this underlying noise that is not meaningful to the actual problem.

Our solution to this issue is to again leverage the properties of HRR operations to create a loss based on our ability to accurately query the predicted statement s for the same components we would expect to find in the true label s. We remind the reader that we can query if a class $c_p \in s$ by checking if $s^\top c_p^* \approx 1$. We normalize this dot product, i.e., use the cosine similarity $\cos(s, c_p^*) = \frac{s^\top c_p^*}{\|s\|\|c_p^*\|}$ to perform these queries in a manner that limits the response magnitude to $[-1, 1]$, which will prevent degenerate solutions that attempt to maximize magnitude of response over query efficacy.

With the bounded cosine response, our loss has two components. First we build a loss term that goes though all present labels $\mathcal{Y}^p$, checking that each can be extracted. This involves computing $\mathbf{p}^* \oplus S$ to extract the symbolic statement representing all present vectors (i.e., $\mathbf{p}^* \oplus S \approx \sum_{c_p \in \mathcal{Y}^p} c_p$). Then we use each label HRR vector c_p and check if it is present in the extracted output. This results in eq. (6)

Next we confirm that the absent labels (the vast majority) are *not* queryable from the output. Rather than enumerate all $L - |\mathcal{Y}^p|$ labels, or perform lossy negative sampling, we can instead leverage the symbolic properties of HRR. We will compute $m^* \oplus s$ to extract the representation of all non-present classes, and perform a dot product against all present classes that are expected. This gives us eq. (7).

$$J_p = \sum_{c_p \in \mathcal{Y}^p} \left(1 - \cos\left(\mathbf{p}^* \oplus \hat{s}, c_p\right)\right) \quad (6) \qquad J_n = \cos\left(\mathbf{m}^* \oplus \hat{s}, \sum_{c_p \in \mathcal{Y}^p} c_p\right) \quad (7)$$

This negative component of the loss works because it is minimized by having the absent labels $m^* \oplus s$ and present labels $\sum_{c_p \in \mathcal{Y}^p} c_p$ be disjoint (i.e., no overlap). If there is any overlap, the dot product between these terms will increase, and thus, increasing the error.

Through this neuro-symbolic manipulation we can create a loss term that simultaneously considers the presence/absence of all L labels in only $d' \ll L$ dimensions and $\mathcal{O}(|\mathcal{Y}^p|)$ time. The final loss is simply $\ell(s, \hat{s}) = J_p + J_n$.

We remind the reader that the target label s is present in the form of knowing the exact $c_p \in \mathcal{Y}^p$ vectors to use. One could, if preferred, denote this loss as $\ell(\mathcal{Y}^p, \hat{s})$. We also note that expectation may be that a new hyper-parameter λ is needed to balance between the relative importance of eq. (6) and eq. (7). However, we find that no such parameter is needed and simply adding them together is effective.

5 Experiments & Analysis

We will now conduct an experimental evaluation of our new HHR based approach to XML classification. We emphasize to the reader that this is to show that the HRR approach of symbolically modeling a goal, and then back-propagating through the vector-symbolic HRR, works and has potential utility broadly. We do not argue for "dominance" at the XML task or to supplant all current approaches, XML is simply a task we are applying the HRR to due to show there are pros (and some cons) to the HRR approach. To this end we will show results with a Fully Connected (FC), Convoluional Neural Network (CNN) based network, and attention augmented Long-Shot Term Memory (LSTM) networks. Each will be endowed with our HRR dense label representations as described in §4 using our improved HRR initialization from §3 (becoming HRR-FC, HRR-CNN, and HRR-LSTM). The CNN & LSTM are taken from the XML-CNN [24] and AttentionXML [30] works. The AttentionXML's heiarchical prediction head is replaced with a fully connected layer in our experiments because we are interested in studying the impact of FC $\rightarrow$ HRR replacement, and how the change to an HRR impacts the standard network behavior. Using the XML tasks we will study the impact of the HRR an ablate choices like the use of fixed vs learned values for the p & m vectors, as well as the label vectors c_p, impact of increasing the HRR dimension d', and impact on model size and training time. We also ablated the impact of our projection step $\pi(\cdot)$, and found that in *all* cases skipping the projection step caused degradation to random-guessing performance, and thus will not be explicitly included in results.

5.1 Datasets & Evaluation Metrics

To assess the impact of dense label representations, we use eight of the datasets from Bhatia et al. [33]. Table 6 (see appendix) provides statistics about each dataset used for experiments. The average number of samples per label varies from 2.29-1902.15, and the average number of labels per data point varies from 2.40-75.54. Bhatia et al. [33] split the dataset into small scale and large datasets depending on the number of labels in each input sample. Small scale datasets consist of at most 5000 labels. The features are a bag-of-words representation of the text in every dataset. Negative labels are as much as $124321\times$ more populous than positive labels per point. TF-IDF style pre-processed features are available for all datasets, but the original text is not. We were unable to obtain the original text for all datasets, and models which require the original text (CNN & LSTM) thus are not tested when the raw text is not available.

We will consider two primary metrics in our evaluation that are common in XML work, Precision at k (P@k) and the propensity score at k (PSP@k). Given $\text{rank}_k(\hat{\mathbf{y}})$ as the rank of all the labels in $\hat{\mathbf{y}}$ and p_l is the relative frequency of the l'th label, the P@k (Equation 8) measures raw predictive accuracy of the top-k guesses, and PSP@k (Equation 9) down-wights correctly predicting frequent classes to counteract the power-law distribution of labels common in XML problems.

$$\text{P@}k := \frac{1}{k} \sum_{l \in \text{rank}_k(\hat{\mathbf{y}})} \mathbf{y}_l \qquad (8) \qquad\qquad \text{PSP@}k := \frac{1}{k} \sum_{l \in \text{rank}_k(\hat{\mathbf{y}})} \frac{\mathbf{y}_l}{p_l} \qquad (9)$$

For brevity we will focus on $k = 1$ in most experiments, but found that $k \in [1, 5]$ scores were all highly correlated and did not meaningfully alter any results. Additional metrics we considered are mentioned in Appendix C, but we found them so highly correlated with either P@k or PSP@k as to make them redundant.

5.2 Network Architectures

The baseline multi-label network is a fully-connected (FC) network with two hidden layers. Both hidden layers have the same size of 512 with a ReLU activation. The basline network has L outputs trained with binary cross entropy (BCE) loss with appropriate sigmoid activation. Our HRR version of this network (HRR-FC) uses the same architecture for input and hidden layers. But unlike the multi-label network, the output layer is significantly constrained (size is $512\times d'$) where d' is the size of dense label representation (§4 for more details). We note that this gives our HRR Network less parameters to solve the same problem, giving it a disadvantage in capacity.

For a CNN based model we will use the XML-CNN approach of [24]. Their original architecture with their code is used as the baseline, and our modified version (HRR-CNN) has the same architecture but replaces the output layer with the HRR approach as we used in HRR-FC just described. We note that the original code selected best results from the test set, leading to over-fitting. We have corrected this issue which prevents us from achieving the same results previously published.

For the LSTM model, we use the attention based bidirectional approach of AttentionXML [30]. The approach used for the output prediction of AttentionXML is involved in a hierarchical sequence of fully connected layers applied per output token to produce a single scalar output, which makes non-viable to directly convert to an HRR based approach. For this reason we replace the final hierarchical prediction heads of AttentionXML with the same attention mechanism but use a standard fully-connected output layer like the FC and XML-CNN models do, and denote this as the "LSTM" model in results. The version that used attention but our HRR based approach is denoted as HRR-LSTM.

Our goal is not to determine the most accurate possible XML model, and for this reason we do not perform any expensive hyper-parameter search over the architectures for any of the six models considered (FC, CNN, LSTM, and HRR variants). Doing so to maximize model accuracy would require considering many parameters and source of variation to make a robust conclusion on accuracy[34], but leaves each model on each dataset to have potentially highly different parameters. This obfuscates our true goal[35], which is to understand the impact of the HRR modification in isolation. For this reason we hold as many other variables as constant (depth, layers, neurons per layer, etc) and stick to the defaults found to work well in prior work for non-HRR networks. This allows us to isolate the HRR's impact, and intrinsically puts the HRR network at a disadvantage because it has fewer parameters.

5.3 XML HRR Accuracy

We first investigate how the smaller HRR space of $d' \ll L$ dimensions impacts each model's accuracy. Table 1 shows the performance of HRR approach to it's respective baselines, evaluated at $k = 1$ for brevity. For all datasets, dimension size d is 400 except in case of Amazon-13K, Wiki10-31K, Delicious-200K and Amazon-670K where d is 3000. In many cases our HRR based model approaches the high accuracies of state-of-the-art work, which is informative in that our HRR approach can be implemented with **XXX** lines of code, compared to hundreds of lines of the more involved methods. We underline the datasets that were used in these prior papers and use [a] to denote being with 5% (relative) of scores reported by [24], and [b] for 5% of the original AttentionXML [30].

Table 1: Accuracy of our baseline models and their HRR counterparts with the same network architecture otherwise. Cases where the HRR outperforms it's baseline counterpart are in **bold**.

	Bibtex		Delicious		Mediamil		Amazon-12K	
Model	FC	HRR-FC	FC	HRR-FC	FC	HRR-FC	CNN	HRR-CNN
P@1	46.4	**60.3**	65.0	**66.5**	84.8	83.9	89.1	84.5
PSP@1	32.5	**45.6**	64.2	**30.0**	64.2	63.7	49.2	44.2
			EURLex-4K				Amazon-13K	
Model	FC	HRR-FC	CNN	HRR-CNN	LSTM	HRR-LSTM	FC	HRR-FC
P@1	73.4	**77.2**[a]	47.1	**50.0**	63.0	**70.4**	93.0[a]	**93.3**[a,b]
PSP@1	32.0	30.7	18.0	17.5	26.4	**26.8**	52.6	49.6
			Wiki10-31K				Amazon-13K	
Model	FC	HRR-FC	CNN	HRR-CNN	LSTM	HRR-LSTM	LSTM	HRR-LSTM
P@1	80.4[a]	**81.1**[a,b]	60.0	**74.3**	83.5	**85.0**	90.0	**93.4**
PSP@1	9.46	9.19	10.4	9.88	10.6	10.5	48.7	**48.8**
			Delicious-200K		Amazon-670K			
Model	FC	HRR-FC	FC	HRR-FC	CNN	HRR-CNN		
P@1	21.8	**44.9**	34.6[a]	19.9	14.1	6.11		
PSP@1	10.5	6.84	5.22	**8.45**	9.39	1.51		

Each bold case shows HRR improving over its baseline. HRR-FC Bibtex improved $1.30 - 1.40\times$ and Delicious-200k's P@1 improved $2.06\times$ despite a $1.52\times$ decrease in PSP@1. HRR-CNN improved the Wiki10-31K results by $1.24\times$. In most cases when the HRR results are not better, they are near the performance of the baseline. Most PSP@1 show a ≤ 1 point decrease, and relative decrease on P@1 results is minimal. The overal results indicate that the HRR approach is moderately worse for retrieval of low-frequency labels, but often significantly better at high-frequency labels (a trade off that is task specific). The primary outlier in behavior is the Amazon-670K dataset, which appears to be pushing the limits of the HRR approach's ability to distinguish between the 670K label vectors. While this is a negative result in terms of XML, our goal was to improve HRRs: the ability to predict & retrieve the a correct label 19.9% of the time out of a space of 670K labels is a near three order of magnitude improvement over the naive HRR without our project step, which could only perform accurate retrievals of fixed and known vectors in a space of < 10 total outputs.

The high relative performance of our HRR-FC compared to XML-CNN and AttentionXML, and our difficulty replicating XML-CNN when fixing the test-set validation bug, does pose interesting questions about the impact of model choice on XML benchmarks. Similar results have been found in systematic review & replication of work in information retrieval and triplet learning [36, 37], but such an investigation is beyond the scope of our work.

5.4 HRR Model Compression & Runtime

Because of the largeness of the output space L, the output fully connected layer can represent an enormous amount of the weights within a neural network in this problem space. We can see in Table 2 that the HRR approach can reduce the number of parameters in the output layer by 59-99%, which accounts for 29-42% of the model's total parameters in most cases. The mild exception is the Amazon-13k corpus, which has a large number of input features and comparatively smaller output space. This shows that our HRR approach naturally provides a more compact representation that could be

applicable for situations with a high arity of discrete outputs, yet allows learning in a continuous fashion without any sampling tricks.

Fewer parameters leads to a natural speedup in training time too. Table 3 shows the optimization time for a training epoch for a multi-label baseline and HRR-FC where we see an up-to $6.3\times$ reduction in optimization time. The larger the output label space is relative to the rest of the network, the more advantage we obtain. The four cases where HRRs are slower are all the fastest cases, with the smallest dimensions, which prevent the overheads of the HRR implementation from fully realizing their benefit. This is because the cross-entropy calculations are highly optimized, and faster than the cosine similarity and for loops needed by our HRR implementation.

We note that separate from the training time, at inference time on the test set the HRR approach currently takes the same time as the fully-connected output. This is because each positive label c_p is queries against the network's output $\hat{s}$, but this need not be the case. There is further potential for improvement by developing specialized Maximum Inner Product Search (MIPS) kernels that interface nicely with PyTorch, don't require memory copies, and can re-constitute the output labels as needed. These are all engineering challenges we consider beyond scope of the current work, as we are concerned with how to learn through HRRs.

Table 2: For each dataset the percentage reduction in parameters of the output layer, and the resulting change for the entire network, by replacing the output layer from a fully-connected softmax with our HRR approach.

Dataset	Dim d'	% Compression	
		Output	Network
Delicious	400	59.30	29.22
EURLex-4K	400	89.98	37.80
Wiki10-31K	3000	90.25	29.49
Amazon-13K	3000	77.49	4.74
Delicious-200K	3000	98.53	41.88
Amazon-670K	3000	99.55	42.09

Table 3: Speedup in training time for HRR-FC over the FC model. **Bold** indicates improved runtime.

Dataset	Speedup
Bibtex	0.35
Delicious	0.38
Mediamill	0.39
EURLex-4K	0.35
Wiki10-31K	**1.48**
Amazon-13K	**1.33**
Delicious-200K	**4.47**
Amazon-670K	**6.28**

5.5 Assessing Impact of Hyper-parameters

By demonstrating non-trivial learning that can match or even improve upon the accuracy of a standard fully-connected output layer that naturally leads to reductions in model size/memory use and improved training time as the models get larger, we have shown that our projection step makes HRRs viable for future learning tasks. This is because without our modification we get consistent random-guessing performance across all datasets.

However, our larger goal is to gain new information about how to learn with HRRs. As such we now perform a number of ablation experiments to elucidate potential factors relevant to future work outside of XML. This includes the impact of the output dimension d', the effect of increasing model size, and if the HRR vectors should be altered via gradient descent or left static as we have done. Due to space limitations, we will show many results on just the Wiki10-31K dataset in this section as we found it tracks well with overall behavior on other corpora.

Label Dimension Size: While training a model with a dense label representation, the vector size d' of the label is fixed. Figure 2 shows the impact of vector dimension size on the model's precision. As observed, Precision@5 increases when the dimension size is increased (and is representative of other metric's behavior). For datasets *Wiki10-31K* and *AmazonCat-13K*, the precision begins to plateau when the dimension size is approximately 10% of the number of labels in that dataset. The trend is consistent across all Precision@k measurements. For a larger dataset like *Delicious-200K*, the precision levels off at

Figure 2: P@5 (y-axis) performance quickly plateaus as the output network size d' (x-axis) increases. The plateau occurs at $d' \leq 10\% \cdot L$, requiring a smaller percentage of all labels L as L increases.

a dimension size of 2500, which is 1.25% of the number of labels. Thus, figure 2 suggests that HRR

can substantially compress the size of the label vector as the number of labels increases (and with it the label distribution itself is increasingly skewed).

Network Layer Size: Our initial results in §5.3 showed that our HRR-FC & HRR-CNN have comparable or better accuracy, while also having less parameters. We also looked at how these results would change as both models are made larger. Results from Wiki10-31K are shown in table 4. We can see that even moderate changes to the baseline network actually produce a drop in accuracy, which is expected since we tuned the initial architecture to baseline performance. For our HRR-FC more layers or hidden neurons have minor impact, but combined with larger output size d' can increase performance from the initial 53.25% up to 58.51%. All of these HRR-FCs still have fewer parameters than the initial baseline network.

Table 4: Increasing the number of layers or hidden neurons has less benefit to the FC baseline compared to the HRR approach.

Net.	Layers	Hidden h	Out d'	P@5
FC	2	512	30938	46.64
	2	2048	30938	47.91
	3	512	30938	41.92
	3	2048	30938	45.25
HRR	3	512	400	55.06
	3	2048	400	55.36
	3	2048	750	56.84
	3	2048	1500	57.80
	3	**2048**	**3000**	**58.51**

Updating p & m Vectors: The p and m vectors are the key to the cumulative positive and negative class vectors. It is possible to backpropagate to these vectors and alter them during training, rather than hold them fixed as we have done. We measure the impact of updating p and m vectors in comparison to keeping them static while the model is being trained. We found that maintaining p and m vectors fixed is beneficial when the dimension size is small ($d' \leq 400$). As d' increases we observe no impact from learning the values of p and m. This was consistent across all datasets and architectures.

Updating Label Vectors c_p: Another question is if we should have allowed the label vectors c_p to be altered during training, rather than holding them fixed at initialized values. We test this in Table 5 using a network with multiple different numbers of hidden neurons h and output dimensions d' for a 2-layer network, where the ∇_{c_p} is the performance when we allow the concept vectors to be learned. We note that this was implemented by always back-propagating through our complex unit magnitude projection π, and resulted in no significant performance difference. Experiments without the projection π had significantly degraded results that gave random-guessing performance.

Table 5: Ablation test of whether label vectors c_p should be altered during training (right most column) or remain fixed (2nd from right). Results are from Wiki10-31K as a representative dataset.

		P@5	
Hidden h	Out d'	Fixed	∇_{c_p}
512	400	55.06	53.50
2048	400	55.36	55.45
2048	750	56.84	56.75
2048	1500	57.80	57.69
2048	3000	58.51	58.18

These experiments show that altering the HRR vectors, at least in the XML application, have no benefit. We had expected this to perform better by giving the network a chance to adjust for any unfavorable initialization. Our current hypothesis is that the network's own parameters are sufficient to learn how to leverage the dynamics of HRR operations, which should still encourage the same properties while training, making the weights of the HRR concept vectors redundant. Further exploration of this is needed in future studies.

6 Conclusion

We have improved the initialization of HRRs to increase binding and retrieval accuracy, allowing for a convenient & differentiable neuro-symbolic approach. To demonstrate potential utility we have applied HRRs to extreme multi-label classification. We observe reduced model size, faster training, and stable-to-improved accuracy. This provide evidence for the general utility and further study of HRRs. The learning dynamics of HRRs are not yet fully understood by our work and have the counter-intuitive behavior that learning with them, but not altering them, tends to have the best results. Compared to prior works looking at HRRs we have significantly improved the viability of building more complex networks that leverage the symbolic manipulation properties of HRRs, which we opens the door to a new kind of approach to modeling problems.

References

[1] T. Plate, "Holographic reduced representations," *IEEE Transactions on Neural Networks*, vol. 6, no. 3, pp. 623–641, 5 1995. [Online]. Available: http://ieeexplore.ieee.org/document/377968/

[2] M. N. Jones and D. J. Mewhort, "Representing word meaning and order information in a composite holographic lexicon," *Psychological Review*, vol. 114, no. 1, pp. 1–37, 2007.

[3] P. Blouw and C. Eliasmith, "A Neurally Plausible Encoding of Word Order Information into a Semantic Vector Space," *35th Annual Conference of the Cognitive Science Society*, vol. 35, pp. 1905–1910, 2013.

[4] T. C. Stewart and C. Eliasmith, "Large-scale synthesis of functional spiking neural circuits," *Proceedings of the IEEE*, vol. 102, no. 5, pp. 881–898, 2014.

[5] P. Blouw, E. Solodkin, P. Thagard, and C. Eliasmith, "Concepts as Semantic Pointers: A Framework and Computational Model," *Cognitive Science*, vol. 40, no. 5, pp. 1128–1162, 7 2016. [Online]. Available: http://doi.wiley.com/10.1111/cogs.12265

[6] C. Eliasmith, T. C. Stewart, X. Choo, T. Bekolay, T. DeWolf, Y. Tang, and D. Rasmussen, "A Large-Scale Model of the Functioning Brain," *Science*, vol. 338, no. 6111, pp. 1202–1205, 11 2012. [Online]. Available: https://www.sciencemag.org/lookup/doi/10.1126/science.1225266

[7] R. Singh and C. Eliasmith, "Higher-Dimensional Neurons Explain the Tuning and Dynamics of Working Memory Cells," *Journal of Neuroscience*, vol. 26, no. 14, pp. 3667–3678, 2006. [Online]. Available: https://www.jneurosci.org/content/26/14/3667

[8] T. Bekolay, J. Bergstra, E. Hunsberger, T. DeWolf, T. Stewart, D. Rasmussen, X. Choo, A. Voelker, and C. Eliasmith, "Nengo: a Python tool for building large-scale functional brain models," *Frontiers in Neuroinformatics*, vol. 7, p. 48, 2014. [Online]. Available: https://www.frontiersin.org/article/10.3389/fninf.2013.00048

[9] M. Nickel, L. Rosasco, and T. Poggio, "Holographic Embeddings of Knowledge Graphs," in *Proceedings of the Thirtieth AAAI Conference on Artificial Intelligence*, ser. AAAI'16. AAAI Press, 2016, p. 1955–1961.

[10] S. Liao and B. Yuan, "CircConv: A Structured Convolution with Low Complexity," in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 33, 7 2019, pp. 4287–4294. [Online]. Available: http://www.aaai.org/ojs/index.php/AAAI/article/view/4337

[11] I. Danihelka, G. Wayne, B. Uria, N. Kalchbrenner, and A. Graves, "Associative Long Short-Term Memory," in *Proceedings of The 33rd International Conference on Machine Learning*, 2016, pp. 1986–1994.

[12] W. Bi and J. Kwok, "Efficient Multi-label Classification with Many Labels," in *ICML*, ser. Proceedings of Machine Learning Research, S. Dasgupta and D. McAllester, Eds., vol. 28, no. 3. Atlanta, Georgia, USA: PMLR, 2013, pp. 405–413. [Online]. Available: http://proceedings.mlr.press/v28/bi13.html

[13] H. Jain, Y. Prabhu, and M. Varma, "Extreme Multi-Label Loss Functions for Recommendation, Tagging, Ranking & Other Missing Label Applications," in *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, ser. KDD '16. New York, NY, USA: Association for Computing Machinery, 2016, p. 935–944. [Online]. Available: https://doi.org/10.1145/2939672.2939756

[14] Y. Prabhu and M. Varma, "FastXML: A Fast, Accurate and Stable Tree-Classifier for Extreme Multi-Label Learning," in *Proceedings of the 20th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, ser. KDD '14. New York, NY, USA: Association for Computing Machinery, 2014, p. 263–272. [Online]. Available: https://doi.org/10.1145/2623330.2623651

[15] J. Weston, A. Makadia, and H. Yee, "Label Partitioning For Sublinear Ranking," in *ICML*, ser. Proceedings of Machine Learning Research, S. Dasgupta and D. McAllester, Eds., vol. 28, no. 2. Atlanta, Georgia, USA: PMLR, 2013, pp. 181–189. [Online]. Available: http://proceedings.mlr.press/v28/weston13.html

[16] W. Siblini, P. Kuntz, and F. Meyer, "CRAFTML, an Efficient Clustering-based Random Forest for Extreme Multi-label Learning," in *ICML*, ser. Proceedings of Machine Learning Research, J. Dy and A. Krause, Eds., vol. 80. Stockholmsmässan, Stockholm Sweden: PMLR, 2018, pp. 4664–4673. [Online]. Available: http://proceedings.mlr.press/v80/siblini18a.html

[17] A. Jalan and P. Kar, "Accelerating Extreme Classification via Adaptive Feature Agglomeration," in *Proceedings of the Twenty-Eighth International Joint Conference on Artificial Intelligence*. California: International Joint Conferences on Artificial Intelligence Organization, 8 2019, pp. 2600–2606. [Online]. Available: https://www.ijcai.org/proceedings/2019/361

[18] Y. Tagami, "AnnexML: Approximate Nearest Neighbor Search for Extreme Multi-Label Classification," in *Proceedings of the 23rd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, ser. KDD '17. New York, NY, USA: Association for Computing Machinery, 2017, p. 455–464. [Online]. Available: https://doi.org/10.1145/3097983.3097987

[19] K. Bhatia, H. Jain, P. Kar, M. Varma, and P. Jain, "Sparse Local Embeddings for Extreme Multi-label Classification," in *Advances in Neural Information Processing Systems 28*, C. Cortes, N. D. Lawrence, D. D. Lee, M. Sugiyama, and R. Garnett, Eds. Curran Associates, Inc., 2015, pp. 730–738. [Online]. Available: http://papers.nips.cc/paper/5969-sparse-local-embeddings-for-extreme-multi-label-classification.pdf

[20] H.-F. Yu, P. Jain, P. Kar, and I. S. Dhillon, "Large-Scale Multi-Label Learning with Missing Labels," in *Proceedings of the 31st International Conference on International Conference on Machine Learning - Volume 32*, ser. ICML'14. JMLR.org, 2014, p. I–593–I–601.

[21] A. Niculescu-Mizil and E. Abbasnejad, "Label Filters for Large Scale Multilabel Classification," in *Proceedings of the 20th International Conference on Artificial Intelligence and Statistics*, ser. Proceedings of Machine Learning Research, A. Singh and J. Zhu, Eds., vol. 54. Fort Lauderdale, FL, USA: PMLR, 2017, pp. 1448–1457. [Online]. Available: http://proceedings.mlr.press/v54/niculescu-mizil17a.html

[22] H. Jain, V. Balasubramanian, B. Chunduri, and M. Varma, "Slice: Scalable Linear Extreme Classifiers Trained on 100 Million Labels for Related Searches," in *Proceedings of the Twelfth ACM International Conference on Web Search and Data Mining*, ser. WSDM '19. New York, NY, USA: Association for Computing Machinery, 2019, p. 528–536. [Online]. Available: https://doi.org/10.1145/3289600.3290979

[23] R. Babbar and B. Schölkopf, "DiSMEC: Distributed Sparse Machines for Extreme Multi-Label Classification," in *Proceedings of the Tenth ACM International Conference on Web Search and Data Mining*, ser. WSDM '17. New York, NY, USA: Association for Computing Machinery, 2017, p. 721–729. [Online]. Available: https://doi.org/10.1145/3018661.3018741

[24] J. Liu, W.-C. Chang, Y. Wu, and Y. Yang, "Deep Learning for Extreme Multi-Label Text Classification," in *Proceedings of the 40th International ACM SIGIR Conference on Research and Development in Information Retrieval*, ser. SIGIR '17. New York, NY, USA: Association for Computing Machinery, 2017, p. 115–124. [Online]. Available: https://doi.org/10.1145/3077136.3080834

[25] T. Jiang, D. Wang, L. Sun, H. Yang, Z. Zhao, and F. Zhuang, "LightXML: Transformer with Dynamic Negative Sampling for High-Performance Extreme Multi-label Text Classification," in *AAAI*, 2021. [Online]. Available: http://arxiv.org/abs/2101.03305

[26] K. Dahiya, D. Saini, A. Mittal, A. Shaw, K. Dave, A. Soni, H. Jain, S. Agarwal, and M. Varma, "DeepXML: A Deep Extreme Multi-Label Learning Framework Applied to Short Text Documents," in *Proceedings of the 14th ACM International Conference on Web Search and Data Mining*, ser. WSDM '21. New York, NY, USA: Association for Computing Machinery, 2021, p. 31–39. [Online]. Available: https://doi.org/10.1145/3437963.3441810

[27] A. Mittal, K. Dahiya, S. Agrawal, D. Saini, S. Agarwal, P. Kar, and M. Varma, "DECAF: Deep Extreme Classification with Label Features," in *Proceedings of the 14th ACM International Conference on Web Search and Data Mining*, ser. WSDM '21. New York, NY, USA: Association for Computing Machinery, 2021, p. 49–57. [Online]. Available: https://doi.org/10.1145/3437963.3441807

[28] W.-C. Chang, H.-F. Yu, K. Zhong, Y. Yang, and I. S. Dhillon, "Taming Pretrained Transformers for Extreme Multi-Label Text Classification," in *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, ser. KDD '20. New York, NY, USA: Association for Computing Machinery, 2020, p. 3163–3171. [Online]. Available: https://doi.org/10.1145/3394486.3403368

[29] T. K. R. Medini, Q. Huang, Y. Wang, V. Mohan, and A. Shrivastava, "Extreme Classification in Log Memory using Count-Min Sketch: A Case Study of Amazon Search with 50M Products," in *Advances in Neural Information Processing Systems*, H. Wallach, H. Larochelle, A. Beygelzimer, F. d\textquotesingle Alché-Buc, E. Fox, and R. Garnett, Eds., vol. 32. Curran Associates, Inc., 2019. [Online]. Available: https://proceedings.neurips.cc/paper/2019/file/69cd21a0e0b7d5f05dc88a0be36950c7-Paper.pdf

[30] R. You, Z. Zhang, Z. Wang, S. Dai, H. Mamitsuka, and S. Zhu, "AttentionXML: Label Tree-based Attention-Aware Deep Model for High-Performance Extreme Multi-Label Text Classification," in *Advances in Neural Information Processing Systems 32*, H. Wallach, H. Larochelle, A. Beygelzimer, F. d\textquotesingle Alché-Buc, E. Fox, and R. Garnett, Eds. Curran Associates, Inc., 2019, pp. 5820–5830. [Online]. Available: http://papers.nips.cc/paper/8817-attentionxml-label-tree-based-attention-aware-deep-model-for-high-performance-extreme-multi-label-text-classifica pdf

[31] C. Guo, A. Mousavi, X. Wu, D. N. Holtmann-Rice, S. Kale, S. Reddi, and S. Kumar, "Breaking the Glass Ceiling for Embedding-Based Classifiers for Large Output Spaces," in *Advances in Neural Information Processing Systems*, H. Wallach, H. Larochelle, A. Beygelzimer, F. d\textquotesingle Alché-Buc, E. Fox, and R. Garnett, Eds., vol. 32. Curran Associates, Inc., 2019. [Online]. Available: https://proceedings.neurips.cc/paper/2019/file/78f7d96ea21ccae89a7b581295f34135-Paper.pdf

[32] M. Wydmuch, K. Jasinska, M. Kuznetsov, R. Busa-Fekete, and K. Dembczynski, "A no-regret generalization of hierarchical softmax to extreme multi-label classification," in *Advances in Neural Information Processing Systems*, 2018, pp. 6355–6366.

[33] K. Bhatia, K. Dahiya, H. Jain, A. Mittal, Y. Prabhu, and M. Varma, "The extreme classification repository: Multi-label datasets and code," 2016. [Online]. Available: http://manikvarma.org/downloads/XC/XMLRepository.html

[34] X. Bouthillier, P. Delaunay, M. Bronzi, A. Trofimov, B. Nichyporuk, J. Szeto, N. Sepah, E. Raff, K. Madan, V. Voleti, S. E. Kahou, V. Michalski, D. Serdyuk, T. Arbel, C. Pal, G. Varoquaux, and P. Vincent, "Accounting for Variance in Machine Learning Benchmarks," in *Machine Learning and Systems (MLSys)*, 2021. [Online]. Available: http://arxiv.org/abs/2103.03098

[35] X. Bouthillier, C. Laurent, and P. Vincent, "Unreproducible Research is Reproducible," in *Proceedings of the 36th International Conference on Machine Learning*, ser. Proceedings of Machine Learning Research, K. Chaudhuri and R. Salakhutdinov, Eds., vol. 97. Long Beach, California, USA: PMLR, 2019, pp. 725–734. [Online]. Available: http://proceedings.mlr.press/v97/bouthillier19a.html

[36] M. F. Dacrema, P. Cremonesi, and D. Jannach, "Are we really making much progress? A Worrying Analysis of Recent Neural Recommendation Approaches," in *Proceedings of the 13th ACM Conference on Recommender Systems - RecSys '19*. New York, New York, USA: ACM Press, 2019, pp. 101–109. [Online]. Available: http://dl.acm.org/citation.cfm?doid=3298689.3347058

[37] K. Musgrave, S. Belongie, and S.-N. Lim, "A Metric Learning Reality Check," in *ECCV*, 2020. [Online]. Available: http://arxiv.org/abs/2003.08505

[38] C. G. Snoek, M. Worring, J. C. Van Gemert, J.-M. Geusebroek, and A. W. Smeulders, "The challenge problem for automated detection of 101 semantic concepts in multimedia," in *Proceedings of the 14th ACM international conference on Multimedia*, 2006, pp. 421–430.

[39] I. Katakis, G. Tsoumakas, and I. Vlahavas, "Multilabel text classification for automated tag suggestion," in *Proceedings of the ECML/PKDD*, vol. 18, 2008, p. 5.

[40] G. Tsoumakas, I. Katakis, and I. Vlahavas, "Effective and efficient multilabel classification in domains with large number of labels," in *Proc. ECML/PKDD 2008 Workshop on Mining Multidimensional Data (MMD'08)*, vol. 21, 2008, pp. 53–59.

[41] J. Leskovec and A. Krevl, "Snap datasets: Stanford large network dataset collection," 2014.

[42] A. Zubiaga, "Enhancing navigation on wikipedia with social tags," *arXiv preprint arXiv:1202.5469*, 2012.

[43] J. McAuley and J. Leskovec, "Hidden factors and hidden topics: understanding rating dimensions with review text," in *Proceedings of the 7th ACM conference on Recommender systems*, 2013, pp. 165–172.

[44] R. Wetzker, C. Zimmermann, and C. Bauckhage, "Analyzing social bookmarking systems: A del. icio. us cookbook," in *Proceedings of the ECAI 2008 Mining Social Data Workshop*, 2008, pp. 26–30.

[45] C. Luo and A. Shrivastava, "SSH (Sketch, Shingle, & Hash) for Indexing Massive-Scale Time Series," in *Proceedings of the Time Series Workshop at NIPS 2016*, ser. Proceedings of Machine Learning Research, O. Anava, A. Khaleghi, M. Cuturi, V. Kuznetsov, and A. Rakhlin, Eds., vol. 55. Barcelona, Spain: PMLR, 2017, pp. 38–58. [Online]. Available: http://proceedings.mlr.press/v55/luo16.html

[46] R. Pratap, "Efficient Dimensionality Reduction for Sparse Binary Data," in *IEEE Big Data*, 2018, pp. 152–157.

[47] J. Liu, W.-C. Chang, Y. Wu, and Y. Yang, "Deep learning for extreme multi-label text classification," in *Proceedings of the 40th International ACM SIGIR Conference on Research and Development in Information Retrieval*, 2017, pp. 115–124.