Randomized Response with Prior and Applications to Learning with Label Differential Privacy

Abstract

The Randomized Response (RR) algorithm [78] is a classical technique to improve robustness in survey aggregation, and has been widely adopted in applications with differential privacy guarantees. We propose a novel algorithm, *Randomized Response with Prior* (RRWithPrior), which can provide more accurate results while maintaining the same level of privacy guaranteed by RR. We then apply RRWithPrior to learn neural networks with *label* differential privacy (LabelDP), and show that when only the label needs to be protected, the model performance can be significantly improved over the previous state-of-the-art private baselines. More-over, we study different ways to obtain priors, which when used with RRWithPrior can additionally improve the model performance, further reducing the accuracy gap between private and non-private models. We complement the empirical results with theoretical analysis showing that LabelDP is provably easier than protecting both the inputs and labels.

1 Introduction

The widespread adoption of machine learning in recent years has increased the concerns about the privacy of individuals whose data is used during model training. Differential privacy (DP) [29, 28] has emerged as a popular privacy notion that has been the basis of several practical deployments including in industry [30, 68, 35, 7, 24] and the U.S. Census [3].

A classical algorithm—that predates DP and was initially designed to eliminate evasive answer biases in survey aggregation—is *Randomized Response* (RR) [78]: when the input is an element from a finite alphabet, the output is equal to the input with a certain probability, and is a uniform random other element from the alphabet with the remaining probability. This simple algorithm is shown to satisfy the strong notion of *local* DP [32, 50], whereby the response of each user is protected, in contrast with the so-called *central* DP setting where a curator has access to the raw user data, and only the output of the curator is required to be DP. We note that schemes building on RR have been studied in several previous works on DP estimation (e.g., [25, 49]), and have been deployed in practice [68].

The large error incurred by RR (e.g., [12]) has stimulated significant research aiming to improve its accuracy, mostly by relaxing to weaker privacy models (e.g., [31, 19, 4]). In this work, we use a different approach and seek to improve RR by leveraging available *prior* information. A recent work of Liu et al. [54] also used priors to improve accuracy, but in the context of the DP *multiplicative weights* algorithm, which applies in the *central* DP setting. The prior information can consist of domain-specific knowledge, (models trained on) publicly available data, or historical runs of a training algorithm. Our algorithm is presented in Section 3 (Algorithm 2). At a high level, given a prior distribution **p** on the alphabet, the algorithm uses **p** to prune the alphabet. If the prior is reliable and even if the alphabet is only minimally pruned, the probability that the output equals the input is larger than when RR is applied to the entire alphabet. On the other hand, if the prior is uniform over the

entire alphabet, then our algorithm recovers the classical RR. To implement the above recipe, one needs to specify how to effect the pruning using **p**. It turns out that the magnitude of pruning can itself vary depending on **p**, but we can obtain a closed-form formula for determining this. Interestingly, by studying a suitable linear program, we show that the resulting RRWithPrior strategy is *optimal* in that among all ε-DP algorithms, it maximizes the probability that that the output equals the input when the latter is sampled from **p** (Theorem 3).

1.1 Applications to Learning with Label Differential Privacy

There have been a great number of papers over the last decade that developed DP machine learning algorithms (e.g., [14, 72, 69]). In the case of deep learning, the seminal work of Abadi et al. [2] introduced a DP training framework (DP-SGD) that was integrated into TensorFlow [67] and PyTorch [75]. Despite numerous followup works, including, e.g., [63–65, 57, 80, 61, 15, 76], and extensive efforts, the accuracy of models trained with DP-SGD remains significantly lower than that of models trained without DP constraints. Notably, for the widely considered CIFAR-10 dataset, the highest reported accuracy for DP models is 69.3% [76], which strikingly relies on *handcrafted* visual features despite that in non-private scenarios *learned* features long been shown to be superior. Even using pre-training with external (CIFAR-100) data, the best reported DP accuracy, 73%[1], is still far below the non-private baselines ($> 95\%$). The performance gap becomes a roadblocker for many real-world applications to adopt DP. In this paper, we focus on a more restricted, but important, special case where the DP guarantee is only required to hold with respect to the labels, as described next.

In the *label differential privacy* (LabelDP) setting, the *labels* are considered sensitive, and their privacy needs to be protected, while the input points are not sensitive. This notion has been studied in the PAC setting [13, 9] and for sparse linear regression [77], and it captures several practical scenarios. Examples include: (i) computational advertising where the impressions are known to the Ad Tech[2], and thus considered non-sensitive, while the conversions reveal user interest and are thus private (see, e.g., Nalpas and Dutton [60]), (ii) recommendation systems where the choices are known, e.g., to the streaming service provider, but the user ratings are considered sensitive, and (iii) user surveys and analytics where demographic information (e.g., age, gender) is non-sensitive but income is sensitive—in fact, this was the motivating reason for Warner [78] to propose RR many decades ago! We present a novel *multi-stage algorithm* (LP-MST) for training deep neural networks with LabelDP that builds on top of RRWithPrior (see Section 3 and Algorithm 3), and we benchmark its empirical performance (Section 5) on multiple datasets, domains, and architectures, including the following.

- On CIFAR-10, we show that it achieves 20% higher accuracy than DP-SGD[3].
- On the more challenging CIFAR-100, we present the first non-trivial DP learning results.
- On MovieLens, which consists of user ratings of movies, we show improvements via LP-MST.
- We demonstrate how priors computed from a (non-private) self-supervised learning phase on the input points can be used to achieve higher accuracy with a LabelDP guarantee with extremely small privacy budgets ($\varepsilon \leq 0.1$, see Section 5.2 for details).

We note that due to the requirement of DP-SGD to compute and clip *per-instance gradient*, it remains technically challenging to scale to larger models or mini-batch sizes, despite numerous attempts to minigate this problem [34, 5, 21, 73]. On the other hand, our formulation allows us to use state-of-the-art deep learning architectures such as ResNet [43]. We also stress that our LP-MST algorithm goes beyond deep learning methods that are robust to label noise. (See [71] for a survey of the latter.)

Our empirical results suggest that protecting the privacy of labels can be significantly easier than protecting the privacy of both inputs and labels. We find further evidence to this by showing that for the special case of stochastic convex optimization (SCO), the sample complexity of algorithms privatizing the labels is much smaller than that of algorithms privatizing both labels and inputs;

---

[1]For DP parameters of $\varepsilon = 8$ and $\delta = 10^{-5}$, cited from Abadi et al. [2, Figure 6]. For a formal definition of DP, we refer the reader to Definition 2.1.

[2]Ad tech (abbreviating Advertising Technology) comprises the tools that help agencies and brands target, deliver, and analyze their digital advertising efforts; see, e.g., `blog.hubspot.com/marketing/what-is-ad-tech`.

[3]We remark that the notion of ε-DP in [2, 64, 63] is *not* directly comparable to ε-Label DP in our work in that they use the addition/removal notion whereas we use the substitution one. Please see the Supplementary Material for more discussion on this.

specifically, we achieve *dimension-independent* bounds for LabelDP. We also show that a good prior can ensure smaller population error for non-convex loss. (Details are in the Supplementary Material.)

2 Preliminaries

For any positive integer K, let $[K] := \{1, \ldots, K\}$. *Randomized response* (RR) [78] is the following: let $\varepsilon \geq 0$ be a parameter and let $y \in [K]$ be the true value known to RR_ε. When an *observer* queries the value of y, RR_ε responds with a random draw $\tilde{y}$ from the following probability distribution:

$$\Pr[\tilde{y} = \hat{y}] = \begin{cases} \frac{e^\varepsilon}{e^\varepsilon + K - 1} & \text{for } \hat{y} = y, \\ \frac{1}{e^\varepsilon + K - 1} & \text{otherwise.} \end{cases} \tag{1}$$

In this paper, we focus on the application of learning with label differential privacy. We recall the definition of differential privacy (DP), which is applicable to any notion of *neighboring datasets*. For a textbook reference, we refer the reader to Dwork and Roth [27].

Definition 2.1 (Differential Privacy (DP) [28, 29])**.** Let $\varepsilon, \delta \in \mathbb{R}_{\geq 0}$. A randomized algorithm A taking as input a dataset is said to be (ε, δ)-*differentially private* ((ε, δ)-DP) if for any two *neighboring datasets* $\mathbf{D}$ and $\mathbf{D}'$, and for any subset S of outputs of A, it is the case that $\Pr[\mathsf{A}(\mathbf{D}) \in S] \leq e^\varepsilon \cdot \Pr[\mathsf{A}(\mathbf{D}') \in S] + \delta$. If $\delta = 0$, then A is said to be ε-*differentially private* (ε-DP).

When applied to machine learning methods in general and deep learning in particular, DP is usually enforced on the weights of the trained model [see, e.g., 14, 51, 2]. In this work, we focus on the notion of label differential privacy.

Definition 2.2 (Label Differential Privacy)**.** Let $\varepsilon, \delta \in \mathbb{R}_{\geq 0}$. A randomized training algorithm A taking as input a dataset is said to be (ε, δ)-*label differentially private* ((ε, δ)-LabelDP) if for any two training datasets $\mathbf{D}$ and $\mathbf{D}'$ that differ in the *label* of a *single example*, and for any subset S of outputs of A, it is the case that $\Pr[\mathsf{A}(\mathbf{D}) \in S] \leq e^\varepsilon \cdot \Pr[\mathsf{A}(\mathbf{D}') \in S] + \delta$. If $\delta = 0$, then A is said to be ε-*label differentially private* (ε-LabelDP).

All proofs skipped in the main body are given in the Supplementary Material.

3 Randomized Response with Prior

In many real world applications, a prior distribution about the labels could be publicly obtained from domain knowledge and help the learning process. In particular, we consider a setting where for each (private) label y in the training set, there is an associated prior $\mathbf{p} = (p_1, \ldots, p_K)$. The goal is to output a randomized label $\tilde{y}$ that maximizes the probability that the output is correct (or equivalently maximizes the signal-to-noise ratio), i.e., $\Pr[y = \tilde{y}]$. The privacy constraint here is that the algorithm should be ε-DP with respect to y. (It need *not* be private with respect to the prior $\mathbf{p}$.)

We first describe our algorithm RRWithPrior by assuming access to such priors.

3.1 Algorithm: RRWithPrior

We build our RRWithPrior algorithm with a subroutine called RRTop-k, as shown in Algorithm 1, which is a modification of randomized response where we only consider the set of k labels i with largest p_i. Then, if the input label y belongs to this set, we use standard randomized response on this set. Otherwise, we output a label from this set uniformly at random.

Algorithm 1 RRTop-k

Input: A label $y \in [K]$
Parameters: $k \in [K]$, prior $\mathbf{p} = (p_1, \ldots, p_K)$

1. Let Y_k be the set of k labels with maximum prior probability (with ties broken arbitrarily).
2. If $y \in Y_k$, then output y with probability $\frac{e^\varepsilon}{e^\varepsilon + k - 1}$ and output $y' \in Y_k \setminus \{y\}$ with probability $\frac{1}{e^\varepsilon + k - 1}$.
3. If $y \notin Y_k$, output an element from Y_k uniformly at random.

The main idea behind RRWithPrior is to dynamically estimate an optimal k^* based on the prior $\mathbf{p}$, and run RRTop-k with k^*. Specifically, we choose k^* by maximizing $\Pr[\text{RRTop-}k(y) = y]$. It is not hard to see that this expression is exactly equal to $\frac{e^{\varepsilon}}{e^{\varepsilon}+k-1} \cdot \left(\sum_{\tilde{y} \in Y_k} p_{\tilde{y}} \right)$ if $y \sim \mathbf{p}$. RRWithPrior is presented in Algorithm 2.

Algorithm 2 RRWithPrior

Input: A label $y \in [K]$
Parameters: prior $\mathbf{p} = (p_1, \ldots, p_K)$
1. For $k \in [K]$:
    (a) Compute $w_k := \frac{e^{\varepsilon}}{e^{\varepsilon}+k-1} \cdot \left(\sum_{\tilde{y} \in Y_k} p_{\tilde{y}} \right)$, where Y_k is the set of k labels with maximum
        prior probability (ties broken arbritrarily).
2. Let $k^* = \arg\max_{k \in [K]} w_k$.
3. Return an output of RRTop-k (y) with $k = k^*$.

3.1.1 Privacy Analysis

It is not hard to show that RRTop-k is ε-DP.

Lemma 1. RRTop-k *is ε-DP.*

The privacy guarantee of RRWithPrior follows immediately from that of RRTop-k (Lemma 1) since our choice of k does not depend on the label y:

Corollary 2. RRWithPrior *is ε-DP.*

For learning with a LabelDP guarantee, we first use RRWithPrior to query a randomized label for each example of the training set, and then apply a general learning algorithm that is robust to random label noise to this dataset. Note that unlike DP-SGD [2] that makes new queries on the gradients in every training epoch, we query the randomized label *once* and reuse it in all the training epochs.

3.2 Optimality of RRWithPrior

In this section we will prove the optimality of RRWithPrior. For this, we will need additional notation. For any algorithm R that takes as input a label y and outputs a randomized label $\tilde{y}$, we let $\mathrm{Obj}_{\mathbf{p}}(\mathsf{R})$ denote the probability that the output label is equal to the input label y when y is distributed as $\mathbf{p}$; i.e., $\mathrm{Obj}_{\mathbf{p}}(\mathsf{R}) = \Pr_{y \sim \mathbf{p}}[\mathsf{R}(y) = y]$, where the distribution of $y \sim \mathbf{p}$ is $\Pr[y = i] = p_i$ for all $i \in [K]$.

The main result of this section is that, among all ε-DP algorithms, RRWithPrior maximizes $\mathrm{Obj}_{\mathbf{p}}(\mathsf{R})$, as stated more formally next.

Theorem 3. *Let $\mathbf{p}$ be any probability distribution on $[K]$ and R be any ε-DP algorithm. We have that*

$$\mathrm{Obj}_{\mathbf{p}}(\text{RRWithPrior}) \geq \mathrm{Obj}_{\mathbf{p}}(\mathsf{R}).$$

Before we proceed to the proof, we remark that our proof employs a linear program (LP) to characterize the optimal mechanisms; a generic form of such LPs has been used before in [40, 33]. However, these works focus on different problems (linear queries) and their results do not apply here.

Proof of Theorem 3. Consider any ε-DP algorithm R, and let $q_{\tilde{y}|y}$ denote $\Pr[\mathsf{R}(y) = \tilde{y}]$. Observe that $\mathrm{Obj}_{\mathbf{p}}(\mathsf{R}) = \sum_{y \in [k]} p_y \cdot q_{y|y}$.

Since $q_{\cdot|y}$ is a probability distribution, we must have that

$$\sum_{\tilde{y} \in [K]} q_{\tilde{y}|y} = 1, \forall y \in [K], \text{ and } q_{\tilde{y}|y} \geq 0, \forall \tilde{y}, y \in [K].$$

Finally, the ε-DP guarantee of R implies that

$$q_{\tilde{y}|y} \leq e^{\varepsilon} \cdot q_{\tilde{y}|y'} \qquad\qquad \forall \tilde{y}, y, y' \in [K].$$

148 Combining the above, $\mathrm{Obj}_{\mathbf{p}}(\mathtt{R})$ is upper-bounded by the optimum of the following linear program
149 (LP), which we refer to as LP1:

$$\max \qquad \sum_{y \in [k]} p_y \cdot q_{y|y}$$

$$\text{s.t.} \qquad q_{\tilde{y}|y} \le e^{\varepsilon} \cdot q_{\tilde{y}|y'} \qquad \forall \tilde{y}, y, y' \in [K], \qquad (2)$$

$$\sum_{\tilde{y} \in [K]} q_{\tilde{y}|y} = 1 \qquad \forall y \in [K], \qquad (3)$$

$$q_{\tilde{y}|y} \ge 0 \qquad \forall \tilde{y}, y \in [K].$$

150 Notice that constraints (2) and (3) together imply that:

$$q_{y|y} + e^{-\varepsilon} \cdot \sum_{\tilde{y} \in [K] \setminus \{y\}} q_{\tilde{y}|\tilde{y}} \le 1 \qquad \forall y \in [K].$$

151 In other words, the optimum of LP1 is at most the optimum of the following LP that we call LP2:

$$\max \qquad \sum_{y \in [k]} p_y \cdot q_{y|y}$$

$$\text{s.t.} \qquad q_{y|y} + e^{-\varepsilon} \cdot \sum_{\tilde{y} \in [K] \setminus \{y\}} q_{\tilde{y}|\tilde{y}} \le 1 \qquad \forall y \in [K], \qquad (4)$$

$$q_{y|y} \ge 0 \qquad \forall y \in [K]. \qquad (5)$$

152 An optimal solution to LP2 must be a vertex (aka extreme point) of the polytope defined by (4)
153 and (5). Recall that an extreme point of a K-dimensional polytope must satisfy K independent
154 constraints with equality. In our case, this means that one of the following occurs:

155 • Inequality (5) is satisfied with equality for all $y \in [K]$ resulting in the all-zero solution
156 (whose objective is zero), or,
157 • For some non-empty subset $Y \subseteq [K]$, inequality (4) is satisfied with equality for all $y \in Y$,
158 and inequality (5) is satisfied with equality for all $y \in [K] \setminus Y$. This results in

$$q_{y|y} = \begin{cases} \frac{e^{\varepsilon}}{e^{\varepsilon} + |Y| - 1} & \text{if } y \in Y, \\ 0 & \text{if } y \notin Y. \end{cases}$$

159 This yields an objective value of $\frac{e^{\varepsilon}}{e^{\varepsilon} + |Y| - 1} \cdot \sum_{y \in Y} p_y$.

160 In conclusion, we have that

$$\mathrm{Obj}_{\mathbf{p}}(\mathtt{R}) \le \max_{\emptyset \ne Y \subseteq [K]} \frac{e^{\varepsilon}}{e^{\varepsilon} + |Y| - 1} \cdot \sum_{y \in Y} p_y$$

$$= \max_{k \in [K]} \frac{e^{\varepsilon}}{e^{\varepsilon} + k - 1} \cdot \max_{Y \subseteq [K], |Y| = k} \sum_{y \in Y} p_y$$

$$= \max_{k \in [K]} \frac{e^{\varepsilon}}{e^{\varepsilon} + k - 1} \cdot \sum_{y \in Y_k} p_y = \max_{k \in [K]} w_k,$$

161 where the last two equalities follow from our definitions of Y_k and w_k. Notice that
162 $\mathrm{Obj}_{\mathbf{p}}(\mathtt{RRWithPrior}) = \max_{k \in [K]} w_k$. Thus, we get that $\mathrm{Obj}_{\mathbf{p}}(\mathtt{RRWithPrior}) \ge \mathrm{Obj}_{\mathbf{p}}(\mathtt{R})$ as de-
163 sired. □

4 Application of `RRWithPrior`: Multi-Stage Training

165 Our `RRWithPrior` algorithm requires publicly available priors, which could usually be obtained from
166 domain specific knowledge. In this section, we describe a training framework that bootstraps from a
167 uniform prior, and progressively learns refined priors via multi-stage training. This general framework
168 can be applied to arbitrary domains even when no public prior distributions are available.

169 Specifically, we assume that we have a training algorithm A that outputs a probabilistic classifier
170 which, on a given unlabeled sample $\mathbf{x}$, can assign a probability p_y to each class $y \in [K]$. We partition
171 our dataset into subsets $S^{(1)}, \ldots, S^{(T)}$, and we start with a trivial model $M^{(0)}$ that outputs equal
172 probabilities for all classes. At each stage $t \in [T]$, we use the most recent model $M^{(t-1)}$ to assign the
173 probabilities $(p_1, \ldots, p_K)$ for each sample $\mathbf{x}_i$ from $S^{(t)}$. Applying RRWithPrior with this prior on
174 the true label y_i, we get a randomized label $\tilde{y}_i$ for $\mathbf{x}_i$. We then use all the samples with randomized
175 labels obtained so far to train the model $M^{(t)}$.

176 The full description of our LP-MST ("Label Privacy Multi-Stage Training) method is presented in
177 Algorithm 3. We remark here that the partition $S^{(1)}, \ldots, S^{(T)}$ can be arbitrarily chosen, as long as it
178 does not depend on the labels $y_1, \ldots, y_n$. We also stress that the training algorithm A need *not* be
179 private. We use LP-1ST to denote our algorithm with one stage, LP-2ST to denote our algorithm with
180 two stages, and so on. We also note that LP-1ST is equivalent to using vanilla RR. The tth stage of a
181 multi-stage algorithm is denoted *stage-t*.

Algorithm 3 Multi-Stage Training (LP-MST)

Input: Dataset $S = \{(\mathbf{x}_1, y_1), \ldots, (\mathbf{x}_n, y_n)\}$
Parameters: Number T of stages, training algorithm A
  1. Partition S into $S^{(1)}, \ldots, S^{(T)}$
  2. Let $M^{(0)}$ be the trivial model that always assigns equal probability to each class.
  3. For $t = 1$ to T:
      (a) Let $\tilde{S}^{(t)} = \emptyset$.
      (b) For each $(\mathbf{x}_i, y_i) \in S^{(t)}$:
            i. Let $\mathbf{p} = (p_1, \ldots, p_K)$ be the probabilities predicted by $M^{(t)}$ on $\mathbf{x}_i$.
            ii. Let $\tilde{y}_i = \text{RRWithPrior}_{\mathbf{p}}(y_i)$.
            iii. Add $(\mathbf{x}_i, \tilde{y}_i)$ to $\tilde{S}^{(t)}$.
      (c) Let $M^{(t)}$ be the model resulting from training on $\tilde{S}^{(1)} \cup \cdots \cup \tilde{S}^{(t)}$ using A.
  4. Output $M^{(T)}$.

---

182 The privacy guarantee of LP-MST is given by the following:

183 **Observation 4.** *For any $\varepsilon > 0$, if RRWithPrior is ε-DP, then LP-MST is ε-LabelDP.*

184 *Proof.* We will in fact prove a stronger statement that the algorithm is ε-DP even when we output all
185 the T models $M^{(1)}, \ldots, M^{(T)}$ together with all the randomized labels $\tilde{y}_1, \ldots, \tilde{y}_n$. For any possible
186 output models $m^{(1)}, \ldots, m^{(T)}$ and output labels $z_1, \ldots, z_n$, we have

$$\Pr[M^{(1)} = m^{(1)}, \ldots, M^{(T)} = m^{(T)}, \tilde{y}_1 = z_1, \ldots, \tilde{y}_n = z_n]$$
$$= \prod_{t=1}^{T} \left(\Pr \left[M^{(t)} = m^{(t)} \middle| \bigwedge_{i \in S^{(1)} \cup \cdots \cup S^{(t)}} \tilde{y}_i = z_i \right] \cdot \prod_{i \in S^{(t)}} \Pr \left[\tilde{y}_i = z_i \middle| M^{(t-1)} = m^{(t-1)} \right] \right).$$

187 Consider any two datasets $\mathbf{D}, \mathbf{D}'$ that differ on a single user's label; suppose this user is j and that the
188 user belongs to partition $\ell \in [T]$. Then, the above expression for $\mathbf{D}$ and that for $\mathbf{D}'$ are the same in all
189 but one term: $\Pr \left[\tilde{y}_j = z_j \middle| M^{(\ell-1)} = m^{(\ell-1)} \right]$, which is the probability that $\text{RRWithPrior}_{m^{(\ell-1)}(x_i)}$
190 outputs z_i. Since RRWithPrior is ε-DP, we can conclude that the ratio between the two probabilities
191 are at most e^ε as desired. □

192 We stress that this observation holds because each sensitive label y_i is only used *once* in Line 3(b)ii of
193 Algorithm 3, as the dataset S is partitioned at the beginning of the algorithm. As a result, since each
194 stage is ε-LabelDP, the entire algorithm is also ε-LabelDP. This is known as (an adaptive version of
195 a) *parallel composition* [58].

5 Empirical Evaluation

197 We evaluate RRWithPrior on standard benchmark datasets that have been widely used in previous
198 works on differentially private machine learning. Specifically, in the first part, we study our general

Table 1: Test accuracy (%) on CIFAR-10. The baseline performances taken from previously published results correspond to (ε, δ)-DP with $\delta = 10^{-5}$. The star* indicates the use of CIFAR-100 pre-trained representations.

Algorithm	$\varepsilon = 1$	$\varepsilon = 2$	$\varepsilon = 3$	$\varepsilon = 4$	$\varepsilon = 6$	$\varepsilon = 8$	$\varepsilon = \infty$
`DP-SGD` w/ pre-train* [2]		67		70		73	80
`DP-SGD` [65]						$61.6_{(\varepsilon=7.53)}$	76.6
Tempered Sigmoid [65]						$66.2_{(\varepsilon=7.53)}$	
Yu et al. [80]					$44.3_{(\varepsilon=6.78)}$		
Nasr et al. [61]			55				
Chen and Lee [15]						53	
ScatterNet+CNN [76]			69.3				
`LP-1ST`	59.96	82.38	89.89	92.58	93.58	94.70	94.96
`LP-2ST`	63.67	86.05	92.19	93.37	94.26	94.52	-
`LP-1ST` w/ pre-train*	67.64	83.99	90.24	92.83	94.02	94.96	95.25
`LP-2ST` w/ pre-train*	70.16	87.22	92.12	93.53	94.41	94.59	-

Table 2: Experiments on CIFAR-100. The non-private baseline ($\varepsilon = \infty$) is 76.38% test accuracy.

Algorithm	$\varepsilon = 3$	$\varepsilon = 4$	$\varepsilon = 5$	$\varepsilon = 6$	$\varepsilon = 8$
`LP-1ST`	20.96	46.28	61.38	68.34	73.59
`LP-2ST`	28.74	50.15	63.51	70.58	74.14

multi-stage training algorithm that boostraps from a uniform prior. We evaluate it on image classification and collaborative filtering tasks. In the second part, we focus on image classification only and use domain-specific techniques to obtain priors for `RRWithPrior`. We use modern neural network architectures (e.g. ResNets [43]) and the mixup [82] regularization for learning with noisy labels. Please see the Supplementary Material for full details on the datasets and the experimental setup.

5.1 Evaluation with Multi-Stage Training

CIFAR-10 [52] is a 10-class image classification benchmark dataset. We evaluate our algorithm and compare it to previously reported DP baselines in Table 1. Due to scalability issues, previous DP algorithms could only use simplified architectures with non-private accuracy significantly below the state-of-the-art. Moreover, even when compared to those weaker non-private baselines, a large performance drop is observed in the private models. In contrast, we use ResNet18 with 95% non-private accuracy. Overall, our algorithms improve the previous state-of-the-art by a margin of 20% across all ε's. Abadi et al. [2] treated CIFAR-100 as public data and use it to pre-train a representation to boost the performance of `DP-SGD`. We also observe performance improvements with CIFAR-100 pre-training (Table 1, bottom 2 rows). But even without pre-training, our results are significantly better than `DP-SGD` even *with* pre-training.

In Table 2 we also show results on CIFAR-100, which is a more challenging CIFAR-10 variant due to the 10× more classes. To the best of our knowledge, these are the first non-trivial reported results on CIFAR-100 for DP learning. For $\varepsilon = 8$, our algorithm is only 2% below the non-private baseline.

In addition, we also evaluate on MovieLens-1M [41], which contains $1,000,209$ anonymous ratings of approximately $3,900$ movies, made by $6,040$ MovieLens users. Following [10], we randomly split the data into 80% train and 20% test, and show the test Root Mean Square Error (RMSE) in Table 3.

Table 3: Experiments on MovieLens-1M. The numbers show the test RMSE.

Algorithm	$\varepsilon = 1$	$\varepsilon = 2$	$\varepsilon = 3$	$\varepsilon = 4$	$\varepsilon = 8$	$\varepsilon = \infty$
`LP-1ST`	1.122	0.981	0.902	0.877	0.867	0.868
`LP-2ST`	1.034	0.928	0.891	0.874	0.865	
Gaussian DP [10]						$0.915\ (\varepsilon \geq 10)$

Figure 1: (a) Test accuracy (%) on various datasets with `LP-MST` for $T > 2$. The curve "CIFAR-10 w/ pre-train" is using CIFAR-100 as public data to pre-train the model. (b) `RRWithPrior` with priors obtained from histogram query based on clustering in various SSL representations.

Results on MNIST [53], Fashion MNIST [79], and KMNIST [20], and comparison to more baselines can be found in the Supplementary Material. In all the datasets we evaluated, our algorithms not only significantly outperform the previous methods, but also greatly shrink the performance gap between private and non-private models. The latter is critical for applications of deep learning systems in real-world tasks with privacy concerns.

Beyond Two Stages In Figure 1(a), we report results on `LP-MST` with $T > 2$. For the cases we tried, we consistently observe 1–2% improvements on test accuracy when going from `LP-2ST` to `LP-3ST`. In our preliminary experiments, going beyond $T > 4$ stages leads to diminishing returns on some datasets.

5.2 Evaluation with Domain-Specific Priors

The multi-stage training framework evaluated in the previous section is a general domain agnostic algorithm that bootstraps itself from uniform priors. In some cases, domain-specific priors can be obtained to further improve the learning performance. In this section, we focus on image classification applications, where new advances in self-supervised learning (SSL) [17, 18, 36, 45, 11] show that high-quality image representations could be learned on large image datasets without using the class labels. In the setting of `LabelDP`, the unlabeled images are considered public data, so we design an algorithm to use SSL to obtain priors, which is then fed to `RRWithPrior` for discriminative learning.

Specifically, we partition the training examples into groups by clustering using their representations extracted from SSL models. We then query a histogram of labels for each group via discrete Laplace mechanism (aka Geometric Mechanism) [33]. If the groups are largely homogeneous, consisting of mostly examples from the same class, then we can make the histogram queries with minimum privacy budget. The queried histograms are used as label priors for all the points in the group. Figure 1(b) shows the results on two different SSL representations: BYOL [36], trained on unlabeled CIFAR-10 images and DINO [11], trained on ImageNet [22] images. Comparing to the baseline, the SSL-based priors significantly improves the model performance with small privacy budgets. Note that since the SSL priors are not *true* priors, with large privacy budget ($\varepsilon = 8$), it actually underperforms the uniform prior. But in most real world applications, small ε's are generally more useful.

6 Theoretical Analysis

Previous works have shown that `LabelDP` can be provably easier than DP in certain settings; specifically, in the PAC learning setting, Beimel et al. [9] proved that finite VC dimension implies learnability by `LabelDP` algorithms, whereas it is known that this is not sufficient for DP algorithms [6].

We extend the theoretical understanding of this phenomenon to the stochastic convex optimization (SCO) setting. Specifically, we show that, by applying `RR` on the labels and running SGD on top of

254 the resulting noisy dataset with an appropriate debiasing of the noise, one can arrive at the following
255 *dimension-independent* excess population loss.

256 **Theorem 5** (Informal)**.** *For any* $\varepsilon \in (0, 1)$*, there is an* ε*-*LabelDP *algorithm for stochastic convex*
257 *optimization with excess population loss* $\tilde{O}\left(DL \cdot \frac{K}{\varepsilon\sqrt{n}}\right)$ *where* D *denotes the diameter of the*
258 *parameter space and* L *denotes the Lipschitz constant of the loss function.*

259 The above excess population loss can be compared to that of Bassily et al. [8], who gave an (ε, δ)-
260 DP algorithm with excess population loss $O_{D,L}\left(\frac{1}{\sqrt{n}} + \frac{\sqrt{p}}{\varepsilon n}\right)$ where p denote the dimension of the
261 parameter space; this bound is also known to be tight in the standard DP setting. The main advantage
262 of our guarantee in Theorem 5 is that it is independent of the dimension p. Furthermore, we show
263 that our bound is tight up to polylogarithmic factors and the dependency on the number of classes K.

264 The above result provides a theoretical evidence that running RR on the labels and then training
265 on this noisy dataset can be effective. We can further extend this to the setting where, instead of
266 running RR, we run RRTop-k before running the aforementioned (debiased) SGD, although—perhaps
267 as expected—our bound on the population loss now depends on the quality of the priors.

268 **Corollary 6** (Informal)**.** *Suppose that we are given a prior* $\mathbf{p}_x$ *for every* x *and let* Y_k^x *denote the*
269 *set of top-k labels with respect to* $\mathbf{p}_x$*. Then, for any* $\varepsilon \in (0, 1)$*, there is an* ε*-*LabelDP *algorithm for*
270 *stochastic convex optimization with excess population loss* $\tilde{O}\left(DL \cdot \left(\frac{k}{\varepsilon\sqrt{n}} + \Pr_{(x,y)\sim\mathcal{D}}[y \notin Y_k^x]\right)\right)$
271 *where* D, L *are as defined in Theorem 5 and* $\mathcal{D}$ *is the data distribution.*

272 When our top-k set is perfect (i.e., y always belongs to Y_k^x), the bound reduces to that of Theorem 5,
273 but with the smaller k instead of K. Moreover, the second term is, in some sense, a penalty we pay for
274 the inaccuracy of the top-k prior. We defer the formal treatment and the proofs to the Supplementary
275 Material, in which we also present additional generalization results for non-convex settings.

276 Note that Corollary 6 is not in the exact setup we run in experiments, where we dynamically calculate
277 an optimal k for each x given generic priors (via RRWithPrior), and for which the utility is much
278 more complicated to analyze mathematically. Nonetheless, the above corollary corroborates the
279 intuition that a good prior helps with training.

280 # 7 Conclusions and Future Directions

281 We introduced a novel algorithm RRWithPrior, and ap-
282 plied it to LabelDP problems. We showed that prior in-
283 formation can be incorporated to the randomized label
284 querying framework while maintaining privacy constraints.
285 We demonstrated two frameworks to apply RRWithPrior:
286 1) A general multi-stage training algorithm LP-MST that
287 bootstraps from uniform priors; 2) An algorithm that build
288 priors from clustering with self-supervised learning (SSL)
289 based representations. The former is general purpose and
290 can be applied to tasks even when no domain specific priors are available, while the latter use
291 domain specific algorithm to extract priors and perform well even with very small privacy budget.
292 As summarized by the figure on the right, in both cases, by focusing on LabelDP, our RRWithPrior
293 significantly improved the model performance of previous state-of-the-art DP models that aimed to
294 protect both the inputs and outputs. The narrowed performance gap between private and non-private
295 models is vital for adding DP to real world deep learning models.

296 Our work opens up several interesting questions. Firstly, note that our multi-stage training procedure
297 uses very different ingredients than those of Abadi et al. [2] (which employ DP-SGD, privacy amplifi-
298 cation by subsampling, and Renyi accounting); can these tools be used to further improve LabelDP?
299 Secondly, while our procedure can be implemented in the most stringent *local* DP setting[4] [50], can
300 it be improved in the weaker central (aka trusted curator) DP model, assuming the curator knows the
301 prior? Thirdly, while our algorithm achieves pure DP (i.e., $\delta = 0$), is higher accuracy possible for
302 approximate DP (i.e., $\delta > 0$)?

---

[4]They can in fact be implemented in the slightly weaker sequentially interactive local DP model [26].

References

[1] M. Abadi, A. Agarwal, P. Barham, E. Brevdo, Z. Chen, C. Citro, G. S. Corrado, A. Davis, J. Dean, M. Devin, S. Ghemawat, I. Goodfellow, A. Harp, G. Irving, M. Isard, Y. Jia, R. Jozefowicz, L. Kaiser, M. Kudlur, J. Levenberg, D. Mané, R. Monga, S. Moore, D. Murray, C. Olah, M. Schuster, J. Shlens, B. Steiner, I. Sutskever, K. Talwar, P. Tucker, V. Vanhoucke, V. Vasudevan, F. Viégas, O. Vinyals, P. Warden, M. Wattenberg, M. Wicke, Y. Yu, and X. Zheng. TensorFlow: Large-scale machine learning on heterogeneous systems, 2015. Software available from `tensorflow.org`.

[2] M. Abadi, A. Chu, I. Goodfellow, H. B. McMahan, I. Mironov, K. Talwar, and L. Zhang. Deep learning with differential privacy. In *CCS*, pages 308–318, 2016.

[3] J. M. Abowd. The US Census Bureau adopts differential privacy. In *KDD*, pages 2867–2867, 2018.

[4] J. Acharya, K. Bonawitz, P. Kairouz, D. Ramage, and Z. Sun. Context aware local differential privacy. In *ICML*, pages 52–62, 2020.

[5] A. Agarwal and I. Ganichev. Auto-vectorizing tensorflow graphs: Jacobians, auto-batching and beyond. *arXiv preprint arXiv:1903.04243*, 2019.

[6] N. Alon, R. Livni, M. Malliaris, and S. Moran. Private PAC learning implies finite littlestone dimension. In *STOC*, pages 852–860, 2019. doi: 10.1145/3313276.3316312. URL `https://doi.org/10.1145/3313276.3316312`.

[7] Apple Differential Privacy Team. Learning with privacy at scale. *Apple Machine Learning Journal*, 2017.

[8] R. Bassily, V. Feldman, K. Talwar, and A. G. Thakurta. Private stochastic convex optimization with optimal rates. In H. M. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. B. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada*, pages 11279–11288, 2019. URL `https://proceedings.neurips.cc/paper/2019/hash/3bd8fdb090f1f5eb66a00c84dbc5ad51-Abstract.html`.

[9] A. Beimel, K. Nissim, and U. Stemmer. Private learning and sanitization: Pure vs. approximate differential privacy. *ToC*, 12(1):1–61, 2016.

[10] Z. Bu, J. Dong, Q. Long, and W. J. Su. Deep learning with Gaussian differential privacy. *Harvard Data Science Review*, 2020(23), 2020.

[11] M. Caron, H. Touvron, I. Misra, H. Jégou, J. Mairal, P. Bojanowski, and A. Joulin. Emerging properties in self-supervised vision transformers. *arXiv preprint arXiv:2104.14294*, 2021.

[12] T. H. Chan, E. Shi, and D. Song. Optimal lower bound for differentially private multi-party aggregation. In *ESA*, pages 277–288, 2012.

[13] K. Chaudhuri and D. Hsu. Sample complexity bounds for differentially private learning. In *COLT*, pages 155–186, 2011.

[14] K. Chaudhuri, C. Monteleoni, and A. D. Sarwate. Differentially private empirical risk minimization. *JMLR*, 12(3), 2011.

[15] C. Chen and J. Lee. Stochastic adaptive line search for differentially private optimization. In *Big Data*, pages 1011–1020, 2020.

[16] P. Chen, B. Liao, G. Chen, and S. Zhang. Understanding and utilizing deep neural networks trained with noisy labels. In *ICML*, pages 1062–1070, 2019.

[17] T. Chen, S. Kornblith, M. Norouzi, and G. Hinton. A simple framework for contrastive learning of visual representations. In *ICML*, pages 1597–1607, 2020.

[18] T. Chen, S. Kornblith, K. Swersky, M. Norouzi, and G. Hinton. Big self-supervised models are strong semi-supervised learners. In *NeurIPS*, 2020.

[19] A. Cheu, A. Smith, J. Ullman, D. Zeber, and M. Zhilyaev. Distributed differential privacy via shuffling. In *EUROCRYPT*, pages 375–403, 2019.

[20] T. Clanuwat, M. Bober-Irizar, A. Kitamoto, A. Lamb, K. Yamamoto, and D. Ha. Deep learning for classical Japanese literature. *arXiv preprint:1812.01718*, 2018.

[21] F. Dangel, F. Kunstner, and P. Hennig. Backpack: Packing more into backprop. *arXiv preprint arXiv:1912.10985*, 2019.

[22] J. Deng, W. Dong, R. Socher, L.-J. Li, K. Li, and L. Fei-Fei. Imagenet: A large-scale hierarchical image database. In *CVPR*, pages 248–255, 2009.

[23] T. DeVries and G. W. Taylor. Improved regularization of convolutional neural networks with cutout. *arXiv preprint:1708.04552*, 2017.

[24] B. Ding, J. Kulkarni, and S. Yekhanin. Collecting telemetry data privately. In *NIPS*, pages 3571–3580, 2017.

[25] J. C. Duchi, M. I. Jordan, and M. J. Wainwright. Local privacy and minimax bounds: sharp rates for probability estimation. In *NIPS*, pages 1529–1537, 2013.

[26] J. C. Duchi, M. I. Jordan, and M. J. Wainwright. Minimax optimal procedures for locally private estimation. *JASA*, 113(521):182–201, 2018.

[27] C. Dwork and A. Roth. The algorithmic foundations of differential privacy. *Foundations and Trends in Theoretical Computer Science*, 9(3-4):211–407, 2014.

[28] C. Dwork, K. Kenthapadi, F. McSherry, I. Mironov, and M. Naor. Our data, ourselves: Privacy via distributed noise generation. In *EUROCRYPT*, pages 486–503, 2006.

[29] C. Dwork, F. McSherry, K. Nissim, and A. D. Smith. Calibrating noise to sensitivity in private data analysis. In *TCC*, pages 265–284, 2006.

[30] Ú. Erlingsson, V. Pihur, and A. Korolova. Rappor: Randomized aggregatable privacy-preserving ordinal response. In *CCS*, pages 1054–1067, 2014.

[31] Ú. Erlingsson, V. Feldman, I. Mironov, A. Raghunathan, K. Talwar, and A. Thakurta. Amplification by shuffling: From local to central differential privacy via anonymity. In *SODA*, pages 2468–2479, 2019.

[32] A. Evfimievski, J. Gehrke, and R. Srikant. Limiting privacy breaches in privacy preserving data mining. In *PODS*, pages 211–222, 2003.

[33] A. Ghosh, T. Roughgarden, and M. Sundararajan. Universally utility-maximizing privacy mechanisms. *SICOMP*, 41(6):1673–1693, 2012.

[34] I. Goodfellow. Efficient per-example gradient computations. *arXiv preprint arXiv:1510.01799*, 2015.

[35] A. Greenberg. Apple's "differential privacy" is about collecting your data – but not your data. *Wired, June*, 13, 2016.

[36] J.-B. Grill, F. Strub, F. Altché, C. Tallec, P. H. Richemond, E. Buchatskaya, C. Doersch, B. A. Pires, Z. D. Guo, M. G. Azar, et al. Bootstrap your own latent: A new approach to self-supervised learning. In *NeurIPS*, 2020.

[37] A. Gupta, K. Ligett, F. McSherry, A. Roth, and K. Talwar. Differentially private combinatorial optimization. In *SODA*, pages 1106–1125, 2010.

[38] B. Han, Q. Yao, X. Yu, G. Niu, M. Xu, W. Hu, I. Tsang, and M. Sugiyama. Co-teaching: Robust training of deep neural networks with extremely noisy labels. In *NeurIPS*, pages 8527–8537, 2018.

[39] B. Han, G. Niu, X. Yu, Q. Yao, M. Xu, I. W. Tsang, and M. Sugiyama. Sigua: Forgetting may make learning with noisy labels more robust. In *ICML*, pages 4006–4016, 2020.

[40] M. Hardt and K. Talwar. On the geometry of differential privacy. In L. J. Schulman, editor, *STOC*, pages 705–714, 2010.

[41] F. M. Harper and J. A. Konstan. The MovieLens datasets: History and context. *ACM Trans. Interact. Intell. Syst.*, 5(4), 2015.

[42] H. Harutyunyan, K. Reing, G. V. Steeg, and A. Galstyan. Improving generalization by controlling label-noise information in neural network weights. In *ICML*, pages 4071–4081, 2020.

[43] K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. In *CVPR*, pages 770–778, 2016.

[44] K. He, X. Zhang, S. Ren, and J. Sun. Identity mappings in deep residual networks. In *European conference on computer vision*, pages 630–645. Springer, 2016.

[45] K. He, H. Fan, Y. Wu, S. Xie, and R. Girshick. Momentum contrast for unsupervised visual representation learning. In *CVPR*, pages 9729–9738, 2020.

[46] X. He, L. Liao, H. Zhang, L. Nie, X. Hu, and T.-S. Chua. Neural collaborative filtering. In *WWW*, pages 173–182, 2017.

[47] W. Hu, Z. Li, and D. Yu. Simple and effective regularization methods for training on noisily labeled data with generalization guarantee. In *ICLR*, 2020.

[48] L. Jiang, D. Huang, M. Liu, and W. Yang. Beyond synthetic noise: Deep learning on controlled noisy labels. In *ICML*, pages 4804–4815, 2020.

[49] P. Kairouz, K. Bonawitz, and D. Ramage. Discrete distribution estimation under local privacy. In *ICML*, pages 2436–2444, 2016.

[50] S. P. Kasiviswanathan, H. K. Lee, K. Nissim, S. Raskhodnikova, and A. Smith. What can we learn privately? *SICOMP*, 40(3):793–826, 2011.

[51] D. Kifer, A. Smith, and A. Thakurta. Private convex empirical risk minimization and high-dimensional regression. In *COLT*, pages 25.1–25.40, 2012.

[52] A. Krizhevsky. Learning multiple layers of features from tiny images. Technical Report TR-2009, University of Toronto, 2009.

[53] Y. LeCun, L. Bottou, Y. Bengio, and P. Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

[54] T. Liu, G. Vietri, T. Steinke, J. Ullman, and Z. S. Wu. Leveraging public data for practical private query release. In *ICML*, 2021.

[55] M. Lukasik, S. Bhojanapalli, A. K. Menon, and S. Kumar. Does label smoothing mitigate label noise? In *ICML*, pages 6448–6458, 2020.

[56] X. Ma, H. Huang, Y. Wang, S. Romano, S. Erfani, and J. Bailey. Normalized loss functions for deep learning with noisy labels. In *ICML*, pages 6543–6553, 2020.

[57] H. B. McMahan, D. Ramage, K. Talwar, and L. Zhang. Learning differentially private recurrent language models. In *ICLR*, 2018.

[58] F. McSherry. Privacy integrated queries: an extensible platform for privacy-preserving data analysis. *CACM*, 53(9):89–97, 2010.

[59] A. K. Menon, A. S. Rawat, S. J. Reddi, and S. Kumar. Can gradient clipping mitigate label noise? In *ICLR*, 2019.

[60] M. Nalpas and S. Dutton. A more private way to measure ad conversions, the Event Conversion Measurement API, October 2020. https://web.dev/conversion-measurement/#how-this-api-preserves-user-privacy.

[61] M. Nasr, R. Shokri, et al. Improving deep learning with differential privacy using gradient encoding and denoising. *arXiv preprint arXiv:2007.11524*, 2020.

[62] D. T. Nguyen, C. K. Mummadi, T. P. N. Ngo, T. H. P. Nguyen, L. Beggel, and T. Brox. Self: Learning to filter noisy labels with self-ensembling. In *ICLR*, 2019.

[63] N. Papernot, M. Abadi, U. Erlingsson, I. Goodfellow, and K. Talwar. Semi-supervised knowledge transfer for deep learning from private training data. In *ICLR*, 2017.

[64] N. Papernot, S. Song, I. Mironov, A. Raghunathan, K. Talwar, and Ú. Erlingsson. Scalable private learning with PATE. In *ICLR*, 2018.

[65] N. Papernot, A. Thakurta, S. Song, S. Chien, and Ú. Erlingsson. Tempered sigmoid activations for deep learning with differential privacy. In *AAAI*, 2021.

[66] G. Pleiss, T. Zhang, E. R. Elenberg, and K. Q. Weinberger. Identifying mislabeled data using the area under the margin ranking. In *ICML*, 2020.

[67] C. Radebaugh and U. Erlingsson. Introducing TensorFlow Privacy: Learning with Differential Privacy for Training Data, March 2019. `blog.tensorflow.org`.

[68] S. Shankland. How Google tricks itself to protect Chrome user privacy. *CNET, October*, 2014.

[69] R. Shokri and V. Shmatikov. Privacy-preserving deep learning. In *CCS*, pages 1310–1321, 2015.

[70] H. Song, M. Kim, D. Park, and J.-G. Lee. Prestopping: How does early stopping help generalization against label noise? *arXiv preprint:1911.08059*, 2019.

[71] H. Song, M. Kim, D. Park, and J.-G. Lee. Learning from noisy labels with deep neural networks: A survey. *arXiv preprint:2007.08199*, 2020.

[72] S. Song, K. Chaudhuri, and A. D. Sarwate. Stochastic gradient descent with differentially private updates. In *GlobalSIP*, pages 245–248, 2013.

[73] P. Subramani, N. Vadivelu, and G. Kamath. Enabling fast differentially private sgd via just-in-time compilation and vectorization. In *PPML*, 2020.

[74] C. Szegedy, W. Liu, Y. Jia, P. Sermanet, S. Reed, D. Anguelov, D. Erhan, V. Vanhoucke, and A. Rabinovich. Going deeper with convolutions. In *CVPR*, pages 1–9, 2015.

[75] D. Testuggine and I. Mironov. PyTorch Differential Privacy Series Part 1: DP-SGD Algorithm Explained, August 2020. `medium.com`.

[76] F. Tramèr and D. Boneh. Differentially private learning needs better features (or much more data). In *International Conference on Learning Representations*, 2021.

[77] D. Wang and J. Xu. On sparse linear regression in the local differential privacy model. In *ICML*, pages 6628–6637, 2019.

[78] S. L. Warner. Randomized response: A survey technique for eliminating evasive answer bias. *JASA*, 60(309):63–69, 1965.

[79] H. Xiao, K. Rasul, and R. Vollgraf. Fashion-MNIST: a novel image dataset for benchmarking machine learning algorithms. *arXiv preprint: 1708.07747*, 2017.

[80] L. Yu, L. Liu, C. Pu, M. E. Gursoy, and S. Truex. Differentially private model publishing for deep learning. In *S & P*, pages 332–349, 2019.

[81] X. Yu, B. Han, J. Yao, G. Niu, I. W. Tsang, and M. Sugiyama. How does disagreement help generalization against label corruption? In *ICML*, pages 7164–7173, 2019.

[82] H. Zhang, M. Cisse, Y. N. Dauphin, and D. Lopez-Paz. mixup: Beyond empirical risk minimization. In *ICLR*, 2018.

[83] Z. Zhang and M. Sabuncu. Generalized cross entropy loss for training deep neural networks with noisy labels. In *NeurIPS*, pages 8778–8788, 2018.

[84] S. Zheng, P. Wu, A. Goswami, M. Goswami, D. Metaxas, and C. Chen. Error-bounded correction of noisy labels. In *ICML*, pages 11447–11457, 2020.