An Explanation of In-context Learning as Implicit Bayesian Inference

Abstract

Large pretrained language models such as GPT-3 have the surprising ability to do in-context learning, where the model learns to do a downstream task simply by conditioning on a prompt consisting of input-output examples. Without being explicitly pretrained to do so, the language model learns from these examples during its forward pass *without parameter updates* on "out-of-distribution" prompts. In-context learning is hard to characterize because of the large scale of the pretraining data. In this paper, we study the role of the pretraining distribution on the emergence of in-context learning. We show that in-context learning emerges via Bayesian inference when the pre-training distribution is a mixture of HMMs. We theoretically characterize when in-context learning occurs despite the distribution mismatch between prompts and pretraining data. In contrast to messy large-scale pretraining datasets needed for in-context learning in natural language, we generate a family of small-scale synthetic datasets (GINC) where Transformer and LSTM language models both exhibit in-context learning.

1 Introduction

Large language models such as GPT-3 (Brown et al., 2020; Lieber et al., 2021) are pretrained on massive text corpora to simply predict the next word given previous words. They demonstrate the surprising ability to do *in-context learning*, where a language model "learns" to do a downstream task simply by conditioning on a prompt containing input-output pairs. In-context learning in GPT-3 has achieved state-of-the-art results in the LAMBADA (Paperno et al., 2016) completion task and the TriviaQA closed book QA task (Joshi et al., 2017) (18% and 3% over previous SOTA (Brown et al., 2020)). For example, consider the task of predicting nationalities from names. A prompt (Figure 1) is constructed by concatenating "training" examples (e.g., "Albert Einstein was German") followed by a "test example" ("Marie Curie was"). The language model conditions on this prompt, presented as a contiguous sequence of examples, to make a prediction. In this example, GPT-3 places the largest probability on the correct output

$$p(\text{"Polish"} \,|\, \text{"Albert Einstein was German \textbackslash n Mahatma Gandhi was Indian \textbackslash n Marie Curie was"}).$$

seemingly by inferring the task (names to nationalities) from the examples. Intuigingly, GPT-3 was not explicitly pretrained to learn from examples and does not optimize any parameters on the downstream task. Given that the distribution of prompts are quite different from real text, how does in-context learning work? Our understanding is limited since (i) real pretraining data is messy and (ii) requires scaling up both the data and the model — in-context learning has not been observed for smaller models such as GPT-2 (Radford et al., 2019)).

In this paper, we introduce a simple pretraining distribution which gives rise to in-context learning. To generate a document, we first draw a latent concept θ, which parameterizes the transitions of a Hidden Markov Model (HMM), then sample a sequence of observations (tokens) from the HMM (see Figure 2). This latent variable structure is common in topic models such as LDA (Blei et al., 2003). We assume the language model fits this pretraining distribution exactly with enough data and expressivity, so that the question of in-context learning becomes characterizing the conditional distribution of completions given prompts $p(\text{output}|\text{prompt})$ under the pretraining distribution, where the prompt is generated from a prompt distribution p_{prompt}. The pretraining distribution marginalizes out the latent concepts (and HMM hidden states), so this conditional distribution is the *posterior predictive distribution*. Thus, in-context learning can be thought of as implicit Bayesian inference.

Ideally, the posterior predictive distribution should concentrate on the correct output as the number of in-context examples increases, but the main challenge is that prompts are not presented as a set of IID

Figure 1: **(Top)** The in-context prompt distribution first samples a latent prompt concept (e.g., names to nationalities), then generates independent examples conditioned on this shared prompt concept. Each prompt example consists of an input x (e.g., Albert Einstein was), an output token y (e.g., German), and a delimiter (e.g., newline) which separates examples. The color of the shaded region refers to the distribution the tokens are sampled from (pretraining→purple, prompt→blue). **(Bottom)** During in-context learning, the prompt is presented as a contiguous sequence rather than IID examples and are thus "out-of-distribution" to the language model. The model must infer the shared prompt concept to generate the correct answer to "Marie Curie was" (e.g., "Polish", not "a scientist".

examples but as a concatenated sequence (Figure 1). Thus, the prompts are from a different distribution than the pretraining distribution. The canonical asymptotic tool in Bayesian methods is the Bernstein-von Mises theorem (van der Vaart, 1998; Kleijn & van der Vaart, 2012; Gunst & Shcherbakova, 2008), which typially assumes that data is drawn from the same (pretraining) distribution and/or independent observations, both of which are not satisfied. However, we prove that in-context learning can emerge in the limit of infinite examples when the signal about the latent concept in each prompt example is larger than the error stemming from the mismatch between the pretraining and prompt distributions. Additionally, we prove that the in-context learning error can be bounded by a function of the length of each example—longer example sequences provide more signal on the latent concept.

As a companion to this theory, we created the **G**enerative **IN**-**C**ontext learning dataset (GINC), which is a small-scale synthetic dataset which we can use to study in-context learning without relying on large-scale, messy real-world data. We find that both Transformer (Vaswani et al., 2017) and LSTM (Hochreiter & Schmidhuber, 1997) language models trained on such datasets exhibit in-context learning. We verify intuitions from the theory, showing that the accuracy of in-context learning improves with the number of examples and example length. Ablations of the GINC dataset show that the mixture-over-concepts structure in the pretraining distribution is crucial to the emergence of in-context learning. The experiments also bring up open questions which go beyond our theory, which only studies the pretraining distribution. We find that scaling up the number of model parameters steadily improves the in-context accuracy despite achieving the same pretraining loss, showing that the inductive bias of scale may improve in-context learning beyond memorizing the training data better.

2 IN-CONTEXT LEARNING SETTING

Pretraining distribution.   In our framework, a latent concept θ from a family of concepts Θ defines a distribution over observed tokens o from a vocabulary $\mathcal{O}$. To generate a document, we first sample a concept from a prior over concepts $p(\theta)$ and then sample a sequence given the concept. We model the pretraining distribution as a mixture of token distributions described by latent concepts. Each pretraining document is a length T sequence:

$$p(o_1,...,o_T) = \int_{\theta \in \Theta} p(o_1,...,o_T|\theta)p(\theta)d\theta \tag{1}$$

In our theoretical analysis, we assume $p(o_1,...,o_T|\theta)$ is described by the distribution over observations from a Hidden Markov Model (HMM). The concept θ determines the transition probability matrix of the HMM hidden states $h_1,...,h_T$ from a hidden state set $\mathcal{H}$.

Prompt distribution.   We define the prompt distribution p_{prompt}, which generates a concatenated sequence of in-context examples. Each prompt is generated with respect to a *prompt concept* θ^*, which

is shared by all the examples. We take the prompt concept θ^* to be unique in this paper to simplify the notation of the prompt distribution p_{prompt}.

An in-context example is composed of an input token sequence x (e.g., Albert Einstein was) concatenated with an output token y (e.g., German). The prompt is a concatenation of n independent training examples and 1 test input x_{test}, where the goal is the predict the test output by predicting the next token. To separate the input and outputs of adjacent examples, each example is separated by a special delimiter token o^{delim}. The delimiter token is usually a token that can appear in a broad range of contexts during pretraining, such as a newline character. The i-th training example O_i is the concatenation of an input $x_i = O_i[1: k-1]$ (the first $k-1$ tokens of the example) with an output token $y_i = O_i[k]$ at the end generated as follows[1]:

1. Generate a start hidden state h_i^{start} from a *prompt start distribution* π_{prompt}.

2. Given h_i^{start}, generate the example sequence $O_i = [x_i, y_i]$ from $p(O_i | h_i^{\text{start}}, \theta^*)$, the *pretraining distribution* conditioned on a *prompt topic* θ^*.

The test example $x_{\text{test}} = x_{n+1}$ is sampled similarly, but without sampling the output. The resulting prompt sequence concatenates the training examples (denoted S_n) and test example (x_{test}) separated by delimiters:

$$[S_n, x_{\text{test}}] = [x_1, y_1, o^{\text{delim}}, x_2, y_2, o^{\text{delim}}, ..., x_n, y_n, o^{\text{delim}}, x_{\text{test}}] \sim p_{\text{prompt}} \qquad (2)$$

In-context predictor and task. For in-context learning, the output target y for each example x is sampled according to $p_{\text{prompt}}(y|x)$

$$y_{\text{test}} \sim p_{\text{prompt}}(y|x_{\text{test}}) = \mathbb{E}_{h_{\text{test}}^{\text{start}} \sim \pi_{\text{prompt}}(h_{\text{test}}^{\text{start}}|x_{\text{test}})}\left[p(y|x_{\text{test}}, h_{\text{test}}^{\text{start}}, \theta^*)\right]. \qquad (3)$$

where $h_{\text{test}}^{\text{start}}$ denotes the hidden state corresponding to the first token of x_{test} and $\pi_{\text{prompt}}(h_{\text{test}}^{\text{start}}|x_{\text{test}})$ is defined as $p_{\text{prompt}}(x_{\text{test}}|h_{\text{test}}^{\text{start}})\pi_{\text{prompt}}(h_{\text{test}}^{\text{start}})/p_{\text{prompt}}(x_{\text{test}})$. The target distribution differs from the pretraining distribution p on the distribution of $h_{\text{test}}^{\text{start}}$.

The central question is, when the number of examples goes to infinity, does the posterior predictive distribution of the pretraining distribution given the prompt concentrate on the correct output? Towards this, we study the in-context predictor $f_n(x_{\text{test}}) = \arg\max_y p(y|S_n, x_{\text{test}})$ and its expected 0-1 error:

$$L_{0\text{-}1}(f_n) = \mathbb{E}_{x_{\text{test}}, y_{\text{test}} \sim p_{\text{prompt}}}\left[\mathbf{1}[f_n(x_{\text{test}}) \neq y_{\text{test}}]\right]. \qquad (4)$$

2.1 ASSUMPTIONS

We detail the assumptions in our framework, including the structure of delimiters and regularity assumptions. We assume that there exists a subset of *delimiter hidden states* $\mathcal{D}$ which generates the special delimiter token o^{delim} deterministically.

Assumption 1 (Delimiter hidden states). *Let the delimiter hidden states $\mathcal{D}$ be a subset of $\mathcal{H}$. For any $h \in \mathcal{D}$ and θ, $p(o^{delim}|h, \theta) = 1$ and for any $h' \notin \mathcal{D}$, $p(o^{delim}|h, \theta) = 0$.*

Thus if we observe the special delimiter token o^{delim}, then the corresponding hidden state must be in $\mathcal{D}$. However, this does not reveal the particular hidden state in $\mathcal{D}$ or the latent prompt concept.

The delimiter token is usually a token that can appear in a broad range of contexts, such as a newline character that separates different examples in the prompt. The delimiter ideally does not distract from the examples — for example, an adversarial delimiter could look like part of the input x. To mitigate these scenarios, we assume that no delimiter (e.g., newline) is significantly more likely under one concept rather than another.

Assumption 2 (Bound on delimiter transitions). *For any delimiter state $h^{delim} \in \mathcal{D}$ and any hidden state $h \in \mathcal{H}$, the probability of transitioning to a delimiter hidden state under θ is upper bounded $p(h^{delim}|h, \theta) < c_1$ for any $\theta \in \Theta$, and is lower bounded $p(h^{delim}|h, \theta^*) > c_2$ for θ^*. Additionally, the start hidden state distribution over delimiters is uniform for all concepts θ: $p(h^{delim}|\theta) = \frac{1}{|\mathcal{D}|}$ for all $\theta \in \Theta$ and $h^{delim} \in \mathcal{D}$.*

---

[1]Example length k is fixed for simplicity, but in practice, it will vary — our analysis can be extended to variable k, but we leave this to future work.

We also assume the prompt concept θ^* is in the family Θ, which we take to be a broad set of concepts seen during pretraining.

Assumption 3 (Well-specification). *The prompt concept θ^* is in Θ.*

Even though the pretraining distribution is broad, the prompt is still out-of-distribution for the pretraining distribution since it concatenates independent examples.

Finally, if the prompt has zero probability under the prompt concept θ^*, then Bayesian inference will not be able to infer the prompt concept as in Section 3.1. The following are regularity assumptions which mainly ensure that the prompt is not zero probability under θ^*.

Assumption 4 (Regularity). *The pretraining distribution p satisfies: 1) Lower bound on transition probability for the prompt concept θ^*: for any pair of hidden states $h, h' \in \mathcal{H}$, $p(h|h', \theta^*) > c_3 > 0$. 2) All tokens can be emitted: for every symbol o, there is some hidden state $h \in \mathcal{H}$ such that $p(o|h, \theta^*) > c_4 > 0$. 3) The hidden state Markov chain for concept θ has stationary distribution π^θ over $\mathcal{H}$. 4)The prior $p(\theta)$ has support over the entire concept family Θ and is bounded above.*

We denote the stationary distribution conditioned on x to be $\pi^\theta(h|x) = (p(x|h,\theta)\pi^\theta(h))/p(x|\theta)$.

3 THEORETICAL ANALYSIS

We prove that in the limit of infinite examples, conditioning the pretraining distribution on the prompt infers the prompt concept to enable in-context learning provided that a *distinguishability* condition holds — the prompt concept θ^* is distinct enough from the other concepts in Θ (e.g., when Θ is a discrete set). In this case, the expected error is optimal. When this distinguishability condition does not hold, we show that the expected error still decreases with example length.

3.1 HIGH-LEVEL APPROACH

In-context learning in GPT-3 is often done with greedy decoding or nucleus sampling (Holtzman et al., 2020), which samples high probability completions. Following this practice, we analyze the most likely prediction over the *pretraining* distribution conditioned on the prompt, which is sampled from the *prompt* distribution. Our goal is to show that $\text{argmax}_y p(y|S_n, x_{\text{test}}) \to \text{argmax}_y p_{\text{prompt}}(y|x_{\text{test}})$ as the number of examples n goes to infinity.

In the following, assume that the prompt has non-zero probability under the pretraining distribution p given θ^*, meaning that $p(S_n, x_{\text{test}}|\theta^*) > 0$. We expand $p(y|S_n, x_{\text{test}})$ to analyze its limit:

$$
\begin{aligned}
p(y|S_n, x_{\text{test}}) &= \int_\theta p(y|S_n, x_{\text{test}}, \theta) p(\theta|S_n, x_{\text{test}}) d\theta \\
&\propto \int_\theta p(y|S_n, x_{\text{test}}, \theta) p(S_n, x_{\text{test}}|\theta) p(\theta) d\theta \quad \text{(Bayes' rule, drop the constant } \frac{1}{p(S_n, x_{\text{test}})}) \\
&= \int_\theta \sum_{h_{\text{test}}^{\text{start}} \in \mathcal{H}} p(y|x_{\text{test}}, h_{\text{test}}^{\text{start}}, \theta) p(h_{\text{test}}^{\text{start}}|S_n, x_{\text{test}}, \theta) \frac{p(S_n, x_{\text{test}}|\theta)}{p(S_n, x_{\text{test}}|\theta^*)} p(\theta) d\theta \quad (5) \\
&\qquad \text{(Divide by } p(S_n, x_{\text{test}}|\theta^*) \text{ (a constant), law of total prob, Markov property)} \\
&= \int_\theta \sum_{h_{\text{test}}^{\text{start}} \in \mathcal{H}} p(y|x_{\text{test}}, h_{\text{test}}^{\text{start}}, \theta) p(h_{\text{test}}^{\text{start}}|S_n, x_{\text{test}}, \theta) \exp(n \cdot r_n(\theta)) p(\theta) d\theta \quad (6)
\end{aligned}
$$

where $r_n(\theta) = \frac{1}{n} \log \frac{p(S_n, x_{\text{test}}|\theta)}{p(S_n, x_{\text{test}}|\theta^*)}$. In Theorem 1, we prove that under a distinguishability condition, $\exp(n \cdot r_n(\theta)) \to 0$ for all concepts θ except the prompt concept θ^*. Therefore, the only nonzero term in the integral is when $\theta = \theta^*$, where $\exp(n \cdot r_n(\theta)) = 1$. Thus, the prompt concept is "selected" as a consequence of Bayesian inference. Note that we can exchange limits and integrals here since probabilities are bounded (dominated convergence), assuming that the prior $p(\theta)$ is bounded. In Lemma 4, we show that the distribution of the hidden start state for the test example $p(h_{\text{test}}^{\text{start}}|S_n, x_{\text{test}}, \theta^*)$ converges to the stationary distribution $\pi^{\theta^*}(h_{\text{test}}^{\text{start}}|x_{\text{test}})$ conditioned on x_{test}. Putting these together with Equation 6, we have that the in-context predictor infers prompt concept θ^*:

$$
\underset{y}{\text{argmax}}\, p(y|S_n, x_{\text{test}}) \to \underset{y}{\text{argmax}}\, \mathbb{E}_{h_{\text{test}}^{\text{start}} \sim \pi^{\theta^*}(h_{\text{test}}^{\text{start}}|x_{\text{test}})}[p(y|x_{\text{test}}, h_{\text{test}}^{\text{start}}, \theta^*)] \quad (7)
$$

Recall that the test label is sampled from $p_{\text{prompt}}(y|x_{\text{test}}) = \mathbb{E}_{h_{\text{test}}^{\text{start}} \sim \pi_{\text{prompt}}(h_{\text{test}}^{\text{start}}|x_{\text{test}})}[p(y|x_{\text{test}}, h_{\text{test}}^{\text{start}}, \theta^*)]$. If the prompt start distribution π_{prompt} equals the stationary distribution π^{θ^*}, then the conditional state distributions $p_{\text{prompt}}(h_{\text{test}}^{\text{start}}|x_{\text{test}}) = \pi^{\theta^*}(h_{\text{test}}^{\text{start}}|x_{\text{test}})$ are the same between pretraining and prompting. Thus, the in-context predictor makes the optimal prediction when $\pi_{\text{prompt}} = \pi^{\theta^*}$.

3.2 HEURISTIC DERIVATION

Recall from Section 3.1 that if $\exp(n \cdot r_n(\theta)) \to 0$ for all $\theta \neq \theta^*$, then Bayesian inference "selects" the prompt concept through marginalization. To do this, we focus on showing that $r_n(\theta)$, the average log-likelihood ratio between θ and θ^*, converges to a negative constant, and thus nr_n converges to $-\infty$.

The main technical challenge is to handle the sequence-of-examples structure of the prompt, which makes all the examples dependent with respect to the pretraining distribution. Our approach uses properties of delimiter tokens to approximately factorize the examples, with constant error per example. We let $O_i^{\text{ex}} = [o_{i-1}^{\text{delim}}, O_i]$ be the i-th input-output pair and the previous delimiter together for $i > 1$ and define $O_1^{\text{ex}} = O_1$. Expanding the likelihood term inside $r_n(\theta)$, our goal is to show

$$p(S_n, x_{\text{test}}|\theta) = p(x_{\text{test}}|S_n, \theta)p(S_n|\theta) \approx \prod_{i=1}^{n} O(1)p(O_i|\theta) \tag{8}$$

To show this, we expand $p(S_n|\theta)$ with the chain rule, and with Assumption 4 (to bound $p(x_{\text{test}}|S_n, \theta)$ by $O(1)$) it can be shown that

$$p(x_{\text{test}}|S_n, \theta)p(S_n|\theta) \approx \prod_{i=1}^{n} O(1)p(O_i^{\text{ex}}|O_{1:i-1}^{\text{ex}}, \theta). \tag{9}$$

We then marginalize $p(O_i^{\text{ex}}|O_{1:i-1}^{\text{ex}}, \theta)$ over the hidden state h_{i-1}^{delim} corresponding to the delimiter in $O_i^{\text{ex}} = [o_{i-1}^{\text{delim}}, O_i]$:

$$\prod_{i=1}^{n} O(1)p(O_i^{\text{ex}}|O_{1:i-1}^{\text{ex}}, \theta) = \prod_{i=1}^{n} O(1) \sum_{h_{i-1}^{\text{delim}} \in \mathcal{D}} p(O_i|h_{i-1}^{\text{delim}}, \theta)p(h_{i-1}^{\text{delim}}|O_{1:i-1}^{\text{ex}}, \theta) \approx \prod_{i=1}^{n} O(1)p(O_i|\theta) \tag{10}$$

While summing over $\mathcal{H}$ would be a trivial equality, we can replace $\mathcal{H}$ with the set of delimiter hidden states $\mathcal{D}$ since $p(h_{i-1}^{\text{delim}}|O_{1:i-1}^{\text{ex}}, \theta) = 0$ for non-delimiter hidden states (Assumption 1). We used in the first equality that $O_{1:i-1}^{\text{ex}} \to h_{i-1}^{\text{delim}} \to O_i^{\text{ex}}$ forms a Markov chain and $p(o_{i-1}^{\text{delim}}|h_{i-1}^{\text{delim}}) = 1$ (Assumption 1) to change O_i^{ex} to O_i. Finally, we can show using properties of delimiter hidden states (Assumption 2) that $p(h_{i-1}^{\text{delim}}|O_{1:i-1}^{\text{ex}}, \theta) \approx O(1)p(h_{i-1}^{\text{delim}}|\theta)$, which allows us to marginalize out h_{i-1}^{delim}. Therefore, we can upper bound $r_n(\theta)$ as

$$r_n(\theta) \leq \frac{1}{n}\left(O(n) + \sum_{i=1}^{n}\log\frac{p(O_i|\theta)}{p(O_i|\theta^*)}\right) \to O(1) + \mathbb{E}_{O \sim p_{\text{prompt}}}\left[\log\frac{p(O|\theta)}{p(O|\theta^*)}\right]. \tag{11}$$

Since all the tokens after the starting token in an example O are drawn from the pretraining distribution p, the expectation becomes a negative KL divergence for tokens 2 through k. Intuitively, there are $O(k)$ KL terms (for each token in the example) and only $O(1)$ other error terms, which come from the distribution mismatch between the prompt and pretraining distributions. If k is large enough so that the KL terms are larger than the error terms, then $r_n(\theta)$ has a negative limit. If this holds for all $\theta \neq \theta^*$, then we have $\exp(n \cdot r_n(\theta)) \to 0$ for all $\theta \neq \theta^*$, enabling in-context learning.

3.3 FORMAL RESULTS

3.3.1 IN-CONTEXT LEARNING UNDER DISTINGUISHABILITY

We define a distinguishability condition which formalizes when in-context learning occurs. Letting p_θ^j be the output distribution of the j-th token given the previous tokens, the condition depends on KL divergence between $p_{\theta^*}^j$ and p_θ^j as well as error terms $\epsilon_{\text{start}}^\theta$ and $\epsilon_{\text{delim}}^\theta$ coming from the distribution mismatch between the prompt and pretraining distributions at the start and delimiter token for each example:

$$p_\theta^j(o) = p(O[j] = o|O[1:j-1], \theta), \quad KL_j(\theta^*\|\theta) = \mathbb{E}_{O[1:j-1] \sim p_{\text{prompt}}}[KL(p_{\theta^*}^j\|p_\theta^j)] \tag{12}$$

$$\epsilon_{\text{start}}^\theta = \mathbb{E}_{O[1] \sim p_{\text{prompt}}}\left[\log\frac{p(O[1]|\theta)}{p(O[1]|\theta^*)}\right], \quad \epsilon_{\text{delim}}^\theta = (\log(c_1) - \log(c_2)). \tag{13}$$

Condition 1 (Distinguishability). *We define θ^* to be distinguishable if for all $\theta \in \Theta, \theta \neq \theta^*$,*

$$\sum_{j=2}^{k} KL_j(\theta^* \| \theta) > \epsilon_{start}^{\theta} + \epsilon_{delim}^{\theta}. \tag{14}$$

This condition operates on the level of one example. When the signal from the KL divergence (LHS) is larger than the error terms, Equation 14 is satisfied. For longer example lengths k, the LHS increases and the condition is more likely satisfied. Intuitively, longer example lengths increases the proportion of the prompt sampled from the pretraining distribution. Under the distinguishability condition, we show that the in-context predictor achieves the optimal expected error as the number of examples increases.

Theorem 1. *Assume the assumptions in Section 2.1 hold. If Condition 1 holds, then as $n \to \infty$ the prediction according to the pretraining distribution is*

$$\underset{y}{\mathrm{argmax}}\, p(y|S_n, x_{test}) \to \underset{y}{\mathrm{argmax}}\, \mathbb{E}_{h_{test}^{start} \sim \pi^{\theta^*}(h_{test}^{start}|x_{test})}[p(y|x_{test}, h_{test}^{start}, \theta^*)]. \tag{15}$$

As a corollary, if the prompt start distribution π_{prompt} is the stationary distribution π^{θ^*} of the hidden state chain for θ^*, then the in-context predictor f_n achieves the optimal expected 0-1 error:

$$\lim_{n \to \infty} L_{0\text{-}1}(f_n) = \inf_{f} L_{0\text{-}1}(f). \tag{16}$$

When the prompt start distribution π_{prompt} matches the hidden state stationary distribution π^{θ^*}, the in-context predictor achieves the optimal error by predicting the most likely token from the same distribution of the test example (Equation 3). When this is not true, there may be additional distribution shift.

3.3.2 NON-DISTINGUISHABLE CASE

Even when the distinguishability condition does not hold, can we give an error guarantee? Note that Condition 1 fails when there is some $\theta \neq \theta^*$ for which the KL between θ and θ^* is less than the error terms. However, this means that the output distributions of θ and θ^* are close in KL. We leverage this to prove that the expected 0-1 error decreases with the example length k under two different settings.

Continuity. Our first result relies on a continuity assumption between the concept parameter and its corresponding output distribution. Our assumption is based on prior works (Kleijn & van der Vaart, 2012), where the KL divergence is assumed to have a 2nd-order Taylor expansion.

Theorem 2. *Let the set of θ which does not satisfy Equation 14 in Condition 1 to be $\mathcal{B}$ and assume $\pi_{prompt} = \pi^{\theta^*}$. Assume that KL divergences have a 2nd-order Taylor expansion around θ^*[2]:*

$$\forall j, \ KL_j(\theta^* \| \theta) = \frac{1}{2}(\theta - \theta^*)^{\top} I_{j,\theta^*}(\theta - \theta^*) + O(\|\theta - \theta^*\|^3) \tag{17}$$

where I_{j,θ^*} is the Fisher information matrix of the j-th token distribution with respect to θ^*. Let $\gamma_{\theta^*} = \frac{\max_j \lambda_{max}(I_{j,\theta^*})}{\min_j \lambda_{min}(I_{j,\theta^*})}$ where $\lambda_{max}, \lambda_{min}$ return the largest and smallest eigenvalues. Then as $n \to \infty$, the 0-1 risk of the in-context learning predictor f_n is bounded as

$$\lim_{n \to \infty} L_{0\text{-}1}(f_n) \leq \inf_{f} L_{0\text{-}1}(f) + g^{-1}\left(O\left(\frac{\gamma_{\theta^*} \sup_{\theta \in \mathcal{B}}(\epsilon_{start}^{\theta} + \epsilon_{delim}^{\theta})}{(k-1)}\right)\right) \tag{18}$$

where $g(\delta) = \frac{1}{2}((1 - \delta)\log(1 - \delta) + (1 + \delta)\log(1 + \delta))$ is a calibration function for the multiclass logistic loss for $\delta \in [0, 1)$.

We note that the inverse calibration function g^{-1} is roughly linear in ϵ for $\epsilon \leq 0.7$, so the excess risk roughly decreases as $O(1/k)$. When the "worst-case condition number" γ_{θ^*} of the Fisher information matrices is smaller (well-conditioned), the error decreases. Intuitively, this means that there is no direction to vary θ^* in which the output distribution will sharply change. As a consequence, the concepts θ in $\mathcal{B}$ that are not distinguishable (via Equation 14) from the prompt concept θ^* parameterize distributions that produce similar outputs to the prompt concept and thus achieve a small error.

---

[2]This requires the KL divergence to be twice differentiable.

Figure 2: The GINC dataset generates sequences from a mixture of HMMs. The HMM hidden states consist of entities (v) and properties (s), which index into a memory matrix to produce the observed token. The entity and property sequences are sampled from independent Markov chains. The concept parameter θ is the transition matrix for properties, which defines relations between properties. In this example, the sequence of properties [2,3,5,4] relates names to nationalities, defining the in-context task.

Varying-length test examples. In the setting where the length of x_{test} is random (uniformly from 2 to k), we can give a similar error guarantee without the continuity assumption from Theorem 2.

Theorem 3. *Let the set of θ which does not satisfy Equation 14 in Condition 1 to be $\mathcal{B}$ and assume $\pi_{prompt} = \pi^{\theta^*}$. Let the length of the test example x_{test} be uniformly distributed between 2 and k, for $k \geq 2$. As $n \to \infty$, the 0-1 risk of the in-context learning predictor f_n is bounded as*

$$\lim_{n \to \infty} L_{\text{0-1}}(f_n) \leq \inf_f L_{\text{0-1}}(f) + g^{-1}\left(\frac{\sup_{\theta \in \mathcal{B}}(\epsilon_{start}^\theta + \epsilon_{delim}^\theta)}{k-1}\right). \tag{19}$$

Here, instead of measuring only the prediction error of the k-th token, we measure the prediction error of the 2nd to k-th token uniformly, allowing us to spread out the error across the positions. However, in this setting there is mismatch between train and test where training examples are consistently length k but test examples have random length. We leave bridging this mismatch to future work.

4 SIMULATIONS

We generate the GINC dataset from a mixture of HMMs and show that Transformers (Vaswani et al., 2017) and LSTMs (Hochreiter & Schmidhuber, 1997) trained on this dataset exhibit in-context learning.

4.1 GINC DATASET

4.1.1 PRETRAINING DATASET

We consider a pretraining distribution from a mixture of HMMs with an interpretable hidden state structure and emission distribution (see AppendixF for details). The HMM hidden state $h_t = [s_t, v_t]$ at time t is composed of an *entity* $v_t \in \{1, ..., |\mathcal{V}|\}$ (e.g., Einstein) and a *property* $s_t \in \{1, ..., |\mathcal{S}|\}$ (e.g., nationality, first name, last name, other grammatical tokens). We model the entities and properties as independent Markov chains (i.e., a factorial HMM (Ghahramani & Jordan, 1997)), while the emissions depend on both. In pretraining documents, we expect that the entities (e.g., Einstein) change slowly over time while and the properties of the entity (e.g., their nationality) change quickly with some pattern to generate natural sentences. We implement this by ensuring that the probability of transitioning to the same entity index in the next step is at least 0.9. The emission distribution depends on a memory matrix M with $|\mathcal{V}|$ rows and $|\mathcal{S}|$ columns (Figure 2). At step t, we use the entity v_t and property s_t to index into the memory matrix. In particular, the observed tokens are deterministic with $p(o_t|h_t) = 1$ if $o_t = M[v_t, s_t]$.

Concept parameter. The concept parameter is the property transition matrix, which controls what properties are related in the sequence and the in-context task — one concept may relate names and nationalities (Figure 2), while another concept may relate names to birthplaces. The entity transition matrix is the same for all concepts. In our experiments, we define a mixture of HMMs with a uniform prior over 5 concepts to generate 1000 documents with about 1̃0 million tokens total.

Figure 3: In-context accuracy (95% intervals) of Transformers (left) and LSTMs (right) on the GINC dataset. Accuracy increases with number of examples n and length of each example k.

Figure 4: Ablation studies for 4 layer Transformers on the GINC dataset with vocab size 50. **(Left)** When pretrained with only one concept, in-context learning fails. **(Middle)** When the pretraining data has random transitions, the model sees all token transitions but in-context learning fails. **(Right)** When prompt concepts are out-of-distribution (and the model is pretrained normally), in-context learning fails.

4.1.2 PROMPT DISTRIBUTION

We generate prompts according to the theoretical setup, where we first sample a concept θ uniformly at random, then use it to generate all the examples in the prompt. The prompt start distribution is chosen to be uniform over entities but with a fixed starting property that is chosen randomly for each prompt, for consistency in the task. We generate prompts with 0 to 64 training examples and example lengths $k = \{3, 5, 8, 10\}$ (2500 prompts for each setting). The target token y_{test} is taken to be the most likely output $\arg\max_y p_{\text{prompt}}(y | x_{\text{test}})$ instead of being sampled to reduce the intrinsic error of the task.

4.2 SIMULATION RESULTS

We train GPT-2-based Transformer (Radford et al., 2019) and LSTM language models on three versions of the GINC dataset with vocabulary sizes 50, 100, and 150, then evaluate the in-context accuracy (see Appendix F.2, F.3) for model details). We average all results over 5 different pretraining runs. Figure 3 shows that for both Transformer and LSTMs, in-context accuracy improves as the number of prompt examples (n) and the example length (k) increase, verifying our theory.

Ablations and out-of-distribution concepts. We ablate the role of the mixture-of-concepts structure in GINC. In Figure 4 (left), we pretrain a 4 layer Transformer on data with only one concept (removing the prior) from Θ, resulting in in-context accuracy curves that do not increase with the number of examples. Figure 4 (middle) shows that when pretraining on random data, which contains all possible transitions between tokens, in-context learning also fails. Therefore, the mixture-of-concepts structure is important to in-context learning and simply seeing a diverse set of token transitions does not enable in-context learning. Finally, we test a 4 layer Transformer pretrained on GINC on randomly generated concepts that are not in the pretraining family of concepts. We generate 5 additional concepts and use these to generate prompts. Figure 4 (right) shows that in-context learning also fails for these concepts.

Effect of model size and inductive bias. Figure 5 shows that increasing the size of the Transformer (4, 12, 16 layers) steadily increases the in-context accuracy, corroborating the results of Brown et al. (2020). Table 6 shows that even though larger Transformers may have the same pretraining loss (e.g., 12 and 16 layer Transformers both get 1.33 validation loss for vocab size 50), the in-context accuracy still improves (81% to 85% from 12 to 16 layers), suggesting that the inductive bias of scale can improve in-context learning beyond increasing the capacity for memorization. Finally, the model architecture also plays a role — LSTMs consistently outperform Transformers on GINC despite having

Figure 5: In-context accuracy (95% intervals) of Transformers improves as model size increases on the GINC dataset for vocabulary sizes 50, 100, and 150.

Model	# Params	Train loss (pretraining)	Val loss (pretraining)	In-context Acc
Vocab size 50, $k=10, n=64$				
Transformer (4 layer)	29M	1.49	1.50	60.2 ± 5.7
Transformer (12 layer)	85M	1.31	1.33	81.2 ± 7.1
Transformer (16 layer)	115M	1.31	1.33	84.7 ± 3.4
LSTM	28M	1.31	1.35	95.8 ± 1.11
Vocab size 100, $k=10, n=64$				
Transformer (4 layer)	29M	1.58	1.59	67.4 ± 4.7
Transformer (12 layer)	85M	1.40	1.42	84.6 ± 3.0
Transformer (16 layer)	115M	1.41	1.43	88.7 ± 1.6
LSTM	28M	1.43	1.44	95.8 ± 1.54
Vocab size 150, $k=10, n=64$				
Transformer (4 layer)	29M	1.44	1.45	92.8 ± 1.9
Transformer (12 layer)	85M	1.27	1.28	98.4 ± 0.4
Transformer (16 layer)	115M	1.27	1.28	98.1 ± 0.5
LSTM	28M	1.26	1.31	99.2 ± 1.06

Figure 6: In-context accuracies (95% intervals) on GINC with vocab sizes (50, 100, 150) for Transformers and LSTMs. Accuracy improves with scale even though the pretraining loss may be the same.

fewer parameters, perhaps due to the similarity between HMMs and LSTMs. We leave analysis of the effect of model architecture and the inductive bias of scaling as an open question.

5 DISCUSSION AND RELATED WORK

Learning via Bayesian inference and misspecification. The Bernstein-von Mises theorem (van der Vaart, 1998) states that under some conditions, the posterior distribution of a parameter in a Bayesian parametric model is asymptotically normal and centered on the MLE. However, this does not apply for in-context learning since the prompt examples are not presented as independent samples but as one contiguous sequence. We also focus on the posterior predictive distribution rather than the parameter. Gunst & Shcherbakova (2008) show a Bernstein-von Mises-type result for observations from an HMM, but do not handle observations from a different distribution. However, we hope to show more precise asymptotic results in the future about the posterior distribution and give results under misspecification (Kleijn & van der Vaart, 2012).

Topic models. Topic models such as LDA (Blei et al., 2003) also use mixture models of text, but learning is typically done through algorithms such as Expectation-Maximization (Dempster et al., 1977), variational inference (Jordan et al., 1999), or MCMC (Metropolis et al., 1953; Hastings, 1970). Since in-context learning occurs as a byproduct of a forward pass, we focus on learning as a natural result of marginalization in Bayesian inference without an explicit inference algorithm.

Modeling the pretraining distribution with HMMs. Wei et al. (2021a) also use an HMM (although not a mixture of HMMs) in their generative model of the pre-training distribution for theoretical analysis. However, their goal is different – they analyze how pre-trained representations can be adapted for downstream tasks through linear probing rather than in-context learning.

Bridging the mismatch between pretraining and prompting. Prior work shows that finetuning language models on text with a prompting format improves its zero-shot performance (Wei et al., 2021b). Relatedly, Gao et al. (2021) optimize prompt templates for few-shot finetuning with respect to likelihood under a T5 model (Raffel et al., 2019). Zhao et al. (2021) improving in-context accuracy via calibration, a form of adaptation to the prompt distribution. These methods support our theoretical intuitions that reducing the prompt distribution mismatch would improve in-context learning.

Meta-learning. Meta-learning methods that train a sequence model to learn from examples (Ravi & Larochelle, 2017) also performs learning during the forward pass of a model. However, meta-learning models are trained to learn, while in-context learning emerges from language model pretraining.

6 CONCLUSION

We cast in-context learning as implicit Bayesian inference, where the pretrained language model implicitly infers a concept when making a prediction. We show both theoretically and experimentally that in-context learning occurs when the pre-training distribution is a mixture of HMMs. Our work provides a first step towards understanding in-context learning, which we hope will provide insight for improving pretraining and prompting.

7 ETHICS STATEMENT

Since the datasets in this paper are synthetically generated, there are no privacy/security issues to report. We investigate the emergent behaviors in large models, which will ultimately require careful consideration of environmental factors (energy usage), bias stemming from pretraining data, and others.

8 REPRODUCIBILITY STATEMENT

The source code for the experiments are included as a supplementary material. Proofs for theoretical results are included in the appendix, and assumptions are in Section 2.1. The datasets used in the experiments can be generated from the supplementary code. The experimental results are averaged over 5 seeds and 95% intervals are reported.

REFERENCES

D. Blei, Andrew Ng, and M. I. Jordan. Latent Dirichlet allocation. *Journal of Machine Learning Research (JMLR)*, 3:993–1022, 2003.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. *arXiv preprint arXiv:2005.14165*, 2020.

A. P. Dempster, Laird N. M., and Rubin D. B. Maximum likelihood from incomplete data via the EM algorithm. *Journal of the Royal Statistical Society: Series B*, 39(1):1–38, 1977.

Tianyu Gao, Adam Fisch, and Danqi Chen. Making pre-trained language models better few-shot learners. *arXiv*, 2021.

Zoubin Ghahramani and Michael Jordan. Factorial hidden Markov models. *Machine Learning*, 29: 245–273, 1997.

M. Gunst and O. Shcherbakova. Asymptotic behavior of bayes estimators for hidden markov models with application to ion channels. *Mathematical Methods of Statistics*, 17:342–356, 2008.

Keith W. Hastings. Monte Carlo sampling methods using Markov chains and their applications. *Biometrika*, 57(1):97–109, 1970.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural Computation*, 9(8): 1735–1780, 1997.

Ari Holtzman, Jan Buys, Li Du, Maxwell Forbes, and Yejin Choi. The curious case of neural text degeneration. In *International Conference on Learning Representations (ICLR)*, 2020.

Michael I. Jordan, Zoubin Ghahramani, Tommi S. Jaakkola, and Lawrence K. Saul. An introduction to variational methods for graphical models. *Machine Learning*, 37:183–233, 1999.

Mandar Joshi, Eunsol Choi, Daniel Weld, and Luke Zettlemoyer. TriviaQA: A large scale distantly supervised challenge dataset for reading comprehension. In *Association for Computational Linguistics (ACL)*, 2017.

Diederik Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *International Conference on Learning Representations (ICLR)*, 2015.

B.J.K. Kleijn and A.W. van der Vaart. The Bernstein-von mises theorem under misspecification. *Electronic Journal of Statistics*, 6, 2012.

Opher Lieber, Or Sharir, Barak Lenz, and Yoav Shoham. Jurassic-1: Technical details and evaluation. Technical report, AI21 Labs, August 2021.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. In *International Conference on Learning Representations (ICLR)*, 2019.

Nicholas Metropolis, Arianna W. Rosenbluth, Marshall N. Rosenbluth, Augusta H. Teller, and Edward Teller. Equation of state calculations by fast computing machines. *The journal of chemical physics*, 21(6):1087–1092, 1953.

Denis Paperno, German Kruszewski, Angeliki Lazaridou, Quan Ngoc Pham, Raffaella Bernardi, Sandro Pezzelle, Marco Baroni, Gemma Boleda, and Raquel Fernandez. The LAMBADA dataset: Word prediction requiring a broad discourse context. In *Association for Computational Linguistics (ACL)*, 2016.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. Language models are unsupervised multitask learners. *OpenAI Blog*, 1(8), 2019.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *arXiv preprint arXiv:1910.10683*, 2019.

Sachin Ravi and Hugo Larochelle. Optimization as a model for few-shot learning. In *International Conference on Learning Representations (ICLR)*, 2017.

Ingo Steinwart. How to compare different loss functions and their risks. *Constructive Approximation*, 26, 2007.

A. W. van der Vaart. *Asymptotic statistics*. Cambridge University Press, 1998.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. *arXiv preprint arXiv:1706.03762*, 2017.

Colin Wei, Sang Michael Xie, and Tengyu Ma. Why do pretrained language models help in downstream tasks? an analysis of head and prompt tuning. *arXiv*, 2021a.

Jason Wei, Maarten Bosma, Vincent Y. Zhao, Kelvin Guu, Adams Wei Yu, Brian Lester, Nan Du, Andrew M. Dai, and Quoc V. Le. Finetuned language models are zero-shot learners. *arXiv*, 2021b.

Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, R'emi Louf, Morgan Funtowicz, and Jamie Brew. HuggingFace's transformers: State-of-the-art natural language processing. *arXiv preprint arXiv:1910.03771*, 2019.

Tony Z. Zhao, Eric Wallace, Shi Feng, Dan Klein, and Sameer Singh. Calibrate before use: Improving few-shot performance of language models. In *International Conference on Machine Learning (ICML)*, 2021.

Bernardo Ávila Pires and Csaba Szepesvári. Multiclass classification calibration functions. *arXiv*, 2016.

A   FRAMEWORK DETAILS

In-context prompt distribution   For in-context learning, we sample a prompt from a new distribution p_{prompt}, which consists of n independent training examples and 1 test example. We first sample n hidden segments H of length k by sampling the first element $h^{\text{start}} = H[1]$ from a prompt start distribution π_{prompt}. Then, we sample the rest of the segment $H^{\text{seg}} = H[2:k]$ from the hidden transition distribution of the pretraining distribution p corresponding to a particular concept θ^*:

$$H_1,...,H_n, \quad H_i = [h_{i,1},...,h_{i,k}] \tag{20}$$

$$h_i^{\text{start}} = H_i[1] \sim \pi_{\text{prompt}}, \quad H_i^{\text{seg}} = H_i[2:k] \sim p(H_i^{\text{seg}}|h^{\text{start}},\theta^*). \tag{21}$$

To end each example (except the test example), we sample n delimiters $h^{\text{delim}} \in \mathcal{D}$ from $p_{\text{prompt}}^{\text{delim}}$:

$$h_1^{\text{delim}},...,h_n^{\text{delim}}, \quad h_i^{\text{delim}} \sim p_{\text{prompt}}^{\text{delim}}. \tag{22}$$

Conditioned on hidden variables H_i and h_i^{delim}, we sample the observed tokens $O_i = [o_{i,1},...,o_{i,k}]$ and o_i^{delim} respectively from the pre-training distribution:

$$O_1,...,O_n, \quad O_i \sim p(O_i|H_i) \tag{23}$$

$$o_1^{\text{delim}},...,o_n^{\text{delim}}, \quad o_i^{\text{delim}} \sim p(o_i^{\text{delim}}|h_i^{\text{delim}},\theta^*) \tag{24}$$

The "input" for each example is $x_i = O_i[1:k-1]$ and the "output" is $y_i = O_i[k]$. Taking S to be the sequence of training examples (without the test example), the resulting prompt sequence is

$$[S_n, x_{\text{test}}] = [O_1, o_1^{\text{delim}}, ..., O_n, o_n^{\text{delim}}, x_{\text{test}}] = [x_1, y_1, o_1^{\text{delim}}, x_2, y_2, o_2^{\text{delim}}, ..., x_n, y_n, o_n^{\text{delim}}, x_{\text{test}}] \sim p_{\text{prompt}} \tag{25}$$

where $x_{\text{test}} = x_{n+1} = O_{n+1}[1:k-1]$ is sampled via the same process but with $k-1$ elements.

B   BOUNDS ON PROBABILITIES FOR THEOREM 1

The following propositions, which lower bound the probability of a delimiter token and probability of an example under θ^*, are direct corollaries of the assumptions.

Proposition 1. *For all i, we have $p(h_i^{delim}|O_1, o_1^{delim}, ..., O_i, \theta^*) > c_2$ and $p(h_i^{delim}|O_1, o_1^{delim}, ..., O_i, \theta) < c_1$.*

Proof. By assumption on the transition probability,

$$p(h_i^{\text{delim}}|O_1, o_1^{\text{delim}}, ..., O_i, \theta) = \sum_{h_{i,k}} p(h_i^{\text{delim}}|h_{i,k})p(h_{i,k}|O_1, o_1^{\text{delim}}, ..., O_i, \theta) \tag{26}$$

$$< \sum_{h_{i,k}} c_1 p(h_{i,k}|O_1, o_1^{\text{delim}}, ..., O_i, \theta) = c_1. \tag{27}$$

Similarly,

$$p(h_i^{\text{delim}}|O_1, o_1^{\text{delim}}, ..., O_i, \theta^*) = \sum_{h_{i,k}} p(h_i^{\text{delim}}|h_{i,k})p(h_{i,k}|O_1, o_1^{\text{delim}}, ..., O_i, \theta^*) \tag{28}$$

$$> \sum_{h_{i,k}} c_2 p(h_{i,k}|O_1, o_1^{\text{delim}}, ..., O_i, \theta^*) = c_2. \tag{29}$$

$\square$

Proposition 2. *The density of an example is lower bounded for θ^*: there is some $c_5 > 0$ such that $p(O_i|h_i^{start}, h_{j,l}, \theta^*) > c_5$ for all i and future hidden states $h_{j,l}$, for all l and $j > i$.*

Proof. We have

$$p(O_i|h_i^{\text{start}}, h_{j,l}, \theta^*) = \sum_H p(O_i|H_i = H)p(H_i = H|h_i^{\text{start}}, h_{j,l}, \theta^*) \tag{30}$$

$$> (c_4)^k p(H_i = H|h_i^{\text{start}}, h_{j,l}, \theta^*) \tag{31}$$

for some H. We have

$$p(H_i = H|h_i^{\text{start}}, h_{j,l}, \theta^*) = \frac{p(h_{j,l}|H, h_i^{\text{start}}, \theta^*)p(H|h_i^{\text{start}}, \theta^*)}{p(h_{j,l}|h_i^{\text{start}}, \theta^*)} > c_3^2 \tag{32}$$

which lower bounds the terms in the numerator by c_3 (marginalizing over previous hidden states), and upper bounding the denominator by 1. Setting $c_5 = (c_4)^k c_3^2$ finishes the proof. $\square$

B.1   MIXING TIME LEMMAS

The following lemmas are used to show that conditioning on a variable that is at the end of the Markov chain has small effect on variables that are far away from the end of the chain (beyond the mixing time of the chain).

Lemma 1. *Suppose $Z_1, ..., Z_t$ are sampled from a Markov chain with stationary distribution π and ϵ-mixing time t_{mix}. Suppose A is any random variable where $p(Z_t|Z_i, A) = p(Z_t|Z_i)$. Then for $i < t - t_{mix}$,*

$$p(Z_i, Z_t|A) \in [p(Z_i|A)(\pi(Z_t) - \epsilon), p(Z_i|A)(\pi(Z_t) + \epsilon)]. \tag{33}$$

Proof. Using the definition of mixing time we have

$$|p(Z_t|Z_i) - \pi(Z_t)| < \epsilon, \tag{34}$$

so that

$$p(Z_i, Z_t|A) = p(Z_i|A)p(Z_t|Z_i) \in [p(Z_i|A)(\pi(Z_t) - \epsilon), p(Z_i|A)(\pi(Z_t) + \epsilon)]. \tag{35}$$

$\square$

Lemma 2. *Suppose $Z_1, ..., Z_t$ are sampled from a Markov chain with stationary distribution π and ϵ-mixing time t_{mix}. Suppose A is any random variable where $p(Z_t|Z_i, A) = p(Z_t|Z_i)$. Then for $i < t - t_{mix}$,*

$$p(Z_i|A, Z_t) \in [C_1 p(Z_i|A), C_2 p(Z_i|A)] \tag{36}$$

where

$$C_1(\epsilon) = \frac{\pi(Z_t) - \epsilon}{\pi(Z_t) + \epsilon} \tag{37}$$

$$C_2(\epsilon) = \frac{\pi(Z_t) + \epsilon}{\pi(Z_t) - \epsilon} \tag{38}$$

Proof.

$$p(Z_i|A, Z_t) = \frac{p(Z_t, Z_i|A)}{p(Z_t)} \tag{39}$$

$$< \frac{p(Z_i|A)(\pi(Z_t) + \epsilon)}{\pi(Z_t) - \epsilon}. \tag{40}$$

using Lemma 1 and $p(Z_t) = \mathbb{E}_{Z_1}[p(Z_t|Z_1)] > \pi(Z_t) - \epsilon$ by the definition of mixing time. We also have

$$p(Z_i|A, Z_t) = \frac{p(Z_t, Z_i|A)}{p(Z_t)} \tag{41}$$

$$> \frac{p(Z_i|A)(\pi(Z_t) - \epsilon)}{\pi(Z_t) + \epsilon}. \tag{42}$$

$\square$

C LEMMA FOR LIMITING DISTRIBUTION OF HIDDEN START STATE

Before showing the limiting distribution of the hidden start state, we first show lower and upper bounds for the likelihood of the prompt examples given a hidden start state for the test example. Intuitively, this lemma allows us to mostly ignore the influence of the hidden start state on the likelihood in the limit of infinite data.

Lemma 3. *Define $\epsilon^\theta(t)$ to be the bound on the TV distance between the distribution on h_{test}^{start} vs. π^θ, for $\epsilon^\theta(t)$-mixing time t. This bound $\epsilon^\theta(t)$ monotonically decreases to 0 as $t \to \infty$. Let $O_i^{ex} = [o_{i-1}^{delim}, O_i]$ be the i-th observation segment and the previous delimiter together for $i > 1$ and define $O_1^{ex} = O_1$. In*

the setting of Section 2.1, we have the following upper and lower bounds:

$$p(S_n | h_{test}^{start}, \theta) \leq p(h_n^{delim} | O_{1:n}^{ex}, h_{test}^{start}, \theta)$$

$$\prod_{i=1}^{n-t} \left[C_2^\theta(\epsilon^\theta(t))^2 \sum_{h_{i-1}^{delim} \in \mathcal{D}} p(O_i | h_{i-1}^{delim}, \theta) p(h_{i-1}^{delim} | O_{1:i-1}^{ex}, \theta) \right] \tag{43}$$

$$\prod_{i=n-t}^{n} \left[\sum_{h_{i-1}^{delim} \in \mathcal{D}} p(O_i | h_{i-1}^{delim}, h_{test}^{start}, \theta) p(h_{i-1}^{delim} | O_{1:i-1}^{ex}, h_{test}^{start}, \theta) \right] \tag{44}$$

$$p(S_n, x_{test} | h_{test}^{start}, \theta) \geq p(x_{test} | h_{test}^{start}, \theta) p(h_n^{delim} | O_{1:n}^{ex}, h_{test}^{start}, \theta)$$

$$\prod_{i=1}^{n-t} \left[C_1^\theta(\epsilon^\theta(t))^2 \sum_{h_{i-1}^{delim} \in \mathcal{D}} p(O_i | h_{i-1}^{delim}, \theta) p(h_{i-1}^{delim} | O_{1:i-1}^{ex}, \theta) \right] \tag{45}$$

$$\prod_{i=n-t}^{n} \left[\sum_{h_{i-1}^{delim} \in \mathcal{D}} p(O_i | h_{i-1}^{delim}, h_{test}^{start}, \theta) p(h_{i-1}^{delim} | O_{1:i-1}^{ex}, h_{test}^{start}, \theta) \right] \tag{46}$$

$$\tag{47}$$

Proof. We analyze the likelihood term:

$$p(S_n | h_{test}^{start}, \theta) = p(S_n | h_{test}^{start}, \theta) \tag{48}$$

$$= p(o_n^{delim} | O_{1:n}^{ex}, h_{test}^{start}, \theta) \prod_{i=1}^{n} p(O_i^{ex} | O_{1:i-1}^{ex} h_{test}^{start}, \theta) \tag{49}$$

$$= p(o_n^{delim} | O_{1:n}^{ex}, h_{test}^{start}, \theta)$$

$$\prod_{i=1}^{n} \left[\sum_{h_{i-1}^{delim} \in \mathcal{D}} p(O_i^{ex} | h_{i-1}^{delim}, h_{test}^{start}, \theta) p(h_{i-1}^{delim} | O_{1:i-1}^{ex}, h_{test}^{start}, \theta) \right] \tag{50}$$

$$= p(h_n^{delim} | O_{1:n}^{ex}, h_{test}^{start}, \theta)$$

$$\prod_{i=1}^{n} \left[\sum_{h_{i-1}^{delim} \in \mathcal{D}} p(O_i | h_{i-1}^{delim}, h_{test}^{start}, \theta) p(h_{i-1}^{delim} | O_{1:i-1}^{ex}, h_{test}^{start}, \theta) \right] \tag{51}$$

where in the last step we use our assumption $p(o^{delim} | h^{delim}) = 1$ for any delimiter token to change O_i^{ex} to O_i and o_n^{delim} to h_n^{delim}. Note that we can take the sum over hidden states to be over $\mathcal{D}$ because of our assumptions on the delimiter hidden states.

First work with

$$p(O_i | h_{i-1}^{delim}, h_{test}^{start}, \theta) = \sum_{H_i} p(O_i | H_i, h_{i-1}^{delim}, \theta) p(H_i | h_{i-1}^{delim}, h_{test}^{start}, \theta). \tag{52}$$

Focusing on the last term, we use Lemma 2 to show that for $i < n - t$,

$$p(H_i | h_{i-1}^{delim}, h_{test}^{start}, \theta) \in [C_1^\theta(\epsilon^\theta(t_n)) \cdot p(H_i | h_{i-1}^{delim}, \theta), C_2^\theta(\epsilon^\theta(t)) \cdot p(H_i | h_{i-1}^{delim}, \theta)] \tag{53}$$

where $C_1^\theta(\epsilon^\theta(t)), C_2^\theta(\epsilon^\theta(t))$ are as defined in Lemma 2, and both quantities converge to 1 as $\epsilon(t) \to 0$. Thus, for $i < n - t$,

$$p(O_i | h_{i-1}^{delim}, h_{test}^{start}, \theta) \leq C_2^\theta(\epsilon^\theta(t)) \cdot p(O_i | h_{i-1}^{delim}, \theta). \tag{54}$$

For the other term, we also invoke Lemma 2 to show that for $i < n - t$

$$p(h_{i-1}^{delim} | O_{1:i-1}^{ex}, h_{test}^{start}, \theta) \leq C_2^\theta(\epsilon^\theta(t)) \cdot p(h_{i-1}^{delim} | O_{1:i-1}^{ex}, \theta). \tag{55}$$

We can put these together to bound the terms in the original sum (Equation 51) for $i < n - t$:

$$\sum_{h_{i-1}^{delim} \in \mathcal{D}} p(O_i | h_{i-1}^{delim}, h_{test}^{start}, \theta) p(h_{i-1}^{delim} | O_{1:i-1}^{ex}, h_{test}^{start}, \theta) \tag{56}$$

$$\leq C_2^\theta(\epsilon^\theta(t))^2 \sum_{h_{i-1}^{delim} \in \mathcal{D}} p(O_i | h_{i-1}^{delim}, \theta) p(h_{i-1}^{delim} | O_{1:i-1}^{ex}, \theta). \tag{57}$$

While these steps result in an upper bound, using $C_1^\theta(\epsilon^\theta(t))$ yields the lower bound. $\qquad \square$

The following lemma is used to show that the hidden start state distribution converges to the stationary distribution with infinite examples in the prompt.

Lemma 4. *In the setting of Section 2.1, we have as* $n \to \infty$ *that*

$$p(h_{test}^{start} | S_n, x_{test}, \theta) \to \pi^\theta(h_{test}^{start} | x_{test}). \tag{58}$$

Proof. First, by Bayes' rule, we have

$$p(h_{test}^{start} | S_n, x_{test}, \theta) = \frac{p(S_n, x_{test} | h_{test}^{start}, \theta) p(h_{test}^{start} | \theta)}{p(S_n, x_{test} | \theta)} \tag{59}$$

$$= \frac{p(S_n | h_{test}^{start}, \theta) p(x_{test} | h_{test}^{start}) p(h_{test}^{start} | \theta)}{p(S_n, x_{test} | \theta)}. \tag{60}$$

We will analyze the following ratio for h_{test}^{start} where $p(S_n, x_{test} | h_{test}^{start}, \theta) > 0$ and show it converges to a constant wrt h_{test}^{start}:

$$\frac{p(S_n, | h_{test}^{start'}, \theta)}{p(S_n, | h_{test}^{start}, \theta)} \to \Theta(1) \tag{61}$$

which implies that

$$\frac{p(S_n, x_{test} | \theta)}{p(S_n | h_{test}^{start}, \theta) p(x_{test} | h_{test}^{start})} = \frac{\sum_{h_{test}^{start'}} p(S_n | h_{test}^{start'}, \theta) p(x_{test} | h_{test}^{start'}) p(h_{test}^{start'} | \theta)}{p(S_n | h_{test}^{start}, \theta) p(x_{test} | h_{test}^{start})} \tag{62}$$

$$\to \Theta(1) \frac{p(x_{test} | \theta)}{p(x_{test} | h_{test}^{start})}. \tag{63}$$

Plugging this into Equation 60 (after taking the reciprocal) and noting that $p(h_{test}^{start} | \theta) \to \pi^\theta(h_{test}^{start})$ show that

$$p(h_{test}^{start} | S_n, x_{test}, \theta) \to \Theta(1) \frac{p(x_{test} | h_{test}^{start}) \pi^\theta(h_{test}^{start})}{p(x_{test} | \theta)} \tag{64}$$

$$= \Theta(1) \pi^\theta(h_{test}^{start} | x_{test}). \tag{65}$$

Since the limiting distribution is a valid distribution (the simplex is closed) and should sum to 1, we can apply this constraint to show that the constant factor is 1, which shows the result.

Now it remains to show that

$$\frac{p(S_n, | h_{test}^{start'}, \theta)}{p(S_n, | h_{test}^{start}, \theta)} \to \Theta(1). \tag{66}$$

Redefining the ratio, we have

$$\frac{p(S_n, | h_{test}^{start'}, \theta)}{p(S_n, | h_{test}^{start}, \theta)} = \exp\left(n \cdot \frac{1}{n} \log \frac{p(S_n | h_{test}^{start'}, \theta)}{p(S_n | h_{test}^{start}, \theta)} \right). \tag{67}$$

As in Lemma 3, let $O_i^{ex} = [o_{i-1}^{delim}, O_i]$ be the i-th observation segment and the previous delimiter together for $i > 1$ and define $O_1^{ex} = O_1$. Define $\epsilon^\theta(t)$ to be the bound on the TV distance between the distribution

on $h_{\text{test}}^{\text{start}}$ vs. π^θ, for $\epsilon^\theta(t)$-mixing time t. Using Lemma 3, we have the following upper and lower bounds:

$$\frac{1}{n}\log\frac{p(S_n\,|\,h_{\text{test}}^{\text{start}'},\theta)}{p(S_n\,|\,h_{\text{test}}^{\text{start}},\theta)} \tag{68}$$

$$\leq \frac{1}{n}\Bigg(\sum_{i=1}^{n-t}\bigg[\log\frac{C_2^\theta(\epsilon^\theta(t))^2}{C_1^\theta(\epsilon^\theta(t))^2}+\log\frac{\sum_{h_{i-1}^{\text{delim}}\in\mathcal{D}}p(O_i|h_{i-1}^{\text{delim}},\theta)p(h_{i-1}^{\text{delim}}|O_{1:i-1}^{\text{ex}},\theta)}{\sum_{h_{i-1}^{\text{delim}}\in\mathcal{D}}p(O_i|h_{i-1}^{\text{delim}},\theta)p(h_{i-1}^{\text{delim}}|O_{1:i-1}^{\text{ex}},\theta)}\bigg]$$

$$+\log\frac{p(h_n^{\text{delim}}|O_{1:n}^{\text{ex}},h_{\text{test}}^{\text{start}'},\theta)}{p(h_n^{\text{delim}}|O_{1:n}^{\text{ex}},h_{\text{test}}^{\text{start}},\theta)}+\sum_{i=n-t}^{n}\log\frac{\sum_{h_{i-1}^{\text{delim}}\in\mathcal{D}}p(O_i|h_{i-1}^{\text{delim}},h_{\text{test}}^{\text{start}'},\theta)p(h_{i-1}^{\text{delim}}|O_{1:i-1}^{\text{ex}},h_{\text{test}}^{\text{start}'},\theta)}{\sum_{h_{i-1}^{\text{delim}}\in\mathcal{D}}p(O_i|h_{i-1}^{\text{delim}},h_{\text{test}}^{\text{start}},\theta)p(h_{i-1}^{\text{delim}}|O_{1:i-1}^{\text{ex}},h_{\text{test}}^{\text{start}},\theta)}\Bigg)$$

$$\leq \frac{1}{n}\Bigg(\sum_{i=1}^{n-t}\log\frac{C_2^\theta(\epsilon^\theta(t))^2}{C_1^\theta(\epsilon^\theta(t))^2}+(\log(c_1)-\log(c_2))+\sum_{i=n-t}^{n}\log\frac{\sum_{h_{i-1}^{\text{delim}}\in\mathcal{D}}1\cdot p(h_{i-1}^{\text{delim}}|O_{1:i-1}^{\text{ex}},h_{\text{test}}^{\text{start}'},\theta)}{\sum_{h_{i-1}^{\text{delim}}\in\mathcal{D}}c_5 p(h_{i-1}^{\text{delim}}|O_{1:i-1}^{\text{ex}},h_{\text{test}}^{\text{start}},\theta)}\Bigg)$$

$$\leq \frac{1}{n}\Bigg(\sum_{i=1}^{n-t}\log\frac{C_2^\theta(\epsilon^\theta(t))^2}{C_1^\theta(\epsilon^\theta(t))^2}+(\log(c_1)-\log(c_2))-\sum_{i=n-t}^{n}\log(c_5)\Bigg)$$

$$\leq \frac{1}{n}\bigg((\log(c_1)-\log(c_2))+O(t)\bigg) \tag{69}$$

$$=O(1/n) \tag{70}$$

We used both Propositions 1 and 2 in the terms involving c_1, c_2 and c_5. Note that in the first line, the sum can must be over the set of delimiter states $\mathcal{D}$ by using the assumption that observing a delimiter o^{delim} implies that the corresponding hidden state h^{delim} must be in $\mathcal{D}$. where we note that $t, C_2^\theta(\epsilon^\theta(t)), C_1^\theta(\epsilon^\theta(t))$ are constants. Flipping the order of $C_2^\theta(\epsilon^\theta(t)), C_1^\theta(\epsilon^\theta(t))$, c_1, c_2 and 1 vs. c_5 gives a lower bound:

$$\frac{1}{n}\log\frac{p(S_n,|\,h_{\text{test}}^{\text{start}'},\theta)}{p(S_n,|\,h_{\text{test}}^{\text{start}},\theta)}\geq\frac{1}{n}\Bigg(\sum_{i=1}^{n-t}\log\frac{C_1^\theta(\epsilon^\theta(t))^2}{C_2^\theta(\epsilon^\theta(t))^2}+(\log(c_2)-\log(c_1))+\sum_{i=n-t}^{n}\log(c_5)\Bigg)$$

$$\geq\frac{1}{n}\bigg((\log(c_2)-\log(c_1))+\Omega(t)\bigg) \tag{71}$$

$$=\Omega(1/n) \tag{72}$$

Together, this shows that

$$\frac{1}{n}\log\frac{p(S_n\,|\,h_{\text{test}}^{\text{start}'},\theta)}{p(S_n\,|\,h_{\text{test}}^{\text{start}},\theta)}=\Theta(1/n) \tag{73}$$

$$\tag{74}$$

which implies that

$$\frac{p(S_n\,|\,h_{\text{test}}^{\text{start}'},\theta)}{p(S_n\,|\,h_{\text{test}}^{\text{start}},\theta)}=\exp\Bigg(n\cdot\frac{1}{n}\log\frac{p(S_n\,|\,h_{\text{test}}^{\text{start}'},\theta)}{p(S_n\,|\,h_{\text{test}}^{\text{start}},\theta)}\Bigg)=\Theta(1) \tag{75}$$

as desired. $\qquad\square$

D PROOF OF THEOREM 1

Proof. We analyze the most likely prediction over the pretraining distribution conditioned on the prompt $\arg\max_y p(y|S_n,x_{\text{test}})$.

$$p(y|S_n,x_{\text{test}})=\int_\theta p(y,|S_n,x_{\text{test}},\theta)p(\theta|S_n,x_{\text{test}})d\theta \tag{76}$$

$$\propto\int_\theta p(y,|S_n,x_{\text{test}},\theta)p(S_n,x_{\text{test}}|\theta)p(\theta)d\theta \tag{77}$$

$$\propto\int_\theta p(y,|S_n,x_{\text{test}},\theta)\frac{p(S_n,x_{\text{test}}|\theta)}{p(S_n,x_{\text{test}}|\theta^*)}p(\theta)d\theta \tag{78}$$

$$=\int_\theta\sum_{h_{\text{test}}^{\text{start}}\in\mathcal{H}}p(y,|S_n,x_{\text{test}},h_{\text{test}}^{\text{start}},\theta)p(h_{\text{test}}^{\text{start}}|S_n,x_{\text{test}},\theta)\frac{p(S_n,x_{\text{test}}|\theta)}{p(S_n,x_{\text{test}}|\theta^*)}p(\theta)d\theta \tag{79}$$

Defining the following quantity,

$$r_n(\theta) = \frac{1}{n}\log\frac{p(S_n, x_{\text{test}}|\theta)}{p(S_n, x_{\text{test}}|\theta^*)}. \tag{80}$$

we will show that under distinguishability for all $\theta \neq \theta^*$, $r_n(\theta)$ converges to a negative constant such that

$$\frac{p(S_n, x_{\text{test}}|\theta)}{p(S_n, x_{\text{test}}|\theta^*)} = \exp(n \cdot r_n(\theta)) = 0 \tag{81}$$

for $\theta \neq \theta^*$, whereas this ratio is always 1 for $\theta = \theta^*$. This will then "select" the desired prompt concept through marginalization.

Taking the limit of Equation 79, we have

$$\lim_{n\to\infty}\int_\theta \sum_{h_{\text{test}}^{\text{start}}\in\mathcal{H}} p(y,|S_n, x_{\text{test}}, h_{\text{test}}^{\text{start}}, \theta)p(h_{\text{test}}^{\text{start}}|S_n, x_{\text{test}}, \theta)\frac{p(S_n, x_{\text{test}}|\theta)}{p(S_n, x_{\text{test}}|\theta^*)}p(\theta)d\theta \tag{82}$$

$$= \lim_{n\to\infty}\int_\theta \sum_{h_{\text{test}}^{\text{start}}\in\mathcal{H}} p(y,|S_n, x_{\text{test}}, h_{\text{test}}^{\text{start}}, \theta)p(h_{\text{test}}^{\text{start}}|S_n, x_{\text{test}}, \theta)\exp(n\cdot r_n(\theta))p(\theta)d\theta \tag{83}$$

$$= \int_\theta \sum_{h_{\text{test}}^{\text{start}}\in\mathcal{H}} \lim_{n\to\infty} p(y,|S_n, x_{\text{test}}, h_{\text{test}}^{\text{start}}, \theta)p(h_{\text{test}}^{\text{start}}|S_n, x_{\text{test}}, \theta)\exp(n\cdot r_n(\theta))p(\theta)d\theta \tag{84}$$

$$= \sum_{h_{\text{test}}^{\text{start}}\in\mathcal{H}} p(y,|S_n, x_{\text{test}}, h_{\text{test}}^{\text{start}}, \theta^*)\pi^{\theta^*}(h_{\text{test}}^{\text{start}})p(\theta^*) \tag{85}$$

$$\propto \sum_{h_{\text{test}}^{\text{start}}\in\mathcal{H}} p(y,|S_n, x_{\text{test}}, h_{\text{test}}^{\text{start}}, \theta^*)\pi^{\theta^*}(h_{\text{test}}^{\text{start}}) \tag{86}$$

$$= \mathbb{E}_{h_{\text{test}}^{\text{start}}\sim\pi^{\theta^*}}\left[p(y|x_{\text{test}}, h_{\text{test}}^{\text{start}}, \theta^*)\right] \tag{87}$$

as desired, where we can swap the limit and integral by the dominated convergence theorem (probabilities are bounded above by 1), and we used Lemma 4 to show the convergence to the stationary distribution.

Now it remains to show that $r_n(\theta)$ converges to a negative constant for $\theta \neq \theta^*$. Let $O_i^{\text{ex}} = [o_{i-1}^{\text{delim}}, O_i]$ be the i-th observation segment and the previous delimiter together for $i > 1$ and define $O_1^{\text{ex}} = O_1$. Expanding the numerator of the ratio in $r_n(\theta)$, we have

$$p(S_n, x_{\text{test}}|\theta) = p(x_{\text{test}}|S_n, \theta)p(S_n|\theta) \tag{88}$$

$$= \sum_{h_{\text{test}}^{\text{start}}} p(x_{\text{test}}|h_{\text{test}}^{\text{start}}, \theta)p(h_{\text{test}}^{\text{start}}|S_n, \theta)\prod_{i=1}^n p(O_i^{\text{ex}}|O_{1:i-1}^{\text{ex}}, \theta) \tag{89}$$

$$= \sum_{h_{\text{test}}^{\text{start}}} p(x_{\text{test}}|h_{\text{test}}^{\text{start}}, \theta)p(h_{\text{test}}^{\text{start}}|S_n, \theta) \tag{90}$$

$$\prod_{i=1}^n \sum_{h_{i-1}^{\text{delim}}\in\mathcal{D}} p(O_i|h_{i-1}^{\text{delim}}, \theta)p(h_{i-1}^{\text{delim}}|O_{1:i-1}^{\text{ex}}, \theta) \tag{91}$$

Note that in the last line, the sum must be over the set of delimiter states $\mathcal{D}$ by using the assumption that observing a delimiter o^{delim} implies that the corresponding hidden state h^{delim} must be in $\mathcal{D}$.

We restrict our attention to θ where $p(S_n, x_{\text{test}}|\theta) > 0$, since otherwise θ does not affect the prediction. Expanding $r_n(\theta)$, we have the following upper bound:

$$r_n(\theta) = \frac{1}{n}\left(\log\frac{p(S_n, x_{\text{test}}|\theta)}{p(S_n, x_{\text{test}}|\theta^*)}\right) \tag{92}$$

$$= \frac{1}{n}\left(\log\frac{\sum_{h_{\text{test}}^{\text{start}}}p(x_{\text{test}}|h_{\text{test}}^{\text{start}},\theta)p(h_{\text{test}}^{\text{start}}|S_n,\theta)}{\sum_{h_{\text{test}}^{\text{start}}}p(x_{\text{test}}|h_{\text{test}}^{\text{start}},\theta^*)p(h_{\text{test}}^{\text{start}}|S_n,\theta^*)} + \sum_{i=1}^{n}\log\frac{\sum_{h_{i-1}^{\text{delim}}\in\mathcal{D}}p(O_i|h_{i-1}^{\text{delim}},\theta)p(h_{i-1}^{\text{delim}}|O_{1:i-1}^{\text{ex}},\theta)}{\sum_{h_{i-1}^{\text{delim}}\in\mathcal{D}}p(O_i|h_{i-1}^{\text{delim}},\theta^*)p(h_{i-1}^{\text{delim}}|O_{1:i-1}^{\text{ex}},\theta^*)}\right) \tag{93}$$

$$\leq \frac{1}{n}\left(\log\frac{\sum_{h_{\text{test}}^{\text{start}}}1\cdot p(h_{\text{test}}^{\text{start}}|S_n,\theta)}{\sum_{h_{\text{test}}^{\text{start}}}c_5\cdot p(h_{\text{test}}^{\text{start}}|S_n,\theta^*)} + n(\log(c_1)-\log(c_2)) + \sum_{i=1}^{n}\log\frac{\sum_{h_{i-1}^{\text{delim}}\in\mathcal{D}}p(O_i|h_{i-1}^{\text{delim}},\theta)}{\sum_{h_{i-1}^{\text{delim}}\in\mathcal{D}}p(O_i|h_{i-1}^{\text{delim}},\theta^*)}\right) \tag{94}$$

$$= \frac{1}{n}\left(-\log(c_5) + n(\log(c_1)-\log(c_2)) + \sum_{i=1}^{n}\log\frac{\sum_{h_{i-1}^{\text{delim}}\in\mathcal{D}}p(O_i|h_{i-1}^{\text{delim}},\theta)}{\sum_{h_{i-1}^{\text{delim}}\in\mathcal{D}}p(O_i|h_{i-1}^{\text{delim}},\theta^*)}\right) \tag{95}$$

$$= \frac{1}{n}\left(-\log(c_5) + n(\log(c_1)-\log(c_2)) + \sum_{i=1}^{n}\log\frac{\sum_{h_{i-1}^{\text{delim}}\in\mathcal{D}}p(h_{i-1}^{\text{delim}}|\theta)p(O_i|h_{i-1}^{\text{delim}},\theta)}{\sum_{h_{i-1}^{\text{delim}}\in\mathcal{D}}p(h_{i-1}^{\text{delim}}|\theta^*)p(O_i|h_{i-1}^{\text{delim}},\theta^*)}\right) \tag{96}$$

$$= \frac{1}{n}\left(-\log(c_5) + n(\log(c_1)-\log(c_2)) + \sum_{i=1}^{n}\log\frac{\sum_{h_{i-1}^{\text{delim}}\in\mathcal{D}}p(O_i|\theta)}{\sum_{h_{i-1}^{\text{delim}}\in\mathcal{D}}p(O_i|\theta^*)}\right) \tag{97}$$

$$\to_{n\to\infty} \mathbb{E}_{O\sim p_{\text{prompt}}}\left[\log\frac{p(O|\theta)}{p(O|\theta^*)}\right] + \log(c_1)-\log(c_2) \tag{98}$$

We used both Propositions 1 and 2 in the terms involving c_1, c_2 and c_5. In the third line, we also use Proposition 2 to bound $p(x_{\text{test}}|\theta^*) > c_5$. Note that in the second line, the sum can must be over the set of delimiter states $\mathcal{D}$ by using the assumption that observing a delimiter o^{delim} implies that the corresponding hidden state h^{delim} must be in $\mathcal{D}$. In the second to last line, we used the assumption that $p(h^{\text{delim}}|\theta) = \frac{1}{|\mathcal{D}|}$ for all θ, h^{delim}, multiplying both top and bottom of the ratio by this constant. The expectation becomes a KL divergence for token 2 through k of each segment (the first token is different due to the starting distribution π_{prompt}).

Aiming to decompose the expectation into a sum over the k tokens, we write $p_\theta^j(o) = p(O[j] = o|O[1:j-1],\theta)$. Then we have that

$$\lim_{n\to\infty} r_n(\theta) < -\sum_{j=2}^{k}\mathbb{E}_{O[1:j-1]\sim p_{\text{prompt}}}[KL(p_{\theta^*}^j\|p_\theta^j)] + \mathbb{E}_{O[1]\sim p_{\text{prompt}}}\left[\log\frac{p(O[1]|\theta)}{p(O[1]|\theta^*)}\right] + (\log(c_1)-\log(c_2)) \tag{99}$$

The second term is an error term that depends on how different the starting prompt distribution π_{prompt} (which is part of p_{prompt}) is to the pre-training distribution. The third term is an error term that comes from the delimiter transitions. The bound is negative when the sum of KL terms is larger in magnitude than the error terms. Note that as k becomes larger, the number of observations of θ^* "overpowers" the OOD transitions in the prompt distribution. This condition is equivalent to the disinguishability condition (Condition 1).

By assumption, for $\theta \neq \theta^*$ the Condition 1 holds, and thus

$$\lim_{n\to\infty}\frac{p(S_n, x_{\text{test}}|\theta)}{p(S_n, x_{\text{test}}|\theta^*)} = \lim_{n\to\infty}\exp(n\cdot r_n(\theta)) = 0 \tag{100}$$

since $r_n(\theta)$ has a negative, constant limit. Note that $\exp(n\cdot r_n(\theta^*)) = 1$ for θ^*.

$\square$

E NON-DISTINGUISHABLE CASE

When Condition 1 is unsatisfied, Equation 14), gives an upper bound on the sum of KL divergences for the next token distributions given different-length histories. In contrast, the in-context task only

measures the accuracy of the last (k-th) token. The main challenge is to relate the different-length histories to each other to give a more precise bound for the error on the in-context task (last token).

Before addressing this challenge, we give the following lemma, which leverages the result of Ávila Pires & Szepesvári (2016); Steinwart (2007) to relate a bound on the KL divergence to 0-1 loss.

Lemma 5. *Let the set of θ which does not satisfy Condition 1 to be $\mathcal{B}$. Assume that $KL(p(y_{test}|x_{test}, \theta^*)\|p(y_{test}|x_{test}, \theta)$ is bounded above for all θ. If $\mathbb{E}_{x_{test}\sim p_{prompt}}[KL(p(y_{test}|x_{test},\theta^*)\|p(y_{test}|x_{test},\theta))]\leq \epsilon_\theta$ for all $\theta\in\mathcal{B}$, then*

$$\lim_{n\to\infty}L_{0\text{-}1}(f_n)\leq\inf_f L_{0\text{-}1}(f)+g^{-1}\left(\sup_{\theta\in\mathcal{B}}\epsilon_\theta\right) \tag{101}$$

where

$$g(\delta)=\frac{1}{2}((1-\delta)\log(1-\delta)+(1+\delta)\log(1+\delta)) \tag{102}$$

is a calibration function for the multiclass logistic loss for $\delta\in[0,1]$.

Proof. First, we note that we can study the 0-1 risk of the limiting predictor:

$$\lim_{n\to\infty}L_{0\text{-}1}(f_n)=\lim_{n\to\infty}\mathbb{E}_{x_{test},y_{test}\sim p_{prompt}}[\mathbf{1}[f_n(x_{test})\neq y_{test}]] \tag{103}$$

$$=\mathbb{E}_{x_{test},y_{test}\sim p_{prompt}}[\lim_{n\to\infty}\mathbf{1}[f_n(x_{test})\neq y_{test}]] \text{ (dominated convergence, boundedness of indicator)} \tag{104}$$

$$=\mathbb{E}_{x_{test},y_{test}\sim p_{prompt}}[\mathbf{1}[\lim_{n\to\infty}f_n(x_{test})\neq y_{test}]] \tag{105}$$

where in the last step we use that since the output space of f_n is discrete and the probabilities that the in-context predictor takes an argmax over converges, then for N large enough, $f_N(x_{test})=\lim_{n\to\infty}f_n(x_{test})$.

Note that for every input x_{test}, the limiting in-context learning predictor outputs the argmax of a predictive distribution which can be a mixture of predictive distributions over $\mathcal{B}$:

$$\lim_{n\to\infty}f_n(x_{test})=\underset{y}{\operatorname{argmax}}\mathbb{E}_{\theta\sim q}[p(y|x_{test},\theta)] \tag{106}$$

for some distribution q over $\mathcal{B}$. The KL divergence between this mixture and the prompt concept is bounded by the KL divergence of any one $\theta\in\mathcal{B}$, due to the convexity of KL:

$$\mathbb{E}_{x_{test}\sim p_{prompt}}[KL(p(y|x_{test},\theta^*)\|\mathbb{E}_{\theta\sim q}[p(y|x_{test},\theta)]] \tag{107}$$

$$\leq\mathbb{E}_{x_{test}\sim p_{prompt}}[\mathbb{E}_{\theta\sim q}[KL(p(y|x_{test},\theta^*)\|p(y|x_{test},\theta))]] \tag{108}$$

$$=\mathbb{E}_{\theta\sim q}[\mathbb{E}_{x_{test}\sim p_{prompt}}[KL(p(y|x_{test},\theta^*)\|p(y|x_{test},\theta))]] \tag{109}$$

$$\leq\sup_{\theta\in\mathcal{B}}\mathbb{E}_{x_{test}\sim p_{prompt}}[KL(p(y|x_{test},\theta^*)\|p(y|x_{test},\theta))] \tag{110}$$

where we can exchange the order of expectations since the KL is bounded (dominated convergence).

From the KL bound $KL(p(y_{test}|x_{test},\theta^*)\|p(y_{test}|x_{test},\theta)$, we thus have

$$\mathbb{E}_{x_{test}\sim p_{prompt}}[KL(p(y_{test}|x_{test},\theta^*)\|p(y_{test}|x_{test},\theta))]=L_{CE}(\theta)-L_{CE}(\theta^*)\leq\sup_{\theta\in\mathcal{B}}\epsilon_\theta \tag{111}$$

where $L_{CE}(\theta)=-\mathbb{E}_{x_{test}\sim p_{prompt}}[p(y_{test}|x_{test},\theta^*)\log p(y_{test}|x_{test},\theta)]$ is the multiclass logistic risk, and $L_{CE}(\theta^*)$ is the entropy of the predictive distribution. Applying Theorem 2.2 and 5.11 of Ávila Pires & Szepesvári (2016), g is a calibration function for the multiclass logistic loss, and allows us to convert the surrogate risk bound to a bound on the 0-1 loss, giving the result. Note that we have zero approximation error here, since $\theta^*\in\Theta$. $\square$

Note that g^{-1} is roughly linear in ϵ for ϵ smaller than 0.7, where the bound is non-vacuous.

E.1 PROOF OF THEOREM 2

Proof. By the continuity assumption, we have for any θ in $\mathcal{B}$ that

$$\sum_{j=2}^{k} KL_j(\theta^*\|\theta) \geq \frac{1}{2}\sum_{j=2}^{k}(\theta-\theta^*)^\top I_{j,\theta^*}(\theta-\theta^*)+(k-1)O(\|\theta-\theta^*\|^3) \tag{112}$$

$$\geq \frac{1}{2}(k-1)\lambda_{\min}(I_{j,\theta^*})\|\theta-\theta^*\|^2 \tag{113}$$

$$\implies \|\theta-\theta^*\|^2 \leq \frac{\epsilon_{\text{start}}^\theta+\epsilon_{\text{delim}}^\theta}{\frac{1}{2}(k-1)(\min_j \lambda_{\min}(I_{j,\theta^*}))}. \tag{114}$$

To bound the last KL term,

$$KL_k(\theta^*\|\theta) = \frac{1}{2}\sum_{j=2}^{k}(\theta-\theta^*)^\top I_{j,\theta^*}(\theta-\theta^*)+O(\|\theta-\theta^*\|^3) \tag{115}$$

$$\leq \frac{1}{2}(\max_j \lambda_{\max}(I_{j,\theta^*}))\|\theta-\theta^*\|^2+O(\|\theta-\theta^*\|^2) \tag{116}$$

$$\leq \frac{(\epsilon_{\text{start}}^\theta+\epsilon_{\text{delim}}^\theta)(\max_j \lambda_{\max}(I_{j,\theta^*})+O(1))}{(k-1)\min_j \lambda_{\min}(I_{j,\theta^*})}. \tag{117}$$

Rearranging and noting that $KL_k(\theta^*\|\theta)=\mathbb{E}_{x_{\text{test}}\sim p_{\text{prompt}}}[KL(p(y_{\text{test}}|x_{\text{test}},\theta^*)\|p(y_{\text{test}}|x_{\text{test}},\theta))]$, we have

$$\mathbb{E}_{x_{\text{test}}\sim p_{\text{prompt}}}[KL(p(y_{\text{test}}|x_{\text{test}},\theta^*)\|p(y_{\text{test}}|x_{\text{test}},\theta))] \leq \frac{(\epsilon_{\text{start}}^\theta+\epsilon_{\text{delim}}^\theta)(\max_j \lambda_{\max}(I_{j,\theta^*})+O(1))}{(k-1)\min_j \lambda_{\min}(I_{j,\theta^*})} \tag{118}$$

Plugging into Lemma 5 gives the result. $\square$

E.2 PROOF OF THEOREM 3

Note that Condition 1 ensures that the sum of KL divergences between positions within a k-length input is bounded. This means that we have a bound over not only the last-position KL divergence, but also for all the intermediate tokens. Intuitively, the random length test example allows the in-context predictor to "take credit" for fitting the intermediate tokens. The proof is immediate given the KL bound and Lemma 5, given that the length of x_{test} is uniformly random between 2 to k.

Proof. Let the set of θ that does not satisfy Condition 1 to be $\mathcal{B}$. We have for any θ in $\mathcal{B}$ that

$$\mathbb{E}_{x_{\text{test}}\sim p_{\text{prompt}}}KL(p(y_{\text{test}}|x_{\text{test}},\theta^*\|p(y_{\text{test}}|x_{\text{test}},\theta)) \tag{119}$$

$$\leq \frac{1}{k-1}\sum_{j=2}^{k}\mathbb{E}_{O[1:j-1]\sim p_{\text{prompt}}}KL(p(O[j]|O[1:j-1],\theta^*\|p(O[j]|O[1:j-1],\theta)) \tag{120}$$

$$\leq \frac{\sup_\theta(\epsilon_{\text{start}}^\theta+\epsilon_{\text{delim}}^\theta)}{k-1} \tag{121}$$

by Theorem 1 and Condition 1. Plugging this into Lemma 5 gives the result. $\square$

F EXPERIMENTAL DETAILS

F.1 GINC DATASET

The GINC dataset is generated from a mixture of HMMs. These HMMs output tokens from a vocabulary of size in $\{50,100,150\}$. The vocabulary contains a special delimiter token, designated to be index 1. All sequences are tokenized by splitting on whitespaces.

Memory matrix. The shared memory matrix has 10 entities and 10 properties, totaling 100 entries (corresponding to 100 hidden states). The first column of the memory matrix is fixed to be the delimiter token, while each remaining entry of the shared memory matrix is populated with a token sampled uniformly from the vocabulary.

Figure 7: In-context accuracy curve of the 4 layer Transformer on the GINC dataset when the entity transition matrix does not have an additional identity component, for vocabulary sizes 50 (left), 100 (middle), and 150 (right). In-context learning is still generally successful.

Transition matrix for properties. We generate 5 property transition matrices, one for each component of the HMM mixture. We generate each transition matrix via a convex combination of 100 random permutation matrices. The weights of the convex combination are randomly generated as

$$\text{softmax}((u-0.5)/t) \tag{122}$$

where $u \in \mathbb{R}^{1}00$ has uniform random entries in $[0,1]$ and t is a temperature parameter, set to 0.1.

Transition matrix for entities. The entity transition matrix is shared between all the HMMs that consistute the mixture. The entity transition matrix is generated in the same way as the property transition matrices, except with one additional step. Letting T be a transition matrix sampled in the same way as a property transition matrix,

In pretraining documents, we expect that the entities (e.g., Einstein) change slowly over time while and the properties of the entity (e.g., their occupation) change quickly with some pattern to generate natural sentences. We implement this by ensuring that the probability of transitioning to the same entity index in the next step is at least 0.9. The final entity transition matrix is then $0.1T+0.9I$ where I is the identity matrix. Although we add the diagonal component for added realism, we also consider not adding this component. Figure 7 shows in-context learning curves for a small (4 layer) Transformer trained on data that does not add the diagonal component (we check this for vocabulary sizes 50, 100, and 150). In-context learning still works similarly in this case.

Start distribution. The starting distribution for the hidden states in all HMMs in the mixture are close to uniform. We generate the start distribution as $\text{softmax}((u-0.5)/t)$ for random vector u with entries uniformly from $[0,1]$ and temperature $t=10$.

Prompt distribution. The prompts are sampled according to the theoretical setup. The prompt start distribution for each prompt is chosen to deterministically output one property that was randomly chosen to be the starting property for each example in the prompt. Each prompt has an independently sampled starting property. Each prompt also generates examples from one particular HMM in the micture (which HMM this is is chosen randomly). Given the starting property, we sample k tokens from the HMM. Finally, we append the delimiter token for the example. We repeat this process for each example in the prompt, concatenating all examples. The label is generated as

$$\underset{y}{\text{argmax}}\, p(y|x_{\text{test}},\theta^*) \tag{123}$$

under the prompt concept θ^*. This differs from the theory, which samples y_{test} instead of taking it to be the most likely token. However, there can be a large amount of intrinsic error that sampling introduces. We define the label this way in the simulations to remove the intrinsic error from sampling.

Dataset details. The dataset contains 1000 training documents and 100 validation documents, where training documents have 10240 tokens and validation documents have 1024 tokens. Each document is generated by first selecting one of the HMMs from the mixture uniformly at random, then generating 10240 tokens from the HMM.

We also generate 2500 in-context prompts for each (example length,number of examples) pair, for example lengths $k = [3,5,8,10]$ and number of examples $n = [0,1,2,4,8,16,32,64]$. Each prompt is generated using a random HMM in the mixture.

F.2 TRANSFORMER DETAILS

Our Transformer models are based on the GPT-2 architectures with 4, 12, and 16 layers respectively, with 12 attention heads, 768 dimensional embeddings, residual/embedding/attention dropout set to 0.1, and a context window of 1024. Other than the number of layers, the other parameters are the default settings from the HuggingFace library (Wolf et al., 2019). We train for 5 epochs using the AdamW optimizer (Loshchilov & Hutter, 2019; Kingma & Ba, 2015) with a batch size of 8 and a linear learning rate schedule (with 1000 step warmup) up to a learning rate of 8e-4 for the 4 layer and 12 layer model, while for the 16 layer model we start with a constant learning rate of 8e-4 and reduce by a factor of 0.25 whenever the best validation loss does not improve. The models took 50 minutes, 2 hours, 3 hours to train respectively. The hardware was mainly Titan Xp GPUs, trained and evaluated using 16-bit precision. All the results are reported with 5 pretraining runs (5 different seeds).

F.3 LSTM DETAILS

We train an LSTM language model with embedding size 768, hidden layer size 768, and 6 layers. We use dropout 0.2 and weight decay 1e-5. The optimizer is AdamW starting with a learning rate of 1e-3, then reducing by a factor of 0.25 whenever the best validation loss does not go down. We train for a total of 10 epochs, with gradient clipping at norm 1.0. We use a batch size of 8 and backpropagate through time for 1024 steps (each pretraining data segment is also 1024 tokens). Each model takes roughly 2 hours to train on Titan Xp GPUs.

Figure 8: In-context accuracy of the 4 layer Transformer on the GINC dataset for vocabulary sizes 50 (left), 100 (middle) and 150 (right). Accuracies generally improve as the vocabulary size increases.

Figure 9: In-context accuracy of the 12 layer Transformer on the GINC dataset for vocabulary sizes 50 (left), 100 (middle) and 150 (right). Accuracies generally improve as the vocabulary size increases.

Figure 10: In-context accuracy of the 16 layer Transformer on the GINC dataset for vocabulary sizes 50 (left), 100 (middle) and 150 (right). Accuracies generally improve as the vocabulary size increases.

F.4 VARYING THE VOCABULARY SIZE

To do well on the in-context learning task, the model must both infer the prompt concept and the last HMM hidden state. In general, increasing the number of observable symbols makes the in-context task easier by making the inference of the HMM hidden state easier. With more symbols, each hidden state

Figure 11: In-context accuracy of the LSTM on the GINC dataset for vocabulary sizes 50 (left), 100 (middle) and 150 (right). Accuracies generally improve as the vocabulary size increases.

Prompt example length	Test Acc (200–300 chars)
Short (200–300 chars)	69.8
Long (500–600 chars)	70.7

Table 1: Accuracies for 5-shot in-context learning of GPT-3 on a filtered LAMBADA test set with short examples (200–300 characters). Even though there is distribution mismatch with the test set, having longer examples improves the accuracy, supporting theoretical intuitions.

is more likely to output a different symbol, making the inference problem easier. This improvement comes despite the number of output classes in the problem (same as the vocabulary size) increasing. Figures 8, 9, 10, 11 show in-context learning curves for vocabulary sizes 50, 100, and 150, keeping other hyperparmeters of the dataset the same.

F.5 EXPERIMENT ON GPT-3

We conduct an additional experiment which shows that longer examples improve in-context learning in GPT-3 on the LAMBADA (Paperno et al., 2016) completion task.

Data. In this experiment, we define a short version of the LAMBADA test dataset (LAMBADA test-short) which contains only test examples with up to 200–300 characters in length. We also define two "training" datasets from which to sample examples for the in-context prompts from. The short training dataset (LAMBADA train-short) contains examples from the training set that are 200–300 characters in length, which matches the distribution of test-short. The long training dataset (LAMBADA train-long) contains training examples that are 500–600 characters long. We cut the number of examples in the larger of the two training datasets so that the two trainign datasets are equally sized (47 examples).

Result. For each test example, we sample 5 random training examples (5-shot learning). Table 1 shows that when evaluating only on LAMBADA test-short, 5-shot in-context learning using LAMBADA train-long improves the test accuracy by almost 1% compared to LAMBADA train-short, despite the long/short distribution mismatch between train and test. This supports intuitions from our theory.