Integrating Large Language Models in Causal Discovery: A Statistical Causal Approach

Abstract

In practical statistical causal discovery (SCD), embedding domain expert knowledge as constraints into the algorithm is important for creating consistent, meaningful causal models, despite the challenges in the systematic acquisition of background knowledge. To overcome these challenges, this paper proposes a novel method for causal inference, in which SCD and knowledge based causal inference (KBCI) with a large language model (LLM) are synthesized through "statistical causal prompting (SCP)" for LLMs and prior knowledge augmentation for SCD. Experiments have revealed that the results of LLM-KBCI and SCD augmented with LLM-KBCI approach the ground truths, more than the SCD result without prior knowledge. It has also been revealed that the SCD result can be further improved if the LLM undergoes SCP. Furthermore, with an unpublished real-world dataset, we have demonstrated that the background knowledge provided by the LLM can improve the SCD on this dataset, even if this dataset has never been included in the training data of the LLM. For future practical application of this proposed method across important domains such as healthcare, we also thoroughly discuss the limitations, risks of critical errors, expected improvement of techniques around LLMs, and realistic integration of expert checks of the results into this automatic process, with SCP simulations under various conditions both in successful and failure scenarios. The careful and appropriate application of the proposed approach in this work, with improvement and customization for each domain, can thus address challenges such as dataset biases and limitations, illustrating the potential of LLMs to improve data-driven causal inference across diverse scientific domains.

The code used in this work will be made publicly available upon the acceptance of this paper.

1 Introduction

1.1 Background

Understanding causal relationships is key to comprehending basic mechanisms in various scientific fields. The statistical causal inference framework, which is widely applied in areas such as medical science, economics, and environmental science, aids this understanding. However, traditional statistical causal inference methods generally rely on the assumed causal graph for determining the existence and strength of causal impacts. To overcome this challenge, data-driven algorithmic methods have been developed as statistical causal discovery (SCD) methods, both in non-parametric (Spirtes et al., 2000; Chickering, 2002; Silander & Myllymäki, 2006; Yuan & Malone, 2013; Huang et al., 2018; Xie et al., 2020) and semi-parametric (Shimizu et al., 2006; Hoyer et al., 2008; Shimizu et al., 2011; Rolland et al., 2022; Tu et al., 2022) approaches. In addition, benchmark datasets have been published for the evaluation of SCD methods (Mooij et al., 2016; Käding & Runge, 2023).

Despite advancements in SCD algorithms, data-driven acquisition of causal graphs without domain knowledge can be inaccurate. This is generally attributed to a mismatch between assumptions in SCD and real-world phenomena (Reisach et al., 2021). Moreover, obtaining experimental and systematic datasets sufficient for causal inference is difficult, whereas observational datasets, which are prone to selection bias and measurement

errors, are more readily accessible (Abdullahi et al., 2020). Consequently, for more persuasive and reliable validation of causal models, the augmentation with domain knowledge plays a critical role (Rohrer, 2017). In

Figure 1: Overall framework of the statistical causal prompt in a large language model (LLM) and statistical causal discovery (SCD) with LLM-based background knowledge.

addition, with respect to efficiency and precision in the SCD, the importance of incorporating constraints on trivial causal relationships into the SCD algorithms has been highlighted (Inazumi et al., 2010; Chowdhury et al., 2023). Causal learning software packages have been augmented with prior knowledge, as demonstrated in "causal-learn" [1], and "LiNGAM" [2] (Zheng et al., 2023b; Ikeuchi et al., 2023).

Moreover, the systematic acquisition of domain expert knowledge is a challenging task. Although there are several examples of constructing directed acyclic graphs (DAGs) by domain experts, as demonstrated in health services research (Rodrigues et al., 2022), practical methods for this process have not been proposed.

The scenario has recently changed with rapid progress in the development of high-end large language models (LLMs). Owing to their high performance in the applications of their domain knowledge acquired from vast amounts of data in the pretraining processes (OpenAI, 2023; Touvron et al., 2023; Gemini Team, Google, 2023), it has been expected that LLMs can also be applied to causal reasoning tasks. In fact, several studies have reported the trial results of LLM knowledge-based causal inference (LLM-KBCI) (Jiang et al., 2023; Jin et al., 2024; Kıcıman et al., 2023; Zečević et al., 2023; Jiralerspong et al., 2024; Zhang et al., 2024), and in particular, the performance enhancement in non-parametric SCD with the guides by LLMs was confirmed (Ban et al., 2023; Vashishtha et al., 2023; Khatibi et al., 2024). However, it remains unclear whether the enhancement in SCD accuracy with background knowledge augmented by LLMs is robustly observed when the task of the SCD depends on closed data uncontained in the pretraining datasets of LLMs, and whether it leads to more statistically valid causal models.

---

[1] https://github.com/py-why/causal-learn
[2] https://github.com/cdt15/lingam

1.2 Central Idea of Our Research

On the basis of the rapidly evolving techniques in the context of causal inference with LLMs, a novel methodology for SCD is proposed in this paper, in which the LLM prompted with the results of the SCD without background knowledge evaluates the probability of the causal relationships considering both the domain knowledge and the statistical characteristics suggested by SCD (Figure 1).

In the first step, an SCD is executed on a dataset without prior knowledge, and the results of the statistical causal analysis are output. To maximize the usage of the expert knowledge acquired in the pretraining process of the LLM, the method of generated knowledge prompting (Liu et al., 2022) is adopted, and then, the process of utilizing the LLM includes the second step (knowledge generation) and the third step (knowledge integration). In the second step, knowledge of the causal relationships between all pairs of variables is generated in detail from the domain knowledge of the LLM based on the zero-shot chain-of-thought (ZSCoT) prompting technique (Kojima et al., 2022). Here, the LLM can be prompted with the results of the SCD as supplemental information for LLM inference, expecting that the in-context learning (Brown et al., 2020) of the SCD results can lead to better performance of the LLM-KBCI in terms of statistics. We define this technique as "statistical causal prompting" (SCP). Thereafter, in the third step, the LLM judges whether there are causal relationships between all pairs of variables with "yes" or "no," thus objectively considering the dialogs of the second step. Here, the probabilities of the responses from the LLM are evaluated and transformed into the prior knowledge matrix. This matrix, the output of LLM-KBCI with SCP, is finally reapplied to SCD in the fourth step.

1.3 Our Contribution

The contributions of the method proposed in this study are as follows:

(1) Realization of the Synthesis of LLM-KBCI and SCD in a Mutually-Referential Manner The practical method for realizing the proposed concept of Figure 1 is detailed, and the SCP method is proposed. Experiments were demonstrated with several benchmark datasets, which are open and have been widely used for the evaluation of SCD algorithms. They all consist of continuous variables.

(2) Mutual Performance Enhancement of SCD and LLM-KBCI We demonstrate that the augmentation by the LLM with SCP, improves the performance of the SCD, and the performance of the LLM-KBCI is also enhanced by the SCP.

(3) Enhancement of SCD Performance by SCP In the experiments, we demonstrate that the outputs of several SCD algorithms augmented by the LLM with SCP, can be a superior causal model to the pattern of prompting without SCP in terms of domain expertise and statistics.

(4) Improvement of SCD results with the background knowledge provided by LLMs even if the dataset is uncontained in the pretraining materials We prepared a closed health screening dataset that is not included in the pretraining materials for LLMs, and demonstrated the experiment on a sub-dataset that has been randomly sampled from the entire dataset. Through this experiment, we clearly confirmed that the proposed method robustly leads to more statistically valid causal models with natural ground truths. This fact proved that the LLMs can indeed contribute to background knowledge augmentation for SCD algorithms in practical situations, even if the dataset used for SCD is not memorized by LLMs.

(5) Discussion on the Reliability and Risks of Integrating LLMs as a "Black-Box" into SCD In addition, we demonstrate some simulations of SCP in various conditions, and confirm the existence of the patterns where SCP firmly works as intended, and the technical and statistical limitations of the proposed method. We also discuss realistic strategies and directions for future practical applications, to overcome the limitations of the proposed method, and to effectively obtain appropriate causal models from both expert and statistical points of view, avoiding critical errors.

2 Related Works and Originality in Our Work

Augmentation of SCD Algorithms with Background Knowledge As introduced in Section 1.1, several SCD algorithms [3] can be systematically augmented with background knowledge. Moreover, their software packages are open. For example, as a non-parametric and constraint-based SCD method, the Peter-Clerk (PC) algorithm (Spirtes et al., 2000) is augmented with background knowledge of the forced or forbidden directed edges in "causal-learn." "Causal-learn" also provides the Exact Search algorithm (Silander & Myllymäki, 2006; Yuan & Malone, 2013) as a non-parametric and score-based SCD method, which can be augmented with the background knowledge of the forbidden directed edges as a super-structure matrix. With respect to a semi-parametric approach, the DirectLiNGAM (Shimizu et al., 2011) algorithm is augmented with prior knowledge of the causal order (Inazumi et al., 2010) in the "LiNGAM" project (Ikeuchi et al., 2023).

Causal Inference in Knowledge-Driven Approach with LLMs In addition to the study on causality detection from natural language texts via language models with additional training datasets (Khetan et al., 2022), the rapid growth of LLMs has made it possible to produce valuable works on causality, including causal inference using LLMs. Attempts have been made to use LLMs for causal inference among a set of variables, prompting with the metadata such as the names of variables, and without the SCD process with the benchmark datasets (Kıcıman et al., 2023; Zečević et al., 2023; Jiralerspong et al., 2024; Zhang et al., 2024). Adopting a similar approach, the concept of causal modeling agents, which improves the precision of causal graphs through iteration of hypothesis generation from LLMs and model fitting to real-world data, has also been proposed (Abdulaal et al., 2024). There are also studies on incorporating LLMs in the process of SCD as an alternative tool for conditional independence tests in the PC algorithm (Cohrs et al., 2023), and for identifying causal graphs beyond the Markov equivalent class (Long et al., 2023). In addition, studies have focused on the use of LLMs to improve the SCD results(Ban et al., 2023; Vashishtha et al., 2023; Khatibi et al., 2024). However, all the experiments were conducted only on popular benchmark datasets, contained in the pretraining datasets of LLMs. Consequently, while acknowledging the valuable foundations laid by previous studies, it has remained uncertain whether the enhancements in SCD accuracy are truly driven by LLMs leveraging their vast knowledge for genuine causal inference, or merely by reproducing the memorized content of datasets (Vashishtha et al., 2023).

Originality in Our Work In contrast to studies with similar focuses on LLM-guided SCD (Ban et al., 2023; Vashishtha et al., 2023; Khatibi et al., 2024), this study also focuses on the construction of background knowledge in a quantitative manner based on the response probability of the LLM, which can reflect the credibility of the decision made by the LLM with SCP. In addition, in the case of a semi-parametric SCD method such as LiNGAM, we detail herein how to achieve both statistical validity and natural interpretation with respect to domain knowledge at a maximally high level, by prompting with the causal coefficients and bootstrap probabilities of all the patterns of directed edges.

Moreover, we validate the proposed method on an unpublished dataset. For future practical applications, we also thoroughly discuss the limitations, risks of critical errors, expected improvement of techniques around LLMs, and the suggestion of realistic integration of domain expert checks of the results into this automatic methodology, with the simulations of SCP in both successful and failing scenarios. These approaches have not only demonstrated the practical utility and robustness of our method for future applications in each domain, but also opened new avenues for supporting the validity and applicability of existing works (Ban et al., 2023; Vashishtha et al., 2023; Khatibi et al., 2024).

3 Materials and Methods

3.1 Algorithms and Elements for LLM-Augmented Causal Discovery

---

[3]All of the algorithms adopted for the experiments in this paper can be used under the assumption of a DAG and with no hidden confounders.

Algorithm 1 Background knowledge construction with the LLM prompted with the results of the SCD

Input 1: Data X with variables $\{x_1, ..., x_n\}$
Input 2: SCD method S
Input 3: Function for bootstrap B
Input 4: Response of the domain expert (GPT-4) ϵ_{GPT4}
Input 5: Log probability of the response $L(\epsilon_{\text{GPT4}})$
Input 6: Prompt function for knowledge generation $Q_{ij}^{(1)}$
Input 7: Prompt function for knowledge integration $Q_{ij}^{(2)}$
Input 8: Transformation from probability matrix to prior knowledge T
Input 9: Number of times to measure the probability M
Output: Result of SCD with prior knowledge $\hat{G}$ on X

SCD result without prior knowledge $\hat{G}_0 = S(X)$
bootstrap probability matrix $\boldsymbol{P} = B(S, X)$
for $i = 1$ **to** n **do**
  for $j = 1$ **to** n **do**
    $\overline{p_{i,i}} = \text{NaN}$
    if $i \neq j$ **then**
      prompt $q_{ij}^{(1)} = Q_{ij}^{(1)}(x_i, x_j, \hat{G}_0, \boldsymbol{P})$
      response $a_{ij} = \epsilon_{\text{GPT4}}(q_{ij}^{(1)})$
      prompt $q_{ij}^{(2)} = Q_{ij}^{(2)}(q_{ij}^{(1)}, a_{ij})$
      for $m = 1$ **to** M **do**
        $L_{ij}^{(m)} = L^{(m)}(\epsilon_{\text{GPT4}}(q_{ij}^{(2)}) = \text{"yes"})$
      end for
      mean probability $\overline{p_{ij}} = \dfrac{\sum_{m=1}^{M} \exp(L_{ij}^{(m)})}{M}$
    end if
  end for
end for
probability matrix $\overline{\boldsymbol{p}} = (\overline{p_{ij}})$
prior knowledge $\boldsymbol{PK} = T(\overline{\boldsymbol{p}})$
return $\hat{G} = S(X, \boldsymbol{PK})$

With respect to practicality, the method of Figure 1 is outlined as Algorithm 1. Following the notation in Algorithm 1, the input elements in the demonstration are explained below.

Algorithms for Statistical Causal Discovery For the SCD method S, we adopted the PC algorithm (Spirtes et al., 2000), the Exact Search algorithm based on the A* algorithm (Yuan & Malone, 2013), and the DirectLiNGAM algorithm (Shimizu et al., 2011), which can all be optionally augmented with prior knowledge, and are open in "causal-learn" (Zheng et al., 2023b) and "LiNGAM" (Ikeuchi et al., 2023). Furthermore, we also implement the bootstrap sampling function B of the SCD algorithm to investigate the statistical properties such as the bootstrap probabilities p_{ij} of the emergence of the directed edges from x_j to x_i. In our experiments, the number of bootstrap resamplings was fixed to 1000.

Conditions of the LLM and Prompting   To utilize the LLM as the domain expert, we adopted `GPT-4-1106-preview`[4] developed by OpenAI; the temperature, a hyperparameter for adjusting the probability distribution of the output, was fixed to 0.7.

The template for the first prompting $q_{ij}^{(1)}$ for knowledge generation is shown in Table 1. This prompting template is based on the underlying principle of the ZSCoT technique[5] (Kojima et al., 2022), which was reported as a potential method to enhance the performance of the LLM generation tasks; enhancement is performed by guiding logical inference and eliciting the background knowledge acquired through the pretraining process from the LLM. Furthermore, expecting that the in-context learning (Brown et al., 2020) of the SCD results can lead to better performance of the LLM-KBCI in terms of statistics, the SCD results, e.g., the causal structure and bootstrap probabilities, can be included in ⟨blank 5⟩ and ⟨blank 9⟩, which are defined as "statistical causal prompting" (SCP). Because the information used in SCP is partially dependent on the SCD algorithms, a brief description of the patterns for constructing the contents of ⟨blank 5⟩ and ⟨blank 9⟩ is presented in Section 3.2.

As shown in Table 2, the generated knowledge is integrated into the second prompt, and GPT-4 is required to judge the existence of the causal effect from x_j on x_i from an objective point of view. Because the response from GPT-4 is required with "yes" or "no," it is simple to quantitatively evaluate the level of confidence of GPT-4 in the existence of a causal relationship based on both the SCD result and domain knowledge. The probability p_{ij} of the assertion that there is a causal effect from x_j on x_i can be output from GPT-4 directly with the optional function of returning the log-probabilities of the most likely tokens at each token position[6]. Although p_{ij} can be evaluated readily from the log probability of the GPT-4 response as "yes," there is a slight fluctuation in the log probability output from GPT-4 (Andriushchenko et al., 2024). Thus, we adopted the mean probability $\overline{p_{ij}}$ of the single-shot measurement M times for the decision of prior knowledge matrix $\boldsymbol{PK}$, and we set $M = 5$ in the experiments. The combination of these prompt techniques can contribute to minimizing the risk of hallucination from the LLM, and it is expected that a reliable probability of the response from the LLM for the causal relationship between a pair of variables is obtained.

For the subsequent SCD with prior knowledge, the probability matrix $\overline{\boldsymbol{p}}$ is transformed with T, as expressed by Algorithm 2, into the background knowledge matrix.

Here, if $PK_{ij} =$ Forbidden, the causal effect from x_j to x_i is forbidden from appearing in the SCD result. However, if $PK_{ij} =$ Forced, the causal effect from x_j to x_i is forced to appear in the SCD result[7]. For the decision of forbidden or forced causal relationship from PK_{ij}, we prepare the probability criterion for the forbidden path as α_1 and that for the forced path as α_2. In our experiments, α_1 is fixed at 0.05, and α_2 is fixed at 0.95 for common settings[8].

---

[4]We recognize that various types of high-performance LLMs have been developed at several institutes, and that it is valuable to demonstrate that including a broader range of LLMs could provide valuable insights into the generalizability and scalability of our method across various LLM architectures. From this recognition, in addition to the main experiments with `GPT-4-1106-preview`, we have also demonstrated our approach with other LLMs, such as `GPT-3.5-turbo-1106`, `GPT-3.5-turbo-0125`, `GPT-4-0125-preview`, and `GPT-4o-2024-08-06`, and have improved the performance of SCD, as described in Appendix H. However, our goal in this work is to explore the effectiveness of integrating LLMs into SCD via the SCP, which requires trials and comparisons of various SCP patterns and SCD algorithms, as described in Section 4. To maintain consistency and control across these trials, it is also important to fix the LLM in the experiments, which has advanced capabilities and state-of-the-art status in various domains. Moreover, we should adopt the LLMs that satisfy specific conditions for our experiments, such as the maximum input token capacity for the prompting processes, and the functionality to obtain the log-probability of the output. For these strategic and technical reasons, we adopted GPT-4 in our thorough experiments.

[5]Although the quality of the LLM outputs can be further enhanced, e.g., by fine-tuning with several datasets containing fundamental knowledge for causal inference or retrieval-augmented generation (RAG), we adopt the idea of ZSCoT to establish low-cost and simple methods, which can be universally applied independent of the targeted fields of causal inference.

[6]The technical detail of this probability sampling is explained in Appendix D .

[7]Although these constraints can be systematically adapted with the augmentation supported in "causal-learn" (Zheng et al., 2023b) and "LiNGAM" (Ikeuchi et al., 2023), the detailed meanings of forced and forbidden causal effects are slightly different among the SCD algorithms. The details are described in Appendix E

[8]These heuristic thresholds follow the widely accepted conventions seen in statistical significance levels. Although the specific choice of threshold might influence the formation of the prior knowledge matrix, the probability outputs from LLMs for clear domain knowledge instances are either very high (close to 100 %) or very low (close to 0 %), ensuring that the essential insights are retained regardless of the threshold. In Appendix D, technical details of this sensitivity around these thresholds are described through the evaluation of the standard error of $\overline{p_{ij}}$, which can be realized by repeating single-shot measurements of $\overline{p_{ij}}$ M times.

Table 1: Prompt template of $Q_{ij}^{(1)}(x_i, x_j, \hat{G}_0, \boldsymbol{P})$ used for the generation of the expert knowledge of the causal effect from x_j on x_i. The "blanks" enclosed with $\langle\ \rangle$ are filled with description words . The word for $\langle$blank 6$\rangle$ is selected from "a" or "no," depending on the content of $\langle$blank 5$\rangle$. Notations of the SCD result without prior knowledge $\hat{G}_0$ and the bootstrap probability matrix $\boldsymbol{P}$ are the same as those in Algorithm 1.

Prompt Template of $q_{ij}^{(1)} = Q_{ij}^{(1)}(x_i, x_j, \hat{G}_0, \boldsymbol{P})$

We want to carry out causal inference on $\langle$blank 1. The theme$\rangle$, considering $\langle$blank 2. The description of all variables$\rangle$ as variables.
First, we have conducted the statistical causal discovery with $\langle$blank 3. The name of the SCD algorithm$\rangle$, using a fully standardized dataset on $\langle$blank 4. Description of the dataset$\rangle$.

$\langle$blank 5. This Includes the information of $\hat{G}_0$ or $\boldsymbol{P}$.The details of the contents depend on the prompting patterns.$\rangle$

According to the results shown above, it has been determined that there may be $\langle$blank 6. a/no$\rangle$ direct impact of a change in $\langle$blank 7. The name of $x_j\rangle$ on $\langle$blank 8. The name of $x_i\rangle$ $\langle$blank 9. The value of causal coefficients or bootstrap probability$\rangle$.
Then, your task is to interpret this result from a domain knowledge perspective and determine whether this statistically suggested hypothesis is plausible in the context of the domain.

Please provide an explanation that leverages your expert knowledge on the causal relationship between $\langle$blank 7. The name of $x_j\rangle$ and $\langle$blank 8. The name of $x_i\rangle$, and assess the naturalness of this causal discovery result. Your response should consider the relevant factors and provide a reasoned explanation based on your understanding of the domain.

Table 2: Prompt template of $Q_{ij}^{(2)}(q_{ij}^{(1)}, a_{ij})$ used for the quantitative evaluation of the probability of GPT-4's assertion that there is a causal effect from x_j on x_i.

Prompt Template of $q_{ij}^{(2)} = Q_{ij}^{(2)}(q_{ij}^{(1)}, a_{ij})$

An expert was asked the question below:
$\langle$blank 10. $q_{ij}^{(1)}\rangle$

Then, the expert replied with its domain knowledge:
$\langle$blank 11. $a_{ij}\rangle$

Considering objectively this discussion above, if $\langle$blank 12. The name of $x_j\rangle$ is modified, will it have a direct or indirect impact on $\langle$blank 13. The name of $x_i\rangle$?
Please answer this question with $\langle$yes$\rangle$ or $\langle$no$\rangle$.
No answers except these two responses are needed.

Furthermore, the differences in the constraints that can be adopted depending on the SCD algorithms should be considered. In the Exact Search algorithm, the constraints of the forced edge cannot be applied. For the case of DirectLiNGAM, because prior knowledge is used for the decision of the causal order in the algorithm, the prior knowledge matrix must be an "acyclic" adjacency matrix when it is represented in the form of a network graph. Thus, when $S = $ DirectLiNGAM and $\boldsymbol{PK}$ is cyclic, an additional transformation algorithm A is required. In addition, there can be several acyclic transformation patterns; only one acyclic matrix with some criteria should be selected. The algorithm for the transformation and the matrix selection criterion in this study are explained in Appendix F.

3.2 Experiment Patterns of SCP

Related to $\langle$blank 5$\rangle$ and $\langle$blank 9$\rangle$ in Table 1, we conducted experiments using several patterns of SCP. the notations of the prompting patterns in the experiments are presented with explanations below:

Algorithm 2 Transformation from the probability matrix into the prior knowledge matrix

---
    Input 1: probability matrix $\boldsymbol{p} = (p_{ij})$
    Input 2: SCD method $S \in \{$ PC, Exact Search, DirectLiNGAM $\}$
    Input 3: probability criterion for the forbidden causal relationship α_1
    Input 4: probability criterion for the forced causal relationship α_2
    Output: prior knowledge matrix $\boldsymbol{PK} = (PK_{ij})$
    for $i = 1$ **to** n **do**
      for $j = 1$ **to** n **do**
        $PK_{ij} = $ Unknown
        if $i = j$ **then**
          $PK_{ij} = $ Forbidden
        else
          if $p_{ij} < \alpha_1$ **then**
            $PK_{ij} = $ Forbidden
          else if $(p_{ij} \geq \alpha_2)$ **and** $(S \neq$ Exact Search$)$ **then**
            $PK_{ij} = $ Forced
          end if
        end if
      end for
    end for
    if $S = $ DirectLiNGAM **then**
      $\boldsymbol{PK} = A(\boldsymbol{PK})$ (acyclic transformation)
    end if
    return $\boldsymbol{PK}$

Pattern 0: without SCP   This pattern corresponds to the reference for the comparison with the other patterns, including SCD results in their prompts. Because the prompt template shown in Table 1 is not adequate for this pattern, we prepare a different template for Pattern 0, which is shown in Appendix B.

Pattern 1: With the list of edges that appeared in the first SCD   Directed or undirected[9] edges between x_i and x_j that emerged in the SCD are listed.

Pattern 2: With the list of edges with their non-zero bootstrap probabilities   Directed or undirected edges between x_i and x_j that emerged in the bootstrap process are listed with their bootstrap probabilities.

Pattern 3: With the list of edges that emerged in the first SCD with the calculated causal coefficients (only for DirectLiNGAM)   On the basis of the property of DirectLiNGAM, which outputs the causal coefficients with the DAG discovered in the algorithm, this pattern is attempted to elucidate whether more information, such as causal coefficients, in addition to Pattern 1, can improve the performance of LLM-KBCI and the subsequent SCD with prior knowledge.

Pattern 4: With the list of edges with their non-zero bootstrap probabilities and calculated causal coefficients for the full dataset (only for DirectLiNGAM)   We also attempt this pattern with the most information of the 1st SCD as a mixture of Patterns 2 and 3.

3.3 Datasets for the Experiments

Although several widely-open benchmark datasets with well-known ground truths exist, particularly for Bayesian network-based causal structure learning (Scutari & Denis, 2014), several of them are fully or partially

---

[9]In the PC algorithm, undirected edges that appear as $x_i - x_j$ with respect to causal relationships between "x_i and x_j" in which the direction cannot be determined, can be detected. The prompt template for reflecting this difference from directed edges is shown in Appendix B.

composed of categorical or discrete variables. However, considering Patterns 3 and 4 for the experiments in this study, because the basic structure causal model assumes the continuous properties of all variables, it is more effective to adopt benchmark datasets fully composed of continuous variables.

Consequently, we select three benchmark datasets for the experiments, as follows: 1. Auto MPG data (Quinlan, 1993) (five continuous variables) , 2. Deutscher Wetterdienst (DWD) climate data (Mooij et al., 2016) (six continuous variables) , 3. Sachs protein data (Sachs et al., 2005) (eleven continuous variables) .

Furthermore, to demonstrate that GPT-4 can aid SCD with its domain knowledge, even if the dataset used in the SCD process and analytics on the dataset are not contained in the pretraining data of GPT-4, the proposed methods are also applied to our dataset of health screening results, which has not been disclosed and therefore not learned by GPT-4. To demonstrate that the proposed methods can be applied when the dataset contains bias, which may lead to highly inaccurate SCD results, the health screening dataset for this experiment was sampled, and we deliberately chose a subset where certain biases are still present. Basic information on these datasets, such as the first SCD results and the ground truths is presented in Appendix C.

4 Results and Discussion

4.1 Results in Benchmark Datasets

For the interpretation of the experimental results, we evaluate PK (for measuring the performance of LLM-KBCI with the prompts, including the first SCD results) and the adjacency matrix obtained in SCD with PK for each pattern (for measuring the performance of the SCD augmented with LLM-KBCI), with the structural hamming distance (SHD), false positive rate (FPR), false negative rate (FNR), precision, and F1 score, using the ground truth adjacency matrix GT as a reference.

All of these metrics are frequently used to evaluate how the results of the causal structure learning are close to the ground truths, and can be calculated solely from the adjacency matrix and GT, as shown in Appendix E.3. In addition, this paper presents an evaluation of the comparative fit index (CFI) (Bentler, 1990), root mean square error of approximation (RMSEA) (Steiger & Lind, 1980) and Bayes information criterion (BIC) (Schwarz, 1978) of the causal structure obtained in SCD with PK, under the assumption of linear-Gaussian data[10]; to evaluate the results with respect to the statistical validity of calculated causal models. To evaluate the effect of PK augmentation by the LLM, the baseline result is that without PK (Baseline A), as a reference for comparison with the SCD results augmented with PK. In contrast, to evaluate the effect of the SCP, the results with the prompt in Pattern 0 become the baseline (Baseline B), for comparison with the results obtained in other SCP patterns. The indices for all patterns on the DWD, Auto MPG, and Sachs datasets are summarized in Table 3.

Enhancing the performance with prior knowledge augmentation by GPT-4 One of the characteristics in Table 3 is that, in most cases, the result of SCD augmented with PK is more similar to GT than the first SCD result without prior knowledge (Baseline A). This behavior is interpreted as the knowledge-based improvement of the causal graph by GPT-4 as a domain expert, which is qualitatively consistent with other related works on LLM-guided causal inference (Ban et al., 2023; Vashishtha et al., 2023). Moreover, in many of the cases of Auto MPG and DWD data, the precision or F1 score are higher after the SCD augmented with PK than the pure PK, which are conclusions of LLM-KBCI, while they are almost comparable in the cases of Sachs data. This comparison implies that even if the LLM-KBCI is not optimal, the ground truths can be better approached by conducting SCD augmented with the LLM-KBCI. In addition, the BIC decreases in almost all the patterns from the SCD result without PK (Baseline A). The aforementioned properties suggest that knowledge-based augmentation from GPT-4 can improve the performance of SCD, indeed, in terms of consistency with respect to domain expert knowledge and the statistical causal structure. However, the amount of improvement can differ depending on the number of variables and the methods of SCD.

---

[10] Although this assumption of linear-Gaussian data for the calculation of the CFI, RMSEA, and BIC, does not match the assumption of a non-Gaussian error distribution in LiNGAM, we adopt these indices to evaluate and compare the results with respect to the same statistical method, irrespective of the difference in the SCD algorithms.

Table 3: Comparison of the SCD results in all the experimental patterns we conducted. While SHD, FPR, FNR, precision, and F1 score are compared to evaluate how close the results are to the ground truths, CFI, RMSEA, and BIC are compared to evaluate the statistical validity of the calculated causal models. Lower values are superior for SHD, FPR, FNR, RMSEA, and BIC, and higher values for precision, F1 score and CFI. The numbers in parentheses indicate theSHD, FPR, FNR, precision, and F1 score of **PK** with ground truths, to evaluate the performance of LLM-KBCI. The values in the blue font are the optimal results among Patterns 0–4, if the dataset and the SCD algorithm are fixed. Baseline A is used for comparison with the SCD results augmented with *PK* generated by the LLM, to evaluate the effect of *PK* augmentation by the LLM. Baseline B is used for comparison with the results obtained in other SCP patterns, to evaluate the effect of the SCP. It is implied that in DWD and Sachs datasets, the outputs of LLM-KBCI in Patterns 1–4 are likely to approach the ground truths more closely than those in Pattern 0. It is also suggested that several of the outputs of Exact Search and DirectLiNGAM in Patterns 1–4 (with SCP), can be superior causal models than those in Pattern 0.

SCD algorithm	Pattern	SHD↓	FPR↓	FNR↓	Precision↑	F1score↑	CFI↑	RMSEA↓	BIC↓
1. Auto MPG data with 5 continuous variables									
PC	wo **PK**(Baseline A)	8	0.40	0.80	0.11	0.14	1.00	0.00	71.65
	Pattern 0 (Baseline B)	3 (5)	0.15 (0.25)	0.20 (0.20)	0.57 (0.44)	0.67 (0.57)	1.00	0.07	65.62
	Pattern 1	4 (7)	0.15 (0.30)	0.20 (0.20)	0.57 (0.40)	0.67 (0.53)	1.00	0.00	59.71
	Pattern 2	3 (6)	0.15 (0.30)	0.20 (0.20)	0.57 (0.40)	0.67 (0.53)	1.00	0.07	65.62
Exact Search	wo **PK**(Baseline A)	5	0.25	0.40	0.38	0.46	1.00	0.07	71.61
	Pattern 0 (Baseline B)	4 (5)	0.20 (0.25)	0.20 (0.20)	0.50 (0.44)	0.62 (0.57)	1.00	0.09	71.59
	Pattern 1	5 (5)	0.20 (0.20)	0.20 (0.20)	0.50 (0.50)	0.62 (0.62)	1.00	0.07	65.62
	Pattern 2	4 (5)	0.20 (0.25)	0.20 (0.20)	0.50 (0.44)	0.62 (0.57)	1.00	0.09	71.59
DirectLiNGAM	wo **PK**(Baseline A)	8	0.40	0.80	0.11	0.14	1.00	0.05	77.61
	Pattern 0 (Baseline B)	3 (5)	0.15 (0.25)	0.20 (0.20)	0.57 (0.44)	0.67 (0.57)	1.00	0.07	65.62
	Pattern 1	3 (5)	0.15 (0.30)	0.20 (0.20)	0.57 (0.40)	0.67 (0.53)	1.00	0.07	65.62
	Pattern 2	3 (5)	0.15 (0.25)	0.20 (0.20)	0.57 (0.44)	0.67 (0.57)	1.00	0.07	65.62
	Pattern 3	4 (6)	0.20 (0.35)	0.20 (0.20)	0.50 (0.36)	0.62 (0.50)	1.00	0.00	71.65
	Pattern 4	3 (5)	0.15 (0.30)	0.20 (0.20)	0.57 (0.40)	0.67 (0.53)	1.00	0.07	65.62
2. DWD climate data with 6 continuous variables									
PC	wo **PK**(Baseline A)	9	0.20	0.83	0.14	0.15	0.90	0.22	69.32
	Pattern 0 (Baseline B)	5 (8)	0.03 (0.20)	0.67 (0.33)	0.67 (0.40)	0.44 (0.50)	0.71	0.36	32.70
	Pattern 1	5 (9)	0.03 (0.23)	0.67 (0.33)	0.67 (0.36)	0.44 (0.47)	0.71	0.36	32.70
	Pattern 2	5 (8)	0.03 (0.20)	0.67 (0.33)	0.67 (0.40)	0.44 (0.50)	0.71	0.36	32.70
Exact Search	wo **PK**(Baseline A)	6	0.20	0.17	0.45	0.59	0.91	0.28	92.87
	Pattern 0 (Baseline B)	5 (8)	0.10 (0.20)	0.33 (0.33)	0.57 (0.40)	0.62 (0.50)	0.98	0.12	58.38
	Pattern 1	5 (5)	0.10 (0.13)	0.33 (0.17)	0.57 (0.56)	0.62 (0.67)	0.91	0.19	57.73
	Pattern 2	6 (9)	0.13 (0.23)	0.33 (0.33)	0.50 (0.36)	0.57 (0.47)	0.91	0.20	63.58
DirectLiNGAM	wo **PK**(Baseline A)	10	0.33	0.67	0.17	0.22	1.00	0.00	99.53
	Pattern 0 (Baseline B)	4 (8)	0.07 (0.20)	0.33 (0.33)	0.67 (0.40)	0.67 (0.50)	1.00	0.00	52.67
	Pattern 1	8 (8)	0.10 (0.10)	0.83 (0.83)	0.25 (0.25)	0.20 (0.20)	0.64	0.43	38.03
	Pattern 2	4 (7)	0.03 (0.17)	0.50 (0.33)	0.75 (0.44)	0.60 (0.53)	0.98	0.09	40.80
	Pattern 3	5 (6)	0.10 (0.13)	0.33 (0.33)	0.57 (0.50)	0.62 (0.57)	0.93	0.16	57.90
	Pattern 4	5 (6)	0.10 (0.17)	0.33 (0.16)	0.57 (0.50)	0.62 (0.62)	0.92	0.18	57.80
3. Sachs' protein data with 11 continuous variables									
PC	wo **PK**(Baseline A)	24	0.16	0.47	0.38	0.44	0.99	0.05	294.15
	Pattern 0 (Baseline B)	15 (19)	0.04 (0.11)	0.58 (0.47)	0.67 (0.48)	0.52 (0.50)	0.89	0.16	166.91
	Pattern 1	25 (43)	0.17 (0.53)	0.68 (0.16)	0.26 (0.23)	0.29 (0.36)	0.97	0.11	284.58
	Pattern 2	23 (23)	0.13 (0.24)	0.74 (0.32)	0.28 (0.35)	0.27 (0.46)	0.97	0.09	231.27
Exact Search	wo **PK**(Baseline A)	31	0.26	0.68	0.18	0.23	0.99	0.07	374.35
	Pattern 0 (Baseline B)	17 (19)	0.07 (0.11)	0.58 (0.47)	0.53 (0.48)	0.47 (0.50)	0.91	0.16	202.97
	Pattern 1	17 (15)	0.05 (0.06)	0.68 (0.58)	0.55 (0.57)	0.40 (0.48)	0.87	0.20	158.26
	Pattern 2	16 (14)	0.11 (0.14)	0.53 (0.32)	0.45 (0.48)	0.46 (0.57)	0.95	0.12	257.53
DirectLiNGAM	wo **PK**(Baseline A)	29	0.25	0.47	0.28	0.36	1.00	0.01	410.23
	Pattern 0 (Baseline B)	17 (19)	0.07 (0.11)	0.53 (0.47)	0.56 (0.48)	0.51 (0.50)	0.91	0.16	203.02
	Pattern 1	15 (13)	0.07 (0.08)	0.47 (0.37)	0.59 (0.60)	0.56 (0.62)	0.88	0.18	220.32
	Pattern 2	22 (21)	0.14 (0.18)	0.63 (0.47)	0.33 (0.36)	0.35 (0.43)	0.70	0.31	269.76
	Pattern 3	22 (23)	0.15 (0.18)	0.53 (0.53)	0.38 (0.33)	0.42 (0.39)	0.92	0.16	301.51
	Pattern 4	20 (16)	0.12 (0.16)	0.53 (0.26)	0.43 (0.47)	0.45 (0.57)	0.89	0.19	264.97

Dependence on the number of variables In the case of Auto MPG data with only five variables, the amount of improvement for each SCD method is almost constant among all the prompting patterns. One of the possible reasons is that, within relatively small numbers of variables, the amount of information in the SCP becomes small, and the difference in the inference performance of GPT-4 among the prompt patterns

becomes subtle. Moreover, because the space for discovery also decreases as the network shrinks, the SCD algorithm may reach a single optimal solution, even if **PK** is different.

On the other hand, in the cases of DWD data with six variables and Sachs data with eleven variables, the difference in the amount of improvement becomes clearer depending on the prompting patterns. This implies that the threshold of the number of variables over which the quality of the **PK** and SCD results depend on the amount of information included. In the SCP for GPT-4, it is approximately five.

Moreover, in many cases of DWD and Sachs data, particularly for Exact Search or DirectLiNGAM, the precision and F1 score of **PK** in Pattern 0 (Baseline B) are usually smaller than those of any of the other patterns, in which GPT-4 experiences SCP. This finding supports the performance enhancement of LLM-KBCI by the SCP.

Prompting pattern dependence on SCD methods On the other hand, considering the output of the SCD augmented with **PK**, Pattern 0 (Baseline B) stably indicates relatively higher performance among all the patterns in terms of both domain knowledge and statistical model fitting. Furthermore, the results of Patterns 0 and 1 are almost the same when the PC or the Exact Search algorithm is adopted; in particular, the result of Pattern 0 with the PC algorithm on Sachs data is superior to that of Pattern 0.

Although it is difficult to explain this behavior, one of the possible reasons, if we focus only on the results on Sachs data, is that we adopted the ground truths partially determined by Bayesian network inference (Sachs et al., 2005). Indeed, the first SCD result in PC is already relatively close to **GT**, as shown in Figure 12 (a), and we interpret that, in this situation, the performance of SCD with **PK** cannot be improved.

The scenario differs when DirectLiNGAM is adopted. The performance of the SCD with **PK** either in Pattern 1 or 2, remains overall superior to that of Pattern 0 (Baseline B) from both statistical and domain expert points of view. This implies that SCP can effectively improve the performance of DirectLiNGAM.

However, from the analysis of Patterns 3 and 4, in which GPT-4 is prompted with the causal coefficients of the first SCD results, it is also revealed that prompting with a greater amount of statistical information does not always lead to improved SCD results. In particular, although **PK** in Pattern 4 is closer to the ground truth matrix than that in Pattern 0 in the DWD or Sachs data [11], the final SCD result augmented with **PK** in Pattern 4 is inferior to that of Pattern 0. One of the possible reasons for this may be the pruning of the candidate edges suggested from **PK** in the SCD process. To elucidate this behavior, further research is required on what type and amount of information in SCP can truly maximize the performance of SCD.

4.2 Results for a Randomly Selected Subsample of Health Screening Data Excluded from the GPT-4 Pretraining Dataset

It is difficult to assert that this improvement is solely due to the LLM's high performance in KBCI from the experimental results on open benchmark datasets, because it cannot be determined whether the improvement stems from the LLM's recall of the data obtained during the pretraining process on these datasets. Furthermore, assuming realistic situations, it is also important to confirm the robust effectiveness of this method, even if the range of the available dataset for statistical causal inference is limited to observation data, which may be statistically biased, and trivial causal relationships are not apparent in SCD without prior knowledge. Therefore, we also apply the proposed methods to the sub-dataset of health screening results, which has been randomly sampled from the entire dataset[12], and the natural ground truth is not presented in the SCD results without **PK**.

In Figure 2(a), the result of DirectLiNGAM without **PK** is shown, and unnatural directed edges to "Age" from other variables are suggested, although the parts of the ground truths from expert knowledge are reversed relationships from these edges, such as "Age"→"HbA1c". However, when the causal discovery is assisted by **PK** generated from GPT-4 with the SCP in Patterns 2 and 4, the causal graph becomes more natural: "Age" is not influenced by other variables, and the ground truth "Age"→"HbA1c", which cannot be detected without **PK** in this randomly selected subset, appears in the causal graph, as shown in Figure 2(b).

---

[11] This fact reinforces the reliability of our interpretation that the SCP enhance the performance of LLM-KBCI.

[12] The details of the sampling method for this experiment are presented in Appendix C

Figure 2: Results of DirectLiNGAM on the health screening data. (a) Result without prior knowledge. (b) Result with prior knowledge, which is generated from GPT-4 with the SCP in Patterns 2 and 4. In this randomly selected subset, the DirectLiNGAM result without prior knowledge exhibits unnatural paths drawn in red in (a), which indicates that "Age" is influenced by "HbA1c." However, when the proposed method is applied, the unnatural behavior is clearly mitigated with the guidance of prior knowledge generated from GPT-4 with SCP, including the value of causal coefficients in (a) or the bootstrap probabilities of the emergence of directed edges.

Because this sub-dataset and the analysis results are not disclosed and have been completely excluded from the pretraining data for GPT-4, GPT-4 cannot respond to prompts asking for causal relationships merely by reproducing the knowledge acquired from the same data. On the basis the above, it is verified that the assistance of GPT-4 with SCP can cause the result of SCD to approach the ground truths to some extent, even when the dataset is not learned by GPT-4 and contains bias. Moreover, the effectiveness of the proposed method demonstrated on both open benchmark datasets and unpublished health-screening datasets also supports the validity and applicability of existing works (Ban et al., 2023; Vashishtha et al., 2023; Khatibi et al., 2024), where knowledge-based improvements with LLMs of the causal graph on open benchmark datasets have been demonstrated using their own methods with unique originality. Our research, by showing versatility across both open and unpublished data, further enhances the validity of these existing works.

For further clarity regarding the behaviors of SCP, the mean probabilities of the positive response on the causal relationships from GPT-4 for ground truths in the health screening data, in addition to the statistics of the fitting results with the structure suggested by DirectLiNGAM with the SCP, are presented in Table 4.

Finally, it is also confirmed that the BIC decreases with the assistance of GPT-4 compared with that without *PK*. In particular, the values in Patterns 1, 2, and 4 are lower than those in Pattern 0. This suggests that SCP can contribute to the discovery of causal structure with more adequate statistical models.

4.3 Discussion on Reliability Evaluation from Domain Knowledge and Prevention of Misuse Toward Practical Applications

However, from a realistic point of view, it is also impossible to control the LLMs as perfectly as possible, for adequate output of the LLM-KBCI tasks. Therefore, for the practical application of the proposed method, it is important not only to confirm the effective points of view shown above, but also to analyze the case of failed outputs of the LLM-KBCI. In fact, as shown in Table 4, while the existence of "Age"→"HbA1c" is supported in the probabilities over 0.95 in Pattern 0 without SCP, the probability decreases for other patterns with SCP. This behavior implies that while GPT-4 itself, without any prompting, accepts "Age"→"HbA1c" as one of the ground truths, SCP, including the result that does not statistically support this edge, reduces the confidence of GPT-4 in this causal relationship.

The primary cause of this behavior is our reliance solely on the knowledge possessed by GPT-4, and the inherent performance limitations of GPT-4 itself may influence these results. Generally, it is challenging to comprehensively confirm what LLMs know or do not know. Although benchmark tests or equivalent performance measurements, as described in the development reports of each LLM, can confirm their knowledge

Table 4: Quantitative evaluation of the characteristic results of SCD in the proposed methods on the subset of health screening data with certain biases.

A: Elements of P generated in each prompting pattern for all the appropriate ground truth causal relationships in these variables. The values enclosed in parentheses are the bootstrap probabilities of the directed edges in the DirectLiNGAM algorithm without PK. It is suggested that the mean probabilities of the positive response on the causal relationships from GPT-4 are influenced by the results of SCD and bootstrap probabilities when they are included in SCP. Moreover, all the probabilities of reversed, unnatural causal relationships in which "age" is influenced by other factors are extremely close to zero.

B: CFI, RMSEA, and BIC were evaluated on the basis of model fitting with the structure discovered by DirectLiNGAM, under the assumption of linear-Gaussian data. The values enclosed in parentheses are the statistics of the structure calculated without PK.

It can be inferred that SCP with bootstrap probabilities in Patterns 2 and 4, enhances the confidence in "Age"→"DBP" by GPT-4 and improves the BIC compared with Pattern 0.

		Pattern 0	Pattern 1	Pattern 2	Pattern 3	Pattern 4
A. Probability of reproducing ground truth from GPT-4	**"Age"→"BMI"** (0.166)	0.901	0.076	0.093	0.306	0.037
	"Age"→"SBP" (0.550)	0.626	0.302	0.207	0.235	0.795
	"Age"→"DBP" (0.308)	0.001	0.019	0.115	0.095	0.926
	"Age"→"HbA1c" (0.327)	0.986	0.170	0.723	0.046	0.176
B. Statistics of linear-Gaussian fitting with the results of DirectLiNGAM	**CFI↑** (1.002)	0.999	0.992	0.995	0.986	0.995
	RMSEA↓ (0.000)	0.018	0.054	0.032	0.057	0.032
	BIC↓ (124.332)	103.581	89.738	89.740	103.506	89.740

to some extent, it is practically difficult to exhaustively grasp all of their knowledge (Kaddour et al., 2023; Pezeshkpour, 2023).

Moreover, although we have adopted several prompt techniques to reduce hallucinations as much as possible in our method, we cannot predict when and how hallucinations might occur during practical applications. Therefore, it is necessary to recognize this point and exercise caution during deployment. Specifically, examining the impact of prompting patterns reveals that while incorporating SCD results through SCP tends to overall improve outcomes compared with not including them, at a granular level such as each causal relationship between a pair of variables, SCP might inadvertently guide LLMs' judgment in the wrong direction.

Recognizing these issues, mechanically applying our method without considering potential countermeasures raises concerns, especially when reliable decisions are expected in critical domains such as healthcare. Therefore, in this section, we also propose a simulation method to verify these issues and conduct experiments to discuss the two types of risks mentioned above.

In particular, on the basis of the discussion of causality in the realm of health-screening as a use case, we demonstrate that certain patterns exist where even for GPT-4, it is obvious that causal relationships cannot exist, and that false positives do not occur even if GPT-4 undergoes SCP with the wrong causal relationships suggested by SCD. In addition, we identify patterns that are considered ground truth from domain knowledge but are not necessarily obvious to GPT-4, resulting in a risk of false negatives through SCP. Furthermore, the potential improvement of the prompt methodology for stabilizing the GPT-4 confidence probability measurement is also discussed. Finally, we discuss realistic strategies to overcome these problems when applying our proposed method.

Simulation Methods for the Assessment of Robustness and Vulnerabilities of the Proposed Method and Influence of SCP

For the simulations mentioned above, we make a minor change in the method shown in Figure 1, and the overall process of these simulations is illustrated in Figure 3. To investigate quantitatively the effect of SCP

Figure 3: Framework of the simulations for assessing the robustness and vulnerabilities of the proposed method and influence of SCP. In particular, the processes of Simulation A (for the assessing the LLM's confidence in edges, where causal relationships are recognized as unnatural) are exemplified, and the entire framework is almost the same as the proposed method illustrated in Figure 1.

including the causal coefficients or bootstrap probabilities, on confidence of GPT-4 in causal relationships, we focus on the case of DirectLiNGAM.

Process A is based on the first step in Figure 1, and "pseudo-results" of SCD is prepared for SCP. We prepare the SCD results from DirectLiNGAM, and find the edge that should obviously not appear, or should appear from the domain knowledge. By changing the causal coefficient c and bootstrap probability b of that edge from the DirectLiNGAM result, "pseudo-results" can be easily manufactured. Processes B and C correspond to the second and third steps in Figure 1, and we evaluate the average probability $p_{ij}(c, b)$ of the output in Process C, as a function of the input causal coefficient c and the bootstrap probability b.

To clearly examine the dependency of p_{ij} on c and b, we consider the following prompt patterns from all the patterns shown in Section 3.2:

- Pattern 2: Prompting only with the bootstrap probabilities (without assigning causal coefficients). In our simulations, p_{ij} is taken in this pattern while varying b in increments of 0.1, from 0 to 1.

- Pattern 3: Prompting only with the causal coefficients (without assigning bootstrap probabilities).In our simulations, p_{ij} is taken in this pattern while varying c in increments of 0.05, from -2 to 2.

- Pattern 4: Prompting with causal coefficients and bootstrap probabilities (assigning both). In our simulations, p_{ij} is taken in this pattern while varying b in increments of 0.1, from 0.1 to 1 and varying c in increments of 0.1, from -1 to 1[13].

---

[13]Although the experimental range of c in Pattern 3 is $-2 \le c \le 2$ for thorough investigation of the dependence on input c, we shrink this range in Pattern 4 into $-1 \le c \le 1$, for practical feasibility of the experiments in the two-dimensional parameter space

Figure 4: Results of Simulation A through the methodology illustrated in Figure 3, with the pseudo-results based on the SCD results for the subsampled health-screening dataset, which is used in the experiment of Section 4.2. Simulations were conducted on unrealistic edges "BMI" → "Age", "Waist" → "Age" and "HbA1c" → "Age." (a) Results for Pattern 2 (various values of causal coefficient c are prompted with in Process B). (b) Results for Pattern 3 (various values of bootstrap probability b are prompted with in Process B). Considering that maximum values of the left vertical axes for these graphs are smaller than 1.0×10^{-5}, GPT-4's confidence probability in these unrealistic edges is fixed around 0, regardless of the causal coefficients or bootstrap probabilities in the pseudo-results of SCD.

In the simulation, following the experimental setup shown in Section 3.1, we adopted `GPT-4-1106-preview`, set the temperature to 0.7, and use a single-shot measurement of repetition count of $M = 5$, calculating the average of $p_{ij}(c,b)$ over five runs as $\overline{p_{ij}}(c,b)$.

By examining the dependency of the average probability $\overline{p_{ij}}(c,b)$ on the coefficient c and bootstrap probability b, we analyze the performance of GPT-4 and the influence of SCP. If $\overline{p_{ij}}$ consistently takes values close to 0 or 1 regardless of these parameters, it suggests that GPT-4 has firm domain knowledge -either recognizing an edge as extremely unnatural (in the case of 0) or natural (in the case of 1). Conversely, if $\overline{p_{ij}}(c,b)$ changes depending on c or b, it indicates that GPT-4's knowledge about the existence of the edge is not firm, and that SCP can influence its judgment.

Simulation A: LLMs' Confidence in Edges Where Causal Relationships Are Recognized as Unnatural (Discussion on Firmly Successful Cases)

First, as in Simulation A, we examine cases where obviously unnatural edges appear, such as "HbA1c" → "Age", and investigate whether changes in causal coefficients or bootstrap probabilities affect the confidence probabilities. We base this analysis on the DirectLiNGAM results from a subsampled dataset of 1,000 instances where such edges actually appear, as shown in Figure 2(a). Process A in Figure 3 clearly illustrates how the causal graph and bootstrap probability matrix are modified and mounted in SCP, in the case of examining "HbA1c" → "Age". In addition, we also examine the cases of "Waist" → "Age" and "BMI" → "Age", all of which are similarly unnatural paths, since "Age" is determined only by birthday and the passage of time.

Figure 4 shows the values of $\overline{p_{ij}}$ and its dependence on causal coefficients in (a) and on bootstrap probabilities in (b). It is confirmed from these graphs that, regardless of the values of c or b, the confidence probabilities in the existence of the causal relationships of "HbA1c" → "Age", "Waist" → "Age" and "BMI" → "Age" are almost zero (below 1×10^{-5})). From these graphs, it is confirmed that, regardless of the coefficient values or bootstrap probabilities, the confidence probabilities in causal relationships for these unnatural edges remain almost zero and constant.

Table 5: Results of linear regression of $\overline{p}_{ij}$ with the causal coefficient c and the bootstrap probability b, for the results of Simulation A on unrealistic edges "BMI" → "Age," "Waist" → "Age," and "HbA1c" → "Age." The values enclosed in parentheses are the root mean squared error (RMSE) obtained through regression. Although we do not discuss whether these coefficients and constants are significantly different from 0 at any significance level, it is obviously illustrated that $\overline{p_{ij}}$ does not depend on c or b for the directed edges above, since all the values are approximately 0 (all of the absolute values are less than 10^{-6}).

Causal Relationship	Variable of Regression	Pattern 2	Pattern 3	Pattern 4
"BMI" → "Age"	**Constant**	7.7×10^{-9} $(\pm 1.2 \times 10^{-8})$	1.0×10^{-7} $(\pm 2.8 \times 10^{-8})$	3.3×10^{-9} $(\pm 6.8 \times 10^{-9})$
	Causal Coefficient c	—	-3.3×10^{-8} $(\pm 2.4 \times 10^{-8})$	-9.8×10^{-9} $(\pm 5.2 \times 10^{-9})$
	Bootstrap Probability b	-3.3×10^{-9} $(\pm 2.1 \times 10^{-8})$	—	1.7×10^{-8} $(\pm 1.1 \times 10^{-8})$
"Waist" → "Age"	**Constant**	1.2×10^{-8} $(\pm 7.4 \times 10^{-9})$	5.3×10^{-8} $(\pm 1.5 \times 10^{-8})$	-1.5×10^{-8} $(\pm 3.0 \times 10^{-8})$
	Causal Coefficient c	—	-2.5×10^{-8} $(\pm 1.3 \times 10^{-8})$	-2.1×10^{-9} $(\pm 2.3 \times 10^{-8})$
	Bootstrap Probability b	-9.4×10^{-9} $(\pm 1.3 \times 10^{-8})$	—	7.9×10^{-8} $(\pm 4.8 \times 10^{-8})$
"HbA1c" → "Age"	**Constant**	-5.7×10^{-10} $(\pm 5.7 \times 10^{-9})$	2.1×10^{-8} $(\pm 8.5 \times 10^{-9})$	6.8×10^{-8} $(\pm 3.3 \times 10^{-8})$
	Causal Coefficient c	—	1.7×10^{-9} $(\pm 7.2 \times 10^{-9})$	2.2×10^{-9} $(\pm 2.5 \times 10^{-8})$
	Bootstrap Probability b	8.6×10^{-9} $(\pm 9.7 \times 10^{-9})$	—	-5.9×10^{-8} $(\pm 5.3 \times 10^{-8})$

Moreover, the results of the regression analysis are also shown in Table 5. Here, the function for the regression [14] is set as follows:

$$\overline{p_{ij}} = \begin{cases} p_0 + \alpha c & \text{(pattern 2)} \\ p_0 + \beta b & \text{(pattern 3)} \\ p_0 + \alpha c + \beta b & \text{(pattern 4)} \end{cases} \tag{1}$$

Here, α is the coefficient for c (the causal coefficient in pseudo-results of SCD), β is the coefficient for b (the bootstrap probability in pseudo-results of SCD), and p_0 is the constant. From the regression results shown in Table 5, it can be confirmed that $\overline{p_{ij}}$ for the unnatural causal assumption "HbA1c" → "Age," "Waist" → "Age," and "BMI" → "Age" is indeed independent of c and b, staying around 0.

This finding suggests that, regardless of how the SCP is performed, the judge of GPT-4 is firm, and it can correctly judge that such unnatural edges as that $\overline{p_{ij}}$ for unnatural causal assumptions "HbA1c" → "Age", "Waist" → "Age" and "BMI" → "Age" should not appear. Therefore, it is possible to identify these unnatural causal hypotheses that even GPT-4 can reject regardless of SCP through the experiments above, and our method indeed effectively contributes to generating prior knowledge for SCD, which effectively avoids the risk of false positives. As a result, the proposed method makes it possible to focus on truly possible causal relationships from the experts' point of view.

Simulation B: LLMs' Confidence in Edges Where Causal Relationships Should Be Recognized and the Influence of SCP (Discussion on Failure Cases)

On the other hand, it is also important to discuss how the LLMs are confident in the causal relationships that are widely accepted as ground truths from an expert's point of view. To clarify this problem, we try

---

[14]For more strict discussion, since the range of the confidence probability $\overline{p_{ij}}$ is $0 \leq \overline{p_{ij}} \leq 1$, it is more natural to introduce a logistic function for fitting. However, to simply understand the dependence of $\overline{p_{ij}}$ on c or b, we tentatively adopt the linear function for the regression in this paper.

Pseudo-Results of SCD for Simulation B
(Testing the Influence of SCP on GPT-4's Confidence Probability for Ground Truth Edges)

Causal Graph Based on DirectLiNGAM
for entire health-screening dataset with 123151 points

Bootstrap Probabilities of Directed Edges

Effected/Cause	BMI	Waist	SBP	DBP	HbA1c	LDL	Age
BMI	–	0.000	0.000	1.000	1.000	1.000	1.000
Waist	1.000	–	1.000	1.000	1.000	0.000	1.000
SBP	1.000	0.000	–	1.000	0.723	0.720	1.000
DBP	0.000	0.000	0.000	–	1.000	1.000	1.000
HbA1c	0.000	0.000	0.000	0.000	–	1.000	b
LDL	0.000	0.000	0.000	0.000	0.000	–	0.000
Age	0.000	0.000	0.000	0.000	0.000	0.000	–

Figure 5:   Example of pseudo-results of DirectLiNGAM in the entire health-screening dataset with 123151 for Simulation B. In this example, on the basis of the initial DirectLiNGAM results shown in Figure 13, the causal coefficient and the bootstrap probability of the directed edge "Age" → "HbA1c" are replaced with the variables c and b, respectively. (The value of the causal coefficient without replacement is 0.02, and the bootstrap probability is 1.000.) Because of the large number of data points of the entire health-screening dataset, some directed edges, including the ground truth bootstrap probabilities, are 1.000. In Simulation B, in addition to this example, the pseudo-results modulating the causal coefficients and bootstrap probabilities of "Age" → "BMI," "Age" → "SBP," and "Age" → "DBP," are also embedded similarly to Figure 3.

Simulation B, the method of which is almost the same as that of Simulation A shown in Figure 3, except for the targeted edges in this simulation, and the base of the pseudo-results included in SCP.

Although the basic experimental processes of Simulation B are the same as those of Simulation A illustrated in Figure 3, there are two types of modifications from Simulation A to demonstrate of the GPT-4's confidence test in ground truth directed edges as follows:

- The basis of the pseudo-results generated in process A is replaced with the DirectLiNGAM results[15] on "entire" health-screening data with 123151 points, as illustrated in Figure 5. Since this basis holds all the ground truth directed edges, the causal coefficients and bootstrap probabilities of these edges can be easily modulated in Process A.

- The modulated directed edges are replaced with "Age" → "BMI," "Age" → "SBP," "Age" → "DBP," and "Age" → "HbA1c." (from "HbA1c" → "Age," "Waist" → "Age," and "BMI" → "Age")

The experimental results in the case of "Age" → "HbA1c" are graphically illustrated in Figure 6 as examples, and the entire results of linear regression of $\overline{p_{ij}}$ with causal coefficient c and the bootstrap probability b are shown in Table 6. From Figure 6 (a), although a large and irregular fluctuation of $\overline{p_{ij}}$ is clearly observed, the dependence of $\overline{p_{ij}}$ on the causal coefficient c in the case of "Age" → "HbA1c" is also confirmed: while $\overline{p_{ij}}$ is relatively unstable and rarely approaches 1 when $c < 0$ is satisfied, it becomes more stable and often approaches 1 when $c > 0$ is satisfied. Conversely, as illustrated in Figure 6 (b), the dependence of $\overline{p_{ij}}$ on

---

[15]The causal graph and bootstrap probability matrix are shown in Appendix C.4.

Figure 6: Representative results of Simulation B through the methodology illustrated in Figure 3, with the pseudo-results based on the SCD results for the full health-screening dataset as shown in Figure 5. Simulations were conducted on unrealistic edges "Age" → "BMI," "Age" → "SBP," "Age" → "DBP," and "Age" → "HbA1c," we representatively show the results on "Age" → "HbA1c."
(a) Results for Pattern 2 (various values of causal coefficient c are prompted with in Process B). although a large and irregular fluctuation of $\overline{p_{ij}}$ is observed, the dependence of $\overline{p_{ij}}$ on the causal coefficient c in the case of "Age" → "HbA1c" is also confirmed: while $\overline{p_{ij}}$ is relatively unstable and rarely approaches 1 when $c < 0$ is satisfied, it becomes more stable and often approaches 1 when $c > 0$ is satisfied.
(b) Results for Pattern 3 (various values of bootstrap probability b are prompted with in Process B). The dependence of $\overline{p_{ij}}$ on the bootstrap probability b is more unstable than that on the causal coefficient c. However, it is also clearly confirmed that $\overline{p_{ij}}$ never becomes stable even when b approaches 0 or 1.

the bootstrap probability b is more unstable than that on the causal coefficient c. However, it is also clearly confirmed that $\overline{p_{ij}}$ never becomes stable even when b approaches 0 or 1.

Moreover, the results of linear regression of $\overline{p_{ij}}$ with c or b are summarized in Table 6, for all the directed edges of "Age" → "BMI," "Age" → "SBP," "Age" → "DBP," and "Age" → "HbA1c." In contrast to the results of Simulation A illustrated in Table 5, all the absolute values of the estimated coefficients and constants are greater than 0.01. In addition, many of the estimated values are considered statistically significant with the criterion of the level 1 %. These results suggest that GPT-4's confidence probabilities of these directed edges, which have been accepted as ground truths by medical experts, can be somehow influenced by the incorporation of c or b into SCP. Moreover, the minus coefficients of b are suggested in Pattern 2 of "Age" → "SBP." From this result, it can be interpreted that the higher bootstrap probability b, which indicates a greater likelihood of statistical causal relationships, can sometimes lead to a lower confidence probability of GPT-4, although the detailed mechanism is unknown. Therefore, it must be recognized that SCP can also induce the risk of false negatives, especially when LLMs are not absolutely confident in the judgment of causal relationships. Adopting these uncertain results as prior knowledge could lead to incorrect causal graph generation.

Toward Stabilization of LLMs' Confidence Probability Measurement with Improvement of Prompting Techniques

For more practical use, the origin of the large fluctuations of $\overline{p_{ij}}$ illustrated in Figure 6 should also be discussed. The main causes of variation in confidence probability are considered as follows:

- The dependency of GPT-4's judgment in Process C of Figure 6 (Step 3 of Figure 2) on the content of the sentences generated in Process B (Step 2 of Figure 2)

Table 6: Results of linear regression of $\overline{p}_{ij}$ with the causal coefficient c and the bootstrap probability b, for the results of the simulation on realistic edges "Age" → "BMI", "Age" → "SBP", "Age" → "DBP" and "Age" → "HbA1c," which are strongly supported in the realm of medical domain and are interpreted as ground truths. The values enclosed in parentheses are the RMSEs obtained through regression. The asterisks $*$, $**$, and $***$ indicate that the coefficients or constants are significantly different from zero at the 10, 5, and 1 % levels, respectively.

Causal Relationship	Variable of Regression	Pattern 2	Pattern 3	Pattern 4
"Age" → "BMI"	**Constant**	0.1347 * (± 0.0764)	0.6623 *** (± 0.0312)	0.0558 (± 0.0361)
	Causal Coefficient c	—	-0.0491 * (± 0.0267)	-0.0661 ** (± 0.0276)
	Bootstrap Probability b	0.0243 (± 0.1310)	—	0.6000 *** (± 0.0581)
"Age" → "SBP"	**Constant**	0.7786 *** (± 0.1180)	0.8106 *** (± 0.0255)	0.8106 *** (± 0.0292)
	Causal Coefficient c	—	-0.0553 ** (± 0.0218)	-0.0114 (± 0.0223)
	Bootstrap Probability b	-0.8103 *** (± 0.2010)	—	-0.0101 (± 0.0471)
"Age" → "DBP"	**Constant**	0.5438 *** (± 0.1070)	0.8058 *** (± 0.0268)	0.3681 *** (± 0.0411)
	Causal Coefficient c	—	-0.0284 (± 0.0229)	0.0548 * (± 0.0314)
	Bootstrap Probability b	-0.3726 ** (± 0.1830)	—	0.4405 *** (± 0.0662)
"Age" → "HbA1c"	**Constant**	0.4650 *** (± 0.1330)	0.7570 *** (± 0.0247)	0.1814 *** (± 0.0393)
	Causal Coefficient c	—	0.1048 *** (± 0.0211)	0.1915 *** (± 0.0300)
	Bootstrap Probability b	-0.1446 (± 0.2270)	—	0.5272 *** (± 0.0633)

- Fluctuations in the log-probabilities in Process C (Step 3 of Figure 2) itself (as already explained in Section 3.1)

While the latter can be mitigated by evaluating $\overline{p_{ij}}$ obtained through multiple measurements, the former arises from the separation of GPT-4's judgment process into Processes B and C (Steps 2 and 3 in Figure 1). As explained in Sections 1.2 and 3.1, we have adopted the method of generated knowledge prompting (Liu et al., 2022) to suppress hallucination. Therefore, each task of Processes B and C (Steps 2 and 3 in Figure 1) is relatively simple, and this separation also makes it possible to detect the tendency of the hallucination, which can further improve the performance of the LLM's causal reasoning with its domain knowledge. For example, if $\overline{p_{ij}}$ generated in Process C (Step 3 in Figure 1) is completely different from the expectation of human experts, there may be a fatal defect in the factual statement or logic in the generated knowledge in Process B (Step 2 in Figure 1), which leads to incorrect judgment in Process C (Step 3 in Figure 1). In that case, checking the generated texts in Process B (Step 2 in Figure 1) from an expert's point of view can also be an effective process for improving the performance of the proposed method. Moreover, this additional process with domain experts can lead to the discovery of new discussions on causal relationships, especially when there is no systematic understanding of the causality between a pair of variables.

However, careful attention is also required so that analysis of the long text generated in Process B (Step 2 in Figure 1) is complicated, because all the tokens are randomly generated with the next token prediction on

Table 7: Textual output in Process B of Simulation B in the case of "Age" $\rightarrow$ "HbA1c" when the causal coefficient is modulated as $c = 1.25$ in SCP Pattern 2.

Output in Process B for $c = 1.25$ (Pattern 2)

The LiNGAM algorithm has suggested a direct causal relationship between age and hemoglobin A1c (HbA1c) with a positive coefficient of 1.25. This implies that as age increases, HbA1c levels are also expected to increase, according to the model.

From the perspective of domain knowledge in medicine and epidemiology, the relationship between age and HbA1c can be assessed for plausibility. Hemoglobin A1c is a measure of the average blood glucose levels over the past two to three months and is used as an indicator of blood sugar control in individuals with diabetes. It reflects the glycation of hemoglobin, a process that is influenced by the concentration of glucose in the blood.

As people age, several physiological changes can affect glucose metabolism:

1. Insulin Sensitivity: Aging is often associated with a decrease in insulin sensitivity, which is also known as insulin resistance. This can lead to higher blood glucose levels because the body's cells are less effective at absorbing glucose from the bloodstream.

2. Pancreatic Function: Beta-cell function in the pancreas may decline with age, leading to less insulin production. Insulin is necessary for glucose uptake in the cells, and a deficit can result in higher blood glucose levels.

3. Lifestyle Factors: Older adults may have changes in their lifestyle, such as decreased physical activity and altered dietary patterns, which can contribute to poorer glycemic control.

4. Comorbidities: With age, the prevalence of comorbid conditions that can impact glucose metabolism, such as obesity and chronic inflammation, tends to increase.

5. Hormonal Changes: Hormonal regulation changes with age and can affect glucose metabolism. For example, growth hormone levels and cortisol rhythms can influence blood sugar levels.

Given these factors, an increase in HbA1c with age can be considered plausible from a biological perspective. However, the coefficient of 1.25 is a standardized metric, and its interpretation depends on the scale of standardization. In a non-standardized real-world setting, this coefficient would typically be much smaller, as the actual increase in HbA1c due to aging alone might be modest. But without the context of the units and the standard deviations of the age and HbA1c variables, it's difficult to assess the magnitude of this relationship's impact.

It's also important to note that while the causal relationship suggested by LiNGAM is statistically inferred, causal claims should also be substantiated by domain knowledge and, if possible, experimental or longitudinal studies. The plausibility of the relationship in this context is supported by domain knowledge, but other factors not included in the model could also be influencing both age and HbA1c levels.

In conclusion, the statistical relationship discovered is consistent with domain knowledge about the physiology of aging and its effect on glucose metabolism. However, the strength and practical significance of this relationship would need further investigation, ideally through longitudinal studies and intervention trials, to confirm the causal pathways and to quantify the effect more precisely.

---

confidence probability generated in Process C: $\overline{p_{ij}} = 0.0493$

Table 8: Textual output in Process B of Simulation B in the case of "Age" → "HbA1c" when the causal coefficient is modulated as $c = 1.30$ in SCP Pattern 2.

Output in Process B for $c = 1.30$ (Pattern 2)

The result from the LiNGAM analysis suggests that there is a direct causal effect of age on hemoglobin A1c (HbA1c) levels with a coefficient of approximately 1.3. This implies that, in the structural causal model derived from your data, an increase in age is associated with an increase in HbA1c levels. To interpret this finding from a domain knowledge perspective, we need to consider the biological relationship between age and HbA1c and whether the magnitude and direction of the effect make sense.

Hemoglobin A1c is a form of hemoglobin that is chemically linked to glucose. The HbA1c test measures the average blood glucose levels over the past 2 to 3 months. It is commonly used as an indicator of long-term glucose control in individuals with diabetes and as a diagnostic tool for diabetes and prediabetes.

From a medical perspective, it is known that as people age, they tend to experience various physiological changes that can affect glucose metabolism. This includes changes such as increased insulin resistance, decreased insulin secretion, and altered hormonal control of blood glucose levels. These changes can contribute to higher blood glucose levels and therefore higher HbA1c levels in older adults.

The plausibility of the causal relationship suggested by the statistical analysis can be assessed by considering the following factors:

1. Biological Mechanism: There is a clear biological mechanism by which aging can affect glucose metabolism and insulin function, leading to higher HbA1c levels.

2. Consistency with Previous Research: The direction of the effect is consistent with epidemiological studies that have found a positive association between age and HbA1c levels.

3. Magnitude of the Effect: The coefficient of 1.3 is a standardized coefficient, representing the change in standard deviations of HbA1c for each standard deviation change in age. The magnitude of this effect should be interpreted within the context of the data distribution and the units of measurement. In general, the magnitude seems large, and it would be important to compare it to existing literature to see if such a change is reasonable.

4. Confounding Factors: The LiNGAM analysis assumes that all relevant variables have been measured and included in the model. If there are unmeasured confounders that are associated with both age and HbA1c, the estimated causal effect could be biased. For example, physical activity, diet, and other lifestyle factors can change with age and affect HbA1c levels.

5. Population-Specific Factors: The analysis is based on working-age adults (40 to 64 years old). The effect of age on HbA1c within this specific age range may differ from that in younger or older populations.

In conclusion, the statistically suggested hypothesis that age has a direct impact on HbA1c is biologically plausible and consistent with prior knowledge. However, further analysis should be conducted to ensure that all relevant confounding factors have been accounted for, and the magnitude of the effect should be compared with existing research to validate the results. Additionally, the clinical significance of this finding should be evaluated in the context of the overall health and management of individuals in the working-age population.

---

confidence probability generated in Process C: $\overline{p_{ij}} = 0.9833$

---

the basis of the probabilistic process. To illustrate this difficulty, we try to analyze the fluctuation observed around $c = 1.25$ in Figure 6(a) in terms of the generated text in Process B. While the $\overline{p_{ij}}$ becomes only 0.0493 when $c = 1.25$, $\overline{p_{ij}}$ becomes 0.9833 when $c = 1.30$. To elucidate the origin of this sudden behavior, we compare the generated text in Process B for $c = 1.25$ illustrated in Table 7, with the text for $c = 1.30$ illustrated in Table 8. It is confirmed that both contents of the texts in these tables do not include critical errors, from the medical domain experts' points of view. However, although only the value c is changed, the textual composition and the tones of generated knowledge in Process B radically change as follows:

- While the discussion is separated into the detailed aspects of the physiological factors of glucose metabolism in the generated text in Table 7, the text of Table 8 breaks down the issue into the validity of statistical causal inference, not only from the medical point of view, but also from the perspective of statistical causal inference methodology.

- While the statement in Table 7 is based on the connection between variables, Table 8 presents the discussion of causality more aggressively.

- While the validity pseudo-result of the SCD is carefully interpreted in terms of the interpretation of the magnitude of the causal coefficient in Table 7, the discussion in Table 8 is positively stated including the magnitude interpretation and consistency with the previous studies.

Consequently, it is inferred that these differences in aspects and tones lead to a significant gap in the confidence probabilities of GPT-4 at the same directed edge "Age" → "HbA1c." However, because the only difference in the SCP between Tables 7 and 8 is whether the causal coefficient of this edge is 1.25 or 1.30, the main factor of these gaps in aspects and tones is the complexity of sentence generation with a probabilistic process.

Therefore, considering the discussion above, it is practically challenging to quantitatively elucidate the tendencies of sentences generated in Process B (Step 2 in Figure 1), including the analysis of reproducibility, the factual likelihood and the tone of the generated knowledge as a long text. For the suppression and realistic evaluation of the fluctuation of GPT-4's confidence probability in Step 3 of the proposed method in this paper, other substitute prompt techniques should be considered.

For example, a more straightforward approach might be to integrate Steps 2 and 3 in Figure 1, applying the approach of "LLM-as-a-Judge" (Zheng et al., 2023a; Yuan et al., 2021; Kocmi & Federmann, 2023). Under the condition of maintaining the measurement of GPT-4's confidence probability in causal relationships in the proposed method, the position for the measurement of token generation probability and for the generation of "yes" or "no" in the generated text from GPT-4 must be fixed to the first or last one, from a practical point of view. Considering the limitations of ZSCoT and the property of the next generation of tokens from LLMs, fixing to the last token produces a better result than fixing to the first token, because the context generated before the token "yes" or "no" is expected to suppress hallucination.

However, continuous caution will still be required for the reproducibility of the last token generation probability. In general, the probability of token generation w_n is expressed by the conditional probability related to the prompt Q and the $\{w_1, w_2, ..., w_{n-1}\}$ as follows:

$$P(w_n|Q, w_1, w_2, ..., w_{n-1}) \tag{2}$$

Therefore, the probability that the last generated token w_L becomes "yes," is calculated as follows:

$$P(w_L = \text{yes}) = \sum_{\text{all}} \prod_{k=1}^{L-1} P(w_k|Q, w_1, w_2, ..., w_{k-1})P(w_L = \text{yes}|Q, w_1, w_2, ..., w_{L-1}) \tag{3}$$

In contrast, the only probability that can be repeatedly measured from a practical point of view, is $P(w_L = \text{yes}|Q, w_1, w_2, ..., w_{L-1})$ in Eq.(3). Although it is possible to evaluate the mean value or distribution of $P(w_L = \text{yes}|Q, w_1, w_2, ..., w_{L-1})$, which can be measured through repetitive measurements as carried out in this paper, there is no guarantee that the true value of $P(w_L = \text{yes})$ can be obtained approximately, as it has

not been clarified how $\prod_{k=1}^{L-1} P(w_k|Q, w_1, w_2, ..., w_{k-1})$ can be measured. Therefore, the integration of Steps 2 and 3 is hardly considered as a fundamental solution, since the effective method for the stabilization of tones and aspects of the generated knowledge for judgment is still lacking.

Consequently, regardless of the integration or separating of Steps 2 and 3, the prompting technique for the stabilization of the generated knowledge is expected to be constructed in detail. Although the discussion of this problem from this point forward requires further complex and careful examination beyond this paper, possible aspects are as follows:

- **Appropriately enumerating the perspectives that need consideration, distinguishing between those that depend on the domain's inherent characteristics and those that do not**
  This comprehensive listing of perspectives, and including them in the prompt can lead to appropriate domain-specific nuances, while maintaining the consistence of analytical knowledge generation and tone.

- **Confirmation of the characteristics of each variable and grouping, before the interpretation process following the listed perspectives as mentioned above**
  In the case of a health-screening dataset, for example, "SBP" and "DBP" are similar variables, that are simultaneously measured in the health screening process and share the same unit of measurement. Therefore, these two variables are expected to have similar causal relationships with other variables, and that "SBP" and "DBP" are somehow correlated, although the detailed causal structure, including "SBP" and "DBP" has not been completely determined. However, as discussed earlier, the variable "Age" has a completely different characteristic from the other variables. This variable is mechanically determined from the birthday and the passage of time. Confirmation of LLMs' understanding of such properties of the variables is expected to contribute to the suppression of hallucinations.

- **A careful examination of how the SCD results in the SCP are interpreted, particularly in handling anomalies that arise owing to limitations of the models for SCD**
  For example, the causal graph discovered through any SCD algorithm without prior knowledge, sometimes displays inappropriate directed edges with a large bootstrap probability, whose orientations are judged as obviously reversed from the experts' point of view, because of the strong statistical correlation between the pairs of variables. Since the SCP proposed in our method includes all the results of SCD, it is expected that the statistical information included in the prompts is handled effectively and appropriately, considering the tendency and limitations of SCD. Addressing these issues necessitates meticulous discussion to solidify a comprehensive understanding of the results, highlighting a significant area for future research.

- **Transforming the standardized coefficients back to values in their original dimensions and including them into the prompts (for Patterns 2 and 4)**
  In the method proposed in this study, the causal coefficients are calculated via DirectLiNGAM, with the datasets standardized before causal discovery, and without transforming them back to the values with original units. We have intentionally adopted the standardized causal coefficients, to ensure consistent scaling, which can lead to a relative comparison of the causal coefficients between different directed edges. However, as shown in Table 7, GPT-4 can insist, "without the context of the units and the standard deviations of the age and HbA1c variables, it is difficult to assess the magnitude of this relationship's impact." Therefore, if it is expected that LLMs possess benchmarks or knowledge for judging the validity of prompted coefficients in some units, including the coefficients that are transformed back into the original dimensions into the prompt may enhance the capability of quantitative judgment.

Once this framework is in place, adopting the technique of few-shot prompting (Brown et al., 2020) with accurate examples can further improve the stability and reliability of the model output. By providing the LLMs with ideal and correct exemplars, one can improve their ability to generate stabilized, consistent, and accurate responses, which contributes to the practical discussion of the reproducibility of LLM-KBCI.

To achieve even greater consistency in the outputs, the instruction tuning (Wei et al., 2022) can also be adopted as an alternative to few-shot prompting. Instruction tuning involves fine-tuning the model via a dataset of instruction-response pairs, aligning the model's behavior more closely with specific analytical requirements. However, this approach presents practical challenges: the cost of data generation for instruction tuning is much higher than that for few-shot prompting, and only fully open-source models (such as Llama2 (Touvron et al., 2023) etc.) currently allow such fine-tuning. Therefore, while instruction tuning offers potential advantages in further stabilizing model outputs, its implementation is limited by resource constraints and model availability.

Moreover, fine-tuning or employing retrieval-augmented generation (RAG) with some domain-specific knowledge sources can be expected to enhance the domain knowledge of the LLM. These approaches could enable LLMs to make more appropriate judgments between various pairs of variables. In particular, adopting RAG can also contribute to the stabilization of the tones of knowledge generation, since the range of information searches can be limited.

Toward Appropriate Application of the Proposed Method

As illustrated above, while GPT-4 has completely denied apparently unnatural directed edges from the domain knowledge such as "HbA1c" → "Age" under any conditions, it has not always been confidently judged in the ground truth edges where causal relationships should exist, such as "Age" → "HbA1c." Moreover, SCP can sometimes unnecessarily decrease the confidence probability of a ground truth edge in LLM-KBCI, although it is still unknown what kind of ground truth causal relationships are likely to be worsened. Therefore, using our proposed method as a "black-box" may lead to unintended erroneous analysis results.

To prevent this crucial risk as much as possible, in addition to further technical clarification as discussed above, benchmarking the basic knowledge of LLMs in the domain in which the application of the proposed method is to be applied, is also important. Furthermore, before applying our method to construct data-driven causal models, especially when there are firm prior knowledge edges that must be reflected, it is advisable to conduct preliminary experiments as performed in Simulations A and B. In addition, having experts review the actual results of the proposed method, including the textual output of Step 2 can be effective. Through these processes, it becomes possible to discuss what domain knowledge should be additionally learned by LLMs, for more precise and effective completion of the proposed method in each domain.

However, although high confidence can be achieved without critical errors through the approaches of adopting expert checks, especially when particularly focusing on small systems, the domain expert check becomes more impractical, as the number of variables increases, since the combinations of variable pairs increase quadratically. Since the strength of the proposed method in this paper lies in automating areas where expert verification becomes unmanageable owing to the large number of variables, premising expert checks in large-scale systems is counterproductive.

Therefore, continuing technical examinations, to overcome these issues, as discussed in this section, remain important, This ongoing effort is essential to enhance the reliability and practical applicability of our proposed method.

Finally, in terms of perfect realization of the expected role of the SCP, LLMs are also required to recognize the validity of the causal models prompted in the first step, and to point out the inadequate part. To achieve these capabilities, accumulation of the modification process by domain experts as mentioned above, and structuring as a dataset for additional reinforcement learning of LLMs are also valuable. This framework can be interpreted as reinforcement learning with human feedback (RLHF) of causal graphs, and is expected to contribute to further suppression of hallucinations, toward the practical application of SCP in any domain.

5 Conclusion

In this study, a novel methodology of causal inference, in which SCD and LLM-KBCI are synthesized with SCP, and prior knowledge augmentation was developed and demonstrated.

It has been revealed that GPT-4 can cause the output of LLM-KBCI and the SCD result with prior knowledge from LLM-KBCI to approach the ground truth, and that the SCD result can be further improved, if GPT-4 undergoes SCP. Furthermore, with an unpublished real-world dataset, we have demonstrated that GPT-4 with SCP can assist in SCD with respect to domain expertise and statistics, and that the proposed method is effective even if the dataset has never been included in the training data of the LLM and the sample size is not sufficiently large to obtain reasonable SCD results.

In addition, we have further simulated the SCP under various conditions, and confirmed both successful and failure cases on the basis of the SCD results on the health-screening dataset with LiNGAM. In successful cases, the existence of patterns where SCP firmly works as intended has been confirmed, especially when the hypothesis of the causal relationship (such as the hypothesis that "Age" is influenced by other factors) is apparently unnatural. In contrast, through the discussion of the failure cases, the technical limitations and risks of critical errors have been thoroughly discussed. Through these discussions, we have presented the expected improvements in techniques around LLMs, and the suggestion of realistic integration of domain expert checks of the results into this automatic methodology.

Technical Limitations of This Work

The details of the technical limitations and future directions for improving the proposed method in this paper are illustrated in Section 4.3. Here, we briefly discuss the general limitations and risks of adopting LLMs in causal inference tasks as the proposed method in this paper.

We fixed the LLM in our experiment to GPT-4 for its extensive general knowledge and capabilities in common-sense reasoning, and our experiments on several real-world datasets, typically within the realm of common-sense reasoning, have illustrated the potential utility of the proposed method across various scientific domains. We expect that the proposed method will work even if other LLMs are adopted, since the capability of LLM-KBCI has already been demonstrated in several models (Zečević et al., 2023). Considering the continuous emergence of new LLMs and the rapid update of existing LLMs, it is expected that the universal effectiveness of the proposed method across different LLMs will be verified.

Moreover, it is also important to recognize the risks of using current LLMs in our methods: hallucinations at Steps 2 and 3 in Figure 1 can worsen the results of LLM-KBCI and SCD. Considering that hallucinations arise from factors such as memorization of training data (McKenna et al., 2023; Carlini et al., 2023), statistical biases (Jones & Steinhardt, 2022; McMilin, 2022), and predictive uncertainty (Yang et al., 2023; Lin et al., 2024), it is essential to be especially careful when our method is applied in highly specialized academic domains (George & Stuhlmueller, 2023; Pal et al., 2023). To reduce these risks when the proposed method is applied in domains with deeper specificity in the future, it is necessary to further improve our method to avoid hallucinations more effectively. Although we have already introduced ZSCoT (Kojima et al., 2022) and generated knowledge prompting (Liu et al., 2022), employing optimal LLMs that are specifically pretrained with materials on specific domains is one possible solution, or incorporating techniques such as fine-tuning and RAG could be necessary. Therefore, systematic research in the context of optimal LLM-KBCI is also required on the selection of the optimal LLMs for each domain and on the techniques for utilizing the LLMs.

Furthermore, for the generalization of the method we have proposed, we also note that although SCP is indeed likely to enhance the performance of SCD more than the prompting without SCP, whether this improvement is observed can depend on the datasets used for SCD. Moreover, there remains a discussion on the potential for overfitting in SCP, especially with small or biased datasets. Although we have shown the effectiveness of SCP on a subsample of the health screening dataset, which contains bias, it is still an open question under what conditions of the LLMs and prompt techniques can guarantee robustness for small or biased datasets. In terms of the more reliable application of the proposed method, further basic research on the effects of causal coefficients or bootstrap probabilities on the results of the LLM-KBCI is required.

Broader Impact Statement

This paper proposed a novel approach that integrates SCD methods with LLMs. This research has the potential to contribute to more accurate causal inference in fields where understanding causality is crucial, such

as healthcare, economics, and environmental science. However, the use of LLMs such as GPT-4 necessitates the extensive consideration of data privacy and biases. Moreover, it should also be noted that incorrect causal inferences, caused by hallucinations, biased training data, or inappropriate use of LLMs, could lead to significant consequences for society. In particular, these risks arise when the proposed method is used for completely "black-box" decision making. To prevent these risks, the transparency and interpretability of the whole system should be clarified.

This study highlights the responsible use of artificial intelligence, considering ethical implications and societal impacts. With appropriate guidelines and ethical standards, the proposed methodology can advance scientific understanding and provide extensive widespread benefits to society.

References

Ahmed Abdulaal, adamos hadjivasiliou, Nina Montana-Brown, Tiantian He, Ayodeji Ijishakin, Ivana Drobnjak, Daniel C. Castro, and Daniel C. Alexander. Causal modelling agents: Causal graph discovery through synergising metadata- and data-driven reasoning. In *The Twelfth International Conference on Learning Representations*, 2024. URL `https://openreview.net/forum?id=pAoqRlTBtY`.

Umar I. Abdullahi, Spyros Samothrakis, and M. Fasli. Causal inference with correlation alignment. In *Proc. 2020 IEEE International Conference on Big Data (Big Data)*, pp. 4971–4980, 2020. doi: 10.1109/BigData50022.2020.9378334.

Dawn E. Alley, Luigi Ferrucci, Mario Barbagallo, Stephanie A. Studenski, and Tamara B. Harris. A Research Agenda: The Changing Relationship Between Body Weight and Health in Aging. *The Journals of Gerontology: Series A*, 63(11):1257–1259, 11 2008. ISSN 1079-5006. doi: 10.1093/gerona/63.11.1257. URL `https://doi.org/10.1093/gerona/63.11.1257`.

Maksym Andriushchenko, Francesco Croce, and Nicolas Flammarion. Jailbreaking leading safety-aligned llms with simple adaptive attacks. *arXiv preprint*, 2024. doi: 10.48550/arXiv.2404.02151.

Taiyu Ban, Lyuzhou Chen, Derui Lyu, Xiangyu Wang, and Huanhuan Chen. Causal structure learning supervised by large language model. *arXiv preprint*, 2023. doi: 10.48550/arXiv.2311.11689.

Peter M. Bentler. Comparative fit indexes in structural models. *Psychological bulletin*, 107 2:238–46, 1990. doi: 10.1037/0033-2909.107.2.238.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel Ziegler, Jeffrey Wu, Clemens Winter, Chris Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 1877–1901. Curran Associates, Inc., 2020. URL `https://proceedings.neurips.cc/paper_files/paper/2020/file/1457c0d6bfcb4967418bfb8ac142f64a-Paper.pdf`.

Nicholas Carlini, Daphne Ippolito, Matthew Jagielski, Katherine Lee, Florian Tramer, and Chiyuan Zhang. Quantifying memorization across neural language models. In *The Eleventh International Conference on Learning Representations*, 2023. URL `https://openreview.net/forum?id=TatRHT_1cK`.

Lu Cheng, Ruocheng Guo, Raha Moraffah, Paras Sheth, K. Selçuk Candan, and Huan Liu. Evaluation methods and measures for causal learning algorithms. *IEEE Transactions on Artificial Intelligence*, 3(6):924–943, 2022. doi: 10.1109/TAI.2022.3150264.

David Maxwell Chickering. Optimal structure identification with greedy search. *The Journal of Machine Learning Research*, 3:507–554, 2002. URL `https://dl.acm.org/doi/10.1162/153244303321897717`.

Jawad Chowdhury, Rezaur Rashid, and Gabriel Terejanu. Evaluation of induced expert knowledge in causal structure learning by NOTEARS. *arXiv preprint*, 2023. doi: 10.48550/arXiv.2301.01817.

Philippa Clarke, Patrick M O'Malley, Lloyd D Johnston, and John E Schulenberg. Social disparities in BMI trajectories across adulthood by gender, race/ethnicity and lifetime socio-economic position: 1986–2004. *International Journal of Epidemiology*, 38(2):499–509, 10 2008. ISSN 0300-5771. doi: 10.1093/ije/dyn214. URL `https://doi.org/10.1093/ije/dyn214`.

Kai-Hendrik Cohrs, Emiliano Diaz, Vasileios Sitokonstantinou, Gherardo Varando, and Gustau Camps-Valls. Large language models for constrained-based causal discovery. In *AAAI 2024 Workshop on "Are Large Language Models Simply Causal Parrots?"*, 2023. URL `https://openreview.net/forum?id=NEAoZRWHPN`.

N. Dubowitz, W. Xue, Q. Long, J. G. Ownby, D. E. Olson, D. Barb, M. K. Rhee, A. V. Mohan, P. I. Watson-Williams, S. L. Jackson, A. M. Tomolo, T. M. Johnson II, and L. S. Phillips. Aging is associated with increased hba1c levels, independently of glucose levels and insulin resistance, and also with decreased hba1c diagnostic specificity. *Diabetic Medicine*, 31(8):927–935, 2014. doi: https://doi.org/10.1111/dme.12459.

Gemini Team, Google. Gemini: A family of highly capable multimodal models. *arXiv preprint*, 2023. doi: 10.48550/arXiv.2312.11805.

Charlie George and Andreas Stuhlmueller. Factored verification: Detecting and reducing hallucination in summaries of academic papers. In Tirthankar Ghosal, Felix Grezes, Thomas Allen, Kelly Lockhart, Alberto Accomazzi, and Sergi Blanco-Cuaresma (eds.), *Proceedings of the Second Workshop on Information Extraction from Scientific Publications*, pp. 107–116, Bali, Indonesia, November 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.wiesp-1.13. URL https://aclanthology.org/2023.wiesp-1.13.

Penny Gordon-Larsen, Natalie S. The, and Linda S. Adair. Longitudinal trends in obesity in the united states from adolescence to the third decade of life. *Obesity*, 18(9):1801–1804, 2010. doi: https://doi.org/10.1038/oby.2009.451.

Michael Gurven, Aaron D. Blackwell, Daniel Eid Rodríguez, Jonathan Stieglitz, and Hillard Kaplan. Does blood pressure inevitably rise with age? *Hypertension*, 60(1):25–33, 2012. doi: 10.1161/HYPERTENSIONAHA.111.189100.

Uzma Hasan, Emam Hossain, and Md Osman Gani. A survey on causal discovery methods for i.i.d. and time series data. *Transactions on Machine Learning Research*, 2023. ISSN 2835-8856.

David W. Hosmer and Stanley Lemeshow. *Applied logistic regression (Wiley Series in probability and statistics)*. Wiley-Interscience Publication, 2 edition, 2000.

Patrik Hoyer, Dominik Janzing, Joris M Mooij, Jonas Peters, and Bernhard Schölkopf. Nonlinear causal discovery with additive noise models. In *Proc. NIPS 2008*, volume 21 of *Advances in Neural Information Processing Systems*, 2008. URL https://proceedings.neurips.cc/paper_files/paper/2008/file/f7664060cc52bc6f3d620bcedc94a4b6-Paper.pdf.

Biwei Huang, Kun Zhang, Yizhu Lin, Bernhard Schölkopf, and Clark Glymour. Generalized score functions for causal discovery. In *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining (KDD '18)*, pp. 1551–1560, 2018. doi: 10.1145/3219819.3220104.

Takashi Ikeuchi, Mayumi Ide, Yan Zeng, Takashi Nicholas Maeda, and Shohei Shimizu. Python package for causal discovery based on LiNGAM. *Journal of Machine Learning Research*, 24(14):1–8, 2023. URL http://jmlr.org/papers/v24/21-0321.html.

Takanori Inazumi, Shohei Shimizu, and Takashi Washio. Use of prior knowledge in a non-Gaussian method for learning linear structural equation models. In *Proc. International Conference on Latent Variable Analysis and Signal Separation (LVA/ICA 2010)*, volume 6365 of *LNCTS (Lecture Notes in Computer Science)*, pp. 221–228, 2010. doi: 10.1007/978-3-642-15995-4_28.

Haitao Jiang, Lin Ge, Yuhe Gao, Jianian Wang, and Rui Song. Large language model for causal decision making. *arXiv preprint*, 2023. doi: 10.48550/arXiv.2312.17122.

Zhijing Jin, Jiarui Liu, Zhiheng LYU, Spencer Poff, Mrinmaya Sachan, Rada Mihalcea, Mona T. Diab, and Bernhard Schölkopf. Can large language models infer causation from correlation? In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=vqIH0ObdqL.

Thomas Jiralerspong, Xiaoyin Chen, Yash More, Vedant Shah, and Yoshua Bengio. Efficient causal graph discovery using large language models. *arXiv preprint*, 2024. doi: 10.48550/arXiv.2402.01207.

Erik Jones and Jacob Steinhardt. Capturing failures of large language models via human cognitive biases. In S. Koyejo, S. Mohamed, A. Agarwal, D. Belgrave, K. Cho, and A. Oh (eds.), *Advances in Neural Information Processing Systems*, volume 35, pp. 11785–11799. Curran Associates, Inc., 2022. URL https://proceedings.neurips.cc/paper_files/paper/2022/file/4d13b2d99519c5415661dad44ab7edcd-Paper-Conference.pdf.

Jean Kaddour, J. Harris, Maximilian Mozes, Herbie Bradley, Roberta Raileanu, and R. McHardy. Challenges and applications of large language models. *arXiv preprint*, 2023. doi: 10.48550/arXiv.2307.10169.

Christoph Käding and Jakob Runge. Distinguishing cause and effect in bivariate structural causal models: A systematic investigation. *Journal of Machine Learning Research*, 24(278):1–144, 2023. URL http://jmlr.org/papers/v24/22-0151.html.

Elahe Khatibi, Mahyar Abbasian, Zhongqi Yang, Iman Azimi, and Amir M. Rahmani. Alcm: Autonomous llm-augmented causal discovery framework. *arXiv preprint*, 2024. doi: 10.48550/arXiv.2404.01744.

Vivek Khetan, Roshni Ramnani, Mayuresh Anand, Subhashis Sengupta, and Andrew E. Fano. Causal bert: Language models for causality detection between events expressed in text. In Kohei Arai (ed.), *Intelligent Computing*, pp. 965–980, Cham, 2022. Springer International Publishing. ISBN 978-3-030-80119-9.

Tom Kocmi and Christian Federmann. Large language models are state-of-the-art evaluators of translation quality. In *Proceedings of the 24th Annual Conference of the European Association for Machine Translation*, pp. 193–203, Tampere, Finland, June 2023. European Association for Machine Translation. URL https://aclanthology.org/2023.eamt-1.19.

Takeshi Kojima, Shixiang (Shane) Gu, Machel Reid, Yutaka Matsuo, and Yusuke Iwasawa. Large language models are zero-shot reasoners. In *Proc. NeurIPS 2022*, volume 35 of *Advances in Neural Information Processing Systems*, pp. 22199–22213, 2022.

Emre Kıcıman, Robert Ness, Amit Sharma, and Chenhao Tan. Causal reasoning and large language models: Opening a new frontier for causality. *arXiv preprint*, 2023. doi: 10.48550/arXiv.2305.00050.

Zhen Lin, Shubhendu Trivedi, and Jimeng Sun. Generating with confidence: Uncertainty quantification for black-box large language models. *Transactions on Machine Learning Research*, 2024. ISSN 2835-8856. URL https://openreview.net/forum?id=DWkJCSxKU5.

Jiacheng Liu, Alisa Liu, Ximing Lu, Sean Welleck, Peter West, Ronan Le Bras, Yejin Choi, and Hannaneh Hajishirzi. Generated knowledge prompting for commonsense reasoning. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (ACL 2022)*, volume 1 (Long Papers), pp. 3154–3169, May 2022. doi: 10.18653/v1/2022.acl-long.225.

Stephanie Long, Alexandre Piché, Valentina Zantedeschi, Tibor Schuster, and Alexandre Drouin. Causal discovery with language models as imperfect experts. In *ICML 2023 Workshop on Structured Probabilistic Inference & Generative Modeling*, 2023. URL https://openreview.net/forum?id=RXlvYZAE49.

Nick McKenna, Tianyi Li, Liang Cheng, Mohammad Javad Hosseini, Mark Johnson, and Mark Steedman. Sources of hallucination by large language models on inference tasks. In *The 2023 Conference on Empirical Methods in Natural Language Processing*, 2023. URL https://openreview.net/forum?id=rJhk7Fpnvh.

Emily McMilin. Selection bias induced spurious correlations in large language models. In *ICML 2022: Workshop on Spurious Correlations, Invariance and Stability*, 2022. URL https://openreview.net/forum?id=8nnaDv9dUli.

Joris M. Mooij, Jonas Peters, Dominik Janzing, Jakob Zscheischler, and Bernhard Schölkopf. Distinguishing cause from effect using observational data: Methods and benchmarks. *Journal of Machine Learning Research*, 17(32):1–102, 2016. URL http://jmlr.org/papers/v17/14-518.html.

OpenAI. GPT-4 technical report. *arXiv preprint*, 2023. doi: 10.48550/arXiv.2303.08774.

Ankit Pal, Logesh Kumar Umapathi, and Malaikannan Sankarasubbu. Med-HALT: Medical domain hallucination test for large language models. In Jing Jiang, David Reitter, and Shumin Deng (eds.), *Proceedings of the 27th Conference on Computational Natural Language Learning (CoNLL)*, pp. 314–334, Singapore, December 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.conll-1.21. URL https://aclanthology.org/2023.conll-1.21.

Lydie N. Pani, Leslie Korenda, James B. Meigs, Cynthia Driver, Shadi Chamany, Caroline S. Fox, Lisa Sullivan, Ralph B. D'Agostino, and David M. Nathan. Effect of Aging on A1C Levels in Individuals Without Diabetes: Evidence from the Framingham Offspring Study and the National Health and Nutrition Examination Survey 2001–2004. *Diabetes Care*, 31(10):1991–1996, 10 2008. ISSN 0149-5992. doi: 10.2337/dc08-0577. URL https://doi.org/10.2337/dc08-0577.

Pouya Pezeshkpour. Measuring and modifying factual knowledge in large language models. In *2023 International Conference on Machine Learning and Applications (ICMLA)*, pp. 831–838, 2023. doi: 10.1109/ICMLA58977.2023.00122.

R. Quinlan. Auto MPG. UCI Machine Learning Repository, 1993. doi: 10.24432/C5859H.

Alec Radford, Jeff Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. Language models are unsupervised multitask learners. 2019.

P. RaviKumar, A. Bhansali, R. Walia, G. Shanmugasundar, and M. Ravikiran. Alterations in hba1c with advancing age in subjects with normal glucose tolerance: Chandigarh urban diabetes study (cuds). *Diabetic Medicine*, 28(5):590–594, 2011. doi: https://doi.org/10.1111/j.1464-5491.2011.03242.x.

Alexander G. Reisach, Christof Seiler, and Sebastian Weichwald. Beware of the simulated DAG! causal discovery benchmarks may be easy to game. In *Proc. NeurIPS 2021*, volume 34 of *Advances in Neural Information Processing Systems*, 2021.

Daniela Rodrigues, Noemi Kreif, Anna Lawrence-Jones, Mauricio Barahona, and Erik Mayer. Reflection on modern methods: constructing directed acyclic graphs (DAGs) with domain experts for health services research. *International Journal of Epidemiology*, 51(4):1339–1348, 06 2022. ISSN 0300-5771. doi: 10.1093/ije/dyac135.

J. Rohrer. Thinking clearly about correlations and causation: Graphical causal models for observational data. *Advances in Methods and Practices in Psychological Science*, 1:27 – 42, 2017. doi: 10.1177/2515245917745629.

Paul Rolland, Volkan Cevher, Matthäus Kleindessner, Chris Russell, Dominik Janzing, Bernhard Schölkopf, and Francesco Locatello. Score matching enables causal discovery of nonlinear additive noise models. In *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *PMLR (Proceedings of Machine Learning Research)*, pp. 18741–18753. PMLR, 17–23 Jul 2022. URL https://proceedings.mlr.press/v162/rolland22a.html.

Karen Sachs, Omar Perez, Dana Pe'er, Douglas A. Lauffenburger, and Garry P. Nolan. Causal protein-signaling networks derived from multiparameter single-cell data. *Science*, 308(5721):523–529, 2005. doi: 10.1126/science.1105809.

Gideon Schwarz. Estimating the Dimension of a Model. *The Annals of Statistics*, 6(2):461 – 464, 1978. doi: 10.1214/aos/1176344136.

Marco Scutari and Jean-Baptiste Denis. *Bayesian Networks with Examples in R*. Chapman and Hall, Boca Raton, 2014.

Shohei Shimizu, Patrik O. Hoyer, Aapo Hyvärinen, and Antti Kerminen. A linear non-Gaussian acyclic model for causal discovery. *Journal of Machine Learning Research*, 7(72):2003–2030, 2006. URL https://dl.acm.org/doi/10.5555/1248547.1248619.

Shohei Shimizu, Takanori Inazumi, Yasuhiro Sogawa, Aapo Hyvärinen, Yoshinobu Kawahara, Takashi Washio, Patrik O. Hoyer, and Kenneth Bollen. DirectLiNGAM: A direct method for learning a linear non-gaussian structural equation model. *Journal of Machine Learning Research*, 12(33):1225–1248, 2011. URL https://dl.acm.org/doi/10.5555/1953048.2021040.

Tomi Silander and Petri Myllymäki. A simple approach for finding the globally optimal Bayesian network structure. In *Proceedings of the Twenty-Second Conference on Uncertainty in Artificial Intelligence (UAI '06)*, pp. 445–452, 2006.

P. Spirtes, C. Glymour, and R. Scheines. *Causation, Prediction, and Search*. MIT press, 2nd edition, 2000.

Peter Spirtes, Clark Glymour, Richard Scheines, and Robert Tillman. Automated Search for Causal Relations: Theory and Practice. In Rina Dechter, Hector Geffner, and Joseph Y. Halpern (eds.), *Heuristics, Probability and Causality: A Tribute to Judea Pearl*, chapter 28, pp. 467–506. College Publications, 2010.

J. H. Steiger and J. C. Lind. Statistically based tests for the number of common factors. In *The Annual Meeting of the Psychometric Society*, 1980.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, Dan Bikel, Lukas Blecher, Cristian Canton Ferrer, Moya Chen, Guillem Cucurull, David Esiobu, Jude Fernandes, Jeremy Fu, Wenyin Fu, Brian Fuller, Cynthia Gao, Vedanuj Goswami, Naman Goyal, Anthony Hartshorn, Saghar Hosseini, Rui Hou, Hakan Inan, Marcin Kardas, Viktor Kerkez, Madian Khabsa, Isabel Kloumann, Artem Korenev, Punit Singh Koura, Marie-Anne Lachaux, Thibaut Lavril, Jenya Lee, Diana Liskovich, Yinghai Lu, Yuning Mao, Xavier Martinet, Todor Mihaylov, Pushkar Mishra, Igor Molybog, Yixin Nie, Andrew Poulton, Jeremy Reizenstein, Rashi Rungta, Kalyan Saladi, Alan Schelten, Ruan Silva, Eric Michael Smith, Ranjan Subramanian, Xiaoqing Ellen Tan, Binh Tang, Ross Taylor, Adina Williams, Jian Xiang Kuan, Puxin Xu, Zheng Yan, Iliyan Zarov, Yuchen Zhang, Angela Fan, Melanie Kambadur, Sharan Narang, Aurelien Rodriguez, Robert Stojnic, Sergey Edunov, and Thomas Scialom. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint*, 2023. doi: 10.48550/arXiv.2307.09288.

Ruibo Tu, Kun Zhang, Hedvig Kjellstrom, and Cheng Zhang. Optimal transport for causal discovery. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=qwBK94cP1y.

Lewis Tunstall, Leandro von Werra, and Thomas Wolf. *Natural Language Processing with Transformers: Building Language Applications with Hugging Face*. O'Reilly Media, Incorporated, 2022. ISBN 1098103246. URL https://books.google.ch/books?id=7hhyzgEACAAJ.

Aniket Vashishtha, Abbavaram Gowtham Reddy, Abhinav Kumar, Saketh Bachu, Vineeth N. Balasubramanian, and Amit Sharma. Causal inference using LLM-guided discovery. In *AAAI 2024 Workshop on "Are Large Language Models Simply Causal Parrots?"*, 2023. URL https://openreview.net/forum?id=4B296hrTIS.

Jason Wei, Maarten Bosma, Vincent Zhao, Kelvin Guu, Adams Wei Yu, Brian Lester, Nan Du, Andrew M. Dai, and Quoc V Le. Finetuned language models are zero-shot learners. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=gEZrGCozdqR.

Feng Xie, Ruichu Cai, Biwei Huang, Clark Glymour, Zeng Hao, and Kun Zhang. Generalized independent noise condition for estimating latent variable causal graphs. In *Proc. NeurIPS 2020*, volume 33 of *Advances in Neural Information Processing Systems*, 2020.

Qi Yang, Shreya Ravikumar, Fynn Schmitt-Ulms, Satvik Lolla, Ege Demir, Iaroslav Elistratov, Alex Lavaee, Sadhana Lolla, Elaheh Ahmadi, Daniela Rus, Alexander Amini, and Alejandro Perez. Uncertainty-aware language modeling for selective question answering. *arXiv preprint*, 2023. doi: 10.48550/arXiv.2311.15451.

Yang Claire Yang, Christine E. Walsh, Moira P. Johnson, Daniel W. Belsky, Max Reason, Patrick Curran, Allison E. Aiello, Marianne Chanti-Ketterl, and Kathleen Mullan Harris. Life-course trajectories of

body mass index from adolescence to old age: Racial and educational disparities. *Proceedings of the National Academy of Sciences*, 118(17):e2020167118, 2021. doi: 10.1073/pnas.2020167118. URL `https://www.pnas.org/doi/abs/10.1073/pnas.2020167118`.

Changhe Yuan and Brandon Malone. Learning optimal Bayesian networks: A shortest path perspective. *Journal of Artificial Intelligence Research*, 48:23–65, 10 2013. doi: 10.1613/jair.4039.

Weizhe Yuan, Graham Neubig, and Pengfei Liu. BARTScore: Evaluating generated text as text generation. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems*, 2021. URL `https://openreview.net/forum?id=5Ya8PbvpZ9`.

Matej Zečević, Moritz Willig, Devendra Singh Dhami, and Kristian Kersting. Causal parrots: Large language models may talk causality but are not causal. *Transactions on Machine Learning Research*, 2023. ISSN 2835-8856. URL `https://openreview.net/forum?id=tv46tCzs83`.

Yuzhe Zhang, Yipeng Zhang, Yidong Gan, Lina Yao, and Chen Wang. Causal graph discovery with retrieval-augmented generation based large language models. *arXiv preprint*, 2024. doi: 10.48550/arXiv.2402.15301.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. Judging LLM-as-a-judge with MT-bench and chatbot arena. In *Thirty-seventh Conference on Neural Information Processing Systems Datasets and Benchmarks Track*, 2023a. URL `https://openreview.net/forum?id=uccHPGDlao`.

Xun Zheng, Bryon Aragam, Pradeep K Ravikumar, and Eric P Xing. Dags with no tears: Continuous optimization for structure learning. In *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc., 2018. URL `https://proceedings.neurips.cc/paper_files/paper/2018/file/e347c51419ffb23ca3fd5050202f9c3d-Paper.pdf`.

Yujia Zheng, Biwei Huang, Wei Chen, Joseph Ramsey, Mingming Gong, Ruichu Cai, Shohei Shimizu, Peter Spirtes, and Kun Zhang. Causal-learn: Causal discovery in python. *arXiv preprint*, 2023b. doi: 10.48550/arXiv.2307.16405.

A   Ethics Review

Ethical Considerations in Methodology and AI Use   This paper proposes a novel approach that integrates SCD with LLMs. We have thoroughly considered the issues of data privacy and biases associated with the use of LLMs. The proposed methodology enhances the accuracy and efficiency of causal discovery; however, it does not introduce explicit ethical implications beyond those generally applicable to machine learning. We are committed to the responsible use of AI and welcome the scrutiny of the ethics review committee.

Institutional Review and Consent Compliance of Health Screening Data   The institutional review board approved this study, and in accordance with the double-blind review process of TMLR, the name of the institution has been withheld. The identity of the institution will be disclosed upon successful completion of the peer review. As we only analyzed anonymized data from the database, the need for informed consent was waived.

B Details of the Contents in Each Prompting Pattern

In this section, the details of the prompting in each pattern are presented. For Pattern 0, another prompting template is detailed instead of the sentences shown in Table 1. Moreover, for Patterns 1, 2, 3, and 4, the contents filled in ⟨blank 5⟩ and ⟨blank 9⟩ of the prompt template for SCP shown in Table 1 are described.

For Pattern 0 Compared with other patterns of SCP, Pattern 0 does not include any results of SCD without prior knowledge. As a result, the prompt template in Table 1 is not suitable for Pattern 0, as it includes blanks filled with descriptions of the dataset and the SCD result. Thus, we prepare another prompt template for Pattern 0, which is completely independent of the SCD result, and require GPT-4 to generate the response solely from its domain knowledge. Table 9 presents the prompt template in Pattern 0, which is composed mainly of the ZSCoT concept. Because it does not include information on the SCD method and relies solely on domain knowledge in GPT-4, the probability matrix obtained from GPT-4 in Pattern 0 is applied independently of the SCD method.

Table 9: The prompt template of $Q_{ij}^{(1)}(x_i, x_j)$ for Pattern 0 for the generation of expert knowledge of the causal effect from x_j on x_i. The "blanks" enclosed with ⟨ ⟩ are filled with description words of the theme of the causal inference and variable names.

Prompt Template of $q_{ij}^{(1)} = Q_{ij}^{(1)}(x_i, x_j)$ in Pattern 0 (for all SCD methods)
We want to carry out causal inference on ⟨blank 1. The theme⟩, considering ⟨blank 2. The description of all variables⟩ as variables.
If ⟨blank 7. The name of x_j⟩ is modified, will it have a direct impact on ⟨blank 8. The name of x_i⟩?
Please provide an explanation that leverages your expert knowledge on the causal relationship between ⟨blank 7. The name of x_j⟩ and ⟨blank 8. The name of x_i⟩.
Your response should consider the relevant factors and provide a reasoned explanation based on your understanding of the domain.

For Patterns 1–4 (in the case of Exact Search and DirectLiNGAM) Following the concept of each SCP pattern, the contents filled in ⟨blank 5⟩ shown in Table 1 are summarized in Table 10. In this table, the names of the causes and effected variables are represented as ⟨ cause i ⟩ and ⟨ effect i ⟩, respectively, and the bootstrap probability of this causal relationship in SCD P_i and the causal coefficient of LiNGAM b_i can be included in Patterns 2–4. In Patterns 2 and 4, only the causal relationships with $P_i \neq 0$ are listed in ⟨ blank 5 ⟩. In Pattern 3, the causal relationships with $b_i \neq 0$ are listed in ⟨ blank 5 ⟩.

The contents of ⟨blank 6⟩ and ⟨blank 9⟩ also depend on the SCP patterns, and are shown in Table 11. Here, we define the bootstrap probability of $x_j \to x_i$ as P_{ij}. We also define the causal coefficient of $x_j \to x_i$ in LiNGAM as b_{ij}, because the structural equation of LiNGAM is usually defined as[16]:

$$x_i = \sum_{i \neq j} b_{ij} x_j + e_i \tag{4}$$

Prompt template in the case of the PC algorithm Although the causal relationships are ultimately represented only as directed edges in Exact Search and DirectLiNGAM, the situation changes slightly when we adopt the PC algorithm along with the codes in "causal-learn." This is because the PC algorithm can also output undirected edges, when the causal direction between a pair of variables cannot be determined. Therefore, we have tentatively decided to include not only directed edges but also undirected edges in SCP. Additionally, we have prepared another prompt template for SCP in the case of PC, as shown in Table 12.

---

[16]Here, the error distribution function e_i is also assumed to be non-Gaussian.

Table 10: Contents filled in ⟨blank 5⟩ shown in Table 1, when Exact Search or DirectLiNGAM is adopted for the SCD process.

SCP Pattern	Content in ⟨blank 5⟩
Pattern 1
Directed edges	All of the edges suggested by the statistical causal discovery are below:
⟨ cause 1 ⟩ → ⟨ effect 1 ⟩
⟨ cause 2 ⟩ → ⟨ effect 2 ⟩
⋮
Pattern 2
Bootstrap probabilities
of directed edges	All of the edges with non-zero bootstrap probabilities
suggested by the statistical causal discovery are below:
⟨ cause 1 ⟩ → ⟨ effect 1 ⟩ (bootstrap probability = P_1)
⟨ cause 2 ⟩ → ⟨ effect 2 ⟩ (bootstrap probability = P_2)
⋮
Pattern 3
(DirectLiNGAM Only)
Non-zero causal coefficients
of directed edges	All of the edges and their coefficients of the structural causal model
suggested by the statistical causal discovery are below:
⟨ cause 1 ⟩ → ⟨ effect 1 ⟩ (coefficient = b_1)
⟨ cause 2 ⟩ → ⟨ effect 2 ⟩ (coefficient = b_2)
⋮
Pattern 4
(DirectLiNGAM Only)
Non-zero causal coefficients
and bootstrap probabilities
of directed edges	All of the edges with non-zero bootstrap probabilities
and their coefficients of the structural causal model
suggested by the statistical causal discovery are below:
⟨ cause 1 ⟩ → ⟨ effect 1 ⟩ (coefficient = b_1, bootstrap probability = P_1)
⟨ cause 2 ⟩ → ⟨ effect 2 ⟩ (coefficient = b_2, bootstrap probability = P_2)
⋮

Table 11: Contents filled in ⟨blank 6⟩ and ⟨blank 9⟩ shown in Table 1, when Exact Search or DirectLiNGAM is adopted for the SCD process.

SCP Pattern	Case Classification	⟨blank 6⟩	Content in ⟨blank 9⟩
Pattern 1
Directed edges	$x_j \to x_i$ emerged	a	-
(No values are filled in)
	$x_j \to x_i$ not emerged	no	-
(No values are filled in)
Pattern 2
Bootstrap probabilities
of directed edges	$P_{ij} \neq 0$	a	with a bootstrap probability of P_{ij}
	$P_{ij} = 0$	no	-
(No values are filled in)
Pattern 3
(DirectLiNGAM Only)
Non-zero causal coefficients
of directed edges	$b_{ij} \neq 0$	a	with a causal coefficient of b_{ij}
	$b_{ij} = 0$	no	-
(No values are filled in)
Pattern 4
(DirectLiNGAM Only)
Non-zero causal coefficients
and bootstrap probabilities
of directed edges	$P_{ij} \neq 0$ and $b_{ij} \neq 0$	a	with a bootstrap probability of P_{ij},
and the coefficient is likely to be b_{ij}
	$P_{ij} \neq 0$ and $b_{ij} = 0$	a	with a bootstrap probability of P_{ij},
but the coefficient is likely to be 0
	$P_{ij} = 0$	no	-
(No values are filled in)

This template is slightly modified from the one in Table 1. The description for ⟨ blank 5 ⟩ in each SCP pattern is augmented by Table 13, and the description for ⟨ blank 6 ⟩ is similarly augmented by Table 14.

As shown in Table 13, the directed and undirected edges are separately listed and clearly distinguished by the edge symbols "→" for directed edges and "—" for undirected edges. These are then filled in ⟨ blank 5 ⟩. The pairs of variables connected by undirected edges are represented as ⟨ cause or effect i-1 ⟩ and ⟨ cause or effect i-2 ⟩, and the bootstrap probability of the emergence of these relationships is represented as P_i^u. On the other hand, the bootstrap probability of ⟨ cause i ⟩ → ⟨ effect i ⟩ is represented as P_i^d.

The division of descriptions in ⟨ blank 6 ⟩ is shown in Table 14. The bootstrap probabilities of the appearance of $x_j \to x_i$ and x_j—x_i are, respectively represented as P_{ij}^d and P_{ij}^u.

Table 12: The prompt template of $Q_{ij}^{(1)}(x_i, x_j, \hat{G}_0, \boldsymbol{P^d}, \boldsymbol{P^u})$ in the case of the PC algorithm. The "blanks" enclosed with $\langle \ \rangle$ are filled with descriptive words considering the theme of the causal inference, variable names, and the SCD result with the PC algorithm.

Prompt Template of $q_{ij}^{(1)} = Q_{ij}^{(1)}(x_i, x_j, \hat{G}_0, \boldsymbol{P^d}, \boldsymbol{P^u})$ for PC

We want to carry out causal inference on $\langle$blank 1. The theme$\rangle$, considering $\langle$blank 2. The description of all variables$\rangle$ as variables.
First, we have conducted the statistical causal discovery with the PC (Peter-Clerk) algorithm, using a fully standardized dataset on $\langle$blank 4. The description of the dataset$\rangle$.

$\langle$blank 5. This includes the information of $\hat{G}_0$ (for Pattern 1), or $\boldsymbol{P^d}$ and $\boldsymbol{P^u}$ (for Pattern 2).
The details of the contents depend on prompting patterns, both for directed and undirected edges.$\rangle$

According to the results shown above, it has been determined that
$\langle$blank 6. The details of the interpretation of whether there is a causal relationship between x_j and x_i from the result shown in blank 5$\rangle$.
Then, your task is to interpret this result from a domain knowledge perspective and determine whether this statistically suggested hypothesis is plausible in the context of the domain.

Please provide an explanation that leverages your expert knowledge on the causal relationship between $\langle$blank 7. The name of $x_j\rangle$ and $\langle$blank 8. The name of $x_i\rangle$, and assess the naturalness of this causal discovery result. Your response should consider the relevant factors and provide a reasoned explanation based on your understanding of the domain.

Table 13: Contents filled in ⟨blank 5⟩ shown in Table 12.

SCP Pattern	Content in ⟨blank 5⟩
Pattern 1
Directed and undirected edges	All of the edges suggested by the statistical causal discovery are below:
⟨ cause 1 ⟩ → ⟨ effect 1 ⟩
⟨ cause 2 ⟩ → ⟨ effect 2 ⟩
$\vdots$
In addition to the directed edges above, all of the undirected edges suggested by the statistical causal discovery are below:
⟨ cause or effect 1-1 ⟩ — ⟨ cause or effect 1-2 ⟩
⟨ cause or effect 2-1 ⟩ — ⟨ cause or effect 2-2 ⟩
$\vdots$
Pattern 2
Bootstrap probabilities
of directed and undirected edges	All of the edges with non-zero bootstrap probabilities suggested by the statistical causal discovery are below:
⟨ cause 1 ⟩ → ⟨ effect 1 ⟩ (bootstrap probability = P_1^d)
⟨ cause 2 ⟩ → ⟨ effect 2 ⟩ (bootstrap probability = P_2^d)
$\vdots$
In addition to the directed edges above, all of the undirected edges suggested by the statistical causal discovery are below:
⟨ cause or effect 1-1 ⟩ — ⟨ cause or effect 1-1 ⟩ (bootstrap probability = P_1^u)
⟨ cause or effect 2-1 ⟩ — ⟨ cause or effect 2-2 ⟩ (bootstrap probability = P_2^u)
$\vdots$

Table 14: Contents filled in ⟨blank 6⟩ shown in Table 12.

SCP Pattern	Case Classification	Content in ⟨blank 6⟩
Pattern 1
Directed and undirected edges	$x_j \to x_i$	there may be a direct impact of a change in ⟨blank 7. The name of x_j⟩ on ⟨blank 8. The name of x_i⟩
	$x_j - x_i$	there may be a direct causal relationship between ⟨blank 7. The name of x_j⟩ and ⟨blank 8. The name of x_i⟩, although the direction has not been determined
	no edge between x_i and x_j	there may be no direct impact of a change in ⟨blank 7. The name of x_j⟩ on ⟨blank 8. The name of x_i⟩
Pattern 2
Bootstrap probabilities of
directed and undirected edges	$P_{ij}^d \neq 0$ and $P_{ij}^u \neq 0$	there may be a direct impact of a change in ⟨blank 7. The name of x_j⟩ on ⟨blank 8. Thename of x_i⟩ with a bootstrap probability of P_{ij}^d.
In addition, it has also been shown above that there may be a direct causal relationship between ⟨blank 7. The name of x_j⟩ and ⟨blank 8. The name of x_i⟩ with a bootstrap probability of P_{ij}^u, although the direction has not been determined
	$P_{ij}^d \neq 0$ and $P_{ij}^u = 0$	there may be a direct impact of a change in ⟨blank 7. The name of x_j⟩ on ⟨blank 8. The name of x_i⟩ with a bootstrap probability of P_{ij}^d
	$P_{ij}^d = 0$ and $P_{ij}^u \neq 0$	there may be a direct causal relationship between ⟨blank 7. The name of x_j⟩ and ⟨blank 8. The name of x_i⟩ with a bootstrap probability of P_{ij}^u, although the direction has not been determined
	$P_{ij}^d = 0$ and $P_{ij}^u = 0$	there may be no direct impact of a change in ⟨blank 7. The name of x_j⟩ on ⟨blank 8. The name of x_i⟩

C   Details of Datasets used in Demonstrations

In this section, the details of the dataset used in the main body and the appendix are clarified. The ground truths set for the evaluation of the SCD and LLM-KBCI results for each dataset are presented.

C.1   Auto MPG data

Auto MPG data were originally open in the UCI Machine Learning Repository (Quinlan, 1993), and used as a benchmark dataset for causal inference (Spirtes et al., 2010; Mooij et al., 2016). This dataset consists of variables related to the fuel consumption of cars. We adopt five variables: "Weight", "Displacement", "Horsepower", "Acceleration" and "Mpg" (miles per gallon). Moreover, the number of points of this dataset in the experiment is 392. The ground truth of the causal relationships we adopt in this paper is shown in Figure 7; the original has been shown as an example of the kPC algorithm (Spirtes et al., 2010). The differences from the original study (Spirtes et al., 2010) are presented below:

(1) Loss of "Cylinders"   Although there is also a discrete variable of "Cylinders" in the original data (Quinlan, 1993), it is omitted in the experiments to focus solely on the continuous variables.

(2) Directed edge from "Weight" to "Displacement"   The "Weight" and "Displacement" are connected with an undirected edge, which indicates that the direction cannot be determined in the kPC algorithm, although a causal relationship between these two variables is suggested. However, it is empirically acknowledged that large and heavy vehicles use engines with larger displacements to provide sufficient power to match their size. Thus, we temporally set the direction of the edge between these two variables as "Weight" → "Displacement."

We also recognize that another ground truth was interpreted in the process of reconstructing the Tübingen database for causal-effect pairs (Mooij et al., 2016) [17], and "Mpg" and "Acceleration" were interpreted as effected variables from other elements. This ground truth seems to be reliable, if we do not significantly discriminate between direct and indirect causal effects and target the identification of cause and effect from a pair of variables. However, we adopt the ground truth based on the result from the kPC algorithm, because our target is to approach the true causal graph, including multi-step causal relationships.

Figure 7: Causal graph of ground truth adopted for Auto MPG data in this study.

In Figure 8, the results of basic causal structure analysis via the PC, Exact Search, and DirectLiNGAM algorithms without prior knowledge are presented. Several reversed edges from ground truths such as "Mpg" → "Weight" are observed.

---

[17]https://webdav.tuebingen.mpg.de/cause-effect/

Figure 8: Results of SCD on Auto MPG data with (A) PC, (B) Exact Search, and (C) DirectLiNGAM.

C.2 DWD climate data

The DWD climate data were originally provided by the DWD [18], and several of the original datasets were merged and reconstructed as a component of the übingen database for causal-effect pairs (Mooij et al., 2016). This dataset consists of six variables: "Altitude", "Latitude", "Longitude", "Sunshine" (duration), "Temperature" and "Precipitation". The number of points of this dataset is 349, which corresponds to the number of weather stations in Germany without missing data.

Because there is no ground truth on this dataset advocated, except for that in the übingen database for causal-effect pairs (Mooij et al., 2016), we adopt it temporally in this experiment, as shown in Figure 9.

Figure 9: Causal graph of the ground truth adopted for the DWD climate data in this study.

In Figure 10, the results of basic causal structure analysis via the PC, Exact Search, and DirectLiNGAM algorithms without prior knowledge are presented. In all the causal graphs in Figure 10, several unnatural behaviors are observed, such as "Altitude" being affected by other climate variables, which we interpret as reversed causal relationships from the ground truths.

Figure 10: Results of SCD on DWD climate data with (A) PC, (B) Exact Search, and (C) DirectLiNGAM.

---

[18]https://www.dwd.de/

C.3 Sachs protein data

This dataset consists of variables related to the phosphorylation levels of proteins and lipids in primary human immune cells, which were originally constructed and analyzed with the non-parametric causal structure learning algorithm by Sachs et al. (2005). It contains 11 continuous variables: "raf", "mek", "plc", "pip2", "pip3", "erk", "akt", "pka", "pkc", "p38" and "jnk". The number of points in this dataset is 7466.

The ground truth adopted in this study is almost the same as the interpretation shown in the study by Sachs et al. (2005). The differences from the causal graph visually displayed in the original paper are presented below:

(1) Reversed edge between "pip3" and "plc" Although the directed edge "plc" → "pip3" was detected in the original study, it was denoted as "reversed," which may be the reversed direction from the expected edge. Thus, we adopt the causal relationship of "pip3" → "plc" which Sachs *et al.* anticipated as true from an expert point of view.

(2) Three missed edges in the original study In the study by Sachs *et al.*, "pip2" → "pkc'," "plc" → "pkc," and "pip3" → "akt" did not appear in the Bayesian network inference result, although they were expected to be direct causal relationships from the domain knowledge. We adopt these three edges for the ground truth, considering that they may not appear under certain SCD conditions and assumptions.

Figure 11: Causal graph of the ground truth adopted for Sachs protein data in this study.

In Figure 12, the results of the basic causal structure analysis via the PC, Exact Search, and DirectLiNGAM algorithms without prior knowledge are shown.

Figure 12: Results of SCD on Sachs data with (A) PC, (B) Exact Search, and (C) DirectLiNGAM.

C.4 Health screening data (closed data and not included in GPT-4's pretraining materials)

To confirm that GPT-4 can adequately judge the existence of causal relationships with SCP, even if the dataset used in SCD is not included in the pretraining dataset of GPT-4, we have additionally prepared a health screening dataset of workers in engineering and construction contractors, which is not disclosed because of its sensitive nature from personal handling and other private aspects. It contains seven continuous variables: body mass index ("BMI"), waist circumference ("Waist"), Systolic blood pressure ("SBP"), Diastolic blood pressure ("DBP"), hemoglobin A1c ("HbA1c"), low density lipoprotein cholesterol ("LDL"), and age ("Age"). The number of total points of this dataset is 123 151.

Although the causal relationships between all pairs of variables are not completely determined, we set two types of ground truths.

(1) Directed edges interpreted as ground truths We empirically set four directed edges below as ground truths.

- "Age"→"BMI"(Clarke et al., 2008; Alley et al., 2008; Gordon-Larsen et al., 2010; Yang et al., 2021)

- at least one of "Age"→"SBP" and "Age"→"DBP"(Gurven et al., 2012)

- "Age"→"HbA1c"(Pani et al., 2008; RaviKumar et al., 2011; Dubowitz et al., 2014)

(2) Variable interpreted as a parent for all other variables "Age" is an unmodifiable background factor. Furthermore, numerous medical studies have clearly demonstrated that aging affects "BMI," "SBP," "DBP," and "HBA1c." Based on this specialized knowledge, we interpret "Age" as a parent for all other variables.

The ground truths introduced above also appear in the result of DirectLiNGAM without prior knowledge, as shown in Figure 13. Although "Age"→"HbA1c" is confirmed in this result, the causal coefficient of this edge is relatively small. Thus, depending on the number of data points or the bias of the dataset, it is possible that this edge does not appear in all SCD methods without prior knowledge. For the experiment, to confirm that GPT-4 can supply SCD with adequate prior knowledge, even if a direct edge of the ground truth is not apparent, we repeated the sampling of 1000 points from the entire dataset, until we obtained a subset on which PC, Exact Search, and DirectLiNGAM cannot discern the causal relationship "Age"→"HbA1c" without prior knowledge.

The results of the SCD on the subset are shown in Figure 14, and this subset is adopted to confirm the effectiveness of the proposed method. It is confirmed in all SCD results that "Age" → "HbA1c" does not appear, and "Age" is directly influenced by other variables, which we interpret as an unnatural behavior from the domain knowledge.

Figure 13: Causal graph suggested by DirectLiNGAM using full points of the health screening data.

Figure 14: Results of SCD on the randomly selected subsample in the health screening dataset with (A) PC, (B) Exact Search, and (C) DirectLiNGAM.

D Token Generation Probabilities as Confidence of LLMs and Sensitivity Analysis

In this section, we provide a supplemental explanation of the properties of the mean probability $\overline{p_{ij}}$, that the LLM generates the token "yes" as the response to the prompt asking for confidence in the causal relationship from x_j to x_i, highlighting the properties of the token generation process in Transformer-based LLMs. We also discuss the mean probability $\overline{r_{ij}}$ that the LLM generates the token "no," and explain the symmetric behavior of $\overline{p_{ij}}$ and $\overline{r_{ij}}$ arising from the empirical relationship $\overline{p_{ij}} + \overline{r_{ij}} = 1$, under the assumption of the "faithfulness" of the LLM to the prompt. Moreover, we quantitatively evaluate the fluctuation of $\overline{p_{ij}}$ with the standard error $SE(p_{ij})$ as indices of the sensitivity or reliability of these probabilities measured in our experiments, through the regression analysis with a phenomenological distribution function $SE(\overline{p_{ij}}) = a_p - b_p(\overline{p_{ij}} - 0.5)^2$. Finally, the precision of the classification of forbidden causal paths is evaluated through numerical simulations.

The discussion in this section not only contributes to the evaluation of the LLM's confidence in the causal relationship between pairs of variables, but also supports the reliability of the LLM's outputs.

D.1 Details of Token Generation Probabilities Calculations

As explained in Section 3.1, we quantitatively evaluate the generation probability of the token "yes" from GPT-4, as the confidence of GPT-4 regarding the existence of the causal relationship. Although the details of GPT-4's architecture have not been disclosed, it is naturally assumed that GPT-4 employs a temperature-adjusted softmax function for token generation, considering the following facts:

- The previous GPT series developed by OpenAI are based on the Transformer architecture (Radford et al., 2019; Brown et al., 2020)

- The temperature hyperparameter can be optionally set

- The log-probabilities of the most likely tokens at each token position can be obtained

In the process of text generation in a Transformer, the model first calculates the logit z_k for token c_k ($0 \le k \le K$, where K is the number of candidate tokens) as a likelihood score for all candidate tokens on the basis of the prompted text X. Then, the conditional probability distribution of the emergence of token c_a with the logit z_a, $P(c_a|X)$, is calculated through the temperature-adjusted softmax function as follows (Tunstall et al., 2022):

$$P(c_a|X, T) = \frac{\exp(z_a/T)}{\sum_{k=0}^{K} \exp(z_k/T)} \tag{5}$$

Here, T is a temperature hyperparameter that adjusts the conditional probability distribution. Finally, the next token is sampled based on the conditional probability distribution above.

In this work, T was fixed to 0.7. In the third step, the log-probability $L_{ij}^{(m)} = L^{(m)}(\epsilon_{\text{GPT4}}(q_{ij}^{(2)}) = \text{"yes"})$ shown in Algorithm 1 is directly sampled for M times via the optional function of GPT-4. Considering that the token generation probability is represented by Eq. (5), we have calculated the mean probability $\overline{p_{ij}}$ as follows:

$$\overline{p_{ij}} = \frac{\sum_{m=1}^{M} \exp(L_{ij}^{(m)})}{M} = \frac{\sum_{m=1}^{M} P^{(m)}\left(\text{"yes"}|q_{ij}^{(2)}, T\right)}{M} \tag{6}$$

We have interpreted $\overline{p_{ij}}$ calculated above as the confidence[19] of GPT-4 in the existence of the causal effect from x_j on x_i.

---

[19]Although it is suggested that this interpretation is valid in common-sense reasoning from our experiments, it should be noted that this probability simply represents the likelihood that the LLM selected the expected token as the answer to the prompt. In this sense, this "confidence" can be biased under some conditions since it depends on the architecture and the pretraining datasets of the LLM. Therefore, as discussed in Section 5, it is necessary to further improve our method to avoid hallucinations more reliably, especially for applications in highly specialized academic domains.

Figure 15: (a) The relationship between $\overline{p_{ij}}$ and $\overline{r_{ij}}$. The red line is the result of least squares regression with $\overline{r_{ij}} = \alpha\overline{p_{ij}} + \beta$. The estimated values ($\pm$ the standard errors) of the coefficients are $\alpha = -1.002 \pm 0.002 (\simeq -1)$ and $\beta = 0.990 \pm 0.001 (\simeq 1)$. (b) The relationship between $SE(\overline{p_{ij}})$ and $SE(\overline{r_{ij}})$. The red line is the result of least squares regression with $SE(\overline{r_{ij}}) = \gamma SE(\overline{p_{ij}}) + \delta$. The estimated values ($\pm$ the standard errors) of the coefficients are $\gamma = 0.933 \pm 0.011 (\simeq 1)$ and $\delta = 0.0015 \pm 0.0002 (\simeq 0)$.

D.2 Confidence in the Absence of the Causal Relationship

Although the generation probability of the token "no" is not evaluated in the main text, it is valuable to discuss the ideal behavior of this probability for the subsequent discussion of the stability of $\overline{p_{ij}}$. In the same context as $\overline{p_{ij}}$, the mean probability of generating the token "no", $\overline{r_{ij}}$, is calculated as follows:

$$\overline{r_{ij}} = \frac{\sum_{m=1}^{M} P^{(m)}\left(\text{"no"}|q_{ij}^{(2)}, T\right)}{M} \tag{7}$$

Since GPT-4 is required to answer only with "yes" or "no," under the assumption that the response from GPT-4 is faithful to the prompt explained in Table 2, it is expected that $P^{(m)}(\text{"yes"}|q_{ij}^{(2)}, T) + P^{(m)}(\text{"no"}|q_{ij}^{(2)}, T) = 1$. In this section, we define this property as "faithfulness." Therefore, from Eqs. (6) and (7), the ideal relation between $\overline{p_{ij}}$ and $\overline{r_{ij}}$ is expressed as follows:

$$\overline{r_{ij}} = -\overline{p_{ij}} + 1 \tag{8}$$

Since Eq. (8) is also expressed in a symmetrical form such as $\overline{r_{ij}} - 0.5 = -(\overline{p_{ij}} - 0.5)$, this property is expected to contribute to a clearer quantitative interpretation of the stability of $\overline{p_{ij}}$. This is particularly important for validating the latter discussion on the fluctuation of $\overline{p_{ij}}$.

D.3 Stability of Token Generation Probabilities

For the quantitative evaluation of the stability of $\overline{p_{ij}}$, we compare $\overline{p_{ij}}$ and $\overline{r_{ij}}$, along with their standard errors ($SE(p_{ij})$ and $SE(r_{ij})$) estimated through trials conducted $M = 5$ times. We temporarily concatenate the results of LLM-KBCI on the datasets of AutoMPG, DWD, and Sachs (for all the prompting patterns

Figure 16: (a) Relationship between the mean probability $\overline{p_{ij}}$ and the standard error $SE(p_{ij})$. The red line is the result of least squares regression with $SE(\overline{p_{ij}}) = a_p - b_p(\overline{p_{ij}} - 0.5)^2$. The estimated values ($\pm$ standard errors) of the coefficients are $a_p = 0.0694 \pm 0.0007$ and $b_p = 0.2783 \pm 0.0030$. (b) Relationship between the mean probability $\overline{r_{ij}}$ and the standard error $SE(r_{ij})$. The red line is the result of least squares regression with $SE(\overline{r_{ij}}) = a_r - b_r(\overline{r_{ij}} - 0.5)^2$. The estimated values ($\pm$ standard errors) of the coefficients are $a_r = 0.0692 \pm 0.0007$ and $b_r = 0.2780 \pm 0.0032$.

and for all the SCD algorithms), and on the health-screening data (for all the prompting patterns with DirectLiNGAM), under the assumption that the relations among $\overline{p_{ij}}$, $\overline{r_{ij}}$, $SE(p_{ij})$ and $SE(q_{ij})$ are almost independent of the domains. This holds even if SCP is conducted within the realm of common-sense reasoning. The number of points of the concatenated data is 1650.

Figure 15 (a) shows the relation between $\overline{p_{ij}}$ and $\overline{r_{ij}}$, and the red line indicates the result of least squares regression with $\overline{r_{ij}} = \alpha\overline{p_{ij}} + \beta$. Considering that the estimated values of the causal coefficients ($\alpha = -1.002$, $\beta = 0.990$) exhibit similar behavior to Eq. (8), it can be inferred that the assumption of the "faithfulness" of the LLM generation to the prompts is valid in our experiments. Therefore, it seems approximately valid to assume the symmetrical relation $\overline{r_{ij}} - 0.5 = -(\overline{p_{ij}} - 0.5)$.

Moreover, Figure 15 (b) shows the relationship between $SE(\overline{p_{ij}})$ and $SE(\overline{r_{ij}})$, where the red line indicates the result of least squares regression with $SE(\overline{r_{ij}}) = \gamma SE(\overline{p_{ij}}) + \delta$. Given the estimated values of the causal coefficients ($\gamma = 0.933$, $\delta = 0.002$), it can be inferred that the approximation $SE(\overline{p_{ij}}) \simeq SE(\overline{r_{ij}})$ holds true. This fact provides further evidence for the approximately symmetric behavior expressed as $\overline{r_{ij}} - 0.5 = -(\overline{p_{ij}} - 0.5)$.

Figure 16 shows the relation between $\overline{p_{ij}}$ and $SE(p_{ij})$ in (a) and the relation between $\overline{r_{ij}}$ and $SE(r_{ij})$ in (b). These two graphs exhibit mutually related characteristics as follows:

- In the limit of $\overline{p_{ij}} \to 1$ or $\overline{r_{ij}} \to 0$, both $SE(p_{ij})$ and $SE(r_{ij})$ approach 0, indicating that $\overline{p_{ij}}$ and $\overline{r_{ij}}$ become highly stable when confidence in the presence of the causal effect from x_j to x_i is very high.

- In the limit of $\overline{p_{ij}} \to 0$ or $\overline{r_{ij}} \to 1$, both $SE(p_{ij})$ and $SE(r_{ij})$ approach 0, indicating that $\overline{p_{ij}}$ and $\overline{r_{ij}}$ become highly stable when confidence in the absence of the causal effect from x_j to x_i is very high.

Furthermore, the entire form of the $\overline{p_{ij}}$ - $SE(p_{ij})$ distribution is quantitatively similar to the $\overline{r_{ij}}$ - $SE(r_{ij})$ distribution. From this fact, it is expected that the functional form of $SE(p_{ij})$ explained with p_{ij} is approximately the same as that of $SE(r_{ij})$ explained with r_{ij}. Therefore, to interpret the stability of the probability easily and clearly, we assume a common distribution function between the $\overline{p_{ij}}$ - $SE(p_{ij})$ and $\overline{r_{ij}}$ - $SE(r_{ij})$ distributions, as well as the symmetric behavior shown in Eq. (8), and regress the $\overline{p_{ij}}$ - $SE(p_{ij})$ distribution with a phenomenological function as follows:

$$SE(p_{ij}) = a_p - b_p(\overline{p_{ij}} - 0.5)^2 \tag{9}$$

In the same context, the $\overline{r_{ij}}$ - $SE(r_{ij})$ distribution is regressed with a phenomenological function as follows:

$$SE(r_{ij}) = a_r - b_r(\overline{r_{ij}} - 0.5)^2 \tag{10}$$

Ideally, if the symmetrical behavior holds true, the relationship $(a_p, b_p) = (a_r, b_r)$ is expected. From the analysis results of the least squares regression, the coefficients of Eqs. (9) and (10) are estimated as $(a_p, b_p) = (0.0694, 0.2783)$ and $(a_r, b_r) = (0.0692, 0.2780)$. Thus, it is confirmed that $(a_p, b_p) \simeq (a_r, b_r)$ holds true.

From the results above, the standard error of p_{ij} becomes the maximum value (expected to be 0.062) when $\overline{p_{ij}} = 0.5$. In our experiments, the fluctuation becomes critical at the criteria α_1 and α_2 explained in Section 3.1. From the phenomenological analysis shown above, the expected standard errors of $\overline{p_{ij}}$ at the criteria ($\alpha_1 = 0.05$ and $\alpha_2 = 0.95$ in our experiments) are estimated through Eq. (9) to be approximately 0.013. Therefore, when $\overline{p_{ij}}$ is near the threshold of 0.05 or 0.95, the probability fluctuation around this standard error can lead to a different **PK** matrix.

D.4 Effect on the Decision of Prior Knowledge Matrix

For a more detailed analysis of the effect of the fluctuation on the determination of **PK**, we focus on two indices of sensitivity: (A) the statistically estimated probability that the true value of p_{ij} (p_{ij}^{true}) satisfies the inequality $p_{ij}^{true} < \alpha_1$, and (B) the area under the curve (AUC) calculated through a Monte Carlo simulation.

(A) Statistically Estimated Probability of True Confidence

For a simple simulation, we assume that $SE(p_{ij})$ is calculated with Eq. (9) and that $(a_p, b_p) = (0.0694, 0.2783)$, as estimated through the regression analysis in Appendix D.3. Moreover, we assume that the distribution of p_{ij}^{true} is expressed with a Gaussian distribution, with mean value $\overline{p_{ij}}$ and standard deviation $SE(\overline{p_{ij}})$, as described in Eq. (11).

$$f_{p_{ij}^{true}}(\overline{p_{ij}}, SE(\overline{p_{ij}}), p) = \frac{1}{\sqrt{2\pi}SE(\overline{p_{ij}})} \exp\left(-\frac{(p - \overline{p_{ij}})^2}{2SE(\overline{p_{ij}})^2} \right) \tag{11}$$

Under the assumptions above, $P(p_{ij}^{true} < \alpha_1)$, the probability that the true confidence probability p_{ij}^{true} is below the forbidden edge threshold α_1, is calculated as follows:

$$P(p_{ij}^{true} < \alpha_1) = \int_0^{\alpha_1} dp\, f_{p_{ij}^{true}}(\overline{p_{ij}}, SE(\overline{p_{ij}}), p) \tag{12}$$

Then, $P(p_{ij}^{true} < \alpha_1)$ is numerically calculated via Eq. (12), and the result is shown in Fig. 17 (a). It is observed that when $\overline{p_{ij}} \leq 0.04$, p_{ij}^{true} is almost certainly below the threshold $\alpha_1 = 0.05$, and when $\overline{p_{ij}} \geq 0.08$, p_{ij}^{true} is almost certainly above 0.05. However, between $0.04 \leq \overline{p_{ij}} \leq 0.08$ (approximately 0.05), $P(p_{ij}^{true} < \alpha_1)$ decreases with increasing $\overline{p_{ij}}$. Although it is confirmed that the width of the region of this decreasing $P(p_{ij}^{true} < \alpha_1)$ is similar in the order of $SE(\overline{p_{ij}}) \simeq 0.013$ around $\overline{p_{ij}} = 0.05$, the slope of the decrease is gentler in the region of $\overline{p_{ij}} \geq 0.05$ than in the region of $\overline{p_{ij}} \leq 0.05$. This asymmetric property originates from the phenomenological nonlinear function of $SE(\overline{p_{ij}})$ as described in Eq. (9). If the threshold of the forbidden edge α_1 is decreased, it is possible to shrink the region of decreasing $P(p_{ij}^{true} < \alpha_1)$ and the asymmetric slope.

Figure 17: (a) Relationship between the calculated $P(p_{ij}^{true} < \alpha_1)$ and $\overline{p_{ij}}$ based on Eq. (12). (b) ROC curve estimated through a Monte Carlo simulation based on Eq. (11). The AUC calculated with this ROC curve is 0.899.

However, although we tentatively set α_1 to 0.05, the optimal threshold is expected to be discussed in future research from a practical point of view. Notably, a lower α_1 leads to a **PK** matrix, which includes more uncertain elements from domain expert knowledge and can be less effective in the fourth step in Fig. 1 than expected.

(B) ROC and AUC Estimated through a Monte Carlo Simulation

Since p_{ij}^{true} cannot be known in our experiments, it is impossible to construct the receiver operating characteristic (ROC) curve directly with the probability data obtained in our experiments. Instead, we have conducted a Monte Carlo simulation, through which p_{ij}^{true} is randomly generated via the distribution described in Eq. (11). Furthermore, for the calculation of the ROC and AUC, we define the conditions for true positive (TP), false positive (FP), true negative (TN), and false negative (FN), in the context of judging whether the causal path from x_j to x_i is forbidden, as follows:

- TP: generated p_{ij}^{true} satisfies $p_{ij}^{true} < \alpha_1$, and experimentally fixed $\overline{p_{ij}}$ satisfies $\overline{p_{ij}} < \alpha_1$.

- FP: generated p_{ij}^{true} satisfies $p_{ij}^{true} \geq \alpha_1$, and experimentally fixed $\overline{p_{ij}}$ satisfies $\overline{p_{ij}} < \alpha_1$.

- TN: generated p_{ij}^{true} satisfies $p_{ij}^{true} \geq \alpha_1$, and experimentally fixed $\overline{p_{ij}}$ satisfies $\overline{p_{ij}} \geq \alpha_1$.

- FN: generated p_{ij}^{true} satisfies $p_{ij}^{true} < \alpha_1$, and experimentally fixed $\overline{p_{ij}}$ satisfies $\overline{p_{ij}} \geq \alpha_1$.

The practical Monte Carlo simulation was conducted 1000 times for each $\overline{p_{ij}}$ value, varying $\overline{p_{ij}}$ from 0.032 to 0.108[20] in increments of 0.001, and the calculated ROC through this simulation is shown in Fig. 17. AUC is

---

[20]

In this region, $P(p_{ij}^{true} < \alpha_1)$ satisfies $0.001 < P(p_{ij}^{true} < \alpha_1) < 0.999$. Therefore, for the practical calculation of the ROC and AUC, we have assumed that when $\overline{p_{ij}}$ satisfies $\overline{p_{ij}} < 0.032$, p_{ij}^{true} is under α_1 and always classified as TP, and that when $\overline{p_{ij}}$ satisfies $\overline{p_{ij}} > 0.108$, p_{ij}^{true} is $\geq \alpha_1$ and always classified as TN.

estimated to be 0.899, indicating excellent discrimination of the forbidden direct causal path (Hosmer & Lemeshow, 2000). From this analysis, it is inferred that in the realm of common-sense reasoning, the decision process of **PK** from the confidence of GPT-4 at the third step in Fig. 1 according to the interpretation obtained in the second step, is statistically valid.

D.5 Limitations in Sensitivity Analysis of Token Generation Probabilities

Although we have discussed the sensitivity of the token generation probabilities as the confidence of GPT-4 above, there are several limitations in elucidating the entire properties of the fluctuations induced by the randomness of the LLMs. For further research to improve our methods, we introduce several additional points related to the measurement stability in the third step in Fig. 1.

Sensitivity in the Explanation Obtained in Step 2

Although we have evaluated the probability fluctuation emergent in Step 3 of Fig. 1, $\overline{p_{ij}}$ and $SE(\overline{p_{ij}})$ can also depend on a_{ij}, the output in Step 2, on the basis of the relationship of $q_{ij}^{(2)} = Q_{ij}^{(2)}(q_{ij}^{(1)}, a_{ij})$. Since it is practically impossible to evaluate the fluctuation of a_{ij} at Step 2 quantitatively, we have discussed the token generation probability and its sensitivity with a fixed a_{ij}.

Furthermore, we have not discussed in this work the validity of a_{ij}, as this is expected to be debated within the domain of research specific to LLMs, which is outside the scope of our study. However, although our method has proven to be effective in many cases through this research, it may be negatively impacted if an LLM makes biased judgments. Therefore, ongoing efforts to eliminate biases in LLMs and prevent hallucinations are required. Additionally, considering the future applications of this method, careful consideration and judgment will continue to be necessary.

Imperfect Satisfaction of the Condition of "Faithfulness"

In our work, "faithfulness" is almost confirmed, as shown in Fig. (15). However, several points obviously deviate from the regression line, or from Eq. (8). Specifically, out of a total of 1650 points in the case of our analysis in this section, approximately 1400 points satisfy the relationship $0.99 < \overline{p_{ij}} + \overline{r_{ij}} < 1$. In contrast, for approximately 80 points, $\overline{p_{ij}} + \overline{r_{ij}} < 0.95$, indicating clear violations of "faithfulness."

The break of this "faithfulness" means that there is a generation probability of the token that is neither "yes" nor "no," at a level that cannot be ignored. One possible explanation for this case is that GPT-4 cannot completely assert "yes" or "no" on the existence of the causal effect from x_j to x_i with the knowledge obtained in Step 2. In more anthropomorphic terms, this could suggest that GPT-4 sometimes struggles with its decision-making.

For further rigid handling in the application of our method, it is required to prevent the break of "faithfulness," or to extend our quantitative handling of the token generation probability to the one that permits the possibility of this behavior.

Temperature Dependence of the Fluctuation and the "Faithfulness"

As described in Eq. (5), the probability distribution depends on the temperature parameter. Since a higher temperature leads to a higher generation probability of the token, unexpected at lower temperatures, it is possible that this parameter can also have effects on the fluctuation of p_{ij} and "faithfulness." Although we have fixed this parameter at 0.7 in all the experiments in this work, further discussion on the optimal temperature for this task is expected.

E Composition of Adjacency Matrices Representing Causal Structure and Evaluation

E.1 Composition of Prior Knowledge Matrices

As shown in Algorithm 2, the composition rule of PK depends on the type of SCD method adopted, and the decision criteria of forced and forbidden edges are tentatively set at 0.95 and 0.05, respectively. While PC and DirectLiNGAM can be augmented with constraints for both forced and forbidden directed edges or paths, Exact Search can only be augmented with constraints for forbidden directed edges. In this section, the composition rule for PK is described in detail for all the SCD algorithms we have adopted in this work.

For PC For the matrix representation of PK, the values of the matrix elements are determined as follows:

- Case 1. If $x_i \rightarrow x_j$ is forced (i.e., $p_{ij} \geq 0.95$), then PK_{ij} is set to 1.

- Case 2. If $x_i \rightarrow x_j$ is forbidden (i.e., $p_{ij} < 0.05$), then PK_{ij} is set to 0.

- Case 3. If the existence of $x_i \rightarrow x_j$ cannot be determined immediately from the domain knowledge generated by GPT-4 (i.e., $0.05 \leq p_{ij} < 0.95$), then PK_{ij} is set to -1.

This ternary matrix composition is based on the constraints of the prior knowledge matrix DirectLiNGAM, which will be explained later, to apply the generated PK to DirectLiNGAM as quickly as possible. Although prior knowledge is represented as a matrix in the PC algorithm widely open in "causal-learn," both forced and forbidden edges can be set, and the possibility of other unknown edges can be explored. This property, which is similar to that of DirectLiNGAM, means that the prior knowledge for this PC algorithm can be represented in a ternary matrix, if we need to do so. Therefore, the composition rule of PK for PC is set to be the same as that for DirectLiNGAM in this work, to treat it as consistently as possible.

For DirectLiNGAM Although the criteria for setting the values in PK are the same as those for PC, the definitions of the values slightly differ. Although the prior knowledge for the PC algorithm in the "causal-learn" package corresponds to the existence of directed edges between pairs of variables, the prior knowledge for DirectLiNGAM is determined with the knowledge of directed paths. The values of the matrix elements are determined as follows:

- Case 1. If the directed path from x_i to x_j is forced (i.e., $p_{ij} \geq 0.95$), then PK_{ij} is set to 1.

- Case 2. If the directed path from x_i to x_j is forbidden (i.e., $p_{ij} < 0.05$), then PK_{ij} is set to 0.

- Case 3. If the existence of the directed path from x_i to x_j cannot be determined immediately from the domain knowledge generated by GPT-4 (i.e., $0.05 \leq p_{ij} < 0.95$), then PK_{ij} is set to -1.

This ternary matrix composition, which uses 1, 0 and -1, is indeed implemented in the software package "LiNGAM."

For Exact Search While PK in cases of PC and DirectLiNGAM is a ternary matrix, one must be careful that PK in Exact Search is a binary matrix. The values of the matrix elements are determined as follows:

- Case 4. If $x_i \rightarrow x_j$ is forbidden (i.e., $p_{ij} < 0.05$), then PK_{ij} is set to 0.

- Case 5. If $x_i \rightarrow x_j$ is forced, or if the existence of this causal relationship cannot be determined immediately from the domain knowledge generated by GPT-4 (i.e., $0.05 \leq p_{ij}$), then PK_{ij} is set to 1.

Notably, although the definition of $PK_{ij} = 0$ in Case 4 for Exact Search is exactly the same as that in Case 2 for PC and DirectLiNGAM, the definition of $PK_{ij} = 1$ in Case 5 for Exact Search encompasses both Case 1 and Case 3 for PC and DirectLiNGAM. This difference must be taken into account when evaluating PK in comparison with the ground truths, to interpret the results in a unified manner regardless of the SCD methods used.

E.2 Composition of the Ground Truth Matrix

The representation of ground truths in matrix form can be simply realized via a binary matrix, provided that it is determined whether a directed edge exists for every possible pair of variables in the system. The composition rule for the ground truth matrix GT is as follows:

- If $x_j \rightarrow x_j$ exists, then GT_{ij} is set to 1.

- If $x_j \rightarrow x_j$ does not exist, then GT_{ij} is set to 0.

The matrix representations of the ground truths of the benchmark datasets of Auto MPG, DWD, and Sachs shown in Appendix C are expressed as follows:

$$GT_{\text{AutoMPG}} = \begin{pmatrix} 0 & 0 & 0 & 1 & 0 \\ 0 & 0 & 1 & 1 & 0 \\ 1 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 & 0 \end{pmatrix} \tag{13}$$

$$GT_{\text{DWD}} = \begin{pmatrix} 0 & 0 & 0 & 0 & 0 & 0 \\ 1 & 0 & 0 & 1 & 0 & 1 \\ 1 & 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 \\ 1 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 \end{pmatrix} \tag{14}$$

$$GT_{\text{Sachs}} = \begin{pmatrix} 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 \\ 1 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 1 & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 & 1 & 0 & 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 1 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 1 & 0 & 0 \end{pmatrix} \tag{15}$$

E.3 Calculation of Metrics for the Evaluation of Structural Consistency with Ground Truths (SHD, FPR, FNR, Precision, F1 Score)

Structural metrics such as SHD, FPR, FNR, precision, and F1 score are commonly calculated for performance evaluation in various machine learning and classification contexts, and are compared with the ground truth data. In a similar context, the causal structures inferred by LLM-KBCI and SCD, especially for benchmark datasets with known ground truths, can also be evaluated via these metrics.

For the practical evaluation of the SCD results in this study, we use the ground truth matrices defined for the benchmark datasets in Eq.(13), (14) and (15) as references, and we measure these metrics via the adjacency matrices that are calculated directly in SCD algorithms or easily transformed from the output causal graphs. Similarly, the calculation of these metrics for evaluating the LLM-KBCI outputs is carried out using PK.

However, it must be noted that there can be some arguments on the definition of metrics for PK on the basis of GT, because the definition of the matrix elements of PK shown in Appendix E.1 is partially different from that of GT described in Appendix E.2. In particular, although GT_{ij} is a binary variable completely determined by whether $x_j \rightarrow x_i$ exists or not, PK_{ij} can be set to -1 for PC and DirectLiNGAM and to 1 for Exact Search. This indicates or includes the case where it is not impossible to definitively assert the presence or absence of $x_j \rightarrow x_i$.

Therefore, although a reasonable extension of the definitions of these metrics may be required for the case above, in this study, we evaluate these metrics from $|\boldsymbol{PK}|$, in which both $PK_{ij} = 1$ and $PK_{ij} = -1$ are interpreted as "tentative assertions of the presence of $x_j \rightarrow x_i$" and are treated identically. This processing of $\boldsymbol{PK}$ can also be interpreted as that of temporarily adopting the composition rule of $\boldsymbol{PK}$ for Exact Search as it is for the evaluation of the SHD, FPR, FNR, precision, and F1 score, for all the SCD methods. With this processing, $\boldsymbol{PK}$ is handled in a unified manner regardless of the SCD methods used. We believe that this approach is the best way to maintain the original concept of composing $\boldsymbol{PK}$, while aiming for consistent discussion across all SCD methods.

Calculation of SHD   According to the original concept of the structural hamming distance (SHD), this metric is represented as the total number of edge additions, deletions, or reversals that are needed to convert the estimated graph G' into its ground truth graph G (Zheng et al., 2018; Cheng et al., 2022; Hasan et al., 2023). As in our study, if network graphs G and G' are represented by binary matrices $\boldsymbol{G}$ and $\boldsymbol{G'}$, respectively, where all the elements are either 0 or 1, then the total number of edge additions (A), deletions (D), and reversals (R) can be simply calculated as follows:

$$A(\boldsymbol{G'}, \boldsymbol{G}) = \sum_{i,j} \mathbf{1}(G_{ij})\mathbf{1}(G_{ji})\mathbf{1}(G'_{ij} - 1) \tag{16}$$

$$D(\boldsymbol{G'}, \boldsymbol{G}) = \sum_{i,j} \mathbf{1}(G'_{ij})\mathbf{1}(G'_{ji})\mathbf{1}(G_{ij} - 1) \tag{17}$$

$$R(\boldsymbol{G'}, \boldsymbol{G}) = \sum_{i,j} \mathbf{1}(G_{ij})\mathbf{1}(G_{ji} - 1)\mathbf{1}(G'_{ij} - 1)\mathbf{1}(G'_{ji}) \tag{18}$$

Here, we introduce the indicator function $\mathbf{1}(x)$, expressed as follows:

$$\mathbf{1}(x) = \begin{cases} 1 & \text{if } x = 0, \\ 0 & \text{otherwise } (x \neq 0). \end{cases} \tag{19}$$

As SHD is defined as $SHD = A + D + R$, it is easily evaluated as follows:

$$SHD(\boldsymbol{G'}, \boldsymbol{G}) =$$
$$\sum_{i,j} \Big\{ \ \mathbf{1}(G_{ij})\mathbf{1}(G_{ji})\mathbf{1}(G'_{ij} - 1) \ + \ \mathbf{1}(G'_{ij})\mathbf{1}(G'_{ji})\mathbf{1}(G_{ij} - 1) \ + \ \mathbf{1}(G_{ij})\mathbf{1}(G_{ji} - 1)\mathbf{1}(G'_{ij} - 1)\mathbf{1}(G'_{ji}) \ \Big\} \tag{20}$$

For the evaluation of the SHD of LLM-KBCI outputs, $SHD(|\boldsymbol{PK}|, \boldsymbol{GT})$ is calculated with Eq. (20).

Calculation of FPR, FNR, Precision, and F1 score   In the similar context to the SHD, for the calculation of metrics such as false positive rate (FPR) and false negative rate (FNR), we prepare the equation for evaluating the number of true positive (TP), false positive (FP), true negative (TN), and false negative (FN) edges as follows:

$$TP(\boldsymbol{G'}, \boldsymbol{G}) = \sum_{i,j} \mathbf{1}(G_{ij} - 1)\mathbf{1}(G'_{ij} - 1) \tag{21}$$

$$FP(\boldsymbol{G'}, \boldsymbol{G}) = \sum_{i,j} \mathbf{1}(G_{ij})\mathbf{1}(G'_{ij} - 1) \tag{22}$$

$$TN(\boldsymbol{G'}, \boldsymbol{G}) = \sum_{i,j} \mathbf{1}(G_{ij})\mathbf{1}(G'_{ij}) \tag{23}$$

$$FN(\boldsymbol{G'}, \boldsymbol{G}) = \sum_{i,j} \mathbf{1}(G_{ij} - 1)\mathbf{1}(G'_{ij}) \tag{24}$$

Then, using Eq. (21)– (24), the definition of FPR, FNR, precision, and F1 score can be expressed as follows:

$$FPR(\boldsymbol{G'}, \boldsymbol{G}) = \frac{FP(\boldsymbol{G'}, \boldsymbol{G})}{TN(\boldsymbol{G'}, \boldsymbol{G}) + FP(\boldsymbol{G'}, \boldsymbol{G})} \tag{25}$$

$$FNR(\boldsymbol{G'}, \boldsymbol{G}) = \frac{FN(\boldsymbol{G'}, \boldsymbol{G})}{TP(\boldsymbol{G'}, \boldsymbol{G}) + FN(\boldsymbol{G'}, \boldsymbol{G})} \tag{26}$$

$$Precision(\boldsymbol{G'}, \boldsymbol{G}) = \frac{TP(\boldsymbol{G'}, \boldsymbol{G})}{TP(\boldsymbol{G'}, \boldsymbol{G}) + FP(\boldsymbol{G'}, \boldsymbol{G})} \tag{27}$$

$$F_1 score(\boldsymbol{G'}, \boldsymbol{G}) = \frac{2\,TP(\boldsymbol{G'}, \boldsymbol{G})}{2\,TP(\boldsymbol{G'}, \boldsymbol{G}) + FN(\boldsymbol{G'}, \boldsymbol{G}) + FP(\boldsymbol{G'}, \boldsymbol{G})} \tag{28}$$

For the evaluation of structural metrics such as the FPR of LLM-KBCI outputs, $FPR(|\boldsymbol{PK}|, \boldsymbol{GT})$, $FNR(|\boldsymbol{PK}|, \boldsymbol{GT})$, $Precision(|\boldsymbol{PK}|, \boldsymbol{GT})$ and $F_1 score(|\boldsymbol{PK}|, \boldsymbol{GT})$ are calculated with Eq. (25)–(28).

F Algorithm A for Transformation of Cyclic PK into Acyclic Adjacency Matrices and Selection of the Optimal Matrix

As briefly described in Section 3.1, for the case of DirectLiNGAM, an acyclicity of $\boldsymbol{PK}$ is also required. Thus, if the $\boldsymbol{PK}$ directly calculated from the probability matrix is cyclic, it must be transformed into an acyclic form. One possible method is to delete the minimum number of edges included in cycles to transform $\boldsymbol{PK}$ into an acyclic matrix. However, several solutions may be transformed from the same $\boldsymbol{PK}$ with the minimum manipulation of deleting edges. Therefore, we have decided to carry out causal discovery with DirectLiNGAM for every possible acyclic prior knowledge matrix to select the best acyclic prior knowledge matrix $\boldsymbol{PK}_A$ in terms of statistical modeling. The dataset is again fitted with a structural equation model under the constraint of the causal structure explored with DirectLiNGAM, assuming linear-Gaussian data, and the Bayes Information Criterion (BIC) is calculated. After this process is repeated, the acyclic prior knowledge matrix with which the BIC becomes the lowest is selected as $\boldsymbol{PK}_A$.

The overall transformation process is described in Algorithm 3. However, in the practical application of this method, completing the list of acyclic prior knowledge matrices A incurs significant computational costs. Hence, as the number of variables increases, completing this calculation algorithm in a realistic time frame becomes more challenging.

For the future generalization and application of our inference method via DirectLiNGAM, the development of more efficient algorithms for transforming a cyclic matrix into an acyclic matrix is anticipated.

Algorithm 3 Transformation of Cyclic PK into Acyclic Adjacency Matrices and Selection of the Optimal Matrix

---

  Input 1: Cyclic prior knowledge matrix PK_C
  Input 2: Data X with variables$\{x_1, ..., x_n\}$
  Input 3: DirectLiNGAM Algorithm $L(X, PK)$
  Output: Optimal acyclic matrix PK_A
  Initialize the temporal set for matrices $T \leftarrow \{PK_C\}$
  Initialize the temporal set for the number of cycles $N \leftarrow \{\}$
  Initialize the temporal set for acyclic matrices $A \leftarrow \{\}$
  repeat
    for matrix $T_m \in T$ **do**
      Count the number of cycles in T_m as N_m
      Add N_m to N
    end for
    if $\exists N_m \in N \ N_m = 0$ **then**
      Detect all T_m, which satisfies $N_m = 0$ and add them to A
    else
      Initialize the temporal set for modified matrices $T' \leftarrow \{\}$
      for $T_m \in T$ **do**
        Initialize the set for edges included in cycles $E_m \leftarrow \{\}$
        Initialize the set for edges to be removed $F_m \leftarrow \{\}$
        Detect all cycles in T_m
        For each detected cycle, identify all the edges that form the cycle
        Add these edges to a set of edges to be removed E_m
        Detect the most frequent edges "$x_i \leftarrow x_j$" in E_m as $(i, j)_f$
        $\forall (i_f, j_f)$ add (i_f, j_f) to F_m
        for $(i_f, j_f) \in F_m$ **do**
          $T'_m = T_m$
          $T'_m(i_f, j_f) \leftarrow 0$
          Add T'_m to T'
        end for
      end for
      Replace T with T'
    end if
  until A is not empty
  Initialize the optimal BIC value $B = $ None
  Initialize the optimal acyclic matrix for prior knowledge in DirectLiNGAM $A_{\text{optimal BIC}} = $ None
  for $A_m \in A$ **do**
    Calculate the adjacency matrix (with the 0 or 1 components) of the causal discovery result $Adj = L(X, PK = A_m)$
    Fit X with the structural causal equation model represented in Adj assuming linear-Gaussian data
    Calculate the BIC with Adj and X as B_{temp}
    if $B > B_{\text{temp}}$ **or** $B = $ None **then**
      $B \leftarrow B_{\text{temp}}$
      $A_{\text{optimal BIC}} = A_m$
    end if
  end for
  return $A_{\text{optimal BIC}}$ as PK_A

G Details of LLM-KBCI Results

It is also valuable to examine the details of the probability matrices generated by LLM-KBCI, both for the basic discussion of whether LLMs can generate a valid interpretation of causality from a domain expert's point of view, and for understanding the characteristics of SCP. In this section, the probability matrices generated by GPT-4 for Auto MPG data and DWD climate data, which are relatively easy to interpret within common daily knowledge, are shown and briefly interpreted. For comparison among various SCP patterns (Patterns 1–4) using the same SCD method as much as possible, the probability matrices generated by GPT-4 with SCP are shown only for DirectLiNGAM. We also briefly present the probability matrices of LLM-KBCI for the sampled sub-dataset of health screening results.

G.1 LLM-KBCI for Auto MPG data

In Table 15, the probabilities of the causal relationships of pairs of variables in the Auto MPG data are shown. The cells highlighted in green are those in which the directed edges are expected to appear from the ground truths shown in Figure 7.

For all the prompting patterns, although the probability of "Weight"→"Displacement", which is interpreted as one of the ground truth directed edges, is 0, the probability of reversed edge "Displacement"→"Weight" is non-zero and over 0.95 in Patterns 1–4. To understand this behavior and elucidate the true causal relationship between these two variables, further discussion is required, including the possibility of the hidden common causes that are excluded from the dataset we have used.

In addition, although we do not believe the existence of the directed edge of "Displacement"→"Acceleration," the probability of this causal relationship is greater than 0.85 for all the prompting patterns. This may be due to the property of the prompt for evaluating the probability. As shown in Table 2, GPT-4 is allowed to judge the existence of both direct and indirect causal relationships, to acquire a positive answer even if any intervening variables are not included in the dataset. However, for example, considering that the probabilities of both "Displacement"→"Horsepower" and "Horsepower"→"Acceleration," which are part of the ground truths, are relatively high, it is also possible that GPT-4 supports the hypothesis of some impact from "Displacement" on "Acceleration" partially due to confidence in the indirect causal relationship of "Displacement"→"Horsepower"→"Acceleration". If one wants to distinguish the direct and indirect causal relationships in the interpretation of the probability matrix, investigating the response from LLMs for the first prompt may lead to further understanding.

Some differences that can be related to the prompting patterns can also be observed. For example, the probability of "Horsepower"→"Mpg" in Pattern 1 is much smaller than that in the other patterns. Moreover, the probabilities of "Horsepower"→"Acceleration" in Patterns 1 and 3 are smaller than those of the other patterns, in which the probability of this edge is almost 1. A possible explanation for these behaviors is that the decision-making of GPT-4 is unsettled with the SCP, in which the causal structure inferred by DirectLiNGAM shown in Figure 8 (c) is included. As neither "Horsepower"→"Acceleration" nor "Horsepower"→"Mpg" appears in Figure 8 (c), despite the confidence in the existence of these edges only from the domain knowledge, the decision-making of GPT-4 may become more careful, taking into account the result of SCD. In future work, the types of decision-making of LLMs are likely to be affected by SCP should be investigated.

G.2 LLM-KBCI for DWD climate data

In Table 16, the probabilities of the causal relationships of pairs of variables in the DWD climate data are shown. The cells highlighted in green are those in which the directed edges are expected to appear from the ground truths shown in Figure 9.

For all the prompting patterns, it is confirmed that all of the probabilities of the causal effects on "Altitude," "Longitude," and "Latitude" from other variables are 0. As these three variables are geographically given and fixed, the interpretation by GPT-4 that they act as parent variables that are not influenced by other factors is completely reasonable. Although "Altitude" and "Latitude" are somehow influenced according to the result of DirectLiNGAM without prior knowledge as shown in Figure 10 (c), the SCP, including these

Table 15: Probabilities of the causal relationships suggested by GPT-4 in Auto MPG data. The cells in which the directed edges are expected to appear from the ground truths, as shown in Figure 7, are highlighted in green.

Pattern 0

EFFECTED\CAUSE	"Displacement"	"Mpg"	"Horsepower"	"Weight"	"Acceleration"
"Displacement"	-	0.000	0.000	0.000	0.000
"Mpg"	0.999	-	0.997	1.000	1.000
"Horsepower"	0.999	0.000	-	0.000	0.000
"Weight"	0.635	0.000	0.000	-	0.000
"Acceleration"	0.996	0.023	0.998	0.998	-

Pattern 1

EFFECTED\CAUSE	"Displacement"	"Mpg"	"Horsepower"	"Weight"	"Acceleration"
"Displacement"	-	0.000	0.000	0.000	0.000
"Mpg"	1.000	-	0.128	0.484	0.058
"Horsepower"	1.000	0.056	-	0.001	0.000
"Weight"	0.994	0.000	0.000	-	0.000
"Acceleration"	0.859	0.000	0.828	0.998	-

Pattern 2

EFFECTED\CAUSE	"Displacement"	"Mpg"	"Horsepower"	"Weight"	"Acceleration"
"Displacement"	-	0.000	0.000	0.000	0.000
"Mpg"	1.000	-	0.999	1.000	0.984
"Horsepower"	1.000	0.000	-	0.000	0.000
"Weight"	0.997	0.000	0.000	-	0.000
"Acceleration"	0.995	0.002	0.996	0.999	-

Pattern 3

EFFECTED\CAUSE	"Displacement"	"Mpg"	"Horsepower"	"Weight"	"Acceleration"
"Displacement"	-	0.000	0.000	0.000	0.000
"Mpg"	0.977	-	0.969	0.754	0.547
"Horsepower"	1.000	0.051	-	0.696	0.010
"Weight"	0.954	0.000	0.000	-	0.000
"Acceleration"	0.981	0.000	0.435	0.809	-

Pattern 4

EFFECTED\CAUSE	"Displacement"	"Mpg"	"Horsepower"	"Weight"	"Acceleration"
"Displacement"	-	0.000	0.000	0.000	0.000
"Mpg"	0.995	-	0.994	0.997	0.940
"Horsepower"	0.999	0.314	-	0.006	0.000
"Weight"	0.999	0.000	0.012	-	0.000
"Acceleration"	0.964	0.000	0.989	0.814	-

unnatural results, has not affected the decision-making of GPT-4. From this behavior, it is inferred that the response regarding axiomatic and self-evident matters from GPT-4 is robust and unlikely to be affected by the SCP, even if the SCD result clearly exhibits unnatural behaviors.

In addition, while "Longitude"→"Temperature," which is assumed to be a ground truth, is unlikely to be asserted by GPT-4, "Temperature"→"Precipitation," which is not expected to be a ground truth, is likely to be asserted by GPT-4, across all the prompting patterns. For further interpretation of these unexpected behaviors from our ground truths, investigation of the response generated in the first prompting process is recommended. Interestingly, although the probabilities of "Longitude"→"Precipitation" are 0 in Patterns 0–2, they become non-zero finite values in Patterns 3 and 4, in which the causal coefficient of this directed

edge calculated with DirectLiNGAM is included in the SCP. This behavior may indicate that SCP can assist the decision-making of GPT-4 even if it generates an incomplete response on causal relationships with its background knowledge.

Table 16: Probabilities of the causal relationships suggested by GPT-4 in DWD climate data. The cells in which the directed edges are expected to appear from the ground truths as shown in Figure 9 are highlighted in green.

Pattern 0

EFFECTED\CAUSE	"Altitude"	"Temperature"	"Precipitation"	"Longitude"	"Sunshine"	"Latitude"
"Altitude"	-	0.000	0.000	0.000	0.000	0.000
"Temperature"	1.000	-	0.891	0.000	1.000	1.000
"Precipitation"	1.000	0.999	-	0.000	0.001	0.995
"Longitude"	0.000	0.000	0.000	-	0.000	0.000
"Sunshine"	1.000	0.000	0.998	0.000	-	1.000
"Latitude"	0.000	0.000	0.000	0.000	0.000	-

Pattern 1

EFFECTED\CAUSE	"Altitude"	"Temperature"	"Precipitation"	"Longitude"	"Sunshine"	"Latitude"
"Altitude"	-	0.000	0.000	0.000	0.000	0.000
"Temperature"	0.384	-	0.034	0.000	0.856	0.011
"Precipitation"	0.025	0.999	-	0.000	0.036	0.026
"Longitude"	0.000	0.000	0.000	-	0.000	0.000
"Sunshine"	0.006	0.011	0.008	0.000	-	0.596
"Latitude"	0.000	0.000	0.000	0.000	0.000	-

Pattern 2

EFFECTED\CAUSE	"Altitude"	"Temperature"	"Precipitation"	"Longitude"	"Sunshine"	"Latitude"
"Altitude"	-	0.000	0.000	0.000	0.000	0.000
"Temperature"	0.997	-	0.007	0.000	0.999	0.989
"Precipitation"	0.739	0.999	-	0.000	0.000	0.384
"Longitude"	0.000	0.000	0.000	-	0.000	0.000
"Sunshine"	0.874	0.010	0.976	0.000	-	0.981
"Latitude"	0.000	0.000	0.000	0.000	0.000	-

Pattern 3

EFFECTED\CAUSE	"Altitude"	"Temperature"	"Precipitation"	"Longitude"	"Sunshine"	"Latitude"
"Altitude"	-	0.000	0.000	0.000	0.000	0.000
"Temperature"	0.919	-	0.016	0.003	0.615	0.973
"Precipitation"	0.585	0.996	-	0.175	0.002	0.008
"Longitude"	0.000	0.000	0.000	-	0.000	0.000
"Sunshine"	0.039	0.000	0.001	0.875	-	0.199
"Latitude"	0.000	0.000	0.000	0.000	0.000	-

Pattern 4

EFFECTED\CAUSE	"Altitude"	"Temperature"	"Precipitation"	"Longitude"	"Sunshine"	"Latitude"
"Altitude"	-	0.000	0.000	0.000	0.000	0.000
"Temperature"	0.982	-	0.023	0.029	0.990	0.958
"Precipitation"	0.826	0.987	-	0.927	0.010	0.797
"Longitude"	0.000	0.000	0.000	-	0.000	0.000
"Sunshine"	0.534	0.021	0.387	0.013	-	0.638
"Latitude"	0.000	0.000	0.000	0.000	0.000	-

G.3 LLM-KBCI for Dataset of Health Screening Results

In Table 17, the probabilities of the causal relationships of pairs of variables in our sampled sub-dataset of health screening results are shown. The cells highlighted in red are those in which the directed edges are expected to appear, as described in Appendix C.4. In contrast, since "Age" is an unmodifiable background factor, it can be concluded that it is not a descendant of any other variables. Therefore, the probabilities in the cells highlighted in blue are expected to be 0.

Across all the prompting patterns, it is confirmed that all the probabilities of the causal effects on "Age" from other variables are indeed 0. From this fact, it is likely to be regarded by GPT-4 as axiomatic and self-evident that "Age" cannot be affected by other variables, and the judgement of causal relationships is not influenced by SCP, even if the SCD result clearly exhibits unnatural behaviors as shown in Figure 14.

Table 17: Probabilities of the causal relationships suggested by GPT-4 in the sampled sub-dataset of health screening results. The cells in which the directed edges are expected to appear from the ground truths are highlighted in red. In contrast, the probabilities in the cells highlighted in blue, are expected to be zero, since "Age" is expected to be a parent variable for all other variables.

Pattern 0

EFFECTED\CAUSE	"BMI"	"Waist"	"SBP"	"DBP"	"HbA1c"	"LDL"	"Age"
"BMI"	-	0.994	0.000	0.000	0.000	0.000	0.901
"Waist"	1.000	-	0.000	0.000	0.000	0.000	0.353
"SBP"	0.999	0.962	-	0.998	0.987	0.000	0.626
"DBP"	0.998	0.995	0.993	-	0.000	0.000	0.001
"HbA1c"	0.998	0.998	0.000	0.000	-	0.000	0.986
"LDL"	0.988	0.967	0.000	0.000	0.000	-	0.002
"Age"	0.000	0.000	0.000	0.000	0.000	0.000	-

Pattern 1

EFFECTED\CAUSE	"BMI"	"Waist"	"SBP"	"DBP"	"HbA1c"	"LDL"	"Age"
"BMI"	-	0.312	0.000	0.000	0.014	0.000	0.076
"Waist"	1.000	-	0.000	0.000	0.023	0.000	0.043
"SBP"	0.999	0.912	-	0.999	0.997	0.000	0.302
"DBP"	0.998	0.421	0.050	-	0.000	0.000	0.019
"HbA1c"	0.517	0.503	0.101	0.000	-	0.000	0.170
"LDL"	0.008	0.527	0.000	0.000	0.000	-	0.517
"Age"	0.000	0.000	0.000	0.000	0.000	0.000	-

Pattern 2

EFFECTED\CAUSE	"BMI"	"Waist"	"SBP"	"DBP"	"HbA1c"	"LDL"	"Age"
"BMI"	-	0.998	0.001	0.001	0.996	0.000	0.093
"Waist"	0.999	-	0.000	0.003	0.959	0.007	0.099
"SBP"	0.998	0.994	-	0.983	0.994	0.040	0.207
"DBP"	0.997	0.975	0.984	-	0.983	0.002	0.115
"HbA1c"	0.982	0.608	0.002	0.000	-	0.000	0.723
"LDL"	0.994	0.946	0.000	0.000	0.452	-	0.171
"Age"	0.000	0.000	0.000	0.000	0.000	0.000	-

Pattern 3

EFFECTED\CAUSE	"BMI"	"Waist"	"SBP"	"DBP"	"HbA1c"	"LDL"	"Age"
"BMI"	-	0.003	0.000	0.000	0.868	0.923	0.306
"Waist"	1.000	-	0.000	0.000	0.983	0.000	0.076
"SBP"	1.000	0.855	-	0.959	0.999	0.000	0.235
"DBP"	1.000	0.032	0.140	-	0.021	0.000	0.095
"HbA1c"	0.967	0.634	0.000	0.000	-	0.000	0.046
"LDL"	0.562	0.165	0.000	0.000	0.085	-	0.013
"Age"	0.000	0.000	0.000	0.000	0.000	0.000	-

Pattern 4

EFFECTED\CAUSE	"BMI"	"Waist"	"SBP"	"DBP"	"HbA1c"	"LDL"	"Age"
"BMI"	-	0.993	0.000	0.000	0.024	0.006	0.037
"Waist"	1.000	-	0.000	0.000	0.957	0.000	0.395
"SBP"	0.999	0.982	-	0.001	0.998	0.000	0.795
"DBP"	0.994	0.204	0.985	-	0.408	0.000	0.926
"HbA1c"	0.824	0.391	0.000	0.000	-	0.000	0.176
"LDL"	0.485	0.403	0.000	0.000	0.000	-	0.027
"Age"	0.000	0.000	0.000	0.000	0.000	0.000	-

H Applicability of the Proposed Method Across Various LLMs

In the main body of this paper, we fix the LLM to `GPT-4-1106-preview`, to maintain consistency and control across the trials with several kinds of datasets. In this section, however, to confirm the universal applicability of the proposed method, we conduct the same experiment of the proposed method with several LLMs, and confirm that adapting the results of LLM-KBCI as prior knowledge of SCD indeed further enhances the performance of SCD with various LLMs.

For this supplemental experiment, in addition to `GPT-4-1106-preview`, we have adopted `GPT-3.5-turbo-1106`, `GPT-3.5-turbo-0125`, `GPT-4-0125-preview`, and `GPT-4o-2024-08-06`. Although these LLMs are mutually different in architecture and generation, the format of the input and output, and the API settings (including the log-probability extraction) are standardized across the models. Therefore, the technical setup is standardized within this range of comparison, and it is easy to compare the performance of these LLMs in the proposed method.

As explained in Sections 1 and 3, LLMs are utilized both in Steps 2 and 3. Therefore, we choose the LLMs for these two steps independently, and confirmed every combination of LLMs in these steps. Furthermore, we adopt the prompting Pattern 0 (prompting without the results of SCD) for comparison, since the purpose of this experiment is to demonstrate that various LLMs can improve the SCD by providing prior knowledge. We also fix the dataset to DWD climate data, for the comparison of performance.

The experimental results are summarized in Table 18. In the same manner as Table 3 in Section 4.1, we evaluate the final SCD results obtained in Step 4, with SHD, FPR, FNR, precision, and F1 score, using the ground truth adjacency matrix **GT** as a reference. Furthermore, we also evaluate the CFI, RMSEA, and BIC of the causal structure obtained after Step 4, under the assumption of linear-Gaussian data; to evaluate the results with respect to the statistical validity of the calculated causal models. To evaluate the effect of **PK** augmentation by the LLMs in Pattern 0, the baseline result is that without **PK** (Baseline A).

It is clearly observed that in any combination of LLMs in Steps 2 and 3, SHD, FPR, FNR, and BIC after Step 4 become equal to or under the values of Baseline A (without **PK**), and that precision and F1 score after Step 4 become larger than those of Baseline A. These facts clearly suggest that the proposed method in this paper indeed improves the SCD results regardless of the LLMs adopted in Steps 2 and 3.

However, it is not clear from this table what types of LLMs can further improve the SCD results. For example, while the GPT-4 series have been reported to perform better than the GPT-3.5 series in many tasks (OpenAI, 2023), this tendency is not observed in Table 18. Moreover, although `GPT-3.5-turbo-0125` and `GPT-4-0125-preview` are updated models of `GPT-3.5-turbo-1106` and `GPT-4-0125-preview`, respectively, the improvement related to these updates is not observed in Table 18. Therefore, for the optimal selection of the LLMs for practical application of this method across various domains, further research is needed on the relationship between the LLM properties and the performance on causal reasoning tasks in each domain, including the possibility of adopting RAG or fine-tuning.

Table 18: Comparison of the SCD results in Pattern 0 (prompting without any SCD results) with the DWD climate dataset we have conducted. While the SHD, FPR, FNR, precision, and F1 score are compared to evaluate how close the results are to the ground truths, CFI, RMSEA, and BIC are compared to evaluate the statistical validity of the calculated causal models. Lower values are superior for SHD, FPR, FNR, RMSEA and BIC, and higher values for precision, F1 score and CFI. The values in the blue font are the same as those in Table 3, which are obtained only with `GPT-4-1106-preview`. Baseline A is used for the comparison with the SCD results augmented with *PK* generated by the LLM, to evaluate the effect of **PK** augmentation by the LLM. It is suggested that the proposed method in this paper indeed improves the SCD results regardless of the LLMs adopted in Steps 2 and 3.

LLM for Step 2	LLM for Step 3	SHD↓	FPR↓	FNR↓	Precision↑	F1score↑	CFI↑	RMSEA↓	BIC↓
wo **PK**(Baseline A)		10	0.33	0.67	0.17	0.22	1.00	0.00	99.53
gpt-3.5-turbo-1106	gpt-3.5-turbo-1106	4	0.07	0.33	0.67	0.67	0.93	0.16	51.98
	gpt-3.5-turbo-0125	4	0.07	0.33	0.67	0.67	0.93	0.16	51.98
	gpt-4-1106-preview	3	0.07	0.17	0.71	0.77	0.93	0.16	57.90
	gpt-4-0125-preview	4	0.07	0.33	0.67	0.67	0.93	0.16	51.98
	gpt-4o-2024-08-06	5	0.07	0.50	0.60	0.55	1.00	0.00	46.81
gpt-3.5-turbo-0125	gpt-3.5-turbo-1106	4	0.03	0.50	0.75	0.60	0.98	0.09	40.80
	gpt-3.5-turbo-0125	4	0.07	0.33	0.67	0.67	0.93	0.16	51.98
	gpt-4-1106-preview	5	0.07	0.50	0.60	0.55	1.00	0.00	46.81
	gpt-4-0125-preview	5	0.07	0.50	0.60	0.55	1.00	0.00	46.81
	gpt-4o-2024-08-06	4	0.07	0.33	0.67	0.67	1.00	0.00	52.67
gpt-4-1106-preview	gpt-3.5-turbo-1106	4	0.07	0.33	0.67	0.67	1.00	0.00	52.67
	gpt-3.5-turbo-0125	4	0.07	0.33	0.67	0.67	1.00	0.00	52.67
	gpt-4-1106-preview	4	0.07	0.33	0.67	0.67	1.00	0.00	52.67
	gpt-4-0125-preview	4	0.07	0.33	0.67	0.67	1.00	0.00	52.67
	gpt-4o-2024-08-06	4	0.07	0.33	0.67	0.67	1.00	0.00	52.67
gpt-4-0125-preview	gpt-3.5-turbo-1106	5	0.07	0.50	0.60	0.55	1.00	0.00	46.81
	gpt-3.5-turbo-0125	4	0.07	0.33	0.67	0.67	0.93	0.16	51.98
	gpt-4-1106-preview	5	0.07	0.50	0.60	0.55	1.00	0.00	46.81
	gpt-4-0125-preview	5	0.07	0.50	0.60	0.55	1.00	0.00	46.81
	gpt-4o-2024-08-06	5	0.07	0.50	0.60	0.55	1.00	0.00	46.81
gpt-4o-2024-08-06	gpt-3.5-turbo-1106	4	0.03	0.50	0.75	0.60	0.98	0.09	40.80
	gpt-3.5-turbo-0125	4	0.07	0.33	0.67	0.67	1.00	0.00	52.67
	gpt-4-1106-preview	5	0.07	0.50	0.60	0.55	1.00	0.00	46.81
	gpt-4-0125-preview	5	0.07	0.50	0.60	0.55	1.00	0.00	46.81
	gpt-4o-2024-08-06	7	0.10	0.67	0.40	0.36	0.51	0.53	42.85