Last-Mile Embodied Visual Navigation

Abstract: Realistic long-horizon tasks like image-goal navigation involve exploratory and exploitative phases. Assigned with an image of the goal, an embodied agent must explore to *discover the goal*, *i.e.*, search efficiently using learned priors. Once the goal is discovered, the agent must accurately calibrate the *last-mile of navigation* to the goal. As with any robust system, *switches* between exploratory goal discovery and exploitative last-mile navigation enable better recovery from errors. Following these intuitive guide rails, we propose SLING to improve performance of existing image-goal navigation systems. Entirely complementing prior methods, we focus on last-mile navigation, and leverage the underlying geometric structure of the problem with neural descriptors. With simple but effective switches, we can easily connect SLING with heuristic, reinforcement learning, and neural modular policies. On a standardized image-goal navigation benchmark [1], we improve performance across policies, scenes, and episode complexity, raising the state-of-the-art from 45% to 55% success rate. Beyond photorealistic simulation, we conduct real-robot experiments in three physical scenes and find these improvements to transfer well to real environments.

Keywords: Visual Navigation, Embodied AI, Image-Goal Navigation, Topological Maps, Perspective-n-Point, AI Habitat, Sim-to-Real.

1 Introduction

Imagine you are at a friend's home and you want to find the couch you have seen in your friend's photo. At first, you use semantic priors *i.e.* priors about the semantic structure of the world, to navigate to the living room (a likely place for the couch). But as soon as you get the first glimpse of the couch, you implicitly estimate the relative position of the couch, use intuitive geometry, and navigate towards it. We term the latter problem, of navigating to a visible object or region, as last-mile navigation.

The field of visual navigation has had a rich history. Early approaches used hand-designed features with geometry for mapping followed by standard planning algorithms. But such an approach fails to capture the necessary semantic priors that could be learned from data. Therefore, in recent years, we have seen more efforts and significant advances in capturing these priors for semantic navigation tasks such as image-goal [2, 3, 4, 1, 5, 6] and object-goal navigation [7, 8, 9, 10]. The core idea is to train a navigation policy using reinforcement or imitation learning and capture semantics. But in an effort to capture the semantic priors, these approaches almost entirely bypass the underlying geometric structure of the problem, specifically when the object or view of interest has already been discovered.

One can argue that last mile navigation can indeed be learned from data itself. We agree that, in principle, it can be. However, we argue and demonstrate that an unstructured local policy for last-mile navigation is either (a) sample inefficient (billions of frames in an RL framework [11]) or (b) biased and generalize poorly when learned from offline-demonstrations (due to distributional shift [12, 13]). Therefore, our solution is to revisit the basics! We propose **S**witchable **L**ast-Mile

Submitted to the 6th Conference on Robot Learning (CoRL 2022). Do not distribute.

(a) Phases in Image-Goal Navigation   (b) Policy Overview

Figure 1: **Switchable Last-Mile Image-Goal Navigation**. (a) Long-horizon semantic tasks such as image-goal navigation involve exploratory discovery of goals and exploitative last-mile navigation, (b) An overview of SLING that allows for *switching* between policies from prior work and our last-mile navigation module.

Image-Goal **N**avi**g**ation (SLING) – a simple yet very effective geometric navigation module and associated switches. Our approach can be combined with any off-the-shelf learned policy that uses semantic priors to explore the scene. As soon as the object or view of interest is detected, the SLING switches to the geometric navigation module. We observe that SLING provides significant performance gains across baselines, simulation datasets, episode difficulty, and real-world scenes.

Our key contributions are: (1) A general-purpose last-mile navigation module and switches, that we connect with five diverse goal discovery methods, leading to improvements across the board. (2) A new state-of the-art of 55.4% success *i.e.* a huge jump of 22.4% *vs*. published work [5] and 9.8% *vs*. a concurrent preprint [6], on the most widely-tested fold (Gibson-curved) of the AI Habitat image-goal navigation benchmark [1]; (3) Extensive robot experiments of image-goal navigation in challenging settings with improved performance over a neural, modular policy [1] trained on real-world data [14].

2   Related Work

Prior work in visual navigation and geometric 3D vision is pertinent to SLING.

Embodied navigation. Anderson *et al*. [15] formalized different goal definitions and metrics for evaluation of embodied agents. In point-goal navigation, relative coordinates of the goal are available (either at all steps [16, 11, 17, 18] or just at the start of an episode [9, 19, 20]). Successful navigation to a point-goal could be done without semantic scene understanding, as seen by competitive depth-only agents [16, 11]. Semantic navigation entails identifying the goal through an image (image-goal [1, 2]), acoustic cues (audio-goal [21, 22]), or a category label (object-goal [8, 9]). In this work, we focus on image-goal navigation in visually rich environments.

Image-goal navigation. Chaplot *et al*. [3] introduced a modular and hierarchical method for navigating to an image-goal that utilizes a topological map memory. Kwon *et al*. [23] introduced a memory representation based on image similarity, which in turn is learned in an unsupervised fashion from unlabeled data and agent's observed images. Following up on [3], NRNS [1] improves the topological-graph-based architecture and open-sourced a public dataset and IL and RL baselines [11, 3], within AI Habitat. This dataset has been adopted for standardized evaluation [5, 6]. ZER [5] focuses on transferring an image-goal navigation policy to other navigation tasks. In a concurrent preprint, Yadav *et al*. [6] utilize self-supervised pretraining [24] to improve end-to-end visual RL policy [11] for the image-goal navigation benchmark. Our contributions are orthogonal to the above, and can be easily combined with them, as we demonstrate in Sec. 4.

Last-mile navigation. The works included above focus primarily on goal discovery. In contrast, recent works have also identified 'last-mile' errors that occur when the goal is in sight of or close to the agent. For multi-object navigation, Wani *et al.* [25] observed a two-fold improvement when allowing an error budget for the final 'found' or 'stop' actions. Chattopadhyay *et al.* [26] found the last step of navigation to be brittle *i.e.* small perturbations lead to severe failures. Ye *et al.* [10] identified last-mile errors as a prominent error mode (10% of the failures) in object-goal navigation. However, none of these works address the problem with the last-mile of navigation.

Connections to 3D vision. The objective of our last-mile navigation module is to predict the relative camera pose between two images *i.e.* agent's view and image-goal. To this end, pose estimation of a calibrated camera from 3D-to-2D point correspondences connects our embodied navigation task to geometric 3D computer vision. The Perspective-n-Point (PnP) formulation, with extensive research and efficient solvers [27, 28, 29], fits this use-case perfectly. To find an accurate PnP solution, locating correspondences between local features of the two images is critical. We utilize SuperGlue *et al.* [30] that is based on correspondences learned via attention graph neural nets and partial assignments. We defer details of PnP and finding correspondences to Sec. 3.3, to make the approach self-sufficient. Notably, different from related 3D vision works, we apply PnP solvers to sequential decision making in embodied settings, particularly, image-goal navigation.

3 SLING

In this section, we begin with an overview of the task and the entire pipeline of SLING. We then discuss the implementations for goal discovery, our proposed module for last-mile navigation, and switches to easily combine it with prior works. While we explain key design choices in the main paper, a supplementary description and a list of hyperparameters, for effective reproducibility, is deferred to the Appendix A.

3.1 Overview

We follow the image-goal navigation task benchmark by Hahn *et al.* [1] (similar to prior formulations [2, 3]). The agent observes an RGB image $\mathbf{I}_a$, a depth map $\mathbf{D}_a$, and the image-goal $\mathbf{I}_g$. The agent can sample actions from $\mathcal{A} = \{$move forward, turn right, turn left, stop$\}$. The stop action terminates the episode.

As shown in Fig. 1a, we divide image-goal navigation into – a goal discovery and a last-mile navigation phase. In the goal discovery phase, the agent is responsible for discovering the goal *i.e.* navigating close enough for the goal to occupy a large portion of the egocentric observation ('goal discovered' image). Fig. 1b shows how the control flows between modules. If the *explore→exploit* switch isn't triggered, learning-based exploration will continue. Otherwise, if the *explore→exploit* switch triggers, the agent's observations now overlap with the image-goal and the control flows to the last-mile navigation module. We find that a one-sided flow (as attempted in [1, 3]) from *explore→exploit* is too optimistic. Therefore, we introduce symmetric switches, including one that flows control back to goal discovery.

3.2 Goal Discovery

We can combine our versatile last-mile navigation module and switching mechanism with any prior method. We demonstrate this with five diverse goal discovery (GD) implementations.

Straight [31]. A simple, heuristic exploration where the agent moves forward and unblocks itself, if stuck, by turning right (similar to an effective exploration baseline in [31]).

Distance Prediction Network (NRNS-GD) [1]. Exploratory navigation is done by proposing waypoints in navigable areas (determined utilizing the agent's depth mask), history is maintained using a topological map, and processed using graph neural nets. The minimum cost waypoint is chosen utilizing outputs from a distance prediction network. More details in the Appendix B and [1].

Figure 2: **Last-Mile Navigation module.** Neural keypoint features descriptors are extracted and matched to obtain correspondences between agent's view and image-goal. The geometric problem of estimating the relative pose between the agent and goal view is solved using efficient perspective-n-point. A *exploit→explore* switch, if triggered, flows control back to the goal discovery phase. Else, the estimations are fed into a local policy head to decide the agent's actions.

Decentralized Distributed PPO (DDPPO-GD) [11]. An implementation of PPO [32] for photorealistic simulators where rendering is the computational bottleneck. This has been a standard end-to-end deep RL baseline in prior works, across tasks [18, 1, 5, 6, 33].

Offline Visual Representation Learning (OVRL-GD) [6]. A DDPPO network, with its visual encoder pretrained using self-supervised pretext tasks [24] on images obtained from 3D scans [34].

Environment-State Distance Prediction (Oracle-GD). To quantify the effect of errors coming from the goal discovery phase, we devise an upper bound. This is an oracle variant of NRNS-GD that directly accesses the environment state to obtain distances for goal discovery phase. For details of its construction, see Appendix B.

3.3 Last-Mile Navigation

The proposed last-mile navigation module transforms the agent's observations and image-goal to actions that takes the agent closer to the goal. The steps are shown in Fig. 2 and detailed next.

Neural Feature Extractor. We first transform agent's RGB $\mathbf{I}_a$ to local features $(\hat{\mathbf{X}}_{\mathbf{a}}, \mathbf{F}_a)$, where $\hat{\mathbf{X}}_{\mathbf{a}} \in \mathbb{R}^{n_a \times 2}$ are the positions and $\mathbf{F}_a \in \mathbb{R}^{n_a \times k}$ are the visual descriptors in the agent's image. Here, n_a is the number of detected local features and k is the length of each descriptor. Similarly, $\mathbf{I}_g$ leads to features $(\hat{\mathbf{X}}_{\mathbf{g}}, \mathbf{F}_g)$, where $\hat{\mathbf{X}}_{\mathbf{g}} \in \mathbb{R}^{n_g \times 2}$ and $\mathbf{F}_g \in \mathbb{R}^{n_g \times k}$ with n_g local features in the image-goal. Following DeTone *et al.* [35], we adopt an interest-point detector, pretrained on synthetic data followed by cross-domain homography adaptation (here, $k = 256$).

Matching Module. From extracted features $(\hat{\mathbf{X}}_{\mathbf{a}}, \mathbf{F}_a)$ and $(\hat{\mathbf{X}}_{\mathbf{g}}, \mathbf{F}_g)$, we predict matched subsets $\mathbf{X}_{\mathbf{a}} \in \mathbb{R}^{n \times 2}$ and $\mathbf{X}_{\mathbf{g}} \in \mathbb{R}^{n \times 2}$. The matching is optimized to have $\mathbf{X}_{\mathbf{a}}$ and $\mathbf{X}_{\mathbf{g}}$ correspond to the same point. We utilize an attention-based graph neural net that tackles partial matches and occlusions well using an optimal transport formulation, following Sarlin *et al.* [30].

Lifting Points from 2D→3D. Next, the agent's 2D local features are lifted to 3D with respect to the agent's coordinate frame *i.e.* $\mathbf{P}_a \in \mathbb{R}^{n \times 3}$. This is done by utilizing the camera intrinsic matrix $\mathbf{K}$ (particularly, principle point p_x, p_y and focal lengths f_x, f_y) and the corresponding depth values for each position in $\mathbf{X}_{\mathbf{a}}$, say $\mathbf{d}_{\mathbf{a}} \in \mathbb{R}^n$. The i^{th} row of $\mathbf{P}_a$ is calculated as

$$\mathbf{P}_a\,(i, :) = \left(\frac{\mathbf{X}_{\mathbf{a}}(i, 1) - p_x}{f_x} * \mathbf{d}_{\mathbf{a}}(i), \frac{\mathbf{X}_{\mathbf{a}}(i, 2) - p_y}{f_y} * \mathbf{d}_{\mathbf{a}}(i), \mathbf{d}_{\mathbf{a}}(i) \right), \tag{1}$$

where $\mathbf{X}_{\mathbf{a}}(i, 1)$ and $\mathbf{X}_{\mathbf{a}}(i, 2)$ correspond to the x and y coordinate of i^{th} feature in $\mathbf{X}_{\mathbf{a}}$, respectively. Formally, $\mathbf{d}_{\mathbf{a}}(i) := \mathbf{D}_a\,(\mathbf{X}_{\mathbf{a}}(i, 1), \mathbf{X}_{\mathbf{a}}(i, 2))$.

Perspective-n-Point. The objective of the next step *i.e.* Perspective-n-Point (PnP) is to find the rotation and translation between agent and goal camera pose that minimized reprojection error. Concretely, for a given rotation matrix $\mathbf{R} \in \mathbb{R}^{3 \times 3}$ and translation vector $\mathbf{t} \in \mathbb{R}^3$, the 3D positions $\mathbf{P}_a$ of local features can be reprojected from the coordinate system of the agent to that of the goal camera:

$$\begin{bmatrix} \tilde{\mathbf{X}}_{\mathbf{g}} \\ 1 \end{bmatrix} = \mathbf{K}\,[\mathbf{R}|\mathbf{t}] \begin{bmatrix} \mathbf{P}_a \\ 1 \end{bmatrix}; \qquad \text{Reprojection error } e = \|\tilde{\mathbf{X}}_{\mathbf{g}} - \mathbf{X}_{\mathbf{g}}\|_2^2. \tag{2}$$

where $\tilde{\mathbf{X}}_{\mathbf{g}}$ are the reprojected positions. Minimizing the reprojection error e, via ePnP [29] and RANSAC [27] (to handles outliers), we obtain the predicted rotation and translation. The reprojection is visualized in Fig. 2, where the agent's amber point is lifted and reprojected in goal camera coordinates. The reprojection is different from its correspondence in the goal image.

Estimating Distance and Heading to Goal. The predicted translation $\mathbf{t}$ can help calculate the distance $\rho = \|\mathbf{t}\|_2$ from the agent to the goal. Similarly, the heading ϕ from the agent to the goal can be obtained from the dot product of the unit vectors along the optical axis (of the agent's view) and $\mathbf{t}$. Concretely, $\phi = \text{sgn}(t[1]) * \arccos\left(\mathbf{t} \cdot \mathbf{o}_a / \|\mathbf{t}\|_2 \|\mathbf{o}_a\|_2\right)$. The sign comes from $t[1]$ which points along the axis perpendicular to the agent's optical axis, but parallel to the ground. The sign is particularly important when calculating heading as it distinguishes between the agent turning right or left.

Local policy. Finally, the distance ρ and heading ϕ between the agent's current position to the estimated goal are utilized to estimate actions in the action space $\mathcal{A}$ to reach the goal. Following accuracte implementations [36, 1], we adopt a local metric map to allow the agent to heuristically avoid obstacles and move towards the goal. For further details, see Appendix A.

3.4 Switches

We define simple but effective switches between the two phases of goal discovery (*explore*) and last-mile navigation (*exploit*). The *explore→exploit* switch is triggered if the number of correspondences $n > n_{\text{th}}$, where n_{th} is a set threshold. This indicates that agent's image has significant overlap with the image-goal, so control can flow to the last-mile navigation phase. We find that this simple switch performs better than training a specific deep net to achieve the same (variations attempted in [1, 3, 4]). For *exploit→explore*, if the optimization for $\mathbf{R}, \mathbf{t}$ (see Eq. (2)) fails or if the predicted distance is greater than d_{th} (tuned to 4m), the agent returns to goal discovery phase.

4 Experiments

We report results for image-goal navigation both in photorealistic simulation and real-world scenes.

4.1 Data and Evaluation

We evaluate image-goal navigation policies on the benchmark introduced by Hahn *et al*. [1] and follow their evaluation protocol and folds. The benchmark consists of numerous folds: {Gibson [37], MP3D [38]}×{straight, curved}×{easy, medium, hard}. For a direct comparison to prior work [3, 1, 5, 6] that reports primarily on 'Gibson-curved' fold, we follow the same in the main paper (and defer results on more folds to the Appendix C). Particularly for MP3D, following [5], we also show (zero-shot) cross-domain transfer of the models that are available only in Gibson. Performance on image-goal navigation is chiefly evaluated via two metrics – percentage of successful episodes (*success*) and success weighted by inverse path length (*SPL*) [15]. The objective of the image-goal navigation task is to execute `stop` within $1m$ of the goal location. The agent is allowed 500 steps.

4.2 Methods

We compare our last-mile navigation with several standardized baselines [39, 11, 1]. Note that field-of-view, rotation amplitude, *etc*. vary across baselines and we adopt the respective settings for fair comparison (specific details are included in Appendix A). Prior methods use a mix of sensors including RGB, depth, and agent pose, but no dense displacement vector to the goal.

Behavior Cloning with Spatial Memory. Applies imitation learning (IL) wherein $\mathbf{I}_a$ and $\mathbf{I}_g$ are represented with ResNet18 [40]. Moreover, using the depth map $\mathbf{D}_a$, the observations are represented as a spatial metric map (found to be effective across embodied AI tasks [36, 25]).

Behavior Cloning with GRU. Another IL baseline where the observations at each time step are encoded identical to the above. However, instead of the spatial metric map, a GRU [41] is employed (CNN-RNN architectures have been effective for semantic navigation [42, 43, 21, 44]).

Table 1: **Results for 'Gibson-curved' and 'MP3D-curved' episodes.** Note the significant gains adding SLING to prior works. Similar trends are seen in straight counterpart (tables in Appendix C).

	Method	Overall		Easy		Medium		Hard	
		Succ↑	SPL↑	Succ↑	SPL↑	Succ↑	SPL↑	Succ↑	SPL↑
					Gibson-curved				
1	BC w/ Spatial Memory [39]	1.3	1.1	3.1	2.5	0.8	0.7	0.2	0.1
2	BC w/ GRU [39, 41]	1.7	1.3	3.6	2.8	1.1	0.9	0.5	0.3
3	DDPPO [11] (from [1])	15.7	12.9	22.2	16.5	20.7	18.5	4.2	3.7
4	NRNS [1]	21.7	8.1	31.4	10.7	22.0	8.2	11.9	5.4
5	ZER [5]	33.0	23.6	48.0	34.2	36.0	25.9	15.1	10.8
6	OVRL [6]	45.6	28.0	53.6	31.8	47.6	30.2	35.6	22.0
7	SLING + Straight-GD	19.5	7.7	39.2	14.3	11.7	5.4	7.7	3.6
8	SLING + DDPPO-GD	37.9	22.8	52.2	32.7	42.2	25.2	19.4	10.5
9	SLING + NRNS-GD	43.5	15.1	58.7	17.4	47.0	17.4	25.0	10.5
10	SLING + OVRL-GD	**55.4**	**37.4**	**68.4**	**47.0**	**57.7**	**39.8**	**40.2**	**25.5**
					MP3D-curved				
11	ZER [5] *(cross-domain)*	14.6	10.8	27.5	20.6	12.2	8.9	4.2	2.8
12	OVRL [6] *(cross-domain)*	16.9	8.3	25.8	13.5	14.3	7.0	10.6	4.6
13	SLING + OVRL [6] *(cross-domain)*	31.7	**18.8**	47.5	30.2	28.4	**17.0**	19.3	9.3
14	NRNS [1]	15.5	7.4	23.1	10.8	15.1	7.3	8.4	4.1
15	SLING + NRNS-GD	**32.6**	14.9	43.2	19.7	**32.5**	15.1	**22.1**	**9.9**

Zero Experience Replay (ZER) [5]. A recent plug-and-play RL policy trained using rewards obtained from moving closer to the goal and to look towards it, as well as view augmentation. The authors shared metrics over the folds of the benchmark [1], particularly Gibson-curved and *cross-domain* transfer results on MP3D, which we include in Tab. 1.[1]

DDPPO [11], NRNS [1], OVRL [6]. These methods have been described as part of goal discovery, see Sec. 3.2. For DDPPO, we report results from Hahn *et al.* [1], trained for 100M steps (10x more compute than NRNS). For NRNS, we report the reproducible metrics from their official implementation (differs slightly from the paper [1]). At time of submission, OVRL is the best-performing method on Gibson-curved fold of the benchmark [1]. For OVRL, we requested their checkpoints, and re-evaluated them to report detailed metrics across easy-medium-hard folds.

SLING & Ablations. For a comprehensive empirical study, we combine SLING with Straight-GD, NRNS-GD, DDPPO-GD, OVRL-GD, and Oracle-GD (see Sec. 3.2 for details). Further, we include clear ablations to show the efficacy of the components of our method and robustness to realistic pose and depth sensor noise:
- *w/ MLP switch:* instead of SLING's explore→exploit switch (that utilizes geometric structure), if a MLP[2] detects similarity between the agent and goal images (as in [1]).
- *w/o Recovery:* if the *exploit→explore* switch is removed *i.e.* one-sided flow of control.
- *w/o Neural Features:* if the neural features [35] are replaced with traditional features [45].
- *w/ Pose Noise:* add noise to pose that emulates real-world sensors [36, 46] (same as [3, 1])
- *w/ Depth Noise:* imperfect depth by adopting Redwood Noisy Depth model [47] in AI Habitat.
- *w/ Oracle-GD:* an upper bound, using ground-truth distances from the simulator (see Sec. 3.2).

4.3 Quantitative Results

In the following, we include takeaways based on the results in Tab. 1 and Tab. 2.

State-of-the-art performance. As Tab. 1 details, SLING + OVRL-GD outperforms a suite of IL, RL, and neural modular baselines. The gibson-curved fold is widely adopted in prior works and hence the focus in the main paper. With a 55.4% overall success and 37.4 SPL we are the best performing method on the benchmark, improving success rate by 22.4% *vs*. ZER and 9.8% *vs*. OVRL ('overall success' column of rows 5,6, and 10).

---

[1]We could not include a 'SLING + ZER-GD' modification or retrain ZER for MP3D results as ZER checkpoints and code could not be made public by the authors.

[2]trained over an offline dataset of expert demonstrations, where adjacent nodes in a topological graph (that they maintain) are considered positives

Table 2: **Ablations on 'Gibson-curved' episodes.** Both switches are key to SLING's performance. SLING is resilient to sensor noise. Even with Oracle-GD, performance improves if SLING is added.

	Method	Overall		Easy		Medium		Hard	
		Succ↑	SPL↑	Succ↑	SPL↑	Succ↑	SPL↑	Succ↑	SPL↑
1	NRNS [1]	21.7	8.1	31.4	10.7	22.0	8.2	11.9	5.4
2	SLING + NRNS	43.5	15.1	58.7	17.4	47.0	17.4	25.0	10.5
3	w/ MLP Switch	42.5	14.8	55.4	16.7	47.3	17.3	24.9	10.5
4	w/ MLP Switch w/o Recovery	31.5	11.5	45.6	14.3	32.8	12.9	16.1	7.3
5	w/o Neural Features	33.7	11.3	47.5	13.5	35.9	13.0	17.7	7.5
6	w/ Pose Noise	43.7	14.3	58.6	16.1	47.6	16.8	24.9	10.1
7	w/ Pose & Depth Noise	43.5	14.0	56.9	15.9	47.2	15.9	26.6	10.3
8	NRNS + Oracle-GD *(upper bound)*	67.7	60.2	68.5	58.4	71.2	63.7	63.5	58.7
9	SLING + Oracle-GD *(upper bound)*	86.2	74.8	85.9	72.2	88.6	77.7	84.3	74.6

SLING works across methods. Using switches, we add our last-mile navigation module to DDPPO [11], NRNS [1], and OVRL [6], and observe gains across the the board. Shown in Tab. 1, SLING improves the success rate of DDPPO by 22.2%, NRNS by 21.8%, and OVRL by 9.8% (rows 3 & 8, 4 & 9, 6 & 10, respectively). Quite surprisingly, SLING even with simple straight exploration, can outperform deep IL and RL baselines (rows 1, 2, & 3).

SLING succeeds across scene datasets Similar improvements are also seen in MP3D scenes – adding SLING to NRNS improves success by 17.1% (rows 14 & 15). In a cross-domain transfer setting, SLING improves the overall success of OVRL by 14.8% (rows 12 & 13).[3] Despite it's cross-domain setting, SLING + OVRL-GD performs best in overall SPL (18.8%) and over several folds of MP3D-curved. NRNS lags behind in planning efficient routes, as evidenced by lower SPL compared to other methods (see rows 4, 9, and 14).

SLING is resilient to sensor noise. As shown in rows 6 & 7 of Tab. 2, minor drops in performance are observed despite challenging noise in pose and depth sensors – SPL successively reduces 15.1→14.3→14.0% (rows 2→6→7).

Geometric switches are better. Performance reduces if we swap out SLING's explore→exploit switch with the MLP switch of NRNS [1]. The effect is exasperated when SLING's exploit→explore switch is also removed, leading to a drop of 12% (rows 2 and 4). The neural features utilized in SLING are useful, as seen by comparing rows 2 and 5. Further, over a set of 6500 image pairs, we evaluate the accuracy of switches. SLING's explore→exploit switch is 92.0% accurate and MLP switch [1] is only at 82.1%. Also, SLING exploit→explore switch is 84.1% accurate while NRNS doesn't have such a recovery switch (details of this study in Appendix D).

Improvements with Oracle-GD. Even if we assume a perfect variant of goal discovery module from [1], we observe that performance saturates at 67.7% success (row 8, Tab. 2). Comparing rows 8 and 9, SLING can boost this asymptotic success rate by 18.5% (67.7→86.2%).

Analysis: Why is SLING more robust? In Fig. 3a, we visualize the frequency distribution of heading (from the agent to the target) in expert demonstrations [1] ('train GT') and that observed at inference ('test GT'). With no geometric structure, NRNS picks up the bias in training data, particularly, towards the heading of 0 (optimal trajectories entail mostly moving forward). Concretely, 72.2% of the training data is within $[-15°, 15°]$. This drops to 39.4% at test time, when the last-mile navigation phase is reached (using the best-performing Oracle-GD). Quantified with (first) Wassertein distance, $W(\text{Test GT}, \text{NRNS}) = 0.0134$ *vs.* $W(\text{Test GT}, \text{SLING}) = 0.0034$, demonstrating SLING can better match the distribution at inference.

4.4 Physical Robot Experiments

We test the navigation policies on a TerraSentia [48] wheeled robot, equipped with an Intel® RealSense™ D435i depth camera (further hardware details in Appendix E). The robot is initialized in an unseen indoor environment and provided an RGB image-goal. We ran a total of 120 trajectories,

---

[3]Since [6] does not train OVRL on MP3D, we can include only a cross-domain evaluation, following [5].

(a) Bias in heading distribution

(b) Physical experimental setup

Figure 3: (a) Significant distribution shift between training and test heading from agent to goal (Sec. 4.3), (b) Navigation policies deployed on a robot in cluttered real-world scenes (Sec. 4.4).

requiring 30 human hours of effort, across three scenes and two levels of difficulty. Particularly, we test within an office and the common areas in two department buildings, over easy and hard episodes (following definitions from [1]). The physical setup (office) is shown in Fig. 3b. As in simulation, the agent is successful if it executes stop action within 1m of the goal. Examples of the image-goal utilized in physical robot experiments and precautions taken are included in Appendix E.

As shown in Tab. 3, for sim-to-real experiments, we base the goal discovery module on the NRNS model. We choose NRNS as the authors published an instantiation trained exclusively on real-world trajectories, particularly, RealEstate10K [14] (house tours videos from YouTube). In preliminary experiments, we verified that

Method	Easy		Hard	
	Succ↑	SPL↑	Succ↑	SPL↑
NRNS [1]	40.0	37.7	3.3	3.3
+ SLING	**56.6**	**53.7**	**20.0**	**19.3**

Table 3: Results in real-world scenes

this NRNS instantiation outperformed its simulation counterpart. For a direct comparison, in SLING + NRNS-GD, we utilize the same goal discovery module but add our switching and last-mile navigation module (SLING) around it. With SLING, we improve performance from 40.0% success to 56.6%. The gains become more prominent as the task horizon increases, leading to an improvement in success rate from 3.3% to 20.0%.

4.5 Limitations

Here, we include limitations of SLING. *First*, we rely on correspondences *i.e.* mistakes in keypoint feature extraction or matching failures directly lead to errors in predicted actions (neural features [35] reduce this effect). *Second*, as we add structure to the last-mile navigation problem, we also add design parameters like distance threshold d_{th} and correspondence threshold n_{th}. The latter we tuned depending on the size of the image (640×480 in NRNS and 128×128 in OVRL). *Third*, currently in SLING we utilize only the agent's current observation for estimating distance and heading. Using temporal smoothening could make our prediction more robust.

Following the baselines proposed in the benchmark [1], we also assume access to depth and pose sensors. Studies in [5] also show improvements when using depth and pose sensors. For physical experiments, the robot comes equipped with an inexpensive depth camera, and uses SLAM [49] for pose estimations. While we demonstrate robustness to sensor noise (Tab. 2), in future work, we could try relaxing this assumption with a depth prediction module.

5 Conclusion

In this work, we identify and leverage the geometric structure of last-mile navigation for the challenging image-goal navigation task [1]. With analysis of data distributions, we demonstrate that learning from expert demonstrations may lead to developing a bias. Being entirely complementary to prior work, we demonstrate that adding SLING leads to improvements across data splits, episode complexity, and goal discovery policies, establishing the new state-of-the-art for image-goal navigation [1]. We also transfer policies trained in simulation to real-world scenes and demonstrate significant gains in performance. Further improvements in switching mechanism, neural keypoint features, visual representations from view augmentations, *etc.* complement our proposed approach to help improve performance in future work.

References

[1] M. Hahn, D. S. Chaplot, S. Tulsiani, M. Mukadam, J. M. Rehg, and A. Gupta. No rl, no simulation: Learning to navigate without navigating. *Advances in Neural Information Processing Systems*, 2021.

[2] Y. Zhu, R. Mottaghi, E. Kolve, J. J. Lim, A. Gupta, L. Fei-Fei, and A. Farhadi. Target-driven Visual Navigation in Indoor Scenes using Deep Reinforcement Learning. In *ICRA*, 2017.

[3] D. S. Chaplot, R. Salakhutdinov, A. Gupta, and S. Gupta. Neural topological slam for visual navigation. In *CVPR*, 2020.

[4] X. Meng, N. Ratliff, Y. Xiang, and D. Fox. Scaling local control to large-scale topological navigation. In *ICRA*, 2020.

[5] Z. Al-Halah, S. K. Ramakrishnan, and K. Grauman. Zero experience required: Plug & play modular transfer learning for semantic visual navigation. In *CVPR*, 2022.

[6] K. Yadav, R. Ramrakhya, A. Majumdar, V.-P. Berges, S. Kuhar, D. Batra, A. Baevski, and O. Maksymets. Offline visual representation learning for embodied navigation. *arXiv preprint arXiv:2204.13226*, 2022.

[7] D. S. Chaplot, D. P. Gandhi, A. Gupta, and R. R. Salakhutdinov. Object goal navigation using goal-oriented semantic exploration. *NeurIPS*, 2020.

[8] D. Batra, A. Gokaslan, A. Kembhavi, O. Maksymets, R. Mottaghi, M. Savva, A. Toshev, and E. Wijmans. Objectnav revisited: On evaluation of embodied agents navigating to objects. *arXiv preprint arXiv:2006.13171*, 2020.

[9] H. Team. Habitat CVPR challenge, 2020. URL https://aihabitat.org/challenge/2020/.

[10] J. Ye, D. Batra, A. Das, and E. Wijmans. Auxiliary tasks and exploration enable objectgoal navigation. In *ICCV*, 2021.

[11] E. Wijmans, A. Kadian, A. Morcos, S. Lee, I. Essa, D. Parikh, M. Savva, and D. Batra. Dd-ppo: Learning near-perfect pointgoal navigators from 2.5 billion frames. In *ICLR*, 2019.

[12] S. Ross, G. Gordon, and D. Bagnell. A reduction of imitation learning and structured prediction to no-regret online learning. In *AISTATS*, 2011.

[13] S. Levine, A. Kumar, G. Tucker, and J. Fu. Offline reinforcement learning: Tutorial, review, and perspectives on open problems. *arXiv preprint arXiv:2005.01643*, 2020.

[14] T. Zhou, R. Tucker, J. Flynn, G. Fyffe, and N. Snavely. Stereo magnification: Learning view synthesis using multiplane images. *arXiv preprint arXiv:1805.09817*, 2018.

[15] P. Anderson, A. Chang, D. S. Chaplot, A. Dosovitskiy, S. Gupta, V. Koltun, J. Kosecka, J. Malik, R. Mottaghi, M. Savva, et al. On evaluation of embodied navigation agents. *arXiv preprint arXiv:1807.06757*, 2018.

[16] M. Savva, A. Kadian, O. Maksymets, Y. Zhao, E. Wijmans, B. Jain, J. Straub, J. Liu, V. Koltun, J. Malik, D. Parikh, and D. Batra. Habitat: A Platform for Embodied AI Research. In *ICCV*, 2019.

[17] H. Team. Habitat CVPR challenge, 2019. URL https://aihabitat.org/challenge/2019/.

[18] J. Ye, D. Batra, E. Wijmans, and A. Das. Auxiliary tasks speed up learning pointgoal navigation. In *CoRL*, 2020.

[19] H. Team. Habitat CVPR challenge, 2021. URL https://aihabitat.org/challenge/2021/.

[20] S. Datta, O. Maksymets, J. Hoffman, S. Lee, D. Batra, and D. Parikh. Integrating egocentric localization for more realistic point-goal navigation agents. *CoRL*, 2020.

[21] C. Chen, U. Jain, C. Schissler, S. V. A. Gari, Z. Al-Halah, V. K. Ithapu, P. Robinson, and K. Grauman. Soundspaces: Audio-visual navigation in 3d environments. In *ECCV*, 2020.

[22] C. Gan, J. Schwartz, S. Alter, D. Mrowca, M. Schrimpf, J. Traer, J. De Freitas, J. Kubilius, A. Bhandwaldar, N. Haber, et al. Threedworld: A platform for interactive multi-modal physical simulation. In *NeurIPS Datasets and Benchmarks Track*, 2021.

[23] O. Kwon, N. Kim, Y. Choi, H. Yoo, J. Park, and S. Oh. Visual graph memory with unsupervised representation for visual navigation. In *ICCV*, 2021.

[24] M. Caron, H. Touvron, I. Misra, H. Jégou, J. Mairal, P. Bojanowski, and A. Joulin. Emerging properties in self-supervised vision transformers. In *CVPR*, 2021.

[25] S. Wani, S. Patel, U. Jain, A. Chang, and M. Savva. Multion: Benchmarking semantic map memory using multi-object navigation. *NeurIPS*, 2020.

[26] P. Chattopadhyay, J. Hoffman, R. Mottaghi, and A. Kembhavi. Robustnav: Towards benchmarking robustness in embodied navigation. In *ICCV*, 2021.

[27] M. A. Fischler and R. C. Bolles. Random sample consensus: a paradigm for model fitting with applications to image analysis and automated cartography. *Communications of the ACM*, 1981.

[28] C.-P. Lu, G. D. Hager, and E. Mjolsness. Fast and globally convergent pose estimation from video images. *TPAMI*, 2000.

[29] V. Lepetit, F. Moreno-Noguer, and P. Fua. Epnp: An accurate o (n) solution to the pnp problem. *IJCV*, 2009.

[30] P.-E. Sarlin, D. DeTone, T. Malisiewicz, and A. Rabinovich. Superglue: Learning feature matching with graph neural networks. In *CVPR*, 2020.

[31] T. Chen, S. Gupta, and A. Gupta. Learning exploration policies for navigation. In *ICLR*, 2019.

[32] J. Schulman, F. Wolski, P. Dhariwal, A. Radford, and O. Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

[33] A. Khandelwal, L. Weihs, R. Mottaghi, and A. Kembhavi. Simple but effective: Clip embeddings for embodied ai. In *CVPR*, 2022.

[34] A. Eftekhar, A. Sax, J. Malik, and A. Zamir. Omnidata: A scalable pipeline for making multitask mid-level vision datasets from 3d scans. In *ICCV*, 2021.

[35] D. DeTone, T. Malisiewicz, and A. Rabinovich. Superpoint: Self-supervised interest point detection and description. In *Proceedings of the IEEE conference on computer vision and pattern recognition workshops*, 2018.

[36] D. S. Chaplot, S. Gupta, A. Gupta, and R. Salakhutdinov. Learning to explore using active neural mapping. In *ICLR*, 2020.

[37] F. Xia, A. R. Zamir, Z. He, A. Sax, J. Malik, and S. Savarese. Gibson env: Real-world perception for embodied agents. In *CVPR*, 2018.

[38] A. Chang, A. Dai, T. Funkhouser, M. Halber, M. Niessner, M. Savva, S. Song, A. Zeng, and Y. Zhang. Matterport3d: Learning from rgb-d data in indoor environments. *arXiv preprint arXiv:1709.06158*, 2017.

[39] M. Bain and C. Sammut. A framework for behavioural cloning. In *Machine Intelligence*, 1995.

[40] K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. In *CVPR*, 2016.

[41] K. Cho, A. C. Courville, and Y. Bengio. Describing multimedia content using attention-based encoder-decoder networks. In *IEEE Transactions on Multimedia*, 2015.

[42] S. Gupta, J. Davidson, S. Levine, R. Sukthankar, and J. Malik. Cognitive Mapping and Planning for Visual Navigation. In *CVPR*, 2017.

[43] S. Gupta, D. Fouhey, S. Levine, and J. Malik. Unifying map and landmark based representations for visual navigation. *arXiv preprint arXiv:1712.08125*, 2017.

[44] Y. Zhu, D. Gordon, E. Kolve, D. Fox, L. Fei-Fei, A. Gupta, R. Mottaghi, and A. Farhadi. Visual Semantic Planning using Deep Successor Representations. In *ICCV*, 2017.

[45] D. Lowe. Object recognition from local scale-invariant features. *ICCV*, 1999.

[46] A. Murali, T. Chen, K. V. Alwala, D. Gandhi, L. Pinto, S. Gupta, and A. Gupta. Pyrobot: An open-source robotics framework for research and benchmarking. *arXiv preprint arXiv:1906.08236*, 2019.

[47] S. Choi, Q.-Y. Zhou, and V. Koltun. Robust reconstruction of indoor scenes. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2015.

[48] V. A. Higuti, A. E. Velasquez, D. V. Magalhaes, M. Becker, and G. Chowdhary. Under canopy light detection and ranging-based autonomous navigation. *Journal of Field Robotics*, 2019.

[49] R. Mur-Artal and J. D. Tardós. ORB-SLAM2: an open-source SLAM system for monocular, stereo and RGB-D cameras. *IEEE Transactions on Robotics*, 2017.

[50] K. He, X. Zhang, S. Ren, and J. Sun. Delving deep into rectifiers: Surpassing human-level performance on imagenet classification. In *Proceedings of the IEEE international conference on computer vision*, 2015.

[51] J. Sun, Z. Shen, Y. Wang, H. Bao, and X. Zhou. Loftr: Detector-free local feature matching with transformers. In *CVPR*, 2021.