Learning Physics Constrained Dynamics Using Autoencoders

Abstract

We consider the problem of estimating states (*e.g.,* position and velocity) and physical parameters (*e.g.,* friction, elasticity) from a sequence of observations when provided a dynamic equation that describes the behavior of the system. The dynamic equation can arise from first principles (*e.g.,* Newton's laws) and provide useful cues for learning, but its physical parameters are unknown. To address this problem, we propose a model that estimates states and physical parameters of the system using two main components. First, an autoencoder compresses a sequence of observations (*e.g.,* sensor measurements, pixel images) into a sequence for the state representation that is consistent with physics by including a simulation of the dynamic equation. Second, an estimator is coupled with the autoencoder to predict the values of the physical parameters. We also theoretically and empirically show that using Fourier feature mappings improves the generalization of the estimator in predicting physical parameters compared to raw state sequences when learning from high-frequency data. In our experiments on three visual and one sensor measurement tasks, our model imposes interpretability on latent states and achieves improved generalization performance for long-term prediction of system dynamics over state-of-the-art baselines.

1 Introduction

Neural networks have become a core computational component in domains such as computer vision [1], natural language processing [2], and deep reinforcement learning [3]. Recent work has shown that neural networks can exhibit an inductive bias that is often introduced via designing specific structures [4]. This bias can be used to encode prior task knowledge that helps the network generalize to unseen data. For example, convolution neural networks capture the translation invariance of key image features. In this spirit, we develop a structured neural network model that leverages a dynamic equation to estimate both the state of a dynamical system (*e.g.,* position and velocity) and its physical parameters (*e.g.,* friction constants) from a sequence of partial observations. Knowing the state and parameters of the system aids learning a control policy and tracking parameter value changes over time. For instance, for a self-driving car, we want to learn a neural network that estimates the vehicle's position and velocity from a sequence of egocentric camera images. The estimated state can then be used in a control policy. In addition, we want to track physical parameters over time, *e.g.,* friction coefficients. This is useful for vehicle maintenance and safety. We expect that exploiting a neural network, regularized to follow a dynamic equation, will streamline the required data-intensive operations and yield improved performance.

Observations can be direct measurements of some system variables (*e.g.,* accelerations), or take a more complex form (*e.g.,* images). We group such observations over specified time windows and also refer to these groupings as observations. We obtain a compact representation for these observations that permits observation reconstruction using an autoencoder (see Fig. 1(a)). $\{h_s\}$ in Fig. 1(a) is

a representation of an observation sequence $\{\boldsymbol{o}_s\}$ over a specified time window, and $\{\hat{\boldsymbol{o}}_s\}$ is the reconstructed observation sequence. Learning the autoencoder is both data and computationally intensive. In addition, $\boldsymbol{h}_s$ may not be physically interpretable and is not guaranteed to have the Markov property, *i.e.,* be a "system state."

Motivated by these observations, we assume a simulator is provided that specifies the physical laws of the system. This model can arise from first principles (*e.g.,* Newton's laws), but its free parameters $\boldsymbol{\theta}$ (*e.g.,* masses, lengths) remain to be specified. Given an initial state and $\boldsymbol{\theta}$, the physics simulator generates a state trajectory $\{\hat{\boldsymbol{x}}_s\}$ consistent with the laws of physics. To leverage this model, we require an estimator $f(\cdot)$ that maps a sequence of states $\{\tilde{\boldsymbol{x}}_s\}$ to an estimate of $\boldsymbol{\theta}$. We then couple the estimator f and the physics simulator with the autoencoder as shown in Fig. 1(b). We train the autoencoder and $f(\cdot)$ to minimize the observation reconstruction loss $\sum_s \|\boldsymbol{o}_s - \hat{\boldsymbol{o}}_s\|_2^2$. Within this process, we train the encoder $h(\cdot)$ to minimize the sum of squared state errors: $\sum_s \|\tilde{\boldsymbol{x}}_s - \hat{\boldsymbol{x}}_s\|_2^2$. The complete model (Fig. 1(b)) is called *Autoencoder with Latent Physics* (ALPS).

Figure 1: **(a)** An autoencoder learns a latent representation from a block of observations. **(b)** Combining a dynamic equation and parameter estimator in (a). (best viewed in color)

The paper's contributions are three-fold. **(1)** We propose and explore a model that integrates physics into an autoencoder to perform unsupervised state and physical parameter predictions. **(2)** We show that one can learn periodic or vibrational behavior in this setting using a Fourier feature of states. **(3)** We evaluate the proposed model in four tasks: **(a)** pendulum with friction observed through images, **(b)** mass-spring-damper system with stiffness observed through images, **(c)** two-body systems with potential energy observed through images, and **(d)** real-world vehicle wheel suspension system with accelerations observed through sensor measurements. The proposed approach can achieve up to 4.8x and 6.3x better physical parameter and state prediction accuracy, respectively, over prior approaches.

2 Related Work

Physics-informed neural networks. There is growing interest in including a physics prior or algebraic and logical constraints into neural networks [5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29]. For example, [30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40] exploit Lagrangian or Hamiltonian mechanics to learn an energy-conserving system based on position, momentum, and the derivatives thereof along trajectories. These works assume the physical parameters of the system are constant and need not be estimated. In contrast, we estimate the physical parameters. This is important for fault detection and localization, and for safety. Papers [41, 42, 43, 44] learn a general physical simulation from data, but their model is required to have *state* information or a *known* forward rendering engine to map states to observations. In contrast, we learn a physics-based autoencoder to estimate states in an unsupervised manner. Paper [45] also uses an autoencoder with physics to predict parameters. However, we show that learning state sequences as in [45] fails to generalize to unseen parameters when the system exhibits high-frequency behavior.

Fourier features for high-frequency data. [46, 47] show that using Fourier features helps neural networks learn high-frequency content in image regression tasks. This approach requires specifying the Fourier series coefficients and the basis frequencies. In contrast, the Fourier features in our model are computed from the states, which allows us to predict physical parameters. In addition, the concurrent work [48] replaces the self-attention sublayers [49] with a Fourier transformation of the input word token in natural language processing. They show that this method is sufficient to capture semantic relationships in several text classification tasks. In this paper, we provide a theoretical justification for using Fourier features to learn system dynamics with high-frequency data.

Figure 2: **ALPS and the tasks.** ALPS consists of four parts: **(1)** an encoder network that estimates states from observations, **(2)** a parameter estimator network that predicts physical parameters from a state sequence, **(3)** a physics simulator generates a state trajectory provided with an initial state and values for the physical parameters, and **(4)** a decoder network reconstructs observations from states.

3 Problem Formulation

We consider the continuous-time system

$$\dot{\boldsymbol{x}} = \boldsymbol{A}\boldsymbol{x} + \boldsymbol{B}\boldsymbol{u}; \quad \boldsymbol{o} = g(\boldsymbol{x}), \tag{1}$$

where $\boldsymbol{A} \in \mathbb{R}^{n \times n}$, $\boldsymbol{B} \in \mathbb{R}^{n \times p}$ and $\boldsymbol{x} \in \mathbb{R}^n$, $\boldsymbol{u} \in \mathbb{R}^p$, $\boldsymbol{o} \in \mathbb{R}^q$, denote the state, input, and observation, respectively. The function g provides a partial observation $\boldsymbol{o}$ of $\boldsymbol{x}$. In most situations we have partial knowledge of $\boldsymbol{A}$ and $\boldsymbol{B}$ from physics. This is true and reasonable in many large-scale industrial applications ranging from wind turbines to aircraft, where system designers use physics knowledge to design machines. Hence we assume mappings $A(\cdot) : \Theta \to \mathbb{R}^{n \times n}$ and $B(\cdot) : \Theta \to \mathbb{R}^{n \times p}$, from physical parameters $\boldsymbol{\theta} \in \Theta$ to the system matrices $A(\boldsymbol{\theta}), B(\boldsymbol{\theta})$, are given (*i.e.,* $\boldsymbol{A}$ and $\boldsymbol{B}$ obtain a specific sparse and parameteric form). In addition, Eq. (1) assumes the system dynamics to be linear, but our approach can be extended to other non-linear cases.

In practice, we only have observations at discrete points in time. For simplicity, we assume these are equally spaced at times $t = 0, 1, \dots$. At sample time t, we have the window of observations $\{\boldsymbol{o}_s\}_{s=t-\tau+1}^{t}$, where τ is the window length. We assume the sampling rate satisfies the Nyquist rate.

Our problem can now be stated as follows. Given functions $A(\cdot) : \Theta \to \mathbb{R}^{n \times n}$, $B(\cdot) : \Theta \to \mathbb{R}^{n \times p}$, we seek to learn a network that estimates a state sequence $\{\boldsymbol{x}_s\}_{s=t-\tau+1}^{t}$, physical parameters $\boldsymbol{\theta}$, and a mapping $g(\cdot)$ from a finite sequence of past observations $\{\boldsymbol{o}_s\}_{s=t-\tau+1}^{t}$ and past known inputs $\{\boldsymbol{u}_s\}_{s=t-\tau+1}^{t}$. Once trained, the network can predict states and has learned to adapt physical parameters to the context without re-training. Note that even though the network operates with time sampled variables, the physics simulator can be used to predict states at any time. This problem setup is distinct from that of HNN [33], HGN [36], or Symplectic ODE-Net [35]. In their setups, the model is only trained on data from a *single* physical parameter $\boldsymbol{\theta}$, and hence they need to re-train networks for every new set of physical parameters. In addition, compared to conventional system identification approaches, we do not need to rerun the solver each time–we only need a forward pass of the network to get the estimation during deployment (testing time).

To make the learning problem well-defined, *i.e.,* to ensure that we can uniquely identify the unknown system parameters, we make the following assumption.

Assumption 3.1. (Identifiability [50]): For a sufficiently large τ, the sequence of states and inputs $\{(\boldsymbol{x}_s, \boldsymbol{u}_s)\}_{s=t-\tau+1}^{t}$ uniquely specifies the unknown parameter $\boldsymbol{\theta}$.

Parameter identifiability is a well-studied problem in system identification [50, 51, 52]. For example, the (continuous time) system $\dot{\boldsymbol{x}} = \begin{bmatrix} -(a+b) & b \\ b & -c \end{bmatrix} \boldsymbol{x} + \begin{bmatrix} 1 \\ 0 \end{bmatrix} \boldsymbol{u}$ with $\boldsymbol{o} = \begin{bmatrix} 1 & 0 \end{bmatrix} \boldsymbol{x}$, where $\boldsymbol{\theta} = [a, b, c]^T$ and $g(\cdot)$ is a linear function, satisfies Assumption 3.1 when $b \neq 0$.

4 Nework Architecture

The network in Fig. 1(b) is expanded in Fig. 2 into its four parts: an encoder network, a parameter estimator network, a physics simulator, and a decoder network.

The encoder network $h(\cdot)$ **(from $\{o_s\}$ to $\{\tilde{x}_s\}$).** We consider two types of observations: **(1)** pixel images, or **(2)** direct measurements of some system variables. For the first case, we use a convolution neural network to compress a pixel observation o into a compact vector embedding $z' \in \mathbb{R}^d$, which preserves image features. For the second case, we use a feedforward network to project an observation o into some higher dimensional space with a vector embedding z'. In addition, to estimating states from these vector embeddings, we need to aggregate $\{z'_s\}$ to extract the local and global context of the dynamics. One approach is to use recurrent neural networks (RNN) (*e.g.,* Dreamer [53]). However, RNNs suffer from vanishing gradient problems and slow computation when processing long-term sequences. Hence we use a self-attention network [49] to attend to z' of greatest importance to predict states and improve efficiency.

Furthermore, to inject a position signal of observations in the sequence, we add a positional encoding $p \in \mathbb{R}^d$ to z' ($z := z' + p$), where p are sine and cosine functions of different frequencies (see [49]). Finally, we stack embeddings over τ steps to form a matrix $Z \in \mathbb{R}^{\tau \times d}$.

The self-attention module can be formulated as querying a dictionary with key-value pairs associated with learnable weight matrices $W^Q \in \mathbb{R}^{d \times d_Q}$, $W^K \in \mathbb{R}^{d \times d_K}$, and $W^V \in \mathbb{R}^{d \times d_V}$ ($d_Q = d_K$ here): $\text{Attention}(Q, K, V) = \text{softmax}(\frac{QK^T}{\sqrt{d}})V$, where $Q := ZW^Q$, $K := ZW^K$, $V := ZW^V$, and the softmax is taken over the sequence length τ. To provide multiview of the embedding subspace, we use the multihead variant of the attention module by concatenating each attention head along the sequence axis

$$\text{Multihead} := \text{Concat}(\text{head}_1, \ldots, \text{head}_i, \ldots, \text{head}_I)W^O, \quad \text{head}_i := \text{Attention}(Q, K, V),$$

where $W^O \in \mathbb{R}^{Id_V \times d}$ are learnable matrices, I is the number of heads, and each attention head i has its own learnable weight matrices $W_i^Q \in \mathbb{R}^{d \times d_Q}$, $W_i^K \in \mathbb{R}^{d \times d_K}$, and $W_i^V \in \mathbb{R}^{d \times d_V}$.

Finally, a feedforward network takes in the Multihead embedding (of size $\mathbb{R}^{\tau \times d}$) and produces the parameters of the distribution for each state in the sequence. The parameters are used to define a posterior distribution over the encoded state $\tilde{x}_s \sim Q(\cdot | \bar{o}_s)$ with the prior $P(\tilde{x}_s)$. For a translational coordinate, the posterior distribution is a Gaussian distribution with a unit Gaussian prior. Hence the network predicts a mean $\mu \in \mathbb{R}^n$ and a standard deviation $\sigma \in \mathbb{R}^n$ of a Gaussian distribution. In addition, for a rotational coordinate, the posterior distribution is a von Mises (vM) distribution with a unit vM prior. Similar to a Gaussian distribution, a vM distribution is defined by two parameters: a mean $\mu \in \mathbb{R}^2$, $\|\mu\|_2 = 1$ (the angular position $(\cos \varphi, \sin \varphi)$), and a concentration $\kappa \in \mathbb{R}^+$ around μ. Such parameterization is found useful in practice, *e.g.,* [54]. Appendix E provides details about self-attention networks for estimating states.

The parameter estimator network $f(\cdot)$ **(from $\{\tilde{x}_s\}$ to θ).** The parameter estimator network predicts physical parameters from state sequences $\{\tilde{x}_s\}$. However, for systems that involve periodic or vibrational behavior, prior work [46] has shown that neural networks fail to capture the high-frequency content in the data. In addition, real-world data often contain noise. To improve generalization and reduce the effect of noise, we do a Fourier transform on each component j of state trajectories $\{\tilde{x}_s(j)\}_{s=t-\tau+1}^t$ to get $\{\tilde{X}_\omega(j)\}_{\omega=t-\tau+1}^t : \tilde{X}_\omega(j) := \sum_{k=t-\tau+1}^t \tilde{x}_k(j)\left[\cos\left(\frac{2\pi}{\tau}\omega k\right) - i \cdot \sin\left(\frac{2\pi}{\tau}\omega k\right)\right]$. Note that for the systems that do not have periodic or vibrational behavior, using $\{\tilde{x}_s(j)\}_{s=t-\tau+1}^t$ would be enough.

One may use $\{\tilde{X}_\omega(j)\}$ as features for the parameter estimator network to predict physical parameters. However in Section 5 we will show that by using the neural tangent kernel (NTK) theory [55], which treats neural networks as a kernel regression, the resulting kernel matrix of $\{\tilde{X}_\omega(j)\}$ does not preserve high-frequency components in the data. To solve this, we will show that using the *magnitude* of the Fourier features $\{|\tilde{X}_\omega(j)|\}$ alleviates the issue. Hence the parameter estimator network takes in a concatenation of $\{|\tilde{X}_\omega(j)|\}$ from each component of the state and predicts physical parameters θ.

The physics simulator (from $\tilde{x}_{t-\tau+1}$ and θ to $\{\hat{x}_s\}$). Given a start state $\tilde{x}_{t-\tau+1}$ (from the encoder's first state prediction) and values for the physical parameters θ, we use the neural ordinary

Figure 3: Using a Fourier feature mapping of k_{MAG} and k_{PHA} results in a wider spectrum, which lets neural networks learn a wide frequency content. **(a)** The time series data with the sine basis frequency of $25, 17.5, 11, 7.7, 2, 1$Hz associated with the amplitude of $1, 1.2, 1, 1, 0.4, 1$. **(b)** The kernel spatial of the kernel matrices. We see that k_{MAG} can preserve high-frequency parts of the signals. **(c-f)** The kernel matrices of the composed NTK. (best viewed in color)

differential equation (ODE) [56], a differential ODE solver, to generate a simulated state trajectory $\{\hat{\boldsymbol{x}}_s\}_{s=t-\tau+1}^{t} : \hat{\boldsymbol{x}}_{t-\tau+1}, \ldots, \hat{\boldsymbol{x}}_{t-1}, \hat{\boldsymbol{x}}_t = \text{ODESolver}(\tilde{\boldsymbol{x}}_{t-\tau+1}, \dot{\boldsymbol{x}} = A(\boldsymbol{\theta})\boldsymbol{x} + B(\boldsymbol{\theta})\boldsymbol{u}, \tau, \Delta)$, where ODESolver takes in a start state, an ODE, a window length, and a sampling time interval Δ. Note that $\hat{\boldsymbol{x}}_{t-\tau+1} = \tilde{\boldsymbol{x}}_{t-\tau+1}$. In addition, using an ODE solver allows us to generate an accurate state trajectory compared to that of RNN as in [53].

The decoder network $g(\cdot)$ **(from $\hat{\boldsymbol{x}}_s$ to $\hat{\boldsymbol{o}}_s$).** Finally, the decoder network is either a deconvolutional network (for image observations) or a feedforward network (for sensor measurements) that takes in each individual ODE-simulated state $\hat{\boldsymbol{x}}_s$ and generates a reconstructed observation $\hat{\boldsymbol{o}}_s$.

The loss function. Given a sequence of τ observations, we minimize the following loss function:

$$\mathcal{L} = \underbrace{\sum_{s=t-\tau+1}^{t} D_{\text{KL}}(Q(\tilde{\boldsymbol{x}}_s|\boldsymbol{o}_s)||P(\tilde{\boldsymbol{x}}_s))}_{\text{VAE loss for } h, f, \text{ and } g} + \underbrace{\sum_{s=t-\tau+1}^{t} \|\boldsymbol{o}_s - \hat{\boldsymbol{o}}_s\|_2^2}_{\text{Obs. recons. loss for } h, f, \text{ and } g} + \underbrace{\sum_{s=t-\tau+1}^{t} \|\tilde{\boldsymbol{x}}_s - \hat{\boldsymbol{x}}_s\|_2^2}_{\text{State recons. loss for } f \text{ and } h}.$$

The variational autoencoder (VAE) [57] loss is a variational bound on the marginal log-likelihood of the data. It is used to train the encoder h, the estimator f, and the decoder g. Using VAEs avoids learning degenerated solutions and provides stable training of the network over a deterministic network. In addition, the observation reconstruction loss encourages reconstructed observations $\{\hat{\boldsymbol{o}}_s\}$ to match true observations $\{\boldsymbol{o}_s\}$, and the state reconstruction loss constrains encoded states $\{\tilde{\boldsymbol{x}}_s\}$ to follow simulated states $\{\hat{\boldsymbol{x}}_s\}$ generated by physics. The former is used to train h, f, and g, and the latter is used to train f and h. Both observation and state reconstruction losses are important for training. We find that removing the state reconstruction term reduces the state prediction performance of the encoder since the network can predict arbitrary sequences. In addition, removing the observation reconstruction term impedes the image reconstruction quality, which is vital for training the whole model. In practice we find using the same weight for each loss term works well.

5 Fourier Feature Mappings for Learning Periodic System Dynamics

An important feature of ALPS is that it uses a Fourier feature mapping of states to learn periodic system dynamics. Prior works [58, 59] have empirically shown that using a Fourier feature can help with high frequency signals. To lay the foundation for the analysis and justify the use of Fourier features, in Section 5.1 we first review the recent work that uses NTK theory [55, 46]. This allows us to control the training of our parameter estimator network as fully-connected networks. Then in Section 5.2 we use these tools to analyze the effects of using Fourier features, their magnitudes, and their phases when predicting system parameters that involve the *periodic behavior*.

5.1 Deep networks as a kernel regression

Consider a set of labelled training data $\{(\boldsymbol{v}_i, y_i)\}_i^m$ with $\boldsymbol{v}_i \in \mathbb{R}^n$, $y_i \in \mathbb{R}$, and $i \in [1:m]$. Set $\boldsymbol{y} = [y_1, \ldots, y_m]^T \in \mathbb{R}^m$. Now bring in a feature map $\phi : \mathbb{R}^n \to \mathbb{R}^r$ with kernel $k(\boldsymbol{v}_i, \boldsymbol{v}_j) = \phi(\boldsymbol{v}_i)^T \phi(\boldsymbol{v}_j)$. Let $\boldsymbol{K} = [k(\boldsymbol{v}_i, \boldsymbol{v}_j)] \in \mathbb{R}^{m \times m}$ denote the kernel matrix for the training examples and $k(\boldsymbol{v}) = [k(\boldsymbol{v}_i, \boldsymbol{v})] \in \mathbb{R}^m$ denote the vector of kernel evaluations $k(\boldsymbol{v}_i, \boldsymbol{v}), i \in [1, m]$, for a test sample $\boldsymbol{v} \in \mathbb{R}^n$. The resulting kernel regression predictor is $\hat{y}(\boldsymbol{v}) = \boldsymbol{y}^T \boldsymbol{K}^{-1} k(\boldsymbol{v})$.

Now bring the concept of NTK proposed by [55]. The theory in [55] says that when the width of the layers of fully-connected deep networks with weights $\boldsymbol{w}$ initialized from a Gaussian distribution $\mathcal{N}$

209 tends to infinity, and the learning rate for stochastic gradient descent tends to zero, the neural network
210 estimator $\hat{y}(\boldsymbol{v}; \boldsymbol{w})$ converges to the kernel regression solution using NTK. The NTK is defined as

$$k_{\mathrm{NTK}}(\boldsymbol{v}_i, \boldsymbol{v}_j) = \mathbb{E}_{\boldsymbol{w} \sim \mathcal{N}} \left[\left(\frac{\partial \hat{y}(\boldsymbol{v}_i; \boldsymbol{w})}{\partial \boldsymbol{w}} \right)^T \left(\frac{\partial \hat{y}(\boldsymbol{v}_j; \boldsymbol{w})}{\partial \boldsymbol{w}} \right) \right].$$

211 Under asymptotic conditions, a neural network's output after t updates can be approximated as

$$\hat{y}^{(t)}(\boldsymbol{v}; \boldsymbol{w}) \approx \boldsymbol{y}^T (\boldsymbol{I} - e^{-\eta \boldsymbol{K} t}) \boldsymbol{K}^{-1} k(\boldsymbol{v}),$$

212 where $e^{\boldsymbol{M}}$ is the n by n matrix $\boldsymbol{M}$ given by the power series $e^{\boldsymbol{M}} = \sum_{i=0}^{\infty} \frac{1}{i!} \boldsymbol{M}^i$ with $\boldsymbol{M}^0 = \boldsymbol{I}$.

213 **Spectral bias in neural networks.** Now we want to compute the training error of a neural network
214 after t times update. Let $\boldsymbol{K} = \boldsymbol{U} \boldsymbol{\Sigma} \boldsymbol{U}^T$ denote the eigendecomposition of the kernel matrix $\boldsymbol{K}$ which
215 must be positive semidefinite (PSD). Here $\boldsymbol{U}$ is an orthogonal matrix and $\boldsymbol{\Sigma}$ is a diagonal matrix whose
216 entries are the nonnegative eigenvalues ordered by magnitude: $\lambda_1 \geq \lambda_2 \geq \cdots \geq \lambda_m \geq 0$. So the
217 training error in terms of L_2 norm $\|\cdot\|_2^2$ is $\left\| \hat{\boldsymbol{y}}^{(t)} - \boldsymbol{y} \right\|_2^2 = \left\| \boldsymbol{U} \mathrm{diag}([e^{-\eta \lambda_1 t}, \ldots, e^{-\eta \lambda_m t}]^T) \boldsymbol{U}^T \boldsymbol{y} \right\|_2^2$.
218 This shows the training convergence will decay exponentially at the rate $\eta \lambda_i$. Hence the components
219 in $\boldsymbol{y}$ will be learned faster if their corresponding eigenvalue is larger. In Section 5.2 we will show
220 that for a sequence of states without doing Fourier transform, the resulting NTK will have smaller
221 eigenvalues at the high-frequency components. This leads to a slower convergence in high-frequency
222 components of data which are essential to identify parameters for the periodic behavior.

5.2 The effect of Fourier feature mapping

224 To understand the effect of the Fourier feature mapping, we first derive the kernel function of Fourier
225 features, their magnitudes, and their phases. Then we compare the spatial bias of the kernel matrices
226 from these three kernels.

227 **Kernels of Fourier feature mapping.** Consider a state trajectory $\boldsymbol{v} = [x_0, x_1, \ldots, x_{\tau-1}]^T$, where
228 here we consider a 1D case for a scalar state $x \in \mathbb{R}$ although it can be extended to a vector state
229 $\boldsymbol{x} \in \mathbb{R}^n$. The feature maps of the Fourier feature mapping, their magnitudes, and their phases are

(1) $\phi_{\mathrm{DFT}}(\boldsymbol{v}) = [X_0, \ldots, X_\omega, \ldots, X_{\tau-1}]^T \in \mathbb{R}^\tau$; **(2)** $\phi_{\mathrm{MAG}}(\boldsymbol{v}) = [|X_0|, \ldots, |X_{\tau-1}|]^T \in \mathbb{R}^\tau$;

(3) $\phi_{\mathrm{PHA}}(\boldsymbol{v}) = [\arg(X_0), \ldots, \arg(X_{\tau-1})]^T \in \mathbb{R}^\tau$,

230 where $X_\omega = \sum_{j=0}^{\tau-1} x_j \left[\cos \left(\frac{2\pi}{\tau} kj \right) - i \sin \left(\frac{2\pi}{\tau} kj \right) \right]$. Set $C_k = \left[\cos \left(\frac{2\pi}{\tau} ki \right) - \sin \left(\frac{2\pi}{\tau} kj \right) \right] \in$
231 $\mathbb{R}^{\tau \times \tau}$, then the kernel functions of these mappings are

(1) $k_{\mathrm{DFT}}(\boldsymbol{v}_1, \boldsymbol{v}_2) = \sum_{k=0}^{\tau-1} \boldsymbol{v}_1^T C_k \boldsymbol{v}_2$; **(2)** $k_{\mathrm{MAG}}(\boldsymbol{v}_1, \boldsymbol{v}_2) = \sum_{k=0}^{\tau-1} \sqrt{\boldsymbol{v}_1^T C_k \boldsymbol{v}_1 \boldsymbol{v}_2^T C_k \boldsymbol{v}_2}$;

(3) $k_{\mathrm{PHA}}(\boldsymbol{v}_1, \boldsymbol{v}_2) = \phi_{\mathrm{PHA}}(\boldsymbol{v}_1)^T \phi_{\mathrm{PHA}}(\boldsymbol{v}_2)$.

232 After mapping the input points into the Fourier features, we feed them into a neural network to obtain
233 $\hat{y}(\phi(\boldsymbol{v}); \boldsymbol{w})$. Hence for DFT kernel function the resulting composed kernel of the neural network is
234 $k_{\mathrm{NTK}}(\phi_{\mathrm{DFT}}(\boldsymbol{v}_1), \phi_{\mathrm{DFT}}(\boldsymbol{v}_2))$. Similarly, we have the kernels for k_{MAG} and k_{PHA}.

235 **Visualizing the composed NTK.** We generate time series data composed of different frequencies and
236 magnitude of sine waves. The length of the data is 200 samples, and we set $\tau = 100$ (*i.e.*, $\boldsymbol{v} \in \mathbb{R}^{100}$)
237 with the sampling rate being 100Hz. We slide a window and hence have 101 instances in total. Fig. 3
238 shows the time series data, the effects of each kernel, and its spatial plot. By construction, k_{MAG} and
239 k_{PHA} have a slower decay in the high-frequency domain as shown in Fig. 3(b). In addition, k_{DFT}
240 and no mapping have the same kernel matrix and a narrower kernel spatial. This observation supports
241 the idea of not using X_ω when learning the system with periodic or vibrational behavior as $|X_\omega|$
242 (magnitude) preserves high-frequency information, which is useful for parameter estimations. Note
243 that for the system that does not have high-frequency signals, both X_ω and $|X_\omega|$ are equally well.

244 **Comparison to [46].** Our work is inspired by [46], which also uses Fourier feature mappings.
245 However, there are a few key differences. **(1) Setup.** The Fourier feature mapping in [46] transforms
246 the low-dimensional x-y coordinates into high-dimensional Fourier features, which *projects* data
247 into a high-dimensional space. In contrast, we use Fourier feature mapping of raw time series data,
248 which *compresses* data into more compact representations. **(2) Analysis**. We discuss the difference of
249 Fourier feature mappings, their magnitudes, and their phases to understand the effect of each mapping
250 for predicting system parameters. In contrast, [46] does not have such analysis.

6 Simulations

We study the following three questions: **(1)** How does ALPS perform compared to other baseline methods without the Fourier feature mapping and physics-in-the-loop? **(2)** What is the effect of self-attention networks in ALPS? **(3)** How does ALPS perform in a real-world time series data?

Visual dataset. We generate three visual datasets: pendulum, mass-spring-damper (MSD), and a two-body system to compare the performance of ALPS to that of the baseline in the literature. These baselines are very commonly used in the prior work. We first randomly sample an initial state and physical parameters, and then generate a 125 step rollout following the true system dynamics, and render corresponding 64 by 64 by 3 pixel observation snapshots. The sampling rate is 20Hz in the pendulum, 100Hz in MSD, and 6Hz in two-body systems. The observation length τ is 100. In total, we generate 500 training and 500 test trajectories, resulting in 13,000 training and test sequences.

(1) Pendulum. The dynamics is $\frac{d}{dt}\begin{bmatrix}\varphi \\ \dot{\varphi}\end{bmatrix} = \begin{bmatrix}\dot{\varphi} \\ -\beta\dot{\varphi} - \frac{G}{L}\sin(\varphi)\end{bmatrix}$, where φ is an angle, $\dot{\varphi}$ is an angular velocity, β is a friction coefficient, G is a gravitational constant, and L is the length of the pendulum. We fix $G = 10$, $L = 1$, then sample β from a uniform distribution $\beta \sim \mathbb{U}(0.1, 1)$, an initial angle from a uniform distribution $\varphi_0 \sim \mathbb{U}(-\pi, +\pi)$, and an initial angular velocity from a uniform distribution $\dot{\varphi}_0 \sim \mathbb{U}(0.5, 4)$. We predict $\boldsymbol{\theta} = [\beta]$ in this task.

(2) Mass-spring-damper. The dynamics of double mass-spring-damper system is

$$\frac{d}{dt}\begin{bmatrix}x(1) \\ x(2) \\ x(3) \\ x(4)\end{bmatrix} = \begin{bmatrix} 0 & 1 & 0 & 0 \\ \frac{-\alpha(1)-\alpha(2)}{m(1)} & \frac{-\alpha(3)-\alpha(4)}{m(1)} & \frac{\alpha(1)}{m(1)} & \frac{\alpha(3)}{m(1)} \\ 0 & 0 & 0 & 1 \\ \frac{\alpha(1)}{m(2)} & \frac{\alpha(3)}{m(2)} & -\frac{\alpha(1)}{m(2)} & \frac{\alpha(3)}{m(2)} \end{bmatrix}\begin{bmatrix}x(1) \\ x(2) \\ x(3) \\ x(4)\end{bmatrix} + \begin{bmatrix} 0 & 0 \\ \frac{\alpha(2)}{m(1)} & \frac{\alpha(4)}{m(1)} \\ 0 & 0 \\ 0 & 0 \end{bmatrix}\begin{bmatrix}u(1) \\ u(2)\end{bmatrix},$$

where $x(1), x(3)$ are the displacement and velocity of the primary spring; $x(2), x(4)$ are the displacement and velocity of the secondary spring; $u(1), u(2)$ are the inputs; $\alpha(2), \alpha(4)$ are the stiffness and damping ratio of the primary spring and damper; $\alpha(1), \alpha(3)$ are the stiffness and damping ratio of the secondary spring and damper, and $m(1), m(2)$ are the mass of the primary and secondary spring. We fix all the parameters and the initial state except for $\alpha(2)$, which is sampled from a uniform distribution $\alpha(2) \sim \mathbb{U}(4 \times 10^3, 4 \times 10^6)$. The input excitations are sampled from a unit Gaussian distribution $\boldsymbol{u} \sim \mathcal{N}(0, 0.05) \times \mathcal{N}(0, 0.05)$ (*i.e.,* white noise). We predict $\boldsymbol{\theta} = [\alpha(2)]$ in this task.

(3) Two-body. In this system two particles interact with each other via an attractive force. The dynamics is a Hamiltonian $\mathcal{H} = \frac{\|p(1)\|_2^2}{2m(1)} + \frac{\|p(2)\|_2^2}{2m(2)} + \frac{Gm(1)m(2)}{\|q(1)-q(2)\|_2}$, where $p(1), p(2)$ are the positions of the particles; $q(1), q(2)$ are the momentum of the particles; $m(1), m(2)$ are the masses of the particles, and G is a gravitational constant. We fix $G = 10, m(1) = m(2) = 1$, then sample $\mathcal{H}$ from a uniform distribution $\mathcal{H} \sim \mathbb{U}(0.4, 1)$. We predict $\boldsymbol{\theta} = [\mathcal{H}]$ in this task.

Time series dataset. In addition, we obtain an MSD system dataset with state measurements.

(4) Real MSD time series data (wheel suspension system). To show the applicability of ALPS, we conduct *real-world* experiments with the data obtained from sensors installed in the train wheel suspension system by a team of engineers. We use full-scale dynamics with 18 state elements, 12 observations, 16 input excitations, and 24 system parameters. We want to identify the stiffness and damping ratio of the 12 spring-dampers. The dynamics are complex due to the interactions of multiple springs and dampers. In addition, this problem is challenging as the data contain noise. The dataset contains 20 trajectories with 500 steps sampled by 100Hz. We use a 50-50 split to get the training and test datasets with $\tau = 100$. Here we *do not* use the self-attention and decoder network in ALPS–the estimator takes in state measurements directly.

Baselines. We select the following baselines that are commonly used in the literature.

(1) Context-aware dynamics model (CDM) [60]. CDM is the state-of-the-art method to learn the system dynamics into two stages: it first learns a context vector that captures the local dynamics, and then predicts the next state based on the context vector and the current state and input. CDM *does not* consider physics prior *nor* Fourier feature mapping. This is to show that using physics priors improves performance and benchmark the results.

	Pendulum			Mass-Spring-Damper			Two-body		
	SE	OE	PE	SE	OE	PE	SE	OE	PE
CDM [60]	345.22	1766.70	–	0.99	**5.69×10⁸**	–	50.23	**2.03×10⁸**	–
Autoencoder	3041.12	**600.84**	–	7.63	7.42×10⁸	–	95.80	2.71×10⁸	–
ALPS (ours)	86.48	1696.91	**0.06**	**0.29**	7.43×10⁸	**0.60×10⁶**	**0.45**	2.59×10⁸	**0.02**
w/o Fourier feat. [45]	90.82	1773.39	0.29	0.93	7.44×10⁸	2.28×10⁶	1.86	2.56×10⁸	**0.02**
w/o self-attention [54]	181.22	1950.77	**0.06**	1.85	7.44×10⁸	1.87×10⁶	511.49	2.72×10⁸	0.27

Figure 4: **(Top)** Evaluation for the tested networks in the visual tasks. **(Bottom)** Selected visualization results. Note that for the pendulum and two-body tasks, the range of $\boldsymbol{\theta}$ is $(0, 10]$; for the MSD tasks, the $\boldsymbol{\theta}$ is in the range of 10^6. SE: state prediction error; OE: observation prediction error; PE: parameter prediction error. And in visualization the true state here is $\boldsymbol{x}$, ENC state is $\tilde{\boldsymbol{x}}$, and ODE state is $\hat{\boldsymbol{x}}$. ALPS achieves competitive performance in predicting physical parameters and states.

(2) Autoencoder. We remove the estimator and the physics simulator to benchmark the mismatch between the true state and the latent representation (equal dimension) of the autoencoder in Fig. 1(a) to show the interpretability of ALPS.

(3) ALPS w/o the Fourier feature mapping. We consider a variant by replacing the Fourier feature mapping with raw encoded state trajectories $\{\tilde{\boldsymbol{x}}_s\}$. This method is *similar* to [45], which also uses time series data to learn system dynamics.

(4) ALPS w/o self-attention networks. We consider a variant by replacing the self-attention network with a simple MLP to predict the position of the system, followed by a first-order finite-difference estimator to estimate the velocity. This uses the same approach as in [54] to estimate states. Finally, we ensure that all baselines are comparable in terms of representation power and the number of parameters. The loss functions used for these baselines are included in Appendix D.

Evaluation metrics. We use a mean squared error (MSE) between simulated $\{\hat{\boldsymbol{x}}_s\}$ and true states $\{\boldsymbol{x}_s\}$ to evaluate the performance: $\text{SE} := \frac{1}{N} \sum_{i=1}^{N} \sum_{s=t-\tau+1}^{t} \|\hat{\boldsymbol{x}}_s - \boldsymbol{x}_s\|_2^2$, where N is the number of test data. We also compute MSE between reconstructed $\{\hat{\boldsymbol{o}}_t\}$ and true observations $\{\boldsymbol{o}_t\}$: $\text{OE} := \frac{1}{N} \sum_{i=1}^{N} \sum_{s=t-\tau+1}^{t} \|\hat{\boldsymbol{o}}_s - \boldsymbol{o}_s\|_2^2$. Moreover, we compute the absolute value difference between estimated $\hat{\boldsymbol{\theta}}$ and true parameters $\boldsymbol{\theta}$: $\text{PE} := \frac{1}{N} \sum_{i=1}^{N} \left\| \hat{\boldsymbol{\theta}} - \boldsymbol{\theta} \right\|_1$.

Results in the visual tasks. Fig. 4 shows the results. We see that **(1)** ALPS achieves the best performance in predicting physical parameters in all cases, with at the most 4.8x lower error in the pendulum task. On the other hand, the Fourier feature mapping does not have much effect in predicting the physical parameter in the two-body system. This verifies the analysis of the Fourier feature mapping: for the task with a wider frequency spectrum (*e.g.,* 100Hz in the MSD), the Fourier feature improves the prediction due to higher eigenvalues in the high-frequency content, whereas for the task with only a low-frequency spectrum (*e.g.,* 6Hz in the two-body), raw state sequences can already capture low-frequency content. This supports the idea of *using Fourier feature mappings for high-frequency data.* **(2)** ALPS achieves competitive results in predicting the states, with at the most 6.3x lower error in the MSD task. We further visualize the state prediction results in the pudendum task for ALPS, which shows that ALPS can accurately track the true states. Without self-attention networks, the network has a substantial SE due to a large error in computing the velocity, as in the

	SE	PE
CDM [60]	56.04	–
ALPS (ours)	**3.02**	**0.44×10⁴**
w/o Fourier feat. [45]	113.07	4.32×10⁶

(a)   **(b)**

Figure 5: **(a)** This image is blurred since it is proprietary. The goal is to identify the stiffness and damping ratio of the 12 spring/damper assemblies (indicated by red circles). **(b)** Results in the MSD system for predicting physical parameters from time series data. Our method achieves the best performance.

two-body task. The smaller the sampling rate is, the greater the velocity estimation error is. In addition, the high SE in autoencoder suggests that its latent representation is uninterpretable. This verifies the idea of using physics to constrain the representation of the autoencoder to estimate states.

In addition, **(3)** ALPS achieves comparable results in reconstructing observations. The low error for CDM in the MSD and two-body tasks is due to degenerated solutions as shown in the Fig. 4. This implies that using physics stabilizes the training and improves the reconstruction of observations. **(4)** Finally, the autoencoder baseline has higher reconstruction loss in some tasks. This is because that it learns a degenerated solution, producing blur images due to high-frequency movements of objects on the scene. Fig. 8 in Appendix E provides more qualitative visualizations of reconstructed images. Specifically, we find that CDM fails to track the state and resulting blur images in the mass-spring-damper system or duplicated objects in the two-body system. In contrast, ALPS can precisely track the state and reconstruct the image well. Our remaining simulations explore ALPS's ability in predicting physical parameters from raw state measurements.

Results in real MSD time series data. To scale the proposed approach to a more complex system, we apply the approach in a system with a full-scale train wheel suspension system. The system contains 18 state elements, 12 observations, 16 input excitations, and 24 system parameters (see Fig. 5(a) for the illustration). Fig. 5(b) shows the results. Here ALPS does not use the encoder nor decoder network–the estimator takes in state measurements directly, as the system is fully-observable in the dataset. Overall we see that **(1)** ALPS achieves the best performance. Without using the Fourier feature mapping, the network cannot learn to identify physical parameters. **(2)** CDM has worse SE since an MLP cannot learn well from data with high-frequency content. In addition, we find that the average prediction error rate (*i.e.,* $\frac{\hat{\theta}-\theta}{\theta}$) for these 24 parameters is *0.42 %* on the real world complex system. This also implies that by providing physics to the network, we can improve SE. These observations show ALPS can robustly identify parameters simultaneously from state measurements, and support the theory of using Fourier features to learn periodic dynamics. Moreover, this result shows ALPS can be deployed in real prognostic applications for tracking physical parameters to enhance railroad safety. Our result is significant for system designers to diagnose the system and hence schedule maintenance. Appendix A provides discussions of the real-world impact.

7 Conclusion and Future Work

We addressed the problem of predicting states and physical parameters of a system from observations with dynamic equations. We showed that the latent representation of the autoencoder is uninterpretable. We then use dynamic equations to constrain the latent representation of the autoencoder to be consistent with the laws of physics. We analyzed the effect of Fourier features for estimating physical parameters. The results showed that ALPS achieves competitive performance in the visual tasks and the real raw time series dataset with up to 24 parameter predictions at the same time. This shows that our method scales to high-dimensional systems and it is useful for real-world applications.

Future work could improve ALPS in several ways. For instance, the understanding of underlying mechanisms in self-attention networks for estimating states from observations can be advanced. In addition, we require to have dynamic equations and assume that the system is linear and exhibits periodic or vibrational behaviors. One solution is to combine known physics with neural models (*e.g.,* interaction networks [13]) to compensate for modeling error, and use time-domain and frequency-domain features together to predict physical parameters. Moreover, it would be interesting to explore other more complex tasks (*e.g.,* non-linear systems, fluid dynamics, molecular simulation).

References

[1] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *2016 IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2016, Las Vegas, NV, USA, June 27-30, 2016*, pages 770–778. IEEE Computer Society, 2016.

[2] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186, Minneapolis, Minnesota, 2019. Association for Computational Linguistics.

[3] Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A. Rusu, Joel Veness, Marc G. Bellemare, Alex Graves, Martin Riedmiller, Andreas K. Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *nature*, 518(7540):529–533, 2015.

[4] Alberto Bietti and Julien Mairal. On the inductive bias of neural tangent kernels. In Hanna M. Wallach, Hugo Larochelle, Alina Beygelzimer, Florence d'Alché-Buc, Emily B. Fox, and Roman Garnett, editors, *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada*, pages 12873–12884, 2019.

[5] Russell Stewart and Stefano Ermon. Label-free supervision of neural networks with physics and domain knowledge. In Satinder P. Singh and Shaul Markovitch, editors, *Proceedings of the Thirty-First AAAI Conference on Artificial Intelligence, February 4-9, 2017, San Francisco, California, USA*, pages 2576–2582. AAAI Press, 2017.

[6] Nicholas Watters, Daniel Zoran, Theophane Weber, Peter W. Battaglia, Razvan Pascanu, and Andrea Tacchetti. Visual interaction networks: Learning a physics simulator from video. In Isabelle Guyon, Ulrike von Luxburg, Samy Bengio, Hanna M. Wallach, Rob Fergus, S. V. N. Vishwanathan, and Roman Garnett, editors, *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pages 4539–4547, 2017.

[7] Yinhao Zhu, Nicholas Zabaras, Phaedon-Stelios Koutsourelakis, and Paris Perdikaris. Physics-constrained deep learning for high-dimensional surrogate modeling and uncertainty quantification without labeled data. *Journal of Computational Physics*, 394:56–81, 2019.

[8] K. Kashinath, M. Mustafa, A. Albert, JL Wu, C. Jiang, S. Esmaeilzadeh, K. Azizzadenesheli, R. Wang, A. Chattopadhyay, A. Singh, et al. Physics-informed machine learning: case studies for weather and climate modelling. *Philosophical Transactions of the Royal Society A*, 379(2194):20200093, 2021.

[9] Rui Wang, Karthik Kashinath, Mustafa Mustafa, Adrian Albert, and Rose Yu. Towards physics-informed deep learning for turbulent flow prediction. In Rajesh Gupta, Yan Liu, Jiliang Tang, and B. Aditya Prakash, editors, *KDD '20: The 26th ACM SIGKDD Conference on Knowledge Discovery and Data Mining, Virtual Event, CA, USA, August 23-27, 2020*, pages 1457–1466. ACM, 2020.

[10] Tianju Xue, Alex Beatson, Sigrid Adriaenssens, and Ryan P. Adams. Amortized finite element analysis for fast pde-constrained optimization. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, volume 119 of *Proceedings of Machine Learning Research*, pages 10638–10647. PMLR, 2020.

[11] Rui Wang, Danielle Maddix, Christos Faloutsos, Yuyang Wang, and Rose Yu. Bridging physics-based and data-driven modeling for learning dynamical systems. *arXiv preprint arXiv:2011.10616*, 2020.

[12] Gustau Camps-Valls, Markus Reichstein, Xiaoxiang Zhu, and Devis Tuia. Advancing deep learning for earth sciences: From hybrid modeling to interpretability. In *IGARSS 2020-2020 IEEE International Geoscience and Remote Sensing Symposium*, pages 3979–3982. IEEE, 2020.

[13] Peter W. Battaglia, Razvan Pascanu, Matthew Lai, Danilo Jimenez Rezende, and Koray Kavukcuoglu. Interaction networks for learning about objects, relations and physics. In Daniel D. Lee, Masashi Sugiyama, Ulrike von Luxburg, Isabelle Guyon, and Roman Garnett, editors, *Advances in Neural Information Processing Systems 29: Annual Conference on Neural Information Processing Systems 2016, December 5-10, 2016, Barcelona, Spain*, pages 4502–4510, 2016.

[14] Alvaro Sanchez-Gonzalez, Nicolas Heess, Jost Tobias Springenberg, Josh Merel, Martin A. Riedmiller, Raia Hadsell, and Peter W. Battaglia. Graph networks as learnable physics engines for inference and control. In Jennifer G. Dy and Andreas Krause, editors, *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, volume 80 of *Proceedings of Machine Learning Research*, pages 4467–4476. PMLR, 2018.

[15] Jiajun Wu, Erika Lu, Pushmeet Kohli, Bill Freeman, and Josh Tenenbaum. Learning to see physics via visual de-animation. In Isabelle Guyon, Ulrike von Luxburg, Samy Bengio, Hanna M. Wallach, Rob Fergus, S. V. N. Vishwanathan, and Roman Garnett, editors, *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pages 153–164, 2017.

[16] Maziar Raissi, Paris Perdikaris, and George E. Karniadakis. Physics-informed neural networks: A deep learning framework for solving forward and inverse problems involving nonlinear partial differential equations. *Journal of Computational Physics*, 378:686–707, 2019.

[17] Jenny Brynjarsdottir and Anthony OHagan. Learning about physical parameters: The importance of model discrepancy. *Inverse problems*, 30(11):114007, 2014.

[18] Yaofeng Desmond Zhong, Biswadip Dey, and Amit Chakraborty. Extending lagrangian and hamiltonian neural networks with differentiable contact models. *Advances in Neural Information Processing Systems*, 34, 2021.

[19] Ori Linial, Neta Ravid, Danny Eytan, and Uri Shalit. Generative ode modeling with known unknowns. In *Proceedings of the Conference on Health, Inference, and Learning*, pages 79–94, 2021.

[20] Pengzhan Jin, Zhen Zhang, Aiqing Zhu, Yifa Tang, and George Em Karniadakis. Sympnets: Intrinsic structure-preserving symplectic networks for identifying hamiltonian systems. *Neural Networks*, 132:166–179, 2020.

[21] Steven L Brunton, Marko Budišić, Eurika Kaiser, and J Nathan Kutz. Modern koopman theory for dynamical systems. *arXiv preprint arXiv:2102.12086*, 2021.

[22] Tom Bertalan, Felix Dietrich, Igor Mezić, and Ioannis G Kevrekidis. On learning hamiltonian systems from data. *Chaos: An Interdisciplinary Journal of Nonlinear Science*, 29(12):121107, 2019.

[23] Steeven Janny, Fabien Baradel, Natalia Neverova, Madiha Nadri, Greg Mori, and Christian Wolf. Filtered-cophy: Unsupervised learning of counterfactual physics in pixel space. *arXiv preprint arXiv:2202.00368*, 2022.

[24] Pingchuan Ma, Tao Du, Joshua B Tenenbaum, Wojciech Matusik, and Chuang Gan. Risp: Rendering-invariant state predictor with differentiable simulation and rendering for cross-domain parameter estimation. *arXiv preprint arXiv:2205.05678*, 2022.

[25] Niv Giladi, Zvika Ben-Haim, Sella Nevo, Yossi Matias, and Daniel Soudry. Physics-aware downsampling with deep learning for scalable flood modeling. *Advances in Neural Information Processing Systems*, 34, 2021.

[26] Rongye Shi, Zhaobin Mo, and Xuan Di. Physics-informed deep learning for traffic state estimation: A hybrid paradigm informed by second-order traffic models. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pages 540–547, 2021.

[27] Andreas Hochlehnert, Alexander Terenin, Steindór Sæmundsson, and Marc Deisenroth. Learning contact dynamics using physically structured neural networks. In *International Conference on Artificial Intelligence and Statistics*, pages 2152–2160. PMLR, 2021.

[28] Rui Wang, Danielle Maddix, Christos Faloutsos, Yuyang Wang, and Rose Yu. Bridging physics-based and data-driven modeling for learning dynamical systems. In *Learning for Dynamics and Control*, pages 385–398. PMLR, 2021.

[29] Aditi Krishnapriyan, Amir Gholami, Shandian Zhe, Robert Kirby, and Michael W Mahoney. Characterizing possible failure modes in physics-informed neural networks. *Advances in Neural Information Processing Systems*, 34, 2021.

[30] Michael Lutter, Christian Ritter, and Jan Peters. Deep lagrangian networks: Using physics as model prior for deep learning. In *7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9, 2019*. OpenReview.net, 2019.

[31] Jayesh K. Gupta, Kunal Menda, Zachary Manchester, and Mykel J. Kochenderfer. A general framework for structured learning of mechanical systems. *arXiv preprint arXiv:1902.08705*, 2019.

[32] Miles Cranmer, Sam Greydanus, Stephan Hoyer, Peter Battaglia, David Spergel, and Shirley Ho. Lagrangian neural networks. *arXiv preprint arXiv:2003.04630*, 2020.

[33] Samuel Greydanus, Misko Dzamba, and Jason Yosinski. Hamiltonian neural networks. In Hanna M. Wallach, Hugo Larochelle, Alina Beygelzimer, Florence d'Alché-Buc, Emily B. Fox, and Roman Garnett, editors, *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada*, pages 15353–15363, 2019.

[34] Rui Wang, Robin Walters, and Rose Yu. Meta-learning dynamics forecasting using task inference. *arXiv preprint arXiv:2102.10271*, 2021.

[35] Yaofeng Desmond Zhong, Biswadip Dey, and Amit Chakraborty. Symplectic ode-net: Learning hamiltonian dynamics with control. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020.

[36] Peter Toth, Danilo J. Rezende, Andrew Jaegle, Sébastien Racanière, Aleksandar Botev, and Irina Higgins. Hamiltonian generative networks. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020.

[37] Irina Higgins, Peter Wirnsberger, Andrew Jaegle, and Aleksandar Botev. Symetric: Measuring the quality of learnt hamiltonian dynamics inferred from vision. *Advances in Neural Information Processing Systems*, 34, 2021.

[38] Alejandro Queiruga, N Benjamin Erichson, Liam Hodgkinson, and Michael W Mahoney. Stateful ode-nets using basis function expansions. *Advances in Neural Information Processing Systems*, 34, 2021.

[39] Yaofeng Desmond Zhong, Biswadip Dey, and Amit Chakraborty. Benchmarking energy-conserving neural networks for learning dynamics from data. In *Learning for Dynamics and Control*, pages 1218–1229. PMLR, 2021.

[40] Kookjin Lee, Nathaniel Trask, and Panos Stinis. Machine learning structure preserving brackets for forecasting irreversible processes. *Advances in Neural Information Processing Systems*, 34, 2021.

[41] Alvaro Sanchez-Gonzalez, Jonathan Godwin, Tobias Pfaff, Rex Ying, Jure Leskovec, and Peter W. Battaglia. Learning to simulate complex physics with graph networks. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, volume 119 of *Proceedings of Machine Learning Research*, pages 8459–8468. PMLR, 2020.

[42] Kiwon Um, Robert Brand, Philipp Holl, Nils Thuerey, et al. Solver-in-the-loop: Learning from differentiable physics to interact with iterative pde-solvers. *arXiv preprint arXiv:2007.00016*, 2020.

[43] Eric Heiden, David Millard, Erwin Coumans, Yizhou Sheng, and Gaurav S. Sukhatme. Neuralsim: Augmenting differentiable simulators with neural networks. *arXiv preprint arXiv:2011.04217*, 2020.

[44] Krishna Murthy Jatavallabhula, Miles Macklin, Florian Golemo, Vikram Voleti, Linda Petrini, Martin Weiss, Breandan Considine, Jerome Parent-Levesque, Kevin Xie, Kenny Erleben, et al. gradsim: Differentiable simulation for system identification and visuomotor control. *arXiv preprint arXiv:2104.02646*, 2021.

[45] Miguel Jaques, Michael Burke, and Timothy M. Hospedales. Physics-as-inverse-graphics: Unsupervised physical parameter estimation from video. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020.

[46] Matthew Tancik, Pratul P. Srinivasan, Ben Mildenhall, Sara Fridovich-Keil, Nithin Raghavan, Utkarsh Singhal, Ravi Ramamoorthi, Jonathan T. Barron, and Ren Ng. Fourier features let networks learn high frequency functions in low dimensional domains. *arXiv preprint arXiv:2006.10739*, 2020.

[47] Ali Rahimi and Benjamin Recht. Random features for large-scale kernel machines. *Advances in neural information processing systems*, 20, 2007.

[48] James Lee-Thorp, Joshua Ainslie, Ilya Eckstein, and Santiago Ontanon. Fnet: Mixing tokens with fourier transforms. *arXiv preprint arXiv:2105.03824*, 2021.

[49] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. In Isabelle Guyon, Ulrike von Luxburg, Samy Bengio, Hanna M. Wallach, Rob Fergus, S. V. N. Vishwanathan, and Roman Garnett, editors, *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pages 5998–6008, 2017.

[50] M. Grewal and Keith Glover. Identifiability of linear and nonlinear dynamical systems. *IEEE Transactions on automatic control*, 21(6):833–837, 1976.

[51] Hannu Pohjanpalo. System identifiability based on the power series expansion of the solution. *Mathematical biosciences*, 41(1-2):21–33, 1978.

[52] Hongyu Miao, Xiaohua Xia, Alan S. Perelson, and Hulin Wu. On identifiability of nonlinear ode models and applications in viral dynamics. *SIAM review*, 53(1):3–39, 2011.

[53] Danijar Hafner, Timothy P. Lillicrap, Ian Fischer, Ruben Villegas, David Ha, Honglak Lee, and James Davidson. Learning latent dynamics for planning from pixels. In Kamalika Chaudhuri and Ruslan Salakhutdinov, editors, *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, volume 97 of *Proceedings of Machine Learning Research*, pages 2555–2565. PMLR, 2019.

[54] Yaofeng Desmond Zhong and Naomi Leonard. Unsupervised learning of lagrangian dynamics from images for prediction and control. *Advances in Neural Information Processing Systems*, 33, 2020.

[55] Arthur Jacot, Clément Hongler, and Franck Gabriel. Neural tangent kernel: Convergence and generalization in neural networks. In Samy Bengio, Hanna M. Wallach, Hugo Larochelle, Kristen Grauman, Nicolò Cesa-Bianchi, and Roman Garnett, editors, *Advances in Neural Information Processing Systems 31: Annual Conference on Neural Information Processing Systems 2018, NeurIPS 2018, December 3-8, 2018, Montréal, Canada*, pages 8580–8589, 2018.

[56] Tian Qi Chen, Yulia Rubanova, Jesse Bettencourt, and David Duvenaud. Neural ordinary differential equations. In Samy Bengio, Hanna M. Wallach, Hugo Larochelle, Kristen Grauman, Nicolò Cesa-Bianchi, and Roman Garnett, editors, *Advances in Neural Information Processing Systems 31: Annual Conference on Neural Information Processing Systems 2018, NeurIPS 2018, December 3-8, 2018, Montréal, Canada*, pages 6572–6583, 2018.

[57] Diederik P. Kingma and Max Welling. Auto-encoding variational bayes. In Yoshua Bengio and Yann LeCun, editors, *2nd International Conference on Learning Representations, ICLR 2014, Banff, AB, Canada, April 14-16, 2014, Conference Track Proceedings*, 2014.

[58] Zongyi Li, Nikola Kovachki, Kamyar Azizzadenesheli, Burigede Liu, Kaushik Bhattacharya, Andrew Stuart, and Anima Anandkumar. Fourier neural operator for parametric partial differential equations. *arXiv preprint arXiv:2010.08895*, 2020.

[59] Vincent Sitzmann, Julien Martel, Alexander Bergman, David Lindell, and Gordon Wetzstein. Implicit neural representations with periodic activation functions. *Advances in Neural Information Processing Systems*, 33:7462–7473, 2020.

[60] Kimin Lee, Younggyo Seo, Seunghyun Lee, Honglak Lee, and Jinwoo Shin. Context-aware dynamics model for generalization in model-based reinforcement learning. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, volume 119 of *Proceedings of Machine Learning Research*, pages 5757–5766. PMLR, 2020.

[61] Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In Yoshua Bengio and Yann LeCun, editors, *3rd International Conference on Learning Representations, ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Conference Track Proceedings*, 2015.

Supplementary Material

Outline. Supplementary material is outlined as follows. Section A discusses the impact of the proposed model. Section B details the proof of the Fourier feature kernels. Section C gives the derivation of the training loss of an NTK. Section D provides details of the training pipeline and the model architecture. Finally, Section E assembles the additional experimental results. These include:

(1) visualization of encoded states estimated from the self-attention network of ALPS and its attention maps in the pendulum task,

(2) visualization of reconstructed observations and prediction of system parameters for each task, and

(3) analysis of self-attention networks in predicting states from observations.

A   Impact of ALPS

Many control systems such as self-driving cars and autonomous robots are complex. In order to deal with this complexity, researchers are increasingly using reinforcement learning (RL) to design control policies. One approach is to design a *model-based* RL algorithm, in which we first learn a model of the system dynamics from trajectory data, and then use this model to learn or synthesize a policy. Compared to the approach that uses neural networks to model the dynamics, ALPS can exploit prior knowledge about the system dynamics to have better learning efficiency and generalization. In addition, using continuous-time system dynamics allows us to better capture the behavior of the system, and incorporate other control properties into the model such as stability and controllability of the system.

One assumption of ALPS is that we need to have prior knowledge of the system. This assumption is reasonable since in many practical applications, system designers can use the law of physics to design models. For example, we know Newton's laws of motion are still true on Mars, but its gravitational constant is different. However, for some systems such as contact dynamics, we do not have good knowledge about how to design models. We make assumptions that ALPS requires knowing the equation of the system dynamics and having a differentiable solver for it. These assumptions are too restrictive to make this useful in practice. A potential way to overcome this is to develop a hybrid approach, in which we use positions and velocities that follow the law of physics as latent state representations, followed by network networks that capture complex dynamics to compensate for unmodeled parts of the system.

This raises several questions: What kind of neural architecture is needed to capture the dynamics of the system? How to applied ALPS in more complicated settings or unseen objects during testing? We believe this paper will encourage future work to develop rigorous design and analysis tools for learning system dynamics.

B   Proof of the Kernel Functions

We now derive the kernel of the Fourier feature mapping. We review the setup here. Consider a state trajectory $\boldsymbol{v} = [x_0, x_1, \ldots, x_{\tau-1}]^T$, where here we consider a 1D case for a scalar state $x \in \mathbb{R}$ although it can be easily extended to a vector state $\boldsymbol{x} \in \mathbb{R}^n$. The feature maps of the Fourier feature mapping, their magnitudes, and their phases are

$$\phi_{\text{DFT}}(\boldsymbol{v}) = [X_0, \ldots, X_k, \ldots, X_{\tau-1}]^T \in \mathbb{R}^\tau, X_k = \sum_{j=0}^{\tau-1} x_j \Big[\cos\Big(\frac{2\pi}{\tau}kj\Big) - i \sin\Big(\frac{2\pi}{\tau}kj\Big) \Big];$$

$$\phi_{\text{MAG}}(\boldsymbol{v}) = [|X_0|, \ldots, |X_k|, \ldots, |X_{\tau-1}|]^T \in \mathbb{R}^\tau;$$

$$\phi_{\text{PHA}}(\boldsymbol{v}) = [\arg(X_0), \ldots, \arg(X_k), \ldots, \arg(X_{\tau-1})]^T \in \mathbb{R}^\tau.$$

670   Set $C_k = \left[\cos \left(\frac{2\pi}{\tau} ki \right) - \sin \left(\frac{2\pi}{\tau} kj \right) \right] \in \mathbb{R}^{\tau \times \tau}$, then the kernel functions of these mappings are

$$k_{\text{DFT}}(\boldsymbol{v}_1, \boldsymbol{v}_2) = \sum_{k=0}^{\tau-1} \boldsymbol{v}_1^T C_k \boldsymbol{v}_2;$$

$$k_{\text{MAG}}(\boldsymbol{v}_1, \boldsymbol{v}_2) = \sum_{k=0}^{\tau-1} \sqrt{\boldsymbol{v}_1^T C_k \boldsymbol{v}_1 \boldsymbol{v}_2^T C_k \boldsymbol{v}_2};$$

$$k_{\text{PHA}}(\boldsymbol{v}_1, \boldsymbol{v}_2) = \phi_{\text{PHA}}(\boldsymbol{v}_1)^T \phi_{\text{PHA}}(\boldsymbol{v}_2).$$

671   *Proof:*

672   **(1)** $k_{\text{DFT}}(\boldsymbol{v}_1, \boldsymbol{v}_2)$: Let $\boldsymbol{v}_1 = \begin{bmatrix} x_{1,1}, \\ \vdots, \\ x_{\tau-1,1} \end{bmatrix}$ and $\boldsymbol{v}_2 = \begin{bmatrix} x_{1,2}, \\ \vdots, \\ x_{\tau-1,2} \end{bmatrix}$. Then

$$
\begin{aligned}
&k_{\text{DFT}}(\boldsymbol{v}_1, \boldsymbol{v}_2)\\
&= \phi_{\text{DFT}}(\boldsymbol{v}_1)^T \phi_{\text{DFT}}(\boldsymbol{v}_2)\\
&= \left[\sum_{j=0}^{\tau-1} x_{j,1} \cos\left(\frac{2\pi}{\tau} j \cdot k \right), \sum_{j=0}^{\tau-1} x_{j,1} \sin\left(\frac{2\pi}{\tau} j \cdot k \right) \right]_k \begin{bmatrix} \sum_{j=0}^{\tau-1} x_{j,2} \cos\left(\frac{2\pi}{\tau} j \cdot k \right) \\ \sum_{j=0}^{\tau-1} x_{j,2} \sin\left(\frac{2\pi}{\tau} j \cdot k \right) \end{bmatrix}_k\\
&= \sum_{k=0}^{\tau-1} \left(\boldsymbol{v}_1^T \begin{bmatrix} \cos\left(\frac{2\pi}{\tau} \cdot 1 \cdot k \right) \\ \vdots \\ \cos\left(\frac{2\pi}{\tau} \cdot (\tau-1) \cdot k \right) \end{bmatrix} \boldsymbol{v}_2^T \begin{bmatrix} \cos\left(\frac{2\pi}{\tau} \cdot 1 \cdot k \right) \\ \vdots \\ \cos\left(\frac{2\pi}{\tau} \cdot (\tau-1) \cdot k \right) \end{bmatrix} \right.\\
&\quad\quad \left. + \boldsymbol{v}_1^T \begin{bmatrix} \sin\left(\frac{2\pi}{\tau} \cdot 1 \cdot k \right) \\ \vdots \\ \sin\left(\frac{2\pi}{\tau} \cdot (\tau-1) \cdot k \right) \end{bmatrix} \boldsymbol{v}_2^T \begin{bmatrix} \sin\left(\frac{2\pi}{\tau} \cdot 1 \cdot k \right) \\ \vdots \\ \sin\left(\frac{2\pi}{\tau} \cdot (\tau-1) \cdot k \right) \end{bmatrix} \right)\\
&= \sum_{k=0}^{\tau-1} \boldsymbol{v}_1^T \left(\begin{bmatrix} \cos\left(\frac{2\pi}{\tau} \cdot 1 \cdot k \right) \\ \vdots \\ \cos\left(\frac{2\pi}{\tau} \cdot (\tau-1) \cdot k \right) \end{bmatrix} \left[\cos\left(\frac{2\pi}{\tau} \cdot 1 \cdot k \right), \ldots, \cos\left(\frac{2\pi}{\tau} \cdot (\tau-1) \cdot k \right) \right] \right.\\
&\quad\quad \left. + \begin{bmatrix} \sin\left(\frac{2\pi}{\tau} \cdot 1 \cdot k \right) \\ \vdots \\ \sin\left(\frac{2\pi}{\tau} \cdot (\tau-1) \cdot k \right) \end{bmatrix} \left[\sin\left(\frac{2\pi}{\tau} \cdot 1 \cdot k \right), \ldots, \sin\left(\frac{2\pi}{\tau} \cdot (\tau-1) \cdot k \right) \right] \right) \boldsymbol{v}_2\\
&= \sum_{k=0}^{\tau-1} \boldsymbol{v}_1^T C_k \boldsymbol{v}_2,
\end{aligned}
$$

673   which completes the proof of $k_{\text{DFT}}(\boldsymbol{v}_1, \boldsymbol{v}_2)$.

674 **(2)** $k_{\mathrm{MAG}}(\boldsymbol{v}_1, \boldsymbol{v}_2)$: Let $\boldsymbol{c}_k = \begin{bmatrix} \cos\left(\frac{2\pi}{\tau} \cdot k \cdot 0\right) \\ \vdots \\ \cos\left(\frac{2\pi}{\tau} \cdot k \cdot (\tau-1)\right) \end{bmatrix}$ and $\boldsymbol{s}_k = \begin{bmatrix} \sin\left(\frac{2\pi}{\tau} \cdot k \cdot 0\right) \\ \vdots \\ \sin\left(\frac{2\pi}{\tau} \cdot k \cdot (\tau-1)\right) \end{bmatrix}$. Then

$$
\begin{aligned}
& k_{\mathrm{MAG}}(\boldsymbol{v}_1, \boldsymbol{v}_2) \\
&= \phi_{\mathrm{MAG}}(\boldsymbol{v}_1)^T \phi_{\mathrm{MAG}}(\boldsymbol{v}_2) \\
&= \left[\sqrt{ \left(\sum_{j=0}^{\tau-1} x_{j,1} \cos\left(\frac{2\pi}{\tau} j \cdot k\right) \right)^2 + \left(\sum_{j=0}^{\tau-1} x_{j,1} \sin\left(\frac{2\pi}{\tau} j \cdot k\right) \right)^2 } \right]^T_k \\
& \qquad \left[\sqrt{ \left(\sum_{j=0}^{\tau-1} x_{j,2} \cos\left(\frac{2\pi}{\tau} j \cdot k\right) \right)^2 + \left(\sum_{j=0}^{\tau-1} x_{j,2} \sin\left(\frac{2\pi}{\tau} j \cdot k\right) \right)^2 } \right]_k \\
&= \sum_{k=0}^{\tau-1} \left(\sqrt{\left(\boldsymbol{v}_1^T \boldsymbol{c}_k\right)^2 + \left(\boldsymbol{v}_1^T \boldsymbol{s}_k\right)^2} \sqrt{\left(\boldsymbol{v}_2^T \boldsymbol{c}_k\right)^2 + \left(\boldsymbol{v}_2^T \boldsymbol{s}_k\right)^2} \right) \\
&= \sum_{k=0}^{\tau-1} \sqrt{\left(\boldsymbol{v}_1^T \boldsymbol{s}_k \boldsymbol{c}_k^T \boldsymbol{v}_2\right)^2 + \left(\boldsymbol{v}_1^T \boldsymbol{c}_k \boldsymbol{s}_k^T \boldsymbol{v}_2\right)^2 + \left(\boldsymbol{v}_1^T \boldsymbol{c}_k \boldsymbol{c}_k^T \boldsymbol{v}_2\right)^2 + \left(\boldsymbol{v}_1^T \boldsymbol{s}_k \boldsymbol{s}_k^T \boldsymbol{s}_2\right)^2}. \qquad (2)
\end{aligned}
$$

675 Set $a_k = \boldsymbol{v}_1^T \boldsymbol{s}_k, b_k = \boldsymbol{v}_2^T \boldsymbol{c}_k, c_k = \boldsymbol{v}_1^T \boldsymbol{c}_k$, and $d_k = \boldsymbol{v}_2^T \boldsymbol{s}_k$. Then

$$
\begin{aligned}
(2) &= \sum_{k=0}^{\tau-1} \sqrt{\left(a_k b_k\right)^2 + \left(c_k d_k\right)^2 + \left(b_k c_k\right)^2 + \left(a_k d_k\right)^2} \\
&= \sum_{k=0}^{\tau-1} \sqrt{\left(a_k^2 + c_k^2\right)\left(b_k^2 + d_k^2\right)} \\
&= \sum_{k=0}^{\tau-1} \sqrt{\left(\boldsymbol{v}_1^T \boldsymbol{s}_k \boldsymbol{s}_k^T \boldsymbol{v}_1 + \boldsymbol{v}_1^T \boldsymbol{c}_k \boldsymbol{c}_k^T \boldsymbol{v}_1\right)^2 + \left(\boldsymbol{v}_2^T \boldsymbol{c}_k \boldsymbol{c}_k^T \boldsymbol{v}_2 + \boldsymbol{v}_2^T \boldsymbol{s}_k \boldsymbol{s}_k^T \boldsymbol{v}_2\right)^2} \\
&= \sum_{k=0}^{\tau-1} \sqrt{\left(\boldsymbol{v}_1^T (\boldsymbol{s}_k \boldsymbol{s}_k^T + \boldsymbol{c}_k \boldsymbol{c}_k^T) \boldsymbol{v}_1\right)^2 + \left(\boldsymbol{v}_2^T (\boldsymbol{c}_k \boldsymbol{c}_k^T + \boldsymbol{s}_k \boldsymbol{s}_k^T) \boldsymbol{v}_2\right)^2} \\
&= \sum_{k=0}^{\tau-1} \sqrt{\boldsymbol{v}_1^T \boldsymbol{C}_k \boldsymbol{v}_1 \boldsymbol{v}_2^T \boldsymbol{C}_k \boldsymbol{v}_2},
\end{aligned}
$$

676 which completes the proof of $k_{\mathrm{MAG}}(\boldsymbol{v}_1, \boldsymbol{v}_2)$. $\qquad\square$

C   Derivation of the Training Loss of NTK

678 We now provide more details on the derivation of the training error of a neural network after
679 t times update. To be complete, we review the notations here. Let $\boldsymbol{K} = \boldsymbol{U}\boldsymbol{\Sigma}\boldsymbol{U}^T$ denote the
680 eigendecomposition of the kernel matrix $\boldsymbol{K}$ which must be positive semidefinite (PSD). Here $\boldsymbol{U}$ is an
681 orthogonal matrix and $\boldsymbol{\Sigma}$ is a diagonal matrix whose entries are the nonnegative eigenvalues ordered

by magnitude: $\lambda_1 \geq \lambda_2 \geq \cdots \geq \lambda_m \geq 0$. So the training error in terms of L_2 norm $\|\cdot\|_2^2$ is

$$
\begin{aligned}
\left\|\hat{\boldsymbol{y}}^{(t)} - \boldsymbol{y}\right\|_2^2 &= \left\| \begin{bmatrix} \boldsymbol{y}^T(\boldsymbol{I} - e^{-\eta \boldsymbol{K} t})\boldsymbol{K}^{-1} k(\boldsymbol{v}_1) \\ \vdots \\ \boldsymbol{y}^T(\boldsymbol{I} - e^{-\eta \boldsymbol{K} t})\boldsymbol{K}^{-1} k(\boldsymbol{v}_m) \end{bmatrix}_{m \times 1} - \boldsymbol{y} \right\|_2^2 \\
&= \left\| \boldsymbol{K}\boldsymbol{K}^{-1}(\boldsymbol{I} - e^{-\eta \boldsymbol{K} t})\boldsymbol{y} - \boldsymbol{y} \right\|_2^2 \\
&= \left\| e^{-\eta \boldsymbol{K} t}\boldsymbol{y} \right\|_2^2 \\
&= \left\| \boldsymbol{U} e^{-\eta \boldsymbol{\Sigma} t}\boldsymbol{U}^T \boldsymbol{y} \right\|_2^2 \\
&= \left\| \boldsymbol{U}\mathrm{diag}([e^{-\eta \lambda_1 t}, \ldots, e^{-\eta \lambda_m t}]^T)\boldsymbol{U}^T \boldsymbol{y} \right\|_2^2,
\end{aligned}
$$

where the last two equations follows the fact that $e^{-\eta \boldsymbol{K} t} = \boldsymbol{U} e^{-\eta \boldsymbol{\Sigma} t}\boldsymbol{U}^T$. This completes the derivation.

D Experimental Details

D.1 Training details

Setup. For all the tasks we train our model and the baselines using Adam [61] with maximum of 10,000 epochs and a learning rate of 3×10^{-3}. The batch size is 32 (*i.e.,* 32 rollouts), and we use a gradient clipping of 1.0 in terms of 2-norm to stabilize training. For the physics simulator, we use the four-step Runge-Kutta (RK4) as the numerical integration scheme in neural ODE. For computational resources, we train our model and the baselines in two machines: machine A has an Intel i9-9980HK CPU, and machine B has an Intel i7-6850K CPU with 4 NVIDIA GTX 1080 GPUs. In general, it takes about 8 hours to finish training. Fig. 6 plots the training curves of the four tasks.

Instructions needed to reproduce the results. The code can be found in the same zip file.

D.2 Implementation and model architectures

We use the same architecture over our model in the visual tasks. A grid search is conducted to find the hyper-parameters of the model (*i.e.,* size of the networks, types of the activation function). We now describe each component in ALPS.

The encoder. To process pixel observations, the encoder uses a convolution neural network (CNN) with two convolutions and 2 by 2 max-poolings–the first convolution has a kernel size of 3 and a channel size of 3, and the second one has a kernel size of 4 and a channel size of 4, followed by vectorization to get a vector representation of an image. To provide the position information to this image representation, we obtain a positional embedding with the same size as the image representation using sine and cosine functions. We then concatenate these two vectors and feed them into a self-attention network, where the network has 10 attention heads and a relu activation function. Finally, the network outputs state estimations along the time horizon. Specifically, we only use the encoder part of the Transformer [49] without a dropout operation. We find that removing a dropout operation and using a relu activation function achieve the best result.

The estimator. For each element of the state predicted from the encoder, we construct a Fourier feature mapping. For example, the state of the pendulum consists of an angle and an angular velocity–we will have two vectors of the Fourier feature mapping here. Then, for each Fourier feature mapping, we use a residual network [1] with two residual blocks and a tanh activation function to get a representation. Finally, we concatenate these representations and feed them into an MLP to predict a system parameter. We find that using residual networks and a tanh activation function makes training faster and converges to a good result.

The simulator. The ODE solver takes in the predicted system parameter, and then rollouts state trajectories given the initial state predicted from the encoder.

The decoder. We use a two-layer MLP with a relu activation function and the size of 400, 400 to take in the simulated states and reconstruct the observations.

Figure 6: Learning curves during training of ALPS in the four tasks.

Figure 7: The state trajectories and the attention maps of the self-attention network in the pendulum task. We see that the self-attention network is able to infer states based on observations.

For the real MSD task, we remove the encoder and decoder in ALPS since we get noisy measurements of states in train wheel systems. For ALPS without Fourier features, we use the same architecture but the estimator becomes a single residual network that takes in an entire state trajectory in the time domain. For ALPS without self-attention networks, we use the same architecture but the encoder becomes a two-layer MLP with a relu activation that takes in image representations and predicts the position of an object. To estimate the velocity, we follow the procedure in [54], which uses a finite difference method.

Finally, for the baseline model CDM, we use the same model in [60], which consists of a context network (an MLP with the size of 400, 400), a forward network (an MLP with the size of 20, 20), and a backward network (an MLP with the size of 20, 20).

Note that CDM is trained with the loss function used in [60]; Autoencoder is trained with the VAE loss and observation reconstruction loss terms; the ablations of ALPS are trained with the same loss functions as the full model.

Figure 8: Examples of reconstructed and true observation sequences of ALPS and CDM over three visual tasks. We see that ALPS is able to robustly generate the observations.

E   Additional Results

E.1   Visualization of encoded states prediction and attention map of the self-attention network

An important feature of ALPS is that it uses self-attention networks to infer states from pixel observations. Fig. 7 shows the encoded states $\{\tilde{x}_s\}$, the ODE-simulated states $\{\hat{x}_s\}$, and the true states $\{x_s\}$ over time horizons τ as well as its attention map in the pendulum task. We see that the self-attention network is able to track the state evolution of the system from pixel observations. In addition, we observe that there is a small delay between the true states and the ODE-simulated states. This is due to a small prediction error in the initial state and the system parameter, which then accumulates over the time horizon.

For the attention map, the summation of each row is equal to one. This map shows that for each time step how much information of each observation in the entire trajectory is needed to predict the state at that time step. Here, we use a mask with the size of 15 to limit the attention width of the network. We see that the network mostly uses the observation in the beginning and the end of the attention mask to infer states. This suggests that the network learns to predict an *average* velocity. In addition, we see that there are vertical attention patterns, which happens to be at the peak of the cosine wave. We suspect that the network uses this information as an anchor to capture the periodic behavior of the pendulum. We leave this as a future work to understand the network.

E.2   Visualization of reconstructed observations and prediction of system parameters

ALPS uses an autoencoder to learn system dynamics. Fig. 8 shows reconstructed observations of ALPS and the baseline in three visual tasks. We see that ALPS is able to accurately reconstruct the observations, whereas CDM fails to predict observations with duplicated particles in the Two-Body system and blur images in the MSD system. This implies that using physics in the loop can help to converge to a good solution.

In addition, Fig. 9 shows the system parameter prediction performance of ALPS over three visual tasks. Please see the caption for more details about the figure. We see that the model is able to reliably predict the system parameters in most cases. However, we also see there are some outliers for each group. We leave this as a future improvement.

E.3   Analysis of self-attention networks

An important feature of ALPS is the use of self-attention networks for estimating states from observations. To provide the intuition about the mechanism of the self-attention network, we regress the self-attention network with true states of the system and visualize its attention weights on a simple

Figure 9: System parameter prediction performance of ALPS in the visual tasks. We categorize the value of the true system parameters, and show the box plot of the corresponding prediction values. The values at the bottom show the prediction mean and standard deviation of each group. We see that ALPS can identify the system parameters well.

vehicle steering dynamics:

$$\frac{d\boldsymbol{x}}{dt} = \begin{bmatrix} 0 & 1 \\ 0 & 0 \end{bmatrix} \boldsymbol{x} + \begin{bmatrix} 0.1 \\ 1 \end{bmatrix} u,$$

where the first element in $\boldsymbol{x} = [x^p, x^r]^T$ represents the lateral path deviation (*i.e.,* the distance between the vehicle and the center of the road), the second element represents turning rate, and u is the input force to the steering wheel. In this example, we want to estimate either x^p or x^r by observing x^r or x^p, respectively. Intuitively, in the first case (estimate x^p from x^r), a self-attention network should perform *derivative* operation, whereas in the second case (estimate x^r from x^p), a self-attention network should perform *integration* operation. Fig. 10 shows the result of the two cases. Here we use a single head self-attention network with a tanh activation function to regress the supervised data, and test on the testing data. In the first case the network attends to the neighboring observations at the current time (*i.e.,* diagonal pattern), whereas in the second case the network attends to the observations from beginning to the current time (*i.e.,* lower triangular pattern, global context). This observation suggests the network does exploit the local context to compute the gradient (*i.e.,* $x_t^r \approx \frac{x_{t+1}^p - x_t^p}{\Delta t}$), and use the global context to obtain the integral (*i.e.,* $x_t^p \approx \sum_{t'=0}^{t-1} x_{t'}^r$).

(a) Estimates the turning rate from the lateral path deviation

(b) Estimates the lateral path deviation from the turning rate

Figure 10: The patterns of the attention weight in the self-attention networks show the network attends to the local context (diagonal) to compute the gradient, and use the global context (lower triangular) to obtain the integral. **(a)** The case where the network estimates the turning rate x^r from the lateral path deviation x^p and its attention weight. **(b)** The case where the network estimates the lateral path deviation x^p from the turning rate x^r and its attention weight. The green lines $\tilde{x}^r$ and $\tilde{x}^p$ are the predictions and the red lines are the true values (turn the screen brighter to see the patterns).