EvoCoder: Evolving Code Generation under the Oracle-Gap through Population-Based Search and Peer-Guided Adaptation

Abstract

Code generation for constraint-heavy problems remains brittle for large language models (LLMs), especially under the oracle-gap, where hidden tests and external evaluators are unavailable at inference time. We propose **EvoCoder**, a single-generation Lamarckian evolutionary framework that decouples natural-language solution strategies (*genotypes*) from executable programs (*phenotypes*) to enable population-based search without an external oracle. EvoCoder operates in three stages: (1) *Genotypic variation and expression*, selecting a diverse strategy subset via k-DPP before code generation; (2) *Surrogate feedback environment construction*, synthesizing boundary-focused tests and improving feedback reliability through dual-channel verification; and (3) *Selection and peer-guided Lamarckian adaptation*, where Semantic Spectrum Analysis localizes failure-driving divergences and transfers peer logic to repair the elite solution. Experiments on program synthesis, competitive programming, and hidden-test benchmarks show consistent gains over strong baselines across proprietary and open-source backbones, achieving up to 98.2% Pass@1 on HumanEval, 93.7% on MBPP, 44.8% on CodeContest, and 57.3% on APPS. EvoCoder also performs best on LiveCodeBench and generalizes better than baselines on ColBench's Backend Programming track.

1 Introduction

Large language models (LLMs) have rapidly improved code generation, producing executable programs on a wide range of synthesis and competitive programming benchmarks.(Chen et al., 2021; Li et al., 2022b; Rozière et al., 2024) Yet generation remains brittle on constraint-heavy problems whose correctness depends on corner cases, boundary conditions, and hidden tests.(Chen et al., 2023) In such settings, inference-time code generation

Figure 1: Limitations of existing paradigms in code generation and an overview of EVOCODER.

faces an oracle-gap: the hidden evaluator that ultimately determines success is unavailable when the model must generate and refine code. This makes complex code generation fundamentally different from settings where candidate programs can be safely compared against a known validation function. Under the oracle-gap, feedback is sparse, self-constructed, and potentially noisy, so a seemingly reasonable refinement step can easily reinforce a wrong hypothesis rather than correct it.

Existing inference-time approaches only partially address this difficulty. One line improves one-shot generation through reasoning and iterative refinement, such as CoT, Self-Planning, and

Reflexion.(Wei et al., 2022; Jiang et al., 2024; Shinn et al., 2023b) Another line organizes generation through structured decomposition, tool use, or multi-agent coordination, such as MapCoder and CodeSim.(Islam et al., 2024, 2025) Despite different implementations, these methods often remain dominated by a single evolving trajectory: once an early algorithmic commitment is wrong, later updates tend to stay anchored to it. Figure 1 summarizes this limitation through three recurring symptoms: linear rigidity, where early wrong assumptions propagate because backtracking is limited; futile refinement, where feedback-driven iteration patches symptoms without fixing the failure-driving logic; and group hallucination, where multi-agent systems converge to a consistent yet incorrect consensus when evaluation signals are unavailable or unstable. These observations suggest that merely refining a single evolving trajectory is insufficient under the oracle-gap; what is needed is a search mechanism that can explicitly maintain competing hypotheses.

Beyond such trajectory-centric inference-time methods, another line of work combines LLMs with search or evolution. These approaches are highly effective when a reliable evaluator exists, because candidates can be ranked, filtered, and iteratively improved against trustworthy external feedback. However, this assumption breaks precisely in oracle-gap code generation, where hidden tests and external judging are unavailable at inference time. The central question of this paper is therefore not simply how to use evolution for code generation, but how to make evolutionary search viable when no reliable evaluator is available.

We answer this question with EVOCODER, a single-generation Lamarckian evolutionary framework for oracle-gap code generation. EvoCoder decouples natural-language solution strategies as genotypes from executable programs as phenotypes, so diversity is induced in strategy space before code generation commits to brittle implementation decisions. This single-generation design is deliberate: under noisy self-constructed feedback, long multi-generation loops can accumulate error and semantic drift, whereas a single controlled evolutionary pass preserves hypothesis diversity, enables evidence-backed repair, and keeps inference cost bounded.

To make evolution work without an external oracle, EvoCoder couples three mechanisms (lower half of Figure 1). In Genotypic Variation & Ex-

pression, EvoCoder samples a strategy pool conditioned on the problem and selects $K \ll M$ representative strategies via quality-aware k-DPP inference, reducing semantic collapse and preserving mutually exclusive algorithmic hypotheses before code realization.(Liu et al., 2021; Belhadji et al., 2018) In Surrogate Feedback Environment Construction, EvoCoder builds a surrogate feedback environment through boundary-focused test synthesis and Dual-Channel Verification (DCV), using a strict consistency gate to improve the reliability of self-constructed test labels. In Selection & Lamarckian Adaptation, EvoCoder selects an elite candidate under this verified surrogate feedback and applies Semantic Spectrum Analysis (SSA) to mine peer-success contrasts: instead of blindly mutating code or repeatedly retrying the same trajectory, EvoCoder transfers localized logic from a peer that succeeds exactly where the elite fails. This turns population diversity into targeted repair while reducing the chance that noisy self-generated feedback drives harmful updates.

Our contributions are three-fold:

- We identify oracle-gap code generation as a distinct inference-time setting in which hidden tests are unavailable and self-constructed feedback is noisy, making both single-trajectory refinement and evaluator-dependent evolutionary search unreliable.

- We propose EVOCODER, a single-generation Lamarckian evolutionary framework that makes search viable in this setting through genotype–phenotype decoupling, verified surrogate feedback construction, and peer-success-gated SSA-guided logic transfer.

- Across program synthesis, contest coding, and backend programming benchmarks, EvoCoder consistently outperforms strong prompting and agentic baselines on both proprietary and open-source LLMs, with especially large gains on hidden-test-sensitive settings.

2 Related Work

2.1 Program Synthesis, Agentic, and Search-Based Code Generation

Recent large language models (LLMs) trained on code have substantially advanced NL-to-code generation. Codex-style models established strong

synthesis baselines, and repeated sampling has proven effective for exploring the program space (Chen et al., 2021). For harder settings such as competitive programming, AlphaCode further scales candidate generation and selection to navigate the combinatorial search space (Li et al., 2022b). Meanwhile, open and specialized code LLMs have rapidly evolved, including CodeGen, InCoder, StarCoder, Code Llama, DeepSeek-Coder, and Qwen2.5-Coder (Nijkamp et al., 2023; Fried et al., 2023; Li et al., 2023; Rozière et al., 2024; Guo et al., 2024; Hui et al., 2024). Beyond direct decoding, recent work improves code generation through planning, self-refinement, multi-agent workflows, explicit search, and tool-augmented debugging, including Chain-of-Thought, Reflexion, MapCoder, CodeSim, Tree-of-Thoughts, CodeTree, LDB, and ChatDBG (Wei et al., 2022; Shinn et al., 2023b; Islam et al., 2024, 2025; Yao et al., 2023; Li et al., 2024; Zhong et al., 2024; Levin et al., 2025). Nevertheless, satisfying strict constraints and hidden tests remains challenging, motivating more reliable search and feedback mechanisms beyond one-shot decoding (Li et al., 2022b).

2.2 Evolutionary and Population-Based Program Search

Existing population-based search methods address different bottlenecks, but each remains limited in the oracle-gap setting. Evaluator-guided evolutionary methods, such as FunSearch, AlphaEvolve, and Evolving Deeper LLM Thinking, improve search by using population-level selection and mutation, but they rely on reliable evaluators or validation environments to rank candidates safely.(Romera-Paredes et al., 2024; Novikov et al., 2025; Lee et al., 2025) Large-scale population sampling methods such as AlphaCode broaden exploration in competitive programming, but they primarily depend on selection over large candidate pools rather than robust adaptation under missing evaluation.(Li et al., 2022a) Direct code-space optimization methods such as SFS improve diversity and search efficiency in code space, but can be misled when validation signals are sparse, self-generated, or noisy.(Light et al., 2025) Taken together, these methods improve search breadth, yet they do not directly resolve how to perform robust search when hidden tests are inaccessible and external evaluation is weak, unstable, or unavailable at inference time.

3 Method

3.1 Problem Formulation

We formulate competitive programming as function synthesis under an oracle-gap. Given a problem instance $\mathcal{P} = (D, \mathcal{I}_{\text{pub}})$, where D specifies the task and hard constraints and $\mathcal{I}_{\text{pub}}$ provides public examples, the goal is to generate an executable program C that passes the hidden test set $\mathcal{T}_{\text{hidden}}$ within the time limit:

$$\forall (x, y) \in \mathcal{T}_{\text{hidden}}, \quad \begin{aligned} \text{Exec}(C, x) &= y, \\ \text{Time}(C, x) &\leq T_{\text{lim}}. \end{aligned} \tag{1}$$

At inference time, $\mathcal{T}_{\text{hidden}}$ and external judging are unavailable, so we decouple generation into a strategy–code mapping:

$$D \xrightarrow{\pi_\theta(\cdot | D)} G \xrightarrow{\phi} C, \tag{2}$$

where $G \in \mathbb{G}$ is a natural-language strategy (genotype) sampled by π_θ, and $\phi : \mathbb{G} \to \mathbb{P}$ expresses G into an executable program $C \in \mathbb{P}$ (phenotype) for downstream evaluation and refinement.

3.2 EvoCoder Framework Overview

EvoCoder views competitive programming under the oracle-gap as feedback-driven search, where hidden tests make single-trajectory generation prone to early lock-in. It decouples natural-language strategies (*genotypes*) from executable programs (*phenotypes*) and runs a three-stage loop (Figure 2). In Stage 1, EvoCoder samples a pool of M strategies and then selects $K \ll M$ diverse representatives via k-DPP for code expression. In Stage 2, it constructs a surrogate feedback environment by Targeted Boundary Probing (TBP) and Dual-Channel Verification (DCV), forming a more reliable surrogate evaluation/feedback environment for comparing candidates. In Stage 3, it selects the elite under this surrogate feedback and performs peer-guided Lamarckian adaptation, where SSA localizes failure-driving divergences for targeted logic transfer.

3.3 Genotypic Variation and Expression

To initialize the evolutionary loop, we construct a high-coverage, low-redundancy population in the strategy space and transfer this diversity to code. We first distill the problem description D into a compact semantic anchor $\mathcal{S}_{\text{goal}}$ that preserves only the objective and hard constraints; subsequent strategy generation and variation are conditioned on

Figure 2: Overview of EVOCODER. **Stage 1:** given problem description D, we sample a strategy pool $\mathcal{G}_{\text{pool}} = \{g_i\}_{i=1}^{M}$ (genotypes), select $K \ll M$ diverse strategies via k-DPP, and express them into an initial code population $\mathcal{P}_{\text{init}}$ (phenotypes) using the coder ϕ. **Stage 2:** we construct a surrogate feedback environment T_{synth} with Targeted Boundary Probing (TBP) and Dual-Channel Verification (DCV) for reliable candidate evaluation. **Stage 3:** we select the elite p_{best} under T_{synth} and perform SSA-guided Lamarckian adaptation by mining peer-success contrasts T_{diff} for targeted logic transfer.

$\mathcal{S}_{\text{goal}}$. Conditioned on $(D, \mathcal{S}_{\text{goal}})$, we sample a strategy pool $\mathcal{G}_{\text{pool}} = \{g_1, \ldots, g_M\}$.

Selecting strategies by confidence-only Top-K often leads to semantic collapse (near-duplicate templates), which weakens exploration across mutually exclusive algorithmic hypotheses. We therefore use a k-DPP to select K representative strategies that trade off quality and diversity. Geometrically, $\det(L_Y)$ can be interpreted as the (squared) volume spanned by the selected strategy embeddings in feature space, so maximizing it encourages a more dispersed subset with broader coverage.

We define a kernel matrix $L \in \mathbb{R}^{M \times M}$:

$$L_{ij} = q_i q_j \, \kappa(\mathbf{v}_i, \mathbf{v}_j), \qquad (3)$$

where $\mathbf{v}_i$ is the ℓ_2-normalized Sentence-BERT embedding of g_i, $\kappa(\cdot, \cdot) \in [0, 1]$ is a semantic similarity, and q_i is a quality prior from token-level

log-likelihood:

$$q_i = \exp\!\Big(\frac{1}{|g_i|} \sum_{t=1}^{|g_i|} \log p_\theta(g_{i,t} \mid g_{i,<t}, D)\Big). \quad (4)$$

We choose $\mathcal{G}_{\text{init}}$ by maximizing $\det(L_Y)$ over $|Y| = K$ and use a greedy approximation:

$$\mathcal{G}_{\text{init}} \leftarrow \mathcal{G}_{\text{init}} \cup \Big\{ \arg\max_{g \in \mathcal{G}_{\text{pool}} \setminus \mathcal{G}_{\text{init}}} \det\!\big(L_{\mathcal{G}_{\text{init}} \cup \{g\}}\big) \Big\}. \quad (5)$$

After selection, we express only the K strategies to form the initial code population $\mathcal{P}_{\text{init}}$. The Coder $\phi : \mathbb{G} \to \mathbb{P}$ instantiates each g_k into an executable program while treating D and $\mathcal{S}_{\text{goal}}$ as immutable constraints and injecting g_k as an explicit path constraint, preserving genotype-level diversity for downstream surrogate feedback environment construction and adaptation.

3.4 Surrogate Feedback Environment Construction

Under the oracle-gap in competitive programming, hidden tests $\mathcal{T}_{\text{hidden}}$ are unavailable at inference time, so candidate evaluation must rely on self-constructed inputs and labels. Stage 2 therefore builds a surrogate feedback environment T_{synth} that is both discriminative and reliable. EvoCoder separates these two goals into two components: Targeted Boundary Probing (TBP), which diversifies synthesized tests toward informative failure regimes, and Dual-Channel Verification (DCV), which conservatively filters their labels through cross-channel agreement.

TBP conditions on $(D, \mathcal{S}_{\text{goal}})$ to synthesize categorized inputs that probe complementary behavioral regimes, including normal cases, boundary extremes, and adversarial traps. The purpose of TBP is not merely to increase the number of tests, but to increase their informativeness: by covering qualitatively different failure patterns, it amplifies behavioral differences among candidate programs and makes the surrogate environment more discriminative for selection.

Given a synthesized input x, DCV validates its label through two complementary channels. The synthesis channel produces

$$(x, y_{\text{gen}}) = \Phi_{\text{gen}}(D, \mathcal{S}_{\text{goal}}), \qquad (6)$$

while an independent shadow-solving channel predicts

$$y_{\text{shadow}} = \Phi_{\text{reason}}(D, \mathcal{S}_{\text{goal}}, x). \qquad (7)$$

We admit (x, y) into T_{synth} iff

$$(x, y) \in T_{\text{synth}} \iff y_{\text{gen}} \equiv y_{\text{shadow}}, \qquad (8)$$

where $\equiv$ denotes semantic equivalence under the output format. DCV is intentionally conservative: disagreement across the two channels leads to rejection rather than weak supervision. This PASS/REJECT gate prioritizes label precision over coverage, yielding a more stable surrogate environment for candidate ranking and the peer-success contrast mining used in Stage 3. Detailed statistics of TBP category composition and DCV acceptance/rejection rates are reported in Appendix A.4.

3.5 Selection and Lamarckian Adaptation

We evaluate the candidate population $\mathcal{P}$ on T_{synth} and retain the elite program p_{best}. Since non-elite candidates may still contain locally correct logic on

boundary regimes where the elite fails, EvoCoder performs repair only on peer-supported differential cases:

$$T_{\text{diff}} = \{ ((x, y), p') \in T_{\text{synth}} \times \mathcal{P} \mid \text{Exec}(p_{\text{best}}, x) \neq y,$$
$$\text{Exec}(p', x) = y \}. \qquad (9)$$

Each $((x, y), p') \in T_{\text{diff}}$ is a witness-backed contrast showing that the target behavior is achievable by at least one peer on the same input.

For each contrast $(x, p') \in T_{\text{diff}}$, Semantic Spectrum Analysis (SSA) identifies the earliest semantic divergence between the elite and the peer that explains the output mismatch on x. Let $\mathcal{B} = \{1, \ldots, 5\}$ denote an ordered set of semantic behavior bands, covering input interpretation, boundary handling, core state representation, state transitions, and output realization. For a program p and input x, let $\tau_b(p, x)$ denote the band-b semantic abstraction of its behavior. SSA locates the earliest output-determining divergence

$$b^\star = \min \left\{ b \in \mathcal{B} \mid \tau_b(p_{\text{best}}, x) \not\equiv_b \tau_b(p', x) \right\}, \qquad (10)$$

where $\equiv_b$ denotes band-specific semantic equivalence. It then produces a localized diagnosis

$$z = (b^\star, \iota, \ell, \mathcal{H}),$$

where ι is a minimal transferable fix intent, ℓ is the implicated logic region, and $\mathcal{H}$ is a small set of boundary conditions that the repair must satisfy.

Given z and its supporting contrast (x, p'), EvoCoder applies a constrained Lamarckian update

$$\hat{p} = \mathcal{U}(p_{\text{best}}, p', z),$$

where $\mathcal{U}$ preserves the elite's global algorithmic skeleton and revises only the diagnosed local logic using the peer as a behavioral reference. When multiple contrasts are available, EvoCoder applies such transfers greedily and accepts a patch only if it fixes the triggering contrast without degrading behaviors already covered by the current elite on T_{synth}. In this way, Stage 3 turns dispersed peer advantages into targeted repairs for boundary failures and mutually exclusive algorithmic hypotheses.

4 Experimental Setup

4.1 Datasets

We evaluate on eight benchmarks spanning basic program synthesis, contest-style coding, and LiveCodeBench. For basic synthesis, we use

HumanEval (164 problems) (Chen et al., 2021) and MBPP (397 problems) (Austin et al., 2021), along with stricter/extended variants HumanEval-ET (Dong et al., 2025), EvalPlus (Liu et al., 2023), and MBPP-ET (Dong et al., 2025). For more challenging contest-style settings, we use APPS (150 problems) (Hendrycks et al., 2021) and CodeContest (165 problems) (Li et al., 2022b), which cover multi-tier difficulty and algorithmic problems with sparse solutions. We also include LiveCodeBench v6 (175 problems) (Jain et al., 2024), a newer benchmark for algorithm selection and robustness on competitive coding tasks.

4.2 Baselines, Metric, and Implementation.

Baselines and metric. We compare EvoCoder against baselines ranging from standard prompting to agentic frameworks, including Direct, CoT (Wei et al., 2022), Self-Planning (Jiang et al., 2024), Analogical Reasoning (Yasunaga et al., 2023), and strong iterative/agent-based systems such as Reflexion (Shinn et al., 2023a), MapCoder (Islam et al., 2024), and CodeSim (Islam et al., 2025). We report Pass@1 (Chen et al., 2021), where a task is solved if one program passes the benchmark test suite.

Backbones and implementation. We test proprietary LLMs (ChatGPT (OpenAI, 2022), GPT4 (Achiam et al., 2023), GPT-4o (Hurst et al., 2024)) and open-source LLMs (Llama-3.1-8B/70B (Dubey et al., 2024), Qwen3-30B (Yang et al., 2025)). EvoCoder samples $M=12$ strategies, selects $K=5$ via k-DPP, and expresses each into one candidate program. We use up to 15 DCV-verified tests per task for selection and SSA-guided adaptation.

5 Main Results

5.1 Results on Proprietary Backbones

Basic Code Generation Table 1 shows that EvoCoder consistently achieves the strongest Pass@1 across foundational code-generation benchmarks, outperforming both prompting baselines and multi-agent systems on all three proprietary backbones.

Its advantage is especially clear on the extended test variants, where robustness beyond public examples matters most. On HumanEval-ET, EvoCoder exceeds the strongest baseline by 11.2–25.0 points across backbones, indicating fewer corner-case failures than trajectory-based refinement methods that can commit early to a flawed line of reasoning.

Figure 3: Pass@1 on APPS by difficulty level across methods; hatch patterns denote different backbones.

Similar, though smaller, gains on MBPP-ET further suggest that EvoCoder improves generalization under harder, distribution-shifted tests rather than only fitting standard benchmark cases.

Competitive Problem Solving We evaluate EvoCoder on contest-style benchmarks, including CodeContest, APPS, and LiveCodeBench v6 (Table 1), which emphasize algorithm selection and corner-case robustness. Across three proprietary LLM backbones, EvoCoder consistently achieves the highest Pass@1, outperforming strong agentic baselines.

The gains are substantial. On CodeContest, EvoCoder surpasses the strongest baseline by up to 15.7 absolute points, and on APPS by up to 29.3 points, highlighting the effectiveness of the evolutionary loop for robust algorithmic choices and boundary handling. Figure 3 breaks down APPS by difficulty (Introductory / Interview / Competition). While performance decreases with difficulty for all methods, EvoCoder's advantage is most pronounced on Introductory and Interview, and it remains among the top-performing methods even on Competition.

On LiveCodeBench, EvoCoder also achieves the highest Pass@1 on GPT-4 (49.14%) and GPT-4o (41.14%), improving over the strongest baseline by +16.57 points and +9.14 points, respectively. These results demonstrate that EvoCoder's gains generalize to a newer and more challenging benchmark beyond the previously tested competitive programming datasets.

ColBench. We observe a similar pattern on ColBench's single-turn Backend Programming track (Zhou et al., 2025), where EvoCoder also achieves the best overall performance under the same backbone; detailed results are deferred to Appendix A.2.

Model	Method	HumanEval	HumanEval-ET	EvalPlus	Avg HumanEval	MBPP	MBPP-ET	Avg MBPP	CodeContest	APPS	LiveCodeBench
ChatGPT	Direct	71.3%	64.6%	67.1%	67.7%	75.8%	52.6%	64.2%	5.5%	20.0%	10.29%
	CoT	70.7%	63.4%	68.3%	67.5%	78.3%	55.7%	67.0%	6.1%	20.0%	16.57%
	Self-Planning	70.7%	61.0%	62.8%	64.8%	73.8%	51.1%	62.5%	6.1%	20.7%	–
	Analogical	67.1%	59.1%	59.1%	61.8%	69.3%	46.9%	58.1%	7.3%	18.0%	–
	Reflexion	67.1%	49.4%	62.2%	59.6%	73.0%	47.4%	60.2%	–	–	–
	MapCoder	80.5%	70.1%	71.3%	74.0%	78.3%	54.4%	66.4%	12.7%	23.3%	21.14%
	CodeSim	86.0%	72.0%	73.2%	77.1%	86.4%	59.7%	73.1%	16.4%	26.7%	26.86%
	EvoCoder	97.0%	97.0%	80.5%	91.5%	90.7%	61.5%	76.1%	32.1%	56.0%	33.71%
GPT4	Direct	80.1%	73.8%	81.7%	78.5%	81.1%	54.7%	67.9%	12.1%	29.3%	22.29%
	CoT	89.0%	61.6%	82.3%	77.6%	82.4%	56.2%	69.3%	5.5%	30.0%	21.71%
	Self-Planning	85.4%	62.2%	79.3%	75.6%	75.8%	50.4%	63.1%	10.9%	34.7%	–
	Analogical	66.5%	48.8%	62.2%	59.2%	58.4%	40.3%	49.4%	10.9%	35.3%	–
	Reflexion	91.0%	78.7%	81.7%	83.8%	78.3%	51.9%	65.1%	–	–	–
	MapCoder	93.9%	82.9%	83.5%	86.8%	83.1%	57.7%	70.4%	28.5%	42.0%	32.57%
	CodeSim	94.5%	81.7%	84.8%	87.0%	89.7%	61.5%	75.6%	29.1%	46.0%	31.43%
	EvoCoder	97.6%	98.8%	92.1%	96.2%	91.4%	63.2%	77.3%	44.8%	57.3%	49.14%
GPT-4o	Direct	90.2%	81.1%	82.3%	84.5%	81.1%	55.9%	68.5%	13.9%	26.7%	13.14%
	CoT	90.9%	82.3%	87.2%	86.8%	82.9%	57.9%	70.4%	18.2%	26.7%	26.29%
	Self-Planning	89.0%	80.5%	84.1%	84.5%	82.6%	56.4%	69.5%	16.4%	28.0%	–
	Analogical	88.4%	80.5%	83.5%	84.1%	75.1%	50.9%	63.0%	5.5%	29.3%	–
	Reflexion	87.2%	81.1%	81.1%	83.1%	81.1%	56.7%	68.9%	–	–	–
	MapCoder	90.2%	80.5%	81.7%	84.1%	88.7%	59.2%	74.0%	29.7%	36.0%	29.71%
	CodeSim	95.1%	86.0%	87.2%	89.4%	90.7%	61.2%	76.0%	20.0%	40.7%	32.00%
	EvoCoder	98.2%	98.2%	90.2%	95.5%	93.7%	64.7%	79.2%	38.8%	50.0%	41.14%

Table 1: Pass@1 on basic code-generation benchmarks, contest-style benchmarks across three proprietary backbones.

5.2 Transferability to Open-Source LLMs

Table 2 reports results on three open-source LLMs over four aggregate metrics: Avg HumanEval, Avg MBPP, CodeContest, and APPS. EvoCoder consistently performs best across backbones and metrics, outperforming both prompting and strong agentic baselines. The gains are largest on harder settings (CodeContest/APPS), suggesting better robustness to long-horizon planning and corner cases. Performance is not monotonic in model size (e.g., Qwen3-30B often surpasses Llama3.1-70B), indicating that backbone characteristics beyond scale also matter. Full per-benchmark results are in Appendix A.3.

6 Ablation Studies and Analyses

6.1 Genotypic Variation and Expression

Table 3 shows that removing the Goal agent or genotypic Variation causes the largest degradation (especially on contest benchmarks), indicating that constraint anchoring and strategy-level exploration are crucial. For w/o Var, we replace strategy-level variation with code-level diversity by sampling multiple programs at temperature 1.0, but this is insufficient, suggesting diversity should be injected at the strategy level rather than only at the code level. Removing k-DPP yields a smaller but consistent drop, implying it mainly prevents strategy collapse and improves coverage.

Model	Method	Avg HumanEval	Avg MBPP	CodeContest	APPS
Llama-3.1-8B	Direct	39.8%	43.8%	7.9%	10.0%
	CoT	44.7%	56.3%	7.3%	11.3%
	Self-Planning	62.0%	54.5%	5.5%	9.3%
	Analogical	57.9%	44.5%	4.9%	9.3%
	Reflexion	35.0%	52.4%	–	–
	MapCoder	62.0%	54.4%	7.3%	12.7%
	CodeSim	68.8%	58.7%	8.5%	14.0%
	EvoCoder	76.0%	63.9%	10.9%	16.7%
Qwen3-30B	Direct	81.7%	61.6%	22.4%	34.0%
	CoT	85.2%	68.9%	18.8%	35.3%
	Self-Planning	86.6%	66.8%	24.2%	37.3%
	Analogical	78.7%	48.1%	16.4%	33.3%
	Reflexion	82.1%	69.9%	–	–
	MapCoder	83.7%	71.3%	25.5%	37.3%
	CodeSim	88.0%	72.7%	27.9%	38.7%
	EvoCoder	**92.5%**	**78.7%**	**31.5%**	**46.0%**
Llama-3.1-70B	Direct	53.4%	56.4%	25.5%	26.7%
	CoT	71.1%	65.4%	23.0%	27.3%
	Self-Planning	87.2%	64.4%	24.9%	30.0%
	Analogical	80.3%	62.2%	17.6%	30.7%
	Reflexion	57.7%	58.9%	–	–
	MapCoder	83.5%	68.5%	23.0%	28.7%
	CodeSim	77.2%	70.0%	26.1%	32.7%
	EvoCoder	89.3%	75.6%	30.3%	34.7%

Table 2: Pass@1 on open-source backbones.

6.2 Surrogate Feedback Environment

Table 4 indicates that both TBP and DCV contribute to performance. TBP synthesizes boundary- and trap-focused tests, making the surrogate environment more discriminative for constraint-sensitive failures than unconstrained test generation. DCV is the main driver of reliability: without the strict dual-channel consistency check, noisy surrogate signals can mis-rank candidates and misguide subsequent refinement. Overall, TBP improves coverage while DCV stabilizes feedback

Model	GPT-4o			
Benchmark	Avg HumanEval	Avg MBPP	CodeContest	APPS
EvoCoder	95.5%	79.2%	38.8%	50.0%
w/o Var	90.4%	71.2%	21.2%	35.3%
w/o k-DPP	92.7%	73.9%	31.5%	40.7%
w/o Goal	89.4%	72.8%	23.0%	36.0%

Table 3: Ablation of Genotypic Variation & Expression. Var: variation; k-DPP: k-determinantal point process; Goal: goal agent.

Model	GPT-4o			
Benchmark	Avg HumanEval	Avg MBPP	CodeContest	APPS
EvoCoder	95.5%	79.2%	38.8%	50.0%
w/o TBP	90.9%	74.8%	30.3%	37.3%
w/o DCV	87.0%	71.9%	21.8%	36.7%

Table 4: Ablations on surrogate feedback environment construction. TBP: targeted boundary probing; DCV: dual-channel verification.

Model	GPT-4o			
Benchmark	Avg HumanEval	Avg MBPP	CodeContest	APPS
EvoCoder	95.5%	79.2%	38.8%	50.0%
w/o Lam	88.8%	70.8%	21.8%	40.7%
w/o SSA	92.7%	75.6%	33.9%	44.0%

Table 5: Ablations on adaptive refinement. Lam: Lamarckian adaptation; SSA: semantic spectrum analysis.

Figure 4: 2D projection of the strategy pool, highlighting the K strategies selected by confidence Top-K versus k-DPP across four benchmarks.

quality, which together underpin the effectiveness of our surrogate feedback environment.

6.3 Selection & Lamarckian Adaptation

Table 5 ablates Selection & Lamarckian Adaptation to isolate the effects of Lamarckian adaptation (Lam) and Semantic Spectrum Analysis (SSA). Removing Lam reduces EvoCoder to selection-only and causes a large performance drop, particularly on contest benchmarks (CodeContest/APPS: 21.8%/40.7%), showing that simply selecting the best candidate is insufficient to fix structured errors. Removing SSA yields a smaller but consistent degradation (33.9%/44.0%), indicating that the gains mainly come from SSA-guided, targeted logic transfer rather than an unguided rewrite.

6.4 k-DPP Diversity Analysis

We evaluate whether k-DPP reduces semantic redundancy relative to confidence-only Top-K. For each dataset, we fix $M=20$, select $K=5$, and run on 20 sampled problems with a fixed seed. Strategies are embedded with Sentence-BERT and visualized in 2D (Figure 4). Top-K selections cluster in high-density regions, indicating near-duplicate templates, whereas k-DPP selects a more dispersed subset and improves coverage under the same candidate pool. We quantify redundancy by the mean pairwise cosine similarity collapse(S) and define

$$\text{gap} = \text{collapse}(\text{Top-}K) - \text{collapse}(k\text{-DPP}). \quad (11)$$

The gap is positive on all four benchmarks (0.085–0.092), confirming that k-DPP yields a less redundant initial strategy population; additional failure-mode analyses are in Appendix A.5.

6.5 Inference Cost

EvoCoder has low and stable inference cost: it uses 5.76 API calls and 8.33K tokens per instance on average, substantially lower than MapCoder/CodeSim (14.75/10.25 calls; 20.43K/16.52K tokens). This efficiency comes from batched inference in Stage 1/2 and conditional refinement in Stage 3, which adds only 1.76 calls on average. Thus, harder instances do not automatically incur more refinement calls. Detailed results are in Appendix A.6 (Table 15).

7 Conclusion

We presented EVOCODER, a population-based evolutionary framework for code generation under the oracle-gap. By coupling strategy-level exploration with verified surrogate feedback and targeted Lamarckian adaptation, EvoCoder enables robust search without access to hidden tests or external judging. Experiments on program synthesis and competitive programming benchmarks show consistent gains over strong baselines across both proprietary and open-source LLMs, with improved robustness under hidden tests.

Limitations

Our current study focuses on the setting of oracle-gap code generation, where functional correctness is the primary target and hidden tests are unavailable at inference time. While EvoCoder shows consistent gains in this setting, extending the framework to broader objectives such as efficiency, readability, and resource awareness remains an interesting direction for future work. In addition, although the surrogate feedback environment improves reliability in practice, it is still an approximation to the true hidden-test distribution. Finally, as with other structured inference-time frameworks, the observed gains can depend on the capability of the underlying LLM, and broader evaluation across model families is left to future work.

References

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, and 1 others. 2023. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*.

Jacob Austin, Augustus Odena, Maxwell Nye, Maarten Bosma, Henryk Michalewski, David Dohan, Ellen Jiang, Carrie Cai, Michael Terry, Quoc Le, and 1 others. 2021. Program synthesis with large language models. *arXiv preprint arXiv:2108.07732*.

Ayoub Belhadji, Rémi Bardenet, and Pierre Chainais. 2018. A determinantal point process for column subset selection. *Preprint*, arXiv:1812.09771.

Bei Chen, Fengji Zhang, Anh Nguyen, Daoguang Zan, Zeqi Lin, Jian-Guang Lou, and Weizhu Chen. 2023. Codet: Code generation with generated tests. In *The Eleventh International Conference on Learning Representations*.

Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, Alex Ray, Raul Puri, Gretchen Krueger, Michael Petrov, Heidy Khlaaf, Girish Sastry, Pamela Mishkin, Brooke Chan, Scott Gray, and 39 others. 2021. Evaluating large language models trained on code. *Preprint*, arXiv:2107.03374.

Yihong Dong, Jiazheng Ding, Xue Jiang, Ge Li, Zhuo Li, and Zhi Jin. 2025. Codescore: Evaluating code generation by learning code execution. *ACM Transactions on Software Engineering and Methodology*, 34(3):1–22.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, and 1 others. 2024. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*.

Daniel Fried, Armen Aghajanyan, Jessy Lin, Sida Wang, Eric Wallace, Freda Shi, Ruiqi Zhong, Scott Yih, Luke Zettlemoyer, and Mike Lewis. 2023. Incoder: A generative model for code infilling and synthesis. In *The Eleventh International Conference on Learning Representations*.

Daya Guo, Qihao Zhu, Dejian Yang, Zhenda Xie, Kai Dong, Wentao Zhang, Guanting Chen, Xiao Bi, Y. Wu, Y. K. Li, Fuli Luo, Yingfei Xiong, and Wenfeng Liang. 2024. Deepseek-coder: When the large language model meets programming – the rise of code intelligence. *Preprint*, arXiv:2401.14196.

Dan Hendrycks, Steven Basart, Saurav Kadavath, Mantas Mazeika, Akul Arora, Ethan Guo, Collin Burns, Samir Puranik, Horace He, Dawn Song, and 1 others. 2021. Measuring coding challenge competence with apps. *arXiv preprint arXiv:2105.09938*.

Binyuan Hui, Jian Yang, Zeyu Cui, Jiaxi Yang, Dayiheng Liu, Lei Zhang, Tianyu Liu, Jiajun Zhang, Bowen Yu, Keming Lu, Kai Dang, Yang Fan, Yichang Zhang, An Yang, Rui Men, Fei Huang, Bo Zheng, Yibo Miao, Shanghaoran Quan, and 5 others. 2024. Qwen2.5-coder technical report. *Preprint*, arXiv:2409.12186.

Aaron Hurst, Adam Lerer, Adam P Goucher, Adam Perelman, Aditya Ramesh, Aidan Clark, AJ Ostrow, Akila Welihinda, Alan Hayes, Alec Radford, and 1 others. 2024. Gpt-4o system card. *arXiv preprint arXiv:2410.21276*.

Md. Ashraful Islam, Mohammed Eunus Ali, and Md Rizwan Parvez. 2024. MapCoder: Multi-agent code generation for competitive problem solving. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 4912–4944, Bangkok, Thailand. Association for Computational Linguistics.

Md. Ashraful Islam, Mohammed Eunus Ali, and Md Rizwan Parvez. 2025. CodeSim: Multi-agent code generation and problem solving through simulation-driven planning and debugging. In *Findings of the Association for Computational Linguistics: NAACL 2025*, pages 5113–5139, Albuquerque, New Mexico. Association for Computational Linguistics.

Naman Jain, King Han, Alex Gu, Wen-Ding Li, Fanjia Yan, Tianjun Zhang, Sida Wang, Armando Solar-Lezama, Koushik Sen, and Ion Stoica. 2024. Livecodebench: Holistic and contamination free evaluation of large language models for code. *Preprint*, arXiv:2403.07974.

Xue Jiang, Yihong Dong, Lecheng Wang, Zheng Fang, Qiwei Shang, Ge Li, Zhi Jin, and Wenpin Jiao. 2024. Self-planning code generation with large language models. *ACM Transactions on Software Engineering and Methodology*, 33(7):1–30.

Kuang-Huei Lee, Ian Fischer, Yueh-Hua Wu, Dave Marwood, Shumeet Baluja, Dale Schuurmans, and Xinyun Chen. 2025. Evolving deeper llm thinking. *Preprint*, arXiv:2501.09891.

Kyla H. Levin, Nicolas van Kempen, Emery D. Berger, and Stephen N. Freund. 2025. Chatdbg: Augmenting debugging with large language models. *Proc. ACM Softw. Eng.*, 2(FSE).

Jierui Li, Hung Le, Yingbo Zhou, Caiming Xiong, Silvio Savarese, and Doyen Sahoo. 2024. Codetree: Agent-guided tree search for code generation with large language models. *Preprint*, arXiv:2411.04329.

Raymond Li, Loubna Ben allal, Yangtian Zi, Niklas Muennighoff, Denis Kocetkov, Chenghao Mou, Marc Marone, Christopher Akiki, Jia LI, Jenny Chim, Qian Liu, Evgenii Zheltonozhskii, Terry Yue Zhuo, Thomas Wang, Olivier Dehaene, Joel Lamy-Poirier, Joao Monteiro, Nicolas Gontier, Ming-Ho Yee, and 39 others. 2023. Starcoder: may the source be with you! *Transactions on Machine Learning Research*. Reproducibility Certification.

Yujia Li, David Choi, Junyoung Chung, Nate Kushman, Julian Schrittwieser, Rémi Leblond, Tom Eccles, James Keeling, Felix Gimeno, Agustin Dal Lago, Thomas Hubert, Peter Choy, Cyprien de Masson d'Autume, Igor Babuschkin, Xinyun Chen, Po-Sen Huang, Johannes Welbl, Sven Gowal, Alexey Cherepanov, and 7 others. 2022a. Competition-level code generation with alphacode. *Science*, 378(6624):1092–1097.

Yujia Li, David Choi, Junyoung Chung, Nate Kushman, Julian Schrittwieser, Rémi Leblond, Tom Eccles, James Keeling, Felix Gimeno, Agustin Dal Lago, Thomas Hubert, Peter Choy, Cyprien de Masson d'Autume, Igor Babuschkin, Xinyun Chen, Po-Sen Huang, Johannes Welbl, Sven Gowal, Alexey Cherepanov, and 7 others. 2022b. Competition-level code generation with alphacode. *Science*, 378(6624):1092–1097.

Jonathan Light, Yue Wu, Yiyou Sun, Wenchao Yu, Yanchi liu, Xujiang Zhao, Ziniu Hu, Haifeng Chen, and Wei Cheng. 2025. Scattered forest search: Smarter code space exploration with llms. *Preprint*, arXiv:2411.05010.

Jiawei Liu, Chunqiu Steven Xia, Yuyao Wang, and Lingming Zhang. 2023. Is your code generated by chatgpt really correct? rigorous evaluation of large language models for code generation. In *Proceedings of the 37th International Conference on Neural Information Processing Systems*, NIPS '23, Red Hook, NY, USA. Curran Associates Inc.

Paul Liu, Akshay Soni, Eun Yong Kang, Yajun Wang, and Mehul Parsana. 2021. Diversity on the go! streaming determinantal point processes under a maximum induced cardinality objective. In *Proceedings of the Web Conference 2021*, WWW '21, page 1363–1372, New York, NY, USA. Association for Computing Machinery.

Erik Nijkamp, Bo Pang, Hiroaki Hayashi, Lifu Tu, Huan Wang, Yingbo Zhou, Silvio Savarese, and Caiming Xiong. 2023. Codegen: An open large language model for code with multi-turn program synthesis. In *The Eleventh International Conference on Learning Representations*.

Alexander Novikov, Ngân Vũ, Marvin Eisenberger, Emilien Dupont, Po-Sen Huang, Adam Zsolt Wagner, Sergey Shirobokov, Borislav Kozlovskii, Francisco J. R. Ruiz, Abbas Mehrabian, M. Pawan Kumar, Abigail See, Swarat Chaudhuri, George Holland, Alex Davies, Sebastian Nowozin, Pushmeet Kohli, and Matej Balog. 2025. Alphaevolve: A coding agent for scientific and algorithmic discovery. *Preprint*, arXiv:2506.13131.

OpenAI. 2022. Introducing ChatGPT. https://openai.com/index/chatgpt/. Accessed: 2026-01-04.

Bernardino Romera-Paredes, Mohammadamin Barekatain, Alexander Novikov, Matej Balog, M. Pawan Kumar, Emilien Dupont, Francisco J. R. Ruiz, Jordan S. Ellenberg, Pengming Wang, Omar Fawzi, Pushmeet Kohli, and Alhussein Fawzi. 2024. Mathematical discoveries from program search with large language models. *Nature*, 625(7995):468–475.

Baptiste Rozière, Jonas Gehring, Fabian Gloeckle, Sten Sootla, Itai Gat, Xiaoqing Ellen Tan, Yossi Adi, Jingyu Liu, Romain Sauvestre, Tal Remez, Jérémy Rapin, Artyom Kozhevnikov, Ivan Evtimov, Joanna Bitton, Manish Bhatt, Cristian Canton Ferrer, Aaron Grattafiori, Wenhan Xiong, Alexandre Défossez, and 7 others. 2024. Code llama: Open foundation models for code. *Preprint*, arXiv:2308.12950.

Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. 2023a. Reflexion: Language agents with verbal reinforcement learning. *Advances in Neural Information Processing Systems*, 36:8634–8652.

Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik R Narasimhan, and Shunyu Yao. 2023b. Reflexion: language agents with verbal reinforcement learning. In *Thirty-seventh Conference on Neural Information Processing Systems*.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, brian ichter, Fei Xia, Ed H. Chi, Quoc V Le, and Denny Zhou. 2022. Chain of thought prompting elicits reasoning in large language models. In *Advances in Neural Information Processing Systems*.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, and 1 others. 2025. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*.

Shunyu Yao, Dian Yu, Jeffrey Zhao, Izhak Shafran, Thomas L. Griffiths, Yuan Cao, and Karthik R Narasimhan. 2023. Tree of thoughts: Deliberate problem solving with large language models. In *Thirty-seventh Conference on Neural Information Processing Systems*.

Michihiro Yasunaga, Xinyun Chen, Yujia Li, Panupong Pasupat, Jure Leskovec, Percy Liang, Ed H Chi, and Denny Zhou. 2023. Large language models as analogical reasoners. *arXiv preprint arXiv:2310.01714.*

Li Zhong, Zilong Wang, and Jingbo Shang. 2024. Debug like a human: A large language model debugger via verifying runtime execution step-by-step. *Preprint*, arXiv:2402.16906.

Yifei Zhou, Song Jiang, Yuandong Tian, Jason Weston, Sergey Levine, Sainbayar Sukhbaatar, and Xian Li. 2025. Sweet-rl: Training multi-turn llm agents on collaborative reasoning tasks. *Preprint*, arXiv:2503.15478.

A Appendix

A.1 Sensitivity Analysis of M and K

Table 6 varies the strategy pool size M and the selected strategy count K (via k-DPP) for EVOCODER under GPT-4o, reporting Pass@1 on HumanEval, MBPP, CodeContest, and APPS. Increasing M or K from smaller values generally improves performance, while results largely saturate around the default setting ($M=12$, $K=5$) with only minor benchmark-specific fluctuations thereafter; given the extra inference cost of larger pools, we adopt $M=12$ and $K=5$ as a cost-effective default.

A.2 Results on ColBench

ColBench evaluates real-world collaborative programming with hidden unit tests, providing a realistic robustness check beyond standard benchmarks.(Zhou et al., 2025) We evaluate EvoCoder on the single-turn Backend Programming track and report *Tests Passed* and *Success Rate* following the official protocol. As shown in Table 7, EvoCoder achieves the best overall performance among all compared methods, indicating that our population-based generation–selection mechanism improves robustness to hidden tests on practical backend programming tasks even under the same backbone.

A.3 Full Results for Open-Source LLMs

Table 8 expands Table 2 with a per-benchmark Pass@1 breakdown on open-source LLMs, including HumanEval, HumanEval-ET, EvalPlus, MBPP, MBPP-ET, and the contest benchmarks CodeContest and APPS (in addition to Avg HumanEval and Avg MBPP). Overall, EVOCODER achieves the best performance across all three open-source LLMs and metrics, with particularly strong gains on stricter or distribution-shifted evaluations

Figure 5: Normalized failure mode profiles across benchmarks (each axis is normalized by the maximum count among methods). WA: wrong answer; RE: runtime error; CE: compilation error; TLE: time limit exceeded; MLE: memory limit exceeded.

(HumanEval-ET, EvalPlus, MBPP-ET), and consistent improvements on long-horizon contest settings (CodeContest and APPS), indicating robust benefits beyond single-trajectory prompting baselines.

A.4 Transparency of Surrogate Feedback Construction

To better characterize the surrogate feedback environment, we report two transparency analyses. Table 9 summarizes the composition of TBP-generated tests among the DCV-verified examples, including the proportion of normal, edge, and tricky cases. Table 10 reports DCV filtering statistics, including acceptance rate, rejection due to cross-channel mismatch, and rejection due to unknown or invalid shadow predictions. These statistics clarify that TBP primarily improves test diversity and informativeness, while DCV primarily improves label precision through conservative filtering.

A.5 Failure-Mode Analysis and Raw Counts

Figure 5 summarizes normalized failure profiles aggregated over three backbones for five methods (Direct, CoT, MapCoder, CodeSim, and EvoCoder). We report WA/CE/RE/TLE for HumanEval/MBPP and additionally include MLE for APPS/CodeContest; each axis is normalized by the maximum count of that error type. Overall, EvoCoder exhibits the most contracted profiles across benchmarks, indicating broader error reduc-

Setting (GPT-4o)	M	K	HumanEval	MBPP	CodeContest	APPS	LiveCodeBench
Varying M (fix $K=5$)							
	8	5	95.7%	91.2%	35.2%	44.0%	37.7%
	10	5	97.0%	92.4%	36.4%	46.7%	38.9%
(default)	12	5	**98.2%**	**93.7%**	**38.8%**	**50.0%**	**41.1%**
	16	5	98.2%	94.0%	39.4%	49.3%	41.7%
	20	5	98.2%	93.7%	38.8%	50.7%	42.9%
Varying K (fix $M=12$)							
	12	3	95.7%	92.4%	34.5%	45.3%	38.9%
	12	4	97.0%	92.4%	36.4%	46.0%	39.4%
(default)	12	5	**98.2%**	**93.7%**	**38.8%**	**50.0%**	**41.1%**
	12	7	98.2%	93.7%	39.4%	49.3%	41.1%
	12	9	98.2%	94.0%	38.8%	48.0%	41.1%

Table 6: Sensitivity to M and K on GPT-4o (Pass@1). Performance improves with larger M and K but quickly saturates around $M=12, K=5$, which we choose as the default for efficiency.

Method	% Tests Passed	% Success Rate
Direct	27.6	16.2
CoT	28.3	16.6
MapCoder	30.1	17.2
CodeSim	31.8	19.3
EvoCoder	**34.4**	**22.5**

Table 7: ColBench (single-turn, GPT-4o): Tests Passed (avg. % unit tests passed) and Success Rate (% tasks passing all unit tests).

tions rather than improvements in a single category. The contraction is most evident on WA and RE, suggesting fewer logic and runtime failures. On APPS and CodeContest, where WA dominates, EvoCoder lowers WA without noticeably increasing TLE/MLE, implying improved corner-case correctness rather than trading efficiency for accuracy.

Tables 11–14 report the raw outcome counts underlying the failure-mode profiles in Figure 5 across backbones and methods, with each solution assigned to exactly one mutually exclusive category (Passed, WA, RE, TLE, CE, and MLE for APPS/CodeContest). Figure 5 is computed by normalizing each error-type axis by the maximum count of that error type among compared methods on the same benchmark, highlighting relative contraction/expansion patterns rather than absolute scale. Overall, the raw counts align with the main-text analysis: on HumanEval/MBPP, EVOCODER mainly reduces WA and RE and increases Passed without inflating TLE/CE, while on APPS/CodeContest it improves the number of solved instances with TLE/MLE remaining com-

parable, suggesting gains from better corner-case correctness rather than trading efficiency for accuracy.

A.6 Full Efficiency Results

Table 15 reports the average number of API calls and token consumption across datasets and LLM backbones. Across all settings, EvoCoder consistently uses fewer API calls than MapCoder and CodeSim, and also reduces token usage compared to these agentic baselines, which often incur longer multi-turn planning/debugging trajectories. Notably, EvoCoder's call count remains tightly concentrated around 5–6 across benchmarks, supporting our claim that inference cost is stable and does not systematically increase with task difficulty. A key reason is that several stages are executed in batched array form rather than as separate per-candidate interactions: Stage 1 generates and evaluates multiple strategies in parallel, and Stage 2 similarly batches test construction and verification over candidate sets. As a result, EvoCoder amortizes coordination overhead across the population, so the number of API calls stays low even when maintaining multiple competing hypotheses. This stability is by design: Stage 1/2 operate under fixed budgets, while Stage 3 is conditional and only applies to a subset of candidates, so harder instances do not automatically trigger proportional increases in refinement calls.

A.7 Prompts

Figures 6–12 provide the exact prompts for all EvoCoder agents, aligned with the three-stage loop in the main text.

Model	Method	HumanEval	HumanEval-ET	EvalPlus	Avg HumanEval	MBPP	MBPP-ET	Avg MBPP	CodeContest	APPS
Llama-3.1-8B	Direct	42.1%	38.4%	39.0%	39.8%	52.4%	35.3%	43.8%	7.9%	10.0%
	CoT	48.8%	42.1%	43.3%	44.7%	66.5%	46.1%	56.3%	7.3%	11.3%
	Self-Planning	65.2%	65.2%	55.5%	62.0%	64.7%	44.3%	54.5%	5.5%	9.3%
	Analogical	59.8%	59.2%	54.9%	57.9%	52.4%	36.5%	44.5%	4.9%	9.3%
	Reflexion	43.9%	31.1%	29.9%	35.0%	62.0%	42.8%	52.4%	–	–
	MapCoder	73.2%	56.1%	56.7%	62.0%	63.2%	45.6%	54.4%	7.3%	12.7%
	CodeSim	79.9%	65.2%	61.2%	68.8%	69.3%	48.1%	58.7%	8.5%	14.0%
	EvoCoder	84.0%	83.5%	60.4%	76.0%	74.8%	52.9%	63.9%	10.9%	16.7%
Qwen3-30B	Direct	84.8%	82.3%	78.1%	81.7%	71.8%	51.4%	61.6%	22.4%	34.0%
	CoT	86.6%	85.4%	83.5%	85.2%	77.8%	60.0%	68.9%	18.8%	35.3%
	Self-Planning	89.0%	86.6%	84.2%	86.6%	76.6%	56.9%	66.8%	24.2%	37.3%
	Analogical	79.9%	79.9%	76.2%	78.7%	56.4%	39.8%	48.1%	16.4%	33.3%
	Reflexion	84.8%	81.7%	79.9%	82.1%	78.1%	61.7%	69.9%	–	–
	MapCoder	85.4%	85.4%	80.5%	83.7%	79.6%	63.0%	71.3%	25.5%	37.3%
	CodeSim	89.6%	88.4%	86.0%	88.0%	81.1%	64.2%	72.7%	27.9%	38.7%
	EvoCoder	**95.7%**	**95.7%**	**86.0%**	**92.5%**	**86.9%**	**70.5%**	**78.7%**	**31.5%**	**46.0%**
Llama-3.1-70B	Direct	57.3%	50.6%	52.4%	53.4%	67.5%	45.3%	56.4%	25.5%	26.7%
	CoT	75.6%	67.7%	70.1%	71.1%	77.3%	53.4%	65.4%	23.0%	27.3%
	Self-Planning	90.9%	90.9%	79.9%	87.2%	75.8%	52.9%	64.4%	24.9%	30.0%
	Analogical	82.3%	82.3%	76.2%	80.3%	73.6%	50.9%	62.2%	17.6%	30.7%
	Reflexion	73.8%	31.1%	68.3%	57.7%	70.0%	47.9%	58.9%	–	–
	MapCoder	87.2%	86.0%	77.4%	83.5%	80.1%	56.9%	68.5%	23.0%	28.7%
	CodeSim	90.2%	65.2%	76.2%	77.2%	81.6%	58.4%	70.0%	26.1%	32.7%
	EvoCoder	94.0%	94.5%	79.3%	89.3%	84.4%	66.8%	75.6%	30.3%	34.7%

Table 8: Full Pass@1 results on open-source LLMs. We report HumanEval/HumanEval-ET/EvalPlus, MBPP/MBPP-ET, their averages, and contest benchmarks (CodeContest, APPS).

Benchmark	Normal	Edge	Tricky
HumanEval	70.5	19.8	9.7
EvalPlus	64.3	25.7	10.0
MBPP	67.2	21.9	10.9
MBPP-ET	59.6	25.4	15.0
APPS	50.8	30.1	19.1
CodeContest	45.2	30.3	24.5
LiveCodeBench	42.7	34.6	22.7

Table 9: TBP test composition among DCV-verified examples. Values under Normal, Edge, and Tricky are proportions (%).

Benchmark	Accept	Mismatch	Unknown
HumanEval	85.2	10.3	4.5
EvalPlus	82.7	12.1	5.2
MBPP	79.8	15.3	4.9
MBPP-ET	74.6	18.2	7.2
APPS	69.5	20.8	9.7
CodeContest	64.3	22.5	13.2
LiveCodeBench	61.7	24.1	14.2

Table 10: DCV filtering statistics. Accept, Mismatch, and Unknown denote the proportions (%) of examples that are accepted, rejected due to cross-channel mismatch, and rejected due to unknown or invalid shadow predictions, respectively.

Stage 1: Goal compresses D into a constraint-focused anchor S_{goal} (Figure 6); Variation generates diverse strategy prompts (genotypes) in JSON (Figure 7); Coder expresses a selected strategy into an executable Python 3 solution (phenotype) under strict I/O constraints (Figure 8).

Stage 2: TBP synthesizes boundary/trap-focused categorized asserts (Figure 9); DCV uses Shadow Prediction to infer expected outputs from (D, S_{goal}) and filters inconsistent tests (Figure 10).

Stage 3: SSA derives a transferable `fix_intent` from elite–peer differential cases (Figure 11); Lamarckian Adaptation applies it for targeted logic transfer while preserving overall structure (Figure 12).

A.8 Case Study

Figures 13–17 provide an end-to-end trace of a representative example. Figure 13 shows the problem, extracted goal, and strategy; Figure 14 presents candidates (elite and peers); Figure 15 summarizes the surrogate tests and pass/fail outcomes for selection and contrast mining; Figure 16 reports the SSA diagnosis and fix intent; and Figure 17 shows the Lamarckian repair as a minimal patch to the elite.

Model	Method	Total	Passed	Wrong Answer	Runtime Error	Time Limit Exceeded	Compilation Error
ChatGPT	Direct	164	117	19	24	0	4
	CoT	164	116	20	23	0	5
	Self-Planning	164	116	22	21	1	4
	Analogical	164	110	27	23	2	2
	Reflexion	164	110	30	20	0	4
	MapCoder	164	132	13	18	0	1
	CodeSim	164	141	9	13	0	1
	EvoCoder	164	159	5	0	0	0
GPT4	Direct	164	132	25	7	0	0
	CoT	164	146	13	5	0	0
	Self-Planning	164	140	17	6	1	0
	Analogical	164	109	17	4	0	34
	Reflexion	164	149	10	4	0	1
	MapCoder	164	154	9	1	0	0
	CodeSim	164	155	9	0	0	0
	EvoCoder	164	160	4	0	0	0
GPT-4o	Direct	164	148	13	2	1	0
	CoT	164	149	12	3	0	0
	Self-Planning	164	146	11	6	1	0
	Analogical	164	145	12	4	0	3
	Reflexion	164	143	15	4	0	2
	MapCoder	164	148	12	3	1	0
	CodeSim	164	156	6	2	0	0
	EvoCoder	164	161	2	1	0	0

Table 11: Raw failure-mode counts on HumanEval across three LLMs(ChatGPT, GPT4, GPT-4o).

Model	Method	Total	Passed	Wrong Answer	Runtime Error	Time Limit Exceeded	Compilation Error
ChatGPT	Direct	397	301	55	38	2	1
	CoT	397	311	51	32	2	1
	Self-Planning	397	293	61	39	2	2
	Analogical	397	275	67	47	2	6
	Reflexion	397	290	51	53	1	2
	MapCoder	397	311	45	38	2	1
	CodeSim	397	343	41	11	1	1
	EvoCoder	397	360	37	0	0	0
GPT4	Direct	397	322	51	24	0	0
	CoT	397	327	48	22	0	0
	Self-Planning	397	301	59	36	1	0
	Analogical	397	232	105	56	0	4
	Reflexion	397	311	82	3	1	0
	MapCoder	397	330	57	10	0	0
	CodeSim	397	356	40	0	1	0
	EvoCoder	397	363	33	0	1	0
GPT-4o	Direct	397	322	55	20	0	0
	CoT	397	329	64	3	1	0
	Self-Planning	397	328	60	9	0	0
	Analogical	397	298	63	35	1	0
	Reflexion	397	322	68	7	0	0
	MapCoder	397	352	44	0	1	0
	CodeSim	397	360	32	5	0	0
	EvoCoder	397	372	24	0	1	0

Table 12: Raw failure-mode counts on MBPP across three LLMs(ChatGPT, GPT4, GPT-4o).

Model	Method	Total	Passed	Wrong Answer	Runtime Error	Time Limit Exceeded	Compilation Error	Memory Limit Exceeded
ChatGPT	Direct	150	30	95	18	6	0	1
	CoT	150	31	94	13	7	5	0
	Self-Planning	150	31	99	12	8	0	0
	Analogical	150	27	98	17	6	1	1
	MapCoder	150	35	83	22	9	0	1
	CodeSim	150	40	81	20	8	1	0
	EvoCoder	150	84	50	8	7	0	1
GPT4	Direct	150	44	67	27	12	0	0
	CoT	150	45	69	25	11	0	0
	Self-Planning	150	52	62	30	5	1	0
	Analogical	150	53	68	21	7	1	0
	MapCoder	150	63	62	19	4	1	1
	CodeSim	150	69	58	17	4	1	1
	EvoCoder	150	86	50	7	6	1	0
GPT-4o	Direct	150	40	89	11	9	0	1
	CoT	150	40	82	17	10	0	1
	Self-Planning	150	42	86	13	8	0	1
	Analogical	150	44	83	15	7	0	1
	MapCoder	150	54	88	6	2	0	0
	CodeSim	150	61	66	13	10	0	0
	EvoCoder	150	75	61	6	8	0	0

Table 13: Raw failure-mode counts on APPS across three LLMs(ChatGPT, GPT4, GPT-4o).

Model	Method	Total	Passed	Wrong Answer	Runtime Error	Time Limit Exceeded	Compilation Error	Memory Limit Exceeded
ChatGPT	Direct	165	9	134	15	5	2	0
	CoT	165	10	131	22	2	0	0
	Self-Planning	165	10	128	23	4	0	0
	Analogical	165	12	124	24	3	1	1
	MapCoder	165	21	122	14	4	1	3
	CodeSim	165	27	121	11	4	1	1
	EvoCoder	165	53	98	11	3	0	0
GPT4	Direct	165	20	126	13	5	0	1
	CoT	165	9	66	86	2	1	1
	Self-Planning	165	18	131	14	2	0	0
	Analogical	165	18	130	13	2	2	0
	MapCoder	165	47	102	10	5	0	1
	CodeSim	165	48	100	11	4	0	2
	EvoCoder	165	74	77	8	5	0	1
GPT-4o	Direct	165	23	130	4	7	0	1
	CoT	165	30	119	10	6	0	0
	Self-Planning	165	27	126	4	7	0	1
	Analogical	165	9	147	5	3	0	1
	MapCoder	165	49	106	4	5	0	1
	CodeSim	165	33	116	9	4	1	2
	EvoCoder	165	64	92	4	3	0	2

Table 14: Raw failure-mode counts on CodeContest across three LLMs(ChatGPT, GPT4, GPT-4o).

LLM	Dataset	Average API Calls			Average Token Consumption (K)		
		EvoCoder	MapCoder	CodeSim	**EvoCoder**	MapCoder	CodeSim
ChatGPT	HumanEval	**6.1**	17	7	**5.64**	10.41	5.48
	MBPP	**5.8**	12	6	**5.89**	4.84	4.24
	APPS	**5.4**	21	15	**8.14**	26.57	19.20
	CodeContest	**5.5**	12	16	**10.78**	34.95	24.02
GPT4	HumanEval	**5.8**	15	5	**5.26**	12.75	5.15
	MBPP	**5.6**	8	5	**5.45**	4.96	5.21
	APPS	**5.6**	19	13	**9.83**	31.80	23.18
	CodeContest	**5.7**	19	17	**11.78**	38.70	41.66
GPT-4o	HumanEval	**6.0**	9	4	**5.53**	6.63	3.84
	MBPP	**5.9**	9	5	**6.10**	6.10	4.43
	APPS	**5.9**	19	14	**11.87**	30.60	22.18
	CodeContest	**5.8**	17	16	**13.64**	36.80	39.70
Average		**5.76**	14.75	10.25	**8.33**	20.43	16.52

Table 15: Average API calls and token consumption (K) across datasets and LLMs.

Goal Agent

You are the Goal Agent in the EvoCoder framework.

Your job is to distill the problem description D into a compact semantic anchor S_goal that preserves ONLY:
- the task objective,
- hard constraints,
- required input-output relationship,
- critical edge cases explicitly stated or strongly implied.

Rules:
- Do NOT mention implementation details, algorithms, data structures, or coding style.
- Do NOT copy the original text verbatim; paraphrase into a crisp specification.
- S_goal must be self-contained and unambiguous.
- Output ONLY S_goal (no headings, no bullets, no extra text).
- Keep it within 1–3 clear English sentences.

Problem description D:

{problem_description}

Produce S_goal: a compact natural-language semantic anchor capturing only the objective and hard constraints.
Return ONLY S_goal in 1–3 English sentences.

Figure 6: Prompt for Goal Agent.

Genotypic Variation Agent

You are the Genotypic Variation Agent in the EvoCoder framework.

Input:
- A programming problem description
- A compact task goal (objective and hard constraints)

Task:
Generate a pool of diverse strategy prompts for solving the SAME task.
All strategies must preserve the same goal and constraints, while maximizing coverage and minimizing redundancy.

Rules:
1) Semantic consistency
- Do not change the goal, constraints, or input/output mode.
- Do not invent assumptions not supported by the problem/goal.

2) No code
- Do not output code, pseudocode, variable names, or library calls.

3) Diversity requirement (avoid semantic collapse)
- Strategies must differ in core reasoning path, not just wording.
- Each strategy must make a DIFFERENT primary choice in at least one of these:
  (a) problem representation (how you model the input and what you treat as the main objects),
  (b) decomposition (which subproblem you solve first and what intermediate quantities you compute),
  (c) main technique (the overarching approach you would rely on),
  (d) constraint focus (which corner cases or limits drive the design).
- Anti-duplicate rule: if two strategies share the same main technique and representation, they are duplicates.
  Rewrite one so that a coder would likely write a different code structure.

Problem description:

{problem_description}

Task goal:

{goal}

Generate {n_strategys} diverse strategy prompts for the same task.
Return ONLY the JSON array.

Output (STRICT):
Return ONLY valid JSON array:
```
[
  {"id": 0, "prompt": "..."},
  {"id": 1, "prompt": "..."},
  ...
]
```

Figure 7: Prompt for Genotypic Variation Agent.

Coder Agent

You are the Coder Agent in the EvoCoder framework.

You will receive:
- A natural-language Strategy (a candidate reasoning path to follow).
- A Task Goal (a compact semantic anchor that defines the required input-output behavior).
- The full Problem Description (may include signature, examples, and constraints).

Your job:
Generate a correct, executable Python 3 solution.

Alignment rules:
- Treat the Task Goal and Problem Description as non-negotiable constraints.
- Treat the Strategy as an explicit guidance path: follow it faithfully to preserve diversity,
  but if any part conflicts with the goal/description, prioritize correctness (goal/description) over the strategy.
- Do NOT output explanations, reasoning, markdown outside the code block, or multiple code blocks.
- Use only Python standard library.
- If a function signature is specified, implement exactly that function.
- Do not print debug logs.

Strategy (follow as the intended reasoning path):

{strategy}

Task Goal (must satisfy; hard constraints):

{goal}

Problem Description (must satisfy; hard constraints):

{problem_description}

Output rules (strict):
- Output ONLY one Python code block in exactly this format:
```python
 
```

Figure 8: Prompt for Coder Agent.

Targeted Boundary Probing Test Synthesis Agent

You are a Targeted Boundary Probing (TBP) test synthesis agent in the EvoCoder framework.

Input:
- Problem description
- Task goal (objective and hard constraints)

Task:
Create test cases that focus on boundary regimes and adversarial traps which are likely to expose behavioral differences
between candidate solutions. Each test must be fully determined from the goal and constraints.

Rules:
- Do NOT assume implementation details.
- Do NOT invent extra constraints beyond the description/goal.
- Derive expected outputs by reasoning from the goal; if an expected output cannot be determined confidently, do NOT include that test.
- Prefer boundary/trap-focused cases over random cases (e.g., off-by-one, empty/minimal, maximal, duplicates/ties, degenerate structure, tricky formatting).
- Output ONLY valid JSON. No explanations.

Notes:
- Use the function name exactly as specified in the signature (if provided).
- For float outputs, use epsilon comparison: abs(func(...) - expected) < 1e-6.
- For boolean outputs, use: assert func(...) is True/False.

Generate {n_tests} TBP-focused test cases for the following task.

Problem description:

{problem_description}

Task goal:

{goal}

Output schema:
Return a JSON array. Each item:
{
  "id": int,
  "category": "normal" | "boundary" | "trap",
  "assert": "a valid Python assert statement calling the target function",
  "input_summary": "brief description of what makes this case boundary/trap (one short phrase)"
}

Figure 9: Prompt for Targeted Boundary Probing Test Synthesis Agent.

Dual-Channel Verification Shadow Prediction Agent

You are the Dual-Channel Verification (DCV) Shadow Prediction Agent in the EvoCoder framework.

Input:
- A programming problem description
- A natural-language task goal (objective and hard constraints)
- One test input (the function call input)

Task:
Compute the correct output for this input strictly according to the task goal and required output format.
This is an independent shadow solution. You will NOT be given any expected output.

Rules:
- Use only the problem description and task goal.
- Do NOT guess. If the output cannot be determined with high confidence from the given information or the output format is ambiguous,
  return status="unknown" with shadow_output=null.
- Otherwise return status="ok" with the correct shadow_output.
- Keep the output consistent with the required output format (e.g., int, float, string, list, tuple, dict).

Problem description:

{problem_description}

Task goal:

{goal}

Test input to solve (function call only; no expected output is provided):

{test_input}

OUTPUT RULE (strict):
Return ONLY a single JSON object. No markdown. No extra text.
Schema:
{
  "status": "ok" | "unknown",
  "shadow_output": <value or null>
}
Constraints:
- If status is "ok", shadow_output must be the fully determined correct output under the required output format.
- If status is "unknown", shadow_output must be null.
- Do NOT include any additional fields.

Figure 10: Prompt for Dual-Channel Verification Shadow Prediction Agent.

Semantic Spectrum Analysis Agent

You are the Semantic Spectrum Analysis (SSA) Agent in the EvoCoder framework.

You will be given:
- The programming problem description and the task goal (ground truth requirements).
- One failing test case (input + expected output).
- An elite program that fails this case.
- A peer program that passes the same case.

Mission:
Perform "semantic spectrum analysis": compare elite vs peer by scanning through semantic behavior bands,
then isolate the earliest minimal divergence that explains the failure, and distill it into a transferable fix intent.

Semantic behavior bands (scan in this order):
Band 1: Input/format interpretation (what the inputs mean, parsing, empty/degenerate inputs)
Band 2: Boundary conditions (off-by-one, minimal/maximal, ties/duplicates, special values, impossible cases)
Band 3: Core state representation (what is tracked as state; key invariant the method relies on)
Band 4: State transitions (update rules inside loops/branches; when and how state changes)
Band 5: Termination and output formatting (return/print rules, rounding/ordering, final selection)

How to apply SSA (internal procedure):
1) For the given input, reason what the elite would do and where it deviates from the task goal.
2) For the same input, reason what the peer does that matches the expected output.
3) Scan the bands from 1 to 5 and find the FIRST band where the elite and peer logically diverge
   in a way that affects the output on this case.
4) Localize the divergence to a minimal logical unit:
   - a missing case distinction, an incorrect boundary check, a violated invariant, or a wrong state update.
5) Distill a syntax-agnostic, transferable fix intent:
   - describe what condition/transition must change, without referring to code structure or variable names.
   - keep it minimal and compatible with preserving the elite's overall approach.

Problem description:

{problem_description}

Task goal:

{goal}

Failing case:
- input:

{test_input}

- expected output:

{expected_output}

Elite program (fails this case):

{elite_code}

Peer program (passes the same case):

{peer_code}

OUTPUT RULE (strict):
Return ONLY a single JSON object. No markdown. No extra text.

Schema:
{
  "summary": "<one sentence: what goes wrong and what peer does differently>",
  "fix_intent": "<implementation-agnostic correction intent, 1–3 sentences>",
  "target_location": "<brief hint: which logic band to change>",
  "must_handle": ["<boundary/special condition 1>", "<condition 2>", "..."]
}

Figure 11: Prompt for Semantic Spectrum Analysis Agent.

Lamarckian Adaptation Agent

You are the Lamarckian Adaptation Agent in the EvoCoder framework.

You will be given:
- The problem description and task goal (these are immutable requirements).
- The current elite program (the best program so far, but it fails some cases).
- A peer program that succeeds on the elite's failing case(s) (for local reference).
- An SSA report summarizing the minimal transferable fix intent and target location.

Task:
Improve the elite program by selectively transferring only the peer logic that fixes the elite's failure, while preserving the elite's global structure and approach.

Hard constraints:
- Preserve the elite program's overall structure: same function names, main flow, and algorithmic skeleton.
- Apply only minimal, targeted edits necessary to satisfy the SSA fix intent.
- Do NOT refactor, redesign, or rewrite the program from scratch.
- Do NOT introduce unrelated changes or optimizations.
- If SSA indicates a specific target_location (e.g., input/boundary/state/transition/output), restrict changes primarily to that area.

How to use the peer:
- The peer is only a reference to understand the correct local behavior.
- Do NOT copy large code blocks from the peer.
- Extract the smallest transferable logic that resolves the failing case(s).

Safety rule:
- If the SSA fix intent is ambiguous or conflicts with the task goal, prefer conservative edits and avoid speculative changes.

Problem description:

{problem_description}

Task goal:

{goal}

Elite program (base to preserve):

{elite_code}

Failing case(s) (input + expected output, and elite observed behavior if available):

{failed_cases}

One peer program that passes the failing case(s):

{peer_code}

SSA report (minimal fix intent and target location):

{ssa_json}

OUTPUT RULE (strict):
Output ONLY one Python code block:
```python
<full corrected code>
```

Figure 12: Prompt for Lamarckian Adaptation Agent.

Problem

Task

Given a positive integer as input, return the output as a string in the following format:

Each element, corresponding to a digit of the number, multiplied by a power of 10 in such a way that with the sum of these elements you can obtain the original number.

Examples

Input	Output
0	""
56	"5*10+6"
60	"6*10"
999	"9*100+9*10+9"
10004	"1*10000+4"

Note: `input >= 0`

Goal

The function takes a non-negative integer as input and returns a string representation of the number decomposed into its digits, where each digit is multiplied by the corresponding power of 10. The terms are combined with a '+' symbol to represent the sum that reconstructs the original number. If the input is 0, the function should return an empty string.

Strategy Pool

Objective
Develop a function that takes a positive integer and represents it as a sum of its digits multiplied by powers of 10. The result should be returned as a string.

Approach
Use an iterative process. Traverse through each digit of the number starting from the highest till the lowest place value. Determine the power of 10 for each digit appropriately and construct the final output string format by concatenating these terms.

Example
For input `56`, generate output `5*10+6`.
For efficiency, handle cases like trailing zeros by skipping them in the formatting.

Implement the `simplify(n)` function to solve this task.

....

Select K From M

Figure 13: Problem, extracted goal, and an example strategy prompt used to generate code.

Code ①

```python
def simplify(n):
    # Handle the zero case
    if n == 0:
        return ""

    # Convert the number to a string to iterate over digits
    str_n = str(n)
    length = len(str_n)
    parts = []

    for i in range(length):
        digit = int(str_n[i])
        if digit != 0:                     ........
            power = length - i - 1
            if power == 0:
                parts.append(f"{digit}")
            else:
                parts.append(f"{digit}*10" + (f"^{power}" if power > 1 else ""))

    # Join the parts with '+' and return
    return "+".join(parts)

# Reading input using sys.stdin as per problem description
import sys
data = sys.stdin.read().split()

# Process each number input
for line in data:
    if line.strip():
        number = int(line.strip())
        result = simplify(number)
        print(result)
```

....

Figure 14: Representative candidate programs produced under different strategies.

Figure 15: Surrogate tests and candidate pass/fail outcomes used for selection and contrast mining.

Semantic Spectrum Analysis

summary

SSA spectrum scan shows Bands 1–4 are semantically aligned; the first output-determining divergence appears in Band 5: the elite prints the units-place contribution with a redundant '1' (e.g., '61'), while the peer applies canonical formatting that suppresses '1' and prints the units digit as a bare literal.

fix_intent

Introduce a transferable units-place canonicalization rule without changing the elite's overall decomposition and joining strategy: when a non-zero digit contributes at exponent/power 0, emit the term as the digit alone (no explicit multiplication by 1); when power > 0, keep emitting the existing 'digit × 10^power' representation. This fix must operate purely at the output-representation layer (format normalization) and preserve digit extraction, zero-skipping, term ordering, and '+' concatenation.

target_location

Band 5: Termination and output formatting (units-place term canonicalization / suppress redundant '1')

must_handle

Band 1 (Input/format interpretation) comparison: both elite and peer interpret input as a single non-negative integer n and handle the degenerate n==0 case by returning an empty string; no Band-1 divergence explains the failure

Band 2 (Boundary conditions) comparison: both handle minimal non-zero inputs (e.g., n=1) and skip zero digit contributions; the failure is not an off-by-one or zero-handling error but a units-place formatting rule mismatch

Band 3 (Core state representation) comparison: both track equivalent semantic state—current digit and its place power (10^power); the state choice itself does not cause the discrepancy

....

Figure 16: SSA diagnosis: earliest semantic divergence between elite and peer, summarized as a fix intent.

final code

```python
def simplify(n):
    # Base case: if n is 0, return an empty string
    if n == 0:
        return ""

    # Recursive function to generate the representation
    def recursive_simplify(n, power):
        if n == 0:
            return ""
        else:
            # Extract current digit
            current_digit = n % 10
            # Recursively process the rest of the number
            rest_of_the_number = n // 10

            # Construct the current term if the digit is not zero
            current_term = ""
            if current_digit != 0:
                if power == 0:
                    current_term = f"{current_digit}"
                else:
                    current_term = f"{current_digit}*{10**power}"

            # Recur for the rest of the number
            rest_terms = recursive_simplify(rest_of_the_number, power + 1)

            # Combine parts, and ensure to join with '+' properly
            if rest_terms and current_term:
                return rest_terms + "+" + current_term
            elif rest_terms:
                return rest_terms
            else:
                return current_term

    # Start the recursive function with n and power 0
    return recursive_simplify(n, 0)

# Input reading and function execution
if __name__ == "__main__":
    import sys
    input_data = sys.stdin.read().strip()
    if input_data:
        n = int(input_data)
        print(simplify(n))
```

Figure 17: Lamarckian repair: a minimal patch applied to the elite guided by the SSA fix intent.