ScaleCert: Scalable Certified Defense against Adversarial Patches with Sparse Superficial Layers

Abstract

Adversarial patch attacks that craft the pixels in a confined region of the input images show their powerful attack effectiveness practically in physical environments even with noises or deformations. However, existing certified defenses work well on small images like MNIST and CIFAR-10 datasets, but achieve very poor certified accuracy on higher-resolution images in ImageNet. It is urgent to design both robust and effective defenses against such a practical and harmful attack in industry-level larger images. In this work, we propose the certified defense methodology that achieves high provable robustness for high-resolution images and largely improves the practicality for real adoption of the certified defense. The basic insight of our work is that the adversarial patch intends to leverage localized superficial important neurons (SIN) to manipulate the prediction results. Hence, we leverage the SIN-based DNN compression techniques to significantly improve the certified accuracy, by reducing the adversarial region searching overhead and filtering the prediction noises. Our experimental results show that the certified accuracy is increased from 36.3% (the state-of-the-art defense) to 60.6% on the ImageNet dataset, largely pushing the certified defenses for practical use.

1 Introduction

Despite the promising opportunities and great success of deep neural network (DNN) techniques in computer vision tasks (Krizhevsky et al., 2012; He et al., 2016), DNN techniques are vulnerable to adversarial attacks that craft the input data with adversarial perturbations to manipulate the output (Carlini and Wagner, 2017; Szegedy et al., 2013; Xu et al., 2019a). Recent studies reach a consensus that compared to the adversarial example attack, adversarial patch attack is more practical and well-demonstrated in physical environment with good effectiveness and transferability in both classification and detection systems (Eykholt et al., 2018; Xu et al., 2020b; Wu et al., 2020; Lee and Kolter, 2019; Levine and Feizi, 2020; Xiang et al., 2021). The key difference between the adversarial example attack and patch attack is the constraint of perturbation. For adversarial example attack, the adversary perturbs all pixels in the image with the ℓ_p-norm of the perturbation in prescribed bounds, while the adversarial patch attack only changes the pixels in a confined region without bounded constraints but free to choose the values. Consider the real-world condition, it's hard to define the ℓ_p-norm constraint of the perturbation due to the environment, viewpoint and object variation. Hence, the adversarial patch attack is much more appropriate to be mounted in the physical world.

The success of practical adversarial patch attacks raises the importance and urgency of defense methodologies. Existing defending methodologies can be classified into two categories, heuristic defenses and certified defenses. For heuristic defense approaches, they have good efficiency but lack robustness against a strong adaptive attack. For example, digital watermarking (DW) (Hayes, 2018) utilizes the magnitude of the saliency maps to detect unusually dense regions and mask

them out of the input. Local gradient smoothing (LGS) (Naseer et al., 2019) pre-processes the image gradient of the classification function with a normalization and a thresholding step and then suppress the adversarial noise based on the gradient. However, these empirical defenses may be invalidated when confront with the strong adaptive attacker that has the white-box knowledge of the defense (Chiang et al., 2020). For certified defenses, they must be proved that have provable robustness, like (Chiang et al., 2020) proposes the first certified defense based on the interval bound propagation (IBP) (Gowal et al., 2019) that are commonly used in adversarial robustness certification problems. De-randomized smoothing (DS) (Levine and Feizi, 2020) proposes the defense method extending randomized smoothing robustness schemes (Cohen et al., 2019) with structured ablation. Moreover, a provable robustness defense based on clipped BagNet (Brendel and Bethge, 2019) with small reception field is proposed by (Zhang et al., 2020b) . However, all of these certified studies achieve distinctly low certified accuracy for large scale datasets such as ImageNet (Krizhevsky et al., 2012). A certified accuracy of 20.5%-36.3% from these methods can hardly be applied in the real world systems. It is a dilemma that certified robustness against such a practical and pernicious attack model can be hardly scaled for realistic usage.

To address this issue, in this paper, we aim to propose the defenses with both certified robustness and good scalability for large scale dataset that used in practical scenarios. Inspired by the existing analysis on the unique distribution of the activation map yielded by adversarial patch attacked input (Xiang et al., 2021; Naseer et al., 2019; Li et al., 2021), and substantial neural network compression techniques without sacrificing natural accuracy (He et al., 2017; Yu et al., 2018), we observe that the adversarial patches rely on the localized superficial important neurons (SINs) to poison the output and can be exceedingly alleviate by utilizing the pruning techniques. We then propose the scalable certified (ScaleCert) defense with SIN-based neural network sparsity approach. The results show that the certified accuracy of ScaleCert on ImageNet dataset achieves 60.6% against 1%-pixel patch, significantly surpassing the highest record of 36.3% in state-of-the-art methods (Xiang and Mittal, 2021). This is the first certified work that largely reduces the gap between clean and certified accuracy, retaining the high certified accuracy with good computing efficiency, which largely pushes the certified defenses for common practice in real adoption.

2 Problem Setup

In this section, we describe the formulation and important terminology of adversarial patch attack and certified defenses against it.

2.1 Adversarial Patch Attack Formulation

Given an input $\mathbf{x} \in \mathcal{X} \subset [0,1]^{W \times H \times 3}$ with a true label y^*, adversarial patch attack can manipulate the output label of victim model, $\mathcal{M}(\cdot)$, by adding the patch perturbation on $\mathbf{x}$. The goal of adversarial patch attack is to find an adversarial patch $\hat{\mathbf{x}}$ that can be added on $\mathbf{x}$ to generate image $\mathbf{x}' \in \mathcal{A}(\mathbf{x})$ satisfying a constraint $\mathcal{A}$ such that $\mathcal{M}(\mathbf{x}') = y' \neq y^*$. y' can be a targeted label (targeted attack) or any arbitrary label not equal to the benign label (untargeted attack) y^* with all adversarial inputs $\mathbf{x}$ derived from data set $\mathcal{X}$. The adversarial patch $\hat{\mathbf{x}}$ can be generated by solving the follow equation:

$$\hat{\mathbf{x}} = arg \max_{\mathbf{x}' \in \mathcal{A}(\mathbf{x})} \mathbb{E}_{\mathcal{X}}[logPr(\mathcal{M}(\mathbf{x}') = y'|\mathbf{x})] \tag{1}$$

The constrain $\mathcal{A}(\mathbf{x})$ is determined by the threat model. In this paper, the adversary is allowed to arbitrarily change pixels within a square contiguous region and locate this region *anywhere* on the image, which is similar to the previous works (Levine and Feizi, 2020; McCoyd et al., 2020b; Xiang et al., 2021). Formally, we use a binary pixel block $\mathbf{p} \in \{0,1\}^{W \times H}$ to represent the restricted square region, where the pixels located in the region are set to one, otherwise zero. For the purpose of stealthiness, $\mathbf{p}$ is extremely smaller than $\mathbf{x}$, usually has the size of 1% to 5% of the $\mathbf{x}$. The constraint set $\mathcal{A}(\mathbf{x})$ can be expressed as:

$$\mathcal{A}(\mathbf{x}) \in \{\mathbf{x}' = (\mathbf{1} - \mathbf{p}) \odot \mathbf{x} + \mathbf{p} \odot \hat{\mathbf{x}}\} \tag{2}$$

where $\odot$ refers to the element-wise product operator, and $\hat{\mathbf{x}}$ is the adversarial patch we generated from Eq. (1).

2.2 Certified Defenses

Bounding the range of a neural network outputs given a ℓ_p-norm of input perturbation has become an important theme for neural network verification and certified adversarial defense (Wong and Kolter, 2018; Gowal et al., 2019; Cohen et al., 2019; Zhang et al., 2020a; Xu et al., 2020a). Recently, researchers also shed light on generalizing the conventional input perturbation constraint to the adversarial patch formulation. Existing certified defenses against adversarial patch attacks can be classified into two major categories with different certification problems:

1) **Certified defense for attack recovery.** The classifier returns the assurance that the classification result will provably not change under any distortion within an adversarial constraint set for the input. It is a heritage from certified defenses towards adversarial example attacks. Formally, the classifier ensures $\mathcal{M}(\mathbf{x}_0) = \mathcal{M}(\mathbf{x}') = y_0$ to produce a certificate for an clean input $\mathbf{x}_0$ for any adversarial example $\mathbf{x}' \in \mathcal{A}(\mathbf{x}_0)$, where $\mathcal{A}(\mathbf{x}_0)$ is the adversarial constraint set defined in Eq.(2). Many existing studies extend the certified techniques in adversarial example attacks with the new constraints of patch perturbation to propose the certified defenses against patch attacks. For example, (Chiang et al., 2020) proposes the certified defenses by extending interval bound propagation (IBP) (Gowal et al., 2019) defenses on patch attacks. (Levine and Feizi, 2020) proposes the derandomized smoothing methodology based on structured ablation scheme by extending the randomized smoothing techniques (Cohen et al., 2019). PatchGuard (Xiang et al., 2021) leverages the DNN models with small reception fields to localize the adversarial features and proposes the robust masking defense to remove adversarial effect of these features.

2) **Certified defense for attack detection.** The classifier returns the assurance that the image is clean or alert when the image is an adversarial input. MRD (McCoyd et al., 2020b) is the first work that proposes the certified attack detection study with the insight that the adversarial effect can be eliminated by occluding the adversarial patches. By examining the pattern of the prediction labels that occlude the windows of the images, the adversarial images can be certified detected. PatchGuard++ (Xiang and Mittal, 2021) aims to improve the certified detection rate by extending PatchGuard with the same insights of MRD.

The latter certified defenses leverage the insights that occluding the adversarial patch eliminates the adversarial effect and would change the prediction results. Such certified defenses for attack detection achieve better certified accuracy. However, even the state-of-the-art approaches obtain low certified accuracy on large scale datasets and can be hardly adopted for practical use. As shown in Table 1, the best certified accuracy in recent literature is about 36.3% when the patch contains 1% pixels of the input image. Therefore, we confront with the dilemma of practicality and low certified provable robustness for the harmful and practical adversarial patch attacks. To address this issue, we aim to propose a defense methodology that bridges the gap between clean and certified accuracy and achieves both provable robustness and good scalability for large scale datasets.

Table 1: Certified accuracy of state-of-the-art defenses on ImageNet.

Certified Defenses (ImageNet, PatchSize=1%)	PatchGuard++ (Xiang and Mittal, 2021)	PG-Mask-BN (Xiang et al., 2021)	PG-Mask-DS (Xiang et al., 2021)	CBN (Brendel and Bethge, 2019)	DS (Levine and Feizi, 2020)
Certified Accuracy	36.3%	32.3%	22.5%	21.9%	20.5%

3 ScaleCert Defense

In this section, we first use an empirical study to motivate the use of superficial important neurons (SIN) distribution to distinguish the adversarial patch and eliminate the adversarial effect and noises. Then we propose the ScaleCert to defend against adversarial patch attack with SIN-based sparsification methodology. To note, Section 3.1 focuses on empirical analysis based on the results of some specific adversarial patch attack methodology. However, the ScaleCert's robustness applies to any arbitrary adversarial patch attack. The provable robustness of this defense is demonstrated and analyzed in Section 3.3.

3.1 SIN in Patched and Benign Images

In observing that the adversarial patch determines the prediction results with a very small region of pixels for a relatively broad range of input images, we thus perform superficial feature importance distribution analysis of patched images and benign images. Though neuron importance analysis

Figure 1: SIN analysis in benign and patched images.

has been widely used for abnormal input detection (Gan et al., 2020; Xu et al., 2020c, 2019b; Li et al., 2021), the metric in our methodology (superficial feature importance) is distinct from previous studies (deep feature importance). The latter focuses on the neurons that contribute significantly to the inference output, while superficial important neurons refers to the neurons that contribute significantly to the shallow feature map values in the first (several) layer(s). Compared to deep important neurons (DIN), SIN has good discrimination to distinguish patched images, more straightforward correlation with the input adversarial regions, and smaller computing overhead without requirement for gradient calculation. More comparison between SIN and DIN is in Appendix A.3.

Specifically, we discover that the SIN of patched images exhibits extremely localized pattern and the adversarial patch effects can be eliminated if localized SINs are removed. For benign images, however, the prediction results do not rely on the localized SINs and thus being more stable. ***The intuition is that the prediction of typical DNN inference on the benign inputs depends on the deep features of the input image, while adversarial inputs have to strengthen the superficial features. Otherwise, its adversarial effect will fade out through the computation of all DNN layers.*** We quantitatively evaluate the impact of SIN during predictions of benign and patched images as follows.

1) ***Localized SIN Feature Analysis***: *SINs in patched images are much more localized than that in benign images.* We show the Top-200 neurons in the activation map of the first layer for benign images and patched images in Figure 1(a). Then, we compare the standard deviation of distance between the Top-200 neurons to the central neuron of benign images and patched images for randomly-selected 10000 images in ImageNet dataset. The patched images' distance deviation is much smaller than benign images, as shown in Figure 1(b). Additionally, we also cluster the Top-k neurons with the classic MeanShift clustering algorithm and observe the cluster number of SINs in patched images is much less than that in benign images. As shown in Figure 1(c), for patched images, about 75% of cases have only one cluster and 99% of cases have less than two clusters. While for benign images, more than 75% of the cases have more than three clusters. The results indicate that SINs are much more localized in patched images in terms of both the distance and cluster number.

2) ***Prediction Stability Analysis***: *By occluding the localized SINs in a small window, the prediction results of patched images are unstable, while benign images seldom change.* Specifically, we examine when moving the localized SIN features, how the prediction results are affected in patched images and benign images. We compare the prediction accuracy of benign objects and patched objects before and after moving out the localized SINs (l-SIN), as shown in Figure 1(d). In this experiment, we consider 10000 randomly-selected ImageNet images that can be correctly classified by the model to eliminate the interference of other factors. The results show that for benign images, the prediction accuracy is not sensitive to the localized SIN features. For the patched images, originally the prediction accuracy is extremely low because of the patch effects. After moving the localized important features, the detection rate increases drastically, which indicates that the patch effect has been effectively eliminated. The results show that the nature images perform robust classification without relying on extremely localized SIN features, while patches rely on the extremely localized SIN features to deceive and induce the object detector to output the incorrect results.

3) ***Adaptive Attack Against SIN-based Detection***: *The adversarial patch attacks confront with the dilemma of either introducing large SINs or hardly affecting the prediction results.* We perform the adaptive attacks on ImageNet dataset and the results are shown in Figure 1 (e). To steer clear of the detection based on SINs, the adversary trains the adversarial patch by taking the superficial activation value into consideration. Compared to Equation(1), a penalty loss of activation value is considered with the parameter α, when α is larger, the attack pays more attention to the stealthiness other than the attack effectiveness. In this way, the adversary aims to build the adversarial patch with both good poisoning effects, but also trying to escape from the adversary candidate searching.

Figure 2: ScaleCert Framework with three stages: SIN-based Pruning; Occlude Prediction; and ScaleCert Detection.

Adversary detection rate refers to the rate that detector correctly identifies the adversarial region in the adversarial inputs or the benign input with no adversarial region. The results show that, it is indeed that the adversary detection rate decrease to 82.1% when adversary attempts to reduce the activation magnitude in the first layer (α increases from 0 to 0.01). However, compared to the gentle slope of adversary detection rate, the attack success rate decreases much more drastically. When α is increased from 0 to 0.01, the adversarial attack success rate drops to 7.9%. These results indicate that the adversary cannot maintain the two goals of high attack success rate and good stealthiness in SINs simultaneously. The detailed attack setup and the datasets are covered in Appendix A.1.

These results show the empirical evidence to the hypothesis that the adversarial patch attacks rely on the strengths of localized SINs to effectively damage the prediction results of victim models. We leverage such insights to design ScaleCert certified defense methodology. Different from the motivation of previous studies (Xiang et al., 2021), we don't constrain the reception field to localize the adversarial feature effect in the deep features, but focus on the elimination of poisoned SIN features. More comparison and discussion between these two design philosophies are provided in Appendix A.3.

3.2 ScaleCert Framework

ScaleCert Overview. ScaleCert consists of three stages: 1) *SIN-based Pruning*: Calculating the SIN-mask, $\mathcal{S}$, and pruning the rest of neurons during inference. We first select the layer s as the superficial important layer, then by applying a SIN-mask we keep Top-k activation neurons and prune other unimportant neurons of this layer, where k is the top-ranking ratio. 2) *Occluding Prediction*: With the SIN-mask of the superficial layer, we calculate the candidate searching region $\mathcal{R}$ on the input image x that contributes to the SIN in the superficial layer. Then we impose a sliding window $\mathbf{w}$ on x and check the overlap with the candidate searching region $\mathcal{R}$, then ScaleCert makes inference by masking out every sliding window that $\mathbf{w} \cap \mathcal{R} \neq \emptyset$, and obtained the occluding prediction map. The size of sliding window $\mathbf{w}$ is $k \times k$, where k equals to the sum of patch size (p) and an additional step $(r-1)$ (r is 3 in the evaluation setting). Therefore, there are at least $r \times r$ windows that completely occlude the adversarial patch with the size of $p \times p$. 3) *ScaleCert Detection*: Finally, check the labels of the prediction map to detect whether there is an adversarial patch. If all the labels in the masked predictions are consistent, there is no attack and return the original model prediction $\mathcal{M}(\mathbf{x})$. ScaleCert leverages SIN-based sparsity to not only reduce the occluding windows, but more importantly filter out the noisy labels in trivial prediction maps and achieves the state-of-the-art certified accuracy.

Neural Network Sparsification. The key success factor of ScaleCert is leveraging the pruning technique on the superficial layer s to improve certified accuracy and efficiency. In order to maintain the clean accuracy of our ScaleCert, we need to finetune the model with the sparse superficial

layers. Figure 2 illustrates the the proposed winner-take-all dropout. We add the SIN-mask after the
superficial layer(s) and prune the non-important neurons according to the activation magnitude. Only
the top-ranking neurons (winners) can forward their outputs to the following layers. To finetune the
sparsified neural networks, we only update the top-ranking neurons selected by the SIN-mask. This
finetuning procedure can be treated as a shallow layers channel pruning, the SIN-mask, $\mathcal{S}$ will also
be updated during each iteration.

Occluding Prediction. With the SIN mask $\mathcal{S}$, we first calculate the input region $\mathcal{R}$ that contribute
to the SINs. The calculation procedure is as follows: for the neuron with the ordinate of (x_s, y_s) in
superficial neural network layer s, its antecedent neurons in layer $s-1$ that contribute to the value
of this neuron are in the square region with the top left ordinate $(x_s * s_s - p_s, y_s * s_s - p_s)$ and
the bottom right ordinate $(x_s * s_s - p_s + k_s - 1, y_s * s_s - p_s + k_s - 1)$, respectively, where p_s, s_s
and k_s are the padding size, stride size and kernel size of layer s. Then, we can iteratively calculate
region in the inference pyramid until back to the initial input layer and obtain region $\mathcal{R}$. $\mathcal{R}$ is the
candidate region for occluding prediction, while all the pixels falling out of this region cannot affect
the prediction results because of the SIN mask.

Then we impose the sliding window $\mathbf{w}$ across all the $\mathcal{R}$ region and obtain the occluding prediction
map by moving out the pixels in the sliding window. The number of candidate window $\mathbf{w}$ has been
largely reduced because of SIN mask. To reduce the overhead of inference procedures in the further
step, we additionally propose to merge adjacent occluding windows when the overlapped area among
every two windows exceed the threshold (τ). To note, the merging operations assure to cover every
occluding window $\mathbf{w}$ that has overlap with $\mathcal{R}$ for the certified robustness.

Figure 3: Merge sliding occluding windows. (a) Original windows. (b) Merged windows.

Detection Methodology The detailed ScaleCert detection algorithm is given in Algorithm 1. Scale-
Cert only imposes sliding window on the $\mathcal{R}$ based on the SIN area since other neurons will be masked
out during inference so that saves the detection time. Interestingly, the SIN-mask not only helps on
saving time but also filters out most noisy area on the original images so that makes the y_i more
consistent in SIN area and benefits on improving the clean accuracy on benign images. For patch
attacked cases, there must be a $r \times r$ region that the label will be changed when we masking out this
area. So the algorithm will alert (line 12) to user. In some rarely happened cases, like there are noises
on the input even in the SIN area, we cannot make the promise decision, and conservatively raise
alarm (line 14).

3.3 Provable Robust Analysis

ScaleCert Certification We consider the strongest adaptive attacker who has the perfect knowledge
of the defense mechanisms as well as the white-box access to the model architecture and weights.
We focus on the *certified robust* defense whose robust guarantee holds for *any* attacker considered
in the threat model. The goal of *certified attack detection* is to make *normal predictions* on clean
images but *alert* when an attack takes place, i.e., the defense should be provable that cannot be fooled
by the adversarial patch attack.

Theorem 1 *If Algorithm 2 returns True for a given image* $\mathbf{x}$*, our defense in Algorithm 1 can either
make a correct prediction or alert on any adversarial image* $\mathbf{x}' \in \mathcal{A}(\mathbf{x})$

Proof: The Algorithm 2 returns True indicates that all single sliding window $\mathbf{w}_i \in \mathcal{W}$ do not affect
the prediction results for image $\mathbf{x}$. Then if we apply adversarial patch attack on $\mathbf{x}$, which means any
$\mathbf{x}' \in \mathcal{A}(\mathbf{x})$ can be fed to Algorithm 1, there are two possible cases:

Algorithm 1 Our adversarial patch detection algorithm $\mathcal{D}$

1: **Inputs**: image $\mathbf{x}$, model $\mathcal{M}$, sliding windows on the input $\mathcal{W}$ and candidate searching region $\mathcal{R}$
2: **Output**: Prediction $\mathcal{M}(\mathbf{x})$ or `alert`
3: $\mathbb{S} \leftarrow \emptyset$
4: $y^* \leftarrow \mathcal{M}(\mathbf{x})$
5: **for** each $\mathbf{w}_i \in \mathcal{W}$ **do**
6:      **if** $\mathbf{w}_i \cap \mathcal{R} \neq \emptyset$ **then**   ▷ Filter out most potential sliding windows
7:          $y_i \leftarrow \mathcal{M}(\mathbf{x} \odot (1 - \mathbf{w}_i))$ ▷ Obtain the label according to the mask-out input
8:          **if** $y_i \neq y^*$ **then**
9:              $\mathbb{S} \leftarrow (\mathbf{w}_i, y_i)$ ▷ Collect potential malicious windows and prediction labels
10: **if** $\mathbb{S} \neq \emptyset$ **then**
11:      **if** $\mathbb{S}$ contains y' **and** $y = y' \Leftrightarrow \mathbf{w}_i \in \mathcal{R}_{r \times r}$ **then**
12:          **return** `alert`   ▷ Adversarial patch detected at $\mathcal{R}_{r \times r}$ area
13:      **else if** MAJORITYVOTING(y_i) $\neq y^*$ **then**
14:          **return** `alert`   ▷ Patch attacked image with noises in $\mathcal{S}$
15:      **else**
16:          **return** y^* ▷ benign image with noises in $\mathcal{S}$
17: **else**
18:      **return** y^* ▷ benign image

Algorithm 2 Our certify algorithm $\mathcal{C}$

1: **Inputs**: image $\mathbf{x}$, label y, model $\mathcal{M}$, sliding windows on the input $\mathcal{W}$ and candidate searching region $\mathcal{R}$
2: **Output**: Whether the image $\mathbf{x}$ has provable robustness to label y
3: **for** each $\mathbf{w}_i \in \mathcal{W}$ **do**
4:      **if** $\mathbf{w}_i \cap \mathcal{R} \neq \emptyset$ **then**
5:          $y_i \leftarrow \mathcal{M}(\mathbf{x} \odot (1 - \mathbf{w}_i))$
6:          **if** $y_i \neq y$ **then**
7:              **return** False
8: **return** True

- Case 1: The adversarial patch is located outside the SIN area. For this case, it's clearly that the result would not change by the patched area since they will be pruned by our model $\mathcal{M}$. The prediction result is true label y^* in Algorithm 1 (line 18).

- Case 2: The adversarial patch is located at the boundary or inside the SIN area. Consider the size of our sliding window and the patch affected area are $k \times k$ and $r \times r$ respectively, respect to the condition that $r \leq k$, there must have one (more) $k \times k$ sliding window(s) which exactly masked out the adversarial patch, and recall the Algorithm 2, the masked out prediction y' is exactly the true label. In this case Algorithm 1 return `alert` (line 12). □

Note that, the line 13-16 in Algorithm 1 is not necessary to the certified defense, since the patch is provably caught in line 11 when the input $\mathbf{x}$ returns True in Algorithm 2. They are designed for the benign image with noises in SIN area or both patch and noises happened in SIN area. In summary, Algorithm 1 is a general empirical adversarial patch detection method but when combining with the Algorithm 2, it can conclusively output normal predictions on clean images but alert when an attack takes place for the certified inputs.

4 Experiments

4.1 Experiment Setup

Evaluation Metrics Certified accuracy: note that our Algorithm 1 can return a provable answer if the input image is benign or can be recovered by our algorithms, but it may be incapable of rare examples that violate our assumption. So the certified accuracy we defined here is a lower bound of the real certified accuracy.

Datasets and Models. We evaluate the clean and certified robustness results on the high resolution dataset with 224×224 sizes (1000-class ImageNet (Krizhevsky et al., 2012)) and low resolution dataset with 32×32 sizes (10-class CIFAR-10 (Krizhevsky et al., 2009)). In our evaluation, we use ResNet50 (He et al., 2016) for ImageNet dataset and ResNet18 (He et al., 2016) for CIFAR-10 dataset.

Baselines. We compare the defense performance with the state-of-the-art studies: PatchGuard++ (Xiang and Mittal, 2021), PG-mask-BN (Xiang et al., 2021), PG-mask-DS (Xiang et al., 2021), Clipped BagNet (CBN) (Brendel and Bethge, 2019), De-randomized Smoothing (Levine and Feizi, 2020), and Interval Bound Propogation based certified defense (IBP) (Chiang et al., 2020). We use the optimal parameter settings in their configurations obtained from their reports.

Attack Patch Size We adopt the similar configurations from previous studies that defend against a single sequare adversairal patch that consists up to 1%, 2%, or 3% pixels of the ImageNet images, and 0.4% and 2.4% pixels of CIFAR-10 images. Additionally, we also report the extremely large patches with 5% and 8% in the Appendix A.4.

4.2 Provable Robustness Results

In this subsection, we present the certified accuracy results of ScaleCert and other recent studies in Table 2. For PatchGuard++, MRD, and ScaleCert, the certified accuracy refers to the certified detection accuracy. For others, the certified accuracy refers to the certified recovery accuracy. These results hold for any attack within the patch size constrain. We draw the following conclusions from the results.

Existing studies achieve good certified accuracy in low-resolution images, but very poor provable robustness in high-resolution images. For example, when patch size is 2.4% of the images, Patch-Guard++, PG-Mask-DS, PG-Mask-BN achieves 74.1%, 57.7%, and 47.3% of certified accuracy. For ImageNet dataset, their certified accuracy decreases to 33.9%, 19.0% and 26.0%. There are two potential reasons behind this phenomenon: 1) Deeper models are used for the classification of high-resolution images. With deeper layers, the reception field becomes larger even using BagNet with limited small kernel size. It is hard to distinguish and eliminate the adversarial effect at the deep feature extraction layer. 2) For high-resolution images, the random ablation in DS-based algorithms is unable to produce satisfactory accuracy due to the loss of the most information of the input images.

MRD and IBP are computational infeasible for high-resolution images. MRD requires to compute the prediction map for every occluding window, which introduces infeasible computational overhead with $O(W \times H)$ inference rounds. For example, MRD requires about 36481 inference rounds when the patch is 2%, which costs about 49 s for V100S GPU platform to verify a single input image with 224×224 pixels even after parallelization optimization. As a comparison, our study reduces the candidate windows number to around 10-20, which significantly removes the computation overhead.

ScaleCert outperforms other defenses with much higher certified accuracy for ImageNet datasets, which pushes the certified defenses into practical usage. ScaleCert achieves both good certified accuracy for low-resolution images and high-resolution images. For high resolution images, particularly, the experimental results show that ScaleCert achieves the best certified accuracy. Specifically, when patch contains 1% pixels of the input images, ScaleCert achieves 60.6%, largely surpassing the PatchGuard++ with 36.3% of certified accuracy.

4.3 Detailed Analysis of ScaleCert

The insight of ScaleCert is to leverage the intrinsic differences of SINs in patched and benign images to achieve effective defenses. There are two key parameters affecting the clean and certified accuracy: the pruning rate in the shadow region and the occluding window size to target the adversarial patch (more discussion in Appendix A.2). In the ScaleCert algorithm, some hyperparameters can affect these two important parameters: the winner rate of SIN mask (k), the overlap ratio for merging the searching window (τ), and the superficial layer selection (l). We analyze the impact of k, τ, l (in Appendix A.4) on the certified defense effectiveness and efficiency.

Pruning Rate of SIN Mask: We test the vanilla model accuracy, clean accuracy, and certified accuracy with different winner rate k ranging from 10% to 20%, as shown in Table 3. The winner rate refers to the top k neurons in superficial layer and pruning others. The results show that: 1) the vanilla model accuracy maintains when the top-ranking rate is larger than 10%. 2) The selection of

Table 2: Comparison of clean and certified accuracy under different defenses

Dataset	ImageNet						Cifar			
Patch size	1% pixels		2% pixles		3% pixels		0.4% pixels		2.4% pixels	
Accuracy	Clean	Cert.	Clean	Cert.	Clean	Cert.	Clean	Cert.	Clean	Cert.
IBP	Computationally infeasible						65.8	51.9	47.8	30.3
CBN	53.5	21.9	53.5	13.7	53.5	7.4	83.2	51.0	83.2	16.2
DS	44.4	20.5	44.4	17.0	44.4	14.9	83.9	68.9	83.9	56.3
PG-Mask-DS	44.5	22.5	44.1	19.0	43.7	16.6	84.7	69.2	84.6	57.7
PG-Mask-BN	55.0	32.3	54.6	26.0	54.0	19.8	84.5	63.8	83.9	47.3
MRD	Computationally infeasible						87.6	82.5	84.2	78.1
PatchGuard++	61.8	36.3	61.6	33.9	61.5	31.1	82.0	78.8	78.2	74.1
ScaleCert (k=20%)	63.6	**60.6**	55.9	**53.3**	56.5	**51.6**	83.1	81.0	78.9	75.3

the winner rate k is the tradeoff between the activation sparsification level and inference accuracy. On one hand, a smaller k reduces more overhead of certified defenses by reducing the candidate sliding windows and filtering more noise prediction labels. On the other hand, it is more challenging to maintain the accuracy of the neural network with the heavy pruning activation map.

Table 3: Effect of Top-Ranking rate

Top-Ranking Rate	10%			15%			20%		
Patch size	Model	Clean	Cert.	Model	Clean	Cert.	Model	Clean	Cert.
1%	73.6	61.4	56.0	74.2	60.5	58.4	75.0	63.6	60.6
2%	73.8	58.7	51.8	74.6	58.7	54.9	74.4	55.9	53.3
3%	73.2	54.0	48.6	74.3	57.3	49.6	74.2	56.5	51.6

Occluding Window Sizes. We also test the impact of overlap ratio threshold (τ) when merging the occluding windows to reduce the searching windows for the better computing efficiency. When τ is larger, less windows will be merged, resulting with larger candidate searching window number and smaller occluding window size. Larger occluding window may hurt the model prediction accuracy. Less candidate searching window can accelerate the detection procedure and remove noises in the prediction map. Hence, the selection of overlap ratio is the tradeoff between occluding window number and window size. As shown in Table 4, the results indicate that ScaleCert can achieve both good certified accuracy and introduce the smallest computing overhead, when overlap ratio threshold is 0.3. We achieve over $100\times$ of speedup compared to MRD (McCoyd et al., 2020a) and comparable computing overhead with PG-Mask-DS (Xiang et al., 2021).

Table 4: Effect of overlap ratio threshold (PatchSize=2%, k=10%)

Overlap Ratio (τ)	0.3	0.4	0.5	0.6
Candidates	11	13	17	21
Execution Latency (V100 GPU)	266ms	296ms	371ms	436ms
Occluding Window Size	77	70	64	58
Clean Accuracy	62.5	62.4	59.8	61.1
Certified Accuracy	56.6	56.1	55.2	56.0

5 Conclusion and Future Work

In this paper, we propose the certified defense methodology ScaleCert for the detection of adversarial patches in high resolution images. We observe that adversarial patch intends to leverage localized superficial important neurons (SIN) to manipulate the prediction results. Hence, we propose SIN-based sparse techniques to reduce the adversarial region searching overhead and filter the prediction noises, which significantly improves the certified accuracy with good computing efficiency.

References

Wieland Brendel and Matthias Bethge. Approximating CNNs with bag-of-local-features models works surprisingly well on ImageNet. In *7th International Conference on Learning Representations (ICLR)*, 2019.

Nicholas Carlini and David Wagner. Adversarial examples are not easily detected: Bypassing ten detection methods. In *Proceedings of the 10th ACM Workshop on Artificial Intelligence and Security*, pages 3–14. ACM, 2017.

Ping-Yeh Chiang, Renkun Ni, Ahmed Abdelkader, Chen Zhu, Christoph Studor, and Tom Goldstein. Certified defenses for adversarial patches. In *8th International Conference on Learning Representations (ICLR)*, 2020.

Jeremy M. Cohen, Elan Rosenfeld, and J. Zico Kolter. Certified adversarial robustness via randomized smoothing. In *Proceedings of the 36th International Conference on Machine Learning (ICML 2019)*, volume 97, pages 1310–1320. PMLR, 2019.

Kevin Eykholt, Ivan Evtimov, Earlence Fernandes, Bo Li, Amir Rahmati, Chaowei Xiao, Atul Prakash, Tadayoshi Kohno, and Dawn Song. Robust physical-world attacks on deep learning visual classification. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 1625–1634, 2018.

Yiming Gan, Yuxian Qiu, Jingwen Leng, Minyi Guo, and Yuhao Zhu. Ptolemy: Architecture support for robust deep learning. In *2020 53rd Annual IEEE/ACM International Symposium on Microarchitecture (MICRO)*, pages 241–255. IEEE, 2020.

Sven Gowal, Krishnamurthy Dvijotham, Robert Stanforth, Rudy Bunel, Chongli Qin, Jonathan Uesato, Relja Arandjelovic, Timothy Arthur Mann, and Pushmeet Kohli. Scalable verified training for provably robust image classification. pages 4841–4850, 2019.

Jamie Hayes. On visible adversarial perturbations & digital watermarking. In *2018 IEEE Conference on Computer Vision and Pattern Recognition Workshops (CVPR Workshops)*, pages 1597–1604, 2018.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

Yihui He, Xiangyu Zhang, and Jian Sun. Channel pruning for accelerating very deep neural networks. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 1389–1397, 2017.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. *Technical Report TR-2009*, 2009.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *Advances in neural information processing systems (NIPS)*, pages 1097–1105, 2012.

Mark Lee and Zico Kolter. On physical adversarial patches for object detection. *arXiv preprint arXiv:1906.11897*, 2019.

Alexander Levine and Soheil Feizi. (De)randomized smoothing for certifiable defense against patch attacks. In *Conference on Neural Information Processing Systems, (NeurIPS)*, 2020.

Fengting Li, Xuankai Liu, Xiaoli Zhang, Qi Li, Kun Sun, and Kang Li. Detecting localized adversarial examples: A generic approach using critical region analysis. *arXiv preprint arXiv:2102.05241*, 2021.

Michael McCoyd, Won Park, Steven Chen, Neil Shah, Ryan Roggenkemper, Minjune Hwang, Jason Xinyu Liu, and David Wagner. Minority reports defense: Defending against adversarial patches. In *International Conference on Applied Cryptography and Network Security*, pages 564–582. Springer, 2020a.

Michael McCoyd, Won Park, Steven Chen, Neil Shah, Ryan Roggenkemper, Minjune Hwang, Jason Xinyu Liu, and David A. Wagner. Minority reports defense: Defending against adversarial patches. In *Applied Cryptography and Network Security Workshops (ACNS Workshops)*, volume 12418, pages 564–582. Springer, 2020b.

Muzammal Naseer, Salman Khan, and Fatih Porikli. Local gradients smoothing: Defense against localized adversarial attacks. In *IEEE Winter Conference on Applications of Computer Vision (WACV)*, pages 1300–1307, 2019.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. 2013.

Eric Wong and J Zico Kolter. Provable defenses against adversarial examples via the convex outer adversarial polytope. In *ICML*, 2018.

Zuxuan Wu, Ser-Nam Lim, Larry S Davis, and Tom Goldstein. Making an invisibility cloak: Real world adversarial attacks on object detectors. In *European Conference on Computer Vision*, pages 1–17. Springer, 2020.

Chong Xiang and Prateek Mittal. Patchguard++: Efficient provable attack detection against adversarial patches. *arXiv preprint arXiv:2104.12609*, 2021.

Chong Xiang, Arjun Nitin Bhagoji, Vikash Sehwag, and Prateek Mittal. Patchguard: A provably robust defense against adversarial patches via small receptive fields and masking. 2021.

Kaidi Xu, Sijia Liu, Pu Zhao, Pin-Yu Chen, Huan Zhang, Quanfu Fan, Deniz Erdogmus, Yanzhi Wang, and Xue Lin. Structured adversarial attack: Towards general implementation and better interpretability. In *International Conference on Learning Representations*, 2019a.

Kaidi Xu, Zhouxing Shi, Huan Zhang, Yihan Wang, Kai-Wei Chang, Minlie Huang, Bhavya Kailkhura, Xue Lin, and Cho-Jui Hsieh. Automatic perturbation analysis for scalable certified robustness and beyond. *Advances in Neural Information Processing Systems (NeurIPS)*, 2020a.

Kaidi Xu, Gaoyuan Zhang, Sijia Liu, Quanfu Fan, Mengshu Sun, Hongge Chen, Pin-Yu Chen, Yanzhi Wang, and Xue Lin. Adversarial t-shirt! evading person detectors in a physical world. In *ECCV*, pages 665–681, 2020b.

Zirui Xu, Fuxun Yu, and Xiang Chen. Dopa: A comprehensive cnn detection methodology against physical adversarial attacks. *arXiv preprint arXiv:1905.08790*, 2019b.

Zirui Xu, Fuxun Yu, and Xiang Chen. Lance: A comprehensive and lightweight cnn defense methodology against physical adversarial attacks on embedded multimedia applications. In *2020 25th Asia and South Pacific Design Automation Conference (ASP-DAC)*, pages 470–475. IEEE, 2020c.

Ruichi Yu, Ang Li, Chun-Fu Chen, Jui-Hsin Lai, Vlad I Morariu, Xintong Han, Mingfei Gao, Ching-Yung Lin, and Larry S Davis. Nisp: Pruning networks using neuron importance score propagation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 9194–9203, 2018.

Huan Zhang, Hongge Chen, Chaowei Xiao, Bo Li, Duane Boning, and Cho-Jui Hsieh. Towards stable and efficient training of verifiably robust neural networks. In *International Conference on Learning Representations*, 2020a.

Zhanyuan Zhang, Benson Yuan, Michael McCoyd, and David Wagner. Clipped bagnet: Defending against sticker attacks with clipped bag-of-features. In *3rd Deep Learning and Security Workshop (DLS)*, 2020b.