Improving Fairness in Image Classification via Sketching

Abstract

Fairness is a fundamental requirement for trustworthy and human-centered Artificial Intelligence (AI) system. However, deep neural networks (DNNs) tend to make unfair predictions when the training data are collected from different sub-populations with different attributes (*i.e.* color, sex, age), leading to biased DNN predictions. We notice that such a troubling phenomenon is often caused by data itself, which means that bias information is encoded to the DNN along with the useful information (*i.e.* class information, semantic information). Therefore, we propose to use sketching to handle this phenomenon. Without losing the utility of data, we explore the image-to-sketching methods that can maintain the useful semantic information for the targeted classification while filtering out the useless bias information. In addition, we design a fair loss for further improving the model fairness. We evaluate our method on extensive experiments on both general scene dataset and medical scene dataset. Our results show that the desired image-to-sketching method improves model fairness and achieves satisfactory results among state-of-the-art (SOTA). Our code would be released based on acceptance.

1 Introduction

Neural networks make many great achievements in different computer vision scenarios including general scenes and medical scenes, bringing much wellness to the society. However, serious challenge also ensues. Standard vision model tends to make unfair predictions on skin color, age, sex, *etc.* [1, 2, 10, 12, 14, 18, 22, 27, 28]. One key reason comes from the bias in the input data. When the images are input to network, the bias information is also encoded thus leading model's unfair prediction.

Taking advantage of the advances in latest image-to-sketch research [4, 7, 8, 13, 24, 26], we exploit the sketch to relieve unfairness while keeping the class or semantic information. Since sketches convey much semantic information from the original images, neural networks could also use them to make predict without sacrificing much accuracy, especially where class discrimination relies little on the color information (*i.e.* skin cancer). Meanwhile, sketches throw the bias factors (*i.e.* color, texture) out with the color and texture information.

Previous methods often handle the unfairness problem into three ways: Pre-processing approach, In-processing approach, and Post-processing approach. (a). The pre-processing work deals with the bias in the database to train a fairer model [19, 21, 27, 31], which means the approaches to reduce the bias contained in the training set, such as transforming the data representation [19], generating paired training data to balance protected attributes [21], and generating adversarial examples to balance the number of protected attributes in the training set [31]. In this work, the way to process the input images into sketches is also pre-processing approach. (b). In-processing method is to introduce a fairness mechanism in the training model [3, 14, 29, 30], such as adding fairness loss to

Figure 1: (a) is original classification pipeline. (b) is the overall pipeline of our proposed method, which we first send input image x_i to sketching model S and then train the image sketches $S(x_i)$ with additional fairness criterion. Note that the green arrow means the pipeline participate in training and gray means the pipeline offline in training.

constrain [29] and using adversarial training to force the model to produce a fair output [3, 14, 30], these methods aim to obtain fairer models by explicitly changing the training procedure. (c).Post-processing approaches adjusts model's predictions according to some fairness criteria [11, 16]. One way is to adjust the model predictions by editing the protected attributes accordingly [16], however this method is difficult to implement in practice [27], another work is to post-process a pre-trained deep learning model and create a new classifier with the same accuracy for people with different protected attributes [11].

Without manipulating model in training stage or adjusting prediction results. We use image sketch as an intuitive solution to complete the pre-process step in the data side. Our contribution could be summarized as follow: (1). We make the first attempt to exploit sketching for improving computer vision fairness. This simple solution could effectively abandon the bias of input data for fair prediction. (2) We introduce a fairness loss to further improve model's fairness results. Our method achieves satisfactory performance among state-of-the-arts.

2 Methods

2.1 Overview

An overview of our method has been shown in Fig. 1, based on standard vision classification paradigm, our pipeline mainly involves two modifications. First we convert the input images into their sketches and feed them to following classification model for prediction. Towards further fairness improvement, in second step we introduce a fairness loss function to mitigate the bias in the model. Sufficient experiments and detailed explanations are shown in Sec. 3.

For each image index i, x_i denotes the original input images, y_i denotes the image label and z_i denotes the bias sensitive attribute. In our method, the input image x_i would first sent in to sketch generation model S to generate x_i's corresponding sketch $S(x_i)$, then the sketch image $S(x_i)$ would be sent into following classifier M to generate classification results $\hat{y}_i = M(S(x_i))$, classification loss $\mathcal{L}_{\text{cls}}$ would by calculating the cross-entropy (CE) loss between $\hat{y}_i$ and y_i, additionally we design a fairness loss $\mathcal{L}_{\text{fair}}$ (Sec. 2.3) for further fairness improvement. Overall, the classfication model M would be optimise by the total loss $\mathcal{L}$ (λ is a non-negative number to balance, which we set it to 1.0 in our experiments):

$$\mathcal{L} = \mathcal{L}_{\text{cls}} + \lambda \cdot \mathcal{L}_{\text{fair}}. \tag{1}$$

Figure 2: Experimental results of original photographs, grayscale images, and sketching images. Target label is smiling and sensitive attributes are gender, skin color, and hair color respectively.

As to evaluation metrics, based on previous works [14, 27], we apply *Statistical Parity Difference (SPD)*, *Equal Opportunity Difference (EOD)*, *Difference in Equalized Odds (DEO)*, and *Average Odds Difference (AOD)* to measure and evaluate model's fairness. For all four evaluation metrics, the smaller the value of their indicators, the higher the fairness of the model.

2.2 Sketch Generation

For sketch generation model S, we employ latest image-to-sketching method [4] to convert input image x_i into its corresponding sketch $S(x_i)$.

The sketching method [4] is an unsupervised model trained on unpaired data between photographs (domain A) and sketchings (domain B). It setups an adversarial training network with generators G_A, G_B and discriminators D_A, D_B, respectively for domain A and B. Different from previous image-to-sketching methods, this model not only focuses on image appearance but also explicitly instills geometric and semantic information into drawings. Specifically, the model is forced to draw lines in important geometric areas under a geometric loss which predicts depth information. In addition, a CLIP [20] model guidance is adopted to constrain the semantic meaning of sketches closer to original images [4, 20].

In the training stage, geometric loss $\mathcal{L}_{\mathrm{Geom}}$ is implemented to maximize the depth information to capture as much depth information as possible. Using a state-of-the-art depth estimation network [17] F, a network G_{Geom} is designed to predict the depth map of sketching during training. Given input a, G_A is the sketching generation network and $I(G(a))$ are the extracted ImageNet [6] features. The depth maps of photographs can be denoted as $F(a)$ and depth maps of sketches is $G_{Geom}(I(G(a)))$. The geometric loss is the absolute difference between these two predicted depth maps. $\mathcal{L}_{\mathrm{Geom}} = |G_{Geom}(I(G(a))) - F(a)|$

The semantic loss encourages minimizing the semantic meaning gap between input image and line drawings. The smaller the semantic distance, the more accurate line drawings are translated into. The semantic loss is defined as the absolute CLIP difference between input image and sketches. $\mathcal{L}_{\mathrm{CLIP}} = |\mathrm{CLIP}(G_A(a)) - \mathrm{CLIP}(a)|$

Moreover, appearance loss $\mathcal{L}_{\text{cycle}}$ and adversarial loss $\mathcal{L}_{\text{GAN}}$ are implemented to encode input appearance and generate images to belong to their domains. The overall loss function is the weighted summation of these four losses:

$$\mathcal{L}_{\text{sketch}} = \lambda_{\text{CLIP}}\mathcal{L}_{\text{CLIP}} + \lambda_{\text{Geom}}\mathcal{L}_{\text{Geom}} + \lambda_{\text{GAN}}\mathcal{L}_{\text{GAN}} + \lambda_{\text{cycle}}\mathcal{L}_{\text{cycle}}. \tag{2}$$

Chan et al. [4] set $\lambda_{\text{CLIP}} = 10$, $\lambda_{\text{Geom}} = 10$, $\lambda_{\text{GAN}} = 1$, and $\lambda_{\text{cycle}} = 0.1$ in practice. Taking advantage of sketch, we are able to reduce the bias. As shown in Figure 2, the sketching images are not inferior in accuracy and has an obvious advantage in the fairness indicator *DEO* when compared with the original images and the grayscale images.

2.3 Fairness Constraint

Since the initial purpose of image-to-sketching method [4, 8, 13, 24, 26] is not designed for fairness improvement, we introduce an additional fairness loss function to further mitigate bias of the model during training. The fairness loss function $\mathcal{L}_{\text{fair}}$ is designed as a mean square error (*MSE*) loss of *Statistical Parity Difference (SPD)* for every mini-batch. During model training, the fairness loss $\mathcal{L}_{\text{fair}}$ would combine with classification loss $\mathcal{L}_{\text{cls}}$ to optimise model parameters (see Eq. 1).

$$\mathcal{L}_{\text{fair}} = \frac{1}{n}\sum_{m=1}^{n}(SPD_{predict_m} - SPD_{ideal_m})^2 \tag{3}$$

Specifically, SPD measures the difference of probability in positive predicted label ($\hat{y} = 1$) between protected ($z = 1$) and unprotected ($z = 0$) attribute groups.

$$SPD = |P(\hat{y} = 1|z = 1) - P(\hat{y} = 1|z = 0)| \tag{4}$$

3 Experiments

3.1 Datasets and Experimental Setup

Datasets. We adopted two datasets for our evaluation, CelebA [15] and Skin ISIC 2018 [5, 25], CelebA for face recognition classification and Skin ISIC 2018 for skin cancer classification.

- CelebA

  The CelebA dataset consists of 202,599 human face images with 40 features per image [15]. Following [27], we choose smiling and attractive as the predicted label for binary class classification. For each predicted label, we choose gender (male and female), hair color (black hair and others), and skin color (pain skin and others) as the bias sensitive attribute. We select 10,000 images for every experiment, of which 70% for training, 15% for validation, and 15% for testing. For each experiment, the number of images in protected attribute and unprotected attribute are equal, which means we adopt a fair dataset.

- Skin ISIC 2018

  The Skin ISIC 2018 dataset consists of 10,015 skin images for 7-class skin cancer classification [5, 25]. Following [14], we choose gender (male and female), age (≥ 60 and < 60), and skin color (dark and light skin) as the bias sensitive attribute. We randomly split the dataset to training set (80%) and testing set (20%) similar to [14].

Training and Evaluation. We use original images and sketches to train the classification model separately. Furthermore, we compare with gray-scale images whose color information is removed. This allows us to evaluate the impact between changing only the color of the image and modifying both the color and texture. In addition, the fairness loss function is added to cross-entropy loss when training on sketched images.

We use ResNet-18 [9] to train CelebA dataset and VGG11 [23] to train ISIC dataset follow previous setting [14, 27]. Batch size is set to 64 in CelebA and 32 in ISIC. Learning rate is set to 1e-3. For evaluation metrics, we evaluate the results CelebA dataset with *SPD* and *DEO*. And we evaluate the results of ISIC dataset with *SPD*, *EOD*, and *AOD*.

3.2 Experimental Results

On CelebA dataset, tables from 1 to 6 show that classification accuracy does not drop too much on other styles of images compared to the one on the original image. Particularly, sketches either with or without fairness loss, exhibits the minimum values of fairness metrics, *SPD* and *DEO*, showing highest fairness compared to the original and grayscale images. The result of Sketchs with $\mathcal{L}_{\text{fair}}$ demonstrates that the fairness loss could further improve fairness in some cases.

We also compare a SOTA fairness method, fair training + FAAP [27]. As shown in table 1, our model outperforms [27] in terms of *SPD* on gender attribute. For accuracy and *DEO*, our model still delivers competitive performance.

While [27] only considers gender as sensitive attribute, we also assess other sensitive attributes that are likely to cause bias such as skin color and hair color. Table 3 and table 4 reports the result on skin color as sensitive attribute. The accuracy on sketches doesn't drop much but the fairness indices are far below that of in original photographs, significantly reducing the bias in orginal images. Table 5 and table 6 also show similar patterns. On both skin color and hair color, the use of sketching images are demonstrated to effectively improve fairness without much sacrafice in classification accuracy.

Table 1: Results on CelebA when the target label is smiling and sensitive attribute is gender

	ACC ↑	SPD ↓	DEO ↓
Original	0.902	0.14	0.0963
Grayscale	0.908	0.1787	0.1461
Fair training+FAAP	**0.9249**	0.1326	**0.0281**
Sketches w/o $\mathcal{L}_{\text{fair}}$	0.91	0.1107	0.0414
Sketches w/ $\mathcal{L}_{\text{fair}}$	0.9087	**0.1053**	0.0682

Table 2: Results on CelebA when the target label is attractive and sensitive attribute is gender

	ACC ↑	SPD ↓	DEO ↓
Original	**0.8127**	0.5067	0.5864
Grayscale	0.8167	0.4827	0.5232
Fair training+FAAP	0.7931	**0.2244**	**0.0434**
Sketches w/o $\mathcal{L}_{\text{fair}}$	0.7893	0.4253	0.4457
Sketches w/ $\mathcal{L}_{\text{fair}}$	0.7007	0.2987	0.2811

Table 3: Results on CelebA when the target label is smiling and sensitive attribute is skin color

	ACC ↑	SPD ↓	DEO ↓
Original	**0.9233**	0.1613	0.0628
Grayscale	0.916	0.1307	0.0651
Sketches w/o $\mathcal{L}_{\text{fair}}$	0.9153	0.132	**0.0281**
Sketches w/ $\mathcal{L}_{\text{fair}}$	0.908	**0.1040**	0.0495

Table 4: Results on CelebA when the target label is attractive and sensitive attribute is skin color

	ACC ↑	SPD ↓	DEO ↓
Original	**0.8093**	0.2787	0.3371
Grayscale	0.8027	0.3107	0.3562
Sketches w/o $\mathcal{L}_{\text{fair}}$	0.7807	**0.1947**	0.204
Sketches w/ $\mathcal{L}_{\text{fair}}$	0.78	0.196	**0.1409**

Table 5: Results on CelebA when the target label is smiling and sensitive attribute is hair color

	ACC ↑	SPD ↓	DEO ↓
Original	0.9127	0.0613	0.0548
Grayscale	**0.9173**	0.052	0.0348
Sketches w/o $\mathcal{L}_{\text{fair}}$	0.904	0.0547	0.0427
Sketches w/ $\mathcal{L}_{\text{fair}}$	0.8913	**0.0373**	**0.0122**

Table 6: Results on CelebA when the target label is attractive and sensitive attribute is hair color

	ACC ↑	SPD ↓	DEO ↓
Original	**0.802**	0.0707	0.0916
Grayscale	0.7913	0.0467	0.1412
Sketches w/o $\mathcal{L}_{\text{fair}}$	0.7793	**0.0227**	0.0848
Sketches w/ $\mathcal{L}_{\text{fair}}$	0.7767	0.0333	**0.0564**

Tables 7 to 9 are the experimental results of ISIC dataset. In table 7, the sensitive attribute is gender. We find that although using sketches does not show more fairness in terms of *SPD*, the gap between the original images and the sketch images is very small. In terms of *EOD* and *AOD*, using sketch images can still effectively reduce bias. In addition, the decline is more significant when fairness loss is added. In table 8 and 9, we can find similar pattern as table 7. After adding fairness loss to the model, *EOD* and *AOD*, significantly decreases.

Table 7: Results on ISIC when the sensitive attribute is gender

	Sex	Precision ↑	Recall ↑	F1-score ↑	SPD ↓	EOD ↓	AOD ↓
Original	Male	0.847	0.826	0.828	0.114	0.143	0.17
	Female	0.877	0.867	0.867			
Ours sketches w/o $\mathcal{L}_{\text{fair}}$	Male	0.81	0.741	0.769	0.136	0.131	0.161
	Female	0.815	0.773	0.787			
Ours sketches w/ $\mathcal{L}_{\text{fair}}$	Male	0.835	0.779	0.799	0.12	0.125	0.152
	Female	0.837	0.79	0.802			

Table 8: Results on ISIC when the sensitive attribute is age

	Age	Precision ↑	Recall ↑	F1-score ↑	SPD ↓	EOD ↓	AOD ↓
Original	≥ 60	0.71	0.689	0.68	0.246	0.15	0.174
	< 60	0.932	0.913	0.921			
Ours sketches w/o $\mathcal{L}_{\text{fair}}$	≥ 60	0.65	0.653	0.646	0.191	0.111	0.149
	< 60	0.896	0.801	0.839			
Ours sketches w/ $\mathcal{L}_{\text{fair}}$	≥ 60	0.647	0.592	0.612	0.223	0.136	0.148
	< 60	0.904	0.74	0.804			

Table 9: Results on ISIC when the sensitive attribute is skin tone

	Skin tone	Precision ↑	Recall ↑	F1-score ↑	SPD ↓	EOD ↓	AOD ↓
Original	Dark	0.853	0.803	0.822	0.134	0.201	0.203
	Light	0.935	0.932	0.932			
Ours sketches w/o $\mathcal{L}_{\text{fair}}$	Dark	0.782	0.72	0.742	0.134	0.179	0.181
	Light	0.847	0.796	0.818			
Ours sketches w/ $\mathcal{L}_{\text{fair}}$	Dark	0.779	0.698	0.714	0.144	0.133	0.155
	Light	0.843	0.808	0.82			

4 Conclusion and Limitation

In this paper, we propose to use image sketching methods to improve model fairness among several bias types (*i.e.* color, sex, age) based on the intuition that suitable sketching method can filter out the bias information while keeping semantic information for classification. We employ the latest image sketching method [4] with CLIP's [20] language encoder guidance to ensure that the images retain category and semantic information. Moreover, we also introduce an additional fairness loss to further improve model's fairness. We d have been made to evaluate our method, which shows that image sketching is a simple but effective way for fairness improvement.

We note that our method may cause accuracy drop, especially when we add the fairness loss $\mathcal{L}_{\text{fair}}$ as an additional supervision. This may be because that bluntly adding fairness makes the model more difficult to converge. In our further study, we're going to improve optimization strategies and combine this improvement for fairness with some sketch adjustment methods (*i.e.* style transfer), which may tackle the accuracy drop issue and even effectively improve the model fairness among all bias settings.

References

[1] Ehsan Adeli, Qingyu Zhao, Adolf Pfefferbaum, Edith V Sullivan, Li Fei-Fei, Juan Carlos Niebles, and Kilian M Pohl. Representation learning with statistical independence to mitigate bias. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 2513–2523, 2021.

[2] Rachel K. E. Bellamy, Kuntal Dey, Michael Hind, Samuel C. Hoffman, Stephanie Houde, Kalapriya Kannan, Pranay Lohia, Jacquelyn Martino, Sameep Mehta, Aleksandra Mojsilovic, Seema Nagar, Karthikeyan Natesan Ramamurthy, John Richards, Diptikalyan Saha, Prasanna Sattigeri, Moninder Singh, Kush R. Varshney, and Yunfeng Zhang. AI Fairness 360: An extensible toolkit for detecting, understanding, and mitigating unwanted algorithmic bias, Oct. 2018.

[3] Alex Beutel, Jilin Chen, Zhe Zhao, and Ed H. Chi. Data decisions and theoretical implications when adversarially learning fair representations. *CoRR*, abs/1707.00075, 2017.

[4] Caroline Chan, Fredo Durand, and Phillip Isola. Learning to generate line drawings that convey geometry and semantics. 2022.

[5] Noel C. F. Codella, David Gutman, M. Emre Celebi, Brian Helba, Michael A. Marchetti, Stephen W. Dusza, Aadi Kalloo, Konstantinos Liopyris, Nabin Mishra, Harald Kittler, and Allan Halpern. Skin lesion analysis toward melanoma detection: A challenge at the 2017 international symposium on biomedical imaging (isbi), hosted by the international skin imaging collaboration (isic). In *2018 IEEE 15th International Symposium on Biomedical Imaging (ISBI 2018)*, pages 168–172, 2018.

[6] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE Conference on Computer Vision and Pattern Recognition*, pages 248–255, 2009.

[7] Songwei Ge, Vedanuj Goswami, C. Lawrence Zitnick, and Devi Parikh. Creative sketch generation, 2020.

[8] David Ha and Douglas Eck. A neural representation of sketch drawings. In *International Conference on Learning Representations*, 2018.

[9] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 770–778, 2016.

[10] Yusuke Hirota, Yuta Nakashima, and Noa Garcia. Quantifying societal bias amplification in image captioning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 13450–13459, June 2022.

[11] Michael P. Kim, Amirata Ghorbani, and James Y. Zou. Multiaccuracy: Black-box post-processing for fairness in classification. *CoRR*, abs/1805.12317, 2018.

[12] Newton M. Kinyanjui, Timothy Odonga, Celia Cintas, Noel C. F. Codella, Rameswar Panda, Prasanna Sattigeri, and Kush R. Varshney. Fairness of classifiers across skin tones in dermatology. In Anne L. Martel, Purang Abolmaesumi, Danail Stoyanov, Diana Mateus, Maria A. Zuluaga, S. Kevin Zhou, Daniel Racoceanu, and Leo Joskowicz, editors, *Medical Image Computing and Computer Assisted Intervention – MICCAI 2020*, pages 320–329, Cham, 2020. Springer International Publishing.

[13] Mengtian Li, Zhe Lin, Radomír Měch, Ersin Yumer, and Deva Ramanan. Photo-sketching: Inferring contour drawings from images. In *WACV*, 2019.

[14] Xiaoxiao Li, Ziteng Cui, Yifan Wu, Lin Gu, and Tatsuya Harada. Estimating and improving fairness with adversarial learning. *arXiv preprint arXiv:2103.04243*, 2021.

[15] Ziwei Liu, Ping Luo, Xiaogang Wang, and Xiaoou Tang. Deep learning face attributes in the wild. In *Proceedings of International Conference on Computer Vision (ICCV)*, December 2015.

[16] Pranay Kr. Lohia, Karthikeyan Natesan Ramamurthy, Manish Bhide, Diptikalyan Saha, Kush R. Varshney, and Ruchir Puri. Bias mitigation post-processing for individual and group fairness. *CoRR*, abs/1812.06135, 2018.

[17] S. Mahdi H. Miangoleh, Sebastian Dille, Long Mai, Sylvain Paris, and Yağız Aksoy. Boosting monocular depth estimation models to high-resolution via content-adaptive multi-resolution merging. 2021.

[18] Novi Quadrianto, Viktoriia Sharmanska, and Oliver Thomas. Discovering fair representations in the data domain. In *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 8219–8228, 2019.

[19] Novi Quadrianto, Viktoriia Sharmanska, and Oliver Thomas. Discovering fair representations in the data domain. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2019.

[20] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. Learning transferable visual models from natural language supervision. In Marina Meila and Tong Zhang, editors, *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pages 8748–8763. PMLR, 18–24 Jul 2021.

[21] Vikram V Ramaswamy, Sunnie SY Kim, and Olga Russakovsky. Fair attribute classification through latent space de-biasing. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 9301–9310, 2021.

[22] Vikram V. Ramaswamy, Sunnie S. Y. Kim, and Olga Russakovsky. Fair attribute classification through latent space de-biasing. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2021.

[23] Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.

[24] Jifei Song, Kaiyue Pang, Yi-Zhe Song, Tao Xiang, and Timothy M Hospedales. Learning to sketch with shortcut cycle consistency. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 801–810, 2018.

[25] Philipp Tschandl, Cliff Rosendahl, and Harald Kittler. The HAM10000 dataset: A large collection of multi-source dermatoscopic images of common pigmented skin lesions. *CoRR*, abs/1803.10417, 2018.

[26] Yael Vinker, Ehsan Pajouheshgar, Jessica Y. Bo, Roman Christian Bachmann, Amit Haim Bermano, Daniel Cohen-Or, Amir Zamir, and Ariel Shamir. Clipasso: Semantically-aware object sketching, 2022.

[27] Zhibo Wang, Xiaowei Dong, Henry Xue, Zhifei Zhang, Weifeng Chiu, Tao Wei, and Kui Ren. Fairness-aware adversarial perturbation towards bias mitigation for deployed deep models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 10379–10388, June 2022.

[28] Depeng Xu, Shuhan Yuan, Lu Zhang, and Xintao Wu. Fairgan: Fairness-aware generative adversarial networks. In *2018 IEEE International Conference on Big Data (Big Data)*, pages 570–575. IEEE, 2018.

[29] Muhammad Bilal Zafar, Isabel Valera, Manuel Gomez Rogriguez, and Krishna P Gummadi. Fairness constraints: Mechanisms for fair classification. In *Artificial intelligence and statistics*, pages 962–970. PMLR, 2017.

[30] Brian Hu Zhang, Blake Lemoine, and Margaret Mitchell. Mitigating unwanted biases with adversarial learning. In *Proceedings of the 2018 AAAI/ACM Conference on AI, Ethics, and Society*, pages 335–340, 2018.

[31] Yi Zhang and Jitao Sang. Towards accuracy-fairness paradox: Adversarial example-based data augmentation for visual debiasing. In *Proceedings of the 28th ACM International Conference on Multimedia*, pages 4346–4354, 2020.

A Fairness evaluation metrics

Let x_i, y_i, z_i as the original input images, label, and bias sensitive attribute for every image *i* in the dataset. $S(x_i)$ can be represented as sketch image and $M(S(x_i))$ is the predicted label $\hat{y}_i$. The true positive rate (*TPR*) and false positive rate (*FPR*) are:

$$TPR_z = P(\hat{y}_i = y_i | z_i = z) \tag{5}$$

$$FPR_z = P(\hat{y}_i \neq y_i | z_i = z) \tag{6}$$

Based on [14, 27], *Statistical Parity Difference (SPD)*, *Equal Opportunity Difference (EOD)*, *Difference in Equalized Odds (DEO)*, and *Average Odds Difference (AOD)* are applied to measure and evaluate the fairness. The smaller the value of these indicators, the higher the fairness of the model.

- *Statistical Parity Difference (SPD)* measures the difference of probability in positive predicted label ($\hat{y} = 1$) between protected ($z = 1$) and unprotected ($z = 0$) attribute groups.

$$SPD = |P(\hat{y} = 1 | z = 1) - P(\hat{y} = 1 | z = 0)| \tag{7}$$

- *Equal Opportunity Difference (EOD)* measures the difference of probability in positive predicted label ($\hat{y} = 1$) between protected ($z = 1$) and unprotected ($z = 0$) attribute groups given positive target labels ($y = 1$). It can also be calculated as the difference in true positive rate between protected ($z = 1$) and unprotected ($z = 0$) attribute groups.

$$EOD = |TPR_{z=1} - TPR_{z=0}| = |P(\hat{y} = 1 | y = 1, z = 1) - P(\hat{y} = 1 | y = 1, z = 0)| \tag{8}$$

- *Difference in Equalized Odds (DEO)* measures the difference of probability in positive predicted label ($\hat{y} = 1$) between protected ($z = 1$) and unprotected ($z = 0$) attribute groups given target labels ($y \in \{0, 1\}$).

$$DEO = |P(\hat{y} = 1 | y, z = 1) - P(\hat{y} = 1 | y, z = 0)|, y \in \{0, 1\} \tag{9}$$

- *Average Odds Difference (AOD)* measures the average of difference in true positive rate (*TPR*) and false negative rate (*FPR*) between protected ($z = 1$) and unprotected ($z = 0$) attribute groups.

$$AOD = \frac{1}{2}(|TPR_{z=1} - TPR_{z=0}| - |FPR_{z=1} - FPR_{z=0}|) \tag{10}$$