Extended Abstract Track

Discretization Invariant Learning on Neural Fields

Editors: List of editors' names

Abstract

With the ability to generate and store continuous data in the form of neural fields (NFs), there is a need for neural networks that can process such fields in a manner that is invariant to the discretization of the data domain. We introduce NF-Net, a framework for learning discretization invariant maps on NFs of any type. Driven by numerical integration, NF-Nets can universally approximate a large class of maps between L^2 functions. We demonstrate our framework on NF classification, and examine the network's ability to generalize to different discretizations.

Keywords: Neural fields, discretization invariance, universal approximation

1. Introduction

Neural fields (NFs), which encode signals as the parameters of a neural network, have many useful properties. NFs can efficiently store and stream continuous data (Sitzmann et al., 2020b; Dupont et al., 2022; Takikawa et al., 2022), represent and render detailed 3D scenes at lightning speeds (Müller et al., 2022), and integrate data from a wide range of modalities (Gao et al., 2022). NFs are thus an appealing data representation for many applications.

However, current approaches for training networks on a dataset of NFs have major limitations. Converting such data to pixels to make them compatible with grid-based networks incurs interpolation errors and sacrifices many desirable properties of NFs. Alternatively, a network can be trained to predict the parameters of NFs (or a lower dimensional "modulation") and tailored for downstream tasks (Dupont et al., 2022; Mehta et al., 2021). But a network based on the parameter space of one type of NF is incompatible with other types, which limits interoperability. There remains a need for a network that can process arbitrary discretizations of NFs and is interoperable between different types of NFs.

In this paper we propose the *NF-Net*, a discretization invariant neural network for learning and inference on NFs (Figure 1). NF-Nets leverage numerical integration to yield desirable convergence properties, can be applied to any type of NF, and are universal approximators on a large class of maps. NF-Nets are a broad class of models that can be applied to classification, segmentation, and many other tasks.

2. Principles of NF-Nets

In this section we define an NF-Net, formalize discretization invariance, and derive properties that enable NF-Nets to serve as a general deep learning framework on continuous data. Specifically, NF-Nets are invariant to NF parameterization, are dense in a large class of maps between L^2 functions, and exhibit convergent empirical gradients.

Figure 1: The NF-Net processes an NF by evaluating it on an arbitrary discretization, which is used to perform numerical integration throughout the network. By treating the NF as a black box, we are not constrained by any particular type of NF, and need not be involved in the NF training process. This framework can be used for a broad range of tasks.

2.1. Preliminaries

Let Ω be a bounded measurable subset of a d-dimensional compact metric space. The most common case is $\Omega \subset \mathbb{R}^d$, and in the Appendix we consider the case of a d-dimensional manifold. Let $\mathcal{F}_c$ denote the space $L^2(\Omega, \mathbb{R}^c) = \{f : \Omega \to \mathbb{R}^c : \int_\Omega \|f\|^2 d\mu < \infty\}$. We refer to all maps $f \in \mathcal{F}_c$ as NFs, although such maps also encompass other types of signals and data formats. We call d the dimensionality of the NF and c the number of channels.[1]

Definition 1 *An NF-Net layer $\mathcal{H}$ is a bounded continuous map $\mathcal{F}_n \to \mathcal{F}_m$ (e.g., linear combinations of channels), or $\mathbb{R}^n \to \mathcal{F}_m$ (e.g., in a generative model), or $\mathcal{F}_n \to \mathbb{R}^m$ (e.g., in a classifier), or $\mathcal{F}_n \times \mathcal{F}_m \to \mathcal{F}_c$ (e.g., in style transfer) for some $n, m, c \in \mathbb{N}$. An NF-Net is a directed acyclic graph of such layers.[2]*

Proposition 2 *An NF-Net is invariant to the parameterization of the NF used to train it. If $f, g \in \mathcal{F}_c$ are equal in the sense that $f_i = g_i$ for all $i \in \{1, ..., c\}$, then any NF-Net or loss function on $\mathcal{F}_c$ maps f and g to the same output.*

This property follows directly from our definition of the NF-Net, and confers interoperability that is missing from hypernetwork or modulation-based learning approaches.

2.2. Discretization Invariance via Numerical Integration

The discretization of a neural field $f \in L^2(\Omega)$ is a point set $X \subset \Omega$ on which the NF is evaluated.[3] We say that the map $\mathcal{H}_\phi : L^2(\Omega) \to \mathbb{R}^n$ is discretizable if it induces a map $\mathfrak{H}_{\phi,X} : L^2(\Omega)/I_X \to \mathbb{R}^n$ for every discretization X, where I_X is the ideal of $L^2(\Omega)$ that vanishes at each $x \in X$. To achieve discretization invariance, we design functionals that preserve quantities under discretization in the following sense:

---

1. For example, an occupancy network (Mescheder et al., 2018) is 3-dimensional and has 1 channel. NeRF (Mildenhall et al., 2020) is 5-dimensional (world coordinates and view angles) and has 4 channels.

2. Note that many common loss functions also generalize naturally to the continuous domain as bounded continuous maps $\mathcal{F}_c \to \mathbb{R}$ or $\mathcal{F}_c \times \mathcal{F}_c \to \mathbb{R}$.

3. For simplicity we only characterize single-channel NFs and NF-Net layers, and in Appendix C we extend each of our results to the multi-channel case.

Extended Abstract Track

Definition 3 *A discretizable functional $\mathcal{H}_\phi : L^2(\Omega) \to \mathbb{R}^n$ is discretization invariant if for every discretization X and input f, the deviation of $\mathcal{H}_\phi$ from the induced map $\mathfrak{H}_{\phi,X}$ is bounded by the product of the variation[4] of f and the discrepancy[5] of X. A map $\bar{\mathcal{H}}_\phi : L^2(\Omega) \to L^2(\Omega)$ is discretization invariant if it is discretization invariant at each point in its image.*

This definition naturally leads to parameterizations of discretization invariant maps as integrals over Ω. In the $L^2(\Omega) \to \mathbb{R}$ case:

$$\mathcal{H}_\phi[f] = \int_\Omega h(x, f(x), \ldots, D^\alpha f(x); \phi) d\mu(x), \tag{1}$$

for a function h which is Fréchet differentiable at all $f \in L^2(\Omega)$, is of bounded variation in Ω for all f, is differentiable w.r.t. its parameters ϕ, and may depend on weak derivative $D^\alpha f = \frac{\partial^{|\alpha|} f}{\partial x_1^{\alpha_1} \ldots \partial x_n^{\alpha_n}}$ for multi-index α.[6] Its induced map for discretization X is then:

$$\mathfrak{H}_\phi[f|_X] = \sum_{x \in X} h(x, f(x), \ldots, D^\alpha f(x); \phi) w(x; \mu, X), \tag{2}$$

where $w(x; \mu, X)$ are optional quadrature weights, and Definition 3 is then automatically satisfied by the Koksma–Hlawka inequality. We can write the $L^2(\Omega) \to L^2(\Omega)$ case similarly. Such a parameterization opens up a rich toolkit of numerical integration methods, although here we focus on quasi-Monte Carlo (QMC) (Caflisch, 1998), which generates low discrepancy discretizations.

Remark 4 *If $\mathcal{H}_\phi$ is a discretization invariant map with discrete map $\mathfrak{H}_\phi$ and $f \in L^2(\Omega)$ has finite variation, $\lim_{N\to\infty} \mathfrak{H}_{\phi,X_N}(f|_{X_N}) = \mathcal{H}_\phi(f)$ under any sequence of discretizations $\{X_N\}_{N\in\mathbb{N}}$ whose discrepancy tends to 0 as $N \to \infty$.*

This property follows immediately from our definition of discretization invariance, and allows us to establish NF-Nets as universal approximators of a large class of maps between function spaces, stated in the following theorem (proved in Appendix C.1):

Theorem 5 (Universal Approximators) *Let $\mathcal{G}, \mathcal{G}'$ be subsets on $L^2(\Omega)$ restricted to piecewise smooth functions, with mild conditions on Ω. For every Lipschitz continuous map $\mathcal{R} : \mathcal{G} \to \mathcal{G}'$, there exists an NF-Net $\mathcal{T}$ that approximates it to arbitrary accuracy w.r.t. a finite measure ν on $\mathcal{G}$. As a corollary, every Lipschitz continuous map $\mathcal{G} \to \mathbb{R}^n$ or $\mathbb{R}^n \to \mathcal{G}$ can also be approximated by some NF-Net.*

---

4. See Appendix B for details on how we characterize the variation of a function.
5. The discrepancy of a point set measures how well-distributed it is on a domain. Discrepancy is high for point sets with regions of high and low density, and low for point sets with uniform density. See Appendix B for more information.
6. The dependence of h on weak derivatives up to order $k = |\alpha|$ requires that f is in the Sobolev space $W^{k,2}(\Omega)$.

3. Design and Implementation of NF-Nets

NF-Nets generalize any neural network that operates on a compact metric space, including point clouds, meshes, grids, and some types of graphs. Only a few types of NF-Net layers are needed to build highly expressive networks, and we focus here on layer parameterizations that mimic pixel-based layers, which even allows NF-Net to be initialized directly with the weights of a pre-trained convolutional neural network or vision transformer (details in Appendix G.1). We describe convolutional layers and multi-scale architectures here (also see Figure D.1), and other layers in Appendix D, including normalization, max pooling, tokenization and attention.

3.1. Training NF-Nets

As with discrete networks, the pipeline for training an NF-Net varies with the task. We outline steps for training a classifier and dense prediction model in Algorithms E.1 and F.2. When training an NF classifier, the discretization may be specified manually or sampled from a low discrepancy sampler to perform QMC integration. When training networks for dense prediction, the input and output discretizations will typically match the coordinates of the ground truth labels. At inference time, the network can be evaluated under any desired output discretization, making the output in effect an NF. Similar pipelines can be used to train NF-Net for other tasks such as scene editing, inverse problems, or representation learning.

4. Experiments

We analyze our model's performance as a classifier of NFs fit to natural images (ImageNet1k) under different discretizations. Appendix E provides more details on the experiment and Appendix F provides an additional experiment on using NF-Net to segment NFs.

Interestingly, changing discretization type at inference time has varying impact, sometimes only slightly degrading the performance of NF-Net (Table 4), and other times resulting in dramatic drops in performance. The greatest drop in accuracy is observed when shifting from a high discrepancy discretization (shrunk[7]) to a low discrepancy discretization (QMC). This suggests that discretization invariance only provides a weak guarantee on the stability of a model's behavior in the general case, and points to the importance of training on the right discretizations to attain a network that generalizes well to other discretizations.

Table 1: NF-Net-2 accuracy under discretizations of 1024 (32×32) points.

Train→Test Type	Accuracy
QMC→Grid	53.7%
Grid→QMC	54.4%
QMC→Shrunk	51.3%
Shrunk→QMC	33.9%
Grid→Grid	55.8%
QMC→QMC	56.6%
Shrunk→Shrunk	**57.0%**

---

7. The Shrunk discretization shrinks a low discrepancy point set towards the center of the image (each point $x_j \in [-1, 1]^2$ is mapped to $x_j^2 \text{sgn}(x_j)$). In image classification, the object of interest is often centered in the image, which may explain why the shrunk→shrunk discretization performs slightly better than QMC→QMC.

References

Christoph Aistleitner and Josef Dick. Low-discrepancy point sets for non-uniform measures, 2013. URL https://arxiv.org/abs/1308.5049.

Alexandre Boulch. Generalizing discrete convolutions for unstructured point clouds. *CoRR*, abs/1904.02375, 2019. URL http://arxiv.org/abs/1904.02375.

Luca Brandolini, Leonardo Colzani, Giacomo Gigante, and Giancarlo Travaglini. On the koksma–hlawka inequality. *Journal of Complexity*, 29(2):158–172, 2013. ISSN 0885-064X. doi: https://doi.org/10.1016/j.jco.2012.10.003. URL https://www.sciencedirect.com/science/article/pii/S0885064X12000854.

Russel E Caflisch. Monte carlo and quasi-monte carlo methods. *Acta numerica*, 7:1–49, 1998.

Eric R Chan, Marco Monteiro, Petr Kellnhofer, Jiajun Wu, and Gordon Wetzstein. pi-gan: Periodic implicit generative adversarial networks for 3d-aware image synthesis. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 5799–5809, 2021.

Tianping Chen and Hong Chen. Approximations of continuous functionals by neural networks with application to dynamic systems. *IEEE Transactions on Neural networks*, 4 (6):910–918, 1993.

Tianping Chen, Hong Chen, and Ruey wen Liu. Approximation capability in c(r /sup n/) by multilayer feedforward networks and related problems. *IEEE Transactions on Neural Networks*, 6(1):25–30, 1995. doi: 10.1109/72.363453.

Taco Cohen and Max Welling. Group equivariant convolutional networks. In *International conference on machine learning*, pages 2990–2999. PMLR, 2016a.

Taco S Cohen and Max Welling. Steerable cnns. *arXiv preprint arXiv:1612.08498*, 2016b.

Marius Cordts, Mohamed Omran, Sebastian Ramos, Timo Rehfeld, Markus Enzweiler, Rodrigo Benenson, Uwe Franke, Stefan Roth, and Bernt Schiele. The cityscapes dataset for semantic urban scene understanding. In *Proc. of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2016.

Abril Corona-Figueroa, Jonathan Frawley, Sam Bond-Taylor, Sarath Bethapudi, Hubert P. H. Shum, and Chris G. Willcocks. Mednerf: Medical neural radiance fields for reconstructing 3d-aware ct-projections from a single x-ray, 2022. URL https://arxiv.org/abs/2202.01020.

J. Deng, W. Dong, R. Socher, L.-J. Li, K. Li, and L. Fei-Fei. ImageNet: A Large-Scale Hierarchical Image Database. In *CVPR09*, 2009.

Emilien Dupont, Yee Whye Teh, and Arnaud Doucet. Generative models as distributions of functions. *CoRR*, abs/2102.04776, 2021. URL https://arxiv.org/abs/2102.04776.

Emilien Dupont, Hyunjik Kim, SM Eslami, Danilo Rezende, and Dan Rosenbaum. From data to functa: Your data point is a function and you should treat it like one. *arXiv preprint arXiv:2201.12204*, 2022.

Logan Engstrom, Andrew Ilyas, Hadi Salman, Shibani Santurkar, and Dimitris Tsipras. Robustness (python library), 2019. URL https://github.com/MadryLab/robustness.

Matthias Fey, Jan Eric Lenssen, Frank Weichert, and Heinrich Müller. Splinecnn: Fast geometric deep learning with continuous b-spline kernels. *CoRR*, abs/1711.08920, 2017. URL http://arxiv.org/abs/1711.08920.

Ruohan Gao, Yen-Yu Chang, Shivani Mall, Li Fei-Fei, and Jiajun Wu. Objectfolder: A dataset of objects with implicit visual, auditory, and tactile representations. In *CoRL*, 2021.

Ruohan Gao, Zilin Si, Yen-Yu Chang, Samuel Clarke, Jeannette Bohg, Li Fei-Fei, Wenzhen Yuan, and Jiajun Wu. Objectfolder 2.0: A multisensory object dataset for sim2real transfer, 2022. URL https://arxiv.org/abs/2204.02389.

Kurt Hornik. Approximation capabilities of multilayer feedforward networks. *Neural networks*, 4(2):251–257, 1991.

Nikola Kovachki, Zongyi Li, Burigede Liu, Kamyar Azizzadenesheli, Kaushik Bhattacharya, Andrew Stuart, and Anima Anandkumar. Neural operator: Learning maps between function spaces. *arXiv preprint arXiv:2108.08481*, 2021.

Abhijit Kundu, Kyle Genova, Xiaoqi Yin, Alireza Fathi, Caroline Pantofaru, Leonidas Guibas, Andrea Tagliasacchi, Frank Dellaert, and Thomas Funkhouser. Panoptic neural fields: A semantic object-aware neural scene representation, 2022. URL https://arxiv.org/abs/2205.04334.

Zongyi Li, Nikola Kovachki, Kamyar Azizzadenesheli, Burigede Liu, Kaushik Bhattacharya, Andrew Stuart, and Anima Anandkumar. Fourier neural operator for parametric partial differential equations. *arXiv preprint arXiv:2010.08895*, 2020.

Zhuang Liu, Hanzi Mao, Chao-Yuan Wu, Christoph Feichtenhofer, Trevor Darrell, and Saining Xie. A convnet for the 2020s. *CoRR*, abs/2201.03545, 2022. URL https://arxiv.org/abs/2201.03545.

Ilya Loshchilov and Frank Hutter. Fixing weight decay regularization in adam. *CoRR*, abs/1711.05101, 2017. URL http://arxiv.org/abs/1711.05101.

Julien NP Martel, David B Lindell, Connor Z Lin, Eric R Chan, Marco Monteiro, and Gordon Wetzstein. Acorn: Adaptive coordinate networks for neural scene representation. *arXiv preprint arXiv:2105.02788*, 2021.

Ishit Mehta, Michaël Gharbi, Connelly Barnes, Eli Shechtman, Ravi Ramamoorthi, and Manmohan Chandraker. Modulated periodic activations for generalizable local functional representations. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 14214–14223, 2021.

Lars M. Mescheder, Michael Oechsle, Michael Niemeyer, Sebastian Nowozin, and Andreas Geiger. Occupancy networks: Learning 3d reconstruction in function space. *CoRR*, abs/1812.03828, 2018. URL http://arxiv.org/abs/1812.03828.

Ben Mildenhall, Pratul P. Srinivasan, Matthew Tancik, Jonathan T. Barron, Ravi Ramamoorthi, and Ren Ng. Nerf: Representing scenes as neural radiance fields for view synthesis. *CoRR*, abs/2003.08934, 2020. URL https://arxiv.org/abs/2003.08934.

Thomas Müller, Alex Evans, Christoph Schied, and Alexander Keller. Instant neural graphics primitives with a multiresolution hash encoding. *arXiv:2201.05989*, January 2022.

Norman Müller, Andrea Simonelli, Lorenzo Porzi, Samuel Rota Bulò, Matthias Nießner, and Peter Kontschieder. Autorf: Learning 3d object radiance fields from single view observations, 2022. URL https://arxiv.org/abs/2204.03593.

Michael Niemeyer, Lars Mescheder, Michael Oechsle, and Andreas Geiger. Occupancy flow: 4d reconstruction by learning particle dynamics. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 5379–5389, 2019.

Michael Niemeyer, Lars Mescheder, Michael Oechsle, and Andreas Geiger. Differentiable volumetric rendering: Learning implicit 3d representations without 3d supervision. In *Proc. IEEE Conf. on Computer Vision and Pattern Recognition (CVPR)*, 2020.

Jeong Joon Park, Peter Florence, Julian Straub, Richard A. Newcombe, and Steven Lovegrove. Deepsdf: Learning continuous signed distance functions for shape representation. *CoRR*, abs/1901.05103, 2019. URL http://arxiv.org/abs/1901.05103.

David W. Romero, Robert-Jan Bruintjes, Jakub M. Tomczak, Erik J. Bekkers, Mark Hoogendoorn, and Jan C. van Gemert. Flexconv: Continuous kernel convolutions with differentiable kernel sizes. *CoRR*, abs/2110.08059, 2021a. URL https://arxiv.org/abs/2110.08059.

David W. Romero, Anna Kuzina, Erik J. Bekkers, Jakub M. Tomczak, and Mark Hoogendoorn. Ckconv: Continuous kernel convolution for sequential data. *CoRR*, abs/2102.02611, 2021b. URL https://arxiv.org/abs/2102.02611.

Nicholas Sharp, Souhaib Attaiki, Keenan Crane, and Maks Ovsjanikov. Diffusionnet: Discretization agnostic learning on surfaces. *ACM Transactions on Graphics (TOG)*, 41(3): 1–16, 2022.

Vincent Sitzmann, Michael Zollhöfer, and Gordon Wetzstein. Scene representation networks: Continuous 3d-structure-aware neural scene representations. *CoRR*, abs/1906.01618, 2019. URL http://arxiv.org/abs/1906.01618.

Vincent Sitzmann, Eric R. Chan, Richard Tucker, Noah Snavely, and Gordon Wetzstein. Metasdf: Meta-learning signed distance functions. *CoRR*, abs/2006.09662, 2020a. URL https://arxiv.org/abs/2006.09662.

Vincent Sitzmann, Julien N. P. Martel, Alexander W. Bergman, David B. Lindell, and Gordon Wetzstein. Implicit neural representations with periodic activation functions. *CoRR*, abs/2006.09661, 2020b. URL https://arxiv.org/abs/2006.09661.

Vincent Sitzmann, Semon Rezchikov, William T. Freeman, Joshua B. Tenenbaum, and Frédo Durand. Light field networks: Neural scene representations with single-evaluation rendering. *CoRR*, abs/2106.02634, 2021. URL https://arxiv.org/abs/2106.02634.

Towaki Takikawa, Alex Evans, Jonathan Tremblay, Thomas Müller, Morgan McGuire, Alec Jacobson, and Sanja Fidler. Variable bitrate neural fields. In *ACM SIGGRAPH 2022 Conference Proceedings*, pages 1–9, 2022.

Mingxing Tan and Quoc V. Le. Efficientnet: Rethinking model scaling for convolutional neural networks. *CoRR*, abs/1905.11946, 2019. URL http://arxiv.org/abs/1905.11946.

Matthew Tancik, Ben Mildenhall, Terrance Wang, Divi Schmidt, Pratul P. Srinivasan, Jonathan T. Barron, and Ren Ng. Learned initializations for optimizing coordinate-based neural representations. *CoRR*, abs/2012.02189, 2020a. URL https://arxiv.org/abs/2012.02189.

Matthew Tancik, Pratul P. Srinivasan, Ben Mildenhall, Sara Fridovich-Keil, Nithin Raghavan, Utkarsh Singhal, Ravi Ramamoorthi, Jonathan T. Barron, and Ren Ng. Fourier features let networks learn high frequency functions in low dimensional domains. *CoRR*, abs/2006.10739, 2020b. URL https://arxiv.org/abs/2006.10739.

Benjamin Ummenhofer, Lukas Prantl, Nils Thuerey, and Vladlen Koltun. Lagrangian fluid simulation with continuous convolutions. In *International Conference on Learning Representations*, 2019.

Shenlong Wang, Simon Suo, Wei-Chiu Ma, Andrei Pokrovsky, and Raquel Urtasun. Deep parametric continuous convolutional neural networks. *CoRR*, abs/2101.06742, 2021. URL https://arxiv.org/abs/2101.06742.

Appendix

Appendix A describes related work. Appendix B provides additional background on quasi-Monte Carlo integration and low discrepancy sequences, including details about the conditions under which our theoretical results hold. Appendix C provides proofs of the Universal Approximator and Convergent Empirical Gradients properties, as well as extensions of these properties from the single-channel case stated in the main text to multi-channel maps. Appendix D provides a detailed specification of NF-Net layers that enable NF-Nets to replicate the behavior of grid-based networks. Appendix E provides additional details of the classification experiment. Appendix F provides an additional experiment on NF segmentation. Appendix G provides several analyses including properties of NF-Nets under different discretizations. Appendix H describes limitations and directions for future work.

Appendix A. Related Work

Neural fields   Multilayer perceptrons (MLPs) can be trained to capture a wide range of continuous data with high fidelity. The most prominent domains include shapes (Park et al., 2019; Mescheder et al., 2018), objects (Niemeyer et al., 2020; Müller et al., 2022), and 3D scenes (Mildenhall et al., 2020; Sitzmann et al., 2021), but previous works also apply NFs to gigapixel images (Martel et al., 2021), volumetric medical images (Corona-Figueroa et al., 2022), acoustic data (Sitzmann et al., 2020b; Gao et al., 2021), tactile data (Gao et al., 2022), depth and segmentation maps (Kundu et al., 2022), and 3D motion (Niemeyer et al., 2019). Hypernetworks and modulation networks were developed for learning directly with NFs, and have been demonstrated on tasks including generative modeling, data imputation, novel view synthesis and classification (Sitzmann et al., 2020b, 2021; Tancik et al., 2020a; Sitzmann et al., 2019, 2020a; Mehta et al., 2021; Chan et al., 2021; Dupont et al., 2021, 2022). Hypernetworks use meta-learning to learn to produce the MLP weights of desired output NFs, while modulation networks predict modulations that can be used to transform the parameters of an existing NF or generate a new NF.

Discretization invariant networks   Building networks that are agnostic to the discretization of the space has been explored in several contexts. Neural operators learn maps between function spaces and can be used to solve partial differential equations in a discretization invariant manner (Li et al., 2020; Kovachki et al., 2021). On surface meshes, DiffusionNet (Sharp et al., 2022) uses the diffusion operator to achieve convergent behavior under mesh refinement. At the core of many other discretization invariant approaches is the continuous convolution, which maintains translation invariance and locality, and whose applications include modeling point clouds (Wang et al., 2021; Boulch, 2019), graphs (Fey et al., 2017), fluids (Ummenhofer et al., 2019), and sequential data (Romero et al., 2021b,a). In this work we develop a formal approach to characterize discretization invariant networks on general metric spaces, and then focus on the continuous convolution as a core layer for vision applications.

Approximation capabilities of neural networks   A fundamental result in approximation theory is that the set of single-layer neural networks is dense in a large space of functionals including $L^p(\mathbb{R}^n)$ (Hornik, 1991). Subsequent works designed constructive examples using various non-linear activations (Chen et al., 1995; Chen and Chen, 1993). While

this result is readily extended to multi-dimensional outputs, existing approximation results for the case of infinite dimensional outputs (e.g., $L^p(\mathbb{R}^n) \to L^p(\mathbb{R}^n)$) do not characterize the contribution of data discretization to the approximation error (Kovachki et al., 2021).

Appendix B. Quasi-Monte Carlo integration and low discrepancy sequences

Definition 6 (Koksma–Hlawka inequality) *A function $f \in L^2(\Omega)$ satisfies a Koksma–Hlawka inequality if for any point set $\{x_j : x_j \in \Omega\}$,*

$$\left| \frac{1}{N} \sum_{j=1}^{N} f(x_j) - \int_{\Omega} f(x)\,dx \right| \leq V(f)\,D(X), \tag{3}$$

for normalized measure dx, some notion of variation V of the function and some notion of discrepancy D of the point set.

The classical inequality gives a tight error bound for functions of bounded variation in the sense of Hardy-Krause (BVHK), a generalization of bounded variation to multivariate functions on $[0,1]^d$ which has bounded variation in each variable. Specifically, the variation is defined as:

$$V_{HK}(f) = \sum_{\alpha \in \{0,1\}^d} \int_{[0,1]^{|\alpha|}} \left| \frac{\partial^\alpha}{\partial x^\alpha} f(x_\alpha) \right| dx, \tag{4}$$

with $\{0,1\}^d$ the multi-indices and $x_\alpha \in [0,1]^d$ such that $x_{\alpha,j} = x_j$ if $j \in \alpha$ and $x_{\alpha,j} = 1$ otherwise. The classical inequality also uses the star discrepancy of the point set X, given by:

$$D^*(X) = \sup_{I \in J} \left| \frac{1}{N} \sum_{j=1}^{N} 1_I(x_j) - \lambda(I) \right|, \tag{5}$$

where J is the set of d-dimensional intervals that include the origin, and λ the Lebesgue measure.

A point set is called low discrepancy if its discrepancy is on the order of $O((\ln N)^d/N)$. Quasi-Monte Carlo calculates the sample mean using a low discrepancy sequence (see Fig. B.1 for examples in 2D), as opposed to the i.i.d. point set generated by standard Monte Carlo, which will generally be high discrepancy. Because the Koksma–Hlawka inequality is sharp, when estimating the integral of a BVHK function on $[0,1]^d$, the error of the QMC approximation decays as $O((\ln N)^d/N)$, in contrast to the error of the standard Monte Carlo approximation that decays as $O(N^{-1/2})$ (Caflisch, 1998).

However, BVHK is a rather restrictive class of functions defined on $[0,1]^d$ that excludes all functions with discontinuities. Brandolini et al. (2013) extended the Koksma–Hlawka inequality to two classes of functions defined below:

Piecewise smooth functions Let f be a smooth function on $[0,1]^d$ and Ω a Borel subset of $[0,1]^d$. Then $f|_\Omega$ is a piecewise smooth function with the Koksma–Hlawka inequality given by variation

$$V(f) = \sum_{\alpha \in \{0,1\}^d} 2^{d-|\alpha|} \int_{[0,1]^d} \left| \frac{\partial^\alpha}{\partial x^\alpha} f(x) \right| dx, \tag{6}$$

Extended Abstract Track

Figure B.1: Examples of low and high discrepancy sequences in 2D.

and discrepancy

$$D(X) = 2^d \sup_{I \subseteq [0,1]^d} \left| \frac{1}{N} \sum_{j=1}^{N} 1_{\Omega \cap I}(x_j) - \lambda(\Omega \cap I) \right|. \tag{7}$$

$W^{d,1}$ **functions on manifolds** Let M be a smooth compact d-dimensional manifold with normalized measure dx. Given local charts $\{\phi_k\}_{k=1}^{K}$, $\phi_k : [0,1]^d \to M$, the variation of a function $f \in W^{d,1}(M)$ is characterized as:

$$V(f) = c \sum_{k=1}^{K} \sum_{|\alpha| \le n} \int_{[0,1]^d} \left| \frac{\partial^\alpha}{\partial x^\alpha} (\psi_k(\phi_k(x)) f(\phi_k(x)) \right| dx, \tag{8}$$

with $\{\psi_k\}_{k=1}^{K}$ a smooth partition of unity subordinate to the charts, and constant $c > 0$ that depends on the charts but not on f. Defining the set of intervals in M as $J = \{U : U = \phi_k(I)$ for some k and $I \subseteq [0,1]^d\}$, with measure $\mu(U) = \lambda(I)$, the discrepancy of a point set $Y = \{y_j\}_{y=1}^{N}$ on M is:

$$D(Y) = \sup_{U \in J} \left| \frac{1}{N} \sum_{j=1}^{N} 1_U(y_j) - \mu(U) \right|. \tag{9}$$

The notion of discrepancy is not limited to the Lebesgue measure. The existence of low discrepancy point sets has been proven for non-negative, normalized Borel measures on $[0,1]^d$ due to Aistleitner and Dick (2013). An extension of our framework to non-uniform measures is a promising direction for future work (see Section H).

Appendix C. Proofs

C.1. Proof of Property 5 (Universal Approximator)

Definition 7 *Let $\mathcal{G}, \mathcal{G}'$ be subsets of $L^2(\Omega)$ restricted to compactly supported functions of absolute bounded variation. By this we mean there exists V^* such that every $f \in \mathcal{G} \cup \mathcal{G}'$ satisfies a Koksma–Hlawka inequality (3) with $V(|f|) < V^*$.*

$\mathcal{G}, \mathcal{G}'$ are bounded in L^1 norm since all their functions are compactly supported and bounded.

Consider a Lipschitz continuous map $\mathcal{R} : \mathcal{G} \rightarrow \mathcal{G}'$ such that $d(\mathcal{R}[f], \mathcal{R}[g])_{L^1} \leq M_0 d(f, g)_{L^1}$ for some constant M_0 and all $f, g \in \mathcal{G}$. Let $M = \max\{M_0, 1\}$.

Select a fixed point set $X = \{x_j\}_{j=1}^N$ in Ω with discrepancy $D(X) = \frac{\epsilon}{12(M+2)V^*}$. By (3) this yields:

$$\left| \frac{1}{N} \sum_{j=1}^N f(x_j) - \int_\Omega f(x)\,dx \right| \leq \frac{\epsilon}{12(M+2)}, \tag{10}$$

for all $f \in \mathcal{G} \cup \mathcal{G}'$.

Definition 8 *The projection* $\pi : f \mapsto \mathbf{f}$ *is a quotient map* $L^2(\Omega) \rightarrow L^2(\Omega)/\sim$ *under the equivalence relation* $f \sim g$ *iff* $f(x_j) = g(x_j)$ *for all* $x_j \in X$.

$L^2(\Omega)/\sim$ can be identified with $\mathbb{R}^N$, and thus can be given the normalized ℓ^1 norm:

$$\|\pi f\|_{\ell^1} = \frac{1}{N} \sum_{j=1}^N |f(x_j)|. \tag{11}$$

Definition 9 *Denote the preimage of* π *as* $\pi^{-1} : \mathbf{f}' \mapsto \{f' \in \mathcal{G}' : \pi f' = \mathbf{f}'\}$. *Invoking the axiom of choice, define the inverse projection* $\pi^{-1} : \pi \mathcal{G}' \rightarrow \mathcal{G}'$ *by a choice function over the sets* $\pi^{-1}(\pi \mathcal{G}')$.

Remark: Note that this inverse projection corresponds to some way of interpolating the N sample points such that the output is in $\mathcal{G}'$. Although our definition implies the existence of such an interpolator, we leave its specification as an open problem. Since Ω only permits discontinuities along a fixed Borel subset of $[0, 1]^d$, these boundaries can be specified *a priori* in the interpolator. Since all functions in $\mathcal{G}'$ are bounded and continuous outside this set, the interpolator can be represented by a bounded continuous map, hence it is expressible by an NF-Net layer.

Definition 10 π *generates a* σ-*algebra on* $\mathcal{G}$ *given by* $A = \{\pi^{-1}(S) : S \in L\}$, *with* L *the* σ-*algebra of Lebesgue measurable sets on* $\mathbb{R}^N$. *Because this* σ-*algebra depends on* ϵ *and the Lipschitz constant of* $\mathcal{R}$ *via the point set discrepancy, we may write it as* $A_{\epsilon, \mathcal{R}}$.

Remark: In this formulation, we let the tolerance ϵ and the Lipschitz constant of $\mathcal{R}$ dictate what subsets of $\mathcal{G}$ are measurable, and thus which measures on $\mathcal{G}$ are permitted. However, if the desired measure ν is more fine-grained than what is permitted by $A_{\epsilon, \mathcal{R}}$, then it is ν that should determine the number of QMC samples N, rather than ϵ or $\mathcal{R}$.

We now state the following lemmas which will be used to prove our universal approximation theorem.

Lemma 11 *There is a map* $\tilde{\mathcal{R}} : \pi \mathcal{G} \rightarrow \pi \mathcal{G}'$ *such that*

$$\int_\Omega \left| \mathcal{R}[f](x) - \pi^{-1} \circ \tilde{\mathcal{R}} \circ \pi[f](x) \right| dx = \frac{\epsilon}{6}. \tag{12}$$

Proof Let $g(x) = |f(x)|$ for $f \in \mathcal{G} \cup \mathcal{G}'$. Because (10) applies to $g(x)$, we have:

$$\left| \frac{1}{N} \sum_{j=1}^{N} g(x_j) - \int_{\Omega} g(x)\, dx \right| \leq \frac{\epsilon}{12(M+2)} \tag{13}$$

$$\left| \|\pi f\|_{\ell^1} - \|f\|_{L^1} \right| \leq \frac{\epsilon}{12(M+2)}. \tag{14}$$

Eqn. (14) also implies that for any $\mathbf{f} \in \pi\mathcal{G} \cup \pi\mathcal{G}'$, we have:

$$\left| \|\mathbf{f}\|_{\ell^1} - \left\|\pi^{-1}\mathbf{f}\right\|_{L^1} \right| \leq \frac{\epsilon}{12(M+2)}. \tag{15}$$

Combining (14) and (15), we obtain

$$\left| \|f\|_{L^1} - \left\|\pi^{-1} \circ \pi[f]\right\|_{L^1} \right| \leq \frac{\epsilon}{6(M+2)}. \tag{16}$$

By the triangle inequality and applying $\mathcal{R}$:

$$\int_{\Omega} \left| \mathcal{R}[f](x) - \pi^{-1} \circ \pi \circ \mathcal{R}[f](x) \right|\, dx \leq \frac{\epsilon}{6(M+2)}. \tag{17}$$

For any $f, g \in \mathcal{G}$ such that $\pi f = \pi g$, (14) tells us that $d(f, g)_{L^1}$ is at most $\epsilon/6(M+2)$. Recall M was defined such that $d(\mathcal{R}[f], \mathcal{R}[g])_{L^1} \leq M d(f, g)_{L^1}$ for any $\mathcal{R}$.

$$d(\pi \circ \mathcal{R}[f], \pi \circ \mathcal{R}[g])_{L^1} \leq \frac{M\epsilon}{6(M+2)} + \frac{\epsilon}{6(M+2)} \tag{18}$$

$$= \frac{(M+1)}{(M+2)} \frac{\epsilon}{6} \tag{19}$$

So defining:

$$\tilde{\mathcal{R}} = \arg\min_{H} d(H \circ \pi[f], \pi \circ \mathcal{R}[f])_{\ell^1}, \tag{20}$$

we have

$$\left| \tilde{\mathcal{R}} \circ \pi[f] - \pi \circ \mathcal{R}[f] \right| \leq \frac{(M+1)}{(M+2)} \frac{\epsilon}{6}. \tag{21}$$

Then by (17),

$$\int_{\Omega} \left| \mathcal{R}[f](x) - \pi^{-1} \circ \tilde{\mathcal{R}} \circ \pi[f](x) \right|\, dx \leq \frac{\epsilon}{6(M+2)} + \frac{(M+1)}{(M+2)} \frac{\epsilon}{6} \tag{22}$$

$$= \frac{\epsilon}{6}. \tag{23}$$

∎

Lemma 12 *Consider the extension of $\tilde{\mathcal{R}}$ to $\mathbb{R}^N \to \mathbb{R}^N$ in which each component of the output has the form:*

$$\tilde{\mathcal{R}}_j(\mathbf{f}) = \begin{cases} \mathcal{R}[\pi^{-1}\mathbf{f}](x_j) & \text{if } \mathbf{f} \in \pi\mathcal{G} \\ 0 & \text{otherwise.} \end{cases} \tag{24}$$

Then any finite measure ν on the measurable space $(\mathcal{G}, A)$ induces a finite measure μ on $(\mathbb{R}^N, L)$, and $\int_{\mathbb{R}^N} |\tilde{\mathcal{R}}_j(\mathbf{f})| \mu(d\mathbf{f}) < \infty$ for each j.

Proof Since the σ-algebra A on $\mathcal{G}$ is generated by π, the measure $\mu : \mu(\pi S) = \nu(S)$ for all $S \in A$ is finite and defined w.r.t. the Lebesgue measurable sets on $\pi\mathcal{G}$. Since $\pi\mathcal{G}$ can be identified with a measurable subset of $\mathbb{R}^N$, μ can be naturally extended to $\mathbb{R}^N$. Doing so makes it absolutely continuous w.r.t. the Lebesgue measure on $\mathbb{R}^N$.

To show $\tilde{\mathcal{R}}_j(\mathbf{f})$ is integrable, it is sufficient to show it is bounded and compactly supported.

$\mathcal{G}$ is bounded in the L^1 norm. Thus by (14), $\pi\mathcal{G}$ is bounded in the normalized ℓ_1 norm. The ℓ_1 norm in $\mathbb{R}^N$ is strongly equivalent to the uniform norm, so there is some compact set $[-c, c]^N$, $c > 0$ for which the extension of $\pi\mathcal{G}$ to $\mathbb{R}^N$ vanishes, so $\text{supp}(\tilde{\mathcal{R}}_j(\mathbf{f})) \subseteq [-c, c]^N$.

Similarly, $\pi\mathcal{G}'$ is bounded in the ℓ^1 norm, hence there exists c' such that $\tilde{\mathcal{R}}_j < c'$ for all j. ∎

Lemma 13 *For any finite measure μ absolutely continuous w.r.t. the Lebesgue measure on $\mathbb{R}^n$, $J \in L^1(\mu)$ and $\epsilon > 0$, there is a network $\mathcal{K}$ such that:*

$$\int_{\mathbb{R}^n} |J(\mathbf{f}) - \mathcal{K}(\mathbf{f})| \, \mu(d\mathbf{f}) < \frac{\epsilon}{2}. \tag{25}$$

Proof The following construction is adapted from lu2017expressive. Since J is integrable, there is a cube $E = [-c, c]^n$ such that:

$$\int_{\mathbb{R}^n \setminus E} |J(\mathbf{f})| \mu(d\mathbf{f}) < \frac{\epsilon}{8} \tag{26}$$

$$\|J - 1_E J\|_1 < \frac{\epsilon}{8}. \tag{27}$$

Case 1: J is non-negative on all of $\mathbb{R}^n$
Define the set under the graph of $J|_E$:

$$G_{E,J} \triangleq \{(\mathbf{f}, y) : \mathbf{f} \in E, y \in [0, J(\mathbf{f})]\}. \tag{28}$$

$G_{E,J}$ is compact in $\mathbb{R}^{n+1}$, hence there is a finite cover of open rectangles $\{R_i'\}$ satisfying $\mu(\cup_i R_i') - \mu(G_{E,J}) < \frac{\epsilon}{8}$ on $\mathbb{R}^n$. Take their closures, and extend the sides of all rectangles indefinitely. This results in a set of pairwise almost disjoint rectangles $\{R_i\}$. Taking only the rectangles $R = \{R_i : \mu(R_i \cap G_{E,J}) > 0\}$ results in a finite cover satisfying:

$$\sum_{i=1}^{|R|} \mu(R_i) - \mu(G_{E,J}) < \frac{\epsilon}{8}. \tag{29}$$

This implies:

$$\sum_{i=1}^{|R|} \mu(R_i) < \|J\|_1 + \frac{\epsilon}{8}, \tag{30}$$

and also,

$$\frac{\epsilon}{8} > \sum_{i=1}^{|R|} \int_{\mathbb{R}^n} 1_{R_i}(\mathbf{f}, J(\mathbf{f}))\, \mu(d\mathbf{f}) + \|J\|_1 \tag{31}$$

$$\geq \int_E |J(\mathbf{f}) - \sum_{i=1}^{|R|} 1_{R_i}(\mathbf{f}, J(\mathbf{f}))|\, \mu(d\mathbf{f}), \tag{32}$$

by the triangle inequality. For each $R_i = [a_{i1}, b_{i1}] \times \ldots [a_{in}, b_{in}] \times [\zeta_i, \zeta_i + y_i]$, let X_i be its first n components (i.e., the projection of R_i onto $\mathbb{R}^n$). Then we have

$$\int_E |J(\mathbf{f}) - \sum_{i=1}^{|R|} y_i 1_{X_i}(\mathbf{f})|\, \mu(d\mathbf{f}) < \frac{\epsilon}{8}. \tag{33}$$

Let $Y(\mathbf{f}) \triangleq \sum_{i=1}^{|R|} y_i 1_{X_i}(\mathbf{f})$. By the triangle inequality,

$$\int_{\mathbb{R}^n} |J(\mathbf{f}) - \mathcal{K}(\mathbf{f})|\, \mu(d\mathbf{f}) \leq \|J - 1_E J\|_1 + \|1_E J - Y\|_1 + \|\mathcal{K} - Y\|_1 \tag{34}$$

$$< \frac{\epsilon}{4} + \|\mathcal{K} - Y\|_1, \tag{35}$$

by (27) and (33). So it remains to construct $\mathcal{K}$ such that $\|\mathcal{K} - Y\|_1 < \frac{\epsilon}{4}$. Because 1_{X_i} is discontinuous at the boundary of the rectangle X_i, it cannot be produced directly from an NF-Net (recall that all layers are continuous maps). However, we can approximate it arbitrarily well with a piece-wise linear function that rapidly ramps from 0 to 1 at the boundary.

For fixed rectangle X_i and $\delta \in (0, 0.5)$, consider the inner rectangle $X_\delta \subset X_i$:

$$X_\delta = (a_1 + \delta(b_1 - a_1), b_1 - \delta(b_1 - a_1)) \times \cdots \times (a_n + \delta(b_n - a_n), b_n - \delta(b_n - a_n)), \tag{36}$$

where we omit subscript j for clarity. Letting $b'_i = b_i - \delta(b_i - a_i)$, define the function:

$$T(\mathbf{f}) = \prod_{i=1}^{n} \frac{1}{\delta} \left[\texttt{ReLU}(\delta - \texttt{ReLU}(\mathbf{f}_i - b'_i)) - \texttt{ReLU}(\delta - \texttt{ReLU}(\mathbf{f}_i - a_i)) \right], \tag{37}$$

where $\texttt{ReLU}(x) = \max(x, 0)$. $T(\mathbf{f})$ is a piece-wise linear function that ramps from 0 at the boundary of X_i to 1 within X_δ, and vanishes outside X_i. Note that

$$\|1_X - T\|_1 < \mu(X) - \mu(X_\delta) \tag{38}$$

$$= (1 - (1 - 2\delta)^n)\mu(X), \tag{39}$$

if μ is the Lebesgue measure. δ may need to be smaller under other measures, but this adjustment is independent of the input $\mathbf{f}$ so it can be specified *a priori*.

Recall that the function we want to approximate is $Y(\mathbf{f}) = \sum_{i=1}^{|R|} y_i 1_{X_i}(\mathbf{f})$. We can build NF-Net layers $\mathcal{K} : \mathbf{f} \mapsto \mathcal{K}(\mathbf{f}) = \sum_{i=1}^{|R|} y_i T_i(\mathbf{f})$, since this only involves linear combinations and ReLUs. Then,

$$\|\mathcal{K} - Y\|_1 = \int_{\mathbb{R}^n} \sum_{i=1}^{|R|} y_i \left(T_i(\mathbf{f}) - 1_{X_i}(\mathbf{f}) \right) d\mathbf{f} \tag{40}$$

$$= \sum_{i=1}^{|R|} y_i \| 1_{X_i} - T_i \|_1 \tag{41}$$

$$< (1 - (1 - 2\delta)^n) \sum_{i=1}^{|R|} y_i \mu(X_i) \tag{42}$$

$$= (1 - (1 - 2\delta)^n) \sum_{i=1}^{|R|} \mu(R_i) \tag{43}$$

$$< (1 - (1 - 2\delta)^n) \left(\|J\|_1 + \frac{\epsilon}{8} \right), \tag{44}$$

by (30). And so by choosing:

$$\delta = \frac{1}{2} \left(1 - \left(1 - \frac{\epsilon}{4} \left(\|J\|_1 + \frac{\epsilon}{8} \right)^{-1} \right)^{1/n} \right), \tag{45}$$

we have our desired bound $\|\mathcal{K} - Y\|_1 < \frac{\epsilon}{4}$ and thereby $\|J - \mathcal{K}\|_1 < \frac{\epsilon}{2}$.

Case 2: J is negative on some region of $\mathbb{R}^n$

Letting $J^+(\mathbf{f}) = \max(0, J(\mathbf{f}))$ and $J^-(\mathbf{f}) = \max(0, -J(\mathbf{f}))$, define:

$$G_{E,J}^+ \triangleq \{(\mathbf{f}, y) : \mathbf{f} \in E, y \in [0, J^+(\mathbf{f})]\} \tag{46}$$

$$G_{E,J}^- \triangleq \{(\mathbf{f}, y) : \mathbf{f} \in E, y \in [0, J^-(\mathbf{f})]\}. \tag{47}$$

As in (29), construct covers of rectangles R^+ over $G_{E,J}^+$ and R^- over $G_{E,J}^-$ each with bound $\frac{\epsilon}{16}$ and $\mathbb{R}^n$ projections X^+, X^-. Let:

$$Y^+(\mathbf{f}) = \sum_{i=1}^{|R^+|} y_i^+ 1_{X_i^+}(\mathbf{f}) \tag{48}$$

$$Y^-(\mathbf{f}) = \sum_{i=1}^{|R^-|} y_i^- 1_{X_i^-}(\mathbf{f}) \tag{49}$$

$$Y = Y^+ - Y^- \tag{50}$$

We can derive an equivalent expression to (33):

$$\frac{\epsilon}{8} > \int_E \left| J(\mathbf{f}) - \sum_{i=1}^{|R^+|} y_i^+ 1_{X_i^+}(\mathbf{f}) + \sum_{i=1}^{|R^-|} y_i^- 1_{X_i^-}(\mathbf{f}) \right| d\mathbf{f} \tag{51}$$

$$= \|1_E J - Y\|_1. \tag{52}$$

Extended Abstract Track

Similarly to earlier, we use (27) and (52) to get:

$$\int_{\mathbb{R}^n} |J(\mathbf{f}) - \mathcal{K}(\mathbf{f})| \, d\mathbf{f} < \frac{\epsilon}{4} + \|\mathcal{K} - Y\|_1. \tag{53}$$

Choosing $T_i^+(\mathbf{f})$ and $T_i^-(\mathbf{f})$ the piece-wise linear functions associated with X_i^+ and X_i^-, and:

$$\mathcal{K}(\mathbf{f}) = \sum_{i=1}^{|R^+|} y_i^+ T_i^+(\mathbf{f}) - \sum_{i=1}^{|R^-|} y_i^- T_i^-(\mathbf{f}), \tag{54}$$

we have:

$$\|\mathcal{K} - Y\|_1 = \int_{\mathbb{R}^n} \left| \sum_{i=1}^{|R^+|} y_i^+ \left(T_i^+(\mathbf{f}) - 1_{X_i^+}(\mathbf{f}) \right) - \sum_{i=1}^{|R^-|} y_i^- \left(T_i^-(\mathbf{f}) - 1_{X_i^-}(\mathbf{f}) \right) \right| d\mathbf{f}, \tag{55}$$

applying the triangle inequality,

$$\leq \sum_{i=1}^{|R^+|} y_i^+ \left\| 1_{X_i^+} - T_i^+ \right\|_1 + \sum_{i=1}^{|R^-|} y_i^- \left\| 1_{X_i^-} - T_i^- \right\|_1 \tag{56}$$

$$< (1 - (1 - 2\delta^+)^n) \sum_{i=1}^{|R^+|} y_i^+ \mu(X_i^+) + (1 - (1 - 2\delta^-)^n) \sum_{i=1}^{|R^-|} y_i^- \mu(X_i^-) \tag{57}$$

$$< (1 - (1 - 2\delta^+)^n) \left(\|J^+\|_1 + \frac{\epsilon}{16} \right) + (1 - (1 - 2\delta^-)^n) \left(\|J^-\|_1 + \frac{\epsilon}{16} \right). \tag{58}$$

By choosing:

$$\delta^+ = \frac{1}{2} \left(1 - \left(1 - \frac{\epsilon}{8} \left(\|J^+\|_1 + \frac{\epsilon}{16} \right)^{-1} \right)^{1/n} \right) \tag{59}$$

$$\delta^- = \frac{1}{2} \left(1 - \left(1 - \frac{\epsilon}{8} \left(\|J^-\|_1 + \frac{\epsilon}{16} \right)^{-1} \right)^{1/n} \right), \tag{60}$$

and proceeding as before, we arrive at the same bounds $\|\mathcal{K} - Y\|_1 < \frac{\epsilon}{4}$ and $\|J - \mathcal{K}\|_1 < \frac{\epsilon}{2}$.

Putting it all together, Algorithm C.1 implements the network logic for producing the function $\mathcal{K}$.

Algorithm C.1 NF-Net approximation of $\mathbf{f} \mapsto J(\mathbf{f})$

Setup **Input:** target function J, L_1 tolerance $\epsilon/2$

Choose rectangles $R_i^+ = [a_{i1}^+, b_{i1}^+] \times \ldots [a_{in}^+, b_{in}^+] \times [\zeta_i^+, \zeta_i^+ + y_i^+]$ satisfying (29) and R^- similarly

$\delta^+ \leftarrow \frac{1}{2}\left(1 - (1 - \frac{\epsilon}{8}\left(\|J^+\|_1 + \frac{\epsilon}{16}\right)^{-1})^{1/n}\right)$ $\quad$ $\delta^- \leftarrow \frac{1}{2}\left(1 - (1 - \frac{\epsilon}{8}\left(\|J^-\|_1 + \frac{\epsilon}{16}\right)^{-1})^{1/n}\right)$

Inference **Input:** discretized input $\mathbf{f} = \{\mathbf{f}_k\}_{k=1}^n$

$x \leftarrow (0, 0, 1, 0, 0)$ **for** rectangle $R_i^+ \in R^+$ **do**

> **for** dimension $k \in 1 : n$ **do**
>
>> $x \leftarrow (\mathbf{f}_k - b_{ik}^+ + \delta(b_{ik}^+ - a_{ik}^+), \mathbf{f}_k - a_{ik}^+, x_3, x_4, x_5)$ $\quad x \leftarrow \texttt{ReLU}(x)$ $\quad x \leftarrow (\delta - x_1, \delta - x_2, x_3, x_4, x_5)$ $\quad x \leftarrow \texttt{ReLU}(x)$ $\quad x \leftarrow (0, 0, x_3(x_1 - x_2)/\delta, x_4, x_5)$
>
> **end**
>
> $x \leftarrow (0, 0, 1, y_i^+ x_3 + x_4, x_5)$

end

for rectangle $R_i^- \in R^-$ **do**

> **for** dimension $k \in 1 : n$ **do**
>
>> $x \leftarrow (\mathbf{f}_k - b_{ik}^- + \delta(b_{ik}^- - a_{ik}^-), \mathbf{f}_k - a_{ik}^-, x_3, x_4, x_5)$ $\quad \ldots$
>
> **end**
>
> $x \leftarrow (0, 0, 1, x_4, y_i^- x_3 + x_5)$

end

Output: $x_4 - x_5$

We can provide x with access to $\mathbf{f}$ either through skip connections or by appending channels with the values $\{c + \mathbf{f}_k\}_{k=1}^n$ (which will be preserved under ReLU). ∎

Theorem 14 (Maps between Single-Channel NFs) *For any Lipschitz continuous map $\mathcal{R} : \mathcal{G} \to \mathcal{G}'$, any $\epsilon > 0$, and any finite measure ν w.r.t. the measurable space $(\mathcal{G}, A_{\epsilon,\mathcal{R}})$, there exists an NF-Net $\mathcal{T}$ that satisfies:*

$$\int_{\mathcal{G}} \|\mathcal{R}(f) - \mathcal{T}(f)\|_{L^1(\Omega)} \nu(df) < \epsilon. \tag{61}$$

Proof If ν is not normalized, the discrepancy of our point set needs to be further divided by $\max\{\nu(\mathcal{G}), 1\}$. We assume for the remainder of this section that ν is normalized. Perform the construction of Lemma 13 N times, each with a tolerance of $\epsilon/2N$. Choose a partition of unity $\{\psi_j\}$ for which $\psi_j(x_k) = \delta_{jk}$, and output N channels with the values $\{\mathcal{K}_j(\mathbf{f})\psi_j(\cdot)\}_{j=1}^N$. By summing these channels we obtain a network $\tilde{\mathcal{K}}$ that fully specifies the desired behavior of $\tilde{\mathcal{R}} : \mathbb{R}^N \to \mathbb{R}^N$, with combined error:

$$\int_{\mathbb{R}^N} \left\|\tilde{\mathcal{R}}(\mathbf{f}) - \tilde{\mathcal{K}}(\mathbf{f})\right\|_{\ell^1} \mu(d\mathbf{f}) < \frac{\epsilon}{2}. \tag{62}$$

Thus,

$$\int_{\mathcal{G}} \left|\frac{1}{N}\sum_{j=1}^N \tilde{\mathcal{R}} \circ \pi[f](x_j) - \tilde{\mathcal{K}} \circ \pi[f](x_j)\right| \nu(df) \leq \frac{\epsilon}{2}. \tag{63}$$

Extended Abstract Track

By (15) we have:

$$\int_{\mathcal{G}} \left| \int_{\Omega} \left| \pi^{-1} \circ \tilde{\mathcal{R}} \circ \pi[f](x) - \pi^{-1} \circ \tilde{\mathcal{K}} \circ \pi[f](x) \right| dx \right| \nu(df) \le \frac{\epsilon}{2} + \frac{\epsilon}{6(M+2)} \qquad (64)$$

By Lemma 11 we have:

$$\int_{\mathcal{G}} \int_{\Omega} \left| \mathcal{R}[f](x) - \pi^{-1} \circ \tilde{\mathcal{K}} \circ \pi[f](x) \right| dx \, \nu(df) \le \frac{\epsilon}{2} + \frac{\epsilon}{6(M+2)} + \frac{\epsilon}{6} \qquad (65)$$

And thus the network $\mathcal{T} = \pi^{-1} \circ \tilde{\mathcal{K}} \circ \pi$ gives us the desired bound:

$$\int_{\mathcal{G}} \|\mathcal{R}(f) - \mathcal{T}(f)\|_{L^1(\Omega)} \nu(df) < \epsilon. \qquad (66)$$

∎

Corollary 15 (Maps from NFs to vectors) *For any Lipschitz continuous map $\mathcal{R}$: $\mathcal{G} \to \mathbb{R}^n$, any $\epsilon > 0$, and any finite measure ν w.r.t. the measurable space $(\mathcal{G}, A_{\epsilon, \mathcal{R}})$, there exists an NF-Net $\mathcal{T}$ that satisfies:*

$$\int_{\mathcal{G}} \|\mathcal{R}(f) - \mathcal{T}(f)\|_{\ell_1(\mathbb{R}^n)} \nu(df) < \epsilon. \qquad (67)$$

Proof Let M_0 be the Lipschitz constant of $\mathcal{R}$ in the sense that $d(\mathcal{R}[f], \mathcal{R}[g])_{\ell^1} \le M_0 d(f,g)_{L^1}$. Let $M = \max\{M_0, 1\}$. There exists $\tilde{\mathcal{R}} : \pi\mathcal{G} \to \mathbb{R}^n$ such that $\left\| \tilde{\mathcal{R}} \circ \pi[f] - \mathcal{R}[f] \right\|_{\ell^1} \le \epsilon/12$. As in Lemma 12, consider the extension of $\tilde{\mathcal{R}}$ to $\mathbb{R}^N \to \mathbb{R}^n$ in which each component of the output has the form:

$$\tilde{\mathcal{R}}_j(\mathbf{f}) = \begin{cases} \mathcal{R}[\pi^{-1}\mathbf{f}]_j & \text{if } \mathbf{f} \in \pi\mathcal{G} \\ 0 & \text{otherwise.} \end{cases} \qquad (68)$$

Then for similar reasoning, ν on $\mathcal{G}$ induces a measure μ on $\mathbb{R}^N$ that is finite and absolutely continuous w.r.t. the Lebesgue measure, and $\int_{\mathbb{R}^N} |\tilde{\mathcal{R}}_j(\mathbf{f})| \mu(d\mathbf{f}) < \infty$ for each j.

We construct our $\mathbb{R}^N \to \mathbb{R}$ approximation n times with a tolerance of $\epsilon/2n$, such that:

$$\int_{\mathbb{R}^N} \left\| \tilde{\mathcal{R}}(\mathbf{f}) - \tilde{\mathcal{K}}(\mathbf{f}) \right\|_{\ell^1(\mathbb{R}^n)} \mu(d\mathbf{f}) < \frac{\epsilon}{2}. \qquad (69)$$

Applying (14), we find that the network $\mathcal{T} = \tilde{\mathcal{K}} \circ \pi$ gives us the desired bound:

$$\int_{\mathcal{G}} \|\mathcal{R}(f) - \mathcal{T}(f)\|_{\ell_1(\mathbb{R}^n)} \nu(df) < \epsilon. \qquad (70)$$

∎

Corollary 16 (Maps from vectors to NFs) *For any Lipschitz continuous map $\mathcal{R} : \mathbb{R}^n \to \mathcal{G}$ and any $\epsilon > 0$, there exists an NF-Net $\mathcal{T}$ that satisfies:*

$$\int_{\mathbb{R}^n} \|\mathcal{R}(x) - \mathcal{T}(x)\|_{L^1(\Omega)} dx < \epsilon. \qquad (71)$$

Proof Define the map $\tilde{\mathcal{R}} : \mathbb{R}^n \to \pi\mathcal{G} \subset \mathbb{R}^N$ by $\tilde{\mathcal{R}} = \pi \circ \mathcal{R}$. Since $\tilde{\mathcal{R}}$ is bounded and compactly supported, $\int_{\mathbb{R}^N} |\tilde{\mathcal{R}}_i(x)|dx < \infty$ for each i.

We construct a $\mathbb{R}^n \to \mathbb{R}$ approximation N times each with a tolerance of $\epsilon/2N$, such that:

$$\int_{\mathbb{R}^n} \left\| \tilde{\mathcal{R}}(x) - \tilde{\mathcal{K}}(x) \right\|_{L^1(\Omega)} dx < \frac{\epsilon}{2}. \tag{72}$$

Applying (15), we find that the network $\mathcal{T} = \pi^{-1} \circ \tilde{\mathcal{K}}$ gives us the desired bound:

$$\int_{\mathbb{R}^n} \|\mathcal{R}(x) - \mathcal{T}(x)\|_{L^1(\Omega)} dx < \epsilon. \tag{73}$$

∎

Denote the space of multi-channel NFs as $\mathcal{F}_c = \{f : \Omega \to \mathbb{R}^c : \int_\Omega \|f\|_1 dx < \infty, \ f_i \in \mathcal{G}$ for each $i\}$. Denote the norm on this space as:

$$\|f\|_{\mathcal{F}_c} = \int_\Omega \sum_{i=1}^c |f_i(x)|dx. \tag{74}$$

$\mathcal{F}_1$ is identified with $\mathcal{G}$.

Definition 17 (Concatenation) *Concatenation is a map from two NF channels $f_i, f_j \in \mathcal{G}$ to $[f_i, f_j] \in \mathcal{F}_2$. The concatenation of NFs can be defined inductively to yield $\mathcal{F}_n \times \mathcal{F}_m \to \mathcal{F}_{n+m}$ for any $n, m \in \mathbb{N}$.*

Remark: All maps $\mathcal{F}_n \times \mathcal{F}_m \to \mathcal{F}_c$ can be expressed as a concatenation followed by a map $\mathcal{F}_{n+m} \to \mathcal{F}_c$. A map $\mathbb{R}^n \to \mathcal{F}_m$ is also equivalent to m maps $\mathbb{R}^n \to \mathcal{G}$ followed by concatenation. Thus, we need only characterize the maps that take one multi-channel NF as input.

Considering the maps $\mathcal{F}_n \to \mathcal{F}_m$, we choose a lower discrepancy point set X on Ω such that the Koksma–Hlawka inequality yields a bound of $\epsilon/12mn(M+2)$. Let π project each component of the input to $\pi\mathcal{G}$, and π^{-1} inverts this projection under some choice function. We take A' to be the product σ-algebra generated from this π: $A' = \{E_1 \times \cdots \times E_c : E_1, \ldots, E_c \in A\}$ where A is the σ-algebra on $\mathcal{G}$ from Definition 10.

Corollary 18 (Maps between multi-channel NFs) *For any Lipschitz continuous map $\mathcal{R} : \mathcal{F}_n \to \mathcal{F}_m$, any $\epsilon > 0$, and any finite measure ν w.r.t. the measurable space $(\mathcal{F}_n, A'_{\epsilon,\mathcal{R}})$, there exists an NF-Net $\mathcal{T}$ that satisfies:*

$$\int_{\mathcal{F}_n} \|\mathcal{R}(f) - \mathcal{T}(f)\|_{\mathcal{F}_m} \nu(df) < \epsilon. \tag{75}$$

Proof The proof is very similar to that of Theorem 14. Our network now requires nN maps from $\mathbb{R}^{mN} \to \mathbb{R}$ each with error $\epsilon/2mnN$. Summing the errors across all input and output channels yields our desired bound. ∎

The multi-channel analogue of Corollary 15 is clear, and we state it here for completeness:

Extended Abstract Track

Corollary 19 (Maps from multi-channel NFs to vectors) *For any Lipschitz continuous map $\mathcal{R} : \mathcal{F}_n \to \mathbb{R}^m$, any $\epsilon > 0$, and any finite measure ν w.r.t. the measurable space $(\mathcal{F}_n, A'_{\epsilon,\mathcal{R}})$, there exists an NF-Net $\mathcal{T}$ that satisfies:*

$$\int_{\mathcal{F}_n} \|\mathcal{R}(f) - \mathcal{T}(f)\|_{\ell_1(\mathbb{R}^m)} \nu(df) < \epsilon. \tag{76}$$

C.2. Convergent Empirical Gradients

Here we establish that backpropagation is sound, by proving the convergence of derivatives through the empirical measure in the following sense:

Theorem 20 (Convergent Empirical Gradients) *An NF-Net permits backpropagation of its outputs with respect to its input as well as all its learnable parameters. Under a sequence of discretizations tending to 0 discrepancy, the gradients of each layer converge to the appropriate derivative under the measure on Ω.*

To establish convergence in the number of QMC samples N, let us suppose we have a family of sequences $\{X_N\}_{N \in \mathbb{N}} : X_N = \{x_j\}_{j=1}^N$ on Ω whose discrepancy converges to 0 as $N \to \infty$.

We note that no convergence statement is needed if the layer does not perform QMC integration. This includes layers which take $\mathbb{R}^n$ as input, as well as point-wise transformations. Then the (sub)derivatives with respect to inputs and parameters need only be well-defined at each point of the output in order to enable backpropagation.

Thus we consider a layer $\mathcal{H}_\phi$ which takes an NF f as input. By (**??**) and (**??**), it can be written as:

$$\mathcal{H}_\phi[f] = \int_\Omega H_\phi[f](x)dx. \tag{77}$$

We write the QMC estimate of $\mathcal{H}_\phi[f]$ under X_N as:

$$\hat{H}_\phi^N[f] = \frac{1}{N} \sum_{j=1}^N H_\phi[f](x_j), \tag{78}$$

and we call the derivatives of this QMC estimate the empirical derivatives of $\mathcal{H}_\phi[f]$. We are interested in proving the convergence of the empirical gradients of $\mathcal{H}_\phi[f]$ with respect to its input f as well as the parameters ϕ of the layer. As in Appendix C.1, we write $\pi f = \{f(x_j)\}_{j=1}^N$.

Theorem 21 *For any NF-Net layer $\mathcal{H}_\phi$ which takes an NF $f \in \mathcal{F}_m$ as input, the empirical gradient of $\mathcal{H}_\phi[f]$ w.r.t. its parameters ϕ is convergent in N:*

$$\lim_{N \to \infty} \left| \nabla_\phi \hat{H}_\phi^N[f] \right| < \infty. \tag{79}$$

Additionally, the empirical gradient of $\mathcal{H}_\phi[f]$ w.r.t. its discretized input πf is convergent in N:

$$\lim_{N \to \infty} \left| \nabla_{\pi f} \hat{H}_\phi^N[f] \right| < \infty. \tag{80}$$

Proof

NF to Vector: gradients w.r.t. parameters Consider the case of a layer $\mathcal{H}_\phi : \mathcal{F}_m \to \mathbb{R}^n$. As in (??), such a layer can be expressed as:

$$\mathcal{H}_\phi[f] = \int_\Omega h(x, f(x), \ldots, D^\alpha f(x); \phi) dx, \tag{81}$$

for some h parameterized by ϕ, with weak derivatives up to order $|\alpha|$ taken with respect to each channel.

If $\phi = (\phi_1, \ldots, \phi_K)$, then denote $\phi + \tau e_k = (\phi_1, \ldots, \phi_{k-1}, \phi_k + \tau, \phi_{k+1}, \ldots, \phi_K)$.

$$\lim_{N \to \infty} \frac{\partial}{\partial \phi_k} \hat{H}_\phi^N[f] = \lim_{N \to \infty} \frac{\partial}{\partial \phi_k} \left(\frac{1}{N} \sum_{j=1}^N H_\phi[f](x_j) \right) \tag{82}$$

$$= \lim_{N \to \infty} \lim_{\tau \to 0} \left(\frac{1}{\tau N} \sum_{j=1}^N H_{\phi+\tau e_k}[f](x_j) - H_\phi[f](x_j) \right) \tag{83}$$

$$= \lim_{\tau \to 0} \frac{1}{\tau} \int_\Omega h(x, f(x), ..., \phi + \tau e_k) - h(x, f(x), ..., \phi) dx \tag{84}$$

$$= \lim_{\tau \to 0} \frac{\mathcal{H}_{\phi+\tau e_k}[f] - \mathcal{H}_\phi[f]}{\tau} \tag{85}$$

$$= \frac{\partial}{\partial \phi_k} \mathcal{H}_\phi[f], \tag{86}$$

where (84) follows by eqn. (81) and the Moore-Osgood theorem. Thus the empirical gradient converges to the Jacobian of $\mathcal{H}_\phi$ w.r.t. each parameter, which is finite by assumption.

NF to NF: gradients w.r.t. parameters From (??), we stated that an NF-Net layer $\bar{\mathcal{H}}_{\phi'} : L^2(\Omega) \to L^2(\Omega)$ can be expressed as:

$$\bar{\mathcal{H}}_{\phi'}[f](x') = \int_\Omega \bar{h}(x, f(x), \ldots, D^\alpha f(x), x', f(x'), \ldots, D^\alpha f(x'); \phi') dx. \tag{87}$$

We can in fact follow the same steps as the NF to Vector case above, to arrive at:

$$\lim_{N \to \infty} \frac{\partial}{\partial \phi_k'} \left(\frac{1}{N} \sum_{j=1}^N \bar{H}_{\phi'}[f] \right) = \frac{\partial}{\partial \phi_k'} \bar{\mathcal{H}}_{\phi'}[f], \tag{88}$$

with equality at each point $x' \in \Omega$ and channel of the output NF.

NF input: gradients w.r.t. inputs Here we combine the NF to vector and NF to NF cases for brevity. For fixed $\tilde{x} \in \Omega$, the empirical derivative of $\mathcal{H}_\phi$ w.r.t. $f(\tilde{x})$ can be written:

$$\frac{\partial}{\partial f(\tilde{x})} \hat{H}_\phi^N[f] = \frac{\partial}{\partial f(\tilde{x})} \left(\frac{1}{N} \sum_{j=1}^N H_\phi[f](x_j) \right) \tag{89}$$

$$= \lim_{\tau \to 0} \frac{1}{\tau N} \sum_{j=1}^N H_\phi[f + \tau \psi_{\tilde{x}, N}](x_j) - H_\phi[f](x_j), \tag{90}$$

Extended Abstract Track

where $\psi_{\tilde{x},N}$ is any function in $W^{|\alpha|,1}(\Omega)$ that is 1 at $\tilde{x}$ and 0 at every $x_j \neq \tilde{x}$, and whose weak derivatives are 0 at every x_j. As an example, take the bump function which vanishes outside a small neighborhood of $\tilde{x}$ and smoothly ramps to 1 on a smaller neighborhood of $\tilde{x}$, making its weak derivatives 0 at $\tilde{x}$.

By (3) we know that the sequences $\left\|\hat{H}_\phi^N[f] - \mathcal{H}_\phi[f]\right\|$ and $\left\|\hat{H}_\phi^N[f + \tau\psi_{\tilde{x},N}] - \mathcal{H}_\phi[f + \tau\psi_{\tilde{x},N}]\right\|$ converge uniformly in N to 0 for any $\tau > 0$, where we can use the ℓ_1 norm for vector outputs or the L^1 norm for NF outputs. So for any $\epsilon > 0$ and any $\tau > 0$, we can choose N_0 large enough such that for any $N > N_0$:

$$\left\|\hat{H}_\phi^N[f + \tau\psi_{\tilde{x},N}] - \mathcal{H}_\phi[f + \tau\psi_{\tilde{x},N}]\right\| < \frac{\epsilon}{2}, \tag{91}$$

and

$$\left\|\hat{H}_\phi^N[f] - \mathcal{H}_\phi[f]\right\| < \frac{\epsilon}{2}. \tag{92}$$

Then,

$$\left\|\hat{H}_\phi^N[f + \tau\psi_{\tilde{x},N}] - \mathcal{H}_\phi[f + \tau\psi_{\tilde{x},N}]\right\| + \left\|\hat{H}_\phi^N[f] - \mathcal{H}_\phi[f]\right\| < \epsilon, \tag{93}$$

by the triangle inequality,

$$\left\|(\hat{H}_\phi^N[f + \tau\psi_{\tilde{x},N}] - \mathcal{H}_\phi[f + \tau\psi_{\tilde{x},N}]) - (\hat{H}_\phi^N[f] - \mathcal{H}_\phi[f])\right\| < \epsilon \tag{94}$$

$$\left\|\left(\hat{H}_\phi^N[f + \tau\psi_{\tilde{x},N}] - \hat{H}_\phi^N[f]\right) - (\mathcal{H}_\phi[f + \tau\psi_{\tilde{x},N}] - \mathcal{H}_\phi[f])\right\| < \epsilon, \tag{95}$$

hence $\left\|\left(\hat{H}_\phi^N[f + \tau\psi_{\tilde{x},N}] - \hat{H}_\phi^N[f]\right) - (\mathcal{H}_\phi[f + \tau\psi_{\tilde{x},N}] - \mathcal{H}_\phi[f])\right\|$ converges uniformly to 0. Since the distance between two vectors is 0 iff they are the same, we can write:

$$\lim_{N\to\infty} \hat{H}_\phi^N[f + \tau\psi_{\tilde{x},N}] - \hat{H}_\phi^N[f] = \lim_{N\to\infty} \mathcal{H}_\phi[f + \tau\psi_{\tilde{x},N}] - \mathcal{H}_\phi[f] \tag{96}$$

$$\lim_{\tau\to 0} \frac{1}{\tau} \lim_{N\to\infty} \left(\hat{H}_\phi^N[f + \tau\psi_{\tilde{x},N}] - \hat{H}_\phi^N[f]\right) = \lim_{\tau\to 0} \frac{1}{\tau} \lim_{N\to\infty} (\mathcal{H}_\phi[f + \tau\psi_{\tilde{x},N}] - \mathcal{H}_\phi[f]). \tag{97}$$

By the Moore-Osgood theorem,

$$\lim_{N\to\infty} \lim_{\tau\to 0} \frac{1}{\tau} \left(\hat{H}_\phi^N[f + \tau\psi_{\tilde{x},N}] - \hat{H}_\phi^N[f]\right) = \lim_{N\to\infty} \lim_{\tau\to 0} \frac{1}{\tau} (\mathcal{H}_\phi[f + \tau\psi_{\tilde{x},N}] - \mathcal{H}_\phi[f]) \tag{98}$$

$$\lim_{N\to\infty} \frac{\partial}{\partial f(\tilde{x})} \hat{H}_\phi^N[f] = \lim_{N\to\infty} d\mathcal{H}_\phi[f; \psi_{\tilde{x},N}]. \tag{99}$$

The limit on the right hand side is finite due to Fréchet differentiability of H_ϕ at all f.

Choose a family $\{\Psi_N\}_{N\in\mathbb{N}}$ of decreasing sequences of bump functions around each x_j, $\Psi_N = \{\psi_{x_j,N}\}_{j=1}^N$. An example of such a family is the (appropriately designed) partitions of unity with N elements.

Then the empirical gradient w.r.t. πf converges to the limit of the Gateaux derivatives of $\mathcal{H}_\phi$ w.r.t. the bump function sequences in this family. ∎

Theorem 22 *Chained empirical derivatives converge in N to the chained Gateaux derivatives.*

Proof Consider a two-layer NF-Net with NF input $f \mapsto (\mathcal{H}_\theta \circ \mathcal{H}_\phi)[f]$. For the case of derivatives w.r.t. the input, we would like to show the analogue of (99):

$$\lim_{N \to \infty} \frac{\partial}{\partial f(\tilde{x})} \left(\hat{H}_\theta^N \circ \hat{H}_\phi^N \right) [f] = \lim_{N \to \infty} d \left(\mathcal{H}_\theta \circ \mathcal{H}_\phi \right) [f; \psi_{\tilde{x}, N}], \tag{100}$$

where the bump function $\psi_{\tilde{x}, N}$ is defined similarly (1 at $\tilde{x}$ and 0 at each $x_j \neq \tilde{x}$).

$$\frac{\partial}{\partial f(\tilde{x})} \left(\hat{H}_\theta^N \circ \hat{H}_\phi^N \right) [f] = \frac{\partial}{\partial f(x)} \left(H_\theta \left[\hat{H}_\phi^N [f] \right] (x_j) \right) \tag{101}$$

$$= \lim_{\tau \to 0} \frac{1}{\tau} \left(H_\theta \left[\hat{H}_\phi^N [f + \tau \psi_{\tilde{x}, N}] \right] (x_j) - H_\theta \left[\hat{H}_\phi^N [f] \right] (x_j) \right) \tag{102}$$

as in (90).

By (3) we know $\left\| \mathcal{H}_\theta \left[\hat{H}_\phi^N [f + \tau \psi_{\tilde{x}, N}] \right] - \hat{H}_\theta \left[\hat{H}_\phi^N [f + \tau \psi_{\tilde{x}, N}] \right] \right\|$ converges to 0 in N for all $\tau > 0$ (where we can use the ℓ_1 norm for vector outputs or the L^1 norm for NF outputs), as does $\left\| \mathcal{H}_\theta \left[\hat{H}_\phi^N [f] \right] - \hat{H}_\theta \left[\hat{H}_\phi^N [f] \right] \right\|_{L^1}$. Reasoning as in (91)-(98), we have:

$$\lim_{N \to \infty} \lim_{\tau \to 0} \frac{1}{\tau} \left(\hat{H}_\theta \left[\hat{H}_\phi^N [f + \tau \psi_{\tilde{x}, N}] \right] - \hat{H}_\theta \left[\hat{H}_\phi^N [f] \right] \right) \tag{103}$$

$$= \lim_{\tau \to 0} \frac{1}{\tau} \lim_{N \to \infty} \left(\mathcal{H}_\theta \left[\hat{H}_\phi^N [f + \tau \psi_{\tilde{x}, N}] \right] - \mathcal{H}_\theta \left[\hat{H}_\phi^N [f] \right] \right) \tag{104}$$

$$= \lim_{N \to \infty} \lim_{\tau \to 0} \frac{1}{\tau} \left(\mathcal{H}_\theta \left[\mathcal{H}_\phi^N [f + \tau \psi_{\tilde{x}, N}] \right] - \mathcal{H}_\theta \left[\mathcal{H}_\phi^N [f] \right] \right) \tag{105}$$

Note that

$$d\mathcal{H}[f; \psi_{\tilde{x}, N}] = \frac{1}{\tau} \left(\mathcal{H}_\phi^N [f + \tau \psi_{\tilde{x}, N}] - \mathcal{H}_\phi^N [f] + o(\tau) \right) \tag{106}$$

$$\mathcal{H}_\phi^N [f + \tau \psi_{\tilde{x}, N}] = \mathcal{H}_\phi^N [f] + \tau d\mathcal{H}[f; \psi_{\tilde{x}, N}] + o(\tau). \tag{107}$$

Then we complete the equality in (100) as follows:

$$\text{LHS} = \lim_{N \to \infty} \frac{\partial}{\partial f(\tilde{x})} \left(\hat{H}_\theta^N \circ \hat{H}_\phi^N \right) [f] \tag{108}$$

$$= \lim_{N \to \infty} \lim_{\tau \to 0} \frac{1}{\tau} \left(\mathcal{H}_\theta \left[\mathcal{H}_\phi^N [f + \tau \psi_{\tilde{x}, N}] \right] - \mathcal{H}_\theta \left[\mathcal{H}_\phi^N [f] \right] \right) \tag{109}$$

$$= \lim_{N \to \infty} \lim_{\tau \to 0} \frac{1}{\tau} \left(\mathcal{H}_\theta \left[\mathcal{H}_\phi^N [f] + \tau d\mathcal{H}[f; \psi_{\tilde{x}, N}] \right] - \mathcal{H}_\theta \left[\mathcal{H}_\phi^N [f] \right] \right) \tag{110}$$

$$= \lim_{N \to \infty} d\mathcal{H}_\theta \left[\mathcal{H}_\phi[f]; d\mathcal{H}_\phi[f; \psi_{\tilde{x}, N}] \right] \tag{111}$$

$$= \lim_{N \to \infty} d \left(\mathcal{H}_\theta \circ \mathcal{H}_\phi \right) [f; \psi_{\tilde{x}, N}] \tag{112}$$

$$= \text{RHS}, \tag{113}$$

by the chain rule for Gateaux derivatives.

The case of derivatives w.r.t. parameters is straightforward. In the same way we used (91)-(98) to obtain (105), we have:

$$\lim_{N\to\infty} \frac{\partial}{\partial\phi_k}(\hat{H}_\theta^N \circ \hat{H}_\phi^N)[f] = \lim_{N\to\infty}\lim_{\tau\to0}\frac{1}{\tau}\left(\hat{H}_\theta^N\left[\hat{H}_{\phi+\tau e_k}^N[f]\right] - \hat{H}_\theta^N[\hat{H}_\phi[f]]\right) \tag{114}$$

$$= \lim_{\tau\to0}\frac{1}{\tau}\left(\mathcal{H}_\theta[\mathcal{H}_{\phi+\tau e_k}[f]] - \mathcal{H}_\theta[\mathcal{H}_\phi[f]]\right) \tag{115}$$

$$= \frac{\partial}{\partial\phi_k}(\mathcal{H}_\theta \circ \mathcal{H}_\phi)[f], \tag{116}$$

Inductively, the chained derivatives extend to an arbitrary number of layers. ∎

Since the properties of NF-Net layers extend to loss functions on NF-Nets, we can treat a loss function similarly to a layer, and write:

$$\mathcal{L}_{g'}[g] = \int_\Omega L[g,g'](x)dx \tag{117}$$

$$\hat{L}_{g'}^N[g] = \frac{1}{N}\sum_{j=1}^N L[g,g'](x_j) \tag{118}$$

$$\lim_{N\to\infty}\frac{\partial}{\partial f(\tilde{x})}\left(\hat{L}_{g'}^N \circ \hat{H}_\theta^N \circ \hat{H}_\phi^N\right)[f] = \lim_{N\to\infty} d\left(\mathcal{L}_{g'} \circ \mathcal{H}_\theta \circ \mathcal{H}_\phi\right)[f;\psi_{\tilde{x},N}], \tag{119}$$

where g' can be some other input to the loss function such as ground truth labels. Thus, we can state the following result.

Corollary 23 *The gradients of an NF-Net's loss function w.r.t. its inputs and all its parameters are convergent in the number of QMC sample points.*

Appendix D. NF-Net Layers Derived from Grid-Based Networks

We use c_{in} to denote the number of channels of an input NF and c_{out} to denote the number of channels of an output NF.

Convolution   For a measurable $S \subset \Omega$ and a polynomial basis $\{p_{j,\phi}\}_{j\geq0}$ that spans $L^2(S)$, S is the support of a polynomial convolutional kernel $K_\phi : \Omega \times \Omega \to \mathbb{R}$ defined by:

$$K_\phi(x,x') = \begin{cases} \sum_{j=0}^n p_{j,\phi}(x-x')^j & \text{if } x-x' \in S \\ 0 & \text{otherwise.} \end{cases} \tag{120}$$

for some chosen $n \in \mathbb{N}$. A convolution is the linear map $\mathcal{H}_\phi : L^2(\Omega) \to L^2(\Omega)$ given by:

$$\mathcal{H}_\phi[f] = \int_\Omega K_\phi(\cdot,x')f(x')dx'. \tag{121}$$

An MLP convolution is defined similarly except the kernel becomes $\tilde{K}_\phi(x,x') = \text{MLP}(x-x';\phi)$ in the non-zero case. While MLP kernels are favored over polynomial kernels in many applications due to their expressive power (Wang et al., 2021), polynomial bases can be

Figure D.1: NF-Nets generalize grid-based networks including convolutional neural networks and vision transformers to arbitrary discretizations of the input and output domains. Low discrepancy point sets used in quasi-Monte Carlo integration are amenable to the multi-scale structures often found in discrete networks. NF-Nets can also be initialized directly from pre-trained discrete networks.

used to construct filters satisfying desired properties such as group equivariance (Cohen and Welling, 2016a,b), k-Lipschitz continuity, or boundary conditions.

A multi-channel convolution layer aggregates information locally and across channels. It has $c_{\text{in}}c_{\text{out}}$ learned filters K_{ij}, which are defined on some support S which may be a ball or orthotope. The layer also learns scalar biases b_j for each output channel:

$$g_j = \sum_{i=1}^{c_{\text{in}}} K_{ij} * f_i + b_j, \tag{122}$$

with $*$ the continuous convolution as in (121).

To transfer weights from a discrete convolutional layer, K can be parameterized as a rectangular B-spline surface that interpolates the weights (Figure D.1 left). To replicate the behavior of a discrete convolution layer with odd kernel size, S is zero-centered. For even kernel size, we shift S by half the dimensions of a pixel. We use a 2nd order B-spline for 3×3 filters and 3rd order for larger filters. We use deBoor's algorithm to evaluate the spline at intermediate points.

Different padding behaviors from the discrete case are treated differently. Zero-padding is replicated by scaling $\mathcal{H}[f](x)$ by $\frac{|(S+x)\cap\Omega|}{S+x}$ where $S + x$ is the kernel support S translated by x. For reflection padding, the value of the NF at points outside its domain are calculated by reflection. For no padding, the NF's domain is reduced accordingly, dropping all sample points that are no longer on the new domain.

Multi-scale architectures Many discretizations permit multi-scale structures by subsampling the discretization. Under QMC, downsampling is easily implemented by truncating the list of coordinates in the low-discrepancy sequence to the desired number of terms, as the truncated sequence is itself low-discrepancy. Similarly, upsampling is implemented by extending the low-discrepancy sequence to the desired number of terms, then perform-

ing nearest neighbor interpolation[8]. Since downsampling and upsampling are both specified with respect to the same discretization, NF-Nets can use multi-scale structures with residual or skip connections (Figure D.1 right).

Linear combinations of channels Linear combinations of channels mimic the function of 1×1 convolutional layers in conventional networks. For learned scalar weights W_{ij} and biases b_j:

$$g_j(x) = \sum_{i=1}^{c_{\text{in}}} W_{ij} f_i(x) + b_j, \tag{123}$$

for all $x \in \Omega$. These weights and biases can be straightforwardly copied from a 1×1 convolutional layer to obtain the same behavior. One can also adopt a normalized version, sometimes used in attention-based networks:

$$W_{ij} = \frac{w_{ij}}{\sum_{k=1}^{c_{\text{in}}} w_{kj}} \tag{124}$$

Normalization All forms of layer normalization readily generalize to the continuous setting by estimating the statistics of each channel with QMC integration, then applying point-wise operations. These layers typically rescale each channel to have some mean m_i and standard deviation s_i.

$$\mu_i = \int_\Omega f_i(x) dx \tag{125}$$

$$\sigma_i^2 = \int_\Omega f_i(x)^2 dx - \mu_i^2 \tag{126}$$

$$g_i(x) = \frac{f_i(x) - \mu_i}{\sigma_i + \epsilon} \times s_i + m_i, \tag{127}$$

where we assume dx is normalized and $\epsilon > 0$ is a small constant. Just as in the discrete case, μ_i and σ_i^2 can be a moving average of the means and variances observed over the course of training different NFs, and they can also be averaged over a minibatch of NFs (batch normalization) or calculated per datapoint (instance normalization). Mean m_i and standard deviation s_i can be learned directly (batch normalization), conditioned on other data (adaptive instance normalization), or fixed at 0 and 1 respectively (instance normalization).

Max pooling Max pooling is only a well-defined NF-Net layer if each NF channel is in $L^\infty(\Omega)$. Assuming this is the case, there are two natural generalizations of the max pooling layer to a collection of points: 1) assigning each point to the maximum of its k nearest neighbors, and 2) taking the maximum value within a fixed-size window around each point. However, both of these specifications change the output's behavior as the density of points increases. In the first case, nearest neighbors become closer together so pooling occurs over smaller regions where there is less total variation in the NF. In the second case, the empirical maximum increases monotonically as the NF is sampled more finely within each window. Because we may want to change the number of sampling points on the fly, both of these behaviors are detrimental.

---

8. Although other types of interpolation on rectilinear grids do not translate directly to a collection of points, we can replicate their behavior at fixed scale using an appropriately designed convolution filter.

If we consider the role of max pooling as a layer that shuttles gradients through a strong local activation, then it is sufficient to use a fixed-size window with some scaling factor that mitigates the impact of changing the number of sampling points. Consider the following simplistic model: assume each point in a given patch of an NF channel is an i.i.d. sample from $\mathcal{U}([-b, b])$. Then the maximum of N samples $\{f_i(x_j)\}_{j=1}^N$ is on average $\frac{N-1}{N+1}b$. So we can achieve an "unbiased" max pooling layer by taking the maximum value observed in each window and scaling it by $\frac{N+1}{N-1}$ (if $N = 1$ or our empirical maximum is negative then we simply return the maximum), then (optionally) multiplying a constant to match the discrete layer.

To replicate the behavior of a discrete max pooling layer with even kernel size, we shift the window by half the dimensions of a pixel, just as in the case of convolution.

Tokenization To tokenize an NF, we choose a finite set of non-overlapping regions $\omega_j \subset \Omega$ of equal measure such that $\cup_j \omega_j = \Omega$. We apply the indicator function of each set to each channel f_i. An embedding of each $f_i|_{\omega_j}$ into $\mathbb{R}^n$ can be obtained by taking its inner product with a polynomial function whose basis spans each $L^2(\omega_j)$. To replicate a pre-trained embedding matrix, we interpolate the weights with B-spline surfaces.

Average pooling An average pooling layer performs a continuous convolution with a box filter, followed by downsampling. To reproduce a discrete average pooling with even kernels, the box filter is shifted, similarly to max pooling.

An adaptive average pooling layer can be replicated by tokenizing the NF and taking the mean of each token to produce a vector of the desired size.

Parametric functions in $L^2(\Omega)$ There are several choices of parametric functions in $L^2(\Omega)$. Such functions can enable an NF to be modulated by taking its elementwise product with the function, or for global information to be aggregated in a learned manner by taking its inner product with the function. If Ω is a subset of $[a, b]^d$, one can use a separable basis defined by the product of rescaled 1D Legendre polynomials along each dimension. If Ω is a d-ball, we can use the Zernike polynomial basis. For any Ω, the function can be represented as an MLP.

Attention layer There are various ways to replicate the functionality of an attention layer. Here we present an approach that preserves the domain. For some $d_k \in \mathbb{N}$ consider a self-attention layer with $c_{\text{in}}d_k$ parametric functions $q_{ij} \in L^2(\Omega)$, $c_{\text{in}}d_k$ parametric functions $k_{ij} \in L^2(\Omega)$, and a convolution with d_k output channels, produce the output NF g as:

$$Q_j = \langle q_{ij}, f_i \rangle \tag{128}$$

$$K_j = \langle k_{ij}, f_i \rangle \tag{129}$$

$$V[f] = \sum_{i=1}^{c_{\text{in}}} v_{ij} * f_i + b_j \tag{130}$$

$$g(x) = \texttt{softmax}\left(\frac{QK^T}{\sqrt{d_k}}\right) V[f](x) \tag{131}$$

A cross-attention layer generates queries from a second input NF. A multihead-attention layer generates several sets of (Q, K, V) triplets and takes the softmax of each set separately.

Activation Layer Pointwise nonlinearities are identical to the discrete case. We use rectified linear units (ReLU) for all our models.

Data augmentation Most data augmentation techniques, including spatial transformations, point-wise functions and normalizations, translate naturally to NFs. Furthermore, spatial transformations are efficient and do not incur the usual cost of interpolating back to the grid. This suggests that NF-Nets may benefit from new data augmentation methods such as adding Gaussian noise to the coordinates of QMC sample points.

Appendix E. NF Classification

Algorithm E.1 Training for Classification

Input: network $\mathcal{T}_\theta$, NF/label dataset $\mathcal{D}$, classifier loss $\mathcal{L}$, discretization x

For step $s \in 1 : N_{\text{steps}}$ **do**

- NFs f_i, labels $y_i \leftarrow \text{minibatch}(\mathcal{D})$

- Label estimates $\hat{y}_i \leftarrow \mathcal{T}_\theta(f_i; x)$

- Backpropagate $\mathcal{L}(\hat{y}_i, y_i)$ to update θ

Output: trained network $\mathcal{T}_\theta$

We perform classification on a dataset of 8,400 NFs fit to a subset of ImageNet1k (Deng et al., 2009), with 700 samples from each of 12 superclasses (Engstrom et al., 2019). The 12 superclasses (dog, structure/construction, bird, clothing, wheeled vehicle, reptile, carnivore, insect, musical instrument, food, furniture, primate) are based on the big_12 dataset (Engstrom et al., 2019), which is in turn derived from the WordNet hierarchy.

Table E.1: NF classifier top-3 accuracy at two resolutions on ImageNet-Big12.

Model Type	32×32	64×64
2-layer CNN	**59.8%**	54.1%
NF-Net-2 (ours)	56.6%	**55.2%**
4-layer CNN	**65.7%**	53.5%
NF-Net-4 (ours)	57.4%	**56.4%**

For each class we train on 500 SIRENs (Sitzmann et al., 2020b) and evaluate on 200 Gaussian Fourier feature networks (Tancik et al., 2020b). Note that training and testing on different NF types is not possible for hypernetwork or modulation-based approaches. We fit SIREN (Sitzmann et al., 2020b) to each image in ImageNet using 5 fully connected layers with 256 channels and sine non-linearities, trained for 2000 steps with an Adam optimizer at a learning rate of 10^{-4}. It takes coordinates on $[-1, 1]^2$ and produces RGB values in $[-1, 1]^3$. We fit Gaussian Fourier feature (Tancik et al., 2020b) networks using 4 fully connected layers with 256 channels with ReLU activations. It takes coordinates on $[0, 1]^2$ and produces RGB values in $[0, 1]^3$. The average pixel-wise error of SIREN is $3 \cdot 10^{-4} \pm 2 \cdot 10^{-4}$, compared to $1.6 \cdot 10^{-2} \pm 8 \cdot 10^{-3}$ for Gaussian Fourier feature networks. The difference in quality is visible at high resolution, but indistinguishable at low resolution (Fig. E.1).

We train NF-Nets with 2 and 4 MLP convolutional layers (NF-Net-2 and NF-Net-4), as well as convolutional neural networks (CNNs) with equivalent architectures. Each network is trained for 8K iterations with an AdamW optimizer (Loshchilov and Hutter, 2017) and a learning rate of 10^{-3}. NF-Net-2 uses strided MLP convolutions, a global average pooling

Figure E.1: Comparison of SIREN (left) and Gaussian Fourier feature network (right) representations of an image, rendered at 256×256 resolution. The Fourier feature network's representation is slightly blurrier (compare the tree bark), but this effect is not noticeable at lower resolutions.

layer, then two fully connected layers. NF-Net-4 adds a residual block with two MLP convolutions after the strided convolutions. At training time, the CNNs sample NFs along the 32×32 grid while NF-Nets sample 1024 points generated from a scrambled Sobol sequence. We evaluate each model with top-3 accuracy at the same resolution as well as at higher resolution (64×64 or 4096 points).

NF-Nets somewhat underperform their CNN counterparts (Table E), and the gap in performance is larger for the deeper models. However, our discretization invariant model better generalizes to higher-resolution images, where it outperforms CNNs on images at twice the resolution and has a very small drop in performance compared to the resolution it was trained on.

Appendix F. NF Semantic Segmentation

Algorithm F.2 Training for Dense Prediction

Input: network $\mathcal{T}_\theta$, NF/label dataset $\mathcal{D}$ with dense coordinate-label pairs, task-specific loss $\mathcal{L}$
For step $s \in 1 : N_{\text{steps}}$ **do**

- NFs f_i, coordinates-label pairs $(x_{ij}, y_{ij}) \leftarrow \text{minibatch}(\mathcal{D})$
- Output NFs $g_i \leftarrow \mathcal{T}_\theta[f_i]$
- Point label estimates $\hat{y}_{ij} \leftarrow g_i(x_{ij})$
- Backpropagate $\mathcal{L}(\hat{y}_{ij}, y_{ij})$ to update θ

Output: trained network $\mathcal{T}_\theta$

Extended Abstract Track

We perform pixel-wise segmentation on SIRENs fit to street view images from Cityscapes (Cordts et al., 2016), grouping the segmentation labels into 7 categories. SIREN is trained on Cityscapes images for 2500 steps, using the same architecture and settings as ImageNet. The average pixel-wise error is $3.6 \cdot 10^{-4} \pm 1.8 \cdot 10^{-4}$. We train on 2975 NFs with coarsely annotated segmentations only, and test on 500 NFs with both coarse and fine annotations (Fig. F.1). Discrete models sample the 48×96 grid, and the NF-Nets sample 4608 points. We compare the performance of 3 and 5 layer NF-Nets and fully convolutional networks (FCNs). NF-Net-3 uses three MLP convolutional layers at the same resolution. NF-Net-5 uses a strided MLP convolution to perform downsampling and nearest neighbor interpolation for upsampling. There is a residual connection between the higher resolution layers. Networks are trained for 10K iterations with a learning rate of 10^{-3}. We evaluate each model based on mean intersection over union (mIoU) and pixel-wise accuracy (PixAcc).

Table F.1: NF segmentation performance (Cityscapes (Cordts et al., 2016)).

Model Type	Coarse Segs		Fine Segs	
	mIoU	PixAcc	mIoU	PixAcc
3-layer FCN	0.409	69.6%	0.374	63.6%
NF-Net-3 (ours)	**0.471**	**78.5%**	**0.417**	**69.4%**
5-layer FCN	**0.488**	**79.4%**	**0.436**	**72.5%**
NF-Net-5 (ours)	0.443	77.7%	0.394	68.4%

NF-Net-3 outperforms the equivalent FCN, and avoids confusing features such as shadows and road markings (Fig. F.1). However, the performance deteriorates when we make the model deeper with a downsampling and upsampling layer (NF-Net-5), and the FCN surpasses both NF-Nets (Table F.1). This echoes the difficulty in scaling NF-Nets observed in classification, and suggests that additional innovations in architecture or training methods are needed for deeper NF-Nets.

Figure F.1: Cityscapes NF segmentations for models trained on coarse segs only. NF-Net produces NF segmentations, which can be evaluated at the subpixel level.

Table G.1: Pre-trained models fine-tuned on ImageNet NF classification.

Model Type	Accuracy
EfficientNet (Tan and Le, 2019)	**66.4%**
NF-Net-EN	48.1%

Table G.2: Pre-trained models fine-tuned on Cityscapes segmentation.

Model Type	Mean IoU	Pixel Accuracy
ConvNexT (Liu et al., 2022)	**0.429**	68.1%
NF-Net-CN	0.376	**68.7%**

Appendix G. Analysis

G.1. Initialization with discrete networks

When an NF-Net is initialized with a large pre-trained discrete network, its outputs are similar[9] by construction. However, the behavior of the pre-trained network is not preserved when the NF-Net switches to QMC – even tiny perturbations from the regular grid are sufficient to change a classifier's predictions. Although the effect on the output of a single layer is much lower than the signal, small differences in each layer accumulate to exert a large influence on the final output. In addition, we find that once grid sampling is abandoned, large NF-Nets cannot easily be fine-tuned to restore the behavior of the discrete network used to initialize it. This suggests that the optimization landscape of NF-Nets may differ substantially from that of discrete networks, and perhaps the approach for learning maps between L^2 functions requires fundamentally different strategies than those for learning maps between discrete functions, even when the functions represent the same underlying signals.

Figure G.2 illustrates that the behavior of a pre-trained NF-Net is not preserved when its sampling scheme switches to QMC. For a NF-Net initialized with a truncated EfficientNet, its outputs deviate rapidly as points shift from a regular grid to a low discrepancy sequence.

In Table G.1 and G.2, we illustrate that NF-Net initialized with a large pre-trained discrete network does not match the performance of the original model when fine-tuned with QMC sampling. We use a truncated version of EfficientNet (Tan and Le, 2019) for classification, and fine-tune for 200 samples per class. For segmentation we use a truncated version of ConvNexT-UPerNet (Liu et al., 2022), fine-tuning with 1000 samples.

We also find that the output of an NF-Net is less stable under changing sampling resolution with a grid pattern (Fig. G.1). While the output of a network with QMC sampling converges at high resolution, the grid sampling scheme has unstable outputs until very high resolution. Only the grids that overlap each other (resolutions in powers of two) produce similar activations.

Our preliminary experience with NF-Nets highlights the need for improved sampling schemes and parameterizations that will allow large continuous-domain neural networks to learn effectively. Stable, scalable methods are needed to realize NF-Nets' full potential for continuous data analysis.

---

9. The accumulation of floating-point errors results in a small but noticeable difference in the final result, even with double precision.

Figure G.1: Distance of the output of a NF-Net from its grid output at 32×32 resolution, when sampling at various resolutions.

Figure G.2: An NF-Net's output diverges as sample points are gradually shifted from a grid layout to a low discrepancy sequence.

G.2. Computational Complexity

The NF-Net's complexity is similar to that of a discrete model with an equivalent architecture. In general time and memory both scale linearly with the number of sample points (regardless of the dimensionality of Ω), as well as with network depth and width.

Implemented naively, the computational cost of the continuous convolution is quadratic in the number of sample points, as it must calculate weights separately for each neighboring pair of points. We can reduce this to a linear cost by specifying a N_{bin} Voronoi partition of the kernel support B, then using the value of the kernel at each seed point for all points in its cell. Thus the kernel need only be evaluated N_{bin} times regardless of the number of sample points. Additionally N_{bin} can be modified during training and inference.

NF-Net-4 performs a forward pass on a batch of 48 images in 96 ± 4ms on a single NVIDIA RTX 2080 Ti GPU.

Appendix H. Limitations

Error propagation When an NF does not faithfully represent the underlying data, it is important to characterize the influence on NF-Net's output. In the worst case, these deviations are adversarial examples, and robustness techniques for discrete networks can also be applied to NF-Net. But what can we say about typical deviations of NFs? Future work should analyze patterns in the mistakes that different types of NFs make, and how to make NF-Nets robust to these.

Inseparable outputs An NF output of an NF-Net cannot be detached from the network without sacrificing the ability to evaluate it anywhere on its domain. Thus it is unwieldy for applications where the output NFs need to be stored long-term or undergo repeated downstream processing. Future work should complement our framework with a method for

efficiently translating output NFs to a new parameterization, such as co-training NF-Net with a hypernetwork or modulation network.

Extending NF-Net to very high-discrepancy sequences   In many applications, there are large regions of the domain that are less informative for the task of interest. For example, most of the information in 3D scenes is concentrated at object surfaces, so NF-Nets should not need to process a NeRF by densely sampling all 5 dimensions. Moreover, ground truth labels for dense prediction tasks may only be available along a high discrepancy point set. Our discretization-invariant construction does not guarantee that the model is well-behaved under more extreme discretizations or highly non-uniform measures, and additional techniques are needed to extend our model to such cases.